

# Week 7 Code along/Challenge

Janelle Tan

2023-10-02

## II. Code to edit and execute using the Code-along-7.Rmd file

### A. All about ggplot2

#### 1. loading Palmer Penguins (Slide #6)

```
# Enter code here
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.3      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```


```
library(palmerpenguins)
glimpse(penguins)
```

```
## Rows: 344
## Columns: 8
## $ species      <fct> Adelie, Adelie, Adelie, Adelie, Adelie, Adelie, Adel~
## $ island       <fct> Torgersen, Torgersen, Torgersen, Torgersen, Torgerse~
## $ bill_length_mm <dbl> 39.1, 39.5, 40.3, NA, 36.7, 39.3, 38.9, 39.2, 34.1, ~
## $ bill_depth_mm <dbl> 18.7, 17.4, 18.0, NA, 19.3, 20.6, 17.8, 19.6, 18.1, ~
## $ flipper_length_mm <int> 181, 186, 195, NA, 193, 190, 181, 195, 193, 190, 186~
## $ body_mass_g   <int> 3750, 3800, 3250, NA, 3450, 3650, 3625, 4675, 3475, ~
## $ sex           <fct> male, female, female, NA, female, male, female, male~
## $ year          <int> 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007, 2007~
```

#### 2. Plot recreation (Slide #8 - 20)


```
# starting w the penguins data frame
```

```
ggplot(data = penguins)
```




```
# map bill depth to the x-axis
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm)) # <- name of var has to be the same of that in dataset
```




```
# Map bill length to the y-axis  
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm))
```



```
# Represent each observation with a point, note the + symbol
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm)) +  
  geom_point()
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



```
# Map species to the colour of each point; ie creating a legend
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point()
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



```
# Title the plot "Bill depth and length", note double quotes needed
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length")
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```




*# Add the subtitle "Dimensions for Adelie, Chinstrap, and Gentoo Penguins"; precise title, descriptive*

```
ggplot(data = penguins,
  mapping = aes(x = bill_depth_mm,
    y = bill_length_mm,
    colour = species)) +
  geom_point() +
  labs(title = "Bill depth and length",
    subtitle = "Dimensions for Adelie,
    Chinstrap, and Gentoo Penguins")
```

## Warning: Removed 2 rows containing missing values ('geom\_point()').

# Bill depth and length

## Dimensions for Adelie, Chinstrap, and Gentoo Penguins



*# Label the x and y axes as "Bill depth (mm)" and "Bill length (mm)"; changing default labels, note dou*


```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length",  
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",  
    x = "Bill depth (mm)",  
    y = "Bill length (mm)")
```

## Warning: Removed 2 rows containing missing values ('geom\_point()').



## Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins




*# labelling the legend "Species", note double quotes*

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length",  
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",  
    x = "Bill depth (mm)",  
    y = "Bill length (mm)",  
    colour = "Species")
```

## Warning: Removed 2 rows containing missing values ('geom\_point()').

## Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins




```
# Add a caption for the data source
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length",  
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",  
    x = "Bill depth (mm)",  
    y = "Bill length (mm)",  
    colour = "Species",  
    caption = "Source: Palmer Station LTER / palmerpenguins package")
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```

## Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins



Source: Palmer Station LTER / palmerpenguins package


```
# catering to the colour-blind
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  labs(title = "Bill depth and length",  
    subtitle = "Dimensions for Adelie, Chinstrap, and Gentoo Penguins",  
    x = "Bill depth (mm)",  
    y = "Bill length (mm)",  
    colour = "Species",  
    caption = "Source: Palmer Station LTER / palmerpenguins package") +  
  scale_colour_viridis_d()
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```

## Bill depth and length

Dimensions for Adelie, Chinstrap, and Gentoo Penguins




Source: Palmer Station LTER / palmerpenguins package

### 3. Alternative way of writing the same code (Slide #20)

```
# omitting data and mapping
```

```
ggplot(data = penguins,  
  mapping = aes(x = bill_depth_mm,  
    y = bill_length_mm,  
    colour = species)) +  
  geom_point() +  
  scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



```
# 2. aes layer outside ggplot function
```

```
ggplot(penguins) + # Data layer  
  aes(x = bill_depth_mm,  
      y = bill_length_mm,  
      colour = species) + # Aesthetics layer  
  geom_point() + # Geometric layer  
  scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



#### 4. Aesthetics options (Slide #21)

```
# Colour  
ggplot(penguins) + aes(x = bill_depth_mm, y = bill_length_mm,  
  colour = species) +  
  geom_point() + scale_colour_viridis_d()
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



*# Shape*

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species,  
  shape = island)) +  
  geom_point() + scale_colour_viridis_d()
```

## Warning: Removed 2 rows containing missing values ('geom\_point()').




```
# Size

ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species, shape = species,
  size = body_mass_g)) +
  geom_point() + scale_colour_viridis_d()
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```






```
# Alpha; transparency
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, colour = species,
  shape = species, size = body_mass_g, alpha = flipper_length_mm)) +
  geom_point() + scale_colour_viridis_d()
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```




## 5. Mapping vs Setting (Slide #27-28)

```
# Setting

ggplot(penguins) +
  aes(x = bill_depth_mm,
      y = bill_length_mm) +
  geom_point(size = 2, alpha = 0.5)
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```




## 6. Faceting (Slide #29-34)

```
# Displays different subsets of data.
# Useful for: exploring conditional relationships and large data

#species vs island
ggplot(penguins) +
  aes(x = bill_depth_mm,
      y = bill_length_mm) +
  geom_point() +
  facet_grid(species ~ island) # <- rows ~ columns
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



```
# species vs sex
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(species ~ sex)
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



```
# sex vs species -> order matters!
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(sex ~ species)
```


```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```



*# only have 1 var ww to sort the data points by instead of 2 like before*

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_wrap(~ species)
```


## Warning: Removed 2 rows containing missing values ('geom\_point()').



```
# arranging into 2 columns
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_wrap(~ species, ncol = 2)
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```




```
# (. ~ species)
```

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm)) + geom_point() +  
  facet_grid(. ~ species)
```

```
## Warning: Removed 2 rows containing missing values ('geom_point()').
```






## 7. Faceting & others (Slide #35)

*# facet & colour & no legend*

```
ggplot(penguins, aes(x = bill_depth_mm, y = bill_length_mm, color = species)) +
  geom_point() + facet_grid(species ~ sex) + scale_color_viridis_d() +
  guides(color = "none")
```

## Warning: Removed 2 rows containing missing values ('geom\_point()').



## B. Visualising numeric variables

### 8. Lending Club dataset (Slides #38-)

```
library(openintro)
```

```
## Loading required package: airports
```

```
## Loading required package: cherryblossom
```

```
## Loading required package: usdata
```

```
glimpse(loans_full_schema)
```

```
## Rows: 10,000
```

```
## Columns: 55
```

```
## $ emp_title
```

```
## $ emp_length
```

```
## $ state
```

```
## $ homeownership
```

```
## $ annual_income
```

```
## $ verified_income
```

```
<chr> "global config engineer ", "warehouse~
<dbl> 3, 10, 3, 1, 10, NA, 10, 10, 10, 3, 1~
<fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, I~
<fct> MORTGAGE, RENT, RENT, RENT, RENT, OWN~
<dbl> 90000, 40000, 40000, 30000, 35000, 34~
<fct> Verified, Not Verified, Source Verifi~
```

```

## $ debt_to_income <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.4~
## $ annual_income_joint <dbl> NA, NA, NA, NA, 57000, NA, 155000, NA~
## $ verification_income_joint <fct> , , , , Verified, , Not Verified, , ~
## $ debt_to_income_joint <dbl> NA, NA, NA, NA, 37.66, NA, 13.12, NA,~
## $ delinq_2y <int> 0, 0, 0, 0, 0, 1, 0, 1, 1, 0, 0, 0, 0~
## $ months_since_last_delinq <int> 38, NA, 28, NA, NA, 3, NA, 19, 18, NA~
## $ earliest_credit_line <dbl> 2001, 1996, 2006, 2007, 2008, 1990, 2~
## $ inquiries_last_12m <int> 6, 1, 4, 0, 7, 6, 1, 1, 3, 0, 4, 4, 8~
## $ total_credit_lines <int> 28, 30, 31, 4, 22, 32, 12, 30, 35, 9,~
## $ open_credit_lines <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,~
## $ total_credit_limit <int> 70795, 28800, 24193, 25400, 69839, 42~
## $ total_credit_utilized <int> 38767, 4321, 16000, 4997, 52722, 3898~
## $ num_collections_last_12m <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ num_historical_failed_to_pay <int> 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0~
## $ months_since_90d_late <int> 38, NA, 28, NA, NA, 60, NA, 71, 18, N~
## $ current_accounts_delinq <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ total_collection_amount_ever <int> 1250, 0, 432, 0, 0, 0, 0, 0, 0, 0, 0, 0,~
## $ current_installment_accounts <int> 2, 0, 1, 1, 1, 0, 2, 2, 6, 1, 2, 1, 2~
## $ accounts_opened_24m <int> 5, 11, 13, 1, 6, 2, 1, 4, 10, 5, 6, 7~
## $ months_since_last_credit_inquiry <int> 5, 8, 7, 15, 4, 5, 9, 7, 4, 17, 3, 4,~
## $ num_satisfactory_accounts <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,~
## $ num_accounts_120d_past_due <int> 0, 0, 0, 0, 0, 0, 0, NA, 0, 0, 0, 0, ~
## $ num_accounts_30d_past_due <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ num_active_debit_accounts <int> 2, 3, 3, 2, 10, 1, 3, 5, 11, 3, 2, 2,~
## $ total_debit_limit <int> 11100, 16500, 4300, 19400, 32700, 272~
## $ num_total_cc_accounts <int> 14, 24, 14, 3, 20, 27, 8, 16, 19, 7, ~
## $ num_open_cc_accounts <int> 8, 14, 8, 3, 15, 12, 7, 12, 14, 5, 8,~
## $ num_cc_carrying_balance <int> 6, 4, 6, 2, 13, 5, 6, 10, 14, 3, 5, 3~
## $ num_mort_accounts <int> 1, 0, 0, 0, 0, 3, 2, 7, 2, 0, 2, 3, 3~
## $ account_never_delinq_percent <dbl> 92.9, 100.0, 93.5, 100.0, 100.0, 78.1~
## $ tax_liens <int> 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ public_record_bankrupt <int> 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0~
## $ loan_purpose <fct> moving, debt_consolidation, other, de~
## $ application_type <fct> individual, individual, individual, i~
## $ loan_amount <int> 28000, 5000, 2000, 21600, 23000, 5000~
## $ term <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 3~
## $ interest_rate <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.7~
## $ installment <dbl> 652.53, 167.54, 71.40, 664.19, 786.87~
## $ grade <fct> C, C, D, A, C, A, C, B, C, A, C, B, C~
## $ sub_grade <fct> C3, C1, D1, A3, C3, A3, C2, B5, C2, A~
## $ issue_month <fct> Mar-2018, Feb-2018, Feb-2018, Jan-201~
## $ loan_status <fct> Current, Current, Current, Current, C~
## $ initial_listing_status <fct> whole, whole, fractional, whole, whol~
## $ disbursement_method <fct> Cash, Cash, Cash, Cash, Cash, Cash, C~
## $ balance <dbl> 27015.86, 4651.37, 1824.63, 18853.26,~
## $ paid_total <dbl> 1999.330, 499.120, 281.800, 3312.890,~
## $ paid_principal <dbl> 984.14, 348.63, 175.37, 2746.74, 1569~
## $ paid_interest <dbl> 1015.19, 150.49, 106.43, 566.15, 754.~
## $ paid_late_fees <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~

```

```
# selecting variables
```

```
loans <- loans_full_schema %>%
  select(loan_amount, interest_rate, term, grade,
```


```
state, annual_income, homeownership, debt_to_income)
glimpse(loans)
```

```
## Rows: 10,000
## Columns: 8
## $ loan_amount    <int> 28000, 5000, 2000, 21600, 23000, 5000, 24000, 20000, 20~
## $ interest_rate  <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.72, 13.59, 11.99, 1~
## $ term           <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 36, 60, 60, 36, 60,~
## $ grade          <fct> C, C, D, A, C, A, C, B, C, A, C, B, C, B, D, D, D, F, E~
## $ state          <fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, IL, IL, FL, SC, CO,~
## $ annual_income  <dbl> 90000, 40000, 40000, 30000, 35000, 34000, 35000, 110000~
## $ homeownership  <fct> MORTGAGE, RENT, RENT, RENT, RENT, RENT, OWN, MORTGAGE, MORTGA~
## $ debt_to_income <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.46, 23.66, 16.19, 3~
```

## 9. Plotting Histograms


```
ggplot(loans) + aes(x = loan_amount) +
  geom_histogram()
```

```
## 'stat_bin()' using 'bins = 30'. Pick better value with 'binwidth'.
```




## 10. Changing histogram binwidths


```
# binwidth = 1000  
ggplot(loans, aes(x = loan_amount)) +  
  geom_histogram(binwidth = 1000)
```



```
# binwidth = 5000  
ggplot(loans, aes(x = loan_amount)) +  
  geom_histogram(binwidth = 5000)
```




```
# binwidth = 20000  
ggplot(loans, aes(x = loan_amount)) +  
  geom_histogram(binwidth = 20000)
```



## 11. Customising histogram


```
# adding labels  
ggplot(loans, aes(x = loan_amount)) + geom_histogram(binwidth = 5000) +  
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans" )
```



## 12. Filling with a categorical variable


```
ggplot(loans, aes(x = loan_amount, fill = homeownership)) +  
  geom_histogram(binwidth = 5000, alpha = 0.5) +  
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans")
```






### 13. Facet with a categorical variable

```
ggplot(loans, aes(x = loan_amount, fill = homeownership)) + geom_histogram(binwidth = 5000) +  
  labs(x = "Loan amount ($)", y = "Frequency", title = "Amounts of Lending Club loans") +  
  facet_wrap(~ homeownership, nrow = 3)
```




#### 14. Density Plot

```
ggplot(loans, aes(x = loan_amount)) +  
  geom_density()
```




#### 14. Adjusting Density Plot bandwidths


```
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 0.5)
```



```
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 1) # <- default bandwidth
```




```
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 2)
```




## 15. Customising Density Plot

```
# adding labels  
ggplot(loans, aes(x = loan_amount)) +  
  geom_density(adjust = 2) +  
  labs( x = "Loan amount ($)", y = "Density", title = "Amounts of Lending Club loans" )
```




## 16. Box Plots & outliers

```
ggplot(loans, aes(x = interest_rate)) +  
  geom_boxplot()
```



```
ggplot(loans, aes(x = annual_income)) +  
  geom_boxplot()
```






## 17. Customising Box Plots

```
# adding labels + removing the ticks along axes (look at diff from prev graph)


ggplot(loans, aes(x = interest_rate)) + geom_boxplot() + labs(x = "Interest rate (%)", y = NULL,
  title = "Interest rates of Lending Club loans") +
  theme( axis.ticks.y = element_blank(), axis.text.y = element_blank() )
```

## Interest rates of Lending Club loans



### 18. Adding a categoric variable


```
# sorting "interest rates" by "grade of application"  
  
ggplot(loans, aes(x = interest_rate,  
  y = grade)) +  
  geom_boxplot() +  
  labs(x = "Interest rate (%)", y = "Grade", title = "Interest rates of Lending Club loans",  
    subtitle = "by grade of loan")
```



## 19. Scatterplots

```
ggplot(loans, aes(x = debt_to_income, y = interest_rate)) +  
  geom_point()
```


```
## Warning: Removed 24 rows containing missing values ('geom_point()').
```




## 20. Hex plots

```
ggplot(loans, aes(x = debt_to_income, y = interest_rate)) +  
  geom_hex()
```

```
## Warning: Removed 24 rows containing non-finite values ('stat_binhex()').
```




```
# filtering debt to income to < 100  
  
ggplot(loans %>% filter(debt_to_income < 100),  
  aes(x = debt_to_income, y = interest_rate)) +  
  geom_hex()
```



## C. Visualising categoric variables


### 21. Bar plot (slide #67)

```
ggplot(loans, aes(x = homeownership)) +  
  geom_bar()
```




## 22. Segmented Bar plot (slide #68-69)

```
ggplot(loans, aes(x = homeownership, fill = grade)) +  
  geom_bar()
```



```
ggplot(loans, aes(x = homeownership, fill = grade)) +  
  geom_bar(position = "fill")
```





### 23. Customising Bar plots (slide #71)


```
ggplot(loans, aes(y = homeownership, fill = grade)) + geom_bar(position = "fill") +
labs( x = "Proportion",
      y = "Homeownership",
      fill = "Grade",
      title = "Grades of Lending Club loans",
      subtitle = "and homeownership of lendeer")
```



## D. Visualising variables of varied types

### 24. Violin plots (slide #73)

```
# helps visualise rs btw var of diff types (eg numeric & categorical)  
ggplot(loans, aes(x = homeownership, y = loan_amount)) +  
  geom_violin()
```



## 25. Ridge plots (slide #74)

*# instead of superimposing them, now placing them above on another*

```
library(ggribes)
ggplot(loans, aes(x = loan_amount, y = grade, fill = grade, color = grade)) +
  geom_density_ridges(alpha = 0.5)
```

## Picking joint bandwidth of 2360

