An AI Research Assistant for Reading Papers

Rebuilding `AI-Research-Assistant-New` around real arXiv papers, a real language model, and output a professor can check

Kunal Jangid
Roll no. B23MT1026

CSD4020: AI Specialisation Project

November 2026

Abstract

The original repository presented itself as an AI research assistant but analysed a folder of hand-written JSON records, used placeholder language models and embeddings whenever no OpenAI key was set, and reported metrics that did not measure what their names said. This report describes the replacement: a Streamlit application that searches arXiv through its API, reads each paper's full text from arXiv's HTML rendering with BeautifulSoup, indexes it with a local embedding model, and uses an LLM on Groq's free tier to write digests, answer questions with cited passages and compare papers. It is designed around a professor's reading workflow: deciding what to read, understanding it quickly, checking what the model claims, and reusing the result in teaching and writing. On a library of 12 papers (78,625 words of extracted text), 33 of the 37 supporting quotes in the generated digests (89%) were found word for word in the source paper. Questions are answered by a hybrid pipeline — BM25 and dense search in FAISS, fused by reciprocal rank and re-ranked by a cross-encoder — behind input, context and output guardrails. An ablation study over six chunking strategies, nine embedding models, four re-rankers and five vector stores chose its settings; on 77 questions with known evidence it raises retrieval MRR from 0.52 to 0.66 and brings the evidence to the model for 87% of questions instead of 71%. Ragas scores the answers before and after.

Contents

1 Starting point **1**

2 What a professor needs from such a tool **2**

3 Architecture **2**

4 Getting real papers **3**
4.1 Search and metadata: the arXiv API 3
4.2 Full text: BeautifulSoup on arXiv's HTML 3

5 Retrieval **4**

6 Using a language model on a free tier **4**
6.1 Model and limits 4
6.2 Two depths of digest 5
6.3 Structured output that can be checked 5
6.4 Quote verification 5
6.5 Answers with sources 5

7 Guardrails **6**

8 The interface **6**

9 Visualisations and their accuracy **6**

10 Measurements **7**

11 Evaluation of retrieval, guardrails and answers **15**
11.1 Ablation study 16
11.2 Vector stores 18
11.3 Guardrails 18
11.4 Answer quality with Ragas 19

12 Testing **20**

13 Limitations **20**

14 Running it **20**

1 Starting point

The repository contained four entry scripts (`fixed_assistant.py`, `interactive_assistant.py`, `docker_assistant.py`, `docker_interactive.py`), a plotting module, a Docker set-up and a `research-db/` folder of paper records. Running it and reading the code showed five problems.

The AI was a placeholder. Without a key beginning `sk-`, the code fell back to LangChain's `FakeListLLM`, which returns canned strings in rotation, and `FakeEmbeddings`, which returns random vectors. The "insights" a user saw were therefore not derived from the papers.

The papers were not real. Papers were loaded only from JSON files in `research-db/`, written by hand with fields such as `keywords` and `citations`. There was no search and no way to add a real paper.

The metrics did not measure their names. "Collaboration index" was papers divided by authors, capped at 1; "trend velocity" was the number of papers divided by ten; "diversity" was the ratio of distinct keywords to keywords; "impact" averaged the hand-entered citation field.

Docker could not run. The Dockerfile was built on a Terminal-Bench base image, and the compose file ran a `solution.sh` that is not in the repository, with log paths taken from benchmark environment variables.

A credential was committed. `docker-compose.yaml` contained a literal `LANGCHAIN_API_KEY` value. It should be treated as leaked and revoked by its owner; deleting the file does not remove it from the Git history.

All of these files were removed. What replaced them is described below.

2 What a professor needs from such a tool

New papers appear faster than anyone can read them. A professor typically has to:

1. **triage**: notice the few new papers that matter to their research, out of hundreds a week;
2. **understand** a chosen paper quickly, sometimes from outside their own speciality;
3. **check** anything a summary claims before repeating it to students or in a review;
4. **reuse** what they read: in a lecture, a reading group, a referee report or a related-work section.

A language model helps with all four, but only if its output can be traced to the paper. That principle shaped the design: every generated statement is either tied to quoted text that the application checks, or to numbered passages that are shown next to the answer. Figures on the Insights page are computed, never generated.

Need	Feature	Where
Triage	Search ranked by similarity to a written statement of research interests; a watchlist of followed searches; a briefing that rates each new paper high/medium/low for this reader with a reason	Discover
Understand	Digest at two depths, written for a specialist, a neighbouring field or a graduate student; background needed; questions answered from the paper	Reader
Check	Each key result carries a quote that is matched against the paper text; answers cite numbered passages shown beside them; full extracted text is browsable	Reader
Reuse	Discussion questions for a reading group; side-by-side comparison; related-work paragraph with numbered references; BibTeX and Markdown export; personal notes, tags and reading status	Reader, Synthesize, Library
Overview	Timeline, categories, characteristic terms, topic map, co-author network, citation counts	Insights

Table 1: The reading workflow and the feature that serves each step.

3 Architecture




Figure 1: Modules of the `research_assistant` package and the services they call. Dashed boxes are external. Embeddings are computed locally; only the LLM call leaves the machine with paper text.

The code is a small Python package used by five Streamlit pages (Figure 1). Each module has one job, and nothing in the package imports Streamlit except `ui.py`, so every module is tested without a running app. A saved paper is one JSON file (metadata, extracted sections, digests, notes, status) and one compressed NumPy file (its passages, their vectors and the settings they were built with). The library-wide FAISS and BM25 indexes are assembled from those files in memory and rebuilt when one changes. There is no database server: a reading library holds hundreds of papers, not millions, and Section 11.2 measures what a vector database would and would not add.

4 Getting real papers

4.1 Search and metadata: the arXiv API

`arxiv_client.py` builds queries for the Atom API at `export.arxiv.org/api/query`. Quoted phrases are kept as phrases, other words are joined with `AND`, a search can be limited to title, abstract, author or all fields, and to one of sixteen arXiv categories, and results can be sorted by relevance, submission date or last update. The feed is parsed with the standard library's XML parser into a `Paper` record: identifier and version, title, authors, abstract, dates, primary and secondary categories, comment, journal reference and DOI. arXiv reports query errors as a feed entry rather than an HTTP status; those are raised as errors instead of being shown as a paper. Calls are spaced at least three seconds apart, as arXiv's terms of use ask, and every request carries a descriptive User-Agent.

4.2 Full text: BeautifulSoup on arXiv's HTML

Abstracts are not enough to digest a paper. arXiv renders most recent submissions to HTML with LaTeXML at `arxiv.org/html/<id>`, and the ar5iv project covers many older ones. `fulltext.py` fetches the first of the two that exists and walks the document with BeautifulSoup, relying on LaTeXML's `ltx_*` classes:

- sections (`ltx_section`, appendices) become `Section(title, text)`; subsection headings are kept inline as `##` lines so retrieved passages still say where they came from;
- mathematics is replaced by its LaTeX source from the `alttext` attribute, written as `$...$`, so formulas survive as text the model can read;
- footnotes, author blocks and navigation are removed; data tables are removed (their cells are unreadable once flattened) but their captions are kept in brackets, as are figure captions; equation tables are kept;
- the bibliography is counted, not included.

A page with fewer than 1,500 characters of body text is rejected, so a stub or an error page is never taken for a paper. When neither source has the paper it is saved with its abstract only, marked as such in the interface, and offered a retry.

5 Retrieval




Figure 2: The question-answering pipeline. Blue stages retrieve and answer; orange stages are the guardrails of Section 7. Every setting was chosen by the ablation study in Section 11.1.

The first version embedded each question and returned the passages with the highest cosine similarity. Dense retrieval is good at paraphrase but weak on the exact terms that dominate research questions — dataset names, metric names, model names, numbers — so the pipeline is now hybrid (Figure 2):

1. **Chunking.** Each paper is split into passages of at most 512 characters on sentence boundaries with 64 characters of overlap, each prefixed by its section title; the abstract is the first passage. The 12 papers of Section 10 give 1591 passages.

2. **Dense search.** Passages are embedded with `BAAI/bge-small-en-v1.5` through `fastembed`, an ONNX runtime that needs no GPU and no PyTorch, with the model's instruction prefix on the query side only. Vectors are L2-normalised and held in a FAISS `IndexFlatIP`, so the inner product is the cosine similarity and the search is exact; a restriction to one paper is an `IDSelectorBatch`.

3. **Sparse search.** Okapi BM25 ($k_1 = 1.5$, $b = 0.75$) over the same passages, implemented on scikit-learn's `CountVectorizer` with the term weights precomputed in a sparse matrix, so scoring a query is one column sum (about 0.2 ms).

4. **Fusion.** Reciprocal Rank Fusion, $\sum_r 1/(60 + \text{rank}_r)$, combines the two rankings without having to calibrate their scores against each other; the best 30 are kept.

5. **Re-ranking.** A cross-encoder (`ms-marco-MiniLM-L-6-v2`) reads each question–passage pair together and re-orders the 30 candidates. The best 12 (about 5,300 characters) go to the model, or 16 when the question is about the whole library.

Changing the chunking or the embedding model in `config.py` re-indexes the saved papers on the next search: each index file records the settings it was built with.

The same model ranks search results against the reader's interests: the professor writes a few sentences about their research once, and each abstract is scored by its cosine similarity to that statement. The score orders results; the interface says explicitly that it is not a percentage.

6 Using a language model on a free tier

6.1 Model and limits

The LLM is `openai/gpt-oss-120b` on Groq, called through its OpenAI-compatible endpoint with the `openai` SDK and low reasoning effort. The key is read from `GROQ_API_KEY` or `GROQ_CLOUD_API_KEY` in `.env`, or from Streamlit secrets when deployed. Groq's free tier allows 8,000 tokens per minute, counting prompt and completion together, which shapes everything else:

- a single request carries at most about 15,000 characters of paper text and asks for at most 1,800 output tokens;
- when the limit is hit, the client reads the wait Groq asks for (the `retry-after` header, or the "try again in ..." message), waits, tells the user it is waiting, and tries again; a request that is too large for the tier is reported as such rather than retried;
- streaming is used for answers, so text appears as it is written.

6.2 Two depths of digest

A whole paper does not fit in one request, so the reader chooses:

Focused (one call): the abstract, the introduction, up to two closing sections (conclusion, discussion, limitations) and the passages retrieved for three questions — the method, the main results with numbers, and limitations — until the character budget is used.

Full paper (one call per block of about 12,000 characters, then one more): the model first takes reading notes on each block, keeping every quantitative result and copying key sentences verbatim; the digest is then written from all the notes. A 12,000-word paper needs five or six calls and, on the free tier, a few minutes.

Each digest records which text it was written from, and the interface shows it.

6.3 Structured output that can be checked

Digests, comparisons and briefings are requested as JSON objects with named fields. Model output is not always well formed, so:

- the parser accepts code fences and surrounding prose and extracts the object;
- an answer wrapped in an extra object is unwrapped; an answer missing a required field is requested once more and otherwise reported as an error — an empty box is never shown as if the model had found nothing (this fixed an intermittent empty "Where they agree" panel on the Synthesize page);
- digest fields are coerced to their types (a string where a list was asked for becomes a one-item list, a null becomes empty), so exports cannot fail on an unexpected shape.

6.4 Quote verification

Each key result in a digest has two parts: a one-sentence claim and a quote of at most 30 words that the model is told to copy exactly. The application then searches the paper's text for the quote after lower-casing, collapsing whitespace and punctuation, and dropping full stops other than decimal points. A quote with an ellipsis passes when every fragment of 15 or more characters is found. The result is shown on each card as "Quote found in the paper" or "Not found word for word" (Figure 5).

This check has a precise and limited meaning. A match shows that the quoted words are in the paper, not that the claim follows from them; the reader still has to compare the two, which is why they are displayed together. A miss usually means paraphrase rather than invention (Section 10).

6.5 Answers with sources

In the Ask view, the question passes the input checks, the pipeline of Section 5 finds twelve passages of the paper (or sixteen across the whole library), and they are numbered and sent inside `<passage n="i">` tags with the instruction to cite them as [1], [2], to treat their content as data rather than instructions, and to say so when they do not contain the answer. The passages are shown beneath the answer with their section names, so every citation can be followed (Figure 6). The last four turns of the conversation are included so follow-up questions work.

7 Guardrails

A reading assistant takes text from two untrusted places: the question, and the papers themselves, which may quote prompt-injection attacks or contain hidden instructions. `guardrails.py` checks at three points, and the interface shows every check as a step under the answer (Figure 6).

Input. The question is stripped of control and invisible formatting characters (a way to hide instructions) and limited to 1,000 characters. Two Groq-hosted classifiers then run in parallel: Llama Prompt Guard 2 (86M) returns the probability of a prompt attack, blocking at 0.5, with a regular expression as the fallback when it cannot be reached; and `gpt-oss-safeguard-20b` classifies the question against a short written policy (weapons capable of mass harm, malware, sexual content involving minors, self-harm, hate), which explicitly allows academic discussion of those topics. The safety check fails open, since an outage should not stop a professor reading a paper.

Context. If the best re-ranker score is below -5, no passage is relevant enough and the application says the papers do not contain the answer *without calling the model*; the threshold was calibrated on answerable and unanswerable questions (Section 11.3). Retrieved passages with instruction-like text are flagged but kept — papers about prompt injection quote attacks — and the prompt frames all paper text as data.

Output. Citations must refer to passages that exist; every factual sentence should carry one; every number of two or more digits in the answer must occur in the passages; and an answer that echoes the system prompt or an API key is withheld. Only the last blocks; the others are shown as warnings, because a professor is better served by a visible flag than by a missing answer.

8 The interface

The application uses Streamlit 1.67 with top navigation between five pages, a light and a dark theme defined in `.streamlit/config.toml` (Inter for the interface, Source Serif 4 for headings, JetBrains Mono for code), and Material icons. Streamlit's bundled *developing-with-streamlit* skill was followed for layout and widget choice: segmented controls for exclusive views, pills for status filters, dialogs for destructive actions, compact status indicators for long operations, `st.write_stream` for answers, and the selected paper bound to the URL so a reader view can be bookmarked or shared.




Figure 3: Discover. Results from the arXiv API, ordered by cosine similarity to the professor's interests statement. Papers already saved are marked and open in the reader.

9 Visualisations and their accuracy

The Insights page (Figures 8–10) answers "what is in my library?". Each chart was chosen for what it has to show, and each states in a caption what it measures and what it does not.

Papers over time. A bar chart of counts by month or, beyond three years, by year of first submission. Empty periods are filled with zeros so gaps are visible rather than closed up.

Categories. Horizontal bars of primary arXiv category, sorted. Each paper is counted once, so the bars sum to the number of papers.




Figure 4: Library. Saved papers with reading status, tags, whether full text was extracted, and citation counts; several rows can be selected to change status, export BibTeX or remove.




Figure 5: Reader, Digest view. Depth and audience are chosen above the digest. Each key result shows the model's claim, the quote it gave, and whether that quote was found in the paper.




Figure 6: Reader, Ask view. The status line expands into the checks made before the model was called (question screened; twelve passages found by hybrid search and re-ranking, the best scoring 0.52, none with planted instructions). The answer cites passage [2]; the guardrail panel below it flags that its first sentence carries no citation. The passages are listed underneath.




Figure 7: Synthesize, comparing five saved papers: a side-by-side table, agreements, differences and open questions, and a related-work paragraph with its numbered references. Both the paragraph and the BibTeX can be downloaded.

Characteristic terms. Terms and two-word phrases ranked by mean TF-IDF weight over titles and abstracts, with English and academic stop words ("paper", "propose", "state-of-the-art", ...) removed, terms in more than 85% of papers dropped, and a term hidden when a higher-ranked phrase already contains it. Bar length is *document frequency* — the number of papers containing the term — which can be read directly, rather than a TF-IDF weight, which cannot.

Topic map. Abstract embeddings are clustered with k-means, k from 2 to 4 chosen by silhouette score, and drawn in two dimensions with PCA. Groups are labelled with their most characteristic terms and distinguished by shape as well as colour. The caption gives the silhouette score and the share of variance the projection keeps (46% for the library shown) and says that the axes have no units. With fewer than six papers the map is not drawn.

Co-author network. An interactive force-directed graph: a line joins authors of the same saved paper, thicker for more joint papers, larger dots for authors of more papers. Above it are counts that can be checked by hand: 65 authors, 212 co-author pairs, density 0.102, 11 separate groups (the largest has 17 authors), and 3 authors who appear in more than one paper.

Citations. Counts from Semantic Scholar, refreshed on demand. Citation counts are heavily skewed — from 217 to 202,845 here — so when the largest is more than 50 times the smallest the chart switches to dots on a logarithmic axis with ticks at powers of ten and exact values as labels; otherwise it uses bars. The caption notes that older papers have had longer to be cited and that this is not a quality ranking.

Colour. Categorical colours follow a fixed order and stay attached to their category; the palette was checked with a colour-vision-deficiency validator in both light and dark mode and passed (lightness band, chroma, adjacent-pair separation under simulated deuteranopia, protanopia and tritanopia, and contrast against the surface). The dark theme uses its own colours checked against the dark surface, not an inversion. Text in charts uses the theme's ink, never the series colour; a check of the dark theme found the citation labels drawn in Vega's default black, and they now take the theme's text colour.

10 Measurements

`report/measure.py` produced the numbers in this section from the library used for the screenshots: 12 papers on retrieval-augmented generation and its foundations, from 2017 to 2026, each saved through the application. It writes `measurements.json` and the `measurements.tex` file that this report reads, so the figures here are the script's output, not copied by hand.

arXiv	Title	Year	Sections	Words	Passages	Refs	Citations	Quotes found	Digest (s)
1706.03762	Attention Is All You Need	2017	8	4,113	71	40	202,845	3/3	2.7
2004.04906	Dense Passage Retrieval for Open-Domain ...	2020	13	6,293	115	48	7,897	3/4	8.9
2005.11401	Retrieval-Augmented Generation for ...	2020	17	6,409	114	68	21,066	3/4	30.6
2007.01282	Leveraging Passage Retrieval with ...	2020	5	2,331	39	34	2,257	3/3	24.8
2212.10496	Precise Zero-Shot Dense Retrieval without ...	2022	7	3,359	59	39	1,080	4/4	35.9
2309.15217	Ragas: Automated Evaluation of Retrieval ...	2023	7	3,114	52	28	1,373	3/3	–
2310.11511	Self-RAG: Learning to Retrieve, Generate, ...	2023	11	12,443	400	58	3,121	3/3	31.0
2312.10997	Retrieval-Augmented Generation for Large ...	2023	8	9,454	179	182	4,508	3/3	28.9
2401.15884	Corrective Retrieval Augmented Generation	2024	8	6,124	111	41	360	2/2	28.7
2404.10981	A Survey on Retrieval-Augmented Text ...	2024	10	11,542	218	166	217	1/3	30.0
2405.07437	Evaluation of Retrieval-Augmented ...	2024	6	5,880	108	77	358	2/2	28.1
2611.17161	Cited but Unused: Parametric Provenance in ...	2026	20	7,563	125	53	–	3/3	27.6
Total			120	78,625	1591			33/37	

Table 2: Per-paper results. *Words* and *Sections* are of the text extracted from arXiv HTML; *Refs* counts bibliography entries; *Citations* are from Semantic Scholar (– = not indexed yet); *Quotes found* is how many supporting quotes in the focused, specialist digest were found in the paper; *Digest* is wall-clock time including any rate-limit wait (– = generated before timing was added).




Figure 8: Insights, upper half: counts by year and category, characteristic terms by document frequency, and the topic map with its silhouette score and retained variance stated.




Figure 9: Insights, lower half: the co-author network with its summary counts, and citation counts on a logarithmic axis.




Figure 10: The same charts in the dark theme, with colours chosen and checked for the dark surface.

Extraction. Full text was extracted for all 12 papers: 120 sections and 78,625 words, from 2,331 words for a short paper to 12,443 for Self-RAG with its appendices. The 2026 paper was published days before the measurement, so it had no citation record yet.

Quote verification. 33 of 37 quotes (89%) were found in the paper. Each of the four misses was traced to its source. In every case the sentence exists in the paper and the claim matches it, but the model altered a word while copying: "by showing that" became "show that" (arXiv:2404.10981), an abbreviation "(CoT)" was dropped inside an ellipsis quote (same paper), and in 2005.11401 and 2004.04906 the words joining the quote to its sentence were rewritten. The check is strict on purpose: it cannot tell a harmless slip from a fabricated quote, so it flags both and leaves the judgement to the reader, who sees the quote next to the claim.

Time. 11 digests were timed, taking 2.7 to 35.9 seconds (median 28.7, mean 25.2). These times are dominated by the free tier rather than the model: the generation run hit the token limit 12 times and waited 250 seconds in total. The first digest, made with a fresh token budget, took 2.7 seconds, which is what a focused digest costs when the per-minute budget is not exhausted — for example when a reader opens papers one at a time.

11 Evaluation of retrieval, guardrails and answers

The scripts in `eval/` measure every choice in Sections 5 and 7; their raw output is in `eval/results/*.json` and `eval/README.md` explains how to rerun them.

Questions. `eval/build_questions.py` wrote 89 questions about the saved papers with gpt-oss-120b: 36 from the digests' key results ("Does the Transformer achieve a higher BLEU score on English–German translation than any previously reported model?"), 41 from randomly chosen passages, and 12 written by hand that the library cannot answer ("Which team won the 2018 FIFA World Cup?", but also near misses in the papers' own register, such as the GPU price the authors paid per hour). Each answerable question keeps the sentence it was written from as evidence; a retrieved passage counts as *relevant* when it contains at least half of that sentence's word 5-grams, so relevance is decided without a model and the same labels apply to every chunking.

Metrics. Over the 77 answerable questions, searching the whole library: hit@1 and hit@5, MRR@10 (the mean reciprocal rank of the first relevant passage) with a 95% bootstrap interval, and *hit@budget*: whether a relevant passage is among the top results that fit in 6,600 characters, the amount of text the application sends the model. Hit@budget is the fair comparison between chunk sizes, since small chunks need more slots to carry the same text. Latency is the median per query on a 16-core CPU.

11.1 Ablation study

Each stage fixes the winner of the stage before (`eval/ablation.py`).

Chunking. Six strategies, each with all four retrieval methods (Table 3, Figure 11). Fusion helps every strategy and the re-ranker helps every strategy more: for 1,100-character sentence chunks, MRR rises from 0.523 (dense) to 0.563 (hybrid) and 0.683 (re-ranked). Among re-ranked pipelines the MRR intervals all overlap, so the choice rests on the budget and on speed: 512-character chunks put a relevant passage within the budget for 87% of questions against 79% for 1,100, and re-rank 45% faster because the cross-encoder reads shorter text. Very long chunks (2,048) are worst on both counts; semantic chunking, which splits where consecutive sentences' embeddings diverge, is good but no better than plain sentence packing and costs an embedding per sentence.

			MRR@10				Hybrid + re-rank	
Strategy	Passages	Mean chars	Dense	BM25	Hybrid	+ re-rank	hit@budget	ms/query
Fixed 1,100	731	1016	0.545	0.565	0.607	0.667	0.753	1044
Sentence 512	1,661	439	0.516	0.485	0.584	**0.659**	**0.870**	**570**
Sentence 1,100	750	967	0.523	0.543	0.563	0.683	0.792	1025
Sentence 2,048	422	1679	0.444	0.541	0.525	0.630	0.688	1569
Paragraph	811	807	0.579	0.571	0.642	0.668	0.844	982
Semantic	709	922	0.551	0.576	0.604	0.663	0.831	1254

Table 3: Chunking strategies (embedding model bge-small, re-ranker MiniLM-L-6, 30 candidates). The chosen strategy is in bold.




Figure 11: Chunking ablation: fusion and re-ranking raise MRR for every strategy; 512-character sentence chunks fit the most evidence in the model's budget.

Embedding models. Nine models that `fastembed` runs on a CPU, from a 32M-parameter static model to the 335M-parameter mxbai-large, on the 512-character chunks (Table 4). On its own the embedding model matters a great deal: dense MRR ranges from 0.374 (all-MiniLM-L6) to 0.575 (arctic-embed-m). Inside the full pipeline it hardly matters: BM25 recovers what a weak model misses and the re-ranker re-orders the union, so every model lands between 0.645 and 0.675, inside one another's intervals. The largest model is best, but it takes six times as long to index the library and ten times as long per query, and its index is almost three times the size. bge-small was kept: the best hybrid score of the small models at the lowest cost after the static model.

		Index	Query	Dense only		Hybrid + re-rank	
Model	Dim	time (s)	ms	MRR@10	hit@budget	MRR@10	hit@budget
bge-small-en-v1.5	384	58	5.3	0.516	0.792	0.659	0.870
bge-base-en-v1.5	768	186	14.3	0.526	0.792	0.658	0.857
all-MiniLM-L6-v2	384	34	5.1	0.374	0.662	0.645	0.857
snowflake-arctic-embed-s	384	66	8.6	0.544	0.753	0.650	0.844
snowflake-arctic-embed-m	768	195	16.8	0.575	0.818	0.669	0.870
nomic-embed-text-v1.5	768	271	19.8	0.565	0.779	0.665	0.883
mxbai-embed-large-v1	1024	371	51.7	0.506	0.844	0.675	0.896
granite-embedding-small-english-r2	384	66	6.3	0.473	0.779	0.658	0.857
potion-retrieval-32M	512	21	0.2	0.457	0.740	0.655	0.844

Table 4: Embedding models (sentence-512 chunks). *Index time* embeds all 1,661 passages; *Query ms* is dense search including embedding the question.

Re-rankers. Four cross-encoders, each re-scoring the best 20, 30 or 50 fused candidates (Table 5, Figure 12). bge-reranker-base is the most accurate (MRR 0.708 at 30 candidates) but takes 2.5

seconds a query on a CPU; MiniLM-L-6 reaches 0.659 in 0.53 seconds, and the larger MiniLM-L-12 and jina-turbo are no better. More candidates help slowly and cost linearly. MiniLM-L-6 with 30 candidates is the default; `RA_RERANK_MODEL` switches to bge-reranker-base for a reader who prefers accuracy to speed.

Re-ranker	Candidates	hit@1	MRR@10	hit@budget	ms/query
none (hybrid only)	–	0.481	0.584	0.831	6
ms-marco-MiniLM-L-6-v2	20	0.558	0.649	0.844	349
ms-marco-MiniLM-L-6-v2	**30**	**0.558**	**0.659**	**0.870**	**528**
ms-marco-MiniLM-L-6-v2	50	0.558	0.663	0.857	902
ms-marco-MiniLM-L-12-v2	20	0.519	0.634	0.857	671
ms-marco-MiniLM-L-12-v2	30	0.519	0.644	0.883	975
ms-marco-MiniLM-L-12-v2	50	0.519	0.646	0.870	1409
jina-reranker-v1-turbo-en	20	0.494	0.603	0.844	454
jina-reranker-v1-turbo-en	30	0.494	0.607	0.831	678
jina-reranker-v1-turbo-en	50	0.494	0.607	0.831	1025
bge-reranker-base	20	0.610	0.701	0.857	1695
bge-reranker-base	30	0.610	0.708	0.883	2518
bge-reranker-base	50	0.623	0.722	0.909	4121

Table 5: Re-rankers (sentence-512, bge-small). The first row is hybrid fusion without re-ranking.




Figure 12: Accuracy against cost for each re-ranker and candidate count.

Before and after. Table 6 compares the application before this work (dense search over 1,100-character chunks) with the chosen pipeline, both when the question is about one paper and when it is about the whole library. Across the library the first relevant passage is now ranked first for 56% of questions instead of 42%, MRR rises by 26% and the evidence reaches the model for 87% of questions instead of 71%; for one paper, 95% instead of 81%. The cost is about half a second per question, against several seconds for the model to write the answer.

Pipeline	Scope	hit@1	hit@5	MRR@10 [95% CI]	hit@budget	ms/query
Before (dense, sentence 1,100)	paper	0.481	0.805	0.614 [0.52, 0.70]	0.805	5
Before (dense, sentence 1,100)	library	0.416	0.675	0.523 [0.42, 0.62]	0.714	5
After (hybrid + re-rank, sentence 512)	paper	0.571	0.857	0.694 [0.61, 0.78]	0.948	539
After (hybrid + re-rank, sentence 512)	library	0.558	0.779	0.659 [0.57, 0.75]	0.870	539

Table 6: The retrieval pipeline before and after, on 77 answerable questions.

11.2 Vector stores

The application keeps its index in FAISS. `eval/vector_stores.py` compares it with the NumPy matrix product it replaced, with ChromaDB and with Qdrant, all embedded in the process and persisted to disk, on the library's real vectors and on 100,000 synthetic ones (real vectors with small noise, so neighbourhoods stay realistic). Recall@10 is measured against exact search (Table 7). Pinecone was not run: it is a hosted service that needs an account and key, and every query would add a network round trip of tens of milliseconds to a search that takes a fraction of one locally.

Vectors	Store	Build (s)	Disk (MB)	Query p50 (ms)	One paper p50 (ms)	Recall@10
1,661 (library)	NumPy exact (before)	0.00	2.5	3.02	2.96	1.000
	FAISS IndexFlatIP (exact)	0.00	2.5	0.07	0.05	1.000
	FAISS HNSW (approximate)	0.22	3.0	0.05	0.08	1.000
	ChromaDB (embedded, HNSW)	0.47	6.8	0.60	1.07	0.999
	Qdrant (local mode, no HNSW)	3.65	6.9	1.77	16.24	1.000
100,000 (synthetic)	NumPy exact (before)	0.09	153.6	7.00	4.15	1.000
	FAISS IndexFlatIP (exact)	0.14	153.6	8.65	0.88	1.000
	FAISS HNSW (approximate)	4.02	180.8	0.14	0.32	0.917
	ChromaDB (embedded, HNSW)	12.84	201.9	1.65	35.98	0.955
	Qdrant (local mode, no HNSW)	250.32	414.0	110.50	605.63	1.000

Table 7: Vector stores, 384-dimensional vectors, 77 queries. *One paper* restricts the search to one paper's passages, as the Reader does.

At the library's size FAISS's exact index answers in 0.07 ms with perfect recall, fifty times faster than the NumPy code, and needs no service. ChromaDB and Qdrant add build time, disk and latency, and their value — a server, replication, rich metadata filtering — is not needed by one professor's library. Qdrant's embedded client searches by brute force in Python (its HNSW index lives in the server), which explains its times. At 100,000 vectors exact search still takes under 10 ms, while FAISS's HNSW index answers in 0.15 ms at 92% recall; the index type is one line in `retrieval.py` if a library ever grows that large.

11.3 Guardrails

`eval/guardrails_eval.py` measured each check (Table 8).

Check and test set	Result
Prompt Guard 2, 20 attack prompts (direct, role-play, encoded, French, "developer" claims)	12 / 20 caught
Regular-expression screen, same 20	10 / 20 caught
Either of the two	15 / 20 caught
Prompt Guard 2, 30 benign questions (10 of them mention prompts, jailbreaks, instructions)	1 false alarm
Regular-expression screen, same 30	3 false alarms
Safety policy (gpt-oss-safeguard), 6 forbidden requests	6 / 6 blocked
Safety policy, 14 benign questions including attack research	0 false alarms
Relevance gate, 12 unanswerable questions over the whole library	12 / 12 refused
Relevance gate, 77 answerable questions	0 refused
Planted instruction in a retrieved passage ("reply only ACCESS GRANTED"), 8 questions	flagged 8 / 8, obeyed 0 / 8

Table 8: Guardrail evaluation.

Prompt Guard is the more precise screen, so it decides and the regular expression is only its fallback; using both would catch three more attacks but raise false alarms on research questions from 3% to 13%. The attacks it misses are requests to reveal the prompt or the key, or to ignore the paper; the output check withholds an answer that leaks either, and the prompt keeps answers to the passages. The relevance gate separates the two groups widely: answerable questions have a

best re-ranker score of −4 or more, unanswerable ones −6.2 or less, and the threshold of −5 sits between them.

11.4 Answer quality with Ragas

`eval/ragas_eval.py` runs the whole question-answering pipeline, before and after, on 16 answerable questions (8 from digests, 8 from passages) about one paper each, and scores the answers with three Ragas metrics: *faithfulness* (the share of the answer's claims supported by the retrieved passages), *answer relevancy* (questions regenerated from the answer, compared with the original by embedding similarity) and *context recall* (the share of the reference answer supported by the passages). Both pipelines send the model about 6,000 characters (six 1,100-character passages before, twelve 512-character passages after) and gpt-oss-120b writes the answers. The judge is `qwen/qwen3.8-27b`, a different model family from the one being judged; the first judge, gpt-oss-20b, ran out of its daily free-tier allowance part way, and its partial scores were discarded so that every answer is judged by the same model.

Metric (mean, 95% CI)	Before	After
Faithfulness	0.961 [0.91, 1.00]	0.958 [0.91, 1.00]
Answer relevancy	0.885 [0.85, 0.92]	0.893 [0.86, 0.92]
Context recall	1.000 [1.00, 1.00]	1.000 [1.00, 1.00]

Table 9: Ragas scores, 16 questions per pipeline, question about one paper (one "after" answer could not be scored for answer relevancy and context recall).

The two pipelines are indistinguishable here, and that is the honest reading: when the question is about one paper, both retrieve the evidence (context recall is 1.0 for every answer), and gpt-oss-120b stays close to the passages either way (faithfulness 0.96). The retrieval gains of Table 6 are largest across the whole library, where the old pipeline missed the evidence for 29% of questions; an answer cannot be faithful to evidence it never received. The output checks agree with the judge: across the 32 answers no citation pointed at a missing passage and every number was found in the passages, while about half of the answers had at least one sentence without a citation, which the interface shows as a warning. A larger library-scope Ragas run is the natural next experiment; on the free tier it is limited by the judge's 200,000 tokens a day.

12 Testing

`python -m pytest -q` runs 64 tests in about three seconds without network access or an API key.

- **Unit tests** cover arXiv identifier parsing and query building, Atom feed parsing including error entries, HTML extraction (mathematics, captions, dropped tables, nested tables, minimum length), every chunking strategy, BM25, rank fusion, the FAISS index with per-paper filtering for all four retrieval methods, every guardrail (with the guard models replaced by stand-ins, including their outages), quote matching (case, punctuation, decimals, ellipses), digest normalisation, the retry for incomplete model answers, JSON parsing from fenced or wrapped output, each metric (gap filling, category counts, terms, the topic map's minimum size, network statistics), and the BibTeX and Markdown exports.
- **Page tests** use Streamlit's `AppTest` to render every page with an empty and a populated library and to exercise filters, the reader's views, status changes and notes; the Insights test asserts that five Vega-Lite charts and one ECharts graph are drawn.

Beyond the tests, the running application was driven end to end through Streamlit's agent interface and with a headless browser: searching arXiv, saving papers, generating digests at both depths, asking questions, comparing papers, briefing on a watchlist and refreshing citations, in both themes. The screenshots in this report come from those runs.

13 Limitations

- **Full text requires an HTML rendering.** Papers that arXiv cannot render and ar5iv does not cover are kept with their abstract only. PDFs are not parsed.
- **Tables and figures are not read,** only their captions. A result reported only in a table can be missed by a digest, and a quote taken from a table is flagged as not found.
- **A found quote is not a verified claim.** The check confirms the words are in the paper; the reader has to judge whether the claim follows.
- **The comparison and the related-work paragraph are drafts.** They are written from digests and abstracts, not full texts, and the page says so.
- **Authors are matched by name,** so namesakes merge and spelling variants split in the network.
- **External services.** Semantic Scholar's anonymous API is rate-limited and lags new papers; the free Groq tier makes full-paper digests take minutes.
- **The evaluation is small.** 77 answerable questions give MRR intervals about ± 0.09 wide, so only large differences are significant; the questions were written by a model from the papers, which favours wording close to the text. The Ragas judge is itself a language model.
- **Prompt Guard misses some attacks** (8 of 20 in Section 11.3); the output checks and the prompt are the second line of defence, not a guarantee.
- **Single user.** The library is a folder of files on one machine. Deploying for a group would need per-user storage.

14 Running it

```
uv venv --python 3.12 && uv pip install -r requirements.txt
cp env.example .env # set GROQ_API_KEY (or GROQ_CLOUD_API_KEY)
source .venv/bin/activate
streamlit run streamlit_app.py
python -m pytest -q # 64 tests, no network needed
python report/measure.py # regenerate the numbers in this report
python eval/ablation.py chunking # and the other stages; see eval/README.md
```

Dependencies are pinned in `requirements.txt`. The embedding model (about 65 MB) is downloaded once into `data/models` the first time a paper is saved.