DynamoDB-style 5-table starter model for a Disney+/Netflix-like app focused on **user data**. It's opinionated for real access patterns (profiles, sessions, watch history, lists), and uses GSIs where they meaningfully help.

1) Accounts

Purpose: Account-level identity and contact info (owner of billing, profiles).
PK: AccountID (S)
GSIs:

- GSI_Email → Email (S) (unique lookup by email)

Example items


```
{
  "AccountID": "ACC#1001",
  "Email": "maria@example.com",
  "FullName": "Maria Lopez",
  "Country": "US",
  "CreatedAt": "2024-07-18T12:44:00Z",
  "Status": "ACTIVE"
}
{
  "AccountID": "ACC#1002",
  "Email": "dave@example.com",
  "FullName": "Dave Kim",
  "Country": "PL",
  "CreatedAt": "2025-01-03T09:10:00Z",
  "Status": "PAST_DUE"
}
```


Common queries

- Get account by email → query GSI_Email with Email = :e
- Get account record → GetItem by AccountID

---

2) Profiles

Purpose: Per-viewer persona under an account (kids, adults, language prefs).
PK: ProfileID (S)
GSIs:

- GSI_AccountProfiles → AccountID (S) (list profiles by account)

Example items


```
{
  "ProfileID": "PROF#p1",
  "AccountID": "ACC#1001",
  "DisplayName": "Mom",
  "MaturityRating": "16+",
  "Language": "en",
  "Avatar": "mickey_02"
}
{
  "ProfileID": "PROF#p2",
  "AccountID": "ACC#1001",
  "DisplayName": "Kids",
  "MaturityRating": "7+",
  "Language": "en",
  "Avatar": "stitch_01",
  "KidsMode": true
}
```


Common queries

- List all profiles for an account → query GSI_AccountProfiles by AccountID
- Fetch a single profile → GetItem by ProfileID

---

3) Sessions (Devices)

Purpose: Active device sessions / tokens with TTL auto-expiry.
PK: SessionID (S)
GSIs:

- GSI_ByAccount → AccountID (S) (all sessions on an account)
- GSI_ByProfile → ProfileID (S) (sessions for a profile)
  Other: ExpiresAt (N) as **TTL** attribute

Example items


```
{
  "SessionID": "SESS#z9",
  "AccountID": "ACC#1001",
  "ProfileID": "PROF#p2",
  "DeviceID": "AppleTV-ABCD",
  "IssuedAt": "2025-10-18T20:12:30Z",
  "ExpiresAt": 1761225600,
  "IP": "203.0.113.15",
  "Region": "eu-central-1"
}
{
  "SessionID": "SESS#y3",
  "AccountID": "ACC#1001",
  "ProfileID": "PROF#p1",
  "DeviceID": "iPhone-XS-2345",
  "IssuedAt": "2025-10-19T09:02:10Z",
  "ExpiresAt": 1761268800,
  "IP": "198.51.100.27",
  "Region": "us-east-1"
}
```


Common queries

- Invalidate / inspect active sessions → query GSI_ByAccount with AccountID
- See which devices a child is using → query GSI_ByProfile with ProfileID

---

4) PlaybackEvents (Watch History)

Purpose: Time-ordered playback & completion signals (“Continue watching”, history).
PK/SK: ProfileID (S) **+** WatchedAt (S, ISO timestamp)
GSIs:

- GSI_ByContent → ContentID (S) (who watched a title—useful for analytics/recs)
- Optional: GSI_ByAccountDate → AccountID (S) + WatchedAt (S) (household view)

Example items


```
{
  "ProfileID": "PROF#p1",
  "WatchedAt": "2025-10-19T21:14:03Z",
  "AccountID": "ACC#1001",
  "ContentID": "MOV#frozen2",
  "ContentType": "MOVIE",
  "PositionSeconds": 4230,
  "DurationSeconds": 6180,
  "Completed": false,
  "DeviceID": "iPhone-XS-2345"
}
{
  "ProfileID": "PROF#p1",
  "WatchedAt": "2025-10-18T18:05:12Z",
  "AccountID": "ACC#1001",
  "ContentID": "EP#ahsoka_s01e03",
  "ContentType": "EPISODE",
  "PositionSeconds": 1670,
  "DurationSeconds": 2520,
  "Completed": true,
  "DeviceID": "AppleTV-ABCD"
}
```


Common queries

- Recent history for a profile → Query by ProfileID, ScanIndexForward=false, Limit=20
- Who watched specific content → query GSI_ByContent with ContentID

---

5) MyList (Favorites / Watchlist)

Purpose: "Add to My List" per profile with quick last-updated sorting.
PK/SK: ProfileID (S) **+** ContentID (S)
GSIs:

- GSI_LastUpdated → ProfileID (S) + UpdatedAt (S) (sort by most recent)

Example items


```
{
  "ProfileID": "PROF#p2",
  "ContentID": "SER#bluey",
  "AddedAt": "2025-10-17T10:11:00Z",
  "UpdatedAt": "2025-10-19T08:45:30Z",
  "Notes": "Favorite"
}
{
  "ProfileID": "PROF#p1",
  "ContentID": "MOV#insideout2",
  "AddedAt": "2025-10-18T12:00:01Z",
  "UpdatedAt": "2025-10-18T12:00:01Z"
}
```


Common queries

- Fetch a profile's list → Query by ProfileID
- Sort by most recently updated → Query GSI_LastUpdated with ProfileID and descending on UpdatedAt