

# Unit Configuration

Report No.: 6101563

Product ID: CN-150C

Date: 2025-07-16

Configuration Type	Cooling Circulation System	Design Pressure	180 bar
Flow Rate	48 L/min	Operating Voltage	480 V / 60 Hz
Service Interval	12 months	Control Valve	Directional 4/3
Battery Capacity	5 Ah	Reservoir Capacity	120 L
Mounting	Skid base with vibration pads	Noise Level	≤ 68 dB(A)
Motor Power	7.5 kW	Dimensions (LxWxH)	1200 x 700 x 1100 mm

Component Materials Overview:		
Label	Base	Specification
LED Light Strip	Glass-Filled Nylon	ISO 2768
Teflon Tape Roll	Teflon Tape Roll	Class A tolerance
O-Ring NBR 60mm	Nitrile Rubber (NBR)	CE certified
Gasket Sheet A4	Nitrile Rubber (NBR)	RoHS compliant
Wiring Loom 1m	PVC (Rigid)	DIN EN 10025
Rubber Gasket 80mm	Nitrile Rubber (NBR)	IP67 rated
Wooden Pallet	Treated Pine Wood	RoHS compliant
Fuse 5A	Ceramic Oxide	DIN EN 10025

Prepared by: Peter Schmidt

Approved by: Peter Schmidt