Product Ref	Component	Dimensions	Target	Tolerance (mm)	Observed	Diff	Tool	Status (Good/Bad)
GH-770J	Bearing 6202 ZZ	Height	67.04	±0.20	66.97	-0.07	CMM	OK
GH-770J	Battery Pack	Width	13.25	±0.20	13.07	-0.18	СММ	ОК
GH-770J	O-Ring NBR 60mm	Height	61.07	±0.20	60.93	-0.14	Laser Scanner	OK
TL-900X	O-Ring NBR 60mm	Length	32.19	±0.20	32.33	+0.14	CMM	OK
SL-430M	Shaft 500mm	Thickness	37.98	±0.20	38.14	+0.16	Laser Scanner	OK
CE-905L	Plastic Rivets	Height	88.36	±0.20	88.22	-0.14	Depth Gauge	OK
RX-310Z	Plastic Rivets	Width	25.57	±0.20	25.64	+0.07	Laser Scanner	OK
GL-980S	Graphite Pad	Inner Diameter	22.98	±0.20	22.87	-0.11	CMM	ОК
JD-700W	Steel Sheet A36	Length	92.51	±0.20	92.48	-0.03	Measuring Tape	ОК
TY-350G	Battery Pack	Inner Diameter	84.03	±0.20	83.92	-0.11	Caliper	OK
TY-350G	Shaft 500mm	Width	21.68	±0.20	21.73	+0.05	Depth Gauge	OK
KP-320E	Hex Bolts M12	Length	39.37	±0.20	39.24	-0.13	Caliper	OK
AL-115Q	O-Ring NBR 60mm	Width	38.54	±0.20	38.54	+0.00	CMM	ОК

Final Count: 13 OK, 0 NOK