

Component Overview

Document No.: PR-656

Product ID: QN-770H

Date: 2025-01-19

| | | | |
|---------------|----------------------------|----------------|-------------------------|
| Model Type | Cooling Circulation System | Rated Pressure | 250 bar |
| Fluid Flow | 75 L/min | Voltage | 480 V / 60 Hz |
| Motor Power | 5.5 kW | Oil Type | HLP 32 |
| Charging Time | 6 h | Cooling | Air-cooled oil radiator |
| Noise Level | ≤ 68 dB(A) | Control Valve | Proportional 4/2 |

| Component Materials Overview: | | |
|-------------------------------|----------------------------------|-------------------|
| Label | Raw Material | Specification |
| Capacitor 450V | Aluminum 6061-T6 | IP67 rated |
| Bearing 6202 ZZ | Stainless Steel 304 | Heat-resistant |
| Support Foot Steel | Stainless Steel 304 | Electrical grade |
| Wooden Pallet | Treated Pine Wood | Class A tolerance |
| Graphite Pad | Graphite Pad | UL-listed |
| Thermal Fuse | Ceramic Oxide | Electrical grade |
| Connector 2P | Glass-Filled Nylon | CE certified |
| Insulated Tube 25mm | Thermoplastic Polyurethane (TPU) | Anticorrosive |

Prepared by: Peter Schmidt

Approved by: Jan Kowalski