

Inspection Results Summary

Inspection performed by Laura Rossi on 2024-02-10.

Product Ref	Part Name	Measurement	Nominal	Actual	Diff	Status (V/X)
ZR-205R	Rubber Gasket 80mm	Width	39.70	39.64	-0.06	V
SL-430M	O-Ring NBR 60mm	Inner Diameter	99.37	99.43	+0.06	V
TY-350G	Power Switch	Hole Ø	74.26	74.25	-0.01	V
TX-820V	Plastic Rivets	Inner Diameter	34.90	34.79	-0.11	V
QP-660F	Plastic Rivets	Hole Ø	25.32	25.33	+0.01	V
HF-390A	Bearing 6202 ZZ	Inner Diameter	74.91	74.78	-0.13	V
TX-820V	Power Switch	Width	43.87	43.95	+0.08	V
XD-710R	O-Ring NBR 60mm	Hole Ø	66.36	66.56	+0.20	V
TR-200B	Graphite Pad	Width	5.63	5.47	-0.16	V
VF-220D	Power Switch	Width	84.75	84.92	+0.17	V
MS-600P	Bearing 6202 ZZ	Inner Diameter	37.93	38.01	+0.08	V
WD-180S	Rubber Gasket 80mm	Width	22.25	22.16	-0.09	V
WD-180S	O-Ring NBR 60mm	Hole Ø	60.83	60.94	+0.11	V
KV-390K	Power Switch	Width	13.40	13.39	-0.01	V
CE-905L	Hex Bolts M12	Depth	16.68	16.75	+0.07	V
GL-980S	Power Switch	Inner Diameter	18.28	18.31	+0.03	V