

Product Data Sheet

Document No.: PR-576

Product ID: PW-515Y

Date: 2024-01-04

| | | | |
|--------------------|------------------------|---------------------|---------------|
| Model Type | Pneumatic Control Unit | Operating Pressure | 180 bar |
| Fluid Flow | 60 L/min | Operating Voltage | 400 V / 50 Hz |
| Pump Type | Vane Pump | Working Temp. Range | 10°C to 55°C |
| Dimensions (LxWxH) | 1000 x 650 x 1000 mm | Battery Capacity | 2 Ah |
| Cooling | Water-cooled exchanger | Noise Level | ≤ 70 dB(A) |
| Total Weight | 180 kg | | |

| Component Materials Overview: | | |
|-------------------------------|------------------------|-------------------|
| Item | Composition | Specification |
| Pressure Valve | Brass CZ121 | Anticorrosive |
| Heat Sink ALU | Aluminum 6061-T6 | Anticorrosive |
| Graphite Pad | Graphite Pad | Class A tolerance |
| Connector 2P | Glass-Filled Nylon | Anticorrosive |
| Teflon Tape Roll | Teflon Tape Roll | CE certified |
| Gasket Sheet A4 | Nitrile Rubber (NBR) | Class A tolerance |
| Power Switch | Polycarbonate + Copper | DIN EN 10025 |
| Cable Tie Pack (100) | Nitrile Rubber (NBR) | UL-listed |

Prepared by: Laura Rossi

Approved by: Anna Nowak