

## Product Data Sheet

Report No.: PR-578

Product ID: BZ-660F

Date: 2024-05-31

<b>Configuration Type</b>	Hydraulic Power Unit	<b>Design Pressure</b>	210 bar
<b>Fluid Flow</b>	75 L/min	<b>Voltage</b>	400 V / 50 Hz
<b>Control Valve</b>	Directional 4/3	<b>Total Weight</b>	250 kg
<b>Service Interval</b>	500 h	<b>Cooling</b>	Air-cooled oil radiator
<b>Working Temp. Range</b>	-10°C to 50°C	<b>Mounting</b>	Wall-mounted
<b>Dimensions (LxWxH)</b>	1200 x 700 x 1100 mm		

Component Materials Overview:		
Item	Base	Specification
Battery Pack	Lithium-Ion Cell Pack	DIN EN 10025
Power Switch	Polycarbonate + Copper	ISO 2768
Cooling Gel Pack	Silicone Rubber	DIN EN 10025
Bearing 6202 ZZ	Stainless Steel 304	DIN EN 10025
Gasket Sheet A4	Nitrile Rubber (NBR)	DIN EN 10025
Wooden Pallet	Treated Pine Wood	CE certified

**Prepared by: Anna Nowak**

**Approved by: Carlos Garcia**