Tolerance Check

Product Ref	Component	Dimensions	Target	Tolerance (mm)	Observed	Diff	Tool	Status (Good/Bad)
PL-601Z	Graphite	Inner	41.86	±0.20	42.05	+0.19	Depth	OK
	Pad	Diameter					Gauge	
QP-660F	Power	Width	86.82	±0.20	86.64	-0.18	Depth	ОК
	Switch						Gauge	
MS-600P	Power	Thickness	41.92	±0.20	42.02	+0.10	Caliper	OK
	Switch							
GH-770J	Battery	Height	85.53	±0.20	85.34	-0.19	Micrometer	ОК
	Pack							
DX-777T	Rubber	Height	41.83	±0.20	41.75	-0.08	Caliper	ОК
	Gasket							
	80mm							
VF-220D	Wooden	Inner	11.18	±0.20	11.22	+0.04	Measuring	ОК
	Pallet	Diameter					Tape	
DX-777T	Rubber	Height	12.41	±0.20	12.57	+0.16	Laser	ОК
	Gasket						Scanner	
	80mm							
NU-440Z	O-Ring NBR	Hole Ø	44.47	±0.20	44.67	+0.20	CMM	ОК
	60mm							
SB-140D	Wooden	Length	56.18	±0.20	56.14	-0.04	Measuring	OK
	Pallet						Tape	
KV-390K	Steel Sheet	Thickness	35.22	±0.20	35.07	-0.15	Laser	ОК
	A36						Scanner	

Inspected Units – V: 10 / X: 0