Article	Component	Dimensions	Target	Tolerance	Observed	Diff	Tool	Status
No.				(mm)				(Good/Bad)
AZ-300T	Bearing 6202 ZZ	Depth	47.52	±0.20	47.68	+0.16	Caliper	OK
MC-	Power	Inner	93.46	±0.20	93.53	+0.07	Laser	OK
540X	Switch	Diameter					Scanner	
VF-220D	Hex Bolts	Height	74.48	±0.20	74.53	+0.05	Laser	ОК
	M12						Scanner	
KV-390K	Battery Pack	Depth	64.58	±0.20	64.71	+0.13	Depth Gauge	ОК
GH-770J	Hex Bolts	Inner	81.09	±0.20	80.96	-0.13	Caliper	ОК
	M12	Diameter						
BZ-660F	Battery Pack	Width	96.44	±0.20	96.54	+0.10	Caliper	ОК
MC- 540X	Battery Pack	Inner Diameter	24.82	±0.20	24.94	+0.12	Caliper	OK
QP-660F	Hex Bolts	Inner	46.72	±0.20	46.81	+0.09	Laser	ОК
	M12	Diameter					Scanner	
SL-430M	Graphite	Inner	56.49	±0.20	56.60	+0.11	Micrometer	ОК
	Pad	Diameter						
JD-	Steel Sheet	Thickness	76.59	±0.20	76.66	+0.07	Depth	ОК
700W	A36						Gauge	
AZ-300T	Bearing 6202 ZZ	Width	38.91	±0.20	39.04	+0.13	Depth Gauge	ОК
FT-730X	Graphite Pad	Thickness	25.68	±0.20	25.75	+0.07	CMM	ОК
WD-	Wooden	Thickness	91.92	±0.20	91.77	-0.15	Measuring	ОК
180S	Pallet		02.02		32	0.120	Tape	
AL-115Q	Shaft	Depth	27.35	±0.20	27.24	-0.11	Measuring	ОК
	500mm						Tape	
LK-890B	Steel Sheet	Depth	85.88	±0.20	85.98	+0.10	Laser	ОК
	A36						Scanner	
RX-310Z	Plastic	Inner	70.57	±0.20	70.38	-0.19	Depth	OK
	Rivets	Diameter					Gauge	
HF-390A	Hex Bolts	Height	37.79	±0.20	37.83	+0.04	Depth	ОК
	M12						Gauge	
GH-770J	Graphite	Length	44.74	±0.20	44.75	+0.01	Depth	ОК
	Pad						Gauge	

Final Count: 18 OK, 0 NOK