

## Dimensional Log

Product Ref	Component	Dimensions	Target	Tolerance (mm)	Actual	Diff	Tool	Status (Good/Bad)
CE-905L	Shaft 500mm	Thickness	48.15	±0.20	47.99	-0.16	Caliper	V
GL-980S	Bearing 6202 ZZ	Inner Diameter	91.12	±0.20	90.95	-0.17	Laser Scanner	V
ZR-205R	Battery Pack	Inner Diameter	19.51	±0.20	19.42	-0.09	CMM	V
FT-730X	Steel Sheet A36	Inner Diameter	32.58	±0.20	32.68	+0.10	Caliper	V
AL-115Q	Bearing 6202 ZZ	Width	46.60	±0.20	46.64	+0.04	CMM	V
FT-730X	Graphite Pad	Hole Ø	72.93	±0.20	72.85	-0.08	CMM	V
TX-820V	Steel Sheet A36	Length	84.18	±0.20	84.36	+0.18	Laser Scanner	V
PW-515Y	Power Switch	Inner Diameter	88.37	±0.20	88.57	+0.20	Depth Gauge	V
FT-730X	Power Switch	Hole Ø	24.91	±0.20	24.90	-0.01	Micrometer	V
MX-450L	Steel Sheet A36	Length	92.15	±0.20	92.02	-0.13	Micrometer	V
KV-390K	Wooden Pallet	Depth	65.96	±0.20	65.89	-0.07	Depth Gauge	V
WD-180S	Hinge Set	Inner Diameter	45.10	±0.20	45.24	+0.14	Caliper	V
GH-770J	Rubber Gasket 80mm	Height	59.73	±0.20	59.80	+0.07	Micrometer	V
SB-140D	Wooden Pallet	Height	21.34	±0.20	21.40	+0.06	Laser Scanner	V

Inspected Units – V: 14 / X: 0