Inspection performed by Laura Rossi on 2025-04-29.

Below are the recorded measurements compared against nominal tolerances. Please review the inspection results for each component listed below. This data extract is prepared for quality-control sign-off. Use this results summary to trigger any corrective actions. Ensure measurement methods align with calibration standards. This report presents the dimensional measurements and inspection results.

Environmental Conditions: Temperature: 20.4 °C, Humidity: 58 %

Item Code	Part Name	Measurement	Target	Observed	Diff	Status (V/X)
VR-940T	Rubber Gasket 80mm	Depth	67.61	67.49	-0.12	OK
RM-860N	Rubber Gasket 80mm	Width	37.83	38.02	+0.19	OK
GL-980S	Wooden Pallet	Thickness	26.50	26.49	-0.01	OK
TX-820V	Hex Bolts M12	Inner Diameter	27.11	27.27	+0.16	OK
HF-390A	Wooden Pallet	Length	46.31	46.28	-0.03	OK
DX-777T	Power Switch	Hole Ø	60.84	60.83	-0.01	OK
SL-430M	Plastic Rivets	Thickness	15.77	15.60	-0.17	OK
PL-601Z	Shaft 500mm	Hole Ø	44.50	44.34	-0.16	OK
JD-700W	O-Ring NBR 60mm	Width	93.34	93.43	+0.09	OK
DX-777T	Graphite Pad	Length	34.89	34.85	-0.04	OK
VR-940T	Steel Sheet A36	Height	71.42	71.27	-0.15	OK
QN-770H	Wooden Pallet	Height	43.33	43.25	-0.08	OK
ZR-205R	Hex Bolts M12	Inner Diameter	65.07	64.91	-0.16	OK
JD-700W	Plastic Rivets	Depth	99.04	99.22	+0.18	OK
SL-430M	Hinge Set	Length	7.18	7.26	+0.08	OK
KV-390K	Shaft 500mm	Inner Diameter	63.07	63.01	-0.06	OK
TX-820V	Bearing 6202 ZZ	Width	91.78	91.78	+0.00	OK
CE-905L	Battery Pack	Inner Diameter	47.61	47.79	+0.18	OK