

Measurement Summary Sheet

| Product Ref | Component | Dimensions | Target | Tolerance (mm) | Observed | Diff | Tool | Status (Good/Bad) |
|-------------|--------------------|----------------|--------|----------------|----------|-------|----------------|-------------------|
| XK-610U | Wooden Pallet | Hole Ø | 26.55 | ±0.20 | 26.49 | -0.06 | Depth Gauge | PASS |
| TL-900X | Rubber Gasket 80mm | Height | 93.93 | ±0.20 | 94.12 | +0.19 | Caliper | PASS |
| KP-320E | Steel Sheet A36 | Depth | 64.46 | ±0.20 | 64.61 | +0.15 | Caliper | PASS |
| ZR-205R | Power Switch | Inner Diameter | 80.17 | ±0.20 | 80.14 | -0.03 | CMM | PASS |
| SB-140D | Hinge Set | Depth | 49.50 | ±0.20 | 49.50 | +0.00 | Caliper | PASS |
| XD-710R | Graphite Pad | Depth | 22.88 | ±0.20 | 23.07 | +0.19 | Micrometer | PASS |
| CN-150C | Shaft 500mm | Height | 44.41 | ±0.20 | 44.53 | +0.12 | CMM | PASS |
| QN-770H | Hinge Set | Thickness | 92.27 | ±0.20 | 92.14 | -0.13 | Micrometer | PASS |
| TL-900X | O-Ring NBR 60mm | Hole Ø | 33.06 | ±0.20 | 33.01 | -0.05 | CMM | PASS |
| RE-850C | Battery Pack | Length | 7.70 | ±0.20 | 7.72 | +0.02 | Measuring Tape | PASS |
| MC-540X | Battery Pack | Thickness | 21.87 | ±0.20 | 21.84 | -0.03 | Laser Scanner | PASS |
| MX-450L | Power Switch | Thickness | 91.94 | ±0.20 | 91.87 | -0.07 | Depth Gauge | PASS |
| XK-610U | Graphite Pad | Length | 65.92 | ±0.20 | 65.78 | -0.14 | Measuring Tape | PASS |
| VR-940T | Hex Bolts M12 | Height | 31.95 | ±0.20 | 32.03 | +0.08 | Caliper | PASS |
| XK-610U | Rubber Gasket 80mm | Hole Ø | 41.44 | ±0.20 | 41.30 | -0.14 | Caliper | PASS |
| ZR-205R | Wooden Pallet | Length | 19.42 | ±0.20 | 19.55 | +0.13 | Depth Gauge | PASS |

Inspected Units – V: 16 / X: 0