

Tolerance Check

Inspection performed by Laura Rossi on 2024-12-17.

Article No.	Part Name	Dim.	Target	Observed	Delta	Status (V/X)
GL-980S	O-Ring NBR 60mm	Width	42.63	42.73	+0.10	OK
LP-555V	Hex Bolts M12	Hole Ø	51.21	51.14	-0.07	OK
WD-180S	Bearing 6202 ZZ	Inner Diameter	28.86	28.95	+0.09	OK
ZR-205R	Graphite Pad	Thickness	22.93	23.03	+0.10	OK
PW-515Y	Battery Pack	Height	81.89	82.08	+0.19	OK
TL-900X	Battery Pack	Height	87.92	87.87	-0.05	OK
MC-540X	O-Ring NBR 60mm	Length	95.11	95.08	-0.03	OK
FT-730X	Hex Bolts M12	Thickness	61.04	61.24	+0.20	OK
FT-730X	Rubber Gasket 80mm	Inner Diameter	37.63	37.64	+0.01	OK
RM-860N	Bearing 6202 ZZ	Height	66.18	66.23	+0.05	OK
VR-940T	Plastic Rivets	Thickness	45.57	45.68	+0.11	OK
RE-850C	O-Ring NBR 60mm	Hole Ø	79.09	79.00	-0.09	OK
VF-220D	Steel Sheet A36	Length	22.00	22.18	+0.18	OK