## **Inspection Results Summary**

Article No.	Component	Dimensions	Nominal	Tolerance (mm)	Observed	Diff	Tool	Status (Good/Bad)
MS-	Steel Sheet	Inner	11.41	±0.20	11.50	+0.09	Measuring	V
600P	A36	Diameter					Таре	
QP-660F	Bearing 6202 ZZ	Length	46.36	±0.20	46.45	+0.09	Measuring Tape	V
ZR-205R	Rubber Gasket 80mm	Depth	32.32	±0.20	32.38	+0.06	Caliper	V
PW-	Power	Inner	66.57	±0.20	66.41	-0.16	Caliper	V
515Y	Switch	Diameter						
VR-940T	Plastic Rivets	Hole Ø	81.96	±0.20	81.81	-0.15	Caliper	V
AZ-300T	O-Ring NBR 60mm	Width	75.95	±0.20	75.98	+0.03	Laser Scanner	V
LK-890B	Graphite Pad	Depth	63.88	±0.20	64.06	+0.18	Depth Gauge	V
KP-320E	Bearing 6202 ZZ	Inner Diameter	94.61	±0.20	94.48	-0.13	Laser Scanner	V
HF-390A	Power Switch	Depth	49.45	±0.20	49.40	-0.05	СММ	V
HF-390A	Power Switch	Depth	83.01	±0.20	82.98	-0.03	Depth Gauge	V
HF-390A	Rubber Gasket 80mm	Thickness	28.20	±0.20	28.14	-0.06	Micrometer	V
VR-940T	Plastic Rivets	Inner Diameter	62.24	±0.20	62.32	+0.08	Depth Gauge	V
RX-310Z	Shaft 500mm	Length	39.08	±0.20	39.16	+0.08	Measuring Tape	V
TX-820V	Battery Pack	Hole Ø	46.37	±0.20	46.30	-0.07	Depth Gauge	V
SB-140D	Bearing 6202 ZZ	Inner Diameter	58.07	±0.20	57.99	-0.08	Depth Gauge	V
GL-980S	Power Switch	Thickness	76.74	±0.20	76.92	+0.18	Depth Gauge	V
CN- 150C	Graphite Pad	Depth	80.02	±0.20	80.12	+0.10	CMM	V

Final Count: 17 OK, 0 NOK