

Article No.	Component	Dimensions	Target	Tolerance (mm)	Actual	Diff	Tool	Status (Good/Bad)
PW-515Y	Bearing 6202 ZZ	Width	33.66	±0.20	33.64	-0.02	Caliper	OK
NU-440Z	Power Switch	Length	55.24	±0.20	55.13	-0.11	Laser Scanner	OK
RE-850C	Hex Bolts M12	Width	17.69	±0.20	17.73	+0.04	Depth Gauge	OK
VF-220D	Hinge Set	Thickness	22.16	±0.20	22.01	-0.15	Micrometer	OK
RE-850C	Hinge Set	Height	90.33	±0.20	90.32	-0.01	Laser Scanner	OK
GH-770J	Rubber Gasket 80mm	Inner Diameter	88.49	±0.20	88.47	-0.02	CMM	OK
RM-860N	Bearing 6202 ZZ	Length	13.38	±0.20	13.44	+0.06	Measuring Tape	OK
MX-450L	Wooden Pallet	Height	57.59	±0.20	57.43	-0.16	CMM	OK
RE-850C	Power Switch	Hole Ø	79.95	±0.20	80.09	+0.14	CMM	OK
SB-140D	Hinge Set	Height	88.72	±0.20	88.86	+0.14	Depth Gauge	OK
HF-390A	Bearing 6202 ZZ	Inner Diameter	74.68	±0.20	74.73	+0.05	CMM	OK
CN-150C	O-Ring NBR 60mm	Thickness	13.53	±0.20	13.59	+0.06	Laser Scanner	OK
FT-730X	Steel Sheet A36	Length	47.43	±0.20	47.41	-0.02	Measuring Tape	OK
VR-940T	Hex Bolts M12	Width	85.74	±0.20	85.64	-0.10	Caliper	OK
JD-700W	Hex Bolts M12	Hole Ø	33.49	±0.20	33.42	-0.07	CMM	OK

**Final Count: 15 OK, 0 NOK**