

Inspection Results Summary

Article No.	Component	Dimensions	Nominal	Tolerance (mm)	Actual	Delta	Tool	Status (Good/Bad)
NU-440Z	Wooden Pallet	Thickness	38.66	±0.20	38.55	-0.11	CMM	OK
BZ-660F	Hex Bolts M12	Length	86.58	±0.20	86.45	-0.13	Laser Scanner	OK
KP-320E	Battery Pack	Thickness	60.40	±0.20	60.54	+0.14	Micrometer	OK
AL-115Q	Wooden Pallet	Thickness	50.85	±0.20	50.69	-0.16	Micrometer	OK
TY-350G	Hex Bolts M12	Depth	24.67	±0.20	24.53	-0.14	CMM	OK
WD-180S	Power Switch	Height	88.48	±0.20	88.48	+0.00	Depth Gauge	OK
DX-777T	Hex Bolts M12	Inner Diameter	44.90	±0.20	44.84	-0.06	Micrometer	OK
SL-430M	Battery Pack	Inner Diameter	44.46	±0.20	44.30	-0.16	Micrometer	OK
MR-160H	Shaft 500mm	Inner Diameter	53.71	±0.20	53.61	-0.10	Micrometer	OK
TX-820V	Graphite Pad	Length	24.96	±0.20	24.98	+0.02	CMM	OK
SB-140D	Bearing 6202 ZZ	Hole Ø	70.87	±0.20	70.68	-0.19	Measuring Tape	OK
TX-820V	Hinge Set	Length	74.34	±0.20	74.29	-0.05	Laser Scanner	OK

Final Count: 12 OK, 0 NOK