

Measurement Summary Sheet

Inspection performed by Anna Nowak on 2025-06-01.

Please review the inspection results for each component listed below. This data extract is prepared for quality-control sign-off. Ensure measurement methods align with calibration standards. Below are the recorded measurements compared against nominal tolerances. Entries include both pass/fail markers and deviation magnitudes. Check that all dimensions comply with ISO and company standards.

Environmental Conditions: Temperature: 25.0 °C, Humidity: 46 %

| Product Ref | Part Name | Dim. | Target | Observed | Diff | Status (V/X) |
|-------------|--------------------|-----------|--------|----------|-------|--------------|
| LP-555V | Shaft 500mm | Depth | 23.08 | 22.93 | -0.15 | OK |
| MX-450L | Shaft 500mm | Depth | 86.88 | 86.90 | +0.02 | OK |
| SL-430M | O-Ring NBR 60mm | Thickness | 16.00 | 16.08 | +0.08 | OK |
| TR-200B | Plastic Rivets | Height | 75.63 | 75.69 | +0.06 | OK |
| LK-890B | Hex Bolts M12 | Width | 73.72 | 73.82 | +0.10 | OK |
| DX-777T | Graphite Pad | Hole Ø | 72.12 | 72.09 | -0.03 | OK |
| VF-220D | Hinge Set | Thickness | 44.21 | 44.35 | +0.14 | OK |
| HF-390A | Rubber Gasket 80mm | Width | 42.08 | 42.13 | +0.05 | OK |
| PW-515Y | Bearing 6202 ZZ | Width | 81.34 | 81.34 | +0.00 | OK |
| PL-601Z | Wooden Pallet | Depth | 29.87 | 30.04 | +0.17 | OK |
| TL-900X | Shaft 500mm | Width | 84.27 | 84.08 | -0.19 | OK |
| TR-200B | Rubber Gasket 80mm | Hole Ø | 61.76 | 61.76 | +0.00 | OK |
| AZ-300T | Plastic Rivets | Hole Ø | 51.67 | 51.84 | +0.17 | OK |
| ZR-205R | Hinge Set | Width | 83.29 | 83.22 | -0.07 | OK |
| LP-555V | Graphite Pad | Length | 76.15 | 75.95 | -0.20 | OK |
| LK-890B | Hinge Set | Hole Ø | 53.30 | 53.39 | +0.09 | OK |