

Inspection Results Summary

Inspection performed by Anna Nowak on 2024-03-06.

This data extract is prepared for quality-control sign-off. Check that all dimensions comply with ISO and company standards. Entries include both pass/fail markers and deviation magnitudes. All measured values are timestamped for audit purposes. Ensure measurement methods align with calibration standards.

Environmental Conditions: Temperature: 20.4 °C, Humidity: 33 %

Product Ref	Component	Measurement	Nominal	Observed	Diff	Status (V/X)
TR-200B	Bearing 6202 ZZ	Inner Diameter	6.29	6.42	+0.13	PASS
CE-905L	Wooden Pallet	Height	13.63	13.73	+0.10	PASS
CN-150C	Shaft 500mm	Depth	90.98	91.10	+0.12	PASS
KV-390K	Rubber Gasket 80mm	Thickness	10.88	11.05	+0.17	PASS
LP-555V	Battery Pack	Depth	42.78	42.66	-0.12	PASS
PW-515Y	Bearing 6202 ZZ	Depth	64.54	64.53	-0.01	PASS
HF-390A	Shaft 500mm	Depth	65.13	65.19	+0.06	PASS
AZ-300T	Battery Pack	Width	89.63	89.75	+0.12	PASS
XK-610U	Battery Pack	Hole Ø	80.79	80.87	+0.08	PASS
LP-555V	Hinge Set	Width	81.56	81.56	+0.00	PASS
QN-770H	Hinge Set	Thickness	71.73	71.53	-0.20	PASS
RX-310Z	Shaft 500mm	Length	84.93	84.84	-0.09	PASS
PL-601Z	Bearing 6202 ZZ	Depth	90.05	90.22	+0.17	PASS
QP-660F	Battery Pack	Hole Ø	16.92	16.90	-0.02	PASS