

Inspection Results Summary

Item Code	Component	Dimensions	Target	Tolerance (mm)	Actual	Delta	Tool	Status (Good/Bad)
TL-900X	Graphite Pad	Inner Diameter	21.05	±0.20	20.97	-0.08	CMM	OK
HF-390A	Rubber Gasket 80mm	Width	63.97	±0.20	63.89	-0.08	Caliper	OK
MX-450L	Shaft 500mm	Width	90.82	±0.20	90.85	+0.03	Measuring Tape	OK
SL-430M	Steel Sheet A36	Thickness	33.43	±0.20	33.49	+0.06	Laser Scanner	OK
RX-310Z	Power Switch	Thickness	21.23	±0.20	21.31	+0.08	Depth Gauge	OK
AL-115Q	Bearing 6202 ZZ	Height	59.59	±0.20	59.51	-0.08	Laser Scanner	OK
GL-980S	Wooden Pallet	Hole Ø	92.55	±0.20	92.59	+0.04	Depth Gauge	OK
TX-820V	Bearing 6202 ZZ	Thickness	37.02	±0.20	36.97	-0.05	Measuring Tape	OK
NE-245A	Hinge Set	Depth	91.98	±0.20	92.01	+0.03	Measuring Tape	OK
KP-320E	Battery Pack	Length	61.57	±0.20	61.63	+0.06	CMM	OK
VF-220D	O-Ring NBR 60mm	Width	39.61	±0.20	39.80	+0.19	Depth Gauge	OK

Final Count: 11 OK, 0 NOK