

Inspection performed by Anna Nowak on 2023-08-27.

Article No.	Part Name	Measurement	Nominal	Actual	Delta	Status (V/X)
SL-430M	Wooden Pallet	Hole Ø	46.26	46.28	+0.02	V
MC-540X	Power Switch	Thickness	79.28	79.11	-0.17	V
SB-140D	Hinge Set	Depth	45.93	46.02	+0.09	V
RX-310Z	Hex Bolts M12	Depth	24.90	24.75	-0.15	V
CN-150C	Steel Sheet A36	Inner Diameter	95.00	94.84	-0.16	V
DX-777T	O-Ring NBR 60mm	Thickness	64.99	64.93	-0.06	V
NU-440Z	Shaft 500mm	Thickness	90.09	90.06	-0.03	V
LP-555V	Hinge Set	Length	14.19	14.36	+0.17	V
RE-850C	Shaft 500mm	Depth	6.87	6.83	-0.04	V
FT-730X	Plastic Rivets	Thickness	86.60	86.77	+0.17	V
PL-601Z	Hex Bolts M12	Thickness	7.59	7.65	+0.06	V
BZ-660F	Power Switch	Inner Diameter	67.88	68.01	+0.13	V
AZ-300T	Hinge Set	Hole Ø	52.38	52.55	+0.17	V
QN-770H	Bearing 6202 ZZ	Depth	21.36	21.29	-0.07	V
NU-440Z	Shaft 500mm	Depth	68.07	68.19	+0.12	V
JD-700W	Bearing 6202 ZZ	Length	31.48	31.31	-0.17	V