Tolerance Check

Item Cod e	Componen t	Dimension s	Nomina I	Toleranc e (mm)	Observe d	Delt a	Tool	Status (Good/Bad)
BZ- 660F	Hex Bolts M12	Inner Diameter	99.66	±0.20	99.52	-0.14	Micromete r	V
PL- 601Z	Hex Bolts M12	Length	87.24	±0.20	87.26	+0.0	Caliper	V
NE- 245A	Steel Sheet A36	Length	69.81	±0.20	69.88	+0.0 7	Caliper	V
GL- 980S	Wooden Pallet	Height	16.53	±0.20	16.44	-0.09	СММ	V
SB- 140D	Bearing 6202 ZZ	Hole Ø	82.22	±0.20	82.21	-0.01	Micromete r	V
CN- 150C	Steel Sheet A36	Hole Ø	91.97	±0.20	91.83	-0.14	CMM	V
CE- 905L	Hinge Set	Hole Ø	94.95	±0.20	95.09	+0.1 4	Caliper	V
SL- 430 M	Graphite Pad	Width	80.00	±0.20	80.20	+0.2	Depth Gauge	V
FT- 730X	Battery Pack	Thickness	44.91	±0.20	45.01	+0.1 0	Micromete r	V
LK- 890B	Shaft 500mm	Width	20.62	±0.20	20.81	+0.1 9	Caliper	V
LK- 890B	Bearing 6202 ZZ	Hole Ø	72.42	±0.20	72.55	+0.1 3	Laser Scanner	V
PL- 601Z	Graphite Pad	Width	81.69	±0.20	81.73	+0.0 4	СММ	V
BZ- 660F	Graphite Pad	Hole Ø	51.36	±0.20	51.33	-0.03	Laser Scanner	V

Final Count: 13 OK, 0 NOK