

| Article No. | Component       | Dimensions     | Target | Tolerance (mm) | Observed | Delta | Tool           | Status (Good/Bad) |
|-------------|-----------------|----------------|--------|----------------|----------|-------|----------------|-------------------|
| PW-515Y     | Hex Bolts M12   | Length         | 9.29   | ±0.20          | 9.43     | +0.14 | Measuring Tape | OK                |
| TR-200B     | Wooden Pallet   | Width          | 65.38  | ±0.20          | 65.19    | -0.19 | Depth Gauge    | OK                |
| KP-320E     | Hinge Set       | Thickness      | 71.50  | ±0.20          | 71.45    | -0.05 | Depth Gauge    | OK                |
| GH-770J     | Bearing 6202 ZZ | Inner Diameter | 31.25  | ±0.20          | 31.18    | -0.07 | Measuring Tape | OK                |
| MX-450L     | O-Ring NBR 60mm | Width          | 49.34  | ±0.20          | 49.43    | +0.09 | Laser Scanner  | OK                |
| TY-350G     | O-Ring NBR 60mm | Length         | 20.96  | ±0.20          | 20.76    | -0.20 | Micrometer     | OK                |
| DX-777T     | Hex Bolts M12   | Inner Diameter | 34.94  | ±0.20          | 34.74    | -0.20 | CMM            | OK                |
| BZ-660F     | Bearing 6202 ZZ | Length         | 12.76  | ±0.20          | 12.78    | +0.02 | Micrometer     | OK                |
| NU-440Z     | O-Ring NBR 60mm | Depth          | 27.01  | ±0.20          | 27.05    | +0.04 | CMM            | OK                |
| RM-860N     | Shaft 500mm     | Length         | 93.35  | ±0.20          | 93.41    | +0.06 | CMM            | OK                |
| WD-180S     | Bearing 6202 ZZ | Thickness      | 30.66  | ±0.20          | 30.62    | -0.04 | Depth Gauge    | OK                |
| NE-245A     | Graphite Pad    | Hole Ø         | 47.74  | ±0.20          | 47.93    | +0.19 | Measuring Tape | OK                |
| QP-660F     | Battery Pack    | Depth          | 91.56  | ±0.20          | 91.67    | +0.11 | Measuring Tape | OK                |
| AL-115Q     | Power Switch    | Hole Ø         | 64.89  | ±0.20          | 64.90    | +0.01 | Depth Gauge    | OK                |
| RE-850C     | Power Switch    | Thickness      | 15.49  | ±0.20          | 15.66    | +0.17 | Depth Gauge    | OK                |
| FT-730X     | Hex Bolts M12   | Height         | 63.58  | ±0.20          | 63.53    | -0.05 | Caliper        | OK                |
| BZ-660F     | Shaft 500mm     | Height         | 26.13  | ±0.20          | 26.23    | +0.10 | Laser Scanner  | OK                |

**Inspected Units – V: 17 / X: 0**