

Inspection performed by Peter Schmidt on 2023-10-13.

Refer to the dimensional log for all component size readings. Ensure measurement methods align with calibration standards. Use this examination summary to confirm component conformity. Check that all dimensions comply with ISO and company standards. All measured values are timestamped for audit purposes. The following data captures key dimensions and any deviations identified.

Environmental Conditions: Temperature: 23.7 °C, Humidity: 53 %

Product Ref	Component	Measurement	Nominal	Actual	Diff	Status (V/X)
SL-430M	Rubber Gasket 80mm	Thickness	16.21	16.08	-0.13	OK
XD-710R	Plastic Rivets	Inner Diameter	92.29	92.30	+0.01	OK
PL-601Z	Hinge Set	Hole Ø	65.52	65.35	-0.17	OK
XD-710R	Plastic Rivets	Hole Ø	54.06	53.97	-0.09	OK
KP-320E	Graphite Pad	Depth	67.69	67.63	-0.06	OK
XD-710R	Hex Bolts M12	Thickness	65.30	65.44	+0.14	OK
RX-310Z	Plastic Rivets	Inner Diameter	10.15	10.30	+0.15	OK
MS-600P	Hinge Set	Inner Diameter	89.08	89.26	+0.18	OK
JD-700W	Shaft 500mm	Width	24.68	24.86	+0.18	OK
GH-770J	Bearing 6202 ZZ	Thickness	56.43	56.53	+0.10	OK
LP-555V	Hinge Set	Hole Ø	65.58	65.49	-0.09	OK
NE-245A	O-Ring NBR 60mm	Hole Ø	47.79	47.86	+0.07	OK
TR-200B	Wooden Pallet	Length	87.35	87.20	-0.15	OK
PW-515Y	Hinge Set	Length	59.44	59.60	+0.16	OK
MC-540X	Rubber Gasket 80mm	Width	73.23	73.08	-0.15	OK
LP-555V	Hex Bolts M12	Width	91.17	91.34	+0.17	OK