

Unit Data Specification

Project:	WD-180S
Internal No.:	PR-378
Prepared By:	Carlos Garcia
Approved By:	Peter Schmidt

Location: Plant 2B | Date: 2024-04-07

Below are the technical parameters and construction materials for the unit. All data entries are traceable to design revision history. Ensure all referenced standards are up to date. This data sheet provides key specifications and material details. Use this sheet to confirm engineering requirements and tolerances.

Unit Type	Cooling Circulation System	Rated Pressure	300 bar
Fluid Flow	75 L/min	Voltage	480 V / 60 Hz
Working Temp. Range	10°C to 55°C	Filtration	5 µm inline, 10 µm return
Mounting	Wall-mounted	Dimensions (LxWxH)	1000 x 650 x 1000 mm
Pump Type	Vane Pump	Protection Class	IP67
Frame Material	Stainless Steel Frame	Cooling	Air-cooled oil radiator
Reservoir Capacity	160 L	Control Valve	Directional 4/3
Oil Type	HLP 32	Motor Power	11 kW
Battery Capacity	2 Ah	Total Weight	250 kg

Document control numbers are included for traceability. Flag any missing parameters for urgent specification updates. Archive this summary for future design-change management. Material choices and process data have been verified for compliance. Refer to parameter table for operating ranges and tolerances. Use this summary to cross-check with BOM and inspection reports.

Material of Construction:

Label	Base
Graphite Pad	Graphite Pad
Wooden Pallet	Treated Pine Wood
Hex Bolts M12	Zinc-Plated Steel
Bearing 6202 ZZ	Stainless Steel 304
Cable Tie Pack (100)	Nitrile Rubber (NBR)
Battery Pack	Lithium-Ion Cell Pack
Rubber Gasket 80mm	Nitrile Rubber (NBR)
Nut M6	Zinc-Plated Steel
Cooling Gel Pack	Silicone Rubber
Capacitor 450V	Aluminum 6061-T6
Connector 2P	Glass-Filled Nylon
Thermal Fuse	Ceramic Oxide