

Unit Data Specification

Project:	XD-710R
Document No.:	PR-434
Prepared By:	Anna Nowak
Approved By:	Peter Schmidt

Location: Plant 1C | Date: 2024-08-02

Below are the technical parameters and construction materials for the unit. This technical overview supports the product-release checklist. The following information outlines performance characteristics and design data. This section details the configuration and parameter set for the product. Use this spec sheet to validate assembly instructions.

Configuration Type	Cooling Circulation System	Design Pressure	210 bar
Throughput	30 L/min	Voltage	400 V / 50 Hz
Battery Capacity	2 Ah	Reservoir Capacity	120 L
Motor Power	7.5 kW	Mounting	Skid base with vibration pads
Working Temp. Range	10°C to 55°C	Pump Type	Gear Pump
Frame Material	Aluminum Frame	Total Weight	250 kg
Control Valve	Proportional 4/2	Dimensions (LxWxH)	1000 x 650 x 1000 mm
Protection Class	IP67	Noise Level	≤ 72 dB(A)

Material of Construction:

Label	Raw Material
Insulated Tube 25mm	Thermoplastic Polyurethane (TPU)
Cooling Gel Pack	Silicone Rubber
O-Ring NBR 60mm	Nitrile Rubber (NBR)
Wiring Loom 1m	PVC (Rigid)
Battery Pack	Lithium-Ion Cell Pack
Graphite Pad	Graphite Pad
Thermal Fuse	Ceramic Oxide