

Unit Data Specification

Check that all material specs align with supplier certifications. This data sheet provides key specifications and material details. Use this sheet to confirm engineering requirements and tolerances. This report extract is prepared for design-verification audits. Please review the specifications and material composition listed below. Use this spec sheet to validate assembly instructions. Entries include both mechanical and electrical specifications.

Product ID:	LK-890B
Document No.:	4309083

Prepared by: Laura Rossi | Approved by: Peter Schmidt | Date: 2023-09-25

Model Type	Hydraulic Power Unit	Operating Pressure	300 bar
Throughput	30 L/min	Voltage	400 V / 50 Hz
Protection Class	IP65	Frame Material	Aluminum Frame
Pump Type	Vane Pump	Mounting	Wall-mounted
Service Interval	1000 h		

Ensure that the listed materials are approved for the application. Archive this summary for future design-change management. Check that all section headers follow the product template. Refer to parameter table for operating ranges and tolerances. All summary comments have been recorded in the revision log.

Material of Construction:

Label	Composition
Gasket Sheet A4	Nitrile Rubber (NBR)
Hex Bolts M12	Zinc-Plated Steel
LED Light Strip	Glass-Filled Nylon
Capacitor 450V	Aluminum 6061-T6
Insulated Tube 25mm	Thermoplastic Polyurethane (TPU)
Teflon Tape Roll	Teflon Tape Roll
Cooling Gel Pack	Silicone Rubber
Wiring Loom 1m	PVC (Rigid)