HOOX TRADING PLATFORM

END-USER WORKSPACE & CLIENT OPERATIONS MANUAL

Generated: 2026-05-19

Classification: Technical Documentation Spec

Design Style: Monospace Terminal Console layout

KV Key	Type	Default	Operational Impact
`trade:kill_switch`	`boolean`	`false`	Global emergency halt. If `true`, all executions halt.
`trade:max_daily_drawdown_percent`	`number`	`.`	Maximum daily loss before the AI Risk Manager triggers the kill switch.
`webhooks:api_key`	`string`	`your_key`	Public webhook passkey checked during signal ingestion.
`webhooks:queue_mode`	`string`	`queue_failover`	Routing behavior: `direct_only`, `queue_failover`, `queue_everywhere`.
`exchanges:default_routing`	`string`	`bybit`	Default CEX fallback router: `binance`, `bybit`, or `mexc`.
`routing:dynamic:enabled`	`boolean`	`false`	Enables/disables dynamically shifting routes based on symbols.
`email:scan_subject`	`string`	`TRADE`	Prefix required in signal email subjects.
`email:coin_pattern`	`string`	`(BTC|ETH)`	Regex expression used to extract asset tokens from email bodies.
`email:action_pattern`	`string`	`(BUY|SELL)`	Regex expression used to resolve buy/sell actions in email bodies.
`email:authorized_senders`	`array`	`[]`	List of email addresses authorized to submit trade signals.
`webhook:tradingview:ip_check`	`boolean`	`false`	Toggles dropping payloads that don't originate from TradingView IPs.

> Tip: You can sync, check, or reset this entire KV manifest in one command: `hoox config kv apply-manifest`!

NEXT STEPS

- [-Minute Quick Start Guide](quick-start.md) - Deploy all workers and fire your first simulated webhook.
- [API Endpoint Reference](api-endpoints.md) - Review full REST schemas, parameters, and error models.