

PROJECT REPORT
ON

**HYDROPONICS BASED PRECISION FARMING
WITH FEATURE OPTIMIZATION**

SUBMITTED BY

JANHAVI BHOR
VARAD CHASKAR
SAHAJ CHAUDHARI

Under the Guidance of
Mr. RAMGOPAL SAHU



DEPARTMENT OF ELECTRONICS & TELECOMMUNICATION
P.E.S'S MODERN COLLEGE OF ENGINEERING
PUNE – 411 005.



SAVITRIBAI PHULE PUNE UNIVERSITY
Academic Year: 2023-2024

CERTIFICATE

This is to certify that

JANHAVI JITENDRA BHOR

Exam No. B190313024

VARAD VINAYAK CHASKAR

Exam No. B190313028

SAHAJ SHEKHAR CHAUDHARI

Exam No. B190313030

of B.E. (E&TC) have successfully completed the project titled '**Hydroponics Based Precision Farming with Feature Optimization**' during the academic year 2023-2024. This report is submitted as partial fulfillment of the requirement of degree in E&TC Engineering as prescribed by Savitribai Phule Pune University.

Dr. Mrs. K. R. Joshi
Principal
P.E.S's MCOE, Pune-05.

Dr. Mrs. R. S. Kamathe
Vice Principal
H.O.D. (E&TC)

Mr. Ramgopal Sahu
Project Guide

ACKNOWLEDGEMENT

We would like to express our sincere appreciation to all the individuals who contributed to the success of our project "Hydroponics Based Precision Farming with Feature Optimization".

First and foremost, We would like to thank our project guide **Mr. Ramgopal Sahu** for his invaluable guidance and support in PCB design, enclosure design, component choices, and modifications. His expertise and experience played a crucial role in the successful implementation of our project. His suggestions on plant choices were also very helpful in achieving our goals. Furthermore, we would also like to extend our heartfelt thanks to **Mrs. Shreyasi Watve** for her brilliant ideas on the farm field and modifications in the report. Her contributions have greatly enhanced the quality of our project.

We would like to express our gratitude to our HOD **Dr. Mrs. R. S. Kamathe** for her constant support and encouragement throughout the project.

We would also like to express our gratitude to our principal **Dr. Mrs. K. R. Joshi** for provision of state-of-the-art infrastructure, access to necessary resources and college's commitment to fostering an environment that encourages innovation, creativity, and hands-on learning.

We would also like to thank the industry expert **Mr. Jayesh Ranjare** who provided valuable suggestions for this project. Their insights and knowledge have been immensely helpful in achieving our objectives.

Lastly, we would like to thank **Mr. Chandrakanth Bhode**, a certified fertilizer shop owner, for providing us with the best knowledge about fertilizer choices for hydroponics systems. His inputs were very valuable for the success of our project.

- Janhavi Bhor
- Varad Chaskar
- Sahaj Chaudhari

ABSTRACT

The world is changing rapidly, bringing both innovations and problems. As the population grows, land and water resources are shrinking. Conventional farming methods are becoming unsustainable due to climate change and harmful environment. Hydroponics offers an innovative solution that uses less space and water and produces more food with fewer chemicals than soil based farming. Furthermore, hydroponics can grow food in any location and season, providing fresh, local, and nutritious vegetables to consumers. The proposed system aims to enhance the hydroponics concept by not only automates crucial aspects of hydroponic systems such as water and nutrient supply but also incorporates features like machine learning algorithms, IoT, cloud computing, and image analysis and controlling environmental parameters in plant growth but also verifying whether the system functions as intended. The system is in product-ready form that may be used commercially or domestically.

LIST OF FIGURES

Sr. No.	Title of Figure	Page No.
1.	1.1 Concept of Hydroponics	2
2.	2.1 Automation by Growtronix	4
3.	2.2 Product by City Greens	5
4.	2.3 Hydroponics Market Size	6
5.	3.1 UPS Module (5V 2A)	8
6.	3.2 Sensor Module	9
7.	3.3 Actuator Module	9
8.	3.4 LED Violet Light Spectrum	10
9.	4.1 Block diagram of the project	11
10.	5.1.1 Schematic Circuit Design of the Sensor Module	14
11.	5.1.2 Side 3D View	14
12.	5.1.3 Elevated 3D View	14
13.	5.2.1 Schematic Circuit Diagram of Actuator Module	17
14.	5.2.2 Front 3D View	17
15.	5.2.3 Elevated 3D View	17
16.	5.2.4 Back Side 3D View	18
17.	5.2.5 Double Layer PCB Design	18
18.	5.2.6 Future Scope 3D View	18
19.	5.3.1 Schematic Circuit Diagram of UPS Module	20
20.	5.3.2 Front 3D View	20

21.	5.3.3 Elevated view 3D View	20
22.	5.4.1 Schematic Circuit Diagram of Camera Module	22
23.	5.4.2 3D View From Front	22
24.	5.4.3 3D View at an angle	22
25.	5.5 Matlab Emulation of the System	25
26.	5.6 3D Enclosure Design of the Sensor Module	26
27.	5.7 3D Enclosure Design of the Actuator Module	26
28.	5.8 2D Design of the Sensor Module	26
29.	5.9 3D Enclosure Design of the UPS Module	27
30.	5.10 3D Enclosure Design of the Stack	27
31.	5.11 2D Design of the Actuator Module	27
32.	5.12 3D Enclosure Design of the NetPot	28
33.	5.13 3D Enclosure Design of the Hydroponic Tank	28
34.	5.14 2D Design of the UPS Module	28
35.	5.15 2D Design of the Hydroponic Tank	29
36.	5.16 2D Design of the NetPot	29
37.	6.1 Flow Chart of the Sensor Module	30
38.	6.2 Flow Chart of the Actuator Module	31
39.	6.3 Cloud Architecture	32
40.	6.4 Power Optimization using Time Slotting	32
41.	6.5 Wireframe Design to Display the Sensor Data	35

42.	6.6 Wireframe Design to Control the Actuator	35
43.	6.7 Flow Chart of the Webpage/Application	36
44.	6.8 Steps to Train AI with Images	37
45.	7.1 Final Setup with Light OFF	41
46.	7.2 Final Setup with Light ON	41
47.	7.3 Screenshots taken while changing the Wi-Fi credentials	42
48.	7.4 Web Interface with Login and Password	43
49.	7.5 Web Interface to Control the Actuators	43
50.	7.6 Android App Icon	44
51.	7.7 Android App Interface	44
52.	7.8 Different with Nutrient Control	45
53.	7.9 Experiment Setup with different TDS on different pots	45
54.	7.10 Plant Height over Growth at Different TDS	45
55.	7.11 Output of Model v1	46
56.	7.12 Output of Model v2	46
57.	7.13 Plot Performance of AI Model	47
58.	7.14 Evaluation of AI Model	47
59.	7.15 Data Inferenced based on AI model	48
60.	7.16 Inference based of AI model	48
61.	7.17 Mung Bean Plant	49
62.	7.18 Wheat Plant	49
63.	7.19 Chickpea Plant	49
64.	7.20 Time Scheduling and React Control Web Interface	50

65.	7.21 Email Alert	51
66.	7.22 Data Exported from the Cloud in Excel	52
67.	7.23 Screenshot of the Simulation Done on Wokwi	52
68.	7.24: Indoor vs Outdoor effect : Based on Light	53
69.	7.25: Indoor vs Outdoor effect : Based on Water Consumption	54

LIST OF TABLES

Sr. No.	Title of Table	Page No.
1.	3.1 Input Specifications of the Actuator Module	7
2.	3.2 Output Specifications of the Actuator Module	7
3.	3.3 General Specifications of the Actuators	8
4.	3.4 Input Specifications of the Sensor Module	8
5.	3.5 General Specifications of the Sensor Module	9
6.	5.1 Specification of the Components	24
7.	6.1 Unit Testing of the Actuator Module	33
8.	6.2 Integration Testing of the Actuator Module	34
11.	6.3 Unit Testing of the Sensor Module	34
12.	6.4 Integration Testing of the Sensor Module	35
13.	7.1 PCB Design	38

TABLE OF CONTENTS

Sr. No.	Title of Chapter	Page No.
1.	Introduction	1 - 2
2.	Literature Survey	3 - 6
3.	Specification of the project	7 - 10
4.	Block Diagram & Description	11 - 12
5.	Hardware System Design	13 - 29
6.	Software System Design	30 - 37
7.	PCB Design (PCB Design & Layouts)	38 - 40
8.	Results and Performance Evaluation	41 - 54
9.	Applications & Future Modifications	55-56
10.	Applications	57
11.	Conclusion	58
12.	References	59-64
13.	Data Sheets. (Only for uncommon components)	

1. INTRODUCTION

With the world's population projected to reach 9.8 billion by 2050,^[1] the agriculture sector faces immense pressure to double its food production to meet this demand.^[2] Automation in agriculture becomes imperative due to several factors including the scarcity of arable land,^[3] fluctuating climate patterns, and the need for increased efficiency and productivity. By automating tasks such as planting, watering, harvesting, and monitoring crop health, we can optimize resource utilization, minimize waste, and enhance yields. Additionally, automation can mitigate the challenges posed by labor shortages^[4] and provide opportunities for more sustainable farming practices, ensuring food security for the growing global population while conserving natural resources for future generations.^[5]

1.1 Need for Hydroponics

Indoor hydroponics presents numerous advantages over traditional soil farming methods, particularly in the context of addressing the challenges posed by limited land availability, water scarcity, and climate variability. Hydroponic systems enable cultivation in controlled environments, allowing for year-round production regardless of external conditions. By providing precise control over nutrient delivery and environmental factors such as temperature, humidity, and light, hydroponics maximizes resource efficiency, minimizes water usage, and reduces the reliance on harmful pesticides and fertilizers. Furthermore, indoor hydroponic setups can be tailored to fit various spatial constraints, making them suitable for urban areas and regions with limited arable land, ultimately offering a sustainable and scalable solution to meet the growing global demand for fresh produce.^[6]

1.2 What is Hydroponics

Hydroponics is a method of growing plants without soil, where plants receive essential nutrients dissolved in water. This soilless cultivation technique utilizes various systems such as nutrient film technique (NFT), deep water culture (DWC), or aeroponics, allowing for precise control over nutrient levels, pH, and environmental conditions. Hydroponics can be used in diverse

applications, including commercial agriculture for growing vegetables, fruits, and herbs in controlled environments, urban farming to maximize space efficiency and enable year-round production, research institutions for studying plant biology and optimizing growth conditions, as well as in areas with poor soil quality or limited access to arable land, providing a sustainable solution for food production.^[7]

1.3 Automating Hydroponics

Automation of hydroponics using technology involves integrating sensors, actuators, and control systems to monitor and regulate key parameters such as nutrient levels, pH, temperature, humidity, and lighting. This can be achieved through the use of IoT (Internet of Things) devices and smart controllers that gather real-time data from the hydroponic system and adjust environmental conditions accordingly. Automated nutrient dosing systems ensure precise delivery of nutrients to plants, while automated irrigation systems maintain optimal moisture levels. Additionally, automated lighting systems can mimic natural sunlight cycles to promote healthy plant growth. By automating these processes, technology streamlines hydroponic operations, increases efficiency, minimizes labor requirements, and enables remote monitoring and management, ultimately enhancing crop yields and sustainability.^[8]




Fig. 1.1: Concept of Hydroponics

Source: <https://www.greenlivingoffgrid.com/hydroponic-gardens-pros-and-cons>

2. LITERATURE SURVEY

2.1 Literature Survey of the Reference Papers

“Nutrient Film Technique (NFT) Hydroponic Monitoring System Based on Wireless Sensor Network,” by Helmy, Marsha Gresia Mahaidayu, Arif Nursyahid, Thomas Agung Setyawan, Abu Hasan (2017), highlights urban development challenges such as agricultural land conversion, prompting interest in hydroponic cultivation. Hydroponics replaces soil with water, nutrients, and oxygen, crucially defining success in techniques like Nutrient Film Technique (NFT).

“A Controlled Environment Agriculture with Hydroponics: Variants, Parameters, Methodologies and Challenges for Smart Farming,” Srivani P, Yamuna Devi C and Manjula S H (2019), discusses urbanization, food scarcity, and climate unpredictability, advocating hydroponics as a sustainable alternative. It enables precision agriculture, conserves resources, and supports urban farming while avoiding pesticides and GMOs.

“Technological Influences on Monitoring and Automation of the Hydroponics System,” by Geetali Saha (2021), explores hydroponics' components and challenges. It emphasizes the need for comprehensive data collection, automated control systems, and interfaces to mitigate weather disruptions and power failures. The study aims to advance hydroponic technology in addressing land scarcity and climate change impacts on traditional farming.

2.2 Brief Findings From Research Literature

- New technologies are currently under research and development, particularly in areas such as nutrient composition, supply mechanisms, growth mediums, and the impact of environmental factors such as light, temperature, humidity, and pH levels. These factors have demonstrated a direct correlation with plant growth outcomes.

- Despite longstanding discussions about the integration of automation and AI in hydroponics, much of the progress has been confined to simulated environments, whether physical or virtual, typically facilitated through platforms like MATLAB. While AI models have been constructed based on real-life data, their practical application in agricultural settings remains largely unexplored.
- The majority of research efforts in this field have failed to employ methodologies conducive to transforming AI and automation into viable products capable of demonstrating efficiency and effectiveness beyond mere plant growth optimization. Our focus is on bridging this gap by implementing research techniques aimed at showcasing the practical benefits of these technologies in real-world farming scenarios.

2.3 Literature Survey Of Similar Products Available In The Market

2.3.1 Automation kit by Growtronix

The Hydroponic Automation Kit by Growtronix and the Hydroponic Starter Kit by General Hydroponics are two comparable products on the market. Growtronix offers a comprehensive automation solution, including temperature/humidity sensors and nutrient dosing systems. In contrast, General Hydroponics provides a simpler kit featuring a water pump, air pump, and air stone for use with a 5-gallon bucket.



Fig. 2.1: Automation by Growtronix

Source: growtronix.com/cart/blog/how-growtronix-works-n5

2.3.2 City Greens

City greens provide low-cost hydroponic solutions for farmers who are on budget and would like to grow seasonal and local crops, but at the same time enjoy higher yields and improved profits as compared to what is possible in traditional farming. They are currently serving 18+ states right now. They provide setup, support, and automation to farming systems.



Fig. 2.2: Product by City Greens

Source: <https://www.citygreens.shop/Images/202211/1080x1080/Kits.webp>

2.4 Comparison With Various Technologies Available

Hydroponic systems offer advantages over traditional soil-based farming, including higher crop yields and reduced water usage, with automation further boosting efficiency. Various technologies exist for hydroponic automation, each with its own advantages and drawbacks.

Automated dosing systems ensure precise nutrient delivery but can be costly and require regular maintenance, while simpler timer-based systems with water pumps may be more affordable but lack precision. Notably, there's no existing system that simultaneously operates UV lights, fans, air pumps, and water pumps, nor the technology to verify their functionality, making this system distinctive in its approach.

2.5 Market Survey



Fig. 2.3: Hydroponics Market Size

Source: <https://www.mordorintelligence.com/industry-reports/hydroponics-market>

- The Hydroponics Market is projected to grow from USD 4.69 billion in 2023 to USD 6.83 billion by 2028, with a CAGR of 7.80% during 2023-2028. North America leads the market, while Asia Pacific shows the fastest growth [4].
- Rapid growth is expected, driven by increased adoption in Australia, Japan, India, and China [5].
- The global market is fragmented, with many companies focusing on R&D to develop advanced techniques for sustainability and cost reduction [6].
- In March 2021, Ahmedabad's state government announced plans to promote hydroponic farming in cities, offering hands-on training and DIY videos to encourage household vegetable cultivation.
- Key players in the hydroponics market include Argus Control Systems Ltd. (Canada), Signify Holding B.V. (Netherlands), The Scotts Miracle-Gro Company (U.S.), and others.

3. SPECIFICATIONS

3.1 Actuator Module Features

- Operates LED violet light using 2 PC817 optoisolators.
- Controls up to 4 motors with adjustable speed using 2 L293D motor drivers.
- Integrates Wemos D1 mini microcontroller for WiFi connectivity.
- Allows system operation through web and app interfaces.
- Operates on 5V power supply.

3.2 Actuator Module Input Specifications

Parameter	Description
Power Supply Voltage	5V
Control Signal	Logic High (3.3V), Logic Low (0V)
Motor Speed Control	Adjustable via PWM signal (0-255)
Communication	WiFi connectivity

Table 3.1: Input Specifications of the Actuator Module

3.3 Actuator Output Specifications

Parameter	Description
LED Voltage	Collector Current: 50 mA, C-E Voltage: max. 35V
Motor Voltage	Up to 5V, Peak Output Current: 600mA, Continuous Output Current: 200mA
Motor Control	Speed control (adjustable PWM)

Table 3.2: Output Specifications of the Actuator Module

3.4 Actuator Module Status/Control

- Status Indication: LED status indicator.
- Control Interface: Web and app-based control through WiFi.
- Motor Activation: Controlled via microcontroller logic.

3.5 Actuator General Specifications

Parameter	Description
Microcontroller	Wemos D1 mini
Optocoupler	PC817
Motor Driver	L293D
Communication Protocol	WiFi (802.11 b/g/n)
Operating Voltage	5V
Dimensions	7cm x 8cm x 2.5cm
Operating Temperature	-40°C to 85°C

Table 3.3: General Specifications of the Actuators




Fig. 3.1: UPS Module (5V 2A)

3.6 Sensor Module Features

- Monitors temperature and humidity using DHT11 sensor.
- Detects light status using an LDR (Light Dependent Resistor).
- Monitors water level depth using a water level sensor.
- Integrates Wemos D1 mini microcontroller for WiFi connectivity.
- Sends data to the cloud through WiFi.

3.7 Sensor Module Input Specifications

Parameter	Description
Power Supply Voltage	5V
Communication	WiFi connectivity
Temperature Range	0°C to 50°C (DHT11 sensor)
Humidity Range	20% to 90% RH (DHT11 sensor)
Light Detection	Analog Voltage Output (LDR)
Water Level Depth	Analog Voltage Output (Water level sensor)

Table 3.4: Input Specifications of the Sensor Module

3.8 Sensor Module Status/Control

- Status Indication: LED status indicators for sensor readings.
- Control Interface: WiFi for data transmission to the cloud.
- Data Transmission: Periodic updates to cloud server.




Fig. 3.2: Sensor Module




Fig. 3.3: Actuator Module

3.9 General Specifications

Parameter	Description
Microcontroller	Wemos D1 mini
Temperature/ Humidity Sensor	DHT11
Light Sensor	LDR (Light Dependent Resistor)
Water Level Sensor	Analog Water Level Sensor
Communication Protocol	WiFi (802.11 b/g/n)
Operating Voltage	5V
Dimensions	7 cm x 8 cm x 2.5 cm
Operating Temperature	-40°C to 85°C

Table 3.5: General Specifications of the Sensor Module

3.10 External system specification

3.10.1 LED Violet light

- Type: USB
- Adjustable intensity
- Adjustable color (red, blue, violet)
- Voltage at Max. Brightness: 5V, DC
- Current at Max. Brightness: 1.45A

3.10.2 Air pump

- Type: USB
- Voltage consumption: 5 – 5.1V, DC
- Current consumption: 0.15A

3.10.3 Fan

- Type: USB
- Voltage consumption at maximum speed: 5V, DC
- Current consumption at maximum speed: 0.91A

3.10.4 Water pump

- Voltage consumption: 5V
- Current consumption: 0.31A

3.11 Camera: ESP32

- FPC connector.
- Support for OV2640 (sold with a board) or OV7670 cameras.
- Image Format: JPEG(OV2640 support only), BMP, grayscale.
- Built-in LED flashlight.
- Temperature Range: Operating: -20 °C ~ 85 °C
- Power Supply: 5V via pin header.
- External Storage: micro SD card slot up to 4GB.




Fig. 3.4: LED Violet Light Spectrum

Source: <https://www.amazon.com/dp/B07312WKX2>

4. BLOCK DIAGRAM AND DESCRIPTION

4.1 Block Diagram




Fig. 4.1: Block Diagram of the System

4.2 Description of the block diagram

4.2.1 Sensors Block

- **Water Level Sensor:** Measures the water level in the hydroponic system to ensure it remains within the desired range and expected setup.
- **Temperature Sensor:** Monitors the temperature within the hydroponic environment for optimal plant growth. And measures the humidity levels to maintain an ideal atmosphere for plant growth.
- **LDR (Light Dependent Resistor):** Checks the light status to determine if additional artificial light is needed.

4.2.2 Controller Block

Wemos D1 mini Microcontroller: It is a compact and cost-effective WiFi module based on the ESP8266 microcontroller, enabling wireless connectivity for IoT and embedded systems.

4.2.3 IoT & Cloud Block

IoT Protocols of Communication: Enables communication with external networks or devices, allowing remote monitoring and control. MQTT and HTTP protocols are used to send and receive the data through the cloud.

4.2.4 Web/App Block

Smartphone/Web UI: Provides a user-friendly interface on a mobile app or web application for users to monitor and control the hydroponics system remotely.

4.2.5 Actuator Block

- **LED Light:** Controls the artificial lighting system to supplement natural light as needed.
- **Fan:** Regulates ventilation and air circulation within the hydroponic environment.
- **Air Pump:** Manages aeration of the nutrient solution for plant roots.
- **Water Pump:** Controls the flow of nutrient-rich water to the plant roots.

4.2.6 Camera Block

ESP32-CAM: It is a compact, Wi-Fi and Bluetooth-enabled module with a built-in camera, suitable for various IoT and image-capture applications.

4.2.7 Power Supply Block

The system requires 5V 2A power supply which we can get using mobile adapters or USB ports.

5. HARDWARE SYSTEM DESIGN

5.1 Sensor Module

5.1.1 Introduction

The primary objective of our Sensor Module is to offer a comprehensive solution for real-time monitoring of key environmental parameters within hydroponics setups. By integrating multiple sensors within a compact enclosure, our module aims to streamline data acquisition while ensuring accuracy and reliability. Through seamless connectivity to the internet, the module facilitates remote access, empowering users to manage their hydroponics systems with unprecedented convenience and effectiveness.

The Sensor Module boasts a versatile array of sensors meticulously chosen to capture vital environmental data essential for hydroponics cultivation. At its core, the module is equipped with a Wemos D1 Mini microcontroller, which serves as the central processing unit for sensor interfacing and data transmission. Sensors include DHT11 which precisely measures ambient temperature and humidity levels, LDR Sensor enables the module to detect variations in ambient light levels. In the event of insufficient light, the module triggers automated light activation to supplement natural lighting, promoting healthy plant growth round the clock, Water-level sensor offers real-time monitoring of the water level within the hydroponics tank

Upon deployment, the Sensor Module continuously gathers data from the connected sensors, leveraging the capabilities of the Wemos D1 Mini to process and transmit this information to a designated web interface. Through seamless integration with our website, users gain instant access to real-time sensor readings, historical data analysis, and remote control functionalities. Furthermore, the module's compatibility with mobile applications enhances accessibility, allowing users to monitor and manage their hydroponics systems remotely via smartphones or tablets.

5.1.2 Schematic Circuit Diagram of Sensor Module




Fig.5.1.1 Schematic Circuit Diagram of Sensor Module

5.1.3 3D Model Design of Sensor Module




Fig . 5.1.2: Slide 3D View




Fig 5.1.3: Elevated 3D View

5.2 Actuator Module

5.2.1 Introduction

The Actuator Module acts as the hub of our control system, much like the heart of the operation. It connects seamlessly with the Sensor Module and takes commands from our website or mobile app. Its primary function is to ensure smooth functioning of all components within the hydroponics setup and adjust as necessary. Our Actuator Module is designed to be incredibly intelligent. It can regulate various aspects of the hydroponics system to maintain optimal conditions for plant growth. We've made it user-friendly so that individuals can easily manage their hydroponic gardens from anywhere, at any time. It's highly responsive too – capable of swiftly adapting to changes in the environment, ensuring that plants receive precisely what they need to thrive. Ultimately, it's all about simplifying and enhancing the process of growing plants for everyone involved.

The Actuator Module is designed with a sturdy framework, focusing on the Wemos D1 Mini microcontroller as its core component, serving as the central processor of the entire system. It efficiently coordinates the signals required to operate various actuators, responding to inputs received from either the website or mobile application. The control mechanisms for these actuators are carefully managed to ensure optimal performance within the hydroponics setup.

One of the primary functions of the Actuator Module is the regulation of airflow, crucial for maintaining a conducive environment for hydroponic growth. This is achieved through precise control facilitated by the L293D motor driver chip. By integrating data from the DHT11 sensor, the module can accurately adjust fan speeds, ensuring the ideal airflow conditions required for plant cultivation.

Additionally, the Actuator Module oversees the operation of the water pump, essential for maintaining adequate circulation within the hydroponic system. Utilizing the control capabilities of the L293D chip, it ensures a consistent flow of water to nourish the plants effectively.

Furthermore, the module controls the air pump, vital for oxygenation within the hydroponic environment. Employing the I293d chip, it regulates the air pump to sustain optimal levels of oxygen required for healthy plant growth.

Moreover, the Actuator Module facilitates precise management of lighting systems. Through the integration of optocouplers, it enables seamless control over the on/off switching and intensity adjustment of the lights. This functionality is augmented by the Sensor Module, which detects ambient light levels to adjust the lighting settings accordingly, ensuring an optimal growth environment for the plants.

Modes of Operation:

Our Actuator Module offers three distinct modes of operation:

1. Schedule Mode: In this mode, users can pre-program specific schedules for activating and deactivating various components such as fans, air pumps, water pumps, and lighting systems. These schedules can be based on time intervals or specific events, allowing for precise control over the hydroponics environment without constant manual intervention.
2. Manual Mode: Manual mode provides users with direct control over individual components via the website or mobile application. Users can toggle the operation of fans, air pumps, water pumps, and lighting systems on or off as needed, providing flexibility for immediate adjustments based on real-time observations or preferences.
3. Automated Mode: Automated mode leverages data collected by the Sensor Module to dynamically adjust control settings in response to environmental conditions. For example, fan speed may be automatically adjusted based on temperature readings from the DHT11 sensor, or lighting intensity may be modulated in response to ambient light levels detected by the LDR sensor. This mode optimizes plant growth by ensuring that environmental parameters are continuously monitored and adjusted to maintain ideal conditions.

5.2.2 Schematic Circuit Diagram of Actuator Module




Fig. 5.2.1 Schematic Circuit Diagram of Actuator Module

5.2.3 3D Model Design of Actuator Module




Fig 5.2.2 Front 3D View




Fig 5.2.3 Elevated 3D View




Fig 5.2.4 Back Side 3D View

5.2.4 Future scope of Actuator Module




Fig. 5.2.5 Double Layer PCB Design




Fig 5.2.6 Future Scope 3D View

5.3 UPS Module

5.3.1 Introduction

The primary objective of our UPS system is to provide uninterrupted power delivery to essential applications, thereby minimizing the risk of data loss, hardware damage, and operational disruptions caused by power outages or fluctuations. By seamlessly transitioning between primary and backup power sources, our system aims to uphold the reliability and integrity of electronic devices, empowering users to maintain productivity and efficiency even in adverse power conditions.

Our UPS system features a sophisticated architecture centered around an electro-mechanical relay, meticulously configured to facilitate seamless power transitions between primary and backup power sources.

We have also designed an ups system which works with an electro-mechanical relay, now you have two power supplies (main and backup) and output to application works like this ground for all is kept same, what goes to VCC of application in com port of relay, in is GND from the main supply, while VCC to replay is also ground, while ground of the relay is attach to VCC of main supply, while VCC of back up is connected to NO port of relay, now really works on active low, so per above connections it's on when main is on, but we attached VCC and ground in reverse to main, at other end of the relay com ports gives power to application, if main is off the theres is connection between com and NO but since back VCC was given to No which is now connected to com which supplies uninterrupted to application our UPS system represents a reliable and effective solution for mitigating the risks associated with power interruptions and fluctuations. By leveraging innovative relay technology and seamless power switching mechanisms, our system offers unparalleled peace of mind, ensuring the continuous operation of critical applications in any power condition.

5.3.2 Schematic Circuit Diagram of UPS Module




Fig. 5.3.1 Schematic Circuit Diagram of UPS Module

5.3.3 3D Model Design of UPS Module




Fig. 5.3.2 Front 3D View




Fig. 5.3.3 Elevated view 3D View

5.4 Camera Module

5.4.1 Introduction

The primary objective of our project is to develop a robust platform for plant monitoring and management. This platform leverages the ESP32-CAM module's capabilities to empower growers with a comprehensive understanding of their crops.

The ESP32-CAM module integrates a camera and microcontroller, enabling the system to collect vital data for plant health assessment. It can accurately measure plant height, a crucial indicator of growth. By analyzing this data, the platform can provide actionable recommendations for fertilizer application, ensuring optimal plant growth and efficient resource utilization. Our project envisions exploring advanced features like plant disease detection in future.

Traditionally, plant monitoring and management have relied on manual methods, which are labor-intensive, time-consuming, and prone to human error. Our project seeks to revolutionize these practices by leveraging the power of automation. By automating data collection and analysis, the platform removes human bias and ensures consistent monitoring.

The ESP32-CAM module acts as the central hub, collecting data from sensors and the camera. This data can be processed locally on the module or transmitted to a centralized server for in-depth analysis. Through seamless integration with user-friendly web interfaces or mobile applications, the platform empowers growers with real-time insights into their crops' health. Users can receive actionable recommendations for adjustments, such as irrigation or temperature control, directly on their mobile devices. This remote management capability allows growers to monitor their crops and make informed decisions from anywhere, at any time.

By implementing this robust plant monitoring and management platform, we aim to empower farmers and growers with the tools they need to optimize crop growth, minimize losses, and achieve sustainable agricultural practices.

5.4.2 Schematic Circuit Diagram of Camera Module




Fig. 5.4.1 Schematic Circuit Diagram of Camera Module

5.4.3 3D Model Design of Camera Module




Fig. 5.4.2: 3D View From Front







Fig. 5.4.3: 3D View at an angle

5.5 Specifications of the Components

<p>Wemos D1 mini</p> <p>Microcontroller: ESP8266EX Operating Voltage: 3.3V Digital I/O Pins: 11 (can be used as GPIO, PWM, I2C, and more) Analog Input Pins: 1 (3.2V max) Flash Memory: 4 MB Wi-Fi: 802.11 b/g/n (2.4 GHz) USB-to-Serial Converter: CH340G Built-in LED: GPIO 2 Reset Button: Yes Temperature Range: -40°C to +125°C Dimensions: 34.2mm x 25.6mm</p>	
<p>L293D Motor Driver</p> <p>Motor Supply Voltage (VS): 4.5V to 36V Logic Supply Voltage (VSS): 4.5V to 7V Output Current (per channel): 600 mA (1.2A peak for short durations) Total Output Current (all channels combined): 1.2A (2.4A peak) Number of Channels: 4 (two H-bridges) Enable/Disable Feature: Yes (enable pin for each H-bridge) Operating Temperature Range: 0°C to 70°C</p>	
<p>DHT11 Sensor</p> <p>Operating Voltage: 3.3V to 5.5V Temperature Range: 0°C to 50°C Temperature Accuracy: ±2°C Humidity Range: 20% to 80% Humidity Accuracy: ±5% Communication Protocol: Single-wire digital signal Response Time: 2 seconds Calibration: Factory calibrated Low Power Consumption: 0.5 mA (average) Dimensions: 15.5mm x 12mm x 5.5mm</p>	

ESP 32- CAM

Microcontroller: ESP32-S Module (Dual-core Tensilica LX6 microprocessor)

Operating Voltage: 5V

Flash Memory: 4 MB

Camera: OV2640 (2 Megapixels)

Wi-Fi: 802.11 b/g/n (2.4 GHz)

Bluetooth: Bluetooth v4.2 BR/EDR and BLE


Digital I/O Pins: 10 (can be used as GPIO, PWM, I2C, etc.)

UART/I2C/SPI Interfaces: Yes

USB-to-Serial Converter: CP2102

Operating Temperature Range: -40°C to +125°C

Dimensions: Approximately 27mm x 40.5mm



PC 817 Opto-Isolator

Isolation Voltage: 5000Vrms (minimum)

Collector-Emitter Breakdown Voltage (VCEO): 80V (minimum)

Collector Current (IC): 50mA (continuous)

Collector Current (IC): 150mA (peak, 10% duty cycle)


Emitter-Collector Breakdown Voltage (VECO): 7V (maximum)

Forward Current (IF): 60mA (maximum)

Power Dissipation (PD): 150mW (total package)

Operating Temperature Range: -55°C to +110°C

Package Type: DIP-4 (Dual In-line Package with 4 pins)



Light Dependent Resistor

Dark Resistance (R_dark): 1 M ohm

Light Resistance (R_light): 10 k ohms

Sensitivity: 100 ohms per lux

Spectral Response: 400 nm to 700 nm (visible light range)

Operating Temperature Range: -40°C to +70°C

Response Time: 20 milliseconds (typical)



Table 5.1: Specification of the Components

5.6 MATLAB Emulation ()




Fig. 5.5: Matlab Emulation of the System

5.7 Enclosure Designs




Fig. 5.6: 3D Enclosure Design of the Sensor Module




Fig. 5.7: 3D Enclosure Design of the Actuator Module




Fig. 5.8: 2D Design of the Sensor Module



Fig. 5.9: 3D EnclosureDesign of the UPS Module




Fig. 5.10: 3D EnclosureDesign of the Stack




Fig. 5.11: 2D Design of the Actuator Module



Fig. 5.12: 3D Enclosure Design of the NetPot




Fig. 5.13: 3D Enclosure Design of the Hydroponic Tank




Fig. 5.14: 2D Design of the UPS Module




Fig. 5.15: 2D Design of the Hydroponic Tank




Fig. 5.16: 2D Design of the NetPot

6. SOFTWARE SYSTEM DESIGN

6.1 Flowchart of the Sensor Module




Fig. 6.1: Flowchart of the Sensor Module

6.2 Flowchart of the Actuator Module




Fig. 6.2: Flowchart of the Actuator Module

6.3 Cloud Architecture




Fig. 6.3: Cloud Architecture

6.4 Power Optimization using Time Slotting




Fig. 6.4: Power Optimization using Time Slotting

6.5 Unit & Integration Testing

6.5.1 Unit Testing of the Actuator Module

Test Case	Description	Expected Result	Actual Result	Pass/Fail
1	Verify WiFiManager setup	WiFiManager initializes successfully	Initialization successful	Pass
2	Check the initialization of ThingSpeak	ThingSpeak client initialized without errors	Initialization without errors	Pass
3	Test WiFi connection	Successfully connect to the WiFi network	Connected to WiFi	Pass
4	Verify GPIO pin modes	Ensure correct initialization of GPIO pins	GPIO pins initialized correctly	Pass
5	Check LED control logic	Validate the control logic for LEDs based on ThingSpeak data	LED control logic functioning as expected	Pass

Table 6.1: Unit Testing of the Actuator Module

6.5.2 Integration Testing of the Actuator Module

Test Case	Description	Expected Result	Actual Result	Pass/Fail
1	Verify end-to-end functionality	Actuator Module successfully connects to WiFi, reads ThingSpeak data, and controls actuators accordingly	All steps completed successfully	Pass
2	Test error handling	Simulate WiFi connection failure and ensure proper error handling and recovery	WiFi connection failure handled, and recovery successful	Pass
3	Check for correct ThingSpeak integration	Confirm that the Actuator Module reads data from the specified ThingSpeak fields and performs as expected	Data read from ThingSpeak and actuators controlled correctly	Pass

4	Validate actuation scenarios	Test various scenarios for actuation based on different values of ThingSpeak fields	Actuators respond appropriately to different scenarios	Pass
5	Test restart functionality	Verify that the Actuator Module restarts if WiFi connection issues persist	Module restarts when WiFi connection issues persist	Pass

Table 6.2: Integration Testing of the Actuator Module

6.5.3 Unit Testing of the Sensor Module

Test Case	Description	Expected Result	Actual Result	Pass/Fail
UT-001	Verify successful initialization of WiFiManager	WiFiManager connects successfully to WiFi	Connected to WiFi	Pass
UT-002	Check DHT sensor initialization	DHT sensor is initialized without errors	Sensor initialized without errors	Pass
UT-003	Read temperature from DHT sensor	Temperature reading within expected range	25.5°C	Pass
UT-004	Read humidity from DHT sensor	Humidity reading within expected range	55%	Pass
UT-005	Read analog input from LDR	Analog value is read successfully	450	Pass
UT-006	Read the water level from ThingSpeak	Water level reading retrieved successfully	1	Pass
UT-007	Write temperature data to ThingSpeak	Temperature data successfully written to ThingSpeak	Data written successfully	Pass
UT-008	Write humidity data to ThingSpeak	Humidity data successfully written to ThingSpeak	Data written successfully	Pass
UT-009	Write LDR value to ThingSpeak	LDR value successfully written to ThingSpeak	Data written successfully	Pass
UT-010	Write water level data to ThingSpeak	Water level data successfully written to ThingSpeak	Data written successfully	Pass

Table 6.3: Unit Testing of the Sensor Module

6.5.4 Integration Testing of the Sensor Module

Test Case	Description	Expected Result	Actual Result	Pass/Fail
IT-001	Ensure WiFi connection and ThingSpeak initialization	WiFi connection and ThingSpeak initialization successful	Connected to WiFi and ThingSpeak initialized successfully	Pass
IT-002	Verify seamless data transmission to ThingSpeak	Data is transmitted to ThingSpeak without errors	Data transmitted without errors	Pass
IT-003	Check correct execution of loop() function	Loop function executes without errors	Loop function executed successfully	Pass

Table 6.4: Integration Testing of the Sensor Module

6.6 Wireframe



Fig. 6.5: Wireframe Design to Display the Sensor Data




Fig. 6.6: Wireframe Design to Control the Actuators

6.7 Flowchart of the Webpage/Application




Fig. 6.7: Flowchart of the Webpage/Application

6.8 Steps to Train AI with Images




Fig. 6.8: Steps to Train AI with Images

7. PCB DESIGN









Sensor Module 	
Actuator Module 	
UPS Module 	
Camera Module 	

Table 7.1 PCB Design

7.2. PCB Material Cross Section as Per Design


ID	Name	Type	Material	Thickness	Dielectric	Power Plane
TR	Top Resist	Surface	Resist	10um	3.50	
TOP	Top Copper	Plane	Copper	35um		
		Core	FR2	1.55mm	4.80	
BOT	Bottom Copper	Signal	Copper	2mm		
BR	Bottom Resist	Surface	Resist	10um	3.50	

Stackup Wizard

Create Power Plane

Total Thickness: 3.605mm

Slot Layer: Mech 1



7.3 PCB Calculations

This Javascript web calculator calculates the trace width for printed circuit board conductors for a given current using formulas from IPC-2221 (formerly IPC-D-275).

Inputs:

Current	2	Amps
Thickness	2	mm <input type="button" value="inch"/>

Optional Inputs:

Temperature Rise	10	Deg <input type="button" value="C"/>
Ambient Temperature	30	Deg <input type="button" value="C"/>
Trace Length	2	inch <input type="button" value="mm"/>

Results for Internal Layers:

Required Trace Width	0.0356	mm <input type="button" value="inch"/>
Resistance	0.0128	Ohms
Voltage Drop	0.0257	Volts
Power Loss	0.0514	Watts

Results for External Layers in Air:

Required Trace Width	0.538	mil <input type="button" value="mm"/>
Resistance	0.0334	Ohms
Voltage Drop	0.0668	Volts
Power Loss	0.134	Watts

Notes:

The trace width is calculated as follows:

First, the Area is calculated:

$$\text{Area}[\text{mils}^2] = (\text{Current}[\text{Amps}] / (k * (\text{Temp_Rise}[\text{deg. C}])^b))^{(1/c)}$$

Then, the Width is calculated:

$$\text{Width}[\text{mils}] = \text{Area}[\text{mils}^2] / (\text{Thickness}[\text{oz}] * 1.378[\text{mils/oz}])$$

For IPC-2221 internal layers: k = 0.024, b = 0.44, c = 0.725

For IPC-2221 external layers: k = 0.048, b = 0.44, c = 0.725

where k, b, and c are constants resulting from curve fitting to the IPC-2221 curves

We find the fabrication thickness to exceed within limit the requirement for current capacity of PCB.

8. RESULT & PERFORMANCE EVALUATION

8.1 Final Setup



Fig 8.1: Final Setup with Lights OFF



Fig 8.2: Final Setup with Lights ON

The two-stack hydroponic automation system integrates LED violet lights, an air pump, a water pump, and a fan, all managed by sensor and actuator modules alongside a UPS module for uninterrupted power supply. This setup optimizes plant growth by providing consistent light, proper aeration, and hydration. Additionally, a time schedule control feature schedules the activation of UV lights and the air pump according to preset timings.

The sensor module regulates environmental conditions, while the actuator module adjusts settings accordingly, ensuring optimal growth conditions. A UPS module guarantees continuous operation, safeguarding against power interruptions. A photo of the system reveals thriving plants on the 22nd day after sowing seeds, highlighting the effectiveness of the automated hydroponic setup in nurturing plant growth.

8.2 Wi-Fi Credentials Change




Fig. 8.3: Screenshots taken while changing the Wi-Fi credentials

This hydroponic automation system offers the flexibility of configuring Wi-Fi credentials for both sensor and actuator modules, akin to setting up new products from the market. Employing softAP technology, the system enables seamless integration into existing Wi-Fi networks. Screenshots detailing the process of changing credentials are provided, showcasing the user-friendly interface.

The implementation utilizes the Wi-Fi manager library, streamlining the configuration process. This feature enhances accessibility and adaptability, allowing users to easily connect the automation system to their preferred Wi-Fi networks with minimal hassle.

8.3 Web Interface




Fig. 8.4: Web Interface with Login and Password




Fig 8.5: Web Interface to Control the Actuators

8.4 App interface




Fig. 8.6: Android App Icon




Fig. 8.7: Android App Interface

The web and app interface screenshots depict a user-friendly control panel for managing the hydroponic automation system. Notably, a key feature ensures that any data modification made through either the web or app interface is promptly updated in the cloud, thereby synchronizing data across all connected devices in real-time. This seamless integration enables users to monitor and adjust settings remotely from anywhere in the world.

Whether it's adjusting light intensity, or monitoring environmental conditions, users can efficiently control the system's operations with ease and convenience, fostering optimal plant growth regardless of location.

8.5 TDS Research



**Fig. 8.8: Difference with
nutrient control**



**Fig. 8.9: Experiment Setup with Different TDS
on different pots**




Fig. 8.10: Plant Height over Growth at Different TDS

The experiment showed that small plants thrive with low TDS levels, while medium-sized ones grow best with around 400 TDS for optimal growth. At the harvest stage, plants need about 800 TDS for faster growth, neither too high nor too low. This TDS consists of one-third each of nitrogen (N), phosphorus (P), and potassium (K) for balanced nutrition and healthy development.

8.6 TDS Recommendation using Camera




Fig. 8.11: Output of Model v1




Fig. 8.12: Output of Model v2

The Hydroponic Automation system integrates a camera module to capture images of the plants within the system, sending them to a local web server for analysis. Using advanced algorithms, the system accurately predicts the Total Dissolved Solids (TDS) required for optimal plant growth based on the height of the plants. On accessing the webpage, users are presented with a clear indication of the TDS needed – whether it's 200 TDS, 400 TDS, 600 TDS, or 800 TDS. Alongside each TDS value is a measure of prediction accuracy, displayed on a scale from 0 to 1, allowing users to gauge the reliability of the system's recommendation. With this seamless integration of imaging technology and predictive analytics, users can effortlessly maintain the ideal nutrient balance for their hydroponic setup, ensuring healthy and thriving plant growth.

By leveraging the camera module and predictive capabilities, the Hydroponic Automation system revolutionizes the way growers manage their hydroponic environments. With just a glance at the webpage, users can make informed decisions about adjusting TDS levels and enhancing efficiency and productivity in their cultivation process. The simplicity and accuracy of the system empower growers of all levels to achieve optimal results, fostering a more sustainable and efficient approach to hydroponic farming. With real-time insights at their fingertips, users can confidently nurture their plants, knowing they are providing the precise nutrients needed for vibrant and robust growth, ultimately maximizing yield and quality.




Fig. 8.13: Plot Performance of AI model




Fig. 8.14: Evaluation of AI model

Data for all images:

	Image Name	Max Height (inches)	Recommended TDS (ppm)
0	feb24 (1).jpg	10.609076	800
1	feb24 (2).jpg	9.899043	800
2	feb24 (3).jpg	10.817916	800
3	feb24 (4).jpg	10.270893	800
4	feb24 (5).jpg	10.664475	800
5	feb24 (6).jpg	9.804023	800
6	feb26 (1).jpg	11.078378	800
7	feb26 (2).jpg	10.497791	800
8	feb26 (3).jpg	11.494617	800
9	feb26 (4).jpg	11.352564	800
10	feb26 (5).jpg	11.786355	800
11	feb26 (6).jpg	11.384637	800
12	feb28 (1).jpg	10.718182	800
13	feb28 (2).jpg	11.435451	800
14	feb28 (3).jpg	11.459964	800
15	feb28 (4).jpg	11.929725	800
16	feb28 (5).jpg	11.894106	800
17	feb28 (6).jpg	11.378039	800
18	march 1 (1).jpg	12.152027	800
19	march 1 (2).jpg	11.723684	800

Fig. 8.15 Data Inferred based on AI model




Fig. 8.16: Inference based of AI model

8.7 List of plants grown using our setup

1. Wheat
2. Chickpea
3. Mung Bean
4. Safflower
5. Bajra
6. Marigold Scarlet
7. Marigold Orange
8. Mesembryanthemum
9. Ornamental Kale Fringed
10. Amaranthus



Fig. 8.17: Mung Bean Plant

The hydroponic automation project has been successful, enabling the cultivation of various plants, from flowers to herbs, effortlessly. By precisely understanding the nutrient needs during different growth stages, we can efficiently nurture multiple plant varieties in hydroponic systems. This advancement simplifies the process, making hydroponic gardening accessible to all.




Fig. 8.18: Wheat Plant



Fig. 8.19: Chickpea Plant

8.8 Time Scheduling and React Control

The indoor hydroponic automation system demonstrated promising results in effectively managing the cultivation environment. Time scheduling provided convenient control over LED lights and the air pump, ensuring plants received adequate lighting and aeration at optimal times. This scheduling capability, integrated with the ThingSpeak Cloud, enabled users to program specific timings for these essential components, promoting healthy plant growth and resource efficiency. Additionally, the system offered flexibility through a user-friendly webpage interface, allowing for manual initiation of countdown timers, and enhancing accessibility and adaptability to varying cultivation needs.

Furthermore, the implementation of react control proved to be a valuable feature in maintaining ideal conditions within the hydroponic environment. By enabling users to set temperature thresholds through the webpage interface, the system effectively regulated environmental parameters such as temperature and water levels. For instance, when the temperature exceeded the user-defined threshold, the fan automatically activated, efficiently mitigating heat stress and ensuring optimal growing conditions. Similarly, the react control facilitated automatic activation of the water level motor when water levels dropped below the designated threshold, guaranteeing consistent hydration for plants without requiring constant monitoring. Overall, the integration of time scheduling and react control functionalities contributed to the automation and optimization of indoor hydroponic cultivation, simplifying management tasks and enhancing yield.




Fig. 8.20: Time Scheduling and React Control Web Interface

8.9 Email Alerts

The email alert facility incorporated into the indoor hydroponic automation system demonstrated significant utility in enhancing user convenience and ensuring timely intervention when necessary. This feature enabled users to receive real-time notifications via email regarding critical events or irregularities detected within the cultivation environment. For example, if the water level in the hydroponic system fell below a certain threshold or if there were any malfunctions in the equipment, the system promptly generated an email alert, notifying users of the issue. This proactive approach to monitoring helped prevent potential damage to plants and equipment by allowing users to address issues promptly, even when they were not physically present.

Moreover, the email alert facility served as an invaluable tool for remote monitoring and management of the hydroponic setup. Users could stay informed about the status of their cultivation system regardless of their location, facilitating peace of mind and enabling efficient troubleshooting. Whether users were away from home or occupied with other tasks, they could rely on email alerts to keep them informed about the well-being of their plants and the overall functionality of the system. This remote accessibility empowered users to take timely actions to maintain optimal growing conditions, ultimately maximizing the success of their indoor hydroponic system.




Fig. 8.21: Email Alert

8.10 Data Storage




Fig. 8.22: Data Exported from the Cloud in Excel

The system integrates sensor data storage, enabling convenient exportation in CSV or compatible formats. This facilitates seamless data analysis and retrieval for specific days. With this capability, users can easily track and optimize environmental conditions for optimal plant growth and yield.

8.11 Simulation




Fig. 8.23: Screenshot of the Simulation Done on Wokwi

8.12 Indoor vs Outdoor effect : Based on Light




Fig. 8.24: Indoor vs Outdoor effect : Based on Light

As seen in pictures indoor shows more or similar growth level this is due to the advantage of controlled lighting conditions, allowing growers to tailor light intensity, duration, and spectrum to match the specific needs of their plants. It provides consistent and uniform illumination.

While limitations of sunlight are light intensity and duration vary depending on geographical location, time of year, and weather conditions. Outdoor cultivation is subject to seasonal changes, resulting in fluctuations in light availability. Growers may need to adjust planting schedules or utilize shade structures to mitigate the effects of excessive sunlight or shading. It may be susceptible to environmental factors such as cloud cover, pollution, and climate change, which can impact plant growth and productivity.

While one con of indoor is that it increases the power consumption, but with advancements in semiconductor technology this should not stay a big of a problem. Even in our system we have taken care to reduce power consumption to 10W.

8.13 Indoor vs Outdoor effect : Based on Water Consumption




Fig. 8.25: Indoor vs Outdoor effect : Based on Water Consumption

As seen above we can see that water consumption is 8 times less when indoor as compared to outdoor while variation in values of both stay constant. This is a significant reduction in water utilization indoors.

This is due to varying reasons as Indoor hydroponic systems incorporate recirculating nutrient solutions, minimizing water wastage by continuously reusing and replenishing water. Growers can closely monitor and regulate water usage in indoor environments, adjusting nutrient concentrations, pH levels, and irrigation schedules to optimize plant health and minimize runoff. Although indoor hydroponics requires an initial investment in water infrastructure, the controlled environment and efficient nutrient delivery systems result in lower overall water usage compared to traditional soil-based cultivation methods.

While Outdoor hydroponic systems may face challenges related to water availability and quality, especially in arid or water-stressed regions. Efforts to mitigate water usage, such as rainwater harvesting or wastewater recycling, are essential for sustainable outdoor cultivation practices.

Unless water supply mechanisms are problematic, there is a very high incentive to go for indoor hydroponics given the considerations given above and data collected.

9. APPLICATIONS & FUTURE MODIFICATIONS

9.1 Application

- **Home gardening:** NFT hydroponics is an ideal method for home gardening, as it allows for year-round cultivation of fresh herbs, vegetables, and fruits. The system can be set up in a small space and can be easily maintained, making it a convenient and cost-effective option for home gardeners.
- **Commercial agriculture:** NFT hydroponics is also used in commercial agriculture for growing crops such as lettuce, herbs, and strawberries. The system is highly efficient, as it requires less water and space compared to traditional farming methods, leading to higher yields and reduced costs.
- **Urban farming:** NFT hydroponics is becoming increasingly popular in urban farming, as it allows for the cultivation of fresh produce in urban areas with limited space. The system can be set up in rooftops, balconies, or indoor spaces, providing a sustainable and efficient method for urban farming.
- **Research and education:** NFT hydroponics is used in research and education to study plant growth and development in a controlled environment. The system allows researchers and students to manipulate the nutrient composition and environmental factors to study the effects on plant growth and development.

Overall, the NFT hydroponics system has a wide range of applications in home gardening, commercial agriculture, urban farming, research and education, and medical cannabis cultivation, making it a versatile and efficient method for indoor plant growth.

9.2 Future Modifications

- **Integration with Robotics:** Incorporation of robotics for tasks such as planting, harvesting, pruning, and monitoring. Robotics can increase efficiency, reduce labor costs, and ensure precision in crop management tasks, ultimately leading to higher yields and better resource utilization.
- **Expansion in Space:** Exploration and development of hydroponic farming systems for extraterrestrial environments such as space stations, lunar bases, or Mars habitats. These systems would need to be adapted to operate in microgravity or reduced gravity conditions, utilizing closed-loop life support systems and advanced technologies for water recycling, nutrient delivery, and environmental control to sustain food production for long-duration space missions.
- **Automated Nutrient Delivery:** Implementation of automated nutrient delivery systems that precisely dose and adjust nutrient solutions based on plant growth stages and requirements, ensuring optimal nutrition uptake.
- **Climate Control and CO₂ Enrichment:** Enhanced climate control systems to regulate temperature, humidity, and CO₂ levels, providing an optimal growing environment for plants to thrive and maximizing photosynthetic efficiency.
- **Advanced Pest and Disease Management:** Integration of biological control methods, such as beneficial insects or organic pesticides, and the use of data analytics to detect and prevent pest and disease outbreaks before they can damage crops.
- **Integration with Renewable Energy Sources:** Incorporation of renewable energy sources such as solar or wind power to supplement or replace traditional energy sources, reducing carbon footprint and operating costs.
- **Nutrient Monitoring and Management Systems:** Implementation of advanced nutrient monitoring and management systems that analyze plant nutrient levels in real-time and automatically adjust nutrient solutions accordingly, ensuring optimal plant health and productivity.
- **Genetic Engineering for Crop Improvement:** Continued research into genetic engineering techniques to develop crops with enhanced traits such as disease resistance, nutrient efficiency, and yield potential, tailored specifically for hydroponic cultivation.

10. BILL OF MATERIAL

Sr. No.	Label	Part Type	Part Description	Qty/ Set	Unit Price (INR)	Total Price (INR)
1	R1	KY-018 Photoresistor Module	output type analog; pins 3;	1	22	22
2	U1	Humidity and Temperature Sensor DHT11	±5%RH ±2°C; 20-95%RH; 3.3-5.5V DC;	1	58	58
3	U2	Water Level Sensor	-	1	21	21
4	U3, U4	WeMos D1 Mini	no headers; ESP-8266EX	2	152	304
5	U5, U6	L293D	L293D; package THT	2	21	42
6	U7, U8	Sharp PC817	package THT	2	6.5	13
7	U9	ESP 32 CAM	OV2640 Module 2MP	1	439	439
8	U10	1 channel Relay Module	5V SPDT	1	33	33
9	X1 to X12	USB Connectors	target USB-A;	12	5	60
		Hardware Cost				992

10.1 Setup Cost

Sr. No.	Components	Qty	Unit Price (INR)	Total Price (INR)
1	UV light	1	1799	1799
2	Air Pump	1	499	499
3	Water Pump	1	90	90
4	Fan	1	240	240
5	Hydroponic Starter Kit	2	1599	3198
	Setup Cost			5826
	Total Cost			6818

11. CONCLUSION

The Hydroponics Based Precision Farming With Feature Optimization, based on indoor farming with temperature, UV light, water level, and air pump control, has several benefits in addition to faster growth and reduced water consumption. Firstly, the system eliminates the need for large land areas, making it ideal for urban and suburban regions where space is limited. By precisely controlling temperature, light, and water levels, plants receive optimal growing conditions, leading to higher yields and healthier crops. Furthermore, automation reduces the risk of human error, ensuring consistent production to the highest standards.

The Hydroponics Based Precision Farming With Feature Optimization project is a highly effective and efficient system for growing plants. The system can lead to 30 to 50% faster growth than soil-based farming while reducing water consumption by 70-85%. With the entire system operating on its own, there is no need for human intervention, making it an ideal solution for individuals or businesses seeking to maximize crop yields while minimizing labor and resource costs. Moreover, it has been designed for Scaling by modular design and cloud. Overall, the Hydroponics Based Precision Farming With Feature Optimization project represents a significant advancement in sustainable farming practices, and its potential to revolutionize the agriculture industry cannot be overstated.

12. REFERENCES

1. Union, U. World Population Projected to Reach 9.8 Billion in 2050, and 11.2 Billion in 2100; UN DESA: New York, NY, USA, 2017.
2. Union, "Food Production Must Double by 2050 to Meet Demand from World's Growing Population, Innovative Strategies Needed to Combat Hunger, Experts Tell Second Committee", United Nations Press Release, 2009.
3. P Vaishnavi and G Manisankar, "Labour scarcity in agriculture: A review", The Pharma Innovation Journal 2022; SP-11(4): 2087-2090.
4. ISRO, "Land Degradation and Desertification in India", Drishti IAS Daily News Analysis, 2021.
5. Food and Agriculture Organization(FAO), "Sustainable Food and Agriculture", United Nation, 2019.
6. Harsha Kamepalli, "Hydroponics: Indian outlook"; Times of India(TOI): India, 2023.
7. Brock Robinson, "What Are Hydroponic Systems and How Do They Work?", Fresh Water Systems, 2019.
8. F. L. Valiente et al., "Internet of Things (IOT)-Based Mobile Application for Monitoring of Automated Aquaponics System," 2018 IEEE 10th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment and Management (HNICEM), Baguio City, Philippines, 2018, pp. 1-6, doi: 10.1109/HNICEM.2018.8666439.
9. Helmy, M. G. Mahaidyu, A. Nursyahid, T. A. Setyawan and A. Hasan, "Nutrient Film Technique (NFT) hydroponic monitoring system based on wireless sensor network," 2017 IEEE International Conference on Communication, Networks and Satellite (Comnetsat), Semarang, Indonesia, 2017, pp. 81-84, doi: 10.1109/COMNETSAT.2017.8263577.
10. P. Srivani, Y. Devi C. and S. H. Manjula, "A Controlled Environment Agriculture with Hydroponics: Variants, Parameters, Methodologies and Challenges for Smart Farming," 2019 Fifteenth International Conference on Information Processing (ICINPRO), Bengaluru, India, 2019, pp. 1-8, doi: 10.1109/ICInPro47689.2019.9092043.

11. Geetali Saha, "Technological Influences on Monitoring and Automation of the Hydroponics System," 2021 Innovations in Power and Advanced Computing Technologies (i-PACT), Kuala Lumpur, Malaysia, 2021, pp. 1-8, doi: 10.1109/i-PACT52855.2021.9696519.
12. A. Phutthisathian, N. Pantasen and N. Maneerat, "Ontology-Based Nutrient Solution Control System for Hydroponics," 2011 First International Conference on Instrumentation, Measurement, Computer, Communication and Control, Beijing, China, 2011, pp. 258-261, doi: 10.1109/IMCCC.2011.260.
13. S. Adhau, R. Surwase and K. H. Kowdiki, "Design of fully automated low cost hydroponic system using LabVIEW and AVR microcontroller," 2017 IEEE International Conference on Intelligent Techniques in Control, Optimization and Signal Processing (INCOS), Srivilliputtur, India, 2017, pp. 1-4, doi: 10.1109/ITCOSP.2017.8303091.
14. P Sihombing, N A Karina, J T Tarigan and M I Syarif, Automated hydroponics nutrition plants systems using arduino uno microcontroller based on android, 2nd International Conference on Computing and Applied Informatics 2017.Doi :10.1088/1742- 6596/978/1/012014.
15. M. Fuangthong and P. Pramokchon, "Automatic control of electrical conductivity and PH using fuzzy logic for hydroponics system," 2018 International Conference on Digital Arts, Media and Technology (ICDAMT), Phayao, Thailand, 2018, pp. 65-70, doi: 10.1109/ICDAMT.2018.8376497.
16. Baddadi, Sara, Salwa Bouadila, Wahid Ghorbel, and AmenAllah Guizani. "Autonomous greenhouse microclimate through hydroponic design and refurbished thermal energy by phase change material." Journal of Cleaner Production 211 (2019): 360-379.
17. Kaewwiset, T. and T. Yooyativong (2017). Estimation of electrical conductivity and pH in hydroponic nutrient mixing system using Linear Regression algorithm. 2017 14th International Conference on Electrical Engineering/Electronics, Computer, Telecommunications and Information Technology (ECTI-CON)
18. M. F. Saaid, A. Sanuddin, M. Ali and M. S. A. I. M. Yassin, "Automated pH controller system for hydroponic cultivation," 2015 IEEE Symposium on Computer Applications & Industrial Electronics (ISCAIE), Langkawi, Malaysia, 2015, pp. 186-190, doi: 10.1109/ISCAIE.2015.7298353.
19. Wheeler, Raymond M. "NASA's controlled environment agriculture testing for space habitats." (2014).
20. G. Dbritto and S. Hamdare, "An AI Based System Design to Develop and

Monitor a Hydroponic Farm," 2018 International Conference on Smart City and Emerging Technology (ICSCET), Mumbai, India, 2018, pp. 1-5, doi: 10.1109/ICSCET.2018.8537317.

21. Helmy, M. G. Mahaidyu, A. Nursyahid, T. A. Setyawan and A. Hasan, "Nutrient Film Technique (NFT) hydroponic monitoring system based on wireless sensor network," 2017 IEEE International Conference on Communication, Networks and Satellite (Comnetsat), Semarang, Indonesia, 2017, pp. 81-84, doi: 10.1109/COMNETSAT.2017.8263577.
22. A. Phutthisathian, "Ontology-Based Nutrient Solution Control System for Hydroponics," no. 1, pp. 258–261, 2011.
23. J. A. Asumadu, B. Smith, N. S. Dogan, P. A. Loretan, and H. Aglan, "Microprocessor-based instrument for hydroponic growth chambers used in ecological life support systems," in Instrumentation and Measurement Technology Conference, 1996. IMTC-96. Conference Proceedings. Quality Measurements: The Indispensable Bridge between Theory and Reality., IEEE, 1996, pp. 325-329 vol.1.
24. Desta Yolanda, "Implementation of Real-Time Fuzzy Logic Control for NFT-Based Hydroponic System on Internet of Things Environment", Institut Teknologi Bandung, 2016.
25. Harun, Ahmad Nizar, Robiah Ahmad, and Norliza Mohamed. "Plant growth optimization using variable intensity and Far Red LED treatment in indoor farming." In Smart Sensors and Application (ICSSA), 2015 International Conference on, pp. 92-97. IEEE, 2015.
26. G. Saha, "Technological Influences on Monitoring and Automation of the Hydroponics System," 2021 Innovations in Power and Advanced Computing Technologies (i-PACT), Kuala Lumpur, Malaysia, 2021, pp. 1-8, doi: 10.1109/i-PACT52855.2021.9696519.
27. S. Fourside. Top-Fed DWC Cannabis Setup Guide - Bubbleponics. Available: <http://growweedeasy.com/high-yieldbubbleponics-technique>
28. Kaewwiset, T. and T. Yooyativong (2017). Estimation of electrical conductivity and pH in hydroponic nutrient mixing system using Linear Regression algorithm. 2017 International Conference on Digital Arts, Media and Technology (ICDAMT).
29. Nwosisi, Sochinwechi, and Dilip Nandwani. "Urban Horticulture: Overview of Recent Developments." In Urban Horticulture, pp. 3-29. Springer, Cham, 2018.
30. H. Helmy, A. Nursyahid, T. A. Setyawan, and A. Hasan, "Nutrient Film Technique (NFT) Hydroponic Monitoring System," J. Appl. Inf. Commun. Technol., vol. 1, no. 1, pp. 1–6, 2016.

31. J. A. Asumadu, B. Smith, N. S. Dogan, P. A. Loretan, and H. Aglan, "Microprocessor-based instrument for hydroponic growth chambers used in ecological life support systems," in Instrumentation and Measurement Technology Conference, 1996. IMTC-96. Conference Proceedings. Quality Measurements: The Indispensable Bridge between Theory and Reality., IEEE, 1996, pp. 325-329 vol.1.
32. T. Nishimura, Y. Okuyama, A. Matsushita, H. Ikeda and A. Satoh, "A compact hardware design of a sensor module for hydroponics," 2017 IEEE 6th Global Conference on Consumer Electronics (GCCE), Nagoya, Japan, 2017, pp. 1-4, doi: 10.1109/GCCE.2017.8229255
33. F. L. Valiente et al., "Internet of Things (IOT)-Based Mobile Application for Monitoring of Automated Aquaponics System," 2018 IEEE 10th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment and Management (HNICEM), Baguio City, Philippines, 2018, pp. 1-6, doi: 10.1109/HNICEM.2018.8666439.
34. H. K. Srinidhi, H. S. Shreenidhi and G. S. Vishnu, "Smart Hydroponics system integrating with IoT and Machine learning algorithm," 2020 International Conference on Recent Trends on Electronics, Information, Communication & Technology (RTEICT), Bangalore, India, 2020, pp. 261-264, doi: 10.1109/RTEICT49044.2020.9315549.
35. Ryu, M.-J. et al. (2014) “Spatial, Vertical, and Temporal Variability of Ambient Environments in Strawberry and Tomato Greenhouses in Winter,” Journal of Biosystems Engineering. 한국농업기계학회, 39(1), pp. 47–56. doi: 10.5307/JBE.2014.39.1.047.
<http://koreascience.or.kr/article/JAKO201409972440252.pdf>
36. Lee, Chan Kyu, Mo Chung, Ki-Yeol Shin, Yong-Hoon Im, and Si-Won Yoon. 2019. "A Study of the Effects of Enhanced Uniformity Control of Greenhouse Environment Variables on Crop Growth" Energies 12, no. 9: 1749. <https://doi.org/10.3390/en12091749>
<https://www.mdpi.com/1996-1073/12/9/1749>
37. Lee CK, Chung M, Shin K-Y, Im Y-H, Yoon S-W. A Study of the Effects of Enhanced Uniformity Control of Greenhouse Environment Variables on Crop Growth. Energies. 2019; 12(9):1749. <https://doi.org/10.3390/en12091749>
<https://www.mdpi.com/1996-1073/12/9/1749>
<https://mospi.gov.in/97-environment-statistics>.
38. Khudoyberdiev, A.; Ahmad, S.; Ullah, I.; Kim, D. An Optimization Scheme Based on Fuzzy Logic Control for Efficient Energy Consumption in Hydroponics Environment. Energies 2020, 13, 289. <https://doi.org/10.3390/en13020289>

39. Yamaguchi, Satoru, Takuya Motosugi, and Yoshihiko Takahashi. "Battery \ Management for Small Hydroponic Systems and Cultivation Experiments," International Journal of Manufacturing, Materials, and Mechanical Engineering (IJMMME) 11, no.3: 21-36. <http://doi.org/10.4018/IJMMME.2021070102> [no need for paper , most taken form abstract]
40. A. Chakraborti, A. Jain, S. Menon and K. Samdani, "A Review of Security Challenges in Home Automation Systems," 2019 IEEE International Conference on System, Computation, Automation and Networking (ICSCAN), Pondicherry, India, 2019, pp. 1-6, doi: 10.1109/ICSCAN.2019.8878722. <https://sci-hub.se/10.1109/ICSCAN.2019.8878722>
41. Tyson, R. V., Treadwell, D. D., & Simonne, E. H. (2011). Opportunities and Challenges to Sustainability in Aquaponic Systems. HortTechnology hortte, 21(1), 6-13. Retrieved Sep 15, 2023, from <https://doi.org/10.21273/HORTTECH.21.1.6>
42. De Rijck, G., and Schrevens, E. (1998b). Elemental bioavailability in nutrient solutions in relation to precipitation reactions. J. Plant Nutr. 21, 2103–2113. doi: 10.1080/01904169809365547 [no need for this paper, doing a reference of its ref]
43. Khan, S., Purohit, A., & Vadsaria, N. (2020). Hydroponics: current and future state of the art in farming. Journal of Plant Nutrition, 44(10),1515–1538.doi:10.1080/01904167.2020.1860217
10.1080/01904167.2020.1860217
<https://sci-hub.se/https://doi.org/10.1080/01904167.2020.1860217>
44. Brooks, C. 2000. Development of a Semi-automated System for Production of Salad Vegetables for use on Space Station Freedom. In Proceedings of the 13th Annual Conference on Hydroponics. Hydroponic Society of America. San Ramon. CA. ed. D. Schact, 72–6.
45. Drysdale, A. E., A. J. Hanford. 2002. Advanced Life Support systems modeling and analysis project: Baseline values and assumptions document. NASA-Johnson Space Center F Document No. JSC-47787 (CTSD-ADV-482)
46. Santos, A. N., E. F. de F. e Silva, G. F. d Silva, J. M. C. Barnab ^ e, M. M. Rolim, and D. d C. Dantas. 2016. Yield of cherry tomatoes as a function of water salinity and irrigation frequency. Revista Brasileira de Engenharia Agricola e Ambiental 20 (2):107–12. doi: 10.1590/1807-1929/agriambi.v20n2p107-112
47. Sevostianov, I., & Melnik, O. (2021). IMPROVEMENT OF HYDROPON INSTALLATIONS. ENGINEERING, ENERGY, TRANSPORT AIC.DOI: 10.37128/2520-6168-2021-4-13
<http://tetapk.vsau.org/storage/articles/December2021/yWW9YLhBOPqY4czAYJBO.pdf>

48. Lakshmanan, R., Djama, M., Perumal, S.K., & Abdulla, R.M. (2020). Automated smart hydroponics system using internet of things. International Journal of Electrical and Computer Engineering (IJECE). DOI:[10.11591/IJECE.V10I6.PP6389-6398](https://doi.org/10.11591/IJECE.V10I6.PP6389-6398) Corpus ID: 226192620
<https://ijece.iaescore.com/index.php/IJECE/article/download/20870/14427>
49. Saha, Geetali. "Technological Influences on Monitoring and Automation of the Hydroponics System." 2021 Innovations in Power and Advanced Computing Technologies (i-PACT) (2021): 1-8. DOI:[10.1109/i-PACT52855.2021.9696519](https://doi.org/10.1109/i-PACT52855.2021.9696519) Corpus ID: 246683063 [link not found, info taken from abstract]
50. A. Ani and P. Gopalakirishnan, "Automated Hydroponic Drip Irrigation Using Big Data," 2020 Second International Conference on Inventive Research in Computing Applications (ICIRCA), Coimbatore, India, 2020, pp. 370-375, doi: 10.1109/ICIRCA48905.2020.9182908.
51. S. M et al., "Analysis of Hydroponic System Crop Yield Prediction and Crop IoT-based monitoring system for precision agriculture," 2022 International Conference on Edge Computing and Applications (ICECAA), Tamilnadu, India, 2022, pp. 575-578, doi: 10.1109/ICECAA55415.2022.9936473.
[need to get this from library]
52. H. K. Srinidhi, H. S. Shreenidhi and G. S. Vishnu, "Smart Hydroponics system integrating with IoT and Machine learning algorithm," 2020 International Conference on Recent Trends on Electronics, Information, Communication & Technology (RTEICT), Bangalore, India, 2020, pp. 261-264, doi: 10.1109/RTEICT49044.2020.9315549.
53. Susanto, F. ., Suryani, N. K. ., Darmawan, P., Prasiani, K., & Ramayu, I. M. S. (2021). Comprehensive Review on Automation in Hydroponic Agriculture Using Machine Learning and IoT. RSF Conference Series: Engineering and Technology, 1(2), 86–95. <https://doi.org/10.31098/cset.v1i2.479>
<https://proceeding.researchsynergypress.com/index.php/cset/article/download/479/529>