

BASIC CODING PREPARATION

By Jani Ahamed Habeeb Mohamed

Table of Contents

1. Problems.....	11
1.1 Minimum moves to spread stones over grid	11
1.2 LRU Cache	13
1.3 LFU Cache.....	17
1.4 IP Address, Subnet, Network Address, Host.....	21
1.5 IP address generation	22
1.6 Validity Of IP Address	24
1.7 Packet Parser	26
1.8 Store IP address.....	28
1.9 Store MAC address.....	29
1.10 Basic Firewall Implementation	30
1.11 Rate Limiter.....	32
1.12 Longest Prefix Match - IP	34
1.13 Trie	35
1.14 Calculator using Tree.....	38
1.15 Balanced Binary Tree	39
1.16 Time Needed To Inform All Employees	41
1.17 Distribute Coins In Binary Tree.....	43
1.18 Find Original Array From Doubled Array.....	45
1.19 Sum Of SubArray Minimums	46
1.20 Valid Parentheses String	49
1.21 Asteroid Collision	50
1.22 ReOrganize String (any two adjacent characters are not same)	52
1.23 Generate All Sub Arrays	53
1.24 Bit manipulations (Set/Reset/Get Bits).....	55
1.25 Decode Ways For String	56
1.26 Multiply Two Strings	57
1.27 Buildings With An Ocean View	59
1.28 Interleaving String	60
1.29 Reverse Linked List Nodes In K Groups	62
1.30 4 Sum	64
1.31 Largest Rectangle In Histogram	66
1.32 Minimum Path Sum.....	67

1.33	House Robber II	69
1.34	Binary Tree Vertical Order Traversal	70
1.35	Course Schedule.....	74
1.36	Word Break	77
1.37	Longest Valid Parentheses	79
1.38	Edit Distance (Minimum Operation to convert word1 to word2)	81
1.39	SubSets II	82
1.40	Nth Digit.....	84
1.41	Minimize The Maximum Difference Of Pairs	85
1.42	Reverse Words In String II	86
1.43	Number Of Flowers In Full Bloom	87
1.44	Restore IP addresses.....	90
1.45	SubArray Sum Divisible By K	92
1.46	Find Missing Observations.....	94
1.47	Largest Palindromic Number.....	96
1.48	Basic Calculator I.....	97
1.49	Basic Calculator II.....	99
1.50	Basic Calculator III	100
1.51	Inorder Successor of Binary Search Tree	101
1.52	Regular Expression Matching	103
1.53	Remove All Adjacent Duplicates In String.....	105
1.54	Fibonacci Series.....	106
1.55	Path With Minimum Effort (Hiking heights).....	108
1.56	Longest Cycle In Graph.....	113
1.57	Maximum Value Of K Coins From Piles	114
1.58	Flip Equivalent Binary Trees.....	116
1.59	Maximum Length Of a Concatenated String With Unique Characters	121
1.60	Buddy Strings.....	122
1.61	Robot Room Cleaner	124
1.62	Count Unique Characters Of All Substrings Of A Given String	125
1.63	Minimum Fuel Cost To Report To The Capital	126
1.64	Remove Duplicate Letters(lexicographical small).....	129
1.65	Score of Parentheses	131
1.66	Maximum Number Of Balloons.....	132
1.67	Buy Two Chocolates	133

1.68	Permutations	134
1.69	Combinations	135
1.70	Remove K Digits (return smallest possible integer)	138
1.71	Car Fleet (arrive at destination)	139
1.72	Match Sticks To Square	140
1.73	132 Pattern	142
1.74	Word Search II	145
1.75	Merge Intervals	148
1.76	Merge Sorted Array	151
1.77	Serialize and Deserialize Binary Tree	153
1.78	Bulb Switcher	157
1.79	Sign Of The Product Of An Array	158
1.80	Excel Sheet Column Title	159
1.81	Remove All Adjacent Duplicates In String (K duplicate removal)	160
1.82	Number Of Islands	162
1.83	Copy List With Random Pointer	164
1.84	Two Sum	167
1.85	Flood Fill	170
1.86	Maximum SubArray	174
1.87	Sort Colors	175
1.88	Median Of Two Sorted Arrays	177
1.89	Root Equals Sum Of Children	178
1.90	Generate Parentheses	179
1.91	Meeting Rooms II – Minimum Rooms Required	181
1.92	Reverse Linked List	183
1.93	Implement Queue Using Stack	186
1.94	Implement Stack Using Queue	189
1.95	Trapping Rain Water	192
1.96	Longest SubString Without Repeating Characters	193
1.97	SubArray Sum Equals K	196
1.98	Search In A Rotated Sorted Array	197
1.99	Top K Frequent Elements	199
1.100	Rotate Image	201
1.101	Gas Station	203
1.102	Delete Node in BST	205

1.103	Word Search.....	209
1.104	Integer To Roman.....	212
1.105	Merge String Alternately	214
1.106	Reverse Linked List II (In between from one position to another).....	216
1.107	Implement Trie – Prefix Tree	218
1.108	Odd Even Linked List	221
1.109	Best Time To Buy And Sell Stock (Single day to buy and different day to sell once)	224
1.110	Longest Consecutive Sequence	225
1.111	Spiral Matrix.....	227
1.112	Populating Next Right Pointer In Each Node.....	230
1.113	String Compression	233
1.114	Construct Binary Tree From Inorder and post Order Traversal	235
1.115	Valid Sudoku	238
1.116	Path Sum	242
1.117	Design Add and Search Words DataStructure	245
1.118	Sudoku Solver	248
1.119	Max Area Of Island	251
1.120	Valid Parentheses.....	254
1.121	Merge Two Sorted Lists.....	255
1.122	Container With Most Water.....	258
1.123	Pascals Triangle.....	260
1.124	Valid Anagram	262
1.125	Unique Paths	263
1.126	Longest Increasing Subsequence	265
1.127	Group Anagrams.....	266
1.128	Longest Palindromic SubString	271
1.129	Three Sum	273
1.130	Single Element In A Sorted Array.....	277
1.131	Letter Combinations Of A Phone Number	278
1.132	Find The Index Of The First Occurrence In The String (strstr – needle in haystack).....	282
1.133	Best Time to Buy And Sell Stock II (Buy Sell Any Times)	283
1.134	Intersection Of Two Arrays	284
1.135	Climbing Stairs.....	285
1.136	Convert Sorted Array To Binary Search Tree.....	286
1.137	Kth Largest Element In Array.....	288

1.138	Kth Smallest Element In Array	290
1.139	Binary Tree ZigZag Level Order Traversal	291
1.140	Find Minimum In Rotated Sorted Array	295
1.141	Binary Search	297
1.142	Construct Binary Tree From PreOrder And Inorder Traversals	298
1.143	Remove Nth Node From End Of List.....	300
1.144	Jump Game	303
1.145	Insert Delete GetRandom O(1)	304
1.146	Daily Temperatures	307
1.147	Reverse Integer	308
1.148	Symmetric Tree	309
1.149	Lowest Common Ancestor Of A binary tree.....	312
1.150	Merge K Sorted Lists	315
1.151	SubSets	317
1.152	Can Place Flowers	319
1.153	Roman To Integer	321
1.154	Find The Duplicate Number.....	323
1.155	Product Of Array Except Self	324
1.156	Coin Change	325
1.157	Contains Duplicate.....	327
1.158	Search A 2D Matrix.....	329
1.159	Validate Binary Search Tree	330
1.160	Plus One.....	332
1.161	Majority Element	334
1.162	Valid Palindrome	335
1.163	House Robber	336
1.164	Next Greater Element.....	337
1.165	Shuffle An Array	338
1.166	MinStack.....	341
1.167	Sum Of Two Integers.....	344
1.168	Maximum Product SubArray	344
1.169	Number Of 1 Bits	346
1.170	Counting Bits.....	347
1.171	Missing Number	348
1.172	Reverse Bits	349

1.173	Detect Cycle in Linked List	350
1.174	Reorder List	352
1.175	Set Matrix Zeros	355
1.176	Insert Intervals	359
1.177	Non Overlapping Intervals	363
1.178	Meeting Rooms (Can attend all meetings)	365
1.179	Longest Repeating Character Replacement	366
1.180	Minimum Window SubString	368
1.181	Palindromic Substrings	371
1.182	Encode And Decode Strings	372
1.183	Longest Common Subsequence	375
1.184	Word Break	378
1.185	Combination Sum IV	379
1.186	House Robber II	379
1.187	Decode Ways	381
1.188	Find Median From Data Stream	382
1.189	Maximum Depth Of Binary Tree	384
1.190	Same Tree	385
1.191	Invert Binary Tree	387
1.192	Binary Tree Maximum Path Sum	389
1.193	Binary Tree Level Order Traversal	392
1.194	Kth Smallest Element In BST	395
1.195	SubTree Of Another Tree	398
1.196	Word Search II	401
1.197	Clone Graph	403
1.198	Course Schedule	408
1.199	Pacific Atlantic Water Flow	410
1.200	Alien Dictionary	413
1.201	Graph Valid Tree	415
1.202	Number Of Connected Components In an Undirected Graph	417
1.203	Longest Prefix Match - Trie	418
1.204	UDP Socket Communication Client and Server	422
1.205	TCP Socket Communication Client and Server	425
1.206	Shared Memory	426
1.207	Message Queues	427

1.208	Dequeue	427
1.209	Regex Search Target String	431
1.210	Quick Sort	433
1.211	Merge Sort	434
1.212	Bloom Filter	435
1.213	Hash Table	437
1.214	Endianess	438
1.215	MALLOC Implementation	440
1.216	Single Linked List	442
1.217	Double Linked List	446
1.218	Stack	449
1.219	Queue	451
1.220	Binary Search Tree	453
1.221	Trie Complete Code	456
1.222	Graph Shortest Path	459
1.223	Semaphore	462
1.224	Mutex	464
1.225	Blocking Queue	465
1.226	String to Integer(atoi)	467
1.227	Add Two Numbers	468
1.228	Next Permutation	469
1.229	First Missing Positive	472
1.230	Permutations	472
1.231	Remove Duplicates From Sorted List	474
1.232	Binary Tree InOrder Traversal	475
1.233	Binary Tree ZigZag Level Order Traversal	477
1.234	Flatten Binary Tree To Linked List	477
1.235	Binary Tree Post Order Traversal	479
1.236	Binary Tree Pre Order Traversal	480
1.237	Excel Sheet Column Number	481
1.238	Ugly Number	481
1.239	Game Of Life	482
1.240	Minimum Number Of Arrows To Burst Balloons	483
1.241	Exclusive Time Of Functions	484
1.242	Top K Frequent Words	485
1.243	Walking Robot Simulation	485
1.244	Cousins In Binary Tree	487

1.245	Maximum Equal Frequency	489
1.246	Packet Parser Multithreading	490
1.247	Thread Pool	494
1.248	Memory Pool.....	496
1.249	DPDK.....	497
1.250	Attack Packet Detection With PCAP	502
1.251	Attack Packet Context Generation - HTTP	503
1.252	Breadth First Search(BFS) Of Binary Tree	504
1.253	Depth First Search(DFS) Of Binary Tree.....	506
1.254	Breadth First Search(BFS) Of Graph.....	507
1.255	Depth First Search(DFS) Of Graph.....	509
1.256	Shortest Path In Graph.....	511
1.257	Sliding Window Maximum	513
1.258	Throughput Load	514
1.259	Middle Element Of Linked List.....	515
1.260	Build Process Tree.....	516
1.261	Construct Tree From Data.....	518
1.262	Peak Element.....	519
1.263	T2 subtree of T1	520
1.264	Minimum Swaps Required To Convert Min Heap to BST	521
1.265	Check If Two Files Are Identical.....	522
1.266	Git Commit History.....	523
1.267	Recursive Links In Web page	524
1.268	Left Most Nodes	526
1.269	Recursive Print Linked List.....	527
1.270	Minimum Distance Between Two Elements	528
1.271	Unique Elements	528
1.272	Square A Sorted Array.....	529
1.273	NTP Logger	530
1.274	Job Scheduler.....	532
1.275	Course Schedule II	534
1.276	Cycle/Loop In Linked List	536
1.277	Version Sorting	537
1.278	Reverse Linked List Using Stack	537
1.279	Hexadecimal to decimal	539

1.280	Decimal To Hexadecimal.....	540
1.281	Absolute Path From Relative Path	541
1.282	LockLess programming	542
1.283	IOCTL.....	542
1.284	I2C	545
1.285	Large File Word Frequency	547
1.286	Compressed String	549
1.287	TCAM	549
1.288	Spin Locks.....	551
1.289	RPC (Remote Procedure Call)	552
1.289.1.1.1	Step1 : Specify the protocol for client server communication	552
1.289.1.1.2	Step 2 – Develop the client program	555
1.289.1.1.3	Step 3 – Develop the server program.....	558
1.290	Ether Types.....	567
1.291	Maximum Length Of A Concatenated String With Unique Characters.....	568

1. Problems

1.1 Minimum moves to spread stones over grid

You are given a **0-indexed** 2D integer matrix grid of size $3 * 3$, representing the number of stones in each cell. The grid contains exactly 9 stones, and there can be **multiple** stones in a single cell.

In one move, you can move a single stone from its current cell to any other cell if the two cells share a side.

Return *the minimum number of moves required to place one stone in each cell*.

Example 1:

Input: grid = [[1,1,0],[1,1,1],[1,2,1]]

Output: 3

Explanation: One possible sequence of moves to place one stone in each cell is:

- 1- Move one stone from cell (2,1) to cell (2,2).
- 2- Move one stone from cell (2,2) to cell (1,2).
- 3- Move one stone from cell (1,2) to cell (0,2).

In total, it takes 3 moves to place one stone in each cell of the grid.

It can be shown that 3 is the minimum number of moves required to place one stone in each cell.

Example 2:

Input: grid = [[1,3,0],[1,0,0],[1,0,3]]

Output: 4

Explanation: One possible sequence of moves to place one stone in each cell is:

- 1- Move one stone from cell (0,1) to cell (0,2).
- 2- Move one stone from cell (0,1) to cell (1,1).
- 3- Move one stone from cell (2,2) to cell (1,2).
- 4- Move one stone from cell (2,2) to cell (2,1).

In total, it takes 4 moves to place one stone in each cell of the grid.

It can be shown that 4 is the minimum number of moves required to place one stone in each cell.

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <limits.h>

#define MAX_SIZE 3
```

```

int min(int a, int b) {
    return a < b ? a : b;
}

int minimumMoves(int** grid, int gridSize, int* gridColSize) {
    int result = INT_MAX;
    int distance = 0;
    for (int i = 0; i < MAX_SIZE; i++) {
        for (int j = 0; j < MAX_SIZE; j++) {
            if (grid[i][j]) continue;
            for (int a = 0; a < MAX_SIZE; a++) {
                for (int b = 0; b < MAX_SIZE; b++) {
                    if (grid[a][b] < 2) continue;
                    int distance = abs(i-a) + abs(j-b);
                    grid[a][b]--;
                    grid[i][j]++;
                    distance += minimumMoves(grid, gridSize, gridColSize);
                    grid[a][b]++;
                    grid[i][j]--;
                    result = min(distance, result);
                }
            }
        }
    }
    return (result == INT_MAX)?0:result;
}

```

```

int main() {
    // Example grid
    int gridSize = MAX_SIZE;
    int gridColSize[MAX_SIZE] = {MAX_SIZE, MAX_SIZE, MAX_SIZE};
    int **grid = (int **)malloc(MAX_SIZE * sizeof(int *));
    for (int i = 0; i < MAX_SIZE; i++) {
        grid[i] = (int *)malloc(MAX_SIZE * sizeof(int));
    }

    // Initialize the grid with sample values
    // Example: {1, 0, 2}
    //           {0, 2, 0}
    //           {1, 0, 0}
    grid[0][0] = 1;
    grid[0][1] = 1;
    grid[0][2] = 0;
    grid[1][0] = 1;
    grid[1][1] = 1;
    grid[1][2] = 1;
    grid[2][0] = 1;
    grid[2][1] = 2;
}

```

```

grid[2][2] = 1;

// Call the function and print the result
int moves = minimumMoves(grid, gridSize, gridColSize);
printf("Minimum moves required: %d\n", moves);

grid[0][0] = 1;
grid[0][1] = 3;
grid[0][2] = 0;
grid[1][0] = 1;
grid[1][1] = 0;
grid[1][2] = 0;
grid[2][0] = 1;
grid[2][1] = 0;
grid[2][2] = 3;

// Call the function and print the result
moves = minimumMoves(grid, gridSize, gridColSize);
printf("Minimum moves required: %d\n", moves);
// Free memory allocated for the grid
for (int i = 0; i < MAX_SIZE; i++) {
    free(grid[i]);
}
free(grid);

return 0;
}

```

Output: 3 and 4

1- Move one stone from cell (2,1) to cell (2,2).
 2- Move one stone from cell (2,2) to cell (1,2).
 3- Move one stone from cell (1,2) to cell (0,2).

1- Move one stone from cell (0,1) to cell (0,2).
 2- Move one stone from cell (0,1) to cell (1,1).
 3- Move one stone from cell (2,2) to cell (1,2).
 4- Move one stone from cell (2,2) to cell (2,1).

Time/Space Complexity:

$O(3^n)/O(n)$

1.2 LRU Cache

Design a data structure that follows the constraints of a [Least Recently Used \(LRU\) cache](#).

Implement the LRU Cache class:

- `LRUCache(int capacity)` Initialize the LRU cache with **positive** size capacity.
- `int get(int key)` Return the value of the key if the key exists, otherwise return -1.

- `void put(int key, int value)` Update the value of the `key` if the `key` exists. Otherwise, add the `key-value` pair to the cache. If the number of keys exceeds the `capacity` from this operation, **evict** the least recently used key.

The functions `get` and `put` must each run in $O(1)$ average time complexity.

Example 1:

Input

```
["LRUCache", "put", "put", "get", "put", "get", "put", "get", "put", "get"]
[[2], [1, 1], [2, 2], [1], [3, 3], [2], [4, 4], [1], [3], [4]]
```

Output

```
[null, null, null, 1, null, -1, null, -1, 3, 4]
```

Explanation

```
LRUCache IRUCache = new LRUCache(2);
IRUCache.put(1, 1); // cache is {1=1}
IRUCache.put(2, 2); // cache is {1=1, 2=2}
IRUCache.get(1); // return 1
IRUCache.put(3, 3); // LRU key was 2, evicts key 2, cache is {1=1, 3=3}
IRUCache.get(2); // returns -1 (not found)
IRUCache.put(4, 4); // LRU key was 1, evicts key 1, cache is {4=4, 3=3}
IRUCache.get(1); // return -1 (not found)
IRUCache.get(3); // return 3
IRUCache.get(4); // return 4
```

C:

```
#include <stdio.h>
#include <stdlib.h>

#define MAX_KEYS 10000

// Structure of a Node in the LRUCache
typedef struct Node {
    int key;
    int value;
    struct Node* next;
    struct Node* prev;
} Node;

// Structure of the LRUCache
typedef struct {
    int capacity;
    int size;
    Node* head;
    Node* tail;
    Node cache[MAX_KEYS]; // Static cache array for quick lookups
} LRUCache;
```

```

// Function to create an LRUCache
LRUCache* lRUCacheCreate(int capacity) {
    LRUCache* obj = (LRUCache*)malloc(sizeof(LRUCache));
    obj->capacity = capacity;
    obj->size = 0;
    obj->head = NULL;
    obj->tail = NULL;

    // Initialize the cache array
    for (int i = 0; i < MAX_KEYS; ++i) {
        obj->cache[i].key = -1; // Mark unused entries with -1
        obj->cache[i].next = NULL;
        obj->cache[i].prev = NULL;
    }

    return obj;
}

// Function to get the value of a key from the LRUCache
int lRUCacheGet(LRUCache* obj, int key) {
    if (obj->cache[key].key == -1) {
        return -1; // Key not found
    }

    // Move the accessed node to the front
    Node* current = &obj->cache[key];
    if (current != obj->head) {
        if (current == obj->tail) {
            obj->tail = current->prev;
        } else {
            current->next->prev = current->prev;
        }

        current->prev->next = current->next;
        current->next = obj->head;
        current->prev = NULL;
        obj->head->prev = current;
        obj->head = current;
    }

    return current->value;
}

// Function to put a key-value pair into the LRUCache
void lRUCachePut(LRUCache* obj, int key, int value) {
    if (obj->cache[key].key != -1) {
        // Key exists, update the value and move the node to the front
        obj->cache[key].value = value;
        lRUCacheGet(obj, key); // Move the node to the front
    }
}

```

```

} else {
    // Key doesn't exist, create a new node and add it to the front
    Node* newNode = &obj->cache[key];
    newNode->key = key;
    newNode->value = value;
    newNode->next = obj->head;
    newNode->prev = NULL;

    if (obj->head != NULL) {
        obj->head->prev = newNode;
    }

    obj->head = newNode;

    if (obj->tail == NULL) {
        obj->tail = newNode;
    }

    // If the cache is full, remove the least recently used element
    if (obj->size == obj->capacity) {
        Node* tailPrev = obj->tail->prev;
        obj->cache[obj->tail->key].key = -1; // Mark the entry as unused
        obj->tail = tailPrev;

        if (obj->tail != NULL) {
            obj->tail->next = NULL;
        }
    } else {
        obj->size++;
    }
}

// Function to free the memory used by the LRUCache
void lRUCacheFree(LRUCache* obj) {
    // No dynamic memory to free in this implementation
    free(obj);
}

// Main function for testing the LRUCache implementation
int main() {
    // Create an LRUCache with a capacity of 2
    LRUCache* cache = lRUCacheCreate(2);

    // Put some key-value pairs into the cache
    lRUCachePut(cache, 1, 1);
    lRUCachePut(cache, 2, 2);

    // Retrieve and print the value associated with key 1
}

```

```

    printf("Value for key 1: %d\n", lRUCacheGet(cache, 1));

    // Put a new key-value pair into the cache, causing eviction of the least recently
    // used item (key 2)
    lRUCachePut(cache, 3, 3);

    // Attempt to retrieve the value associated with evicted key 2
    printf("Value for key 2 after eviction: %d\n", lRUCacheGet(cache, 2)); // Should
print -1

    lRUCachePut(cache, 4, 4);
    printf("Value for key 1 after eviction: %d\n", lRUCacheGet(cache, 1));
    printf("Value for key 3 after eviction: %d\n", lRUCacheGet(cache, 3));
    printf("Value for key 3 after eviction: %d\n", lRUCacheGet(cache, 4));
    // Free the memory used by the LRUCache
    lRUCacheFree(cache);

    return 0;
}

```

Output:

```

LRUCache lRUCache = new LRUCache(2);
lRUCache.put(1, 1); // cache is {1=1}
lRUCache.put(2, 2); // cache is {1=1, 2=2}
lRUCache.get(1); // return 1
lRUCache.put(3, 3); // LRU key was 2, evicts key 2, cache is {1=1, 3=3}
lRUCache.get(2); // returns -1 (not found)
lRUCache.put(4, 4); // LRU key was 1, evicts key 1, cache is {4=4, 3=3}
lRUCache.get(1); // return -1 (not found)
lRUCache.get(3); // return 3
lRUCache.get(4); // return 4

```

Time/Space Complexity: O(1)/O(K)

1.3 LFU Cache

```

#include <stdlib.h>
#include <stdio.h>

// Define the Node struct
typedef struct Node {
    int key, val, cnt;
    struct Node *next, *prev;
} Node;

// Define the List struct
typedef struct List {
    int len;
    Node *head, *tail;
} List;

// Define the LFUCache struct

```

```

typedef struct LFUCache {
    int minFreq, currSize, cacheCapacity;
    struct Node* addrOfKey[100000]; // Assuming the key range is within 10,0000
    struct List* freqListMap[100000]; // Assuming the key range is within 10,0000
} LFUCache;

// Create a new Node
Node* createNode(int key, int value) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->key = key;
    newNode->val = value;
    newNode->cnt = 1;
    newNode->next = NULL;
    newNode->prev = NULL;
    return newNode;
}

// Initialize a new List
List* createList() {
    List* newList = (List*)malloc(sizeof(List));
    newList->head = createNode(0, 0);
    newList->tail = createNode(0, 0);
    newList->head->next = newList->tail;
    newList->tail->prev = newList->head;
    newList->len = 0;
    return newList;
}

// Add a new Node to the List
void addNode(List* list, Node* newNode) {
    Node* temp = list->head->next;
    newNode->next = temp;
    newNode->prev = list->head;
    list->head->next = newNode;
    temp->prev = newNode;
    list->len++;
}

// Delete a Node from the List
void deleteNode(List* list, Node* delNode) {
    Node* delPrev = delNode->prev;
    Node* delNext = delNode->next;
    delPrev->next = delNext;
    delNext->prev = delPrev;
    list->len--;
}

// LFUCache constructor

```

```

LFUCache* lFUCacheCreate(int capacity) {
    LFUCache* obj = (LFUCache*)malloc(sizeof(LFUCache));
    obj->cacheCapacity = capacity;
    obj->minFreq = 0;
    obj->currSize = 0;
    for (int i = 0; i < 100000; i++) {
        obj->addrOfKey[i] = NULL;
        obj->freqListMap[i] = createList();
    }
    return obj;
}

// Get the value associated with the given key
int lFUCacheGet(LFUCache* obj, int key) {
    if (obj->addrOfKey[key] == NULL) {
        return -1;
    }
    Node* resNode = obj->addrOfKey[key];
    int res = resNode->val;
    int freq = resNode->cnt;
    // Update the frequency map
    deleteNode(obj->freqListMap[freq], resNode);
    if (obj->minFreq == freq && obj->freqListMap[freq]->len == 0) {
        obj->minFreq++;
    }
    resNode->cnt++;
    addNode(obj->freqListMap[freq + 1], resNode);
    obj->addrOfKey[key] = resNode;
    return res;
}

// Put a key-value pair into the LFUCache
void lFUCachePut(LFUCache* obj, int key, int value) {
    if (obj->cacheCapacity == 0) {
        return;
    }
    if (obj->addrOfKey[key] != NULL) {
        Node* existingNode = obj->addrOfKey[key];
        existingNode->val = value;
        int freq = existingNode->cnt;
        deleteNode(obj->freqListMap[freq], existingNode);
        if (obj->minFreq == freq && obj->freqListMap[freq]->len == 0) {
            obj->minFreq++;
        }
        existingNode->cnt++;
        addNode(obj->freqListMap[freq + 1], existingNode);
        obj->addrOfKey[key] = existingNode;
    } else {
        if (obj->currSize == obj->cacheCapacity) {

```

```

        List* list = obj->freqListMap[obj->minFreq];
        Node* prevNode = list->tail->prev;
        int keyToBeErased = prevNode->key;
        obj->addrOfKey[keyToBeErased] = NULL;
        deleteNode(list, prevNode);
        obj->currSize--;
    }
    obj->currSize++;
    obj->minFreq = 1;
    Node* newNode = createNode(key, value);
    addNode(obj->freqListMap[obj->minFreq], newNode);
    obj->addrOfKey[key] = newNode;
}
}

// Free the memory used by the LFUCache
void lFUCacheFree(LFUCache* obj) {
    for (int i = 0; i < 100000; i++) {
        if (obj->freqListMap[i] != NULL) {
            free(obj->freqListMap[i]->head);
            free(obj->freqListMap[i]->tail);
            free(obj->freqListMap[i]);
        }
    }
    free(obj);
}

int main() {
    LFUCache* cache = lFUCacheCreate(2);
    lFUCachePut(cache, 1, 1);
    lFUCachePut(cache, 2, 2);
    printf("%d\n", lFUCacheGet(cache, 1)); // returns 1
    lFUCachePut(cache, 3, 3);           // evicts key 2
    printf("%d\n", lFUCacheGet(cache, 2)); // returns -1 (not found)
    printf("%d\n", lFUCacheGet(cache, 3)); // returns 3.
    lFUCachePut(cache, 4, 4);           // evicts key 1.
    printf("%d\n", lFUCacheGet(cache, 1)); // returns -1 (not found)
    printf("%d\n", lFUCacheGet(cache, 3)); // returns 3
    printf("%d\n", lFUCacheGet(cache, 4)); // returns 4
    lFUCacheFree(cache);
    return 0;
}

```

["LFUCache", "put", "put", "get", "put", "get", "get", "put", "get", "get", "get", "get"]
 [[2], [1, 1], [2, 2], [1], [3, 3], [2], [3], [4, 4], [1], [3], [4]]

Output

[null, null, null, 1, null, -1, 3, null, -1, 3, 4]

Explanation

```
// cnt(x) = the use counter for key x
// cache=[] will show the last used order for tiebreakers (leftmost element is most recent)
LFUCache lfu = new LFUCache(2);
lfu.put(1, 1); // cache=[1,_], cnt(1)=1
lfu.put(2, 2); // cache=[2,1], cnt(2)=1, cnt(1)=1
lfu.get(1); // return 1
               // cache=[1,2], cnt(2)=1, cnt(1)=2
lfu.put(3, 3); // 2 is the LFU key because cnt(2)=1 is the smallest, invalidate 2.
                // cache=[3,1], cnt(3)=1, cnt(1)=2
lfu.get(2); // return -1 (not found)
lfu.get(3); // return 3
               // cache=[3,1], cnt(3)=2, cnt(1)=2
lfu.put(4, 4); // Both 1 and 3 have the same cnt, but 1 is LRU, invalidate 1.
                 // cache=[4,3], cnt(4)=1, cnt(3)=2
lfu.get(1); // return -1 (not found)
lfu.get(3); // return 3
               // cache=[3,4], cnt(4)=1, cnt(3)=3
lfu.get(4); // return 4
               // cache=[4,3], cnt(4)=2, cnt(3)=3
```

Time/Space Complexity: O(n)/O(1)

1.4 IP Address, Subnet, Network Address, Host

```
#include <stdio.h>
#include <stdint.h>
#include <netinet/in.h>
#include <arpa/inet.h>

// Function to calculate the network address
struct in_addr calculateNetworkAddress(struct in_addr ipAddr, struct in_addr netmask) {
    struct in_addr networkAddr;
    networkAddr.s_addr = ipAddr.s_addr & netmask.s_addr;
    return networkAddr;
}

// Function to calculate the broadcast address
struct in_addr calculateBroadcastAddress(struct in_addr networkAddr, struct in_addr netmask) {
    struct in_addr broadcastAddr;
    printf("%d : %u", ~netmask.s_addr, networkAddr.s_addr);
    broadcastAddr.s_addr = networkAddr.s_addr | ~netmask.s_addr;
    return broadcastAddr;
}

// Function to calculate the number of usable hosts
uint32_t calculateNumUsableHosts(uint32_t numHosts) {
    return numHosts - 2;
}
```

```

int main() {
    // IP address and subnet mask
    struct in_addr ipAddr, netmask;

    // Input IP address
    printf("Enter IP address in dotted decimal notation (e.g., 192.168.1.10): ");
    char ipAddrStr[INET_ADDRSTRLEN];
    fgets(ipAddrStr, INET_ADDRSTRLEN, stdin);
    inet_aton(ipAddrStr, &ipAddr);

    // Input subnet mask
    printf("Enter subnet mask in dotted decimal notation (e.g., 255.255.255.248): ");
    char netmaskStr[INET_ADDRSTRLEN];
    fgets(netmaskStr, INET_ADDRSTRLEN, stdin);
    inet_aton(netmaskStr, &netmask);

    // Calculate network address
    struct in_addr networkAddr = calculateNetworkAddress(ipAddr, netmask);

    // Calculate broadcast address
    struct in_addr broadcastAddr = calculateBroadcastAddress(networkAddr, netmask);

    // Calculate number of hosts
    uint32_t numHosts = ntohl(~netmask.s_addr) + 1;

    // Calculate number of usable hosts
    uint32_t numUsableHosts = calculateNumUsableHosts(numHosts);

    // Print the details
    printf("\nIP Address:\t%s\n", inet_ntoa(ipAddr));
    printf("Network Address:\t%s\n", inet_ntoa(networkAddr));
    printf("Usable Host IP Range:\t%s - %s\n", inet_ntoa(networkAddr),
        inet_ntoa(broadcastAddr));
    printf("Broadcast Address:\t%s\n", inet_ntoa(broadcastAddr));
    printf("Total Number of Hosts:\t%u\n", numHosts);
    printf("Number of Usable Hosts:\t%u\n", numUsableHosts);
    printf("Subnet Mask:\t%s\n", inet_ntoa(netmask));
    printf("IP Class:\tC\n");

    return 0;
}

```

1.5 IP address generation

```

#include <stdio.h>

// Function to generate IP addresses in a given network with multiple subnets
void generateIPAddresses(char network[], int numSubnets, int hostsPerSubnet) {
    int i, j;

```

```

// Loop through each subnet
for (i = 0; i < numSubnets; i++) {
    // Loop through the range of valid host addresses in each subnet
    for (j = 1; j <= hostsPerSubnet; j++) {
        // Print the generated IP addresses
        printf("%s.%d.%d\n", network, i + 1, j);

        // Check if the desired number of addresses is reached
        if (j == hostsPerSubnet) {
            break;
        }
    }
}

int main() {
    char network[] = "192.168";      // Example network address
    int numSubnets = 3;              // Number of subnets
    int hostsPerSubnet = 254;        // Number of hosts per subnet (excluding network and
                                    // broadcast addresses)

    // Generate IP addresses across multiple subnets
    generateIPAddresses(network, numSubnets, hostsPerSubnet);

    return 0;
}

#include <stdio.h>
#include <stdint.h>

// Function to convert a 32-bit unsigned integer to dotted-decimal IP format
void printIPAddress(uint32_t ipAddress) {
    printf("%u.%u.%u.%u", (ipAddress >> 24) & 0xFF, (ipAddress >> 16) & 0xFF, (ipAddress
>> 8) & 0xFF, ipAddress & 0xFF);
}

// Function to generate and print IP addresses within a given subnet
void generateIPAddresses(uint32_t ipAddress, uint32_t subnetMask, int numAddresses) {
    // Calculate the network address
    uint32_t networkAddress = ipAddress & subnetMask;

    // Calculate the number of hosts in the subnet (excluding network and broadcast
    // addresses)
    int hostsInSubnet = (1 << (32 - __builtin_popcount(subnetMask)));

    // Print the generated IP addresses
    printf("Network Address: ");
    printIPAddress(networkAddress);
}

```

```

printf("\nNumber of Hosts in Subnet: %d\n", hostsInSubnet);

for (int i = 1; i <= numAddresses; i++) {
    if (i >= hostsInSubnet) {
        printf("Exhausted available hosts in subnet.\n");
        break;
    }

    uint32_t generatedIP = networkAddress + i;
    printf("Generated IP Address %d: ", i);
    printIPAddress(generatedIP);
    printf("\n");
}
}

int main() {
    uint32_t ipAddress = 0xC0A80101; // Example IP address: 192.168.1.1 (in
hexadecimal)
    uint32_t subnetMask = 0xFFFFF00; // Example subnet mask: 255.255.255.0 (in
hexadecimal)
    int numAddresses = 300; // Number of IP addresses to generate

    generateIPAddresses(ipAddress, subnetMask, numAddresses);

    return 0;
}

```

1.6 Validity Of IP Address

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Function to check if a string is a valid IP address
int isValidIPAddress(char *ipAddress) {
    int num, dots = 0;
    int len = strlen(ipAddress);

    // Check for empty string
    if (len == 0) {
        return 0;
    }

    // Count the number of dots in the IP address
    for (int i = 0; i < len; i++) {
        if (ipAddress[i] == '.') {
            dots++;
        }
    }
}

```

```

// An IP address should have exactly three dots
if (dots != 3) {
    return 0;
}

// Tokenize the string based on dots
char *token = strtok(ipAddress, ".");

// Check each token
while (token != NULL) {
    // Convert the token to an integer
    num = atoi(token);

    // Check if the integer is between 0 and 255 (inclusive)
    if (num < 0 || num > 255) {
        return 0;
    }

    // Check for leading zeros in each token
    if (num != 0 && token[0] == '0') {
        return 0;
    }

    // Move to the next token
    token = strtok(NULL, ".");
}

// If token is NULL and there should be more tokens, return 0
if (token == NULL && dots != 0) {
    return 0;
}
}

// If everything is fine, return 1 (valid IP address)
return 1;
}

int main() {
    char ipAddress[20]; // Assuming a maximum length of 20 characters for the IP
address

    // Get the input from the user
    printf("Enter an IP address: ");
    scanf("%s", ipAddress);

    // Check the validity of the IP address
    if (isValidIPAddress(ipAddress)) {
        printf("The entered IP address (%s) is valid.\n", ipAddress);
    } else {
        printf("The entered IP address (%s) is not valid.\n", ipAddress);
    }
}

```

```
    }

    return 0;
}
```

1.7 Packet Parser

```
#include <stdio.h>
#include <stdint.h>
#include <arpa/inet.h>

// Ethernet header structure
struct EthernetHeader {
    uint8_t destMAC[6];
    uint8_t srcMAC[6];
    uint16_t etherType;
};

// IPv4 header structure
struct IPv4Header {
    uint8_t versionIHL;
    uint8_t dscpECN;
    uint16_t totalLength;
    uint16_t identification;
    uint16_t flagsFragmentOffset;
    uint8_t timeToLive;
    uint8_t protocol;
    uint16_t headerChecksum;
    uint32_t srcIP;
    uint32_t destIP;
};

// TCP header structure
struct TCPHeader {
    uint16_t srcPort;
    uint16_t destPort;
    uint32_t sequenceNumber;
    uint32_t ackNumber;
    uint8_t dataOffsetReserved;
    uint8_t flags;
    uint16_t windowSize;
    uint16_t checksum;
    uint16_t urgentPointer;
};

void processEthernetFrame(const uint8_t* frame, uint16_t frameLength);
void processIPv4Packet(const uint8_t* packet, uint16_t packetLength);
void processTCPHeader(const uint8_t* tcpHeader, uint16_t tcpHeaderLength);
void processApplicationData(const uint8_t* data, uint16_t dataLength);
```

```

void printMACAddress(const uint8_t* mac) {
    printf("%02x:%02x:%02x:%02x:%02x:%02x", mac[0], mac[1], mac[2], mac[3], mac[4],
mac[5]);
}

int main() {
    // Example Ethernet frame containing IPv4, TCP, and application data
    uint8_t frame[] = {
        // Ethernet header
        0x00, 0x11, 0x22, 0x33, 0x44, 0x55, // Source MAC
        0x66, 0x77, 0x88, 0x99, 0xAA, 0xBB, // Destination MAC
        0x08, 0x00, // EtherType (IPv4)
        // IPv4 header
        0x45, 0x00, 0x00, 0x3C, 0x12, 0x34, 0x40, 0x00, 0x40, 0x06, 0x00, 0x00,
        0xC0, 0xA8, 0x01, 0x01, // Source IP: 192.168.1.1
        0xC0, 0xA8, 0x01, 0x02, // Destination IP: 192.168.1.2
        // TCP header
        0x00, 0x50, 0x00, 0x37, 0xB8, 0xA0, 0x00, 0x00, 0x00, 0x00, 0xA0, 0x02,
        0xFA, 0xF0, 0x00, 0x00, 0x02, 0x04, 0x05, 0xB4, 0x01, 0x03, 0x03, 0x06,
        // Application data (HTTP request)
        0x47, 0x45, 0x54, 0x20, 0x2F, 0x20, 0x48, 0x54, 0x54, 0x50, 0x2F, 0x31,
        0x2E, 0x31, 0x0D, 0x0A, 0x48, 0x6F, 0x73, 0x74, 0x3A, 0x20, 0x77, 0x77,
        // ... (HTTP request continues)
    };
}

processEthernetFrame(frame, sizeof(frame));

return 0;
}

void processEthernetFrame(const uint8_t* frame, uint16_t frameLength) {
    if (frameLength < sizeof(struct EthernetHeader)) {
        printf("Invalid Ethernet frame\n");
        return;
    }

    struct EthernetHeader* ethHeader = (struct EthernetHeader*)frame;

    printf("Ethernet Frame - Source MAC: ");
    printMACAddress(ethHeader->srcMAC);
    printf(", Destination MAC: ");
    printMACAddress(ethHeader->destMAC);
    printf(", EtherType: %04x\n", ntohs(ethHeader->etherType));

    // Assuming Ethernet frame contains IPv4 packet
    if (ntohs(ethHeader->etherType) == 0x0800) {
        processIPv4Packet(frame + sizeof(struct EthernetHeader), frameLength -
        sizeof(struct EthernetHeader));
    } else {

```

```

        printf("Unsupported EtherType: %04x\n", ntohs(ethHeader->etherType));
    }

}

void processIPv4Packet(const uint8_t* packet, uint16_t packetLength) {
    if (packetLength < sizeof(struct IPv4Header)) {
        printf("Invalid IPv4 packet\n");
        return;
    }

    struct IPv4Header* ipv4Header = (struct IPv4Header*)packet;
    printf("IPv4 Packet - Source IP: %s, Destination IP: %s\n",
           inet_ntoa(*(struct in_addr*)&ipv4Header->srcIP), inet_ntoa(*((struct
in_addr*)&ipv4Header->destIP)));

    // Assuming IPv4 packet contains TCP header
    processTCPHeader(packet + (ipv4Header->versionIHL & 0x0F) * 4, packetLength -
(ipv4Header->versionIHL & 0x0F) * 4);
}

void processTCPHeader(const uint8_t* tcpHeader, uint16_t tcpHeaderLength) {
    if (tcpHeaderLength < sizeof(struct TCPHeader)) {
        printf("Invalid TCP header\n");
        return;
    }

    struct TCPHeader* tcpHeaderStruct = (struct TCPHeader*)tcpHeader;
    printf("TCP Header - Source Port: %u, Destination Port: %u\n",
           ntohs(tcpHeaderStruct->srcPort), ntohs(tcpHeaderStruct->destPort));

    // Assuming TCP header contains application data
    processApplicationData(tcpHeader + (tcpHeaderStruct->dataOffsetReserved >> 4) * 4,
tcpHeaderLength - (tcpHeaderStruct->dataOffsetReserved >> 4) * 4);
}

void processApplicationData(const uint8_t* data, uint16_t dataLength) {
    // Add code to process application-specific data
    printf("Application Data (%u bytes):\n", dataLength);
    for (uint16_t i = 0; i < dataLength; ++i) {
        printf("%c", data[i]);
    }
    printf("\n");
}

```

1.8 Store IP address

```

#include<stdio.h>
typedef struct ip_address {
    unsigned char ip[4];
} ip_addr_t;

```

```

void store_ip(char *input_ip, ip_addr_t *ip) {
    sscanf(input_ip, "%hu.%hu.%hu.%hu", &ip->ip[0], &ip->ip[1], &ip->ip[2], &ip->ip[3]);
    printf("\nStored ip is : %hu.%hu.%hu.%hu", ip->ip[0], ip->ip[1], ip->ip[2], ip->ip[3]);
}
void retrieve_ip(char *output_ip, ip_addr_t *ip) {
    sprintf(output_ip, "%hu.%hu.%hu.%hu", ip->ip[0], ip->ip[1], ip->ip[2], ip->ip[3]);
}
void main() {
    char input_ip[15];
    char output_ip[15];
    ip_addr_t stored_ip;
    printf("\nEnter an ip address : ");
    scanf("%s", input_ip);
    printf("\nInput ip address is : %s", input_ip);
    store_ip(&input_ip, &stored_ip);
    retrieve_ip(&output_ip, &stored_ip);
    printf("\nRetrieved ip address is : %s", output_ip);
}

```

1.9 Store MAC address

```

#include<stdio.h>
typedef struct mac_address {
    unsigned char mac[6];
} mac_addr_t;
void store_mac(char *input_mac, mac_addr_t *mac) {
    printf("\naddress of mac %p", &mac);
    printf("\naddress of mac->mac[0] %p", &mac->mac[0]);
    sscanf(input_mac, "%hhx:%hhx:%hhx:%hhx:%hhx:%hhx", &mac->mac[0], &mac->mac[1], &mac->mac[2], &mac->mac[3], &mac->mac[4], &mac->mac[5]);
    printf("\nStored mac is : %02x:%02x:%02x:%02x:%02x:%02x", mac->mac[0], mac->mac[1], mac->mac[2], mac->mac[3], mac->mac[4], mac->mac[5]);
}
void retrieve_mac(char *output_mac, mac_addr_t *mac) {
    sprintf(output_mac, "%hhx:%hhx:%hhx:%hhx:%hhx:%hhx", mac->mac[0], mac->mac[1], mac->mac[2], mac->mac[3], mac->mac[4], mac->mac[5]);
}
void main() {
    char input_mac[18];
    char output_mac[18];
    mac_addr_t stored_mac;
    printf("\nEnter a mac address : ");
    scanf("%s", input_mac);
    printf("\nInput mac address is : %s", input_mac);
    store_mac(&input_mac, &stored_mac);
    printf("\naddress of stored mac %p", &stored_mac);
    printf("\naddress of stored mac->mac[0] %p", &stored_mac.mac[0]);
    retrieve_mac(&output_mac, &stored_mac);
}

```

```
    printf("\nRetrieved mac address is : %s",output_mac);
}
```

1.10 Basic Firewall Implementation

```
#include <stdio.h>
#include <pcap.h>
#include <stdlib.h>
#include <string.h>

#define MAX_PACKET_SIZE 1500

// IP address structure
typedef struct {
    unsigned char octet1;
    unsigned char octet2;
    unsigned char octet3;
    unsigned char octet4;
} IPAddress;

// Rule structure
typedef struct {
    IPAddress source_ip;
    IPAddress destination_ip;
    int source_port;
    int destination_port;
    int allow; // 1 for allow, 0 for deny
} FirewallRule;

// Function to check if a packet matches a firewall rule
int packet_matches_rule(const unsigned char* packet, const FirewallRule* rule) {
    // Assuming Ethernet frames
    int ethernet_header_length = 14;

    // Assuming IPv4 packets
    int ip_header_length = (packet[ethernet_header_length] & 0x0F) * 4;

    // Extract source and destination IP addresses
    IPAddress source_ip = {
        packet[ethernet_header_length + 12],
        packet[ethernet_header_length + 13],
        packet[ethernet_header_length + 14],
        packet[ethernet_header_length + 15]
    };

    IPAddress destination_ip = {
        packet[ethernet_header_length + ip_header_length + 12],
        packet[ethernet_header_length + ip_header_length + 13],
        packet[ethernet_header_length + ip_header_length + 14],
        packet[ethernet_header_length + ip_header_length + 15]
    }
```

```

};

// Assuming TCP packets
int tcp_header_length = ((packet[ethernet_header_length + ip_header_length + 12] &
0xF0) >> 4) * 4;

// Extract source and destination ports
int source_port = (packet[ethernet_header_length + ip_header_length + 20] << 8) |
packet[ethernet_header_length + ip_header_length + 21];
int destination_port = (packet[ethernet_header_length + ip_header_length + 22] << 8)
| packet[ethernet_header_length + ip_header_length + 23];

// Check if the packet matches the rule
return (memcmp(&source_ip, &rule->source_ip, sizeof(IPAddress)) == 0 &&
memcmp(&destination_ip, &rule->destination_ip, sizeof(IPAddress)) == 0 &&
source_port == rule->source_port &&
destination_port == rule->destination_port);
}

// Function to process each packet
void packet_handler(unsigned char* user, const struct pcap_pkthdr* pkthdr, const
unsigned char* packet) {
FirewallRule* rule = (FirewallRule*)user;

// Check if the packet matches the rule
if (packet_matches_rule(packet, rule)) {
    if (rule->allow) {
        printf("Allowed packet\n");
    } else {
        printf("Blocked packet\n");
    }
} else {
    printf("Passing through\n");
}
}

int main() {
char errbuf[PCAP_ERRBUF_SIZE];
pcap_t* handle;

// Open the network interface for packet capture
handle = pcap_open_live("your_network_interface", MAX_PACKET_SIZE, 1, 1000, errbuf);
if (handle == NULL) {
    fprintf(stderr, "Couldn't open device: %s\n", errbuf);
    return 2;
}

// Set a packet filter to capture all traffic
struct bpf_program fp;

```

```

    char filter_exp[] = "tcp or udp or icmp";
    if (pcap_compile(handle, &fp, filter_exp, 0, PCAP_NETMASK_UNKNOWN) == -1) {
        fprintf(stderr, "Couldn't parse filter %s: %s\n", filter_exp,
pcap_geterr(handle));
        return 2;
    }
    if (pcap_setfilter(handle, &fp) == -1) {
        fprintf(stderr, "Couldn't install filter %s: %s\n", filter_exp,
pcap_geterr(handle));
        return 2;
    }

    // Define a firewall rule (Example: Allow TCP traffic from source IP 192.168.1.2 to
destination IP 192.168.1.1 on port 80)
    FirewallRule rule;
    rule.source_ip = (IPAddress){192, 168, 1, 2};
    rule.destination_ip = (IPAddress){192, 168, 1, 1};
    rule.source_port = 0; // Any source port
    rule.destination_port = 80;
    rule.allow = 1; // Allow the specified traffic

    // Start capturing packets
    pcap_loop(handle, 0, packet_handler, (unsigned char*)&rule);

    // Close the handle
    pcap_close(handle);

    return 0;
}

```

1.11 Rate Limiter

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <unistd.h>

#define TOKEN_RATE_LIMIT 5
#define BUCKET_CAPACITY 10

struct TokenBucket {
    int tokens;
    pthread_mutex_t mutex;
    pthread_cond_t tokenAdded;
};

void initTokenBucket(struct TokenBucket* bucket) {
    bucket->tokens = BUCKET_CAPACITY;
    pthread_mutex_init(&bucket->mutex, NULL);
    pthread_cond_init(&bucket->tokenAdded, NULL);
}

```

```

}

void* tokenRefill(void* tokenBucket) {
    struct TokenBucket* bucket = (struct TokenBucket*)tokenBucket;

    while (1) {
        usleep(1000000 / TOKEN_RATE_LIMIT);

        pthread_mutex_lock(&bucket->mutex);
        if (bucket->tokens < BUCKET_CAPACITY) {
            bucket->tokens++;
            printf("Token added: %d\n", bucket->tokens);

            // Signal that a token has been added
            pthread_cond_signal(&bucket->tokenAdded);
        }
        pthread_mutex_unlock(&bucket->mutex);
    }
}

void processRequest(struct TokenBucket* bucket, int requestId) {
    pthread_mutex_lock(&bucket->mutex);

    // Wait until a token is available
    while (bucket->tokens <= 0) {
        printf("Request %d waiting for token...\n", requestId);
        pthread_cond_wait(&bucket->tokenAdded, &bucket->mutex);
    }

    // Token is available, process the request
    bucket->tokens--;
    pthread_mutex_unlock(&bucket->mutex);

    printf("Request %d processed\n", requestId);
}

int main() {
    struct TokenBucket tokenBucket;
    initTokenBucket(&tokenBucket);

    pthread_t refillThread;
    pthread_create(&refillThread, NULL, tokenRefill, (void*)&tokenBucket);

    // Simulate requests
    for (int i = 1; i <= 20; i++) {
        processRequest(&tokenBucket, i);
        usleep(200000);
    }
}

```

```

    // Cancel the token refill thread
    pthread_cancel(refillThread);
    pthread_join(refillThread, NULL);

    return 0;
}

```

1.12 Longest Prefix Match - IP

```

#include <stdio.h>
#include <stdint.h>
#include <arpa/inet.h>

typedef struct {
    char network[20];
    int subnet;
} CIDR;

void findLongestPrefixMatch(CIDR cidrList[], int n, char* inputIP) {
    uint32_t input = ntohl(inet_addr(inputIP)); // Convert input IP to integer,
consider network byte order

    int maxPrefixLength = -1;
    char* matchingCIDR = NULL;

    for (int i = 0; i < n; ++i) {
        uint32_t network = ntohl(inet_addr(cidrList[i].network)); // Convert network IP
to integer
        uint32_t subnetMask = ~(1u << (32 - cidrList[i].subnet)) - 1;
        uint32_t subnetMask = (0xFFFFFFFFu << (32 - cidrList[i].subnet));
        if ((input & subnetMask) == (network & subnetMask)) {
            if (cidrList[i].subnet > maxPrefixLength) {
                maxPrefixLength = cidrList[i].subnet;
                matchingCIDR = cidrList[i].network;
            }
        }
    }

    if (matchingCIDR != NULL) {
        printf("Longest Prefix Match: %s/%d\n", matchingCIDR, maxPrefixLength);
    } else {
        printf("No match found.\n");
    }
}

int main() {
    CIDR cidrList[] = {{"192.168.1.0", 24}, {"10.0.0.0", 16}, {"172.16.0.0", 20}};
    char inputIP[] = "192.168.1.15";
}

```

```

        findLongestPrefixMatch(cidrList, sizeof(cidrList) / sizeof(cidrList[0])), inputIP);

    return 0;
}

```

1.13 Trie

```

#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h> // Include for bool data type

// Define TrieNode structure
typedef struct TrieNode {
    struct TrieNode* children[26];
    bool isEndOfWord;
} TrieNode;

// Define Trie structure
typedef struct {
    TrieNode* root;
} Trie;

// Function to create a new TrieNode
TrieNode* createNode() {
    TrieNode* newNode = (TrieNode*)malloc(sizeof(TrieNode));
    for (int i = 0; i < 26; i++) {
        newNode->children[i] = NULL;
    }
    newNode->isEndOfWord = false;
    return newNode;
}

// Initialize the Trie
Trie* trieCreate() {
    Trie* trie = (Trie*)malloc(sizeof(Trie));
    trie->root = createNode();
    return trie;
}

// Insert a word into the Trie
void trieInsert(Trie* obj, char* word) {
    TrieNode* node = obj->root;
    while (*word) {
        int index = *word - 'a';
        if (node->children[index] == NULL) {
            node->children[index] = createNode();
        }

```

```

        node = node->children[index];
        word++;
    }
    node->isEndOfWord = true;
}

// Search for a word in the Trie
bool trieSearch(Trie* obj, char* word) {
    TrieNode* node = obj->root;
    while (*word) {
        int index = *word - 'a';
        if (node->children[index] == NULL) {
            return false;
        }
        node = node->children[index];
        word++;
    }
    return node->isEndOfWord;
}

// Check if a prefix exists in the Trie
bool trieStartsWith(Trie* obj, char* prefix) {
    TrieNode* node = obj->root;
    while (*prefix) {
        int index = *prefix - 'a';
        if (node->children[index] == NULL) {
            return false;
        }
        node = node->children[index];
        prefix++;
    }
    return true;
}

// Free the Trie memory
void trieFree(Trie* obj) {
    // Use recursive helper function to free Trie nodes
    void freeNode(TrieNode* node) {
        if (node == NULL) {
            return;
        }
        for (int i = 0; i < 26; i++) {
            freeNode(node->children[i]);
        }
        free(node);
    }

    freeNode(obj->root);
    free(obj);
}

```

```

}

// Function to print all words stored in the Trie
void printTrieHelper(TrieNode* node, char* buffer, int depth) {
    // Base case: If node is NULL, return
    if (node == NULL) {
        return;
    }

    // If current node is end of a word, print the word
    if (node->isEndOfWord) {
        buffer[depth] = '\0'; // Null-terminate the buffer
        printf("%s\n", buffer);
    }

    // Recursively traverse children nodes
    for (int i = 0; i < 26; i++) {
        if (node->children[i] != NULL) {
            buffer[depth] = 'a' + i; // Add current character to buffer
            printTrieHelper(node->children[i], buffer, depth + 1);
        }
    }
}

void printTrie(Trie* trie) {
    char buffer[100]; // Assuming maximum word length is 100
    printTrieHelper(trie->root, buffer, 0);
}

int main() {
    Trie* trie = trieCreate();

    // Example usage
    trieInsert(trie, "apple");
    printf("Search for 'apple': %s\n", trieSearch(trie, "apple") ? "Found" : "Not found");
    printf("Search for 'app': %s\n", trieSearch(trie, "app") ? "Found" : "Not found");
    printf("Starts with 'app': %s\n", trieStartsWith(trie, "app") ? "True" : "False");
    trieInsert(trie, "app");
    printf("Search for 'app' after insertion: %s\n", trieSearch(trie, "app") ? "Found" : "Not found");

    // Free memory
    trieFree(trie);

    return 0;
}

```

1.14 Calculator using Tree

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <ctype.h>

// Define structure for expression tree node
typedef struct TreeNode {
    char data;
    struct TreeNode* left;
    struct TreeNode* right;
} TreeNode;

// Function to create a new node
TreeNode* createNode(char data) {
    TreeNode* newNode = (TreeNode*)malloc(sizeof(TreeNode));
    newNode->data = data;
    newNode->left = newNode->right = NULL;
    return newNode;
}

// Function to check if a character is an operator
bool isOperator(char c) {
    return (c == '+' || c == '-' || c == '*' || c == '/');
}

// Function to build expression tree from postfix expression
TreeNode* buildExpressionTree(char postfix[]) {
    TreeNode* stack[100]; // Assuming the expression won't exceed 100 characters
    int top = -1;

    for (int i = 0; postfix[i] != '\0'; i++) {
        TreeNode* newNode = createNode(postfix[i]);

        if (!isOperator(postfix[i])) {
            stack[++top] = newNode;
        } else {
            newNode->right = stack[top--];
            newNode->left = stack[top--];
            stack[++top] = newNode;
        }
    }

    return stack[top];
}

// Function to evaluate expression tree
int evaluate(TreeNode* root) {
    if (root == NULL) {
```

```

        return 0;
    }
    if (!isOperator(root->data)) {
        return root->data - '0'; // Convert char to int
    }

    int leftValue = evaluate(root->left);
    int rightValue = evaluate(root->right);

    switch (root->data) {
        case '+': return leftValue + rightValue;
        case '-': return leftValue - rightValue;
        case '*': return leftValue * rightValue;
        case '/': return leftValue / rightValue;
        default: return 0;
    }
}

int main() {
    char postfix[100];
    printf("Enter postfix expression: ");
    scanf("%s", postfix);

    TreeNode* root = buildExpressionTree(postfix);

    int result = evaluate(root);
    printf("Result: %d\n", result);

    return 0;
}

```

1.15 Balanced Binary Tree

```

#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h> // Include the bool type

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Helper function to calculate the height of a subtree
int getHeight(struct TreeNode* root) {
    if (root == NULL) {
        return 0;
    }

```

```

        int leftHeight = getHeight(root->left);
        int rightHeight = getHeight(root->right);
        return 1 + (leftHeight > rightHeight ? leftHeight : rightHeight);
    }

    // Main function to check if the binary tree is height-balanced
    bool isBalanced(struct TreeNode* root) {
        if (root == NULL) {
            return true; // An empty tree is height-balanced
        }

        int leftHeight = getHeight(root->left);
        int rightHeight = getHeight(root->right);

        // Check if the height difference of left and right subtrees is more than 1
        if (abs(leftHeight - rightHeight) > 1) {
            return false;
        }

        // Recursively check if both left and right subtrees are height-balanced
        return isBalanced(root->left) && isBalanced(root->right);
    }

    // Function to create a new tree node
    struct TreeNode* createNode(int val) {
        struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
        newNode->val = val;
        newNode->left = NULL;
        newNode->right = NULL;
        return newNode;
    }

    // Function to free memory allocated for the tree
    void freeTree(struct TreeNode* root) {
        if (root == NULL) {
            return;
        }
        freeTree(root->left);
        freeTree(root->right);
        free(root);
    }

int main() {
    // Create a sample binary tree
    struct TreeNode* root = createNode(1);
    root->left = createNode(2);
    root->right = createNode(3);
    root->left->left = createNode(4);
    root->left->right = createNode(5);
}

```

```

root->right->left = createNode(6);
root->right->right = createNode(7);

// Check if the binary tree is height-balanced
if (isBalanced(root)) {
    printf("The binary tree is height-balanced.\n");
} else {
    printf("The binary tree is not height-balanced.\n");
}

freeTree(root);
// Create a sample binary tree
root = createNode(1);
root->left = createNode(2);
root->right = createNode(2);
root->left->left = createNode(3);
root->left->right = createNode(3);
root->left->right->left = createNode(6);
root->left->right->right = createNode(7);

// Check if the binary tree is height-balanced
if (isBalanced(root)) {
    printf("The binary tree is height-balanced.\n");
} else {
    printf("The binary tree is not height-balanced.\n");
}

// Free memory allocated for the binary tree
freeTree(root);

return 0;
}

```

Time/Space Complexity: O(n^2)/O(n)

1.16 Time Needed To Inform All Employees

```

#include <stdio.h>
#include <stdlib.h>
#include <math.h>

typedef struct Node {
    int val;
    struct Node* next;
} Node;

typedef struct {
    Node* head;
} List;

```

```

List* createList() {
    List* list = (List*)malloc(sizeof(List));
    list->head = NULL;
    return list;
}

void printList(List* list) {
    Node* current = list->head;

    while (current != NULL) {
        printf("%d ", current->val);
        current = current->next;
    }

    printf("\n");
}

void addToList(List* list, int val) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    newNode->val = val;
    newNode->next = list->head;
    list->head = newNode;
}

int helper(int* informTime, List** list, int curr) {
    printf("\ncurr : %d", curr);
    if (list[curr] == NULL) return 0;

    int min = 0;
    Node* current = list[curr]->head;

    while (current != NULL) {
        min = fmax(helper(informTime, list, current->val), min);
        current = current->next;
    }

    return min + informTime[curr];
}

int numOfMinutes(int n, int headID, int* manager, int managerSize, int* informTime, int
informTimeSize) {
    List** list = (List**)malloc(n * sizeof(List*));

    for (int i = 0; i < n; i++) {
        list[i] = createList();
    }

    for (int i = 0; i < n; i++) {
        if (manager[i] != -1) {

```

```

        addToList(list[manager[i]], i);
    }
}
for (int i = 0; i < n; i++) {
    printf("\ni = %d", i);
    printList(list[i]);
}
int result = helper(informTime, list, headID);

for (int i = 0; i < n; i++) {
    free(list[i]);
}

free(list);

return result;
}

int main() {
    int n = 6;
    int headID = 2;
    int manager[] = {2, 2, -1, 2, 2, 2};
    int informTime[] = {0, 0, 1, 0, 0, 0};

    int result = numOfMinutes(n, headID, manager, sizeof(manager) / sizeof(manager[0]),
informTime, sizeof(informTime) / sizeof(informTime[0]));

    printf("Time taken for all employees to receive the information: %d minutes\n",
result);

    return 0;
}

```

Output: 1 minute

Time/Space Complexity : O(n^2)/O(n)

1.17 Distribute Coins In Binary Tree

```

#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Function to create a new TreeNode
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));

```

```

node->val = val;
node->left = NULL;
node->right = NULL;
return node;
}

// Helper function to perform DFS and calculate the number of moves required
int helper(struct TreeNode* root, int* moves) {
    if (root == NULL)
        return 0;

    // Recursively traverse left and right subtrees
    int coinsLeft = helper(root->left, moves);
    int coinsRight = helper(root->right, moves);

    // Calculate total coins for the current subtree
    int coins = coinsLeft + coinsRight;

    // Adjust coins based on the current node's value
    if (root->val == 0)
        coins -= 1;
    else if (root->val == 1)
        coins += 0;
    else
        coins += root->val - 1;

    // Update the number of moves required
    *moves += abs(coins);

    return coins;
}

// Function to distribute coins in the binary tree and return the total number of moves
// required
int distributeCoins(struct TreeNode* root) {
    int moves = 0;
    helper(root, &moves);
    return moves;
}

// Main function for testing
int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(3);
    root->left = newNode(0);
    root->right = newNode(0);
    //root->left->right = newNode(3);

    // Distribute coins and calculate the number of moves required
}

```

```

    int moves = distributeCoins(root);
    printf("Total moves required to distribute coins: %d\n", moves);

    // Free dynamically allocated memory for the binary tree
    // (Not included in the original implementation as it doesn't involve dynamic memory
    allocation)
    free(root->left->right);
    free(root->left);
    free(root->right);
    free(root);

    return 0;
}

```

Output: 2

Time/Space Complexity: O(n)/O(n) or O(log n)

1.18 Find Original Array From Doubled Array

```

#include <stdio.h>
#include <stdlib.h>

int* findOriginalArray(int* changed, int changedSize, int* returnSize) {
    *returnSize = 0;

    int n = changedSize;
    if (n % 2 == 1) {
        return NULL;
    }

    int* ans = (int*)malloc((n / 2) * sizeof(int));
    int idx = 0;
    int* freq = (int*)calloc(100005, sizeof(int));

    for (int i = 0; i < n; i++) {
        freq[changed[i]]++;
    }

    for (int num = 100000; num >= 0; num--) {
        while (freq[num]-- > 0) {
            if ((num & 1) == 1) {
                free(ans);
                free(freq);
                return NULL;
            }
        }
    }

    int div = num / 2;

    if (freq[div] == 0) {
        free(ans);
        free(freq);
    }
}
```

```

        return NULL;
    }

    ans[idx++] = div;
    freq[div]--;
}
}

*returnSize = idx;
return ans;
}

int main() {
    int changed[] = {1, 3, 4, 2, 6, 8};
    int changedSize = sizeof(changed) / sizeof(changed[0]);
    int returnSize;
    int* originalArray = findOriginalArray(changed, changedSize, &returnSize);

    if (originalArray == NULL) {
        printf("No original array found!\n");
    } else {
        printf("Original array: ");
        for (int i = 0; i < returnSize; i++) {
            printf("%d ", originalArray[i]);
        }
        printf("\n");

        // Free dynamically allocated memory for the original array
        free(originalArray);
    }

    return 0;
}

```

Output: 4,3,1 or 1,3,4
Time/Space Complexity : $O(n)/O(1)$

1.19 Sum Of SubArray Minimums

```

#include <stdio.h>
#include <stdlib.h>

int ind = 0;
int *ssize;

// Function to count the number of subarrays for given array size
int countSubarrays(int size) {
    return (size * (size + 1)) / 2;
}

```

```

// Function to store all subarrays of an array
int storeSubarrays(int arr[], int size) {
    int result = 0; // Variable to store the cumulative sum of minimums

    for (int i = 0; i < size; ++i) {
        for (int j = i; j < size; ++j) {
            int min = arr[i]; // Assume the first element as minimum

            // Find the actual minimum element in the subarray
            for (int k = i + 1; k <= j; ++k) {
                if (arr[k] < min) {
                    min = arr[k];
                }
            }

            // Add the minimum element to the result variable
            result = (result + min);
        }
    }

    return result;
}

int main() {
    int arr[] = {3, 1, 2, 4};
    int len = sizeof(arr) / sizeof(int);

    // Count the number of subarrays
    int subarraysSize = countSubarrays(len);

    // Calculate the sum of minimums of all subarrays
    int result = storeSubarrays(arr, len);

    // Print the result
    printf("Sum of minimums of all subarrays: %d\n", result);

    return 0;
}

=====

#include <stdio.h>
#include <stdlib.h>

#define MOD 1000000007
int ind = 0;
int *ssize;

```

```

int sumOfMinimums(int** subarrays, int numSubarrays) {
    int result = 0; // Variable to store the cumulative sum of minimums

    // Calculate the sum of minimums for each subarray and add to the result variable
    for (int i = 0; i < numSubarrays; ++i) {
        int min = subarrays[i][0]; // Assume the first element as minimum

        // Find the actual minimum element in the subarray
        for (int j = 1; j < ssize[i]; ++j) {
            if (subarrays[i][j] < min) {
                min = subarrays[i][j];
            }
        }
        printf("\nMin is : %d",min);
        // Add the minimum element to the result variable
        result += min;
    }

    return result;
}

// Function to count the number of subarrays for given array size
int countSubarrays(int size) {
    return (size * (size + 1)) / 2;
}

// Function to allocate memory for subarrays array
int** allocateSubarrays(int subarraysSize) {
    int** subarrays = (int**)malloc(subarraysSize * sizeof(int*)); // Allocate memory
    for subarrays

    return subarrays;
}

// Function to store all subarrays of an array
int storeSubarrays(int arr[], int size, int** subarrays) {
    int subarraysIndex = 0;

    for (int i = 0; i < size; ++i) {
        for (int j = i; j < size; ++j) {
            int subarraySize = j - i + 1;
            ssize[ind++] = subarraySize;
            printf("\nSize %d",subarraySize);
            subarrays[subarraysIndex] = (int*)malloc(subarraySize * sizeof(int)); // Allocate memory for each subarray
            for (int k = i; k <= j; ++k) {
                subarrays[subarraysIndex][k - i] = arr[k];
            }
            subarraysIndex++;
        }
    }
}

```

```

    }

    return subarraysIndex;
}

int main() {
    int arr[] = {3, 1, 2, 4};
    int len = sizeof(arr) / sizeof(int);

    // Count the number of subarrays
    int subarraysSize = countSubarrays(len);

    // Allocate memory for subarrays
    int** subarrays = allocateSubarrays(subarraysSize);
    ssize = (int *) malloc (subarraysSize*sizeof(int));
    // Store all subarrays
    int numSubarrays = storeSubarrays(arr, len, subarrays);
    printf("\nResult is : %d\n",sumOfMinimums(subarrays,numSubarrays));
    // Print the stored subarrays
    for (int i = 0; i < numSubarrays; ++i) {
        int subarraySize = i + 1;
        printf("Subarray %d: ", i + 1);
        for (int j = 0; j < ssize[i]; ++j) {
            printf("%d ", subarrays[i][j]);
        }
        printf("\n");
        // Free memory for each subarray
        free(subarrays[i]);
    }

    // Free allocated memory for subarrays array
    free(subarrays);

    return 0;
}

```

Time/Space Complexity: $O(n^2)/O(n)$

1.20 Valid Parentheses String

```

#include <stdio.h>
#include <stdbool.h>
#include <string.h>

bool checkValidString(char* s) {
    int minBalance = 0; // Minimum possible balance of open left parentheses
    int maxBalance = 0; // Maximum possible balance of open left parentheses

```

```

int n = strlen(s);

for (int i = 0; i < n; i++) {
    if (s[i] == '(') {
        minBalance++;
        maxBalance++;
    } else if (s[i] == ')') {
        minBalance = (minBalance > 0) ? minBalance - 1 : 0;
        maxBalance--;
        if (maxBalance < 0) {
            return false; // More right parentheses ')' than left '('
        }
    } else { // When s[i] == '*'
        minBalance = (minBalance > 0) ? minBalance - 1 : 0; // Treat '*' as ')'
        maxBalance++; // Treat '*' as '('
    }
}

return minBalance == 0;
}

int main() {
    char* s1 = "()"; // Expected output: true
    char* s2 = "(*>"; // Expected output: true
    char* s3 = "(*)"; // Expected output: true
    char* s4 = "((**))"; // Expected output: true
    char* s5 = "((())*"; // Expected output: true
    char* s6 = "(())*"; // Expected output: false

    printf("%s\n", checkValidString(s1) ? "true" : "false");
    printf("%s\n", checkValidString(s2) ? "true" : "false");
    printf("%s\n", checkValidString(s3) ? "true" : "false");
    printf("%s\n", checkValidString(s4) ? "true" : "false");
    printf("%s\n", checkValidString(s5) ? "true" : "false");
    printf("%s\n", checkValidString(s6) ? "true" : "false");

    return 0;
}

```

Time/Space Complexity:O(n)/O(1)

1.21 Asteroid Collision

```

#include <stdio.h>
#include <stdlib.h>

int* asteroidCollision(int* asteroids, int asteroidsSize, int* returnSize) {
    int* stack = (int*)malloc(asteroidsSize * sizeof(int)); // Stack to simulate
    asteroids moving
    int top = -1; // Initialize top of the stack

```

```

*returnSize = 0; // Initialize the return size

// Simulate asteroids moving and collisions
for (int i = 0; i < asteroidsSize; ++i) {
    int current = asteroids[i];

    // If stack is empty or current asteroid moves to right (positive)
    if (top == -1 || current > 0) {
        stack[++top] = current;
        (*returnSize)++;
    } else {
        // Resolve collisions
        while (top >= 0 && stack[top] > 0 && stack[top] < -current) {
            top--; // Top asteroid explodes
            (*returnSize]--;
        }
    }

    // Check if current asteroid survives collision
    if (top >= 0 && stack[top] == -current) {
        top--; // Both asteroids explode
        (*returnSize)--;
    } else if (top == -1 || stack[top] < 0) {
        stack[++top] = current; // Current asteroid survives collision
        (*returnSize)++;
    }
}

return stack;
}

int main() {
// Test cases
int asteroids1[] = {5, 10, -5};
int size1;
int* result1 = asteroidCollision(asteroids1, 3, &size1);
printf("Output for test case 1: ");
for (int i = 0; i < size1; ++i) {
    printf("%d ", result1[i]);
}
printf("\n");
free(result1);

int asteroids2[] = {8, -8};
int size2;
int* result2 = asteroidCollision(asteroids2, 2, &size2);
printf("Output for test case 2: ");
for (int i = 0; i < size2; ++i) {
    printf("%d ", result2[i]);
}
}

```

```

    }
    printf("\n");
    free(result2);

    int asteroids3[] = {10, 2, -5};
    int size3;
    int* result3 = asteroidCollision(asteroids3, 3, &size3);
    printf("Output for test case 3: ");
    for (int i = 0; i < size3; ++i) {
        printf("%d ", result3[i]);
    }
    printf("\n");
    free(result3);

    return 0;
}

```

Time/Space Complexity: O(n)/O(n)

1.22 ReOrganize String (any two adjacent characters are not same)

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* reorganizeString(char* s) {
    int charCounts[26] = {0}; // Array to store the frequency of each character
    int maxCount = 0, letter = 0;
    int len = strlen(s);

    // Count the frequency of each character
    for (int i = 0; i < len; i++) {
        charCounts[s[i] - 'a']++;
    }

    // Find the character with the highest frequency
    for (int i = 0; i < 26; i++) {
        if (charCounts[i] > maxCount) {
            maxCount = charCounts[i];
            letter = i;
        }
    }

    // If the most frequent character exceeds half the length of the string + 1, it's
    // impossible to rearrange
    if (maxCount > (len + 1) / 2) {
        return "";
    }
}

```

```

// Create an array to store the result
char* ans = (char*)malloc((len + 1) * sizeof(char));
ans[len] = '\0';
int index = 0;

// Place the most frequent letter
while (charCounts[letter] != 0) {
    ans[index] = letter + 'a';
    index += 2;
    charCounts[letter]--;
}

// Place the rest of the letters in any order
for (int i = 0; i < 26; i++) {
    while (charCounts[i] > 0) {
        if (index >= len) {
            index = 1;
        }
        ans[index] = i + 'a';
        index += 2;
        charCounts[i]--;
    }
}

return ans;
}

int main() {
    char s1[] = "aab";
    char* result1 = reorganizeString(s1);
    printf("Output for test case 1: %s\n", result1);
    free(result1);

    char s2[] = "aaab";
    char* result2 = reorganizeString(s2);
    printf("Output for test case 2: %s\n", result2);
    free(result2);

    return 0;
}

```

Time/Space Complexity: O(n)/O(1)

1.23 Generate All Sub Arrays

```

#include <stdio.h>
#include <stdlib.h>

int ind = 0;

```

```

int *ssize;
// Function to count the number of subarrays for given array size
int countSubarrays(int size) {
    return (size * (size + 1)) / 2;
}

// Function to allocate memory for subarrays array
int** allocateSubarrays(int subarraysSize) {
    int** subarrays = (int**)malloc(subarraysSize * sizeof(int*)); // Allocate memory
for subarrays

    return subarrays;
}

// Function to store all subarrays of an array
int storeSubarrays(int arr[], int size, int** subarrays) {
    int subarraysIndex = 0;

    for (int i = 0; i < size; ++i) {
        for (int j = i; j < size; ++j) {
            int subarraySize = j - i + 1;
            ssize[ind++] = subarraySize;
            printf("\nSize %d", subarraySize);
            subarrays[subarraysIndex] = (int*)malloc(subarraySize * sizeof(int)); // Allocate memory for each subarray
            for (int k = i; k <= j; ++k) {
                subarrays[subarraysIndex][k - i] = arr[k];
            }
            subarraysIndex++;
        }
    }

    return subarraysIndex;
}

int main() {
    int arr[] = {3, 1, 2, 4};
    int len = sizeof(arr) / sizeof(int);

    // Count the number of subarrays
    int subarraysSize = countSubarrays(len);

    // Allocate memory for subarrays
    int** subarrays = allocateSubarrays(subarraysSize);
    ssize = (int *) malloc (subarraysSize*sizeof(int));
    // Store all subarrays
    int numSubarrays = storeSubarrays(arr, len, subarrays);

    // Print the stored subarrays

```

```

        for (int i = 0; i < numSubarrays; ++i) {
            int subarraySize = i + 1;
            printf("Subarray %d: ", i + 1);
            for (int j = 0; j < ssize[i]; ++j) {
                printf("%d ", subarrays[i][j]);
            }
            printf("\n");
            // Free memory for each subarray
            free(subarrays[i]);
        }

        // Free allocated memory for subarrays array
        free(subarrays);

        return 0;
    }

```

Time/Space Complexity : O(n^3)/O(n^2)

1.24 Bit manipulations (Set/Reset/Get Bits)

```

#include<stdio.h>
#include<stdlib.h>
#include<string.h>
char result[32] = "\0";
int count(int a) {
    int c = 0;
    for (int j = 0; j < 32; j++) {
        if (a & 1)
            c++;
        a >>= 1;
    }
    return c;
}
char *bits(int a) {
    memset(result, 0, sizeof(result));
    for(int i = 31; i >=0; i--) {
        if (a & (1 << i)) {
            strcat(result, "1");
        } else {
            strcat(result, "0");
        }
    }
    return result;
}
char *swap_nibble(int a) {
    int lmask = 0xf0;
    int rmask = 0x0f;
    int left = a & lmask;
    int right = a & rmask;
    memset(result, 0, sizeof(result));

```

```

        int res = right << 4;
        res |= (left >> 4);
        return bits(res);

    }
    char *swap_nibbles(int a) {
        memset(result, 0, sizeof(result));

        // Swap the nibbles using bitwise operations
        int res = ((a & 0x0F) << 4) | ((a & 0xF0) >> 4);

        return bits(res);
    }
    int set_bit(int a, int b) {
        int c = 1 << b;
        a |= c;
        return a;
    }
    int get_bit(int a, int b) {
        int d = a;
        return (d >> b)&1;
    }
    int main(int argc, char *argv[]) {
        int i = atoi(argv[1]);
        printf("\nBit representation is : %s",bits(i));
        printf("\nNo of 1 bits : %d",count(i));
        printf("\nSwapped Nibble : %s",swap_nibble(i));
        printf("\nSwapped Nibbles : %s",swap_nibbles(i));
        printf("\nBit representation is : %s",bits(0x432));
        printf("\nBit representation is : %d",get_bit(0x432,13));
        int r = set_bit(0x432,13);
        printf("\nBit representation is : %s",bits(r));
        printf("\nBit got is : %d",get_bit(r,13));
    }
}

```

1.25 Decode Ways For String

```

#include <stdio.h>
#include <string.h>

int numDecodings(char* s) {
    int n = strlen(s);
    int dp[n + 1];

    dp[0] = 1; // Base case: empty string has one decoding
    dp[1] = (s[0] == '0') ? 0 : 1; // First character

    for (int i = 2; i <= n; i++) {

```

```

        // One-digit decoding
        if (s[i - 1] != '0') {
            dp[i] = dp[i - 1];
        } else {
            dp[i] = 0;
        }

        // Two-digit decoding
        int twoDigit = (s[i - 2] - '0') * 10 + (s[i - 1] - '0');
        if (twoDigit >= 10 && twoDigit <= 26) {
            dp[i] += dp[i - 2];
        }
    }

    return dp[n];
}

int main() {
    char s1[] = "12";
    printf("Output for test case 1: %d\n", numDecodings(s1));

    char s2[] = "226";
    printf("Output for test case 2: %d\n", numDecodings(s2));

    char s3[] = "06";
    printf("Output for test case 3: %d\n", numDecodings(s3));

    return 0;
}

```

Time/Space Complexity: O(n)/O(n)

1.26 Multiply Two Strings

```

// Function to calculate the length of a string
int strLength(char* str) {
    int length = 0;
    while (str[length] != '\0') {
        length++;
    }
    return length;
}

// Function to convert character digit to integer
int charToInt(char c) {
    return c - '0';
}

// Function to convert integer to character digit
char intToChar(int num) {

```

```

        return num + '0';
    }

// Function to multiply two numbers represented as strings
char* multiply(char* num1, char* num2) {
    int len1 = strLength(num1);
    int len2 = strLength(num2);
    int len3 = len1 + len2;

    // Allocate memory for the result string
    char* result = (char*)malloc((len3 + 1) * sizeof(char));
    result[len3] = '\0';

    // Initialize result with '0'
    for (int i = 0; i < len3; i++) {
        result[i] = '0';
    }

    // Perform multiplication digit by digit
    for (int i = len1 - 1; i >= 0; i--) {
        int carry = 0;
        for (int j = len2 - 1; j >= 0; j--) {
            int digit = charToInt(num1[i]) * charToInt(num2[j]) + charToInt(result[i + j + 1]) + carry;
            carry = digit / 10;
            result[i + j + 1] = intToChar(digit % 10);
        }
        if (carry > 0) {
            result[i] = intToChar(charToInt(result[i]) + carry);
        }
    }

    // Trim leading zeros if any
    int startIdx = 0;
    while (result[startIdx] == '0' && startIdx < len3 - 1) {
        startIdx++;
    }

    // Shift the result string to remove leading zeros
    if (startIdx > 0) {
        for (int i = 0; i < len3 - startIdx; i++) {
            result[i] = result[i + startIdx];
        }
        result[len3 - startIdx] = '\0';
    }

    return result;
}

int main() {

```

```

char* num1 = "123";
char* num2 = "456";

char* result = multiply(num1, num2);

printf("Multiplication of %s and %s is: %s\n", num1, num2, result);

// Free memory allocated for result
free(result);

return 0;
}

```

Space/Time Complexity:O(n²)/O(n)

1.27 Buildings With An Ocean View

```

#include <stdio.h>
#include <stdlib.h>

int* findBuildings(int* heights, int heightsSize, int* returnSize) {
    // Allocate memory for the result array
    int* result = (int*)malloc(heightsSize * sizeof(int));
    *returnSize = 0;

    // Initialize the maximum height seen so far
    int maxHeight = 0;

    // Traverse the buildings from right to left
    for (int i = heightsSize - 1; i >= 0; i--) {
        // Check if the current building has an ocean view
        if (heights[i] > maxHeight) {
            // Update the maximum height seen so far
            maxHeight = heights[i];
            // Store the index of the building in the result array
            result[(*returnSize)++] = i;
        }
    }

    // Reverse the result array to have indices in increasing order
    for (int i = 0; i < *returnSize / 2; i++) {
        int temp = result[i];
        result[i] = result[*returnSize - i - 1];
        result[*returnSize - i - 1] = temp;
    }

    return result;
}

```

```

int main() {
    int heights[] = {4, 2, 3, 1};
    int heightsSize = sizeof(heights) / sizeof(heights[0]);
    int returnSize;
    int* result = findBuildings(heights, heightsSize, &returnSize);

    printf("Buildings with ocean view: ");
    for (int i = 0; i < returnSize; i++) {
        printf("%d ", result[i]);
    }
    printf("\n");

    // Free the dynamically allocated memory
    free(result);

    return 0;
}

```

Time/Space Complexity:O(n)/O(n)

1.28 Interleaving String

```

#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Define a helper function with memoization
bool isInterleaveHelper(char *s1, char *s2, char *s3, int p1, int p2, int p3, bool
**memo) {
    // Base case: If both s1 and s2 have reached the end
    if (s1[p1] == '\0' && s2[p2] == '\0') {
        return s3[p3] == '\0';
    }

    // If the result is already memoized, return it
    if (memo[p1][p2]) {
        return false;
    }

    // If the current character of s1 matches the current character of s3
    if (s1[p1] == s3[p3]) {
        // Recursively check if remaining characters of s1 and s3 can interleave with s2
        and s3
        if (isInterleaveHelper(s1, s2, s3, p1 + 1, p2, p3 + 1, memo)) {
            return true;
        }
    }
}

```

```

// If the current character of s2 matches the current character of s3
if (s2[p2] == s3[p3]) {
    // Recursively check if remaining characters of s2 and s3 can interleave with s1
and s3
    if (isInterleaveHelper(s1, s2, s3, p1, p2 + 1, p3 + 1, memo)) {
        return true;
    }
}

// Memoize the result to avoid redundant computations
memo[p1][p2] = true;

return false;
}

bool isInterleave(char *s1, char *s2, char *s3) {
    int len1 = strlen(s1), len2 = strlen(s2), len3 = strlen(s3);

    // If the lengths of s1 and s2 do not sum up to the length of s3, it's impossible to
interleave them
    if (len1 + len2 != len3) {
        return false;
    }

    // Initialize memoization table
    bool **memo = (bool **)malloc((len1 + 1) * sizeof(bool *));
    for (int i = 0; i <= len1; i++) {
        memo[i] = (bool *)calloc(len2 + 1, sizeof(bool));
    }

    // Call the helper function recursively
    bool result = isInterleaveHelper(s1, s2, s3, 0, 0, 0, memo);

    // Free memory allocated for memoization table
    for (int i = 0; i <= len1; i++) {
        free(memo[i]);
    }
    free(memo);

    return result;
}

int main() {
    char s1[] = "aabcc";
    char s2[] = "dbbca";
    char s3[] = "aadbbcbcac";

    if (isInterleave(s1, s2, s3)) {
        printf("%s and %s can interleave to form %s\n", s1, s2, s3);
    }
}

```

```

    } else {
        printf("%s and %s cannot interleave to form %s\n", s1, s2, s3);
    }

    return 0;
}

```

Time/Space Complexity:O(m*n)/O(m*n)

1.29 Reverse Linked List Nodes In K Groups

```

#include <stdio.h>
#include <stdlib.h>

// Define the ListNode structure
struct ListNode {
    int val;
    struct ListNode *next;
};

// Define the helper function to reverse a sublist of the linked list
struct ListNode* reverseList(struct ListNode* head, struct ListNode* tail) {
    struct ListNode* prev = NULL;
    struct ListNode* curr = head;
    while (prev != tail) {
        struct ListNode* nextTemp = curr->next;
        curr->next = prev;
        prev = curr;
        curr = nextTemp;
    }
    return prev;
}

// Define the function to reverse linked list in groups of k nodes
struct ListNode* reverseKGroup(struct ListNode* head, int k) {
    struct ListNode* dummy = (struct ListNode*)malloc(sizeof(struct ListNode));
    dummy->val = 0;
    dummy->next = head;

    struct ListNode* prevGroupTail = dummy;
    while (head) {
        struct ListNode* groupHead = head;
        struct ListNode* groupTail = groupHead;
        int count = 1;
        while (groupTail && count < k) {
            groupTail = groupTail->next;
            count++;
        }
        if (!groupTail) break;
        struct ListNode* nextGroupHead = groupTail->next;
        groupTail->next = prevGroupTail;
        prevGroupTail = groupHead;
        head = nextGroupHead;
    }
    return dummy->next;
}

```

```

        struct ListNode* nextGroupHead = groupTail->next;
        struct ListNode* reversedGroupHead = reverseList(groupHead, groupTail);

        prevGroupTail->next = reversedGroupHead;
        groupHead->next = nextGroupHead;

        prevGroupTail = groupHead;
        head = nextGroupHead;
    }

    struct ListNode* result = dummy->next;
    free(dummy);
    return result;
}

// Function to create a new node
struct ListNode* createNode(int val) {
    struct ListNode* newNode = (struct ListNode*)malloc(sizeof(struct ListNode));
    newNode->val = val;
    newNode->next = NULL;
    return newNode;
}

// Function to print the linked list
void printList(struct ListNode* head) {
    while (head) {
        printf("%d -> ", head->val);
        head = head->next;
    }
    printf("NULL\n");
}

int main() {
    // Create a linked list: 1 -> 2 -> 3 -> 4 -> 5 -> NULL
    struct ListNode* head = createNode(1);
    head->next = createNode(2);
    head->next->next = createNode(3);
    head->next->next->next = createNode(4);
    head->next->next->next->next = createNode(5);
    printf("Original linked list: ");
    printList(head);

    // Reverse the linked list in groups of 2 nodes
    int k = 2;
    struct ListNode* reversedHead = reverseKGroup(head, k);
    printf("Reversed linked list in groups of %d nodes: ", k);
    printList(reversedHead);

    // Free the memory allocated for the linked lists
}

```

```

    struct ListNode* temp;
    while (reversedHead) {
        temp = reversedHead;
        reversedHead = reversedHead->next;
        free(temp);
    }

    return 0;
}

```

Input: head = [1,2,3,4,5], k = 2
Output: [2,1,4,3,5]
Input: head = [1,2,3,4,5], k = 3
Output: [3,2,1,4,5]

Time/Space Complexity: O(n)/O(1)

1.30 4 Sum

```

#include <stdio.h>
#include <stdlib.h>

// Function to compare integers (used for qsort)
int compareIntegers(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}

// Function to return an array of arrays of size *returnSize
int **fourSum(int *nums, int numsSize, int target, int *returnSize, int
**returnColumnSizes) {
    // Sort the array in non-decreasing order
    qsort(nums, numsSize, sizeof(int), compareIntegers);

    // Initialize variables
    int **result = NULL;
    *returnSize = 0;

    // Iterate over each element up to numsSize - 4
    for (int i = 0; i < numsSize - 3; i++) {
        // Skip duplicates
        if (i > 0 && nums[i] == nums[i - 1]) continue;

        for (int j = i + 1; j < numsSize - 2; j++) {
            // Skip duplicates
            if (j > i + 1 && nums[j] == nums[j - 1]) continue;

            int left = j + 1;
            int right = numsSize - 1;

            while (left < right) {

```

```

        int sum = nums[i] + nums[j] + nums[left] + nums[right];
        if (sum == target) {
            // Add the quadruplet to the result
            (*returnSize)++;
            result = (int **)realloc(result, (*returnSize) * sizeof(int *));
            result[*returnSize - 1] = (int *)malloc(4 * sizeof(int));
            result[*returnSize - 1][0] = nums[i];
            result[*returnSize - 1][1] = nums[j];
            result[*returnSize - 1][2] = nums[left];
            result[*returnSize - 1][3] = nums[right];

            // Skip duplicates
            while (left < right && nums[left] == nums[left + 1]) left++;
            while (left < right && nums[right] == nums[right - 1]) right--;
            left++;
            right--;
        } else if (sum < target) {
            left++;
        } else {
            right--;
        }
    }
}

// Set returnColumnSizes
*returnColumnSizes = (int *)malloc((*returnSize) * sizeof(int));
for (int i = 0; i < *returnSize; i++) {
    (*returnColumnSizes)[i] = 4;
}

return result;
}

// Function to free the memory allocated for the result
void freeResult(int **result, int returnSize) {
    for (int i = 0; i < returnSize; i++) {
        free(result[i]);
    }
    free(result);
}

// Function to print the result
void printResult(int **result, int returnSize, int *returnColumnSizes) {
    printf("[\n");
    for (int i = 0; i < returnSize; i++) {
        printf("  [");
        for (int j = 0; j < returnColumnSizes[i]; j++) {

```

```

        printf("%d", result[i][j]);
        if (j < returnColumnSizes[i] - 1) printf(",");
    }
    printf("]");
    if (i < returnSize - 1) printf(",");
    printf("\n");
}
printf("]\n");
}

int main() {
    int nums1[] = {1, 0, -1, 0, -2, 2};
    int target1 = 0;
    int numsSize1 = sizeof(nums1) / sizeof(nums1[0]);
    int returnSize1;
    int *returnColumnSizes1;
    int **result1 = fourSum(nums1, numsSize1, target1, &returnSize1,
    &returnColumnSizes1);
    printf("Example 1:\n");
    printResult(result1, returnSize1, returnColumnSizes1);
    freeResult(result1, returnSize1);
    free(returnColumnSizes1);

    int nums2[] = {2, 2, 2, 2, 2};
    int target2 = 8;
    int numsSize2 = sizeof(nums2) / sizeof(nums2[0]);
    int returnSize2;
    int *returnColumnSizes2;
    int **result2 = fourSum(nums2, numsSize2, target2, &returnSize2,
    &returnColumnSizes2);
    printf("Example 2:\n");
    printResult(result2, returnSize2, returnColumnSizes2);
    freeResult(result2, returnSize2);
    free(returnColumnSizes2);

    return 0;
}

```

Time/Space Complexity:O(n³)/O(1)

1.31 Largest Rectangle In Histogram

```

#include <stdio.h>
#include <stdlib.h>

int largestRectangleArea(int* heights, int heightsSize) {
    // Initialize a stack to store the indices of bars
    int* stack = (int*)malloc((heightsSize + 1) * sizeof(int));
    int top = -1;
    int maxArea = 0;

```

```

for (int i = 0; i <= heightsSize; i++) {
    // Get the current bar's height
    int currentHeight = (i == heightsSize) ? 0 : heights[i];

    // While the stack is not empty and the current bar's height is less than the
    // height of the bar at the top of the stack
    while (top >= 0 && heights[stack[top]] > currentHeight) {
        // Pop the index of the bar from the stack
        int heightIndex = stack[top--];

        // Calculate the width of the rectangle
        int width = (top == -1) ? i : i - stack[top] - 1;

        // Calculate the area of the rectangle
        int area = heights[heightIndex] * width;

        // Update the maximum area
        if (area > maxArea) {
            maxArea = area;
        }
    }

    // Push the current bar's index onto the stack
    stack[++top] = i;
}

// Free the allocated memory for the stack
free(stack);

return maxArea;
}

int main() {
    int heights[] = {2, 1, 5, 6, 2, 3};
    int heightsSize = sizeof(heights) / sizeof(heights[0]);

    int maxArea = largestRectangleArea(heights, heightsSize);
    printf("Largest Rectangle Area: %d\n", maxArea);

    return 0;
}

```

Time/Space Complexity:O(n)/O(n)

1.32 Minimum Path Sum

```
#include <stdio.h>
#include <stdlib.h>
```

```

int min(int a, int b) {
    return (a < b) ? a : b;
}

int minPathSum(int** grid, int gridSize, int* gridColSize) {
    for (int i = gridSize - 1; i >= 0; i--) {
        for (int j = *gridColSize - 1; j >= 0; j--) {
            if (i == gridSize - 1 && j != *gridColSize - 1)
                grid[i][j] += grid[i][j + 1];
            else if (j == *gridColSize - 1 && i != gridSize - 1)
                grid[i][j] += grid[i + 1][j];
            else if (j != *gridColSize - 1 && i != gridSize - 1)
                grid[i][j] += min(grid[i + 1][j], grid[i][j + 1]);
        }
    }
    return grid[0][0];
}

int main() {
    int gridSize = 3;
    int gridColSize = 3;
    int** grid = (int**)malloc(gridSize * sizeof(int*));
    for (int i = 0; i < gridSize; i++) {
        grid[i] = (int*)malloc(gridColSize * sizeof(int));
    }

    // Initialize grid values
    grid[0][0] = 1;
    grid[0][1] = 3;
    grid[0][2] = 1;
    grid[1][0] = 1;
    grid[1][1] = 5;
    grid[1][2] = 1;
    grid[2][0] = 4;
    grid[2][1] = 2;
    grid[2][2] = 1;

    // Print original grid
    printf("Original grid:\n");
    for (int i = 0; i < gridSize; i++) {
        for (int j = 0; j < gridColSize; j++) {
            printf("%d ", grid[i][j]);
        }
        printf("\n");
    }

    // Calculate and print the minimum path sum
    int minSum = minPathSum(grid, gridSize, &gridColSize);
    printf("\nMinimum path sum: %d\n", minSum);
}

```

```

    // Free allocated memory for grid
    for (int i = 0; i < gridSize; i++) {
        free(grid[i]);
    }
    free(grid);

    return 0;
}

```

Original Array

1	3	4	8
3	2	2	4
5	7	1	9
2	3	2	3

dp	14	13	12	24
13	14	13	12	24
15	13	10	8	16
10	15	13	6	12
	10	8	5	3

Space/Time Complexity: $O(n*m)/O(1)$

1.33 House Robber II

```

#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int rob_simple(int* nums, int start, int end) {
    int t1 = 0;
    int t2 = 0;

    for (int i = start; i <= end; i++) {
        int temp = t1;
        int current = nums[i];
        t1 = max(current + t2, t1);
        t2 = temp;
    }

    return t1;
}

int rob(int* nums, int numsSize) {

```

```

if (numsSize == 0)
    return 0;

if (numsSize == 1)
    return nums[0];

int max1 = rob_simple(nums, 0, numsSize - 2);
int max2 = rob_simple(nums, 1, numsSize - 1);

return max(max1, max2);
}

int main() {
    int nums[] = {2, 7, 9, 3, 1};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int result = rob(nums, numsSize);
    printf("Maximum amount that can be robbed: %d\n", result);

    return 0;
}

```

Time/Space Complexity:O(n)/O(1)

1.34 Binary Tree Vertical Order Traversal

```

#include <stdlib.h>
#include <stdio.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Definition for a queue node.
struct QueueNode {
    struct TreeNode *node;
    int hd; // Horizontal distance
    struct QueueNode *next;
};

// Definition for a queue.
struct Queue {
    struct QueueNode *front, *rear;
};

// Function to create a new queue node.

```

```

struct QueueNode* newQueueNode(struct TreeNode *node, int hd) {
    struct QueueNode* temp = (struct QueueNode*)malloc(sizeof(struct QueueNode));
    temp->node = node;
    temp->hd = hd;
    temp->next = NULL;
    return temp;
}

// Function to create a new queue.
struct Queue* createQueue() {
    struct Queue* q = (struct Queue*)malloc(sizeof(struct Queue));
    q->front = q->rear = NULL;
    return q;
}

// Function to enqueue a node to the rear of the queue.
void enqueue(struct Queue* q, struct TreeNode *node, int hd) {
    struct QueueNode* temp = newQueueNode(node, hd);
    if (q->rear == NULL) {
        q->front = q->rear = temp;
        return;
    }
    q->rear->next = temp;
    q->rear = temp;
}

// Function to dequeue a node from the front of the queue.
struct QueueNode* dequeue(struct Queue* q) {
    if (q->front == NULL) return NULL;
    struct QueueNode* temp = q->front;
    q->front = q->front->next;
    if (q->front == NULL) q->rear = NULL;
    return temp;
}

// Function to perform vertical order traversal of the binary tree.
int** verticalOrder(struct TreeNode* root, int* returnSize, int** returnColumnSizes) {
    if (root == NULL) {
        *returnSize = 0;
        return NULL;
    }

    // Initialize the variables and data structures
    int minHd = 0, maxHd = 0;
    struct Queue* q = createQueue();
    enqueue(q, root, 0);

    // Traverse the tree and populate the map
    while (q->front != NULL) {

```

```

        struct QueueNode* current = dequeue(q);
        int hd = current->hd;
        struct TreeNode* node = current->node;
        if (hd < minHd) minHd = hd;
        if (hd > maxHd) maxHd = hd;

        // Enqueue left child
        if (node->left != NULL) enqueue(q, node->left, hd - 1);

        // Enqueue right child
        if (node->right != NULL) enqueue(q, node->right, hd + 1);

        free(current);
    }

    // Calculate the number of columns
    *returnSize = maxHd - minHd + 1;

    // Allocate memory for the result arrays
    int** result = (int**)malloc((*returnSize) * sizeof(int*));
    *returnColumnSizes = (int*)malloc((*returnSize) * sizeof(int));
    for (int i = 0; i < *returnSize; i++) {
        result[i] = (int*)malloc(1000 * sizeof(int)); // Assuming maximum 1000 nodes in
        each column
        (*returnColumnSizes)[i] = 0;
    }

    // Reset the queue and enqueue the root node with its horizontal distance
    q = createQueue();
    enqueue(q, root, 0);

    // Traverse the tree again and fill the result arrays
    while (q->front != NULL) {
        struct QueueNode* current = dequeue(q);
        int hd = current->hd;
        struct TreeNode* node = current->node;
        int index = hd - minHd;

        // Add the node's value to the corresponding column in the result
        result[index][(*returnColumnSizes)[index]++] = node->val;

        // Enqueue left child
        if (node->left != NULL) enqueue(q, node->left, hd - 1);

        // Enqueue right child
        if (node->right != NULL) enqueue(q, node->right, hd + 1);

        free(current);
    }
}

```

```

    return result;
}

// Function to create a new binary tree node.
struct TreeNode* newTreeNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

// Sample main function for testing
int main() {
    // Create a sample binary tree
    struct TreeNode* root = newTreeNode(3);
    root->left = newTreeNode(9);
    root->right = newTreeNode(20);
    root->right->left = newTreeNode(15);
    root->right->right = newTreeNode(7);

    int returnSize, *returnColumnSizes;
    int** result = verticalOrder(root, &returnSize, &returnColumnSizes);

    // Print the result
    printf("[");
    for (int i = 0; i < returnSize; i++) {
        printf("[");
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d", result[i][j]);
            if (j < returnColumnSizes[i] - 1) printf(",");
        }
        printf("]");
        if (i < returnSize - 1) printf(",");
    }
    printf("]\n");

    // Free memory allocated for result arrays
    for (int i = 0; i < returnSize; i++) {
        free(result[i]);
    }
    free(result);
    free(returnColumnSizes);

    // Free memory allocated for the binary tree
    // (Note: Actual implementation may vary depending on the tree structure)
    free(root->left);
    free(root->right);
}


```

```

    free(root);

    return 0;
}

```



```
d = { -3: [3], -2: [4], -1: [9, 11], 0: [2, 1], 1: [8, 5], 2: [7] }
```

Time/Space Complexity: O(n)/O(n)

1.35 Course Schedule

```

#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Definition for a queue node
struct QueueNode {
    int val;
    struct QueueNode* next;
};

// Definition for a queue
struct Queue {
    struct QueueNode* front;
    struct QueueNode* rear;
};

// Function to create a new queue node
struct QueueNode* newQueueNode(int val) {
    struct QueueNode* node = (struct QueueNode*)malloc(sizeof(struct QueueNode));
    node->val = val;
    node->next = NULL;
    return node;
}

// Function to enqueue a node
void enqueue(struct Queue* q, struct QueueNode* node) {
    if (q->rear == NULL) {
        q->front = node;
        q->rear = node;
    } else {
        q->rear->next = node;
        q->rear = node;
    }
}

// Function to dequeue a node
struct QueueNode* dequeue(struct Queue* q) {
    if (q->front == NULL) {
        return NULL;
    }
    struct QueueNode* temp = q->front;
    q->front = q->front->next;
    if (q->front == NULL) {
        q->rear = NULL;
    }
    return temp;
}

// Function to check if a course schedule is valid
bool isScheduleValid(struct Queue* q, int numCourses) {
    int indegree[numCourses];
    for (int i = 0; i < numCourses; i++) {
        indegree[i] = 0;
    }
    while (q->front != NULL) {
        struct QueueNode* node = dequeue(q);
        int course = node->val;
        for (int i = 0; i < numCourses; i++) {
            if (indegree[i] > 0 && !isCoursePrerequisite(i, course)) {
                return false;
            }
        }
        for (int i = 0; i < numCourses; i++) {
            if (isCoursePrerequisite(course, i)) {
                indegree[i]++;
            }
        }
    }
    return true;
}

// Helper function to check if course i is a prerequisite for course j
bool isCoursePrerequisite(int i, int j) {
    // Implementation of isCoursePrerequisite function
    // ...
}

int main() {
    // Implementation of main function
    // ...
}

```

```

node->val = val;
node->next = NULL;
return node;
}

// Function to create a new queue
struct Queue* createQueue() {
    struct Queue* q = (struct Queue*)malloc(sizeof(struct Queue));
    q->front = q->rear = NULL;
    return q;
}

// Function to enqueue a node to the rear of the queue
void enqueue(struct Queue* q, int val) {
    struct QueueNode* newNode = newQueueNode(val);
    if (q->rear == NULL) {
        q->front = q->rear = newNode;
        return;
    }
    q->rear->next = newNode;
    q->rear = newNode;
}

// Function to dequeue a node from the front of the queue
int dequeue(struct Queue* q) {
    if (q->front == NULL) return -1;
    struct QueueNode* temp = q->front;
    int val = temp->val;
    q->front = q->front->next;
    if (q->front == NULL) q->rear = NULL;
    free(temp);
    return val;
}

// Function to check if it's possible to finish all courses
bool canFinish(int numCourses, int** prerequisites, int prerequisitesSize, int*
prerequisitesColSize) {
    int* indegree = (int*)calloc(numCourses, sizeof(int));
    int** adj = (int**)malloc(numCourses * sizeof(int*));

    // Initialize adjacency list and indegree array
    for (int i = 0; i < numCourses; i++) {
        adj[i] = (int*)malloc(numCourses * sizeof(int));
        for (int j = 0; j < numCourses; j++) {
            adj[i][j] = 0;
        }
    }

    // Populate adjacency list and indegree array

```

```

        for (int i = 0; i < prerequisitesSize; i++) {
            int course = prerequisites[i][0];
            int prereq = prerequisites[i][1];
            if (!adj[prereq][course]) {
                adj[prereq][course] = 1;
                indegree[course]++;
            }
        }

        // Perform topological sort using BFS
        struct Queue* q = createQueue();
        for (int i = 0; i < numCourses; i++) {
            if (indegree[i] == 0) {
                enqueue(q, i);
            }
        }

        int nodesVisited = 0;
        while (q->front) {
            int course = dequeue(q);
            nodesVisited++;
            for (int i = 0; i < numCourses; i++) {
                if (adj[course][i]) {
                    indegree[i]--;
                    if (indegree[i] == 0) {
                        enqueue(q, i);
                    }
                }
            }
        }
    }

    // Check if all courses can be finished
    bool canFinish = (nodesVisited == numCourses);

    // Free memory
    free(indegree);
    for (int i = 0; i < numCourses; i++) {
        free(adj[i]);
    }
    free(adj);
    free(q);

    return canFinish;
}

int main() {
    int numCourses = 2;
    int prerequisitesSize = 2;
    int prerequisitesColSize[] = {2, 2};

```

```

int** prerequisites = (int**)malloc(prerequisitesSize * sizeof(int*));
prerequisites[0] = (int*)malloc(2 * sizeof(int));
prerequisites[1] = (int*)malloc(2 * sizeof(int));
prerequisites[0][0] = 1;
prerequisites[0][1] = 0;
prerequisites[1][0] = 0;
prerequisites[1][1] = 1;

bool result = canFinish(numCourses, prerequisites, prerequisitesSize,
prerequisitesColSize);
printf("Result: %s\n", result ? "true" : "false");

// Free allocated memory
for (int i = 0; i < prerequisitesSize; i++) {
    free(prerequisites[i]);
}
free(prerequisites);

return 0;
}

```

Time/Space Complexity:O(1)/O(n)

1.36 Word Break

```

#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

#define ALPHABET_SIZE 26

struct TrieNode {
    struct TrieNode* children[ALPHABET_SIZE];
    bool isEndOfWord;
};

// Function to initialize a new Trie node
struct TrieNode* createNode() {
    struct TrieNode* node = (struct TrieNode*)malloc(sizeof(struct TrieNode));
    for (int i = 0; i < ALPHABET_SIZE; ++i) {
        node->children[i] = NULL;
    }
    node->isEndOfWord = false;
    return node;
}

// Function to insert a word into the Trie
void insert(struct TrieNode* root, char* word) {
    struct TrieNode* curr = root;

```

```

        while (*word) {
            int index = *word - 'a';
            if (!curr->children[index]) {
                curr->children[index] = createNode();
            }
            curr = curr->children[index];
            ++word;
        }
        curr->isEndOfWord = true;
    }

    // Function to perform DFS traversal to check if the input string can be segmented
    bool dfs(struct TrieNode* root, char* s) {
        struct TrieNode* curr = root;
        while (*s) {
            int index = *s - 'a';
            if (!curr->children[index]) {
                return false; // Cannot find the current character in the trie
            }
            curr = curr->children[index];
            ++s;
            if (curr->isEndOfWord) {
                if (*s == '\0') {
                    return true; // Reach the end of the input string and find a complete word
                }
                if (dfs(root, s)) {
                    return true; // Check if the remaining substring can be segmented
                }
            }
        }
        return false;
    }

    // Function to free the memory used by the Trie
    void freeTrie(struct TrieNode* root) {
        if (!root) {
            return;
        }
        for (int i = 0; i < ALPHABET_SIZE; ++i) {
            freeTrie(root->children[i]);
        }
        free(root);
    }

    // Function to check if the input string can be segmented into words from the dictionary
    bool wordBreak(char* s, char** wordDict, int wordDictSize) {
        struct TrieNode* root = createNode();
        // Build the trie

```

```

        for (int i = 0; i < wordDictSize; ++i) {
            insert(root, wordDict[i]);
        }
        // Perform DFS traversal
        bool result = dfs(root, s);
        // Free the memory used by the Trie
        freeTrie(root);
        return result;
    }

    int main() {
        char* s = "leetcode";
        char* wordDict[] = {"leet", "code"};
        int wordDictSize = 2;

        bool result = wordBreak(s, wordDict, wordDictSize);

        if (result) {
            printf("The string \"%s\" can be segmented into words from the dictionary.\n",
s);
        } else {
            printf("The string \"%s\" cannot be segmented into words from the
dictionary.\n", s);
        }

        return 0;
    }

```

Time/Space Complexity: O(n)/O(1)

1.37 Longest Valid Parentheses

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_STACK_SIZE 10000 // Maximum size of the stack

// Stack structure
typedef struct {
    int* arr;
    int top;
} Stack;

// Function to initialize the stack
Stack* createStack() {
    Stack* stack = (Stack*)malloc(sizeof(Stack));
    stack->arr = (int*)malloc(MAX_STACK_SIZE * sizeof(int));
    stack->top = -1;
    return stack;
}

```

```

// Function to check if the stack is empty
int isEmpty(Stack* stack) {
    return stack->top == -1;
}

// Function to push an element onto the stack
void push(Stack* stack, int val) {
    stack->arr[stack->top] = val;
}

// Function to pop an element from the stack
int pop(Stack* stack) {
    return stack->arr[stack->top--];
}

int longestValidParentheses(char* s) {
    int maxans = 0;
    Stack* stack = createStack();
    push(stack, -1); // Push -1 as a base index onto the stack

    for (int i = 0; s[i] != '\0'; i++) {
        if (s[i] == '(') {
            push(stack, i);
        } else { // s[i] == ')'
            pop(stack);
            if (isEmpty(stack)) {
                push(stack, i); // Update the base index
            } else {
                maxans = (i - stack->arr[stack->top] > maxans) ? i - stack->arr[stack->top] : maxans;
            }
        }
    }

    free(stack->arr);
    free(stack);
    return maxans;
}

int main() {
    // Test cases
    char* s1 = "((())";
    printf("Input: %s\n", s1);
    printf("Output: %d\n", longestValidParentheses(s1)); // Output: 2

    char* s2 = ")()())";
    printf("Input: %s\n", s2);
    printf("Output: %d\n", longestValidParentheses(s2)); // Output: 4
}

```

```

    char* s3 = "";
    printf("Input: %s\n", s3);
    printf("Output: %d\n", longestValidParentheses(s3)); // Output: 0

    return 0;
}

```

Time/Space Complexity:O(n)/O(n)

1.38 Edit Distance (Minimum Operation to convert word1 to word2)

```

#include <stdio.h>
#include <string.h>

// Function to find the minimum of three integers
int min(int a, int b, int c) {
    int min = (a < b) ? a : b;
    return (min < c) ? min : c;
}

// Function to find the minimum edit distance between two strings
int minDistance(char *word1, char *word2) {
    int m = strlen(word1);
    int n = strlen(word2);
    if (m == 0) return n;
    if (n == 0) return m;

    int md[m + 1][n + 1];

    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0) {
                md[i][j] = j;
            } else if (j == 0) {
                md[i][j] = i;
            } else if (word1[i - 1] == word2[j - 1]) {
                md[i][j] = md[i - 1][j - 1];
            } else {
                md[i][j] = 1 + min(md[i - 1][j - 1], md[i - 1][j], md[i][j - 1]);
            }
        }
    }

    return md[m][n];
}

int main() {
    char word1[] = "horse";
    char word2[] = "ros";
}

```

```
    printf("Minimum edit distance between '%s' and '%s' is: %d\n", word1, word2,
minDistance(word1, word2));
```

```
    return 0;
}
```

Input: word1 = "horse", word2 = "ros"

Output: 3

Explanation:

horse -> rorse (replace 'h' with 'r')

rorse -> rose (remove 'r')

rose -> ros (remove 'e')

Time/Space Complexity: O(m*n)/O(m*n)

1.39 SubSets II

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Helper function to compare integers for qsort
int compareIntegers(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}

// Helper function for backtracking to generate subsets
void backtrack(int *nums, int numsSize, int start, int *temp, int tempSize, int
**result, int *returnSize, int **returnColumnSizes) {
    // Allocate memory for the new subset and copy the elements
    int *subset = (int *)malloc(tempSize * sizeof(int));
    memcpy(subset, temp, tempSize * sizeof(int));
    // Add the subset to the result array
    result[*returnSize] = subset;
    (*returnColumnSizes)[*returnSize] = tempSize;
    (*returnSize)++;

    // Explore all possible subsets
    for (int i = start; i < numsSize; i++) {
        // Skip duplicates
        if (i > start && nums[i] == nums[i - 1]) continue;
        // Add current element to the temporary subset
        temp[tempSize] = nums[i];
        // Recursively generate subsets starting from the next index
        backtrack(nums, numsSize, i + 1, temp, tempSize + 1, result, returnSize,
        returnColumnSizes);
    }
}
```

```

int** subsetsWithDup(int* nums, int numsSize, int* returnSize, int** returnColumnSizes)
{
    // Sort the input array to handle duplicates efficiently
    qsort(nums, numsSize, sizeof(int), compareIntegers);

    // Allocate memory for the result array and column sizes array
    int capacity = 10000; // Initial capacity, can be adjusted
    int **result = (int **)malloc(capacity * sizeof(int *));
    *returnColumnSizes = (int *)malloc(capacity * sizeof(int));
    *returnSize = 0;

    // Temporary array to store subsets during backtracking
    int *temp = (int *)malloc(numsSize * sizeof(int));

    // Use backtracking to generate subsets
    backtrack(nums, numsSize, 0, temp, 0, result, returnSize, returnColumnSizes);

    // Free memory for the temporary array
    free(temp);

    return result;
}

int main() {
    // Example input
    int nums[] = {1, 2, 2};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Variables to store the result
    int returnSize;
    int *returnColumnSizes;

    // Generate subsets
    int **result = subsetsWithDup(nums, numsSize, &returnSize, &returnColumnSizes);

    // Print the result
    printf("[");
    for (int i = 0; i < returnSize; i++) {
        printf("[");
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d", result[i][j]);
            if (j < returnColumnSizes[i] - 1) printf(", ");
        }
        printf("]");
        if (i < returnSize - 1) printf(", ");
    }
    printf("]\n");

    // Free dynamically allocated memory
}

```

```

        for (int i = 0; i < returnSize; i++) {
            free(result[i]);
        }
        free(result);
        free(returnColumnSizes);
    }

    return 0;
}

```

Time/Space Complexity:O(2^n)/O(n*2^n)

1.40 Nth Digit

```

#include <stdio.h>

int findNthDigit(int n) {
    long base = 9;
    int digits = 1;

    // Step 1: Determine the length of the numbers at each level
    while (n > base * digits) {
        n -= base * digits;
        base *= 10;
        digits++;
    }

    // Step 2: Calculate the actual number where the nth digit belongs
    int number = 1;
    for (int i = 1; i < digits; i++) {
        number *= 10;
    }
    number += (n - 1) / digits;

    // Step 3: Find the position of the digit within that number
    int position = (n - 1) % digits;

    // Step 4: Return the digit at the specified position
    for (int i = digits - 1; i > position; i--) {
        number /= 10;
    }

    return number % 10;
}

int main() {
    // Example usage
    int n = 11;
}

```

```

    int nthDigit = findNthDigit(n);

    // Print the result
    printf("The %dth digit is: %d\n", n, nthDigit);

    return 0;
}

```

Output: The 11th digit of the sequence 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, ... is a 0, which is part of the number 10.

Time/Space Complexity:O(log n)/O(1)

1.41 Minimize The Maximum Difference Of Pairs

```

#include <stdio.h>
#include <stdlib.h>

// Function to compare integers for qsort
int compare(const void* a, const void* b) {
    return (*(int*)a - *(int*)b);
}

// Function to find the number of valid pairs by greedy approach
int countValidPairs(int* nums, int size, int threshold) {
    int index = 0, count = 0;
    while (index < size - 1) {
        // If a valid pair is found, skip both numbers.
        if (nums[index + 1] - nums[index] <= threshold) {
            count++;
            index++;
        }
        index++;
    }
    return count;
}

// Function to minimize the maximum difference between pairs
int minimizeMax(int* nums, int size, int p) {
    // Sort the array
    qsort(nums, size, sizeof(int), compare);

    int left = 0, right = nums[size - 1] - nums[0];

    while (left < right) {
        int mid = left + (right - left) / 2;

        // If there are enough pairs, look for a smaller threshold.
        // Otherwise, look for a larger threshold.
        if (countValidPairs(nums, size, mid) >= p) {

```

```

        right = mid;
    } else {
        left = mid + 1;
    }
}
return left;
}

int main() {
    // Example usage
    int nums[] = {10, 1, 2, 7, 1, 3};
    int size = sizeof(nums) / sizeof(nums[0]);
    int p = 2;

    // Find the minimum maximum difference between pairs
    int result = minimizeMax(nums, size, p);

    printf("The minimum maximum difference between pairs: %d\n", result);

    return 0;
}

```

The first pair is formed from the indices 1 and 4, and the second pair is formed from the indices 2 and 5. The maximum difference is $\max(|\text{nums}[1] - \text{nums}[4]|, |\text{nums}[2] - \text{nums}[5]|) = \max(0, 1) = 1$. Therefore, we return 1

Output: 1

Time/Space Complexity: $O(n \log n)/O(1)$

1.42 Reverse Words In String II

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Function to reverse a portion of the array
void reverse(char* s, int start, int end) {
    while (start < end) {
        char temp = s[start];
        s[start] = s[end];
        s[end] = temp;
        start++;
        end--;
    }
}

// Function to reverse the order of words in-place
void reverseWords(char* s, int sSize) {
    // Step 1: Reverse the entire array
    reverse(s, 0, sSize - 1);

    // Step 2: Reverse each individual word
}
```

```

int start = 0;
for (int i = 0; i < sSize; i++) {
    if (s[i] == ' ' || i == sSize - 1) {
        // If space is encountered or at the end, reverse the word
        if (i == sSize - 1)
            reverse(s, start, i);
        else
            reverse(s, start, i - 1);
        start = i + 1;
    }
}
}

int main() {
    // Example usage
    char s[] = "the sky is blue";
    int sSize = strlen(s);

    // Reverse the order of words in the string
    reverseWords(s, sSize);

    // Print the result
    printf("Reversed string: %s\n", s);

    return 0;
}

```

Output: Blue is Sky The

Time/Space Complexity: O(n)/O(1)

1.43 Number Of Flowers In Full Bloom

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */

#include <stdio.h>
#include <stdlib.h>

// Utility function to perform binary search
int compareInt(const void* a, const void* b) {
    return (*(int*)a - *(int*)b);
}

int binarySearch(int* arr, int size, int target) {
    int left = 0, right = size - 1;
    while (left <= right) {
        int mid = left + (right - left) / 2;
        if (arr[mid] <= target) {
            left = mid + 1;
        } else {

```

```

        right = mid - 1;
    }
}
return left;
}

int* fullBloomFlowers(int** flowers, int flowersSize, int* flowersColSize, int* people,
int peopleSize, int* returnSize) {
    // Initialize arrays for start and end times
    int* starts = (int*)malloc(flowersSize * sizeof(int));
    int* ends = (int*)malloc(flowersSize * sizeof(int));

    // Populate start and end arrays
    for (int i = 0; i < flowersSize; i++) {
        starts[i] = flowers[i][0];
        ends[i] = flowers[i][1] + 1;
    }

    // Sort the start and end arrays
    qsort(starts, flowersSize, sizeof(int), compareInt);
    qsort(ends, flowersSize, sizeof(int), compareInt);

    // Initialize result array
    int* result = (int*)malloc(peopleSize * sizeof(int));

    // Process each person's arrival time
    for (int i = 0; i < peopleSize; i++) {
        int startCount = binarySearch(starts, flowersSize, people[i]);
        int endCount = binarySearch(ends, flowersSize, people[i]);
        result[i] = startCount - endCount;
    }

    // Set the return size
    *returnSize = peopleSize;

    // Free allocated memory
    free(starts);
    free(ends);

    return result;
}

int main() {
    // Example usage
    int flowersSize = 4;
    int* flowersColSize = (int*)malloc(flowersSize * sizeof(int));
    int** flowers = (int**)malloc(flowersSize * sizeof(int*));
    for (int i = 0; i < flowersSize; i++) {
        flowersColSize[i] = 2;
    }
}
```

```

        flowers[i] = (int*)malloc(flowersColSize[i] * sizeof(int));
    }
flowers[0][0] = 1; flowers[0][1] = 6;
flowers[1][0] = 3; flowers[1][1] = 7;
flowers[2][0] = 9; flowers[2][1] = 12;
flowers[3][0] = 4; flowers[3][1] = 13;
int people[] = {2, 3, 7, 11};
int peopleSize = sizeof(people) / sizeof(people[0]);
int returnSize;

// Call the function and get the result
int* result = fullBloomFlowers(flowers, flowersSize, flowersColSize, people,
peopleSize, &returnSize);

// Print the result
printf("Result: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", result[i]);
}
printf("\n");

// Free allocated memory
for (int i = 0; i < flowersSize; i++) {
    free(flowers[i]);
}
free(flowersColSize);
free(flowers);
free(result);

return 0;
}

```

Output:

1	2	3	4	5	6	7	8	9	10	11	12	13	
	0	1				2				3			

Input: flowers = [[1,6],[3,7],[9,12],[4,13]], people = [2,3,7,11]

Output: [1,2,2,2]

Explanation: The figure above shows the times when the flowers are in full bloom and when the people arrive.

For each person, we return the number of flowers in full bloom during their arrival.

How many flowers can you see at time 11?

starts	1	3	4	9
--------	---	---	---	---

4 flowers have already started blooming

ends	6	7	12	13
------	---	---	----	----

2 flowers have already finished blooming

Time/Space Complexity: $O(m+n(\log n))/O(m + n)$

1.44 Restore IP addresses

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

typedef struct {
    char* data;
    int length;
} String;

void rec(const char* s, int i, char** address, int addressSize, char*** addresses, int* returnSize);
int isValid(const char* s, int start, int length);

void rec(const char* s, int i, char** address, int addressSize, char*** addresses, int* returnSize) {
    if (addressSize == 4) {
        if (s[i] == '\0') {
            // If we have reached the end of the input string, add the current address
            // to the list of valid addresses
            char* current = (char*)malloc(16 * sizeof(char)); // Maximum IP address
            // length is 15
            sprintf(current, 16, "%s.%s.%s.%s", address[0], address[1], address[2],
            address[3]);
            *addresses = realloc(*addresses, (*returnSize + 1) * sizeof(char*));
            (*addresses)[*returnSize] = current;
            (*returnSize)++;
        }
    }
}
```

```

        (*returnSize)++;  

        *addresses = (char**)realloc(*addresses, (*returnSize) * sizeof(char*));  

        (*addresses)[*returnSize - 1] = current;  

    }  

} else {  

    // Try all possible next segments for the current address  

    for (int j = i + 1; j <= i + 3 && s[j - 1] != '\0'; j++) {  

        char* nextInt = (char*)malloc((j - i + 1) * sizeof(char));  

        strncpy(nextInt, s + i, j - i);  

        nextInt[j - i] = '\0';  

        // Check if the next segment is valid (between 0 and 255, and not starting  

        with 0 unless it is 0)  

        if (isValid(nextInt, 0, j - i)) {  

            // Add the next segment to the current address  

            address[addressSize] = nextInt;  

            // Recursively call the function to generate the next segment  

            rec(s, j, address, addressSize + 1, addresses, returnSize);  

        }
    }
}
}

int isValid(const char* s, int start, int length) {
    int num = 0;
    for (int i = 0; i < length; i++) {
        num = num * 10 + (s[start + i] - '0');
    }
    return (num <= 255) && (length == 1 || (s[start] != '0'));
}

char** restoreIpAddresses(char* s, int* returnSize) {
    *returnSize = 0;
    char** addresses = NULL;

    char* address[4] = {"", "", "", ""};
    rec(s, 0, address, 0, &addresses, returnSize);

    return addresses;
}

int main() {
    char* s = "25525511135";
    int returnSize;
    char** addresses = restoreIpAddresses(s, &returnSize);

    // Print the restored IP addresses
    printf("Restored IP Addresses:\n");
    for (int i = 0; i < returnSize; i++) {

```

```

        printf("%s\n", addresses[i]);
        free(addresses[i]); // Free memory allocated for each address
    }
    free(addresses); // Free memory allocated for the array of addresses

    return 0;
}

```

Output:["255.255.11.135","255.255.111.35"]

Time/Space Complexity:O(3 ^ 4) / O(3 ^ 4) - 3 choices for 4 segments

1.45 SubArray Sum Divisible By K

```

#include <stdio.h>
#include <stdlib.h>

int subarraysDivByK(int* nums, int numsSize, int k) {
    int n = numsSize;
    int prefixMod = 0, result = 0;

    // There are k mod groups 0...k-1.
    int* modGroups = (int*)calloc(k, sizeof(int));
    modGroups[0] = 1;

    for (int i = 0; i < n; ++i) {
        // Take modulo twice to avoid negative remainders.
        prefixMod = (prefixMod + nums[i] % k + k) % k;
        // Add the count of subarrays that have the same remainder as the current
        result += modGroups[prefixMod]++;
    }

    free(modGroups);

    return result;
}

int main() {
    int nums[] = {4, 5, 0, -2, -3, 1};
    int numsSize = sizeof(nums) / sizeof(nums[0]);
    int k = 5;

    int result = subarraysDivByK(nums, numsSize, k);

    printf("Number of subarrays divisible by %d: %d\n", k, result);

    return 0;
}

```

The problem is based on the concept of using prefix sums to compute the total number of subarrays that are divisible by k . A prefix sum array for nums is another array prefixSum of the same size as nums , such that the value of $\text{prefixSum}[i]$ is the sum of all elements of the nums array from index 0 to index i , i.e., $\text{nums}[0] + \text{nums}[1] + \text{nums}[2] + \dots + \text{nums}[i]$.

The sum of the subarray $[i+1]$ to j (inclusive) is computed by $\text{prefixSum}[j] - \text{prefixSum}[i]$. Using this, we can count the number of pairs that exist for every pair (i, j) where $i < j$ and $(\text{prefixSum}[j] - \text{prefixSum}[i]) \% k = 0$. There are $n * (n - 1) / 2$ pairs for an array of length n (pick any two from n). As a result, while this will provide the correct answer for every test case, it will take $O(n^2)$ time, indicating that the time limit has been exceeded (TLE).

The character $\%$ is the modulo operator.

Let's try to use the information with respect to the remainders of every prefix sum and try to optimize the above approach.


As stated previously, our task is to determine the number of pairs (i, j) where $i < j$ and $(\text{prefixSum}[j] - \text{prefixSum}[i]) \% k = 0$. This equality can only be true if $\text{prefixSum}[i] \% k = \text{prefixSum}[j] \% k$. We will demonstrate this property.

We can express any number as $\text{number} = \text{divisor} \times \text{quotient} + \text{remainder}$. For example, 13 when divided by 3 can be written as $13 = 3 * 4 + 1$. So we can express:


- $\text{prefixSum}[i]$ as $\text{prefixSum}[i] = A * k + R_0$ where A is the quotient and R_0 is the remainder when divided by k .
- Similarly, $\text{prefixSum}[j] = B * k + R_1$ where B is the quotient and R_1 is the remainder when divided by k .

We can write, $\text{prefixSum}[j] - \text{prefixSum}[i] = k * (B - A) + (R_1 - R_0)$. The first term $(k * (B - A))$ is divisible by k , so for the entire expression to be divisible by k , $R_1 - R_0$ must also be divisible by k . This gives us an equation $R_1 - R_0 = C * k$, where C is some integer. Rearranging it yields $R_1 = C * k + R_0$. Because the values of R_0 and R_1 will be between 0 and $k - 1$, R_1 cannot be greater than k . So the only possible value for C is 0 , leading to $R_0 = R_1$, which proves the above property. If $C > 0$, then the RHS would be at least k , but as stated the LHS (R_1) is between 0 and $k - 1$.

Here are two visual examples showing the calculations:



Since $\text{prefixSum}[j]\%k == \text{prefixSum}[i] \%k$, we can see the subarray from $i+1$ to j , is divisible by k .



Since $\text{prefixSum}[j]\%k != \text{prefixSum}[i] \%k$, we can see the subarray from $i+1$ to j , is not divisible by k .

Output: There are 7 subarrays with a sum divisible by $k = 5$:

[4, 5, 0, -2, -3, 1], [5], [5, 0], [5, 0, -2, -3], [0], [0, -2, -3], [-2, -3]

Time/Space complexity : $O(n)/O(k)$

1.46 Find Missing Observations

/**

```

 * Note: The returned array must be malloced, assume caller calls free().
 */
#include <stdio.h>
#include <stdlib.h>

int* missingRolls(int* rolls, int rollsSize, int mean, int n, int* returnSize) {
    int orig_sum = 0;

    *returnSize = 0;
    int *result = (int *)malloc(sizeof(int) * n);
    for (int i = 0; i < rollsSize; i++) {
        orig_sum += rolls[i];
    }
    printf("\nOrig_sum = %d", orig_sum);
    int expected_sum = (mean * (n + rollsSize));
    printf("\nExpected_sum = %d", expected_sum);
    int missing_sum = expected_sum - orig_sum;
    printf("\nMissing_sum = %d", missing_sum);
    int missing_value = missing_sum / n;
    int remainder = missing_sum % n;
    printf("\nMissing Value = %d", missing_value);
    if ((missing_value > 6) || (missing_sum != 0 && missing_value == 0) || (missing_sum
< 0) || ((missing_value == 6) && (remainder != 0))) return result;
    for (int j = 0; j < n; j++) {
        result[j] = missing_value;
        (*returnSize)++;
    }
    for (int j = 0; j < n; j++) {
        while (remainder != 0) {
            if (missing_value < 6) {
                if (result[j] < 6) {
                    result[j]++;
                    remainder -= 1;
                } else {
                    break;
                }
            } else {
                continue;
            }
        }
    }
    return result;
}

int main() {
    int rolls[] = {3, 2, 4, 3};
    int rollsSize = sizeof(rolls) / sizeof(rolls[0]);
    int mean = 4;
}

```

```

int n = 2;

int returnSize;
int* result = missingRolls(rolls, rollsSize, mean, n, &returnSize);

printf("Missing Rolls: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", result[i]);
}
printf("\n");

free(result); // Don't forget to free allocated memory

return 0;
}

```

Output:[6,6]

Explanation: The mean of all $n + m$ rolls is $(3 + 2 + 4 + 3 + 6 + 6) / 6 = 4$.

Time/Space Complexity:O(n)/O(1)

1.47 Largest Palindromic Number

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* largestPalindromic(char* num) {
    int cnt[10] = {0};
    int n = strlen(num);

    // Count occurrences of each digit
    for (int i = 0; i < n; i++) {
        cnt[num[i] - '0']++;
    }

    char* lp = (char*)malloc((n + 1) * sizeof(char));
    char* rp = (char*)malloc((n + 1) * sizeof(char));
    int lpIndex = 0;
    int rpIndex = 0;

    // Build left and right partitions
    for (int i = 0; i < n; i++) {
        for (int j = 9; j >= 0; j--) {
            if (cnt[j] > 1 && (j > 0 || lpIndex > 0)) {
                lp[lpIndex++] = '0' + j;
                rp[rpIndex++] = '0' + j;
                cnt[j] -= 2;
                break;
            }
        }
    }
}

```

```

    }

    // Find the middle digit (if any)
    for (int i = 9; i >= 0; i--) {
        if (cnt[i]) {
            lp[lpIndex++] = '0' + i;
            break;
        }
    }

    // Reverse the right partition
    for (int i = rpIndex - 1; i >= 0; i--) {
        lp[lpIndex++] = rp[i];
    }

    // Null-terminate the result
    lp[lpIndex] = '\0';

    free(rp);

    return lp;
}

int main() {
    char num[] = "444947137";
    char* result = largestPalindromic(num);

    printf("Largest Palindromic Integer: %s\n", result);

    free(result); // Don't forget to free allocated memory

    return 0;
}

```

Output: Use the digits "4449477" from "**444947**13**7**" to form the palindromic integer "7449447".
 It can be shown that "7449447" is the largest palindromic integer that can be formed.

Time/Space Complexity:O(n)/O(n)

1.48 Basic Calculator I

```

#include <stdio.h>
#include <ctype.h>

int evaluate(char operator, int x, int y) {
    if (operator == '+') {
        return x + y;
    } else if (operator == '-') {
        return x - y;
    } else if (operator == '*') {

```

```

        return x * y;
    }

    return x / y;
}

int calculate(const char* s) {
    int result = 0;
    int num = 0;
    char op = '+';
    const char* ptr = s;

    while (*ptr != '\0') {
        if (isdigit(*ptr)) {
            num = 0;
            while (isdigit(*ptr)) {
                num = num * 10 + (*ptr - '0');
                ptr++;
            }
            result = evaluate(op, result, num);
        } else if (*ptr == '+' || *ptr == '-' || *ptr == '*' || *ptr == '/') {
            op = *ptr;
            ptr++;
        } else {
            // Ignore whitespace
            ptr++;
        }
    }

    return result;
}

int main() {
    const char* expression = "3 + 4 * 2 - 10 / 5"; // Example expression
    int result = calculate(expression);
    printf("Result: %d\n", result); // Output the result
    return 0;
}

```

Example 2:

Input:	s = "2-1+2"
Output:	3

Example 3:

Input:	s = "(1+(4+5+2)-3)+(6+8)"
Output:	23

Time/Space Complexity : O(n)/O(1)

1.49 Basic Calculator II

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

int parseExpr(char* s, int* i);
int parseNum(char* s, int* i);
int calculate(char* s);

int main() {
    char expression[] = "3 + 4 * 2 - 10 / 5"; // Example expression
    int result = calculate(expression);
    printf("Result: %d\n", result); // Output the result
    return 0;
}

int calculate(char* s) {
    int i = 0;
    return parseExpr(s, &i);
}

int parseExpr(char* s, int* i) {
    int nums[1000]; // Assuming a maximum of 1000 numbers
    int numIndex = 0;
    char op = '+';
    for (; *i < strlen(s); (*i)++) {
        if (s[*i] == ' ') continue;
        int n = parseNum(s, i);
        switch(op) {
            case '+': nums[numIndex++] = n; break;
            case '-': nums[numIndex++] = -n; break;
            case '*': nums[numIndex - 1] *= n; break;
            case '/': nums[numIndex - 1] /= n; break;
        }
        op = s[*i];
    }

    int result = 0;
    for (int j = 0; j < numIndex; j++) {
        result += nums[j];
    }

    return result;
}

int parseNum(char* s, int* i) {
    int n = 0;
```

```

    while(*i < strlen(s) && isdigit(s[*i]))
        n = s[(*i)++] - '0' + 10 * n;
    return n;
}

```

Input: s = "3+2*2"

Output: 7

Time/Space Complexity: O(n)/O(1)

1.50 Basic Calculator III

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <ctype.h>

int evaluate(char operator, int x, int y) {
    if (operator == '+') {
        return x;
    } else if (operator == '-') {
        return -x;
    } else if (operator == '*') {
        return x * y;
    }

    return x / y;
}

int solve(const char* s, int* i) {
    int stack[1000];
    int top = -1;
    int curr = 0;
    char previousOperator = '+';

    while (s[*i] != '\0') {
        char c = s[(*i)++];
        if (c == '(') {
            curr = solve(s, i);
        } else if (isdigit(c)) {
            curr = curr * 10 + (c - '0');
        } else {
            if (previousOperator == '*' || previousOperator == '/') {
                stack[++top] = evaluate(previousOperator, stack[top--], curr);
            } else {
                stack[++top] = evaluate(previousOperator, curr, 0);
            }
        }

        if (c == ')') {
            break;
        }
    }
}

```

```

        }

        curr = 0;
        previousOperator = c;
    }
}

int ans = 0;
for (int j = 0; j <= top; j++) {
    ans += stack[j];
}

return ans;
}

int calculate(const char* s) {
    char str[strlen(s) + 2];
    strcpy(str, s);
    strcat(str, "@");
    int i = 0;
    return solve(str, &i);
}

int main() {
    const char* expression = "2*(5+5*2)/3+(6/2+8)";
    int result = calculate(expression);
    printf("Result: %d\n", result);
    return 0;
}

```

Input: s = "2*(5+5*2)/3+(6/2+8)"

Output: 21

s


Time/Space Complexity : O(n)/O(n)

1.51 Inorder Successor of Binary Search Tree

Given the root of a binary search tree and a node p in it, return *the in-order successor of that node in the BST*. If the given node has no in-order successor in the tree, return null.

The successor of a node p is the node with the smallest key greater than p.val.

Example 1:




Input: root = [2,1,3], p = 1

Output: 2

Explanation: 1's in-order successor node is 2. Note that both p and the return value is of `TreeNode` type.

Example 2:



Input: root = [5,3,6,2,4,null,null,1], p = 6

Output: null

Explanation: There is no in-order successor of the current node, so the answer is null.

C:

```

#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to find the inorder successor of a given node in a binary search tree
struct TreeNode* inorderSuccessor(struct TreeNode* root, struct TreeNode* p) {
    struct TreeNode *successor = NULL;
    while (root != NULL) {
        if (p->val < root->val) {
            successor = root;
            root = root->left;
        } else {
            root = root->right;
        }
    }
    return successor;
}

```

```

        root = root->left;
    } else {
        root = root->right;
    }
}
return successor;
}

// Function to create a new node
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

// Main function for testing the inorderSuccessor function
int main() {
    struct TreeNode* root = newNode(2);
    root->left = newNode(1);
    root->right = newNode(3);

    struct TreeNode* target = root->left; // Node with value 6
    struct TreeNode* successor = inorderSuccessor(root, target);

    if (successor != NULL) {
        printf("Inorder successor of %d is %d.\n", target->val, successor->val);
    } else {
        printf("Inorder successor of %d does not exist.\n", target->val);
    }

    // Free allocated memory
    free(root->left);
    free(root->right);
    free(root);

    return 0;
}

```

Output: 1's in-order successor node is 2. Note that both p and the return value is of TreeNode type.

Time/Space Complexity:O(height)/ O(1)

1.52 Regular Expression Matching

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <string.h>
```

```

bool isMatch(char* s, char* p) {
    int m = strlen(s);
    int n = strlen(p);

    // Create a 2D array to store intermediate results
    bool dp[m + 1][n + 1];
    memset(dp, false, sizeof(dp));

    // Empty pattern matches empty string
    dp[0][0] = true;

    // Handle patterns with '*'
    for (int j = 1; j <= n; j++) {
        if (p[j - 1] == '*') {
            dp[0][j] = dp[0][j - 2];
        }
    }

    // Dynamic programming to fill the rest of the array
    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (p[j - 1] == s[i - 1] || p[j - 1] == '.') {
                dp[i][j] = dp[i - 1][j - 1];
            } else if (p[j - 1] == '*') {
                dp[i][j] = dp[i][j - 2];
                if ((s[i - 1] == p[j - 2]) || (p[j - 2] == '.')) {
                    dp[i][j] = dp[i][j] | dp[i-1][j];
                }
            }
        }
    }

    return dp[m][n];
}

// Main function for testing the isMatch function
int main() {
    char s[] = "aa";
    char p[] = "a*";

    bool result = isMatch(s, p);

    if (result) {
        printf("String \"%s\" matches pattern \"%s\".\n", s, p);
    } else {
        printf("String \"%s\" does not match pattern \"%s\".\n", s, p);
    }
}

```

```
    return 0;
}
```

Example 1:

Input: s = "aa", p = "a"

Output: false

Explanation: "a" does not match the entire string "aa".

Example 2:

Input: s = "aa", p = "a*"

Output: true

Explanation: '*' means zero or more of the preceding element, 'a'. Therefore, by repeating 'a' once, it becomes "aa".

Example 3:

Input: s = "ab", p = ".*"

Output: true

Explanation: ".*" means "zero or more (*) of any character ()".

Output:'*' means zero or more of the preceding element, 'a'. Therefore, by repeating 'a' once, it becomes "aa".

Time/Space Complexity:O(m*n)/O(m*n)

1.53 Remove All Adjacent Duplicates In String

```
#include<stdio.h>
#include<string.h>
char* removeDuplicates(char* s) {
    int len = strlen(s);
    int top = -1; // Initialize top of the "stack"

    for (int i = 0; i < len; ++i) {
        if (top >= 0 && s[top] == s[i]) {
            // If the current character matches the top of the "stack", pop the "stack"
            --top;
        } else {
            // Otherwise, push the current character onto the "stack"
            s[++top] = s[i];
        }
    }

    // Null-terminate the string
    s[top + 1] = '\0';
}
```

```

        return s;
    }
int main() {
    char s[] = "abbaca";
    printf("Original string: %s\n", s);

    char* result = removeDuplicates(s);

    printf("String after removing duplicates: %s\n", result);

    return 0;
}

```

Input:	s = "abbaca"
Output:	"ca"

Time/Space Complexity:O(n)/O(1)

1.54 Fibonacci Series

```

int fib(int N) {
    if (N <= 1) {
        return N;
    }

    int current = 0;
    int prev1 = 1;
    int prev2 = 0;

    for (int i = 2; i <= N; i++) {
        current = prev1 + prev2;
        prev2 = prev1;
        prev1 = current;
    }
    return current;
}

int main() {
    int n = 6;
    int result = fib(n);
    printf("fib(%d) = %d\n", n, result);
    return 0;
}

```

O(N)/O(1)

```
#include <stdio.h>

int fib(int n){
    if (n == 0) return 0;
    if (n == 1) return 1;
```

```

        return fib(n-1) + fib(n-2);
    }

int main() {
    int n = 6;
    int result = fib(n);
    printf("fib(%d) = %d\n", n, result);
    return 0;
}

#include <stdio.h>

int memo[31] = {0}; // Memoization array for Fibonacci numbers

// Recursive function to calculate Fibonacci number
int fib(int n) {
    if (n <= 1)
        return n;
    if (memo[n]) // If the value is already memoized, return it
        return memo[n];
    return memo[n] = fib(n - 1) + fib(n - 2); // Memoize and return the Fibonacci number
    // Alternatively, you can use a 1-liner:
    // return memo[n] = memo[n] ? memo[n] : n <= 1 ? n : fib(n - 1) + fib(n - 2);
}

int main() {
    // Test the fib function
    int n = 10; // Example input
    printf("Fibonacci number at position %d is: %d\n", n, fib(n));

    return 0;
}

#include <stdio.h>

int dp[31] = {0}; // Dynamic programming array for Fibonacci numbers

// Function to calculate Fibonacci number iteratively using dynamic programming
int fib(int n) {
    if (n <= 1)
        return n;
    dp[0] = 0, dp[1] = 1; // Initialize dp array for base cases
    for (int i = 2; i <= n; i++)
        dp[i] = dp[i - 1] + dp[i - 2]; // Compute Fibonacci numbers iteratively
    return dp[n];
}

int main() {
    // Test the fib function

```

```

    int n = 10; // Example input
    printf("Fibonacci number at position %d is: %d\n", n, fib(n));

    return 0;
}

```

Time/Space Complexity: O(n)/O(n)

1.55 Path With Minimum Effort (Hiking heights)

```

#include <stdio.h>
#include <stdlib.h>
#include <limits.h>
#include <math.h>

// Structure to represent a priority queue node
typedef struct {
    int dist;
    int row;
    int col;
} PQNode;

// Structure to represent a priority queue
typedef struct {
    PQNode data[10000];
    int size;
} PriorityQueue;

// Function to initialize the priority queue
void initPriorityQueue(PriorityQueue *pq) {
    pq->size = 0;
}

void push(PriorityQueue *pq, PQNode node) {
    int idx = pq->size++;
    pq->data[idx] = node;

    // Maintain min heap property
    while (idx > 0 && pq->data[(idx - 1) / 2].dist > pq->data[idx].dist) {
        // Swap the current node with its parent
        PQNode temp = pq->data[idx];
        pq->data[idx] = pq->data[(idx - 1) / 2];
        pq->data[(idx - 1) / 2] = temp;

        // Move up in the heap
        idx = (idx - 1) / 2;
    }
}

// Function to pop the top node from the priority queue
PQNode pop(PriorityQueue *pq) {

```

```

PQNode top = pq->data[0];
for (int i = 1; i < pq->size; ++i) {
    pq->data[i - 1] = pq->data[i];
}
pq->size--;
return top;
}

// Function to find the minimum of two integers
int min(int a, int b) {
    return a < b ? a : b;
}

// Function to get the absolute difference of two integers
int absDiff(int a, int b) {
    return abs(a - b);
}

// Function to find the minimum effort path
int minimumEffortPath(int** heights, int heightsSize, int* heightsColSize) {
    int m = heightsSize;
    int n = *heightsColSize;

    // Initialize distance array with a large value
    int dist[m][n];
    for (int i = 0; i < m; ++i) {
        for (int j = 0; j < n; ++j) {
            dist[i][j] = INT_MAX;
        }
    }
}

// Initialize priority queue
PriorityQueue pq;
initPriorityQueue(&pq);

// Push source cell into the priority queue
PQNode source = {0, 0, 0};
push(&pq, source);
dist[0][0] = 0;
int ans = INT_MAX;
// Directions array
int DIR[] = {0, 1, 0, -1, 0};

// Dijkstra's algorithm
while (pq.size > 0) {
    PQNode node = pop(&pq);
    int d = node.dist;
    int r = node.row;
    int c = node.col;
}

```

```

    if (r == m - 1 && c == n - 1) {
        ans = fmin(ans,d);
    }

    // Explore neighbors
    for (int i = 0; i < 4; ++i) {
        int nr = r + DIR[i];
        int nc = c + DIR[i + 1];

        if (nr >= 0 && nr < m && nc >= 0 && nc < n) {
            int newDist = fmax(d, absDiff(heights[nr][nc], heights[r][c]));
            if (dist[nr][nc] > newDist) {
                dist[nr][nc] = newDist;
                PQNode newNode = {newDist, nr, nc};
                push(&pq, newNode);
            }
        }
    }
}

return (ans == INT_MAX)?0:ans;
}

int main() {
    int heights1[3][3] = {{1, 2, 2}, {3, 8, 2}, {5, 3, 5}};
    int heightsSize1 = 3;
    int heightsColSize1 = 3;
    printf("Minimum effort path for example 1: %d\n", minimumEffortPath((int**)heights1,
heightsSize1, &heightsColSize1));

    return 0;
}

```

Time/Space Complexity: $O(\log n)/O(n)$

I've explained the first test case below for better understanding.

1631) Path with Minimum Effort

1	2	2
3	8	2
5	3	5

dist	0	∞	∞
	∞	∞	∞
	∞	∞	∞

$PA = \underline{\underline{0, 1, 0, 0}}$

top

$dist[i][j]$ = minimum effort for a path which goes through $[i][j]$ cell

We can see, for cell $[0, 1]$ we have

$$\text{new effort} = \max(0, 2-1) = 1$$

& for $[1, 0]$ we have

$$\text{new effort} = \max(0, 3-1) = 2$$

so

0	1	∞
2	∞	∞
∞	∞	∞

$PA = \underline{\underline{1, 0, 1, 2, 1, 0, 0}}$

top & pop

Now least effort we have for $[0][1]$ cell

so we explore it

$$[1, 1] \rightarrow \max(8-2, 1) = 6$$

$$[0, 2] \rightarrow \max(2-2, 1) = 1$$

PA

$\underline{\underline{1, 0, 1, 2, 1, 2, 1, 1, 0, 1, 1, 1}}$

0	1	1
2	6	∞
∞	∞	∞

Now, next least is cell $[0, 2]$

so, update efforts for its adjacent

0	1	1
2	6	1
∞	∞	∞

$$[1][2] \rightarrow \max(2-2, 1) = 1$$

PQ $\rightarrow \underline{1, f_{1,2}} | 2, f_{1,0y} | 6, f_{1,1y}$

Next least is cell $[1, 2]$

$$[1, 2] \rightarrow \max(8-2, 6) = 6 \quad \& \quad 6 = 6$$

$$[2, 2] \rightarrow \max(5-2, 1) = 3 \quad \& \quad 3 < \infty$$

PQ $\rightarrow \underline{2, f_{2,0y}} | 3, f_{2,2y} | 6, f_{1,1y}$

Next least is cell $[1, 0]$

$$[1, 0] \rightarrow \max(8-3, 2) = 5 \quad \& \quad 5 < 6$$

$$[2, 0] \rightarrow \max(5-3, 2) = 2 \quad \& \quad 2 < \infty$$

PQ $\rightarrow \underline{2, f_{2,0y}} | 3, f_{2,2y} | 5, f_{1,1y}$

Next least is cell $[2, 0]$

0	1	1
2	5 y	1
2	2	3

$$[1, 0] \rightarrow \max(5-3, 2) = 2 \quad \& \quad 2 = 2$$

$$[2, 1] \rightarrow \max(5-3, 2) = 2 \quad \& \quad 2 < \infty$$

PQ $\rightarrow \underline{2, f_{2,1y}} | 3, f_{2,2y} | 5, f_{1,1y}$

Next least is cell $[2, 1]$

$$[2, 1] \rightarrow \max(5-3, 2) = 2 \quad \& \quad 2 < 3$$

PQ $\rightarrow \underline{2, f_{2,1y}} | 3, f_{2,2y} | 5, f_{1,1y}$

Next least is $[2, 2]$

But $[2, 2]$ is our destination

so 2 is our answer

0	1	1
2	5 y	1
2	2	3 y

1.56 Longest Cycle In Graph

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <limits.h>

#define MAX_NODES 1000 // Assuming a maximum of 1000 nodes

int longestCycle(int* edges, int edgesSize) {
    int n = edgesSize;
    int visit[MAX_NODES] = {0};
    int indegree[MAX_NODES] = {0};

    // Count indegree of each node.
    for (int i = 0; i < n; i++) {
        int edge = edges[i];
        if (edge != -1) {
            indegree[edge]++;
        }
    }

    // Kahn's algorithm starts.
    int q[MAX_NODES], front = 0, rear = -1;
    for (int i = 0; i < n; i++) {
        if (indegree[i] == 0) {
            q[++rear] = i;
        }
    }

    while (front <= rear) {
        int node = q[front++];
        visit[node] = 1;
        int neighbor = edges[node];
        if (neighbor != -1) {
            indegree[neighbor]--;
            if (indegree[neighbor] == 0) {
                q[++rear] = neighbor;
            }
        }
    }

    // Kahn's algorithm ends.

    int answer = -1;
    for (int i = 0; i < n; i++) {
        if (!visit[i]) {
            int neighbor = edges[i];
            int count = 1;
```


```

        visit[i] = 1;
        // Iterate in the cycle.
        while (neighbor != i) {
            visit[neighbor] = 1;
            count++;
            neighbor = edges[neighbor];
        }
        answer = (answer < count) ? count : answer;
    }
}

return answer;
}

int main() {
    int edges[] = {3,3,4,2,3}; // Example edges array
    int edgesSize = sizeof(edges) / sizeof(edges[0]);
    int result = longestCycle(edges, edgesSize);
    printf("Length of the longest cycle: %d\n", result);
    return 0;
}

```



Input: edges = [3,3,4,2,3]

Output: 3

Explanation: The longest cycle in the graph is the cycle: 2 -> 4 -> 3 -> 2.

The length of this cycle is 3, so 3 is returned.

Time/Space Complexity: O(n)/O(n)

1.57 Maximum Value Of K Coins From Piles

```

#include <stdio.h>
#include <stdlib.h>

#define max(a, b) ((a) > (b) ? (a) : (b))
#define min(a, b) ((a) < (b) ? (a) : (b))

#define MAX_N 100
#define MAX_K 10000

```

```

int** dp;

int knapsack(int** piles, int* pilesColSize, int n, int k) {
    if (n < 0 || k == 0) return 0;

    if (dp[n][k] != -1) return dp[n][k];

    int pileSize = pilesColSize[n];
    int maxSize = min(pileSize, k);

    int exclude = knapsack(piles, pilesColSize, n - 1, k);

    int include = 0;
    for (int j = 0, sum = 0; j < maxSize; j++) {
        sum += piles[n][j];
        include = max(sum + knapsack(piles, pilesColSize, n - 1, k - j - 1), include);
    }

    int res = max(include, exclude);

    dp[n][k] = res;
    return res;
}

int maxValueOfCoins(int** piles, int pilesSize, int* pilesColSize, int k) {
    dp = (int**)malloc((pilesSize + 1) * sizeof(int*));
    for (int i = 0; i <= pilesSize; i++) {
        dp[i] = (int*)malloc((k + 1) * sizeof(int));
        for (int j = 0; j <= k; j++) {
            dp[i][j] = -1;
        }
    }

    int result = knapsack(piles, pilesColSize, pilesSize - 1, k);

    for (int i = 0; i <= pilesSize; i++) {
        free(dp[i]);
    }
    free(dp);

    return result;
}

int main() {
    // Example 1
    int piles1[][3] = {{1,100,3}, {7,8,9}};
    int pilesColSize1[] = {3, 3};
    int k1 = 2;
}

```

```


    printf("Example 1 Output: %d\n", maxValueOfCoins((int**)piles1, 2, pilesColSize1,
k1)); // Output: 101

    // Example 2
    int piles2[][7] = {{100}, {100}, {100}, {100}, {100}, {100}, {1,1,1,1,1,1,700}};
    int pilesColSize2[] = {1, 1, 1, 1, 1, 1, 7};
    int k2 = 7;
    printf("Example 2 Output: %d\n", maxValueOfCoins((int**)piles2, 7, pilesColSize2,
k2)); // Output: 706

    return 0;
}

```

Example 1:



Input: piles = [[1,100,3],[7,8,9]], k = 2

Output: 101

Explanation:

The above diagram shows the different ways we can choose k coins.

The maximum total we can obtain is 101.

Time/Space Complexity: O(n*k*maxsize)/O(n*k)

1.58 Flip Equivalent Binary Trees

```

#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

```

```

// Function prototypes
void dfs(struct TreeNode* node, int** vals, int* valsSize);
bool flipEquiv(struct TreeNode* root1, struct TreeNode* root2);

bool flipEquiv(struct TreeNode* root1, struct TreeNode* root2) {
    // If both roots are NULL, they are equivalent
    if (root1 == NULL && root2 == NULL) {
        return true;
    }
    // If one root is NULL and the other is not, they are not equivalent
    if (root1 == NULL || root2 == NULL) {
        return false;
    }
    // If values are not equal, they are not equivalent
    if (root1->val != root2->val) {
        return false;
    }
    // Check if either both nodes have no children or both nodes have children
    bool childrenEquivalent = (flipEquiv(root1->left, root2->left) && flipEquiv(root1->right, root2->right)) ||
                                (flipEquiv(root1->left, root2->right) && flipEquiv(root1->right, root2->left));
    return childrenEquivalent;
}
// Function to create a new tree node
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

int main() {
    // Example trees
    struct TreeNode* root1 = newNode(1);
    root1->left = newNode(2);
    root1->right = newNode(3);
    root1->left->left = newNode(4);
    root1->left->right = newNode(5);
    root1->right->left = newNode(6);
    root1->right->right = newNode(-1);
    root1->left->left->left = newNode(-1);
    root1->left->left->right = newNode(-1);
    root1->left->right->left = newNode(7);
    root1->left->right->right = newNode(8);

    struct TreeNode* root2 = newNode(1);

```

```

root2->left = newNode(3);
root2->right = newNode(2);
root2->left->left = newNode(-1);
root2->left->right = newNode(4);
root2->left->right->left = newNode(-1);
root2->left->right->right = newNode(-1);
root2->right->left = newNode(6);
root2->right->left->left = newNode(-1);
root2->right->left->right = newNode(-1);
root2->right->right = newNode(5);
root2->right->right->left = newNode(8);
root2->right->right->right = newNode(7);

// Check if the trees are flip equivalent
printf("Trees are %s flip equivalent.\n", flipEquiv(root1, root2) ? "" : " not");


// Free memory
free(root1->left->right->left);
free(root1->left->right->right);
free(root1->left->right);
free(root1->left);
free(root1->right->left);
free(root1->right->right);
free(root1->right);
free(root1);

free(root2->left->right);
free(root2->left);
free(root2->right->left);
free(root2->right->right->left);
free(root2->right->right->right);
free(root2->right->right);
free(root2->right);
free(root2);

return 0;
}

```

Example 1:



Input: root1 = [1,2,3,4,5,6,null,null,null,7,8], root2 = [1,3,2,null,6,4,5,null,null,null,8,7]

Output: true

Explanation: We flipped at nodes with values 1, 3, and 5.

Time/Space Complexity : O(n)/O(h)

```
// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function prototypes
void dfs(struct TreeNode* node, int** vals, int* valsSize);
bool flipEquiv(struct TreeNode* root1, struct TreeNode* root2);

// Function to perform depth-first traversal and store node values
void dfs(struct TreeNode* node, int** vals, int* valsSize) {
    if (node != NULL) {
        // Add node value to the list of values
        (*vals)[(*valsSize)++] = node->val;

        // Store values of left and right children, or -1 if child is NULL
        int L = node->left != NULL ? node->left->val : -1;
        int R = node->right != NULL ? node->right->val : -1;

        // Choose the order of traversal based on values of left and right children
        if (L < R) {
            dfs(node->left, vals, valsSize);
            dfs(node->right, vals, valsSize);
        } else {
            dfs(node->right, vals, valsSize);
            dfs(node->left, vals, valsSize);
        }
    }
}
```

```

        dfs(node->left, vals, valsSize);
    }

    // Add a marker (null) to indicate end of subtree
    (*vals)[(*valsSize)++] = -1;
}
}

// Function to check if two trees are flip equivalent
bool flipEquiv(struct TreeNode* root1, struct TreeNode* root2) {
    // If both roots are NULL, they are equivalent
    if (root1 == NULL && root2 == NULL) {
        return true;
    }
    // If one root is NULL and the other is not, they are not equivalent
    if (root1 == NULL || root2 == NULL) {
        return false;
    }

    // Allocate memory to store values of tree nodes during traversal
    int* vals1 = (int*)malloc(sizeof(int) * 1000);
    int* vals2 = (int*)malloc(sizeof(int) * 1000);
    int valsSize1 = 0, valsSize2 = 0;

    // Perform depth-first traversal for both trees
    dfs(root1, &vals1, &valsSize1);
    dfs(root2, &vals2, &valsSize2);

    // Check if the values obtained from both trees are equal
    bool areEquivalent = true;
    if (valsSize1 == valsSize2) {
        for (int i = 0; i < valsSize1; i++) {
            if (vals1[i] != vals2[i]) {
                areEquivalent = false;
                break;
            }
        }
    } else {
        areEquivalent = false;
    }

    // Free dynamically allocated memory
    free(vals1);
    free(vals2);

    return areEquivalent;
}

```

1.59 Maximum Length Of a Concatenated String With Unique Characters

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Function prototype
int solve(char** arr, int arrSize, char* str, int index);
int maxLength(char** arr, int arrSize);

// Function to calculate the maximum length of a string without repeating characters
int maxLength(char** arr, int arrSize) {
    return solve(arr, arrSize, "", 0);
}

// Function to recursively calculate the maximum length of a string without repeating
// characters
int solve(char** arr, int arrSize, char* str, int index) {
    // Create a set to store unique characters
    int charSet[26] = {0};

    // Calculate the length of the current string
    int len = strlen(str);

    // Check if the current string contains duplicate characters
    for (int i = 0; i < len; i++) {
        if (charSet[str[i] - 'a'] > 0) {
            return 0;
        }
        charSet[str[i] - 'a']++;
    }

    // Initialize answer with the length of the current string
    int ans = len;

    // Iterate over the array of strings starting from the given index
    for (int i = index; i < arrSize; i++) {
        // Concatenate the current string with the next string in the array
        char* newStr = (char*)malloc((len + strlen(arr[i]) + 1) * sizeof(char));
        strcpy(newStr, str);
        strcat(newStr, arr[i]);

        // Recursively call solve function with the updated string and index
        int newLen = solve(arr, arrSize, newStr, i + 1);

        // Update the answer with the maximum length obtained so far
        ans = (ans > newLen) ? ans : newLen;
    }

    // Free the dynamically allocated memory for newStr
```

```

        free(newStr);
    }

    // Return the maximum length of the string without repeating characters
    return ans;
}

int main() {
    // Example array of strings
    char* arr[] = {"un", "iq", "ue"};

    // Calculate the maximum length of the string without repeating characters
    printf("Maximum length of string without repeating characters: %d\n", maxLength(arr,
3));

    return 0;
}

```

Input: arr = ["un", "iq", "ue"]

Output: 4

Explanation: All the valid concatenations are:

- ""
- "un"
- "iq"
- "ue"
- "uniq" ("un" + "iq")
- "ique" ("iq" + "ue")

Maximum length is 4.

Time/Space Complexity : O(n*m*k)/O(n)

1.60 Buddy Strings

```

#include <stdbool.h>
#include <stdio.h>
#include <string.h>

// Function prototype
bool buddyStrings(char* s, char* goal);

// Function to check if two strings are buddy strings
bool buddyStrings(char* s, char* goal) {
    // Calculate the lengths of the strings
    int len_s = strlen(s);
    int len_goal = strlen(goal);

    // If lengths are not equal, strings cannot be buddy strings
    if (len_s != len_goal) {
        return false;
    }

```

```

// If strings are equal, check if there are duplicate characters
if (strcmp(s, goal) == 0) {
    // Create an array to store the frequency of characters
    int frequency[26] = {0};

    // Count the frequency of each character in the string
    for (int i = 0; i < len_s; i++) {
        frequency[s[i] - 'a']++;
        if (frequency[s[i] - 'a'] == 2) {
            return true;
        }
    }
    // If there are no duplicate characters, strings cannot be buddy strings
    return false;
}

// Initialize indices to store positions of differing characters
int firstIndex = -1;
int secondIndex = -1;

// Iterate through the strings to find differing characters
for (int i = 0; i < len_s; ++i) {
    if (s[i] != goal[i]) {
        if (firstIndex == -1) {
            firstIndex = i;
        } else if (secondIndex == -1) {
            secondIndex = i;
        } else {
            // If there are more than two differing characters, strings cannot be
            // buddy strings
            return false;
        }
    }
}

// If there is only one differing character, strings cannot be buddy strings
if (secondIndex == -1) {
    return false;
}

// Check if swapping characters at differing positions makes strings equal
return s[firstIndex] == goal[secondIndex] && s[secondIndex] == goal[firstIndex];
}

int main() {
    // Example strings
    char s[] = "ab";
    char goal[] = "ba";
}

```

```

    // Check if the strings are buddy strings
    printf("Are the strings buddy strings? %s\n", buddyStrings(s, goal) ? "Yes" : "No");

    return 0;
}

```

Input: s = "ab", goal = "ba"

Output: true

Explanation: You can swap s[0] = 'a' and s[1] = 'b' to get "ba", which is equal to goal.

Time/Space Complexity: O(n)/O(1)

1.61 Robot Room Cleaner

```

/**
 * // This is the robot's control interface.
 * // You should not implement it, or speculate about its implementation
 * interface Robot {
 *     // Returns true if the cell in front is open and robot moves into the cell.
 *     // Returns false if the cell in front is blocked and robot stays in the current
 *     // cell.
 *     public boolean move();
 *
 *     // Robot will stay in the same cell after calling turnLeft/turnRight.
 *     // Each turn will be 90 degrees.
 *     public void turnLeft();
 *     public void turnRight();
 *
 *     // Clean the current cell.
 *     public void clean();
 * }
 */

```

```

class Solution {
    private final int[][] directions = {{-1, 0}, {0, 1}, {1, 0}, {0, -1}};
    private Set<String> visited = new HashSet<>();

    public void cleanRoom(Robot robot) {
        dfs(robot, 0, 0, 0);
    }

    private void dfs(Robot robot, int x, int y, int dir) {
        visited.add(x + "-" + y);
        robot.clean();

        for (int i = 0; i < 4; i++) {
            int newDir = (dir + i) % 4;
            int newX = x + directions[newDir][0];
            int newY = y + directions[newDir][1];

```

```

        if (!visited.contains(newX + "-" + newY) && robot.move()) {
            dfs(robot, newX, newY, newDir);
            goBack(robot);
        }

        robot.turnRight();
    }
}

private void goBack(Robot robot) {
    robot.turnRight();
    robot.turnRight();
    robot.move();
    robot.turnRight();
    robot.turnRight();
}
}

```

Input: room = [[1,1,1,1,1,0,1,1],[1,1,1,1,1,0,1,1],[1,0,1,1,1,1,1,1],[0,0,0,1,0,0,0,0],[1,1,1,1,1,1,1,1]], row = 1, col = 3

Output: Robot cleaned all rooms.

Explanation: All grids in the room are marked by either 0 or 1.

0 means the cell is blocked, while 1 means the cell is accessible.

The robot initially starts at the position of row=1, col=3.

From the top left corner, its position is one row below and three columns right.

Time/Space Complexity: O(n)/O(n)

1.62 Count Unique Characters Of All Substrings Of A Given String

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <math.h>

#define ALPHABET_SIZE 26
#define MOD ((int)pow(10, 9) + 7)

int uniqueLetterString(char* s) {
    int mod = MOD;
    int index[ALPHABET_SIZE][2];
    memset(index, -1, sizeof(index));
    int ans = 0;
    int n = strlen(s);
    for (int i = 0; i < n; i++) {
        int c = s[i] - 'A';
        ans = (ans + ((long long)(i - index[c][1]) * (index[c][1] - index[c][0]) % mod)
+ mod) % mod;
        index[c][0] = index[c][1];
        index[c][1] = i;
    }
}

```

```

    }
    for (int c = 0; c < ALPHABET_SIZE; ++c)
        ans = (ans + ((long long)(n - index[c][1]) * (index[c][1] - index[c][0]) % mod)
+ mod) % mod;
    return ans;
}
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int uniqueLetterString(char* s) {
    int sum = 0, curr = 0, n = strlen(s);

    int last[26];
    int prev[26];

    memset(last, -1, sizeof(last));
    memset(prev, -1, sizeof(prev));

    for (int i = 0; i < n; i++) {
        char c = s[i];
        curr += (i - last[c - 'A'] - 1) - (last[c - 'A'] - prev[c - 'A']) + 1;
        prev[c - 'A'] = last[c - 'A'];
        last[c - 'A'] = i;
        sum += curr;
    }

    return sum;
}
int main() {
    char s[] = "ABC";
    printf("Output: %d\n", uniqueLetterString(s));
    return 0;
}

Input: s = "ABC"
Output: 10
Explanation: All possible substrings are: "A","B","C","AB","BC" and "ABC".  

Every substring is composed with only unique letters.  

Sum of lengths of all substring is  $1 + 1 + 1 + 2 + 2 + 3 = 10$ 

```

Time/Space Complexity: $O(n)/O(1)$

1.63 Minimum Fuel Cost To Report To The Capital

```

#include <stdio.h>
#include <stdlib.h>

// Structure to represent a node in the adjacency list
typedef struct Node {
    int data;

```

```

        struct Node* next;
    } Node;

    // Structure to represent the adjacency list
    typedef struct {
        Node* head;
    } List;

    // Function to create a new node
    Node* createNode(int data) {
        Node* newNode = (Node*)malloc(sizeof(Node));
        if (newNode) {
            newNode->data = data;
            newNode->next = NULL;
        }
        return newNode;
    }

    // Function to initialize the adjacency list
    List initializeList() {
        List list;
        list.head = NULL;
        return list;
    }

    // Function to add a new edge to the adjacency list
    void addEdge(List** adjList, int src, int dest) {
        Node* newNode = createNode(dest);
        newNode->next = (*adjList)[src].head;
        (*adjList)[src].head = newNode;

        newNode = createNode(src);
        newNode->next = (*adjList)[dest].head;
        (*adjList)[dest].head = newNode;
    }

    // Function to perform depth-first search (DFS)
    void dfs(List* adjList, int node, int parent, int* size) {
        size[node] = 1;
        Node* current = adjList[node].head;
        while (current) {
            if (current->data != parent) {
                dfs(adjList, current->data, node, size);
                size[node] += size[current->data];
            }
            current = current->next;
        }
    }
}

```

```

// Function to calculate the minimum fuel cost
long long minimumFuelCost(int** roads, int roadsSize, int* roadsColSize, int seats) {
    int n = roadsSize + 1;

    // Initialize size array to store subtree sizes
    int* size = (int*)calloc(n, sizeof(int));

    // Initialize adjacency list
    List* adjList = (List*)malloc(n * sizeof(List));
    for (int i = 0; i < n; i++) {
        adjList[i] = initializeList();
    }

    // Construct the adjacency list from the input roads
    for (int i = 0; i < roadsSize; i++) {
        int a = roads[i][0];
        int b = roads[i][1];
        addEdge(&adjList, a, b);
    }

    // Perform depth-first search (DFS) to calculate subtree sizes
    dfs(adjList, 0, -1, size);

    // Calculate the minimum fuel cost
    long long ans = 0;
    for (int i = 1; i < n; ++i) {
        int cnt = size[i];
        ans += 1LL * ((cnt + seats - 1) / seats);
    }

    // Free dynamically allocated memory
    for (int i = 0; i < n; i++) {
        Node* current = adjList[i].head;
        while (current) {
            Node* temp = current;
            current = current->next;
            free(temp);
        }
    }
    free(adjList);
    free(size);

    return ans;
}

int main() {
    int roadsSize = 6;
    int roadsColSize[] = {2, 2, 2, 2, 2, 2};
    int** roads = (int**)malloc(roadsSize * sizeof(int*));

```

```

for (int i = 0; i < roadsSize; i++) {
    roads[i] = (int*)malloc(2 * sizeof(int));
}
roads[0][0] = 3; roads[0][1] = 1;
roads[1][0] = 3; roads[1][1] = 2;
roads[2][0] = 1; roads[2][1] = 0;
roads[3][0] = 0; roads[3][1] = 4;
roads[4][0] = 0; roads[4][1] = 5;
roads[5][0] = 4; roads[5][1] = 6;

int seats = 2;

long long result = minimumFuelCost(roads, roadsSize, roadsColSize, seats);
printf("Minimum fuel cost: %lld\n", result);

// Free dynamically allocated memory for roads
for (int i = 0; i < roadsSize; i++) {
    free(roads[i]);
}
free(roads);

return 0;
}

```

Input: roads = [[3,1],[3,2],[1,0],[0,4],[0,5],[4,6]], seats = 2

Output: 7

Explanation:

- Representative₂ goes directly to city 3 with 1 liter of fuel.
- Representative₂ and representative₃ go together to city 1 with 1 liter of fuel.
- Representative₂ and representative₃ go together to the capital with 1 liter of fuel.
- Representative₄ goes directly to the capital with 1 liter of fuel.
- Representative₅ goes directly to the capital with 1 liter of fuel.
- Representative₆ goes directly to city 4 with 1 liter of fuel.
- Representative₂ and representative₆ go together to the capital with 1 liter of fuel.

It costs 7 liters of fuel at minimum.

It can be proven that 7 is the minimum number of liters of fuel needed.

Time/Space Complexity:O(V+E)/O(V+E)

1.64 Remove Duplicate Letters(lexicographical small)

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* removeDuplicateLetters(char* s) {
    int n = strlen(s);

    // Array to store the last occurrence index of each character

```

```

int lastIndex[26] = {0};
for (int i = 0; i < n; i++) {
    lastIndex[s[i] - 'a'] = i;
}

// Array to keep track of seen characters
int seen[26] = {0};

// Stack to maintain selected characters
int stack[26];
int top = -1;

// Iterate through the string
for (int i = 0; i < n; i++) {
    int curr = s[i] - 'a';

    // If the character is already seen, continue to the next iteration
    if (seen[curr]) {
        continue;
    }

    // Pop characters from the stack if the current character is smaller,
    // there are remaining occurrences of the characters in the stack,
    // and the character at the top of the stack is greater than the current
    character
    while (top >= 0 && curr < stack[top] && i < lastIndex[stack[top]]) {
        seen[stack[top--]] = 0; // Pop out and mark unseen
    }

    // Push the current character onto the stack and mark it as seen
    stack[++top] = curr;
    seen[curr] = 1; // Mark seen
}

// Build the result string from the characters in the stack
char* result = (char*)malloc((top + 2) * sizeof(char));
for (int i = 0; i <= top; i++) {
    result[i] = stack[i] + 'a';
}
result[top + 1] = '\0';

return result;
}

// Main function for testing the removeDuplicateLetters function
int main() {
    char s[] = "bcabc";

    char* result = removeDuplicateLetters(s);
}

```

```

printf("Original string: %s\n", s);
printf("String after removing duplicate letters: %s\n", result);

free(result);

return 0;
}
Output:abc
Time/Space complexity:O(n)/O(1)

```

1.65 Score of Parentheses

```

#include <stdio.h>

int scoreOfParentheses(char* S) {
    int ans = 0, bal = 0;
    for (int i = 0; S[i] != '\0'; ++i) {
        if (S[i] == '(') {
            bal++;
        } else {
            bal--;
            if (S[i - 1] == '(') {
                ans += 1 << bal;
            }
        }
    }

    return ans;
}

int main() {
    // Test cases
    char* test1 = "((())";
    char* test2 = "(((()))";
    char* test3 = "(()())";
    char* test4 = "())";

    printf("Score of %s: %d\n", test1, scoreOfParentheses(test1));
    printf("Score of %s: %d\n", test2, scoreOfParentheses(test2));
    printf("Score of %s: %d\n", test3, scoreOfParentheses(test3));
    printf("Score of %s: %d\n", test4, scoreOfParentheses(test4));

    return 0;
}

```

Input: s = "()"

Output: 1

Input: s = "(())"

Output: 2

Time/Space Complexity:O(n)/O(1)

1.66 Maximum Number Of Balloons

```
#include <stdio.h>
#include <string.h>

#define min(a,b) ((a) < (b) ? (a) : (b))

int maxNumberOfBalloons(char* text) {
    int bCount = 0, aCount = 0, lCount = 0, oCount = 0, nCount = 0;

    // Count the frequency of all the five characters
    for (int i = 0; i < strlen(text); i++) {
        if (text[i] == 'b') {
            bCount++;
        } else if (text[i] == 'a') {
            aCount++;
        } else if (text[i] == 'l') {
            lCount++;
        } else if (text[i] == 'o') {
            oCount++;
        } else if (text[i] == 'n') {
            nCount++;
        }
    }

    // Find the potential of each character.
    // Except for 'l' and 'o', the potential is equal to the frequency.
    lCount = lCount / 2;
    oCount = oCount / 2;

    // Find the bottleneck.
    int ret = min(oCount, nCount);
    ret = min(ret, lCount);
    ret = min(ret, aCount);
    ret = min(ret, bCount);
    return ret;
}

int main() {
    // Test cases
    char* test1 = "nlaebolko";
    char* test2 = "loonbalxballpoon";
    char* test3 = "nlaablonn";

    printf("Maximum number of balloons in \"%s\": %d\n", test1,
maxNumberOfBalloons(test1));
    printf("Maximum number of balloons in \"%s\": %d\n", test2,
maxNumberOfBalloons(test2));
```

```
    printf("Maximum number of balloons in \"%s\": %d\n", test3,
maxNumberOfBalloons(test3));
```

```
    return 0;
}
```

Output: 1/ 2

Time/Space Complexity:O(n)/O(1)

1.67 Buy Two Chocolates

```
#include <stdio.h>

int buyChoco(int* prices, int pricesSize, int money) {
    // Assume minimum and second minimum
    int minimum = prices[0] < prices[1] ? prices[0] : prices[1];
    int secondMinimum = prices[0] > prices[1] ? prices[0] : prices[1];

    // Iterate over the remaining elements
    for (int i = 2; i < pricesSize; i++) {
        if (prices[i] < minimum) {
            secondMinimum = minimum;
            minimum = prices[i];
        } else if (prices[i] < secondMinimum) {
            secondMinimum = prices[i];
        }
    }

    // Minimum Cost
    int minCost = minimum + secondMinimum;

    // We can buy chocolates only if we have enough money
    if (minCost <= money) {
        // Return the Amount of Money Left
        return money - minCost;
    }

    // We cannot buy chocolates. Return the initial amount of money
    return money;
}

int main() {
    // Test cases
    int prices1[] = {1,2,2};
    int money1 = 3;

    int prices2[] = {3,2,3};
    int money2 = 3;
```

```

        printf("Money left after buying chocolates: %d\n", buyChoco(prices1, sizeof(prices1)
/ sizeof(prices1[0]), money1));
        printf("Money left after buying chocolates: %d\n", buyChoco(prices2, sizeof(prices2)
/ sizeof(prices2[0]), money2));

    return 0;
}
Output:0/3
Time/Space Complexity: O(n)/O(1)

```

1.68 Permutations

```

#include <stdio.h>
#include <stdlib.h>

void swap(int* a, int* b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

void permute(int* nums, int start, int end) {
    if (start == end) {
        // Print the current permutation
        for (int i = 0; i <= end; i++) {
            printf("%d ", nums[i]);
        }
        printf("\n");
        return;
    }

    for (int i = start; i <= end; i++) {
        // Swap elements to create different permutations
        swap(&nums[start], &nums[i]);

        // Recursively generate permutations for the remaining elements
        permute(nums, start + 1, end);

        // Backtrack (undo the swap) to explore other possibilities
        swap(&nums[start], &nums[i]);
    }
}

int main() {
    int n;
    printf("Enter the number of elements: ");
    scanf("%d", &n);

    int* nums = (int*)malloc(n * sizeof(int));

```

```

printf("Enter the elements: ");
for (int i = 0; i < n; i++) {
    scanf("%d", &nums[i]);
}

printf("Permutations:\n");
permute(nums, 0, n - 1);

free(nums);

return 0;
}

```

```

Enter the number of elements: 4
Enter the elements: 1
2
3
4
Permutations:
1 2 3 4
1 2 4 3
1 3 2 4
1 3 4 2
1 4 3 2
1 4 2 3
2 1 3 4
2 1 4 3
2 3 1 4
2 3 4 1
2 4 3 1
2 4 1 3
3 2 1 4
3 2 4 1
3 1 2 4
3 1 4 2
3 4 1 2
3 4 2 1
4 2 3 1
4 2 1 3
4 3 2 1
4 3 1 2
4 1 3 2
4 1 2 3

```

1.69 Combinations

```

#include <stdio.h>
#include <stdlib.h>

void combine(int* nums, int n, int k, int start, int* current, int currentSize) {

```

```

if (currentSize == k) {
    // Print the current combination
    for (int i = 0; i < k; i++) {
        printf("%d ", current[i]);
    }
    printf("\n");
    return;
}

for (int i = start; i < n; i++) {
    current[currentSize] = nums[i];

    // Recursively generate combinations for the remaining elements
    combine(nums, n, k, i + 1, current, currentSize + 1);
}
}

int main() {
    int n, k;
    printf("Enter the number of elements: ");
    scanf("%d", &n);

    int* nums = (int*)malloc(n * sizeof(int));

    printf("Enter the elements: ");
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    printf("Enter the size of combinations (k): ");
    scanf("%d", &k);

    if (k > n) {
        printf("Invalid input! Size of combinations (k) cannot be greater than the
number of elements.\n");
        free(nums);
        return 1;
    }

    int* current = (int*)malloc(k * sizeof(int));

    printf("Combinations:\n");
    combine(nums, n, k, 0, current, 0);

    free(nums);
    free(current);

    return 0;
}

```

```

Enter the number of elements: 3
Enter the elements: 1
2
3
Enter the size of combinations (k): 2
Combinations:
1 2
1 3
2 3
/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
calls free().
 */
void backtrack(int n, int k, int start, int* current, int** result, int* returnSize,
int** returnColumnSizes, int currentSize) {
    if (currentSize == k) {
        // Add the current combination to the result
        result[*returnSize] = (int*)malloc(k * sizeof(int));
        for (int i = 0; i < k; i++) {
            result[*returnSize][i] = current[i];
        }
        (*returnColumnSizes)[*returnSize] = k;
        (*returnSize)++;
        return;
    }

    for (int i = start; i <= n; i++) {
        current[currentSize] = i;
        // Recursively generate combinations
        backtrack(n, k, i + 1, current, result, returnSize, returnColumnSizes,
        currentSize + 1);
    }
}

int** combine(int n, int k, int* returnSize, int** returnColumnSizes) {
    *returnSize = 0;

    // Allocate memory for the result
    int** result = (int**)malloc(10000 * sizeof(int*)); // Assuming a maximum limit for
the returnSize
    *returnColumnSizes = (int*)malloc(10000 * sizeof(int));

    int* current = (int*)malloc(k * sizeof(int));

    // Start backtracking from the first element
    backtrack(n, k, 1, current, result, returnSize, returnColumnSizes, 0);
}

```

```

    free(current);

    return result;
}

```

1.70 Remove K Digits (return smallest possible integer)

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* removeKdigits(char* num, int k) {
    int n = strlen(num);

    // Check if k is equal to the length of the number
    if (k == n) {
        char* result = (char*)malloc(2 * sizeof(char));
        result[0] = '0';
        result[1] = '\0';
        return result;
    }

    // Initialize a stack to keep track of the digits
    char* stack = (char*)malloc((n + 1) * sizeof(char));
    int top = -1;

    // Iterate through the digits of the number
    for (int i = 0; i < n; i++) {
        // Pop elements from the stack if the current digit is smaller than the top of
        // the stack
        while (k > 0 && top >= 0 && num[i] < stack[top]) {
            top--;
            k--;
        }

        // Push the current digit onto the stack
        stack[++top] = num[i];
    }

    // Pop remaining elements from the stack to remove excess digits
    while (k > 0 && top >= 0) {
        top--;
        k--;
    }

    // Find the first non-zero digit in the stack
    int nonZeroIndex = 0;
    while (nonZeroIndex <= top && stack[nonZeroIndex] == '0') {
        nonZeroIndex++;
    }
}

```

```

// If the resulting number is empty, return "0"
if (nonZeroIndex > top) {
    char* result = (char*)malloc(2 * sizeof(char));
    result[0] = '0';
    result[1] = '\0';
    free(stack);
    return result;
}

// Construct the resulting number
char* result = (char*)malloc((top - nonZeroIndex + 2) * sizeof(char));
int resultIndex = 0;
for (int i = nonZeroIndex; i <= top; i++) {
    result[resultIndex++] = stack[i];
}
result[resultIndex] = '\0';

free(stack);
return result;
}

int main() {
    char num[] = "1432219";
    int k = 3;

    char* result = removeKdigits(num, k);
    printf("Resulting number after removing %d digits: %s\n", k, result);
    free(result);

    return 0;
}
Output:1219

```

1.71 Car Fleet (arrive at destination)

```

#include <stdio.h>
#include <stdlib.h>

int carFleet(int target, int* position, int positionSize, int* speed, int speedSize) {
    int res = 0;
    double* timeArr = (double*)malloc(target * sizeof(double));

    // Calculate time to destination for each car
    for (int i = 0; i < positionSize; i++) {
        timeArr[position[i]] = (double)(target - position[i]) / speed[i];
    }

    double prev = 0.0;
    for (int i = target - 1; i >= 0; i--) {

```

```

        double cur = timeArr[i];
        if (cur > prev) {
            prev = cur;
            res++;
        }
    }

    free(timeArr);
    return res;
}

int main() {
    int target = 12;
    int position[] = {10, 8, 0, 5, 3};
    int positionSize = sizeof(position) / sizeof(position[0]);
    int speed[] = {2, 4, 1, 1, 3};
    int speedSize = sizeof(speed) / sizeof(speed[0]));

    int fleet = carFleet(target, position, positionSize, speed, speedSize);
    printf("Number of car fleets: %d\n", fleet);

    return 0;
}

```

Output:3

Input: target = 12, position = [10,8,0,5,3], speed = [2,4,1,1,3]

Output: 3

Explanation:

The cars starting at 10 (speed 2) and 8 (speed 4) become a fleet, meeting each other at 12.

The car starting at 0 does not catch up to any other car, so it is a fleet by itself.

The cars starting at 5 (speed 1) and 3 (speed 3) become a fleet, meeting each other at 6. The fleet moves at speed 1 until it reaches target.

Note that no other cars meet these fleets before the destination, so the answer is 3.

1.72 Match Sticks To Square

```

#include <stdio.h>
#include <stdbool.h>

bool canMake(int index, int bucketsize, int* matchsticks, int* bucket, int
matchstickSize) {
    if (index == matchstickSize)
        return bucket[0] == bucket[1] && bucket[1] == bucket[2] && bucket[2] ==
bucket[3];

    for (int i = 0; i < 4; i++) {
        if (bucket[i] + matchsticks[index] > bucketsize)
            continue;

```

```

        int j = i;
        while (--j >= 0)
            if (bucket[i] == bucket[j])
                break;

        if (j != -1)
            continue;

        bucket[i] += matchsticks[index];
        if (canMake(index + 1, bucketsize, matchsticks, bucket, matchstickSize))
            return true;

        bucket[i] -= matchsticks[index];
    }

    return false;
}

bool makesquare(int* matchsticks, int matchstickSize) {
    int sum = 0;

    for (int i = 0; i < matchstickSize; i++)
        sum += matchsticks[i];

    if (sum == 0 || sum % 4)
        return false;

    for (int i = 0; i < matchstickSize - 1; i++) {
        for (int j = 0; j < matchstickSize - i - 1; j++) {
            if (matchsticks[j] < matchsticks[j + 1]) {
                // swap
                int temp = matchsticks[j];
                matchsticks[j] = matchsticks[j + 1];
                matchsticks[j + 1] = temp;
            }
        }
    }

    int bucket[4] = {0};
    return canMake(0, sum / 4, matchsticks, bucket, matchstickSize);
}

int main() {
    int matchsticks[] = {1, 1, 2, 2, 2};
    int matchstickSize = sizeof(matchsticks) / sizeof(matchsticks[0]);

    if (makesquare(matchsticks, matchstickSize)) {
        printf("It is possible to form a square with the given matchsticks.\n");
    }
}


```

```

    } else {
        printf("It is not possible to form a square with the given matchsticks.\n");
    }

    return 0;
}

```



Input: matchsticks = [1,1,2,2,2]

Output: true

Explanation: You can form a square with length 2, one side of the square came two sticks with length 1.

1.73 132 Pattern

```

#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <math.h>

bool find132pattern(int* nums, int numsSize) {
    if (numsSize < 3) {
        return false;
    }

    int* min = malloc(numsSize * sizeof(int));
    min[0] = nums[0];

    for (int i = 1; i < numsSize; i++) {
        min[i] = fmin(min[i - 1], nums[i]);
    }

    int* stack = malloc(numsSize * sizeof(int));
    int top = -1;

    for (int j = numsSize - 1; j >= 0; j--) {
        if (nums[j] > min[j]) {

```

```

        while (top != -1 && stack[top] <= min[j]) {
            stack[top--];
        }

        if (top != -1 && stack[top] < nums[j]) {
            free(min);
            free(stack);
            return true;
        }

        stack[++top] = nums[j];
    }
}

free(min);
free(stack);
return false;
}

int main() {
    int nums[] = {3, 1, 4, 2};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    if (find132pattern(nums, numsSize)) {
        printf("The pattern 132 exists in the array.\n");
    } else {
        printf("The pattern 132 does not exist in the array.\n");
    }

    return 0;
}

```

Output: [1, 4, 2].

```

#include <limits.h>
#include <stdbool.h>
#include <stdlib.h>
#include <stdio.h>

typedef struct {
    int *data;
    int top;
    int capacity;
} Stack;

// Function to initialize the stack
Stack *createStack(int capacity) {
    Stack *stack = (Stack *)malloc(sizeof(Stack));
    stack->data = (int *)malloc(capacity * sizeof(int));

```

```

    stack->top = -1;
    stack->capacity = capacity;
    return stack;
}

// Function to check if the stack is empty
bool isEmpty(Stack *stack) {
    return stack->top == -1;
}

// Function to check if the stack is full
bool isFull(Stack *stack) {
    return stack->top == stack->capacity - 1;
}

// Function to push an element onto the stack
void push(Stack *stack, int value) {
    if (isFull(stack)) {
        printf("Stack overflow\n");
        return;
    }
    stack->data[++stack->top] = value;
}

// Function to pop an element from the stack
int pop(Stack *stack) {
    if (isEmpty(stack)) {
        printf("Stack underflow\n");
        return INT_MIN;
    }
    return stack->data[stack->top--];
}

// Function to get the top element of the stack without popping
int peek(Stack *stack) {
    if (isEmpty(stack)) {
        return INT_MIN;
    }
    return stack->data[stack->top];
}

// Function to free the memory occupied by the stack
void freeStack(Stack *stack) {
    free(stack->data);
    free(stack);
}

// Function to find the 132 pattern
bool find132pattern(int *nums, int numsSize) {

```

```

int thirdValue = INT_MIN;
Stack *candidates = createStack(numsSize);

for (int i = numsSize - 1; i >= 0; --i) {
    if (nums[i] < thirdValue) {
        // Found a valid 132 pattern
        freeStack(candidates);
        return true;
    }

    while (!isEmpty(candidates) && peek(candidates) < nums[i]) {
        thirdValue = pop(candidates);
    }

    push(candidates, nums[i]);
}

// No 132 pattern found
freeStack(candidates);
return false;
}

int main() {
    // Example usage
    int nums[] = {3, 1, 4, 2};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    bool result = find132pattern(nums, numsSize);

    if (result) {
        printf("Found 132 pattern\n");
    } else {
        printf("No 132 pattern found\n");
    }

    return 0;
}

```

1.74 Word Search II

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

typedef struct TrieNode {
    struct TrieNode* children[26];
    char* word;
} TrieNode;

// Trie Initialization

```

```

TrieNode* createTrieNode() {
    TrieNode* node = (TrieNode*)malloc(sizeof(TrieNode));
    memset(node->children, 0, sizeof(node->children));
    node->word = NULL;
    return node;
}

// Trie Insertion
void insertWord(TrieNode* root, char* word) {
    TrieNode* node = root;
    for (int i = 0; i < strlen(word); i++) {
        int index = word[i] - 'a';
        if (!node->children[index]) {
            node->children[index] = createTrieNode();
        }
        node = node->children[index];
    }
    node->word = word;
}

// DFS to find words on the board
void findWordsDFS(char** board, int boardSize, int* boardColSize, int row, int col,
TrieNode* node, char*** result, int* returnSize) {
    char c = board[row][col];
    TrieNode* child = node->children[c - 'a'];

    if (child == NULL) {
        return;
    }

    if (child->word != NULL) {
        (*returnSize)++;
        *result = (char**)realloc(*result, (*returnSize) * sizeof(char*));
        (*result)[(*returnSize) - 1] = child->word;
        child->word = NULL; // Avoid duplicates
    }

    board[row][col] = '#'; // Mark visited

    int directions[][][2] = {{-1, 0}, {1, 0}, {0, -1}, {0, 1}};

    for (int i = 0; i < 4; i++) {
        int newRow = row + directions[i][0];
        int newCol = col + directions[i][1];

        if (newRow >= 0 && newRow < boardSize && newCol >= 0 && newCol < boardColSize[0]
&& board[newRow][newCol] != '#') {
            findWordsDFS(board, boardSize, boardColSize, newRow, newCol, child, result,
returnSize);
        }
    }
}

```

```

        }
    }

    board[row][col] = c; // Restore the original character
}

// Find Words on the Board
char** findWords(char** board, int boardSize, int* boardColSize, char** words, int
wordsSize, int* returnSize) {
    *returnSize = 0;
    char** result = NULL;

    TrieNode* root = createTrieNode();

    // Insert words into the Trie
    for (int i = 0; i < wordsSize; i++) {
        insertWord(root, words[i]);
    }

    // Traverse the board and search for words
    for (int i = 0; i < boardSize; i++) {
        for (int j = 0; j < boardColSize[i]; j++) {
            findWordsDFS(board, boardSize, boardColSize, i, j, root, &result,
returnSize);
        }
    }

    // Free Trie and return result
    free(root);

    return result;
}

int main() {
    char* board[] = {"oaan", "etae", "ihkr", "iflv"};
    int boardSize = sizeof(board) / sizeof(board[0]);
    int boardColSize[] = {4, 4, 4, 4};

    char* words[] = {"oath", "pea", "eat", "rain"};
    int wordsSize = sizeof(words) / sizeof(words[0]);

    int returnSize = 0;
    char** result = findWords(board, boardSize, boardColSize, words, wordsSize,
&returnSize);

    printf("Found words:\n");
    for (int i = 0; i < returnSize; i++) {
        printf("%s\n", result[i]);
    }
}

```

```

// Free allocated memory
for (int i = 0; i < returnSize; i++) {
    free(result[i]);
}
free(result);

return 0;
}

```

Example 1:

o	a	a	n
e	t	a	e
i	h	k	r
i	f	l	v

Input: board = [["o","a","a","n"],["e","t","a","e"],["i","h","k","r"],["i","f","l","v"]], words = ["oath","pea","eat","rain"]

Output: ["eat","oath"]

1.75 Merge Intervals

Given an array of intervals where intervals[i] = [start_i, end_i], merge all overlapping intervals, and return *an array of the non-overlapping intervals that cover all the intervals in the input.*

Example 1:

Input: intervals = [[1,3],[2,6],[8,10],[15,18]]

Output: [[1,6],[8,10],[15,18]]

Explanation: Since intervals [1,3] and [2,6] overlap, merge them into [1,6].

Example 2:**Input:** intervals = [[1,4],[4,5]]**Output:** [[1,5]]**Explanation:** Intervals [1,4] and [4,5] are considered overlapping.**C:**

```
/*
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 * calls free().
 */
// Definition for an interval.
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int start;
    int end;
} Interval;

int compareIntervals(const void* a, const void* b) {
    return ((Interval*)a)->start - ((Interval*)b)->start;
}

int** merge(int** intervals, int intervalsSize, int* intervalsColSize, int* returnSize,
int** returnColumnSizes) {
    if (intervalsSize <= 0) {
        *returnSize = 0;
        *returnColumnSizes = NULL;
        return NULL;
    }

    // Convert the input to Interval structures
    Interval* intervalsStruct = (Interval*)malloc(intervalsSize * sizeof(Interval));
    for (int i = 0; i < intervalsSize; i++) {
        intervalsStruct[i].start = intervals[i][0];
        intervalsStruct[i].end = intervals[i][1];
    }

    // Sort intervals based on the start time
    qsort(intervalsStruct, intervalsSize, sizeof(Interval), compareIntervals);

    // Initialize result array
    int** result = (int**)malloc(intervalsSize * sizeof(int*));
    *returnSize = 0;
    *returnColumnSizes = (int*)malloc(intervalsSize * sizeof(int));

    // Merge overlapping intervals
```

```

result[*returnSize] = (int*)malloc(2 * sizeof(int));
result[*returnSize][0] = intervalsStruct[0].start;
result[*returnSize][1] = intervalsStruct[0].end;

for (int i = 1; i < intervalsSize; i++) {
    if (result[*returnSize][1] >= intervalsStruct[i].start) {
        // Merge overlapping intervals
        result[*returnSize][1] = (result[*returnSize][1] > intervalsStruct[i].end) ?
result[*returnSize][1] : intervalsStruct[i].end;
    } else {
        // Move to the next non-overlapping interval
        (*returnSize)++;
        result[*returnSize] = (int*)malloc(2 * sizeof(int));
        result[*returnSize][0] = intervalsStruct[i].start;
        result[*returnSize][1] = intervalsStruct[i].end;
    }
}

(*returnSize)++;
*returnColumnSizes = (int*)realloc(*returnColumnSizes, *returnSize * sizeof(int));
for (int i = 0; i < *returnSize; i++) {
    (*returnColumnSizes)[i] = 2;
}

// Clean up
free(intervalsStruct);

return result;
}

int main() {
    int intervalsSize = 4;
    int intervalsColSize[] = {2, 2, 2, 2};
    int** intervals = (int**)malloc(intervalsSize * sizeof(int*));
    intervals[0] = (int*)malloc(2 * sizeof(int));
    intervals[0][0] = 1;
    intervals[0][1] = 3;
    intervals[1] = (int*)malloc(2 * sizeof(int));
    intervals[1][0] = 2;
    intervals[1][1] = 6;
    intervals[2] = (int*)malloc(2 * sizeof(int));
    intervals[2][0] = 8;
    intervals[2][1] = 10;
    intervals[3] = (int*)malloc(2 * sizeof(int));
    intervals[3][0] = 15;
    intervals[3][1] = 18;

    int returnSize;
    int* returnColumnSizes;
}

```

```

int** mergedIntervals = merge(intervals, intervalsSize, intervalsColSize,
&returnSize, &returnColumnSizes);

printf("Merged Intervals:\n");
for (int i = 0; i < returnSize; i++) {
    printf("[%d, %d]\n", mergedIntervals[i][0], mergedIntervals[i][1]);
}

// Free allocated memory
for (int i = 0; i < intervalsSize; i++) {
    free(intervals[i]);
}
free(intervals);
for (int i = 0; i < returnSize; i++) {
    free(mergedIntervals[i]);
}
free(mergedIntervals);
free(returnColumnSizes);

return 0;
}

```

Input: intervals = [[1,3],[2,6],[8,10],[15,18]]

Output: [[1,6],[8,10],[15,18]]

Explanation: Since intervals [1,3] and [2,6] overlap, merge them into [1,6].

1.76 Merge Sorted Array

You are given two integer arrays nums1 and nums2, sorted in **non-decreasing order**, and two integers m and n, representing the number of elements in nums1 and nums2 respectively.

Merge nums1 and nums2 into a single array sorted in **non-decreasing order**.

The final sorted array should not be returned by the function, but instead be *stored inside the array* nums1. To accommodate this, nums1 has a length of m + n, where the first m elements denote the elements that should be merged, and the last n elements are set to 0 and should be ignored. nums2 has a length of n.

Example 1:

Input: nums1 = [1,2,3,0,0,0], m = 3, nums2 = [2,5,6], n = 3

Output: [1,2,2,3,5,6]

Explanation: The arrays we are merging are [1,2,3] and [2,5,6].

The result of the merge is [1,2,2,3,5,6] with the underlined elements coming from nums1.

Example 2:

Input: nums1 = [1], m = 1, nums2 = [], n = 0

Output: [1]

Explanation: The arrays we are merging are [1] and [].

The result of the merge is [1].

Example 3:

Input: nums1 = [0], m = 0, nums2 = [1], n = 1

Output: [1]

Explanation: The arrays we are merging are [] and [1].

The result of the merge is [1].

Note that because m = 0, there are no elements in nums1. The 0 is only there to ensure the merge result can fit in nums1.

C:

```
#include <stdio.h>

void merge(int* nums1, int nums1Size, int m, int* nums2, int nums2Size, int n){
    int i = m - 1;
    int j = n - 1;
    int k = m + n - 1;

    while (i >= 0 && j >= 0) {
        if (nums1[i] < nums2[j]) {
            nums1[k--] = nums2[j--];
        } else {
            nums1[k--] = nums1[i--];
        }
    }

    // If there are remaining elements in nums2, copy them to nums1
    while (i >= 0) {
        nums1[k--] = nums1[i--];
    }
    while (j >= 0) {
        nums1[k--] = nums2[j--];
    }
}

int main() {
    int nums1[] = {1, 2, 3, 0, 0, 0};
    int m = 3;
    int nums2[] = {2, 5, 6};
    int n = 3;
    int nums1Size = m + n;

    merge(nums1, nums1Size, m, nums2, n, n);

    printf("Merged Array: ");
    for (int i = 0; i < nums1Size; i++) {
        printf("%d ", nums1[i]);
    }
}
```

```

    }
    printf("\n");

    return 0;
}

```


1.77 Serialize and Deserialize Binary Tree

Serialization is the process of converting a data structure or object into a sequence of bits so that it can be stored in a file or memory buffer, or transmitted across a network connection link to be reconstructed later in the same or another computer environment.

Design an algorithm to serialize and deserialize a binary tree. There is no restriction on how your serialization/deserialization algorithm should work. You just need to ensure that a binary tree can be serialized to a string and this string can be deserialized to the original tree structure.

Clarification: The input/output format is the same as [how LeetCode serializes a binary tree](#). You do not necessarily need to follow this format, so please be creative and come up with different approaches yourself.

Example 1:



Input: root = [1,2,3,null,null,4,5]
Output: [1,2,3,null,null,4,5]

Example 2:

Input: root = []

Output: []

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Definition for a binary tree node
struct TreeNode {
    int val;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Serialize helper function
void serializeHelper(struct TreeNode* root, char* result, int* index) {
    if (root == NULL) {
        // Append "null," to the result string
        sprintf(result + *index, "null,");
        (*index) += strlen("null,");
    } else {
        // Convert the node value to a string and append it to the result
        sprintf(result + *index, "%d,", root->val);
        (*index) += strlen(result + *index);

        // Recursively serialize the left and right subtrees
        serializeHelper(root->left, result, index);
        serializeHelper(root->right, result, index);
    }
}

// Deserialize helper function
struct TreeNode* deserializeHelper(char* data, int* index) {
    if (data[*index] == '\0' || strncmp(data + *index, "null", 4) == 0) {
        // End of string or "null" node
        *index += 5; // Move index to the next position after "null,"
        return NULL;
    }

    // Extract the node value from the data string
    int val;
    sscanf(data + *index, "%d,", &val);
    (*index) += numDigits(val) + 1; // Move index to the next position after the comma

    // Create a new tree node with the extracted value
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->val = val;
```

```

// Recursively deserialize the left and right subtrees
newNode->left = deserializeHelper(data, index);
newNode->right = deserializeHelper(data, index);

return newNode;
}

// Serialize function
char* serialize(struct TreeNode* root) {
    // Allocate memory for the result string
    char* result = (char*)malloc(1024 * sizeof(char));
    int index = 0;

    // Call the serializeHelper to populate the result string
    serializeHelper(root, result, &index);

    // Null-terminate the result string
    result[index] = '\0';

    // Resize the result buffer to the actual size needed
    result = (char*)realloc(result, (index + 1) * sizeof(char));

    return result;
}

// Deserialize function
struct TreeNode* deserialize(char* data) {
    int index = 0;
    return deserializeHelper(data, &index);
}

// Utility function to calculate the number of digits in an integer
int numDigits(int num) {
    int count = 0;
    while (num != 0) {
        num /= 10;
        count++;
    }
    return count;
}

// Function to print the inorder traversal of a binary tree (for verification)
void inorderTraversal(struct TreeNode* root) {
    if (root != NULL) {
        inorderTraversal(root->left);
        printf("%d ", root->val);
        inorderTraversal(root->right);
    }
}

```

```
}

int main() {
    // Construct a binary tree for testing
    struct TreeNode* root = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->val = 1;
    root->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->left->val = 2;
    root->left->left = NULL;
    root->left->right = NULL;
    root->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->right->val = 3;
    root->right->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->right->left->val = 4;
    root->right->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->right->right->val = 5;


    // Serialize the binary tree
    char* serializedTree = serialize(root);
    printf("Serialized tree: %s\n", serializedTree);

    // Deserialize the serialized string
    struct TreeNode* deserializedRoot = deserialize(serializedTree);

    // Print the inorder traversal of the deserialized tree for verification
    printf("Inorder traversal of deserialized tree: ");
    inorderTraversal(deserializedRoot);
    printf("\n");

    // Clean up memory
    free(root->left);
    free(root->right);
    free(root);
    free(serializedTree);
    free(deserializedRoot);

    return 0;
}
```



Input: root = [1,2,3,null,null,4,5]

Output: [1,2,3,null,null,4,5]

Time/Space Complexity: O(n)/O(n)

1.78 Bulb Switcher

```

#include <stdio.h>
#include <math.h>

int bulbSwitch(int n) {
    return sqrt(n);
}

int main() {
    int n;
    printf("Enter the number of bulbs: ");
    scanf("%d", &n);

    int result = bulbSwitch(n);
    printf("Number of bulbs on after n rounds: %d\n", result);

    return 0;
}
  
```

Initially all bulbs are off

We toggle all bulbs which have factor 1.
We turn on all the bulbs.

We toggle all bulbs which have factor 2.
We turn off 2nd, 4th, 6th, 8th, 10th bulbs.

We toggle all bulbs which have factor 3.
We turn off 3rd, 9th bulbs, and on 6th bulb.

We toggle all bulbs which have factor 4.
We turn on 4th, 8th bulb.

.

.

.


.

.

.

.

We toggle all bulbs which have factor 10.
We turn off 10th bulb.



1.79 Sign Of The Product Of An Array

```
#include <stdio.h>

int arraySign(int* nums, int numsSize) {
    int countNegatives = 0;
    int hasZero = 0;

    for (int i = 0; i < numsSize; i++) {
        if (nums[i] == 0) {
            hasZero = 1;
            break;
        } else if (nums[i] < 0) {
            countNegatives++;
        }
    }

    if (hasZero) {
        return 0;
    }

    return countNegatives % 2 == 0 ? 1 : -1;
}
```

```

int main() {
    int nums[] = { -1, 2, -3, 4, 0 };
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int result = arraySign(nums, numsSize);
    printf("Sign of the product of all elements: %d\n", result);

    return 0;
}

```

1.80 Excel Sheet Column Title

```

#include <stdio.h>
#include <stdlib.h>

char* convertToTitle(int columnNumber) {
    // Calculate the length of the result string
    int len = 0;
    int temp = columnNumber;
    while (temp > 0) {
        len++;
        temp = (temp - 1) / 26;
    }

    // Allocate memory for the result string
    char* result = (char*)malloc((len + 1) * sizeof(char));
    result[len] = '\0';

    // Fill in the result string from right to left
    for (int i = len - 1; i >= 0; i--) {
        result[i] = (columnNumber - 1) % 26 + 'A';
        columnNumber = (columnNumber - 1) / 26;
    }

    return result;
}

int main() {
    int columnNumber = 701; // Example input

    char* title = convertToTitle(columnNumber);
    printf("Column title for column number %d: %s\n", columnNumber, title);
    free(title); // Free allocated memory

    return 0;
}

```

For example:

```
A -> 1  
B -> 2  
C -> 3  
...  
Z -> 26  
AA -> 27  
AB -> 28  
...
```

1.81 Remove All Adjacent Duplicates In String (K duplicate removal)

You are given a string s and an integer k, a k **duplicate removal** consists of choosing k adjacent and equal letters from s and removing them, causing the left and the right side of the deleted substring to concatenate together.

We repeatedly make k **duplicate removals** on s until we no longer can.

Return *the final string after all such duplicate removals have been made*. It is guaranteed that the answer is **unique**.

Example 1:

Input: s = "abcd", k = 2

Output: "abcd"

Explanation: There's nothing to delete.

Example 2:

Input: s = "deeedbbcccbdaa", k = 3

Output: "aa"

Explanation:

First delete "eee" and "ccc", get "ddbbaaa"

Then delete "bbb", get "dddaa"

Finally delete "ddd", get "aa"

Example 3:

Input: s = "pbbccggtciippooaais", k = 2

Output: "ps"

C:

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

struct Stack {
    int *arr;
    int top;
    int capacity;
};

// Function to initialize a stack
struct Stack* createStack(int capacity) {
    struct Stack* stack = (struct Stack*)malloc(sizeof(struct Stack));
    stack->capacity = capacity;
    stack->top = -1;
    stack->arr = (int*)malloc(stack->capacity * sizeof(int));
    return stack;
}

// Function to check if the stack is empty
int isEmpty(struct Stack* stack) {
    return stack->top == -1;
}

// Function to push an element onto the stack
void push(struct Stack* stack, int item) {
    stack->arr[++stack->top] = item;
}

// Function to pop an element from the stack
int pop(struct Stack* stack) {
    if (isEmpty(stack)) {
        return -1; // Stack underflow
    }
    return stack->arr[stack->top--];
}

// Function to remove duplicates in a string
char* removeDuplicates(char* s, int k) {
    int length = strlen(s);
    struct Stack* counts = createStack(length);

    for (int i = 0; i < length; ++i) {
        if (i == 0 || s[i] != s[i - 1]) {
            push(counts, 1);
        } else {
            int incremented = pop(counts) + 1;
            if (incremented == k) {
                memmove(s + i - k + 1, s + i + 1, length - i);
            }
        }
    }
}

```

```

        i = i - k;
        length = length - k;
    } else {
        push(counts, incremented);
    }
}
}

return s;
}

int main() {
    char s[] = "deeedbbcccbdaa"; // Example input string
    int k = 3; // Example value of k

    printf("Original string: %s\n", s);
    char* result = removeDuplicates(s, k);
    printf("String after removing duplicates: %s\n", result);

    free(result); // Free dynamically allocated memory

    return 0;
}

```

1.82 Number Of Islands

Given an $m \times n$ 2D binary grid grid which represents a map of '1's (land) and '0's (water), return *the number of islands*.

An **island** is surrounded by water and is formed by connecting adjacent lands horizontally or vertically. You may assume all four edges of the grid are all surrounded by water.

Example 1:

Input: grid =
`[["1","1","1","1","0"],
 ["1","1","0","1","0"],
 ["1","1","0","0","0"],
 ["0","0","0","0","0"]]`

Output: 1

Example 2:

Input: grid =
`[["1","1","0","0","0"],
 ["1","1","0","0","0"]]`

```
[["0","0","1","0","0"],  
 ["0","0","0","1","1"]  
]
```

Output: 3

C:

```
#include <stdio.h>  
#include <stdlib.h>  
  
void dfs(char** grid, int gridSize, int gridColSize, int crow, int ccol) {  
    if (crow < 0 || crow >= gridSize || ccol < 0 || ccol >= gridColSize ||  
        grid[crow][ccol] == '0') {  
        return;  
    }  
    grid[crow][ccol] = '0';  
    dfs(grid, gridSize, gridColSize, crow - 1, ccol);  
    dfs(grid, gridSize, gridColSize, crow + 1, ccol);  
    dfs(grid, gridSize, gridColSize, crow, ccol + 1);  
    dfs(grid, gridSize, gridColSize, crow, ccol - 1);  
}  
  
int numIslands(char** grid, int gridSize, int* gridColSize) {  
    if (grid == NULL || gridSize == 0 || gridColSize == NULL || *gridColSize == 0) {  
        return 0;  
    }  
    int num_of_islands = 0;  
    for (int i = 0; i < gridSize; i++) {  
        for (int j = 0; j < *gridColSize; j++) {  
            if (grid[i][j] == '1') {  
                num_of_islands++;  
                dfs(grid, gridSize, *gridColSize, i, j);  
            }  
        }  
    }  
    return num_of_islands;  
}  
  
int main() {  
    // Example grid dimensions  
    int gridSize = 4;  
    int gridColSize[] = {5, 5, 5, 5}; // Column sizes for each row  
  
    // Allocate memory for the grid  
    char** grid = (char**)malloc(gridSize * sizeof(char*));  
    for (int i = 0; i < gridSize; i++) {  
        grid[i] = (char*)malloc((gridColSize[i] + 1) * sizeof(char)); // +1 for the null  
        terminator  
    }  
  
    // Populate the grid with the example data
```

```

strcpy(grid[0], "11110");
strcpy(grid[1], "11010");
strcpy(grid[2], "11000");
strcpy(grid[3], "00000");

// Call the numIslands function
int islands = numIslands(grid, gridSize, gridColSize);
printf("Number of islands: %d\n", islands);

// Free dynamically allocated memory
for (int i = 0; i < gridSize; i++) {
    free(grid[i]);
}
free(grid);

return 0;
}

```

1.83 Copy List With Random Pointer

A linked list of length n is given such that each node contains an additional random pointer, which could point to any node in the list, or null.

Construct a **deep copy** of the list. The deep copy should consist of exactly n **brand new** nodes, where each new node has its value set to the value of its corresponding original node. Both the next and random pointer of the new nodes should point to new nodes in the copied list such that the pointers in the original list and copied list represent the same list state. **None of the pointers in the new list should point to nodes in the original list.**

For example, if there are two nodes X and Y in the original list, where X.random --> Y, then for the corresponding two nodes x and y in the copied list, x.random --> y.


Return ***the head of the copied linked list.***

The linked list is represented in the input/output as a list of n nodes. Each node is represented as a pair of [val, random_index] where:

- val: an integer representing Node.val
- random_index: the index of the node (range from 0 to n-1) that the random pointer points to, or null if it does not point to any node.

Your code will **only** be given the head of the original linked list.


Example 1:



Input: head = [[7,null],[13,0],[11,4],[10,2],[1,0]]

Output: [[7,null],[13,0],[11,4],[10,2],[1,0]]


Example 2:



Input: head = [[1,1],[2,1]]

Output: [[1,1],[2,1]]

Example 3:



Input: head = [[3,null],[3,0],[3,null]]

Output: [[3,null],[3,0],[3,null]]

C:

```
/**
 * Definition for a Node.
 * struct Node {
 *     int val;
 *     struct Node *next;
 *     struct Node *random;
 * };
 */
```

```
#include <stdio.h>
#include <stdlib.h>
```

```

// Definition for a Node
struct Node {
    int val;
    struct Node* next;
    struct Node* random;
};

// Function to copy a random linked list
struct Node* copyRandomList(struct Node* head) {
    if (head == NULL) {
        return NULL;
    }
    struct Node *curr = head;
    while (curr != NULL) {
        struct Node* new = (struct Node*) malloc (sizeof(struct Node));
        new->val = curr->val;
        new->next = curr->next;
        new->random = NULL;
        curr->next = new;
        curr = new->next;
    }
    curr = head;
    while (curr != NULL) {
        if (curr->random != NULL) {
            curr->next->random = curr->random->next;
        }
        curr = curr->next->next;
    }
    curr= head;
    struct Node* new_head = head->next;
    struct Node *new_curr = new_head;
    while (curr != NULL) {
        curr->next = new_curr->next;
        curr = curr->next;
        if (curr != NULL) {
            new_curr->next = curr->next;
            new_curr = new_curr->next;
        }
    }
    return new_head;
}

int main() {
    // Create example nodes
    struct Node* head = (struct Node*)malloc(sizeof(struct Node));
    struct Node* second = (struct Node*)malloc(sizeof(struct Node));
    struct Node* third = (struct Node*)malloc(sizeof(struct Node));

    // Assign values
}

```

```

head->val = 1;
head->next = second;
head->random = third;

second->val = 2;
second->next = third;
second->random = head;

third->val = 3;
third->next = NULL;
third->random = second;

// Copy the linked list with random pointers
struct Node* newHead = copyRandomList(head);

// Display original and copied list information
printf("Original List:\n");
struct Node* curr = head;
while (curr != NULL) {
    printf("Node val: %d, Random val: %d\n", curr->val, curr->random ? curr->random->val : -1);
    curr = curr->next;
}

printf("\nCopied List:\n");
curr = newHead;
while (curr != NULL) {
    printf("Node val: %d, Random val: %d\n", curr->val, curr->random ? curr->random->val : -1);
    curr = curr->next;
}

// Free allocated memory
free(head);
free(second);
free(third);

return 0;
}

```

1.84 Two Sum

Given an array of integers `nums` and an integer `target`, return *indices of the two numbers such that they add up to target*.

You may assume that each input would have **`exactly one solution`**, and you may not use the `same` element twice.

You can return the answer in any order.

Example 1:

Input: nums = [2,7,11,15], target = 9

Output: [0,1]

Explanation: Because nums[0] + nums[1] == 9, we return [0, 1].

Example 2:

Input: nums = [3,2,4], target = 6

Output: [1,2]

Example 3:

Input: nums = [3,3], target = 6

Output: [0,1]

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

typedef struct {
    int key;
    int value;
} hashEntry_t;

typedef struct {
    hashEntry_t *table;
    int capacity;
} hashTable_t;

void init(hashTable_t *t, int capacity) {
    t->table = (hashEntry_t *)malloc(sizeof(hashEntry_t) * capacity);
    t->capacity = capacity;
}

bool contains(hashTable_t *t, int complement, int *index) {
    for (int i = 0; i < t->capacity; i++) {
        if (t->table[i].key == complement) {
            *index = t->table[i].value;
            return true;
        }
    }
}
```

```

        return false;
    }

int insert(hashTable_t *t, int number, int number_index, int target) {
    int index = 0;
    int complement = target - number;
    if (contains(t, complement, &index)) {
        return index;
    } else {
        t->table[number_index].key = number;
        t->table[number_index].value = number_index;
    }
    return -1;
}

int* twoSum(int* nums, int numsSize, int target, int* returnSize) {
    hashTable_t t;
    init(&t, numsSize);
    int *result = (int *)malloc(sizeof(int) * 2);

    for (int i = 0; i < numsSize; i++) {
        int j = insert(&t, nums[i], i, target);
        if (j != -1) {
            result[0] = i;
            result[1] = j;
            *returnSize = 2;
            return result;
        }
    }

    free(t.table);
    return NULL;
}

int main() {
    int nums[] = {2, 7, 11, 15};
    int target = 9;
    int returnSize;
    int *result = twoSum(nums, sizeof(nums) / sizeof(nums[0]), target, &returnSize);
    if (result != NULL) {
        printf("Indices: [%d, %d]\n", result[0], result[1]);
        free(result);
    } else {
        printf("No two elements found with the sum equal to the target.\n");
    }
    return 0;
}

```

1.85 Flood Fill


An image is represented by an $m \times n$ integer grid image where $\text{image}[i][j]$ represents the pixel value of the image.

You are also given three integers sr , sc , and color. You should perform a **flood fill** on the image starting from the pixel $\text{image}[sr][sc]$.

To perform a **flood fill**, consider the starting pixel, plus any pixels connected **4-directionally** to the starting pixel of the same color as the starting pixel, plus any pixels connected **4-directionally** to those pixels (also with the same color), and so on. Replace the color of all of the aforementioned pixels with color.

Return *the modified image after performing the flood fill*.

Example 1:



Input: $\text{image} = [[1,1,1],[1,1,0],[1,0,1]]$, $sr = 1$, $sc = 1$, $\text{color} = 2$

Output: $[[2,2,2],[2,2,0],[2,0,1]]$

Explanation: From the center of the image with position $(sr, sc) = (1, 1)$ (i.e., the red pixel), all pixels connected by a path of the same color as the starting pixel (i.e., the blue pixels) are colored with the new color.

Note the bottom corner is not colored 2, because it is not 4-directionally connected to the starting pixel.

Example 2:

Input: $\text{image} = [[0,0,0],[0,0,0]]$, $sr = 0$, $sc = 0$, $\text{color} = 0$

Output: $[[0,0,0],[0,0,0]]$

Explanation: The starting pixel is already colored 0, so no changes are made to the image.

C:

```
/**  
 * Return an array of arrays of size *returnSize.  
 * The sizes of the arrays are returned as *returnColumnSizes array.  
 * Note: Both returned array and *columnSizes array must be malloced, assume caller  
 calls free().  
 */  
#include <stdio.h>  
#include <stdlib.h>  
  
void dfs(int** image, int imageSize, int* imageColSize, int sr, int sc, int  
originalColor, int newColor) {  
    // Base case: check if the current pixel is out of bounds or already colored with  
    // the new color  
    if (sr < 0 || sr >= imageSize || sc < 0 || sc >= imageColSize[sr] || image[sr][sc]  
!= originalColor) {  
        return;  
    }  
  
    // Change the color of the current pixel  
    image[sr][sc] = newColor;  
  
    // Recursive calls for the neighboring pixels  
    dfs(image, imageSize, imageColSize, sr - 1, sc, originalColor, newColor); // Up  
    dfs(image, imageSize, imageColSize, sr + 1, sc, originalColor, newColor); // Down  
    dfs(image, imageSize, imageColSize, sr, sc - 1, originalColor, newColor); // Left  
    dfs(image, imageSize, imageColSize, sr, sc + 1, originalColor, newColor); // Right  
}  
  
int** floodFill(int** image, int imageSize, int* imageColSize, int sr, int sc, int  
color, int* returnSize, int** returnColumnSizes) {  
    if (image == NULL || imageSize == 0 || imageColSize == NULL) {  
        *returnSize = 0;  
        return NULL;  
    }  
  
    int originalColor = image[sr][sc];  
  
    // Check if the fill color is the same as the original color  
    if (originalColor == color) {  
        *returnSize = imageSize;  
        *returnColumnSizes = imageColSize;  
        return image;  
    }  
  
    // Allocate memory for the result image  
    int** result = (int**)malloc(imageSize * sizeof(int*));  
    *returnColumnSizes = (int*)malloc(imageSize * sizeof(int));
```

```

    for (int i = 0; i < imageSize; i++) {
        result[i] = (int*)malloc(imageColSize[i] * sizeof(int));
        (*returnColumnSizes)[i] = imageColSize[i];
    }

    // Copy the original image to the result image
    for (int i = 0; i < imageSize; i++) {
        for (int j = 0; j < imageColSize[i]; j++) {
            result[i][j] = image[i][j];
        }
    }

    // Apply the flood fill algorithm
    dfs(result, imageSize, *returnColumnSizes, sr, sc, originalColor, color);

    *returnSize = imageSize;
    return result;
}

int main() {
    // Example image
    int imageSize = 3;
    int imageColSize[] = {3, 3, 3};
    int** image = (int**)malloc(imageSize * sizeof(int*));
    for (int i = 0; i < imageSize; i++) {
        image[i] = (int*)malloc(imageColSize[i] * sizeof(int));
    }

    // Initialize the example image
    int exampleImage[3][3] = {
        {1, 1, 1},
        {1, 1, 0},
        {1, 0, 1}
    };

    // Copy the example image to the allocated memory
    for (int i = 0; i < imageSize; i++) {
        for (int j = 0; j < imageColSize[i]; j++) {
            image[i][j] = exampleImage[i][j];
        }
    }

    // Print the original image
    printf("Original Image:\n");
    for (int i = 0; i < imageSize; i++) {
        for (int j = 0; j < imageColSize[i]; j++) {
            printf("%d ", image[i][j]);
        }
    }
    printf("\n");
}

```

```

    }

    printf("\n");

    // Apply flood fill to change color at position (1,1) to 2
    int returnSize;
    int* returnColumnSizes;
    int** filledImage = floodFill(image, imageSize, imageColSize, 1, 1, 2, &returnSize,
&returnColumnSizes);


    // Print the filled image
    printf("Filled Image:\n");
    for (int i = 0; i < returnSize; i++) {
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d ", filledImage[i][j]);
        }
        printf("\n");
    }

    // Free memory
    for (int i = 0; i < imageSize; i++) {
        free(image[i]);
        free(filledImage[i]);
    }
    free(image);
    free(filledImage);
    free(returnColumnSizes);

    return 0;
}

```

Example 1:



Input: image = [[1,1,1],[1,1,0],[1,0,1]], sr = 1, sc = 1, color = 2

Output: [[2,2,2],[2,2,0],[2,0,1]]

Explanation: From the center of the image with position $(sr, sc) = (1, 1)$ (i.e., the red pixel), all pixels connected by a path of the same color as the starting pixel (i.e., the blue pixels) are colored with the new color.

Note the bottom corner is not colored 2, because it is not 4-directionally connected to the starting pixel.

1.86 Maximum SubArray

Given an integer array `nums`, find the

subarray

with the largest sum, and return *its sum*.



Example 1:

Input: `nums = [-2,1,-3,4,-1,2,1,-5,4]`

Output: 6

Explanation: The subarray `[4,-1,2,1]` has the largest sum 6.

Example 2:

Input: `nums = [1]`

Output: 1

Explanation: The subarray `[1]` has the largest sum 1.

Example 3:

Input: `nums = [5,4,-1,7,8]`

Output: 23

Explanation: The subarray `[5,4,-1,7,8]` has the largest sum 23.

C:

```
int maxSubArray(int* nums, int numsSize) {
    if (numsSize == 0) {
        // Empty array case
        return 0;
    }

    int maxSum = nums[0]; // Initialize maxSum with the first element
    int currentSum = nums[0]; // Initialize currentSum with the first element

    for (int i = 1; i < numsSize; i++) {
        // Update currentSum to either continue the current subarray or start a new one
        currentSum = (currentSum > 0) ? currentSum + nums[i] : nums[i];

        // Update maxSum if the current subarray sum is greater
        if (currentSum > maxSum) {
            maxSum = currentSum;
        }
    }
}
```

```

        }
    }

    return maxSum;
}

int main() {
// Test cases
int nums1[] = {-2, 1, -3, 4, -1, 2, 1, -5, 4};
int size1 = sizeof(nums1) / sizeof(nums1[0]);
printf("Max subarray sum of nums1: %d\n", maxSubArray(nums1, size1));

int nums2[] = {1, 2, 3, 4, 5};
int size2 = sizeof(nums2) / sizeof(nums2[0]);
printf("Max subarray sum of nums2: %d\n", maxSubArray(nums2, size2));

int nums3[] = {-1, -2, -3, -4, -5};
int size3 = sizeof(nums3) / sizeof(nums3[0]);
printf("Max subarray sum of nums3: %d\n", maxSubArray(nums3, size3));

return 0;
}

```

1.87 Sort Colors

Given an array `nums` with n objects colored red, white, or blue, sort them [in-place](#) so that objects of the same color are adjacent, with the colors in the order red, white, and blue.

We will use the integers 0, 1, and 2 to represent the color red, white, and blue, respectively.

You must solve this problem without using the library's sort function.

Example 1:

Input: <code>nums = [2,0,2,1,1,0]</code>
Output: <code>[0,0,1,1,2,2]</code>

Example 2:

Input: <code>nums = [2,0,1]</code>
Output: <code>[0,1,2]</code>

C:

```
#include <stdio.h>

void sortColors(int* nums, int numsSize) {
    int low = 0;           // Index for 0
    int high = numsSize - 1; // Index for 2
```

```

for (int i = 0; i <= high;) {
    if (nums[i] == 0) {
        // Swap current element with the one at the low index
        int temp = nums[i];
        nums[i] = nums[low];
        nums[low] = temp;

        // Move low and i to the right
        low++;
        i++;
    } else if (nums[i] == 2) {
        // Swap current element with the one at the high index
        int temp = nums[i];
        nums[i] = nums[high];
        nums[high] = temp;

        // Move high to the left
        high--;
    } else {
        // Element is 1, move i to the right
        i++;
    }
}

int main() {
    // Test case
    int nums[] = {2, 0, 2, 1, 1, 0};
    int size = sizeof(nums) / sizeof(nums[0]);

    printf("Original array: ");
    for (int i = 0; i < size; i++) {
        printf("%d ", nums[i]);
    }
    printf("\n");

    sortColors(nums, size);

    printf("Sorted array: ");
    for (int i = 0; i < size; i++) {
        printf("%d ", nums[i]);
    }
    printf("\n");

    return 0;
}

```

1.88 Median Of Two Sorted Arrays

Given two sorted arrays nums1 and nums2 of size m and n respectively, return **the median** of the two sorted arrays.

The overall run time complexity should be $O(\log(m+n))$.

Example 1:

Input: $\text{nums1} = [1,3]$, $\text{nums2} = [2]$

Output: 2.00000

Explanation: merged array = [1,2,3] and median is 2.

Example 2:

Input: $\text{nums1} = [1,2]$, $\text{nums2} = [3,4]$

Output: 2.50000

Explanation: merged array = [1,2,3,4] and median is $(2 + 3) / 2 = 2.5$.

C:

```
#include <stdio.h>

double findMedianSortedArrays(int* nums1, int nums1Size, int* nums2, int nums2Size) {
    int totalSize = nums1Size + nums2Size;
    int merged[totalSize];

    // Merge the two sorted arrays
    int i = 0, j = 0, k = 0;
    while (i < nums1Size && j < nums2Size) {
        if (nums1[i] < nums2[j]) {
            merged[k++] = nums1[i++];
        } else {
            merged[k++] = nums2[j++];
        }
    }

    // Add remaining elements from both arrays
    while (i < nums1Size) {
        merged[k++] = nums1[i++];
    }

    while (j < nums2Size) {
        merged[k++] = nums2[j++];
    }

    // Calculate the median
    if (totalSize % 2 == 0) {
```

```

        return (double)(merged[totalSize / 2 - 1] + merged[totalSize / 2]) / 2.0;
    } else {
        return (double)merged[totalSize / 2];
    }
}

int main() {
// Test case
int nums1[] = {1, 3};
int nums1Size = 2;
int nums2[] = {2};
int nums2Size = 1;

double median = findMedianSortedArrays(nums1, nums1Size, nums2, nums2Size);
printf("Median: %lf\n", median);

return 0;
}

```

Input: nums1 = [1,3], nums2 = [2]

Output: 2.00000

Explanation: merged array = [1,2,3] and median is 2.

1.89 Root Equals Sum Of Children

```

#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to check if a given node is a valid tree node
bool checkTree(struct TreeNode* root) {
    return (root != NULL && (root->left != NULL) && (root->right != NULL) && (root-
>left->val + root->right->val == root->val)) ? true : false;
}

// Main function
int main() {
// Example usage
    struct TreeNode* root = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->val = 5;

    root->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));

```

```

root->left->val = 2;

root->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
root->right->val = 3;

root->left->left = NULL;
root->left->right = NULL;


root->right->left = NULL;
root->right->right = NULL;

// Check if the root is a valid tree node
if (checkTree(root)) {
    printf("Root node is a valid tree node.\n");
} else {
    printf("Root node is not a valid tree node.\n");
}

// Free memory
free(root->left);
free(root->right);
free(root);

return 0;
}

```



Input: root = [10,4,6]

Output: true

Explanation: The values of the root, its left child, and its right child are 10, 4, and 6, respectively. 10 is equal to 4 + 6, so we return true.

Time/Space Complexity: O(1)/O(1)

1.90 Generate Parentheses

Given n pairs of parentheses, write a function to generate all combinations of well-formed parentheses.

Example 1:**Input:** n = 3**Output:** [")("), ")("), ")("), ")("), ")(")]**Example 2:****Input:** n = 1**Output:** ["()"]**C:**

```
/*
 * Note: The returned array must be malloced, assume caller calls free().
 */
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

void backtracking(char*** result, int* returnSize, char* curString, int leftCount, int rightCount, int n, int index) {
    if (index == 2 * n) {
        curString[index] = '\0';
        (*result)[*returnSize] = strdup(curString);
        (*returnSize)++;
        return;
    }

    if (leftCount < n) {
        curString[index] = '(';
        backtracking(result, returnSize, curString, leftCount + 1, rightCount, n, index + 1);
    }

    if (leftCount > rightCount) {
        curString[index] = ')';
        backtracking(result, returnSize, curString, leftCount, rightCount + 1, n, index + 1);
    }
}

char** generateParenthesis(int n, int* returnSize) {
    char** result = (char**)malloc(1000 * sizeof(char*));
    *returnSize = 0;

    char* curString = (char*)malloc((2 * n + 1) * sizeof(char));
    curString[0] = '\0';

    backtracking(&result, returnSize, curString, 0, 0, n, 0);
}
```

```

        free(curString);

        return result;
    }

int main() {
    int n = 3;
    int returnSize;
    char** result = generateParenthesis(n, &returnSize);

    printf("Generated Parentheses:\n");
    for (int i = 0; i < returnSize; i++) {
        printf("%s\n", result[i]);
        free(result[i]);
    }
    free(result);

    return 0;
}

```

1.91 Meeting Rooms II – Minimum Rooms Required

Given an array of meeting time intervals intervals where intervals[i] = [start_i, end_i], return *the minimum number of conference rooms required*.

Example 1:

Input: intervals = [[0,30],[5,10],[15,20]]
Output: 2

Example 2:

Input: intervals = [[7,10],[2,4]]
Output: 1

C:

```

#include <stdio.h>
#include <stdlib.h>

int compare(const void* a, const void* b) {
    return ((int**)a)[0][0] - ((int**)b)[0][0];
}

int minMeetingRooms(int** intervals, int intervalsSize, int* intervalsColSize) {

```

```

if (intervals == NULL || intervalsSize == 0) {
    return 0;
}

// Sort the intervals based on start times
qsort(intervals, intervalsSize, sizeof(int*), compare);

// Priority queue to store end times of meetings
int* endTimes = (int*)malloc(sizeof(int) * intervalsSize);
int rooms = 0;

// Iterate through the sorted intervals
for (int i = 0; i < intervalsSize; i++) {
    int start = intervals[i][0];
    int end = intervals[i][1];

    // Check if there is an available room
    int j;
    for (j = 0; j < rooms; j++) {
        if (endTimes[j] <= start) {
            endTimes[j] = end;
            break;
        }
    }

    // If no available room, allocate a new room
    if (j == rooms) {
        endTimes[rooms++] = end;
    }
}

free(endTimes);

return rooms;
}

int main() {
    // Example intervals
    int intervalsSize = 3;
    int intervalsColSize[] = {2, 2, 2};
    int** intervals = (int**)malloc(intervalsSize * sizeof(int*));
    intervals[0] = (int*)malloc(2 * sizeof(int));
    intervals[0][0] = 0;
    intervals[0][1] = 30;
    intervals[1] = (int*)malloc(2 * sizeof(int));
    intervals[1][0] = 5;
    intervals[1][1] = 10;
    intervals[2] = (int*)malloc(2 * sizeof(int));
    intervals[2][0] = 15;
}

```

```

intervals[2][1] = 20;

int rooms = minMeetingRooms(intervals, intervalsSize, intervalsColSize);
printf("Minimum meeting rooms required: %d\n", rooms);

// Free allocated memory
for (int i = 0; i < intervalsSize; i++) {
    free(intervals[i]);
}
free(intervals);


return 0;
}

```

1.92 Reverse Linked List

Given the head of a singly linked list, reverse the list, and return *the reversed list*.




Example 1:



Input: head = [1,2,3,4,5]

Output: [5,4,3,2,1]

Example 2:



Input: head = [1,2]

Output: [2,1]

Example 3:

Input: head = []

Output: []

C:

```

/*
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */
#include <stdio.h>
#include <stdlib.h>

// Definition for singly-linked list.
struct ListNode {
    int val;
    struct ListNode *next;
};

// Function to reverse a singly-linked list
struct ListNode* reverseList(struct ListNode* head) {
    struct ListNode *prev = NULL;
    struct ListNode *curr = head;
    struct ListNode *next = NULL;
    while (curr != NULL) {
        next = curr->next;
        curr->next = prev;
        prev = curr;
        curr = next;
    }
    return prev;
}

```

```

// Function to create a new node
struct ListNode* createNode(int val) {
    struct ListNode* newNode = (struct ListNode*)malloc(sizeof(struct ListNode));
    newNode->val = val;
    newNode->next = NULL;
    return newNode;
}

// Function to free memory allocated for the linked list
void freeList(struct ListNode* head) {
    struct ListNode* temp;
    while (head != NULL) {
        temp = head;
        head = head->next;
        free(temp);
    }
}

// Function to print the linked list
void printList(struct ListNode* head) {
    while (head != NULL) {
        printf("%d -> ", head->val);
        head = head->next;
    }
    printf("NULL\n");
}

int main() {
    // Creating a sample linked list: 1 -> 2 -> 3 -> 4 -> 5 -> NULL
    struct ListNode* head = createNode(1);
    head->next = createNode(2);
    head->next->next = createNode(3);
    head->next->next->next = createNode(4);
    head->next->next->next->next = createNode(5);

    printf("Original list: ");
    printList(head);

    // Reversing the linked list
    head = reverseList(head);

    printf("Reversed list: ");
    printList(head);

    // Freeing the memory allocated for the linked list
    freeList(head);

    return 0;
}

```

}

1.93 Implement Queue Using Stack

Implement a first in first out (FIFO) queue using only two stacks. The implemented queue should support all the functions of a normal queue (push, peek, pop, and empty).

Implement the MyQueue class:

- void push(int x) Pushes element x to the back of the queue.
- int pop() Removes the element from the front of the queue and returns it.
- int peek() Returns the element at the front of the queue.
- boolean empty() Returns true if the queue is empty, false otherwise.

Notes:

- You must use **only** standard operations of a stack, which means only push to top, peek/pop from top, size, and is empty operations are valid.
- Depending on your language, the stack may not be supported natively. You may simulate a stack using a list or deque (double-ended queue) as long as you use only a stack's standard operations.

Example 1:

Input

```
["MyQueue", "push", "push", "peek", "pop", "empty"]
[], [1], [2], [], [], []]
```

Output

```
[null, null, null, 1, 1, false]
```

Explanation

```
MyQueue myQueue = new MyQueue();
myQueue.push(1); // queue is: [1]
myQueue.push(2); // queue is: [1, 2] (leftmost is front of the queue)
myQueue.peek(); // return 1
myQueue.pop(); // return 1, queue is [2]
myQueue.empty(); // return false
```

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

// Definition for a MyQueue struct
```

```

typedef struct {
    int* stack1; // Stack for enqueue operation (push)
    int* stack2; // Stack for dequeue operation (pop, peek)
    int top1;    // Top index for stack1
    int top2;    // Top index for stack2
    int capacity; // Capacity of the stacks
} MyQueue;

// Function to create a new MyQueue
MyQueue* myQueueCreate() {
    MyQueue* queue = (MyQueue*)malloc(sizeof(MyQueue));
    queue->capacity = 100; // You can adjust the capacity based on your needs
    queue->stack1 = (int*)malloc(sizeof(int) * queue->capacity);
    queue->stack2 = (int*)malloc(sizeof(int) * queue->capacity);
    queue->top1 = -1;
    queue->top2 = -1;
    return queue;
}

// Function to enqueue an element into the queue
void enqueue(MyQueue* obj, int x) {
    if (obj->top1 == obj->capacity - 1) {
        // Resize stack1 if needed
        obj->capacity *= 2;
        obj->stack1 = realloc(obj->stack1, sizeof(int) * obj->capacity);
    }
    obj->stack1[++(obj->top1)] = x;
}

// Function to transfer elements from stack1 to stack2
void transferStacks(MyQueue* obj) {
    while (obj->top1 != -1) {
        obj->stack2[+(obj->top2)] = obj->stack1[(obj->top1)--];
    }
}

// Function to push an element into the queue
void myQueuePush(MyQueue* obj, int x) {
    enqueue(obj, x);
}

// Function to pop an element from the queue
int myQueuePop(MyQueue* obj) {
    if (obj->top2 == -1) {
        // If stack2 is empty, transfer elements from stack1
        transferStacks(obj);
    }
    if (obj->top2 == -1) {

```

```

        return -1; // Queue is empty
    }

    return obj->stack2[(obj->top2)--];
}

// Function to peek the front element of the queue
int myQueuePeek(MyQueue* obj) {
    if (obj->top2 == -1) {
        // If stack2 is empty, transfer elements from stack1
        transferStacks(obj);
    }

    if (obj->top2 == -1) {
        return -1; // Queue is empty
    }

    return obj->stack2[obj->top2];
}

// Function to check if the queue is empty
bool myQueueEmpty(MyQueue* obj) {
    return (obj->top1 == -1) && (obj->top2 == -1);
}

// Function to free memory allocated for the queue
void myQueueFree(MyQueue* obj) {
    free(obj->stack1);
    free(obj->stack2);
    free(obj);
}

// Main function to test the MyQueue implementation
int main() {
    // Create a new queue
    MyQueue* obj = myQueueCreate();

    // Push elements into the queue
    myQueuePush(obj, 1);
    myQueuePush(obj, 2);
    myQueuePush(obj, 3);

    // Pop and print elements from the queue
    printf("Dequeued element: %d\n", myQueuePop(obj)); // Output: 1
    printf("Dequeued element: %d\n", myQueuePop(obj)); // Output: 2

    // Peek and print the front element of the queue
    printf("Front element: %d\n", myQueuePeek(obj)); // Output: 3
}

```

```

// Check if the queue is empty
printf("Is the queue empty? %s\n", myQueueEmpty(obj) ? "Yes" : "No"); // Output: No

// Free memory allocated for the queue
myQueueFree(obj);

return 0;
}

```

1.94 Implement Stack Using Queue

Implement a last-in-first-out (LIFO) stack using only two queues. The implemented stack should support all the functions of a normal stack (push, top, pop, and empty).

Implement the MyStack class:

- void push(int x) Pushes element x to the top of the stack.
- int pop() Removes the element on the top of the stack and returns it.
- int top() Returns the element on the top of the stack.
- boolean empty() Returns true if the stack is empty, false otherwise.

Notes:

- You must use **only** standard operations of a queue, which means that only push to back, peek/pop from front, size and is empty operations are valid.
- Depending on your language, the queue may not be supported natively. You may simulate a queue using a list or deque (double-ended queue) as long as you use only a queue's standard operations.

Example 1:

Input

```
["MyStack", "push", "push", "top", "pop", "empty"]
[], [1], [2], [], [], []]
```

Output

```
[null, null, null, 2, 2, false]
```

Explanation

```
MyStack myStack = new MyStack();
myStack.push(1);
myStack.push(2);
myStack.top(); // return 2
myStack.pop(); // return 2
myStack.empty(); // return False
```

C:

```
#include <stdio.h>
```

```

#include <stdlib.h>
#include <stdbool.h>

// Definition for MyStack struct
typedef struct {
    int* queue;
    int front;
    int rear;
} MyStack;

// Function to create a new MyStack
MyStack* myStackCreate() {
    MyStack* obj = (MyStack*)malloc(sizeof(MyStack));
    obj->queue = (int*)malloc(1000 * sizeof(int)); // Adjust the size according to your
requirements
    obj->front = obj->rear = -1;
    return obj;
}

// Function to enqueue an element into the queue
void enqueue(int* queue, int* rear, int x) {
    queue[++(*rear)] = x;
}

// Function to dequeue an element from the queue
int dequeue(int* queue, int* front) {
    return queue[(*front)++];
}

// Function to push an element onto the stack
void myStackPush(MyStack* obj, int x) {
    enqueue(obj->queue, &(obj->rear), x);

    // Rotate the queue to make the recently pushed element at the front
    int size = obj->rear - obj->front + 1;
    for (int i = 0; i < size - 1; ++i) {
        enqueue(obj->queue, &(obj->rear), dequeue(obj->queue, &(obj->front)));
    }
}

// Function to pop the top element from the stack
int myStackPop(MyStack* obj) {
    if (obj == NULL || obj->front > obj->rear) {
        // Stack is empty
        return -1;
    }

    return dequeue(obj->queue, &(obj->front));
}

```

```

// Function to get the top element of the stack without popping it
int myStackTop(MyStack* obj) {
    if (obj == NULL || obj->front > obj->rear) {
        // Stack is empty
        return -1;
    }

    return obj->queue[obj->front];
}

// Function to check if the stack is empty
bool myStackEmpty(MyStack* obj) {
    return obj == NULL || obj->front > obj->rear;
}

// Function to free memory allocated for the stack
void myStackFree(MyStack* obj) {
    free(obj->queue);
    free(obj);
}

// Main function to test the MyStack implementation
int main() {
    // Create a new stack
    MyStack* obj = myStackCreate();

    // Push elements onto the stack
    myStackPush(obj, 1);
    myStackPush(obj, 2);
    myStackPush(obj, 3);

    // Pop and print elements from the stack
    printf("Popped element: %d\n", myStackPop(obj)); // Output: 3
    printf("Popped element: %d\n", myStackPop(obj)); // Output: 2

    // Get the top element of the stack without popping it
    printf("Top element: %d\n", myStackTop(obj)); // Output: 1

    // Check if the stack is empty
    printf("Is the stack empty? %s\n", myStackEmpty(obj) ? "Yes" : "No"); // Output: No

    // Free memory allocated for the stack
    myStackFree(obj);

    return 0;
}

/**

```

```

* Your MyStack struct will be instantiated and called as such:
* MyStack* obj = myStackCreate();
* myStackPush(obj, x);

* int param_2 = myStackPop(obj);

* int param_3 = myStackTop(obj);

* bool param_4 = myStackEmpty(obj);

* myStackFree(obj);
*/

```

1.95 Trapping Rain Water

Given n non-negative integers representing an elevation map where the width of each bar is 1, compute how much water it can trap after raining.

Example 1:



Input: height = [0,1,0,2,1,0,1,3,2,1,2,1]

Output: 6

Explanation: The above elevation map (black section) is represented by array [0,1,0,2,1,0,1,3,2,1,2,1]. In this case, 6 units of rain water (blue section) are being trapped.

Example 2:

Input: height = [4,2,0,3,2,5]

Output: 9

C:

```

#include <stdio.h>

int trap(int* height, int heightSize) {
    int left = 0, right = heightSize - 1;
    int ans = 0;

```

```

int leftMax = 0, rightMax = 0;

while (left < right) {
    if (height[left] < height[right]) {
        if (height[left] >= leftMax) {
            leftMax = height[left];
        } else {
            ans += (leftMax - height[left]);
        }
        left++;
    } else {
        if (height[right] >= rightMax) {
            rightMax = height[right];
        } else {
            ans += (rightMax - height[right]);
        }
        right--;
    }
}

return ans;
}

int main() {
    // Example heights
    int height[] = {0,1,0,2,1,0,1,3,2,1,2,1};
    int heightSize = sizeof(height) / sizeof(height[0]);

    // Calculate the trapped water
    int trappedWater = trap(height, heightSize);

    // Print the result
    printf("Trapped water: %d\n", trappedWater);

    return 0;
}

```

1.96 Longest SubString Without Repeating Characters

Given a string s, find the length of the **longest**

substring
without repeating characters.

Example 1:

Input: s = "abcabcbb"

Output: 3

Explanation: The answer is "abc", with the length of 3.

Example 2:

Input: s = "bbbbbb"

Output: 1

Explanation: The answer is "b", with the length of 1.

Example 3:

Input: s = "pwwkew"

Output: 3

Explanation: The answer is "wke", with the length of 3.

Notice that the answer must be a substring, "pwke" is a subsequence and not a substring.



C:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int lengthOfLongestSubstring(char* s) {
    int n = strlen(s);
    if (n == 0) {
        return 0;
    }

    int* charIndex = (int*)malloc(sizeof(int) * 128);
    for (int i = 0; i < 128; i++) {
        charIndex[i] = -1;
    }

    int maxLength = 0;
    int start = 0;

    for (int end = 0; end < n; end++) {
        if (charIndex[s[end]] != -1) {
            start = fmax(charIndex[s[end]] + 1, start);
        }

        maxLength = fmax(maxLength, end - start + 1);
        charIndex[s[end]] = end;
    }
}
```

```

        free(charIndex);
        return maxLength;
    }

int main() {
    // Test string
    char* s = "abcabcbb";

    // Calculate the length of the longest substring without repeating characters
    int length = lengthOfLongestSubstring(s);

    // Print the result
    printf("Length of the longest substring without repeating characters: %d\n",
length);

    return 0;
}

class Solution {
    public int lengthOfLongestSubstring(String s) {
        if (s.length() == 0) return 0;
        else if (s.length() == 1) return 1;
        else {
            HashSet <Character> hs = new HashSet<Character>();
            int max_length = 0;
            for (int k = 0; k < s.length(); k++) {
                hs.add(s.charAt(k));
                for (int i = k+1; i < s.length(); i++) {
                    if (!hs.contains(s.charAt(i))) {
                        hs.add(s.charAt(i));
                        if (i == s.length()-1) {
                            max_length = Math.max(max_length,hs.size());
                            hs.clear();
                        }
                    }
                }
                else {
                    max_length = Math.max(max_length,hs.size());
                    hs.clear();
                    break;
                }
            }
        }
        return max_length;
    }
}

```

1.97 SubArray Sum Equals K

Given an array of integers `nums` and an integer `k`, return *the total number of subarrays whose sum equals to k*.

A subarray is a contiguous **non-empty** sequence of elements within an array.

Example 1:

Input: `nums = [1,1,1]`, `k = 2`

Output: 2

Example 2:

Input: `nums = [1,2,3]`, `k = 3`

Output: 2

C:

```
#include <stdio.h>
#include <stdlib.h>

int subarraySum(int* nums, int numsSize, int k) {
    int count = 0;
    int sum = 0;

    // Create a hashmap to store cumulative sum frequencies
    int* hashmap = (int*)malloc(sizeof(int) * (numsSize + 1));
    for (int i = 0; i <= numsSize; i++) {
        hashmap[i] = 0;
    }
    hashmap[0] = 1;

    for (int i = 0; i < numsSize; i++) {
        sum += nums[i];

        int diff = sum - k;

        if (hashmap[diff] > 0) {
            count += hashmap[diff];
        }

        hashmap[sum]++;
    }

    free(hashmap);
}
```

```

// Debugging output
printf("Count: %d\n", count);
return count;
}

int main() {
    // Test array
    int nums[] = {1, 1, 1};

    // Size of the array
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Target sum
    int k = 2;

    // Calculate the number of subarrays with the sum equal to k
    int count = subarraySum(nums, numsSize, k);

    // Print the result
    printf("Number of subarrays with sum equal to %d: %d\n", k, count);

    return 0;
}

```

1.98 Search In A Rotated Sorted Array

There is an integer array `nums` sorted in ascending order (with **distinct** values).

Prior to being passed to your function, `nums` is **possibly rotated** at an unknown pivot index `k` ($1 \leq k < \text{nums.length}$) such that the resulting array is `[nums[k], nums[k+1], ..., nums[n-1], nums[0], nums[1], ..., nums[k-1]]` (**0-indexed**). For example, `[0,1,2,4,5,6,7]` might be rotated at pivot index 3 and become `[4,5,6,7,0,1,2]`.

Given the array `nums` **after** the possible rotation and an integer target, return *the index of target if it is in nums, or -1 if it is not in nums.*

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [4,5,6,7,0,1,2]`, `target = 0`
Output: `4`

Example 2:

Input: `nums = [4,5,6,7,0,1,2]`, `target = 3`

Output: -1

Example 3:

Input: nums = [1], target = 0

Output: -1

C:

```
#include <stdio.h>

int search(int* nums, int numsSize, int target) {
    int n = numsSize;
    int left = 0, right = n - 1;

    while (left <= right) {
        int mid = left + (right - left) / 2;

        // Case 1: find target
        if (nums[mid] == target) {
            return mid;
        }

        // Case 2: subarray on mid's left is sorted
        else if (nums[mid] >= nums[left]) {
            if (target >= nums[left] && target < nums[mid]) {
                right = mid - 1;
            } else {
                left = mid + 1;
            }
        }

        // Case 3: subarray on mid's right is sorted
        else {
            if (target <= nums[right] && target > nums[mid]) {
                left = mid + 1;
            } else {
                right = mid - 1;
            }
        }
    }

    return -1; // Target not found
}

int main() {
    // Test array
    int nums[] = {4, 5, 6, 7, 0, 1, 2};

    // Size of the array
```

```

int numsSize = sizeof(nums) / sizeof(nums[0]);

// Target element to search
int target = 0;

// Search for the target element in the rotated sorted array
int index = search(nums, numsSize, target);

// Print the result
if (index != -1) {
    printf("Target element %d found at index %d.\n", target, index);
} else {
    printf("Target element %d not found in the array.\n", target);
}

return 0;
}

```

1.99 Top K Frequent Elements

Given an integer array `nums` and an integer `k`, return `the k most frequent elements`. You may return the answer in `any order`.

Example 1:

Input: `nums = [1,1,1,2,2,3], k = 2`
Output: `[1,2]`

Example 2:

Input: `nums = [1], k = 1`
Output: `[1]`

C:

```

#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int value;
    int frequency;
} Element;

int compare(const void *a, const void *b) {
    return ((Element *)b)->frequency - ((Element *)a)->frequency;
}

```

```

int* topKFrequent(int* nums, int numsSize, int k, int* returnSize) {
    // Initialize a hash table with calloc
    int* hashTable = (int*)calloc(1001, sizeof(int));

    // Count the frequency of each element and store it in the hash table
    for (int i = 0; i < numsSize; ++i) {
        hashTable[nums[i]]++;
    }

    // Populate the elements array with values and frequencies from the hash table
    Element* elements = (Element*)malloc(1001 * sizeof(Element));
    int count = 0;
    for (int i = 0; i <= 1000; ++i) {
        if (hashTable[i] > 0) {
            elements[count++] = (Element){i, hashTable[i]};
        }
    }

    // Sort the elements array based on frequency in descending order
    qsort(elements, count, sizeof(Element), compare);

    // Allocate memory for the result array
    int* result = (int*)malloc(k * sizeof(int));

    // Copy the top k frequent elements to the result array
    for (int i = 0; i < k; ++i) {
        result[i] = elements[i].value;
    }

    // Update the returnSize
    *returnSize = k;

    // Free allocated memory
    free(elements);
    free(hashTable);

    return result;
}

int main() {
    // Test array
    int nums[] = {1, 1, 1, 2, 2, 3};
    int numsSize = sizeof(nums) / sizeof(nums[0]);
    int k = 2; // Number of top frequent elements to find

    // Get the top k frequent elements
    int returnSize;
    int* topKElements = topKFrequent(nums, numsSize, k, &returnSize);
}

```

```

// Print the top k frequent elements
printf("Top %d frequent elements: ", k);
for (int i = 0; i < returnSize; ++i) {
    printf("%d ", topKElements[i]);
}
printf("\n");

// Free allocated memory
free(topKElements);

return 0;
}


```

1.100 Rotate Image

You are given an $n \times n$ 2D matrix representing an image, rotate the image by **90** degrees (clockwise).

You have to rotate the image **in-place**, which means you have to modify the input 2D matrix directly. **DO NOT** allocate another 2D matrix and do the rotation.

Example 1:



Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]

Output: [[7,4,1],[8,5,2],[9,6,3]]

Example 2:

The diagram illustrates a 4x4 matrix rotation. On the left, the original matrix is shown with values: 5, 1, 9, 11; 2, 4, 8, 10; 13, 3, 6, 7; and 15, 14, 12, 16. An arrow points to the right, where the rotated matrix is shown with values: 15, 13, 2, 5; 14, 3, 4, 1; 12, 6, 8, 9; and 16, 7, 10, 11.

Input: matrix = [[5,1,9,11],[2,4,8,10],[13,3,6,7],[15,14,12,16]]

Output: [[15,13,2,5],[14,3,4,1],[12,6,8,9],[16,7,10,11]]

C:

```
#include <stdio.h>
#include <stdlib.h>

void transpose(int** matrix, int matrixSize, int matrixColSize) {
    for (int i = 0; i < matrixSize; i++) {
        for (int j = i + 1; j < matrixColSize; j++) {
            int temp = matrix[i][j];
            matrix[i][j] = matrix[j][i];
            matrix[j][i] = temp;
        }
    }
}

void reverse(int** matrix, int matrixSize, int matrixColSize) {
    for (int i = 0; i < matrixSize; i++) {
        for (int j = 0; j < matrixColSize / 2; j++) {
            int temp = matrix[i][j];
            matrix[i][j] = matrix[i][matrixColSize - j - 1];
            matrix[i][matrixColSize - j - 1] = temp;
        }
    }
}

void rotate(int** matrix, int matrixSize, int* matrixColSize) {
    transpose(matrix, matrixSize, *matrixColSize);
    reverse(matrix, matrixSize, *matrixColSize);
}

int main() {
    // Example matrix
    int matrixSize = 3;
```

```

int matrixColSize = 3;
int** matrix = (int**)malloc(matrixSize * sizeof(int*));
for (int i = 0; i < matrixSize; i++) {
    matrix[i] = (int*)malloc(matrixColSize * sizeof(int));
    for (int j = 0; j < matrixColSize; j++) {
        matrix[i][j] = i * matrixColSize + j + 1;
    }
}

// Print the original matrix
printf("Original Matrix:\n");
for (int i = 0; i < matrixSize; i++) {
    for (int j = 0; j < matrixColSize; j++) {
        printf("%d ", matrix[i][j]);
    }
    printf("\n");
}

// Rotate the matrix
rotate(matrix, matrixSize, &matrixColSize);

// Print the rotated matrix
printf("\nRotated Matrix:\n");
for (int i = 0; i < matrixSize; i++) {
    for (int j = 0; j < matrixColSize; j++) {
        printf("%d ", matrix[i][j]);
    }
    printf("\n");
}

// Free allocated memory
for (int i = 0; i < matrixSize; i++) {
    free(matrix[i]);
}
free(matrix);

return 0;
}

```

1.101 Gas Station

There are n gas stations along a circular route, where the amount of gas at the i^{th} station is $\text{gas}[i]$.

You have a car with an unlimited gas tank and it costs $\text{cost}[i]$ of gas to travel from the i^{th} station to its next ($i + 1)^{\text{th}}$ station. You begin the journey with an empty tank at one of the gas stations.

Given two integer arrays `gas` and `cost`, return *the starting gas station's index if you can travel around the circuit once in the clockwise direction, otherwise return -1*. If there exists a solution, it is **guaranteed** to be **unique**

Example 1:

Input: `gas = [1,2,3,4,5]`, `cost = [3,4,5,1,2]`

Output: 3

Explanation:

Start at station 3 (index 3) and fill up with 4 unit of gas. Your tank = $0 + 4 = 4$

Travel to station 4. Your tank = $4 - 1 + 5 = 8$

Travel to station 0. Your tank = $8 - 2 + 1 = 7$

Travel to station 1. Your tank = $7 - 3 + 2 = 6$

Travel to station 2. Your tank = $6 - 4 + 3 = 5$

Travel to station 3. The cost is 5. Your gas is just enough to travel back to station 3.

Therefore, return 3 as the starting index.

Example 2:

Input: `gas = [2,3,4]`, `cost = [3,4,3]`

Output: -1

Explanation:

You can't start at station 0 or 1, as there is not enough gas to travel to the next station.

Let's start at station 2 and fill up with 4 unit of gas. Your tank = $0 + 4 = 4$

Travel to station 0. Your tank = $4 - 3 + 2 = 3$

Travel to station 1. Your tank = $3 - 3 + 3 = 3$

You cannot travel back to station 2, as it requires 4 unit of gas but you only have 3.

Therefore, you can't travel around the circuit once no matter where you start.

C:

```
#include <stdio.h>

int canCompleteCircuit(int* gas, int gasSize, int* cost, int costSize) {
    int totalGas = 0;
    int totalCost = 0;
    int currentGas = 0;
    int startStation = 0;

    for (int i = 0; i < gasSize; ++i) {
        totalGas += gas[i];
        totalCost += cost[i];
        currentGas += gas[i] - cost[i];

        // If the current sum becomes negative, reset the starting station to the next
        // station
        if (currentGas < 0) {
            currentGas = 0;
            startStation = i + 1;
        }
    }

    if (totalGas <= totalCost) {
        return -1;
    } else {
        return startStation;
    }
}
```

```

        }
    }

    // If the total gas is less than the total cost, there is no solution
    if (totalGas < totalCost) {
        return -1;
    }

    return startStation;
}

int main() {
    // Example gas and cost arrays
    int gas[] = {1, 2, 3, 4, 5};
    int gasSize = sizeof(gas) / sizeof(gas[0]);
    int cost[] = {3, 4, 5, 1, 2};
    int costSize = sizeof(cost) / sizeof(cost[0]);

    // Calculate the starting station
    int startStation = canCompleteCircuit(gas, gasSize, cost, costSize);

    // Print the result
    printf("Starting station: %d\n", startStation);

    return 0;
}

```

Input: gas = [1,2,3,4,5], cost = [3,4,5,1,2]

Output: 3

Explanation:

Start at station 3 (index 3) and fill up with 4 unit of gas. Your tank = $0 + 4 = 4$

Travel to station 4. Your tank = $4 - 1 + 5 = 8$

Travel to station 0. Your tank = $8 - 2 + 1 = 7$

Travel to station 1. Your tank = $7 - 3 + 2 = 6$

Travel to station 2. Your tank = $6 - 4 + 3 = 5$

Travel to station 3. The cost is 5. Your gas is just enough to travel back to station 3.

Therefore, return 3 as the starting index.


1.102 Delete Node in BST

Given a root node reference of a BST and a key, delete the node with the given key in the BST.
Return the root node reference (possibly updated) of the BST.

Basically, the deletion can be divided into two stages:

1. Search for a node to remove.
2. If the node is found, delete the node.

Example 1:




Input: root = [5,3,6,2,4,null,7], key = 3

Output: [5,4,6,2,null,null,7]

Explanation: Given key to delete is 3. So we find the node with value 3 and delete it.

One valid answer is [5,4,6,2,null,null,7], shown in the above BST.

Please notice that another valid answer is [5,2,6,null,4,null,7] and it's also accepted.



Example 2:

Input: root = [5,3,6,2,4,null,7], key = 0

Output: [5,3,6,2,4,null,7]

Explanation: The tree does not contain a node with value = 0.

Example 3:

Input: root = [], key = 0

Output: []

Constraints:

C:

```
/*
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */

#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to find the minimum node in a BST
struct TreeNode* findMin(struct TreeNode* node) {
    while (node->left != NULL) {
        node = node->left;
    }
    return node;
}

// Function to delete a node with a given key from a BST
struct TreeNode* deleteNode(struct TreeNode* root, int key) {
    if (root == NULL) {
        return NULL;
    }

    if (key < root->val) {
        root->left = deleteNode(root->left, key);
    } else if (key > root->val) {
        root->right = deleteNode(root->right, key);
    } else {
        if (root->left == NULL) {
            struct TreeNode* temp = root->right;
            free(root);
            return temp;
        } else if (root->right == NULL) {
            struct TreeNode* temp = root->left;
            free(root);
            return temp;
        } else {
            struct TreeNode* temp = findMin(root->right);
            root->val = temp->val;
            root->right = deleteNode(root->right, temp->val);
        }
    }
}
```

```

        return temp;
    }

    struct TreeNode* temp = findMin(root->right);
    root->val = temp->val;
    root->right = deleteNode(root->right, temp->val);
}

return root;
}

// Function to create a new TreeNode
struct TreeNode* createNode(int val) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->val = val;
    newNode->left = newNode->right = NULL;
    return newNode;
}

// Function to print the inorder traversal of the tree
void inorderTraversal(struct TreeNode* root) {
    if (root != NULL) {
        inorderTraversal(root->left);
        printf("%d ", root->val);
        inorderTraversal(root->right);
    }
}

// Main function to test the deleteNode function
int main() {
    // Creating a sample BST
    struct TreeNode* root = createNode(5);
    root->left = createNode(3);
    root->right = createNode(6);
    root->left->left = createNode(2);
    root->left->right = createNode(4);
    root->right->right = createNode(7);

    printf("Original BST: ");
    inorderTraversal(root);
    printf("\n");

    // Deleting node with key 3
    root = deleteNode(root, 3);

    printf("BST after deleting node with key 3: ");
    inorderTraversal(root);
    printf("\n");
}

```

```

    // Freeing memory
    // You should implement a function to free the memory of the tree nodes
    // Here, we're just printing the tree after deletion to show the result

    return 0;
}

```

1.103 Word Search

Given an $m \times n$ grid of characters board and a string word, return true if word exists in the grid.

The word can be constructed from letters of sequentially adjacent cells, where adjacent cells are horizontally or vertically neighboring. The same letter cell may not be used more than once.

Example 1:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A","B","C","E"],["S","F","C","S"],["A","D","E","E"]], word = "ABCED"

Output: true

Example 2:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A","B","C","E"],["S","F","C","S"],["A","D","E","E"]], word = "SEE"

Output: true

Example 3:

A	B	C	E
S	F	C	S
A	D	E	E

Input: board = [["A","B","C","E"],["S","F","C","S"],["A","D","E","E"]], word = "ABCB"

Output: false

C:

```
bool backtrack(char** board, int row, int col, int boardSize, int* boardColSize, char* word, int index) {
    if (index == strlen(word)) {
        // All characters of the word are found
        return true;
    }

    if (row < 0 || col < 0 || row >= boardSize || col >= boardColSize[row] || board[row][col] != word[index]) {
        // Out of bounds or the current cell does not match the current character of the word
        return false;
    }
}
```

```

// Mark the current cell as visited
char original = board[row][col];
board[row][col] = '\0';

// Explore neighbors in all four directions
bool found = (backtrack(board, row - 1, col, boardSize, boardColSize, word, index +
1) ||
               backtrack(board, row + 1, col, boardSize, boardColSize, word, index +
1) ||
               backtrack(board, row, col - 1, boardSize, boardColSize, word, index +
1) ||
               backtrack(board, row, col + 1, boardSize, boardColSize, word, index +
1));
}

// Restore the original value of the current cell
board[row][col] = original;

return found;
}

bool exist(char** board, int boardSize, int* boardColSize, char* word) {
    for (int i = 0; i < boardSize; i++) {
        for (int j = 0; j < boardColSize[i]; j++) {
            if (backtrack(board, i, j, boardSize, boardColSize, word, 0)) {
                // If the word is found starting from (i, j)
                return true;
            }
        }
    }

    return false;
}

int main() {
    char* board[][] = {{ {"A", "B", "C", "E"}, {"S", "F", "C", "S"}, {"A", "D", "E", "E"} }};
    int boardSize = sizeof(board) / sizeof(board[0]);
    int boardColSize[] = {4, 4, 4};
    char* word = "ABCED";

    // Check if the word exists on the board
    bool result = exist((char**)board, boardSize, boardColSize, word);

    // Print the result
    if (result) {
        printf("The word '%s' exists on the board.\n", word);
    } else {
        printf("The word '%s' does not exist on the board.\n", word);
    }
}

```

```
        return 0;  
    }
```

1.104 Integer To Roman

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two one's added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given an integer, convert it to a roman numeral.

Example 1:

Input: num = 3

Output: "III"

Explanation: 3 is represented as 3 ones.

Example 2:

Input: num = 58

Output: "LVIII"

Explanation: L = 50, V = 5, III = 3.

Example 3:

Input: num = 1994

Output: "MCMXCIV"

Explanation: M = 1000, CM = 900, XC = 90 and IV = 4.

C:

```
#include <stdio.h>
#include <stdbool.h>
#include <string.h>

bool backtrack(char** board, int row, int col, int boardSize, int* boardColSize, char* word, int index) {
    if (index == strlen(word)) {
        // All characters of the word are found
        return true;
    }

    if (row < 0 || col < 0 || row >= boardSize || col >= boardColSize[row] || board[row][col] != word[index]) {
        // Out of bounds or the current cell does not match the current character of the word
        return false;
    }

    // Mark the current cell as visited
    char original = board[row][col];
    board[row][col] = '\0'; // <-- This line causes the segmentation fault

    // Explore neighbors in all four directions
    bool found = (backtrack(board, row - 1, col, boardSize, boardColSize, word, index + 1) ||
                  backtrack(board, row + 1, col, boardSize, boardColSize, word, index + 1) ||
                  backtrack(board, row, col - 1, boardSize, boardColSize, word, index + 1) ||
                  backtrack(board, row, col + 1, boardSize, boardColSize, word, index + 1));

    // Restore the original value of the current cell
    board[row][col] = original;

    return found;
}

bool exist(char** board, int boardSize, int* boardColSize, char* word) {
    for (int i = 0; i < boardSize; i++) {
        for (int j = 0; j < boardColSize[i]; j++) {
            if (backtrack(board, i, j, boardSize, boardColSize, word, 0)) {
                // If the word is found starting from (i, j)
                return true;
            }
        }
    }
}
```

```

    }

    return false;
}

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* intToRoman(int num) {
    const char* thousands[] = {"", "M", "MM", "MMM"};
    const char* hundreds[] = {"", "C", "CC", "CCC", "CD", "D", "DC", "DCC", "DCCC",
    "CM"};
    const char* tens[] = {"", "X", "XX", "XXX", "XL", "L", "LX", "LXX", "LXXX", "XC"};
    const char* ones[] = {"", "I", "II", "III", "IV", "V", "VI", "VII", "VIII", "IX"};

    char *result = (char *)malloc(sizeof(char) * 16);
    result[0] = '\0';

    strcat(result, thousands[(num / 1000)]);
    strcat(result, hundreds[(num % 1000) / 100]);
    strcat(result, tens[(num % 100) / 10]);
    strcat(result, ones[(num % 10)]);

    return result;
}

int main() {
    int num = 3549;
    char *roman = intToRoman(num);
    printf("Roman numeral representation of %d is: %s\n", num, roman);
    free(roman); // Don't forget to free the allocated memory
    return 0;
}

```

1.105 Merge String Alternately

You are given two strings word1 and word2. Merge the strings by adding letters in alternating order, starting with word1. If a string is longer than the other, append the additional letters onto the end of the merged string.

Return *the merged string.*

Example 1:

Input: word1 = "abc", word2 = "pqr"
Output: "apbqcr"

Explanation: The merged string will be merged as so:

word1: a b c

word2: p q r

merged: a p b q c r

Example 2:

Input: word1 = "ab", word2 = "pqrs"

Output: "apbqrs"

Explanation: Notice that as word2 is longer, "rs" is appended to the end.

word1: a b

word2: p q r s

merged: a p b q r s

Example 3:

Input: word1 = "abcd", word2 = "pq"

Output: "apbqcd"

Explanation: Notice that as word1 is longer, "cd" is appended to the end.

word1: a b c d

word2: p q

merged: a p b q c d

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* mergeAlternately(char* word1, char* word2) {
    int i = 0;
    int j = 0;
    int k = 0;
    int len1 = strlen(word1);
    int len2 = strlen(word2);
    int len = len1 + len2;
    char* result = (char*)malloc(sizeof(char) * (len + 1));
    memset(result, 0, sizeof(char) * (len + 1));

    while (i < len1 || j < len2) {
        if (i < len1) result[k++] = word1[i++];
        if (j < len2) result[k++] = word2[j++];
    }

    return result;
}
```

```


int main() {
    char* word1 = "abc";
    char* word2 = "defgh";
    char* merged = mergeAlternately(word1, word2);
    printf("Merged string: %s\n", merged);
    free(merged); // Don't forget to free the allocated memory
    return 0;
}

```

1.106 Reverse Linked List II (In between from one position to another)

Given the head of a singly linked list and two integers left and right where $left \leq right$, reverse the nodes of the list from position left to position right, and return the reversed list.

Example 1:



Input: head = [1,2,3,4,5], left = 2, right = 4

Output: [1,4,3,2,5]

Example 2:

Input: head = [5], left = 1, right = 1

Output: [5]

C:

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };

```

```

*/
#include <stdio.h>
#include <stdlib.h>

struct ListNode {
    int val;
    struct ListNode *next;
};

struct ListNode* reverseBetween(struct ListNode* head, int m, int n) {
    if (head == NULL) {
        return NULL;
    }

    struct ListNode* dummy = (struct ListNode*)malloc(sizeof(struct ListNode));
    dummy->next = head;
    struct ListNode* pre = dummy;

    // Move pre to the node before the sublist to be reversed
    for (int i = 0; i < m - 1; i++) {
        pre = pre->next;
    }

    struct ListNode* curr = pre->next; // Start of the sublist to be reversed
    struct ListNode* next = curr->next; // Node that will be reversed

    // Reverse the sublist from m to n
    for (int i = 0; i < n - m; i++) {
        curr->next = next->next;
        next->next = pre->next;
        pre->next = next;
        next = curr->next;
    }

    // The sublist has been reversed, and we return the modified list
    return dummy->next;
}

// Function to create a new node with a given value
struct ListNode* createNode(int val) {
    struct ListNode* newNode = (struct ListNode*)malloc(sizeof(struct ListNode));
    newNode->val = val;
    newNode->next = NULL;
    return newNode;
}

// Function to print the linked list
void printList(struct ListNode* head) {
    while (head != NULL) {

```

```

        printf("%d ", head->val);
        head = head->next;
    }
    printf("\n");
}

int main() {
// Create a sample linked list
struct ListNode* head = createNode(1);
head->next = createNode(2);
head->next->next = createNode(3);
head->next->next->next = createNode(4);
head->next->next->next->next = createNode(5);

printf("Original list: ");
printList(head);

int m = 2, n = 4;
struct ListNode* reversed = reverseBetween(head, m, n);

printf("Reversed list from %d to %d: ", m, n);
printList(reversed);

// Free the memory allocated for the linked lists
while (head != NULL) {
    struct ListNode* temp = head;
    head = head->next;
    free(temp);
}

return 0;
}

```

1.107 Implement Trie – Prefix Tree

A **trie** (pronounced as "try") or **prefix tree** is a tree data structure used to efficiently store and retrieve keys in a dataset of strings. There are various applications of this data structure, such as autocomplete and spellchecker.

Implement the Trie class:

- `Trie()` Initializes the trie object.
- `void insert(String word)` Inserts the string word into the trie.
- `boolean search(String word)` Returns true if the string word is in the trie (i.e., was inserted before), and false otherwise.
- `boolean startsWith(String prefix)` Returns true if there is a previously inserted string word that has the prefix prefix, and false otherwise.

Example 1:**Input**

```
["Trie", "insert", "search", "search", "startsWith", "insert", "search"]  
[], ["apple"], ["apple"], ["app"], ["app"], ["app"], ["app"]]
```

Output

```
[null, null, true, false, true, null, true]
```

Explanation

```
Trie trie = new Trie();  
trie.insert("apple");  
trie.search("apple"); // return True  
trie.search("app"); // return False  
trie.startsWith("app"); // return True  
trie.insert("app");  
trie.search("app"); // return True
```

C:

```
// Define TrieNode structure  
typedef struct TrieNode {  
    struct TrieNode* children[26];  
    bool isEndOfWord;  
} TrieNode;  
  
// Define Trie structure  
typedef struct {  
    TrieNode* root;  
} Trie;  
  
// Function to create a new TrieNode  
TrieNode* createNode() {  
    TrieNode* newNode = (TrieNode*)malloc(sizeof(TrieNode));  
    for (int i = 0; i < 26; i++) {  
        newNode->children[i] = NULL;  
    }  
    newNode->isEndOfWord = false;  
    return newNode;  
}  
  
// Initialize the Trie  
Trie* trieCreate() {  
    Trie* trie = (Trie*)malloc(sizeof(Trie));  
    trie->root = createNode();
```

```

        return trie;
    }

    // Insert a word into the Trie
    void trieInsert(Trie* obj, char* word) {
        TrieNode* node = obj->root;
        while (*word) {
            int index = *word - 'a';
            if (node->children[index] == NULL) {
                node->children[index] = createNode();
            }
            node = node->children[index];
            word++;
        }
        node->isEndOfWord = true;
    }

    // Search for a word in the Trie
    bool trieSearch(Trie* obj, char* word) {
        TrieNode* node = obj->root;
        while (*word) {
            int index = *word - 'a';
            if (node->children[index] == NULL) {
                return false;
            }
            node = node->children[index];
            word++;
        }
        return node->isEndOfWord;
    }

    // Check if a prefix exists in the Trie
    bool trieStartsWith(Trie* obj, char* prefix) {
        TrieNode* node = obj->root;
        while (*prefix) {
            int index = *prefix - 'a';
            if (node->children[index] == NULL) {
                return false;
            }
            node = node->children[index];
            prefix++;
        }
        return true;
    }

    // Free the Trie memory
    void trieFree(Trie* obj) {
        // Use recursive helper function to free Trie nodes
        void freeNode(TrieNode* node) {

```

```

    if (node == NULL) {
        return;
    }
    for (int i = 0; i < 26; i++) {
        freeNode(node->children[i]);
    }
    free(node);
}

freeNode(obj->root);
free(obj);
}

/**
 * Your Trie struct will be instantiated and called as such:
 * Trie* obj = trieCreate();
 * trieInsert(obj, word);

 * bool param_2 = trieSearch(obj, word);

 * bool param_3 = trieStartsWith(obj, prefix);

 * trieFree(obj);
 */

```

1.108 Odd Even Linked List



Given the head of a singly linked list, group all the nodes with odd indices together followed by the nodes with even indices, and return *the reordered list*.

The **first** node is considered **odd**, and the **second** node is **even**, and so on.

Note that the relative order inside both the even and odd groups should remain as it was in the input.



You must solve the problem in O(1) extra space complexity and O(n) time complexity.

Example 1:



Input: head = [1,2,3,4,5]
Output: [1,3,5,2,4]

Example 2:



Input: head = [2,1,3,5,6,4,7]
Output: [2,3,6,7,1,5,4]

C:

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */
#include <stdio.h>
#include <stdlib.h>

struct ListNode {
    int val;
    struct ListNode *next;
};

struct ListNode* oddEvenList(struct ListNode* head) {
    if (head == NULL || head->next == NULL) {
        return head; // No or only one node, no reordering needed
    }
    struct ListNode* odd = head;
    struct ListNode* even = head->next;
    struct ListNode* even_head = even;
    while (odd->next != NULL && even->next != NULL) {
        odd->next = even->next;
        odd = odd->next;
        even->next = odd->next;
        even = even->next;
    }
    odd->next = even_head;
    return head;
}
```

```

}

struct ListNode* oddHead = head; // Head of the odd indices list
struct ListNode* evenHead = head->next; // Head of the even indices list
struct ListNode* odd = oddHead; // Pointer for iterating over odd indices
struct ListNode* even = evenHead; // Pointer for iterating over even indices

while (even != NULL && even->next != NULL) {
    // Connect odd indices
    odd->next = even->next;
    odd = odd->next;

    // Connect even indices
    even->next = odd->next;
    even = even->next;
}

// Combine the odd and even lists
odd->next = evenHead;

return oddHead;
}

// Function to create a new node with a given value
struct ListNode* createNode(int val) {
    struct ListNode* newNode = (struct ListNode*)malloc(sizeof(struct ListNode));
    newNode->val = val;
    newNode->next = NULL;
    return newNode;
}

// Function to print the linked list
void printList(struct ListNode* head) {
    while (head != NULL) {
        printf("%d ", head->val);
        head = head->next;
    }
    printf("\n");
}

int main() {
    // Create a sample linked list
    struct ListNode* head = createNode(1);
    head->next = createNode(2);
    head->next->next = createNode(3);
    head->next->next->next = createNode(4);
    head->next->next->next->next = createNode(5);

    printf("Original list: ");
}

```

```

printList(head);

// Reorder the list based on odd and even indices
struct ListNode* reordered = oddEvenList(head);

printf("Reordered list: ");
printList(reordered);

// Free the memory allocated for the linked lists
while (head != NULL) {
    struct ListNode* temp = head;
    head = head->next;
    free(temp);
}

return 0;
}

```

1.109 Best Time To Buy And Sell Stock (Single day to buy and different day to sell once)

You are given an array prices where prices[i] is the price of a given stock on the i^{th} day.

You want to maximize your profit by choosing a **single day** to buy one stock and choosing a **different day in the future** to sell that stock.

Return *the maximum profit you can achieve from this transaction*. If you cannot achieve any profit, return 0.

Example 1:

Input: prices = [7,1,5,3,6,4]

Output: 5

Explanation: Buy on day 2 (price = 1) and sell on day 5 (price = 6), profit = 6-1 = 5.

Note that buying on day 2 and selling on day 1 is not allowed because you must buy before you sell.

Example 2:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: In this case, no transactions are done and the max profit = 0

C:

```

#include <stdio.h>
#include <limits.h>

int maxProfit(int* prices, int pricesSize) {

```

```

if (pricesSize <= 1) {
    return 0; // No transactions can be done with less than 2 prices
}

int minPrice = INT_MAX; // Initialize minimum price to maximum possible value
int maxProfit = 0;

for (int i = 0; i < pricesSize; i++) {
    // Update the minimum price if the current price is smaller
    if (prices[i] < minPrice) {
        minPrice = prices[i];
    }
    // Update the maximum profit if selling at the current price yields a higher
    profit
    else if (prices[i] - minPrice > maxProfit) {
        maxProfit = prices[i] - minPrice;
    }
}

return maxProfit;
}

int main() {
    int prices[] = {7, 1, 5, 3, 6, 4};
    int pricesSize = sizeof(prices) / sizeof(prices[0]);

    int profit = maxProfit(prices, pricesSize);

    printf("Maximum profit: %d\n", profit);

    return 0;
}

```

1.110 Longest Consecutive Sequence

Given an unsorted array of integers nums, return *the length of the longest consecutive elements sequence.*

You must write an algorithm that runs in O(n) time.

Example 1:

Input: nums = [100,4,200,1,3,2]

Output: 4

Explanation: The longest consecutive elements sequence is [1, 2, 3, 4]. Therefore its length is 4.

Example 2:

Input: nums = [0,3,7,2,5,8,4,6,0,1]

Output: 9

C:

```
#include <stdio.h>
#include <stdlib.h>

// HashSet structure
typedef struct {
    int* array;
    int size;
} HashSet;

// Function to initialize a HashSet
HashSet* initHashSet(int size) {
    HashSet* set = (HashSet*)malloc(sizeof(HashSet));
    set->array = (int*)calloc(size, sizeof(int));
    set->size = size;
    return set;
}

// Function to insert an element into the HashSet
void insertHashSet(HashSet* set, int value) {
    set->array[value] = 1;
}

// Function to check if an element exists in the HashSet
int containsHashSet(HashSet* set, int value) {
    return set->array[value];
}

// Function to calculate the length of the longest consecutive sequence
int longestConsecutive(int* nums, int numsSize) {
    if (numsSize <= 1) {
        return numsSize; // No consecutive sequence with one or zero elements
    }

    // Find min and max values in the array
    int min = nums[0], max = nums[0];
    for (int i = 1; i < numsSize; i++) {
        if (nums[i] < min) {
            min = nums[i];
        } else if (nums[i] > max) {
            max = nums[i];
        }
    }

    // Initialize the HashSet
```

```

HashSet* set = initHashSet(max - min + 1);

// Insert all elements into the HashSet
for (int i = 0; i < numsSize; i++) {
    insertHashSet(set, nums[i] - min);
}

// Calculate the length of the longest consecutive sequence
int longestStreak = 0, currentStreak = 0;
for (int i = 0; i <= max - min; i++) {
    if (containsHashSet(set, i)) {
        currentStreak++;
    } else {
        longestStreak = currentStreak > longestStreak ? currentStreak :
longestStreak;
        currentStreak = 0;
    }
}

// Free memory allocated for the HashSet
free(set->array);
free(set);

return longestStreak > currentStreak ? longestStreak : currentStreak;
}

int main() {
    int nums[] = {100, 4, 200, 1, 3, 2};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int longest = longestConsecutive(nums, numsSize);

    printf("Length of the longest consecutive sequence: %d\n", longest);


    return 0;
}

```

1.111 Spiral Matrix

Given an $m \times n$ matrix, return *all elements of the* matrix *in spiral order*.


Example 1:



Input: matrix = [[1,2,3],[4,5,6],[7,8,9]]

Output: [1,2,3,6,9,8,7,4,5]

Example 2:



Input: matrix = [[1,2,3,4],[5,6,7,8],[9,10,11,12]]

Output: [1,2,3,4,8,12,11,10,9,5,6,7]

C:

```
/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
#include <stdio.h>
#include <stdlib.h>

int* spiralOrder(int** matrix, int matrixSize, int* matrixColSize, int* returnSize) {
    if (matrixSize == 0 || matrixColSize[0] == 0) {
        *returnSize = 0;
    }
    else {
        *returnSize = matrixSize * matrixColSize[0];
        int* result = (int*)malloc(*returnSize * sizeof(int));
        int rowStart = 0, rowEnd = matrixSize - 1;
        int colStart = 0, colEnd = matrixColSize[0] - 1;
        int direction = 0; // 0: right, 1: down, 2: left, 3: up
        int index = 0;

        while (index < *returnSize) {
            if (direction == 0) {
                for (int i = colStart; i <= colEnd; i++) {
                    result[index] = matrix[rowStart][i];
                    index++;
                }
                rowStart++;
            }
            else if (direction == 1) {
                for (int i = rowStart; i <= rowEnd; i++) {
                    result[index] = matrix[i][colEnd];
                    index++;
                }
                colEnd--;
            }
            else if (direction == 2) {
                for (int i = colEnd; i >= colStart; i--) {
                    result[index] = matrix[rowEnd][i];
                    index++;
                }
                rowEnd--;
            }
            else if (direction == 3) {
                for (int i = rowEnd; i >= rowStart; i--) {
                    result[index] = matrix[i][colStart];
                    index++;
                }
                colStart++;
            }
            direction = (direction + 1) % 4;
        }
    }
    return result;
}
```

```

        return NULL;
    }

    int totalElements = matrixSize * matrixColSize[0];
    int* result = (int*)malloc(sizeof(int) * totalElements);

*returnSize = totalElements;

    int top = 0, bottom = matrixSize - 1;
    int left = 0, right = matrixColSize[0] - 1;
    int index = 0;

    while (top <= bottom && left <= right) {
        // Traverse top row
        for (int i = left; i <= right; i++) {
            result[index++] = matrix[top][i];
        }
        top++;

        // Traverse right column
        for (int i = top; i <= bottom; i++) {
            result[index++] = matrix[i][right];
        }
        right--;

        // Check if there's a bottom row to traverse
        if (top <= bottom) {
            // Traverse bottom row
            for (int i = right; i >= left; i--) {
                result[index++] = matrix[bottom][i];
            }
            bottom--;
        }
    }

    // Check if there's a left column to traverse
    if (left <= right) {
        // Traverse left column
        for (int i = bottom; i >= top; i--) {
            result[index++] = matrix[i][left];
        }
        left++;
    }
}

return result;
}

int main() {
    int matrixSize = 3;

```

```

int matrixColSize[] = {4, 4, 4};
int** matrix = (int**)malloc(matrixSize * sizeof(int *));
for (int i = 0; i < matrixSize; i++) {
    matrix[i] = (int*)malloc(matrixColSize[i] * sizeof(int));
    for (int j = 0; j < matrixColSize[i]; j++) {
        matrix[i][j] = i * matrixColSize[i] + j + 1;
    }
}

int returnSize;
int* result = spiralOrder(matrix, matrixSize, matrixColSize, &returnSize);

printf("Spiral order: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", result[i]);
}
printf("\n");

// Free dynamically allocated memory
for (int i = 0; i < matrixSize; i++) {
    free(matrix[i]);
}
free(matrix);
free(result);

return 0;
}

```

1.112 Populating Next Right Pointer In Each Node

You are given a **perfect binary tree** where all leaves are on the same level, and every parent has two children. The binary tree has the following definition:

```

struct Node {
    int val;
    Node *left;
    Node *right;
    Node *next;
}

```

Populate each next pointer to point to its next right node. If there is no next right node, the next pointer should be set to NULL.

Initially, all next pointers are set to NULL.

Example 1:




Figure A




Figure B

Input: root = [1,2,3,4,5,6,7]

Output: [1,#,2,3,#,4,5,6,7,#]

Explanation: Given the above perfect binary tree (Figure A), your function should populate each next pointer to point to its next right node, just like in Figure B. The serialized output is in level order as connected by the next pointers, with '#' signifying the end of each level.

Example 2:

Input: root = []

Output: []

C:

```

/*
 * Definition for a Node.
 * struct Node {
 *     int val;
 *     struct Node *left;
 *     struct Node *right;
 *     struct Node *next;
 * };
 */

#include <stdio.h>
#include <stdlib.h>

// Definition for a Node.
struct Node {
    int val;
    struct Node *left;
    struct Node *right;
    struct Node *next;
};

struct Node* connect(struct Node* root) {
    if (root == NULL) {
        return NULL;
    }

    struct Node* curr = root;
    while (curr != NULL) {
        struct Node* temp = curr;
        curr = curr->left;
        while (curr != NULL) {
            curr->next = temp->right;
            temp = curr;
            curr = curr->right;
        }
        curr = temp->next;
    }
}

int main() {
    struct Node* root = NULL;
    // Create a sample tree
    //      1
    //     / \
    //    2   3
    //   / \ / \
    //  4  5 6  7
    // 4-->5
    // 5-->6
    // 6-->7
    // 7-->NULL
    // 1-->NULL
    // 3-->NULL
    // Call the function
    struct Node* result = connect(root);
    // Print the result
    // ...
}

```

```

    struct Node* leftmost = root; // Start from the leftmost node in the current level

    while (leftmost->left != NULL) {
        struct Node* current = leftmost;

        // Traverse the current level and connect nodes in the next level
        while (current != NULL) {
            current->left->next = current->right;

            if (current->next != NULL) {
                current->right->next = current->next->left;
            }

            current = current->next; // Move to the next node in the current level
        }

        leftmost = leftmost->left; // Move to the leftmost node in the next level
    }

    return root;
}

// Helper function to create a new node
struct Node* createNode(int val) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->val = val;
    newNode->left = NULL;
    newNode->right = NULL;
    newNode->next = NULL;
    return newNode;
}

// Function to print the next pointers of each node in the tree
void printNextPointers(struct Node* root) {
    while (root != NULL) {
        struct Node* current = root;
        while (current != NULL) {
            printf("%d -> ", current->val);
            current = current->next;
        }
        printf("NULL\n");
        root = root->left;
    }
}

int main() {
    // Create a sample tree
    struct Node* root = createNode(1);

```

```

root->left = createNode(2);
root->right = createNode(3);
root->left->left = createNode(4);
root->left->right = createNode(5);
root->right->left = createNode(6);
root->right->right = createNode(7);

// Connect the nodes
struct Node* connectedRoot = connect(root);

// Print the next pointers of each node in the tree
printf("Next pointers of each node in the tree:\n");
printNextPointers(connectedRoot);

// Free dynamically allocated memory
// Note: This part is omitted for brevity

return 0;
}

```

1.113 String Compression

Given an array of characters chars, compress it using the following algorithm:

Begin with an empty string s. For each group of **consecutive repeating characters** in chars:

- If the group's length is 1, append the character to s.
- Otherwise, append the character followed by the group's length.

The compressed string s **should not be returned separately**, but instead, be stored **in the input character array chars**. Note that group lengths that are 10 or longer will be split into multiple characters in chars.

After you are done **modifying the input array**, return ***the new length of the array***.

You must write an algorithm that uses only constant extra space.

Example 1:

Input: chars = ["a", "a", "b", "b", "c", "c", "c"]

Output: Return 6, and the first 6 characters of the input array should be: ["a", "2", "b", "2", "c", "3"]

Explanation: The groups are "aa", "bb", and "ccc". This compresses to "a2b2c3".

Example 2:

Input: chars = ["a"]

Output: Return 1, and the first character of the input array should be: ["a"]

Explanation: The only group is "a", which remains uncompressed since it's a single character.

Example 3:

Input: chars = ["a", "b", "b"]

Output: Return 4, and the first 4 characters of the input array should be: ["a", "b", "1", "2"].

Explanation: The groups are "a" and "bbbbbbbbbb". This compresses to "ab12".

C:

```
#include <stdio.h>
#include <stdlib.h>

int compress(char* chars, int charsSize) {
    if (charsSize <= 1) {
        return charsSize;
    }

    int writeIndex = 0, readIndex = 0;

    while (readIndex < charsSize) {
        char currentChar = chars[readIndex];
        int count = 0;

        while (readIndex < charsSize && chars[readIndex] == currentChar) {
            readIndex++;
            count++;
        }

        if (count == 1) {
            chars[writeIndex++] = currentChar;
        } else {
            chars[writeIndex++] = currentChar;

            // Process the count and update the array
            int tempCount = count;
            while (tempCount > 0) {
                chars[writeIndex++] = '0' + tempCount % 10;
                tempCount /= 10;
            }
        }

        // Reverse the count characters in the array
        int start = writeIndex - count + 1;
        int end = writeIndex - 1;
        while (start < end) {
            char temp = chars[start];
```

```

        chars[start] = chars[end];
        chars[end] = temp;
        start++;
        end--;
    }
}
}

return writeIndex;
}

int main() {
    char chars[] = {'a', 'a', 'b', 'b', 'c', 'c', 'c'};
    int charsSize = sizeof(chars) / sizeof(chars[0]);

    printf("Original array: ");
    for (int i = 0; i < charsSize; i++) {
        printf("%c ", chars[i]);
    }
    printf("\n");

    int compressedSize = compress(chars, charsSize);

    printf("Compressed array: ");
    for (int i = 0; i < compressedSize; i++) {
        printf("%c ", chars[i]);
    }
    printf("\n");


    return 0;
}

```

1.114 Construct Binary Tree From Inorder and post Order Traversal

Given two integer arrays inorder and postorder where inorder is the inorder traversal of a binary tree and postorder is the postorder traversal of the same tree, construct and return *the binary tree*.

Example 1:



Input: inorder = [9,3,15,20,7], postorder = [9,15,7,20,3]

Output: [3,9,20,null,null,15,7]

Example 2:

Input: inorder = [-1], postorder = [-1]

Output: [-1]

Constraints:

- $1 \leq \text{inorder.length} \leq 3000$
- $\text{postorder.length} == \text{inorder.length}$
- $-3000 \leq \text{inorder}[i], \text{postorder}[i] \leq 3000$
- inorder and postorder consist of **unique** values.
- Each value of postorder also appears in inorder.
- inorder is **guaranteed** to be the inorder traversal of the tree.
- postorder is **guaranteed** to be the postorder traversal of the tree.

C:

```

#include <stdio.h>
#include <stdlib.h>

// TreeNode structure
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};
  
```

```

// Function to create a new TreeNode
struct TreeNode* createNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

// Helper function to construct the binary tree from inorder and postorder traversals
struct TreeNode* helper(int* inorder, int in_left, int in_right, int* post_idx, int*
postorder) {
    // If there are no elements to construct subtrees
    if (in_left > in_right)
        return NULL;

    // Pick up post_idx element as a root
    int root_val = postorder[(*post_idx)];
    struct TreeNode* root = createNode(root_val);

    // Root splits inorder list into left and right subtrees
    int index = 0;
    for (int i = in_left; i <= in_right; i++) {
        if (inorder[i] == root_val) {
            index = i;
            break;
        }
    }

    // Recursion
    (*post_idx]--;
    // Build the right subtree
    root->right = helper(inorder, index + 1, in_right, post_idx, postorder);
    // Build the left subtree
    root->left = helper(inorder, in_left, index - 1, post_idx, postorder);
    return root;
}

// Function to construct the binary tree from inorder and postorder traversals
struct TreeNode* buildTree(int* inorder, int inorderSize, int* postorder, int
postorderSize) {
    int post_idx = postorderSize - 1;
    return helper(inorder, 0, inorderSize - 1, &post_idx, postorder);
}

// Function to perform inorder traversal of the binary tree
void inorderTraversal(struct TreeNode* root) {
    if (root != NULL) {
        inorderTraversal(root->left);

```

```

        printf("%d ", root->val);
        inorderTraversal(root->right);
    }
}

int main() {
    // Example inorder and postorder traversals
    int inorder[] = {9, 3, 15, 20, 7};
    int inorderSize = sizeof(inorder) / sizeof(inorder[0]);
    int postorder[] = {9, 15, 7, 20, 3};
    int postorderSize = sizeof(postorder) / sizeof(postorder[0]);

    // Construct the binary tree
    struct TreeNode* root = buildTree(inorder, inorderSize, postorder, postorderSize);

    // Perform inorder traversal to verify the constructed tree
    printf("Inorder traversal of the constructed tree: ");
    inorderTraversal(root);
    printf("\n");

    // Free allocated memory for the tree nodes (not included here for brevity)

    return 0;
}

```

1.115 Valid Sudoku

Determine if a 9×9 Sudoku board is valid. Only the filled cells need to be validated according to the following rules:

1. Each row must contain the digits 1-9 without repetition.
2. Each column must contain the digits 1-9 without repetition.
3. Each of the nine 3×3 sub-boxes of the grid must contain the digits 1-9 without repetition.

Note:

- A Sudoku board (partially filled) could be valid but is not necessarily solvable.
- Only the filled cells need to be validated according to the mentioned rules.

Example 1:

5	3		7					
6			1	9	5			
	9	8				6		
8			6					3
4		8		3				1
7			2				6	
	6				2	8		
		4	1	9				5
			8			7	9	

Input: board =

```
[["5","3","","","","7","","","","",""]
 ,["6","","","","1","9","5","","","",""]
 ,[".","9","8","","","","","6","."]
 ,["8","","","","6","","","","3"]
 ,["4","","","8",".","3","","","1"]
 ,["7","","","","2","","","","6"]
 ,[".","6","","","","2","8","."]
 ,["","","","4","1","9","","","5"]
 ,["","","","","8","","","","7","9"]]
```

Output: true

Example 2:

Input: board =

```
[["8","3","","","","7","","","","",""]
 ,["6","","","","1","9","5","","","",""]
 ,[".","9","8","","","","","6","."]
 ,["8","","","","6","","","","3"]
 ,["4","","","8",".","3","","","1"]
 ,["7","","","","2","","","","6"]
 ,[".","6","","","","2","8","."]
 ,["","","","4","1","9","","","5"]
 ,["","","","","8","","","","7","9"]]
```

Output: false

Explanation: Same as Example 1, except with the **5** in the top left corner being modified to **8**. Since there are two 8's in the top left 3x3 sub-box, it is invalid.

C:

```
#include <stdbool.h>
#include <stdio.h>

bool isValidSudoku(char** board, int boardSize, int* boardColSize) {
    // Arrays to check for duplicate digits in rows, columns, and sub-boxes
    bool row[9][9] = {false};
```

```

bool col[9][9] = {false};
bool box[9][9] = {false};

for (int i = 0; i < boardSize; i++) {
    for (int j = 0; j < *boardColSize; j++) {
        if (board[i][j] != '.') {
            int digit = board[i][j] - '1';

            // Check for duplicate in the same row
            if (row[i][digit]) {
                return false;
            }
            row[i][digit] = true;

            // Check for duplicate in the same column
            if (col[j][digit]) {
                return false;
            }
            col[j][digit] = true;

            // Check for duplicate in the same 3x3 sub-box
            int boxIndex = (i / 3) * 3 + j / 3;
            if (box[boxIndex][digit]) {
                return false;
            }
            box[boxIndex][digit] = true;
        }
    }
}

return true;
}

int main() {
    char* board[] = {
        "53..7....",
        "6..195....",
        ".98.....6.",
        "8....6....3",
        "4...8.3..1",
        "7....2....6",
        ".6.....28..",
        "...419..5",
        "....8....79"
    };
    int boardSize = sizeof(board) / sizeof(board[0]);
    int boardColSize[] = {9, 9, 9, 9, 9, 9, 9, 9, 9};

    bool valid = isValidSudoku(board, boardSize, boardColSize);
}

```

```

    if (valid) {
        printf("The Sudoku board is valid.\n");
    } else {
        printf("The Sudoku board is not valid.\n");
    }

    return 0;
}

Time/Space Complexity:O(n2)/O(n2)
#include <stdbool.h>

bool isValidSudoku(char** board, int boardSize, int* boardColSize) {
    int N = 9;

    // Use a binary number to record previous occurrence
    int rows[N];
    int cols[N];
    int boxes[N];

    for (int r = 0; r < N; r++) {
        for (int c = 0; c < N; c++) {
            // Check if the position is filled with a number
            if (board[r][c] == '.') {
                continue;
            }
            int val = board[r][c] - '0';
            int pos = 1 << (val - 1);

            // Check the row
            if ((rows[r] & pos) > 0) {
                return false;
            }
            rows[r] |= pos;

            // Check the column
            if ((cols[c] & pos) > 0) {
                return false;
            }
            cols[c] |= pos;

            // Check the box
            int idx = (r / 3) * 3 + c / 3;
            if ((boxes[idx] & pos) > 0) {
                return false;
            }
            boxes[idx] |= pos;
        }
    }
}

```

```

        return true;
    }

int main() {
    // Example usage
    char* board[9] = {"53..7....",
                      "6..195....",
                      ".98....6..",
                      "8...6...3",
                      "4..8.3..1",
                      "7....2...6",
                      ".6.....28.",
                      "...419..5",
                      "....8..79"};
    int boardSize = 9;
    int boardColSize[9] = {9, 9, 9, 9, 9, 9, 9, 9, 9};

    bool result = isValidSudoku(board, boardSize, boardColSize);
    if (result) {
        printf("Valid Sudoku board\n");
    } else {
        printf("Invalid Sudoku board\n");
    }

    return 0;
}

```


Time/Space Complexity : O(n²)/O(n)

1.116 Path Sum

Given the root of a binary tree and an integer targetSum, return true if the tree has a **root-to-leaf** path such that adding up all the values along the path equals targetSum.

A **leaf** is a node with no children.

Example 1:




Input: root = [5,4,8,11,null,13,4,7,2,null,null,null,1], targetSum = 22

Output: true

Explanation: The root-to-leaf path with the target sum is shown.

Example 2:



Input: root = [1,2,3], targetSum = 5

Output: false

Explanation: There two root-to-leaf paths in the tree:

(1 --> 2): The sum is 3.

(1 --> 3): The sum is 4.

There is no root-to-leaf path with sum = 5.

Example 3:

Input: root = [], targetSum = 0

Output: false

Explanation: Since the tree is empty, there are no root-to-leaf paths.

C:

```
/*
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

// TreeNode structure
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to create a new TreeNode
struct TreeNode* createNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

// Function to check if a binary tree has a path sum equal to the target sum
bool hasPathSum(struct TreeNode* root, int targetSum) {
    // Base case: If the current node is NULL, return false.
    if (root == NULL) {
        return false;
    }

    // Subtract the value of the current node from the target sum.
    targetSum -= root->val;

    // If the current node is a leaf node and the remaining sum is 0, return true.
    if (root->left == NULL && root->right == NULL) {
        return targetSum == 0;
    }

    // Recursively check the left and right subtrees.
    bool leftResult = hasPathSum(root->left, targetSum);
```

```

        bool rightResult = hasPathSum(root->right, targetSum);

        // Return true if either the left or right subtree has a path sum equal to the
        // target sum.
        return leftResult || rightResult;
    }

int main() {
    // Construct a sample binary tree
    struct TreeNode* root = createNode(5);
    root->left = createNode(4);
    root->right = createNode(8);
    root->left->left = createNode(11);
    root->left->left->left = createNode(7);
    root->left->left->right = createNode(2);
    root->right->left = createNode(13);
    root->right->right = createNode(4);
    root->right->right->right = createNode(1);

    // Target sum to search for
    int targetSum = 22;

    // Check if the binary tree has a path sum equal to the target sum
    bool result = hasPathSum(root, targetSum);

    // Print the result
    if (result) {
        printf("The binary tree has a path sum equal to %d.\n", targetSum);
    } else {
        printf("The binary tree does not have a path sum equal to %d.\n", targetSum);
    }

    // Free allocated memory for the tree nodes (not included here for brevity)

    return 0;
}

```

1.117 Design Add and Search Words DataStructure

Design a data structure that supports adding new words and finding if a string matches any previously added string.

Implement the WordDictionary class:

- WordDictionary() Initializes the object.
- void addWord(word) Adds word to the data structure, it can be matched later.

- `bool search(word)` Returns true if there is any string in the data structure that matches word or false otherwise. word may contain dots '.' where dots can be matched with any letter.

Example:

Input

```
["WordDictionary","addWord","addWord","addWord","addWord","search","search","search","search"]
[],["bad"],["dad"],["mad"],["pad"],["bad"],[".ad"],["b.."]]
```

Output

```
[null,null,null,null,false,true,true,true]
```

Explanation

```
WordDictionary wordDictionary = new WordDictionary();
wordDictionary.addWord("bad");
wordDictionary.addWord("dad");
wordDictionary.addWord("mad");
wordDictionary.search("pad"); // return False
wordDictionary.search("bad"); // return True
wordDictionary.search(".ad"); // return True
wordDictionary.search("b.."); // return True
```

C :

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

// Definition for a trie node
typedef struct TrieNode {
    bool isEnd;
    struct TrieNode* children[26];
} TrieNode;

// Definition for WordDictionary
typedef struct {
    TrieNode* root;
} WordDictionary;

// Helper function to create a new trie node
TrieNode* createTrieNode() {
    TrieNode* node = (TrieNode*)malloc(sizeof(TrieNode));
    node->isEnd = false;
    memset(node->children, 0, sizeof(node->children));
    return node;
}

WordDictionary* wordDictionaryCreate() {
```

```

WordDictionary* obj = (WordDictionary*)malloc(sizeof(WordDictionary));
obj->root = createTrieNode();
return obj;
}

void addWordToTrie(TrieNode* root, char* word) {
    TrieNode* node = root;
    for (int i = 0; i < strlen(word); ++i) {
        int index = word[i] - 'a';
        if (node->children[index] == NULL) {
            node->children[index] = createTrieNode();
        }
        node = node->children[index];
    }
    node->isEnd = true;
}

void wordDictionaryAddWord(WordDictionary* obj, char* word) {
    addWordToTrie(obj->root, word);
}

bool searchInTrie(TrieNode* node, char* word) {
    for (int i = 0; i < strlen(word); ++i) {
        if (word[i] == '.') {
            for (int j = 0; j < 26; ++j) {
                if (node->children[j] != NULL &&
                    searchInTrie(node->children[j], word + i + 1)) {
                    return true;
                }
            }
            return false;
        } else {
            int index = word[i] - 'a';
            if (node->children[index] == NULL) {
                return false;
            }
            node = node->children[index];
        }
    }
    return node->isEnd;
}

bool wordDictionarySearch(WordDictionary* obj, char* word) {
    return searchInTrie(obj->root, word);
}

void freeTrie(TrieNode* node) {
    if (node == NULL) {
        return;
    }
}

```

```

    }
    for (int i = 0; i < 26; ++i) {
        freeTrie(node->children[i]);
    }
    free(node);
}

void wordDictionaryFree(WordDictionary* obj) {
    freeTrie(obj->root);
    free(obj);
}

int main() {
    WordDictionary* obj = wordDictionaryCreate();

    // Example usage
    wordDictionaryAddWord(obj, "bad");
    wordDictionaryAddWord(obj, "dad");
    wordDictionaryAddWord(obj, "mad");
    printf("%s\n", wordDictionarySearch(obj, "pad") ? "true" : "false"); // Output:
false
    printf("%s\n", wordDictionarySearch(obj, "bad") ? "true" : "false"); // Output: true
    printf("%s\n", wordDictionarySearch(obj, ".ad") ? "true" : "false"); // Output: true
    printf("%s\n", wordDictionarySearch(obj, "b..") ? "true" : "false"); // Output: true

    wordDictionaryFree(obj);
    return 0;
}

/**
 * Your WordDictionary struct will be instantiated and called as such:
 * WordDictionary* obj = wordDictionaryCreate();
 * wordDictionaryAddWord(obj, word);

 * bool param_2 = wordDictionarySearch(obj, word);

 * wordDictionaryFree(obj);
 */

```

1.118 Sudoku Solver

Write a program to solve a Sudoku puzzle by filling the empty cells.

A sudoku solution must satisfy **all of the following rules**:

1. Each of the digits 1-9 must occur exactly once in each row.
2. Each of the digits 1-9 must occur exactly once in each column.
3. Each of the digits 1-9 must occur exactly once in each of the 9 3x3 sub-boxes of the grid.

The '.' character indicates empty cells.

Example 1:

5	3	.	.	7
6	.	.	1	9	5	.	.	.
9	8	6	.	.
8	.	.	6	3
4	.	8	.	3	.	.	.	1
7	.	.	2	.	.	.	6	.
6	2	8	.	.
.	4	1	9	.	.	.	5	.
.	.	8	.	.	7	9	.	.

Input: board =

```
[["5","3","","","7","","","","","."],[ "6","","","","1","9","5","","","."],[".","9","8","","","","","6","."],[ "8","","","","","6",".,".,".,".,"3"],[ "4","","","8","","3","","","1"],[ "7","","","","2","","","6"],[ ".","6","","","","2","8","."],[ ".",".,".,"4","1","9","","5"],[ ".","","","","8","","","7","9"]]
```

Output:

```
[["5","3","4","6","7","8","9","1","2"],[ "6","7","2","1","9","5","3","4","8"],[ "1","9","8","3","4","2","5","6","7"],[ "8","5","9","7","6","1","4","2","3"],[ "4","2","6","8","5","3","7","9","1"],[ "7","1","3","9","2","4","8","5","6"],[ "9","6","1","5","3","7","2","8","4"],[ "2","8","7","4","1","9","6","3","5"],[ "3","4","5","2","8","6","1","7","9"]]
```

Explanation: The input board is shown above and the only valid solution is shown below:

5	3	4	6	7	8	9	1	2
6	7	2	1	9	5	3	4	8
1	9	8	3	4	2	5	6	7
8	5	9	7	6	1	4	2	3
4	2	6	8	5	3	7	9	1
7	1	3	9	2	4	8	5	6
9	6	1	5	3	7	2	8	4
2	8	7	4	1	9	6	3	5
3	4	5	2	8	6	1	7	9

C:

```
#define SIZE 9
```

```
bool isSafe(char** board, int row, int col, char num) {  
    // Check if 'num' is not already present in the current row and column  
    for (int x = 0; x < SIZE; x++) {
```

```

        if (board[row][x] == num || board[x][col] == num) {
            return false;
        }
    }

// Check if 'num' is not already present in the current 3x3 sub-grid
int startRow = row - row % 3;
int startCol = col - col % 3;
for (int i = 0; i < 3; i++) {
    for (int j = 0; j < 3; j++) {
        if (board[i + startRow][j + startCol] == num) {
            return false;
        }
    }
}

return true;
}

bool findUnassignedLocation(char** board, int* row, int* col) {
    for (*row = 0; *row < SIZE; (*row)++) {
        for (*col = 0; *col < SIZE; (*col)++) {
            if (board[*row][*col] == '.') {
                return true;
            }
        }
    }
    return false;
}

bool solve(char** board) {
    int row, col;

    if (!findUnassignedLocation(board, &row, &col)) {
        // No unassigned location, puzzle is solved
        return true;
    }

    for (char num = '1'; num <= '9'; num++) {
        if (isSafe(board, row, col, num)) {
            // Try placing 'num' in the current position
            board[row][col] = num;

            // Recursively solve the rest of the puzzle
            if (solve(board)) {
                return true;
            }
        }
    }

    // If placing 'num' didn't lead to a solution, backtrack
}

```

```

        board[row][col] = '.';
    }
}

// No number can be placed in the current position
return false;
}

void solveSudoku(char** board, int boardSize, int* boardColSize) {
    solve(board);
}

int main() {
    char* sudoku[SIZE] = {
        "53..7....",
        "6..195....",
        ".98....6..",
        "8....6....3",
        "4..8.3..1..",
        "7....2....6",
        ".6.....28..",
        "...419....5",
        "...8....79"
    };
    printf("Sudoku puzzle before solving:\n");
    for (int i = 0; i < SIZE; i++) {
        printf("%s\n", sudoku[i]);
    }

    solveSudoku(sudoku, SIZE, NULL);

    printf("\nSudoku puzzle after solving:\n");
    for (int i = 0; i < SIZE; i++) {
        printf("%s\n", sudoku[i]);
    }

    return 0;
}

```

1.119 Max Area Of Island

You are given an $m \times n$ binary matrix grid. An island is a group of 1's (representing land) connected **4-directionally** (horizontal or vertical.) You may assume all four edges of the grid are surrounded by water.

The **area** of an island is the number of cells with a value 1 in the island.

Return **the maximum area of an island in** grid. If there is no island, return 0.

Example 1:

0	0	1	0	0	0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	1	1	1	0	0	0	0
0	1	1	0	1	0	0	0	0	0	0	0	0	0
0	1	0	0	1	1	0	0	1	0	1	0	0	0
0	1	0	0	1	1	0	0	1	1	1	0	0	0
0	0	0	0	0	0	0	0	0	0	1	0	0	0
0	0	0	0	0	0	0	1	1	1	0	0	0	0
0	0	0	0	0	0	0	1	1	0	0	0	0	0

Input: grid =
[[0,0,1,0,0,0,0,1,0,0,0,0,0],[0,0,0,0,0,0,0,1,1,1,0,0,0],[0,1,1,0,1,0,0,0,0,0,0,0,0],[0,1,0,0,1,1,0,0,1,0,1,0,0],[0,1,0,0,1,1,0,0,1,1,1,0,0],[0,0,0,0,0,0,0,0,1,1,0,0,0],[0,0,0,0,0,0,0,1,1,1,0,0,0],[0,0,0,0,0,0,1,1,0,0,0,0,0]]

Output: 6

Explanation: The answer is not 11, because the island must be connected 4-directionally.

Example 2:

Input: grid = [[0,0,0,0,0,0,0]]

Output: 0

C:

```
int maxAreaOfIsland(int** grid, int gridSize, int* gridColSize) {
    int maxArea = 0;

    if (grid == NULL || gridSize == 0) {
        return maxArea;
    }

    for (int i = 0; i < gridSize; i++) {
        for (int j = 0; j < gridColSize[i]; j++) {
            if (grid[i][j] == 1) {
                int area = evaluateGrid(grid, i, j, gridSize, gridColSize[i]);
                maxArea = area > maxArea ? area : maxArea;
            }
        }
    }
}
```

```

        }
    }

    return maxArea;
}

int evaluateGrid(int** grid, int i, int j, int row, int col) {
    if (i < 0 || j < 0 || i >= row || j >= col || grid[i][j] != 1) {
        return 0;
    }

    grid[i][j] = 2;
    int area = 1; // Current cell contributes to the area

    // Explore neighbors
    area += evaluateGrid(grid, i - 1, j, row, col);
    area += evaluateGrid(grid, i + 1, j, row, col);
    area += evaluateGrid(grid, i, j - 1, row, col);
    area += evaluateGrid(grid, i, j + 1, row, col);

    return area;
}

int main() {
    // Example grid
    int row = 5;
    int col = 5;
    int **grid = (int **)malloc(row * sizeof(int *));
    for (int i = 0; i < row; i++) {
        grid[i] = (int *)malloc(col * sizeof(int));
    }
    grid[0][0] = 1;
    grid[0][1] = 1;
    grid[0][2] = 0;
    grid[0][3] = 0;
    grid[0][4] = 0;
    grid[1][0] = 1;
    grid[1][1] = 1;
    grid[1][2] = 0;
    grid[1][3] = 0;
    grid[1][4] = 0;
    grid[2][0] = 0;
    grid[2][1] = 0;
    grid[2][2] = 0;
    grid[2][3] = 1;
    grid[2][4] = 1;
    grid[3][0] = 0;
    grid[3][1] = 0;
    grid[3][2] = 0;
}

```

```

grid[3][3] = 1;
grid[3][4] = 1;
grid[4][0] = 0;
grid[4][1] = 0;
grid[4][2] = 0;
grid[4][3] = 1;
grid[4][4] = 1;

int maxSize = maxAreaOfIsland(grid, row, &col);
printf("The maximum area of the island is: %d\n", maxSize);

// Free memory
for (int i = 0; i < row; i++) {
    free(grid[i]);
}
free(grid);

return 0;
}

```

1.120 Valid Parentheses

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Example 1:

Input: s = "()"
Output: true

Example 2:

Input: s = "()[]{}"
Output: true

Example 3:

Input: s = "()"
Output: false

C:

```
bool isValid(char* s) {
    int length = 0;
    char* stack = (char*)malloc(strlen(s) * sizeof(char));

    for (int i = 0; s[i] != '\0'; i++) {
        if (s[i] == '(' || s[i] == '[' || s[i] == '{') {
            stack[length++] = s[i];
        } else {
            if (length == 0) {
                free(stack);
                return false; // No corresponding open bracket
            }

            char openBracket = stack[--length];

            if ((s[i] == ')' && openBracket != '(') ||
                (s[i] == ']' && openBracket != '[') ||
                (s[i] == '}' && openBracket != '{')) {
                free(stack);
                return false; // Mismatched brackets
            }
        }
    }

    bool result = (length == 0); // Stack should be empty for a valid string
    free(stack);
    return result;
}

int main() {
    // Example string
    char* inputString = "{[()]}";

    // Check if the input string is valid
    bool isValidString = isValid(inputString);

    // Print the result
    if (isValidString) {
        printf("The input string is valid.\n");
    } else {
        printf("The input string is not valid.\n");
    }

    return 0;
}
```


1.121 Merge Two Sorted Lists

You are given the heads of two sorted linked lists list1 and list2.

Merge the two lists into one **sorted** list. The list should be made by splicing together the nodes of the first two lists.

Return *the head of the merged linked list*.

Example 1:



Input: list1 = [1,2,4], list2 = [1,3,4]

Output: [1,1,2,3,4,4]

Example 2:

Input: list1 = [], list2 = []

Output: []

Example 3:

Input: list1 = [], list2 = [0]

Output: [0]

C:

```
struct ListNode* mergeTwoLists(struct ListNode* list1, struct ListNode* list2){
    struct ListNode *dummy = (struct ListNode *)malloc(sizeof(struct ListNode));
    dummy->next = NULL;
    struct ListNode *curr = dummy;
    while (list1 != NULL && list2 != NULL) {
        if (list1->val < list2->val) {
            dummy->next = list1;
            list1 = list1->next;
            dummy = dummy->next;
        } else {
```

```

        dummy->next = list2;
        list2 = list2->next;
        dummy = dummy->next;
    }
}
while (list1 != NULL) {
    dummy->next = list1;
    list1 = list1->next;
    dummy = dummy->next;
}
while (list2 != NULL) {
    dummy->next = list2;
    list2 = list2->next;
    dummy = dummy->next;
}

return curr->next;
}
int main() {
// Define two sorted linked lists
struct ListNode* list1 = NULL;
struct ListNode* list2 = NULL;

// Populate list1
list1 = (struct ListNode*)malloc(sizeof(struct ListNode));
list1->val = 1;
list1->next = (struct ListNode*)malloc(sizeof(struct ListNode));
list1->next->val = 2;
list1->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
list1->next->next->val = 4;
list1->next->next->next = NULL;

// Populate list2
list2 = (struct ListNode*)malloc(sizeof(struct ListNode));
list2->val = 1;
list2->next = (struct ListNode*)malloc(sizeof(struct ListNode));
list2->next->val = 3;
list2->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
list2->next->next->val = 4;
list2->next->next->next = NULL;

// Merge the two lists
struct ListNode* mergedList = mergeTwoLists(list1, list2);

// Print the merged list
printf("Merged List: ");
while (mergedList != NULL) {
    printf("%d ", mergedList->val);
    mergedList = mergedList->next;
}
}

```

```

    }

    printf("\n");

    // Free the memory allocated for the lists
    struct ListNode* temp;
    while (list1 != NULL) {
        temp = list1;
        list1 = list1->next;
        free(temp);
    }
    while (list2 != NULL) {
        temp = list2;
        list2 = list2->next;
        free(temp);
    }

    return 0;
}

```

1.122 Container With Most Water


You are given an integer array height of length n. There are n vertical lines drawn such that the two endpoints of the i^{th} line are $(i, 0)$ and $(i, \text{height}[i])$.

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return *the maximum amount of water a container can store.*

Notice that you may not slant the container.

Example 1:



Input: height = [1,8,6,2,5,4,8,3,7]

Output: 49

Explanation: The above vertical lines are represented by array [1,8,6,2,5,4,8,3,7]. In this case, the max area of water (blue section) the container can contain is 49.

Example 2:

Input: height = [1,1]

Output: 1

C:

```
#define MAX(a,b) ((a) > (b)?(a):(b))
#define MIN(a,b) ((a) > (b)?(b):(a))
int maxArea(int* height, int heightSize) {
    int max_area = INT_MIN;
    int left = 0;
    int right = heightSize-1;
    while (left < right) {
        max_area = MAX(max_area,(MIN(height[left],height[right])*abs(left-right)));
        if (height[left] < height[right]) left++;
        else right--;
    }
    return max_area;
}
int main() {
    // Sample input array of heights
    int height[] = {1, 8, 6, 2, 5, 4, 8, 3, 7};
    int heightSize = sizeof(height) / sizeof(height[0]);
    // Calculate the maximum area
}
```

```

        int result = maxArea(height, heightSize);

        // Print the result
        printf("The maximum area of water that can be held is: %d\n", result);


        return 0;
    }

```

1.123 Pascals Triangle

Given an integer numRows, return the first numRows of **Pascal's triangle**.

In **Pascal's triangle**, each number is the sum of the two numbers directly above it as shown:



Example 1:

Input: numRows = 5
Output: [[1],[1,1],[1,2,1],[1,3,3,1],[1,4,6,4,1]]

Example 2:

Input: numRows = 1
Output: [[1]]

C:

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 * calls free().

```

```

*/
int** generate(int numRows, int* returnSize, int** returnColumnSizes) {
    if (numRows <= 0) {
        *returnSize = 0;
        *returnColumnSizes = NULL;
        return NULL;
    }

    // Allocate memory for the result
    int** result = (int**)malloc(sizeof(int*) * numRows);
    *returnColumnSizes = (int*)malloc(sizeof(int) * numRows);

    for (int i = 0; i < numRows; i++) {
        result[i] = (int*)malloc(sizeof(int) * (i + 1));
        (*returnColumnSizes)[i] = i + 1;

        // Set the first and last elements to 1
        result[i][0] = result[i][i] = 1;

        // Calculate the middle elements based on the previous row
        for (int j = 1; j < i; j++) {
            result[i][j] = result[i - 1][j - 1] + result[i - 1][j];
        }
    }

    *returnSize = numRows;
    return result;
}

int main() {
    // Sample input for numRows
    int numRows = 5;

    // Variables to store the result and column sizes
    int** result;
    int* returnSize;
    int* returnColumnSizes;

    // Call the generate function
    result = generate(numRows, returnSize, &returnColumnSizes);

    // Print the generated Pascal's triangle
    printf("Pascal's Triangle with %d rows:\n", numRows);
    for (int i = 0; i < numRows; i++) {
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d ", result[i][j]);
        }
        printf("\n");
    }
}

```

```

    // Free allocated memory
    for (int i = 0; i < numRows; i++) {
        free(result[i]);
    }
    free(result);
    free(returnColumnSizes);

    return 0;
}

```

1.124 Valid Anagram

Given two strings s and t, return true if t is an anagram of s, and false otherwise.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: s = "anagram", t = "nagaram"
Output: true

Example 2:

Input: s = "rat", t = "car"
Output: false

C:

```

bool isAnagram(char* s, char* t) {
    // Check if the lengths of both strings are equal
    int lenS = 0, lenT = 0;
    while (s[lenS] != '\0') {
        lenS++;
    }
    while (t[lenT] != '\0') {
        lenT++;
    }
    if (lenS != lenT) {
        return false;
    }

    // Initialize an array to store the frequency of characters
    int frequency[26] = {0}; // Assuming input only contains lowercase English letters

    // Increment frequency for characters in string s
    for (int i = 0; i < lenS; i++) {
        frequency[s[i] - 'a']++;
    }
}
```

```

    }

    // Decrement frequency for characters in string t
    for (int i = 0; i < lenT; i++) {
        frequency[t[i] - 'a']--;
    }

    // Check if all frequencies are zero
    for (int i = 0; i < 26; i++) {
        if (frequency[i] != 0) {
            return false;
        }
    }

    // If all checks pass, the strings are anagrams
    return true;
}

int main() {
    // Sample input strings
    char s[] = "anagram";
    char t[] = "nagaram";

    // Call the isAnagram function
    bool result = isAnagram(s, t);

    // Output the result
    if (result) {
        printf("%s and %s are anagrams.\n", s, t);
    } else {
        printf("%s and %s are not anagrams.\n", s, t);
    }

    return 0;
}

```

1.125 Unique Paths

There is a robot on an $m \times n$ grid. The robot is initially located at the **top-left corner** (i.e., $\text{grid}[0][0]$). The robot tries to move to the **bottom-right corner** (i.e., $\text{grid}[m - 1][n - 1]$). The robot can only move either down or right at any point in time.

Given the two integers m and n , return *the number of possible unique paths that the robot can take to reach the bottom-right corner*.

The test cases are generated so that the answer will be less than or equal to $2 * 10^9$.

Example 1:



Input: m = 3, n = 7

Output: 28

Example 2:

Input: m = 3, n = 2

Output: 3

Explanation: From the top-left corner, there are a total of 3 ways to reach the bottom-right corner:

1. Right -> Down -> Down
2. Down -> Down -> Right
3. Down -> Right -> Down

C:

```
int uniquePaths(int m, int n) {
    // Create a 2D array to store the number of unique paths for each position.
    int dp[m][n];

    // Initialize the leftmost column (only one way to reach any position in the
    // leftmost column).
    for (int i = 0; i < m; i++) {
        dp[i][0] = 1;
    }

    // Initialize the top row (only one way to reach any position in the top row).
    for (int j = 0; j < n; j++) {
        dp[0][j] = 1;
    }

    // Fill in the rest of the array by summing the number of unique paths from the top
    // and left.
    for (int i = 1; i < m; i++) {
        for (int j = 1; j < n; j++) {
            dp[i][j] = dp[i - 1][j] + dp[i][j - 1];
        }
    }
}
```

```

    // The result is stored in the bottom-right corner of the array.
    return dp[m - 1][n - 1];
}

int main() {
    // Sample input values for m and n
    int m = 3;
    int n = 7;

    // Call the uniquePaths function
    int result = uniquePaths(m, n);

    // Output the result
    printf("Number of unique paths for a %d x %d grid: %d\n", m, n, result);

    return 0;
}

```

1.126 Longest Increasing Subsequence

Given an integer array nums, return *the length of the longest strictly increasing subsequence*

subsequence

.



Example 1:

Input: nums = [10,9,2,5,3,7,101,18]

Output: 4

Explanation: The longest increasing subsequence is [2,3,7,101], therefore the length is 4.

Example 2:

Input: nums = [0,1,0,3,2,3]

Output: 4

Example 3:

Input: nums = [7,7,7,7,7,7,7]

Output: 1



C:

```

int lengthOfLIS(int* nums, int numsSize) {
    if (numsSize == 0) {
        return 0;
    }

    // Initialize an array to store the elements of the increasing subsequence
    int sub[numsSize];
    sub[0] = nums[0];
    int subSize = 1;

    for (int i = 1; i < numsSize; i++) {
        int num = nums[i];
        if (num > sub[subSize - 1]) {
            sub[subSize] = num;
            subSize++;
        } else {
            // Find the first element in sub that is greater than or equal to num
            int j = 0;
            while (num > sub[j]) {
                j++;
            }

            sub[j] = num;
        }
    }

    return subSize;
}

int main() {
    // Sample input array
    int nums[] = {10, 9, 2, 5, 3, 7, 101, 18};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Call the lengthOfLIS function
    int result = lengthOfLIS(nums, numsSize);

    // Output the result
    printf("Length of the longest increasing subsequence: %d\n", result);

    return 0;
}

```

1.127 Group Anagrams

Given an array of strings `strs`, group **the anagrams** together. You can return the answer in **any order**.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: strs = ["eat", "tea", "tan", "ate", "nat", "bat"]
Output: [["bat"], ["nat", "tan"], ["ate", "eat", "tea"]]

Example 2:

Input: strs = [""]
Output: [[]]

Example 3:

Input: strs = ["a"]
Output: [["a"]]

C:

```
class Solution {
    public List<List<String>> groupAnagrams(String[] strs) {
        HashMap<String, List<String>> hm = new HashMap<String, List<String>>();
        int[] count_map = new int[26];
        for (int i = 0; i < strs.length; i++) {
            Arrays.fill(count_map, 0);
            for (int j = 0; j < strs[i].length(); j++) {
                count_map[strs[i].charAt(j)-'a']++;
            }
            StringBuilder sb = new StringBuilder();
            for (int m = 0; m < 26; m++) {
                sb.append("*");
                sb.append(count_map[m]);
            }
            if (!hm.containsKey(sb.toString())) {
                hm.put(sb.toString(), new ArrayList());
            }
            hm.get(sb.toString()).add(strs[i]);
            System.out.println(sb.toString());
        }
        return new ArrayList(hm.values());
    }
}**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 calls free().
 */
```

```

// Structure to represent a hash table node
struct Node {
    char* key;
    char** values;
    int size;
    struct Node* next;
};

// Function to calculate the hash value for a string
unsigned int calculateHash(const char* str) {
    unsigned int hash = 5381;
    int c;

    while ((c = *str++)) {
        hash = ((hash << 5) + hash) + c; // Hash * 33 + character
    }

    return hash;
}

// Function to insert a key and value into the hash table
void insertIntoHash(struct Node** hashTable, const char* key, const char* value) {
    unsigned int hashValue = calculateHash(key);
    int bucket = hashValue % 1009; // Use a prime number as the hash table size

    // Create a new node
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->key =  strdup(key);
    newNode->values = (char**)malloc(sizeof(char*));
    newNode->values[0] =  strdup(value);
    newNode->size = 1;
    newNode->next = NULL;

    // Insert into the hash table
    if (hashTable[bucket] == NULL) {
        hashTable[bucket] = newNode;
    } else {
        newNode->next = hashTable[bucket];
        hashTable[bucket] = newNode;
    }
}

// Function to group anagrams
char*** groupAnagrams(char** strs, int strsSize, int* returnSize, int** returnColumnSizes) {
    // Initialize variables
    *returnSize = 0;
}

```

```

    struct Node* hashTable[1009] = {NULL}; // Hash table with 1009 buckets (prime
number)
    char*** result = NULL;

    // Iterate through each string in the input
    for (int i = 0; i < strsSize; i++) {
        // Count the frequency of each character in the string
        int count_map[26] = {0};
        for (int j = 0; j < strlen(strs[i]); j++) {
            count_map[strs[i][j] - 'a']++;
        }

        // Build a key using the frequency of characters
        char key[100];
        int keyIndex = 0;
        for (int k = 0; k < 26; k++) {
            keyIndex += sprintf(key + keyIndex, "%d*", count_map[k]);
        }

        // Check if the key is already in the hash table
        unsigned int hashValue = calculateHash(key);
        int bucket = hashValue % 1009;
        struct Node* current = hashTable[bucket];

        while (current != NULL) {
            if (strcmp(current->key, key) == 0) {
                // Anagram found, add the original string to the values
                current->values = realloc(current->values, (current->size + 1) *
sizeof(char*));
                current->values[current->size] = strdup(strs[i]);
                current->size++;
                break;
            }
            current = current->next;
        }

        // If the key is not in the hash table, create a new node
        if (current == NULL) {
            insertIntoHash(hashTable, key, strs[i]);
        }
    }

    // Count the number of unique groups
    int uniqueGroups = 0;
    for (int i = 0; i < 1009; i++) {
        struct Node* current = hashTable[i];
        while (current != NULL) {
            uniqueGroups++;
        }
    }
}

```

```

        current = current->next;
    }
}

// Allocate memory for the result
result = (char***)malloc(uniqueGroups * sizeof(char**));
*returnColumnSizes = (int*)malloc(uniqueGroups * sizeof(int));

// Populate the result array
int resultIndex = 0;
for (int i = 0; i < 1009; i++) {
    struct Node* current = hashTable[i];
    while (current != NULL) {
        int groupSize = current->size;

        // Allocate memory for the group
        result[resultIndex] = (char**)malloc(groupSize * sizeof(char*));
        (*returnColumnSizes)[resultIndex] = groupSize;

        // Copy values to the result array
        for (int j = 0; j < groupSize; j++) {
            result[resultIndex][j] = strdup(current->values[j]);
        }

        // Move to the next group
        resultIndex++;
        current = current->next;
    }
}

// Free memory used by the hash table
for (int i = 0; i < 1009; i++) {
    struct Node* current = hashTable[i];
    while (current != NULL) {
        free(current->key);
        for (int j = 0; j < current->size; j++) {
            free(current->values[j]);
        }
        free(current->values);
        struct Node* temp = current;
        current = current->next;
        free(temp);
    }
}

*returnSize = uniqueGroups;
return result;
}

```

```

// Function to free memory allocated for the grouped anagrams result
void freeGroupedAnagrams(char*** result, int returnSize, int* returnColumnSizes) {
    for (int i = 0; i < returnSize; i++) {
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            free(result[i][j]);
        }
        free(result[i]);
    }
    free(result);
    free(returnColumnSizes);
}

```

1.128 Longest Palindromic SubString

Given a string s, return *the longest*

palindromic
 substring
 in s.

Example 1:

Input: s = "babad"
Output: "bab"
Explanation: "aba" is also a valid answer.

Example 2:

Input: s = "cbbd"
Output: "bb"

C:

```

class Solution {
    public String longestPalindrome(String s) {
        int n = s.length();
        boolean[][] dp = new boolean[n][n];

        // All substrings of length 1 are palindromes
        for (int i = 0; i < n; i++) {
            dp[i][i] = true;
        }

        int start = 0; // Start index of the longest palindrome
        int maxLength = 1; // Length of the longest palindrome

```

```

        // Check substrings of length 2
        for (int i = 0; i < n - 1; i++) {
            if (s.charAt(i) == s.charAt(i + 1)) {
                dp[i][i + 1] = true;
                start = i;
                maxLength = 2;
            }
        }

        // Check substrings of length 3 and more
        for (int len = 3; len <= n; len++) {
            for (int i = 0; i <= n - len; i++) {
                int j = i + len - 1;
                if (dp[i + 1][j - 1] && s.charAt(i) == s.charAt(j)) {
                    dp[i][j] = true;
                    start = i;
                    maxLength = len;
                }
            }
        }

        return s.substring(start, start + maxLength);
    }
}

char* longestPalindrome(char* s) {
    int n = strlen(s);

    // Create a new string to insert '#' between characters
    char* modifiedString = (char*)malloc((2 * n + 2) * sizeof(char));
    int j = 0;

    for (int i = 0; i < n; i++) {
        modifiedString[j++] = '#';
        modifiedString[j++] = s[i];
    }
    modifiedString[j++] = '#';
    modifiedString[j] = '\0';

    // Initialize the palindrome array
    int* palindrome = (int*)malloc((2 * n + 2) * sizeof(int));
    memset(palindrome, 0, (2 * n + 2) * sizeof(int));

    int center = 0, right = 0;

    for (int i = 0; i < 2 * n + 1; i++) {
        int mirror = 2 * center - i;

        // Check if the mirror of i is within the right boundary

```

```

        if (i < right) {
            palindrome[i] = (right - i < palindrome[mirror]) ? right - i :
palindrome[mirror];
        }

        // Expand around the center
        int a = i + (1 + palindrome[i]);
        int b = i - (1 + palindrome[i]);

        while (a < 2 * n + 1 && b >= 0 && modifiedString[a] == modifiedString[b]) {
            palindrome[i]++;
            a++;
            b--;
        }

        // If palindrome[i] reaches the boundary of the current rightmost palindrome,
        // update the center and right boundary accordingly
        if (i + palindrome[i] > right) {
            center = i;
            right = i + palindrome[i];
        }
    }

    // Find the maximum element in the palindrome array
    int maxLen = 0, centerIndex = 0;

    for (int i = 0; i < 2 * n + 1; i++) {
        if (palindrome[i] > maxLen) {
            maxLen = palindrome[i];
            centerIndex = i;
        }
    }

    // Extract the longest palindrome from the modified string
    int start = (centerIndex - maxLen) / 2;
    char* result = (char*)malloc((maxLen + 1) * sizeof(char));
    strncpy(result, s + start, maxLen);
    result[maxLen] = '\0';

    // Clean up
    free(modifiedString);
    free(palindrome);

    return result;
}

```

1.129 Three Sum

Given an integer array nums, return all the triplets [nums[i], nums[j], nums[k]] such that i != j, i != k, and j != k, and nums[i] + nums[j] + nums[k] == 0.

Notice that the solution set must not contain duplicate triplets.

Example 1:

Input: nums = [-1,0,1,2,-1,-4]

Output: [[-1,-1,2],[-1,0,1]]

Explanation:

nums[0] + nums[1] + nums[2] = (-1) + 0 + 1 = 0.

nums[1] + nums[2] + nums[4] = 0 + 1 + (-1) = 0.

nums[0] + nums[3] + nums[4] = (-1) + 2 + (-1) = 0.

The distinct triplets are [-1,0,1] and [-1,-1,2].

Notice that the order of the output and the order of the triplets does not matter.

Example 2:

Input: nums = [0,1,1]

Output: []

Explanation: The only possible triplet does not sum up to 0.

Example 3:

Input: nums = [0,0,0]

Output: [[0,0,0]]

Explanation: The only possible triplet sums up to 0.

C :

```
/*
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
calls free().
 */
int compare(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}
int** threeSum(int* nums, int numsSize, int* returnSize, int** returnColumnSizes) {
    // Sort the array to simplify the solution
    qsort(nums, numsSize, sizeof(int), compare);

    // Allocate memory for the result
    int** result = NULL;
    *returnSize = 0;
    *returnColumnSizes = NULL;

    // Iterate through the array
    for (int i = 0; i < numsSize - 2; ++i) {
        // Skip duplicates to avoid duplicate triplets
        if (i > 0 && nums[i] == nums[i - 1]) {
```

```

        continue;
    }

    int left = i + 1;
    int right = numsSize - 1;

    while (left < right) {
        int sum = nums[i] + nums[left] + nums[right];
        if (sum == 0) {
            // Found a triplet, allocate memory for it
            result = (int**)realloc(result, (*returnSize + 1) * sizeof(int*));
            result[*returnSize] = (int*)malloc(3 * sizeof(int));

            // Assign values to the triplet
            result[*returnSize][0] = nums[i];
            result[*returnSize][1] = nums[left];
            result[*returnSize][2] = nums[right];

            // Increment the result size
            (*returnSize)++;
        }

        // Skip duplicates for left pointer
        while (left < right && nums[left] == nums[left + 1]) {
            left++;
        }

        // Skip duplicates for right pointer
        while (left < right && nums[right] == nums[right - 1]) {
            right--;
        }

        // Move pointers
        left++;
        right--;
    } else if (sum < 0) {
        left++;
    } else {
        right--;
    }
}

// Allocate memory for column sizes
*returnColumnSizes = (int*)malloc(*returnSize * sizeof(int));
for (int i = 0; i < *returnSize; ++i) {
    (*returnColumnSizes)[i] = 3;
}

return result;

```

```

}

int main() {
    int nums[] = {-1, 0, 1, 2, -1, -4};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int returnSize;
    int* returnColumnSizes;

    int** result = threeSum(nums, numsSize, &returnSize, &returnColumnSizes);

    printf("[");
    for (int i = 0; i < returnSize; ++i) {
        printf("[");
        for (int j = 0; j < returnColumnSizes[i]; ++j) {
            printf("%d", result[i][j]);
            if (j < returnColumnSizes[i] - 1) {
                printf(", ");
            }
        }
        printf("]");
        if (i < returnSize - 1) {
            printf(", ");
        }
    }
    printf("]\n");

    // Free allocated memory
    for (int i = 0; i < returnSize; ++i) {
        free(result[i]);
    }
    free(result);
    free(returnColumnSizes);

    return 0;
}

class Solution {
    public List<List<Integer>> threeSum(int[] nums) {
        HashSet<Integer> hs = new HashSet<Integer>();
        HashMap<Integer, Integer> hm = new HashMap<Integer, Integer>();
        HashSet<List<Integer>> result = new HashSet<List<Integer>>();

        for (int i = 0; i < nums.length; i++) {
            if (hs.add(nums[i])) {
                for (int j = i+1; j < nums.length; j++) {
                    int target = -nums[i]-nums[j];
                    if (hm.containsKey(target) && hm.get(target) == i) {
                        List<Integer> entry = new ArrayList<Integer>();
                        entry.add(nums[i]);

```

```

        entry.add(nums[j]);
        entry.add(target);
        Collections.sort(entry);
        result.add(entry);
    } else {
        hm.put(nums[j], i);
    }
}
}
return new ArrayList(result);
}
/*
[-1,0,1,2,-1,-4]
duplicates: -1 , hm : 0:0 and complement = 1
duplicates: -1 , hm: 0:0 and 2:0 complement = -1
*/

```

1.130 Single Element In A Sorted Array

You are given a sorted array consisting of only integers where every element appears exactly twice, except for one element which appears exactly once.

Return *the single element that appears only once*.

Your solution must run in $O(\log n)$ time and $O(1)$ space.

Example 1:

Input: nums = [1,1,2,3,3,4,4,8,8]

Output: 2

Example 2:

Input: nums = [3,3,7,7,10,11,11]

Output: 10

C:

```

int singleNonDuplicate(int* nums, int numsSize) {
    int r = 0;
    for (int i = 0; i < numsSize; i++)
        r = r ^ nums[i];
}

```

```
        return r;
    }

int main() {
    int nums[] = {1, 1, 2, 3, 3, 4, 4, 8, 8};
    int numsSize = sizeof(nums) / sizeof(nums[0]));

    int result = singleNonDuplicate(nums, numsSize);
    printf("The single non-duplicate element is: %d\n", result);

    return 0;
}
```

1.131 Letter Combinations Of A Phone Number

Given a string containing digits from 2-9 inclusive, return all possible letter combinations that the number could represent. Return the answer in any order.

A mapping of digits to letters (just like on the telephone buttons) is given below. Note that 1 does not map to any letters.



Example 1:

Input: digits = "23"
Output: ["ad", "ae", "af", "bd", "be", "bf", "cd", "ce", "cf"]

Example 2:

Input: digits = ""
Output: []

Example 3:

Input: digits = "2"
Output: ["a", "b", "c"]

C:

/**

* Note: The returned array must be malloced, assume caller calls free().

```

/*
// Helper function to append a character to a string
void append(char* str, char c) {
    int len = strlen(str);
    str[len] = c;
    str[len + 1] = '\0';
}

// Helper function to perform backtracking
void backtrack(char** result, char* digits, char* current, char** mapping, int index,
int* returnSize) {
    // If the current combination is complete, add it to the result
    if (digits[index] == '\0') {
        result[*returnSize] = strdup(current);
        (*returnSize)++;
        return;
    }

    // Get the letters corresponding to the current digit
    char* letters = mapping[digits[index] - '0'];

    // Iterate through the letters and backtrack
    for (int i = 0; letters[i] != '\0'; i++) {
        append(current, letters[i]);
        backtrack(result, digits, current, mapping, index + 1, returnSize);
        // Remove the last character to backtrack
        current[strlen(current) - 1] = '\0';
    }
}

// Main function to generate letter combinations
char** letterCombinations(char* digits, int* returnSize) {
    // Define the mapping of digits to letters
    char* mapping[] = {"", "", "abc", "def", "ghi", "jkl", "mno", "pqrs", "tuv",
"wxyz"};

    // Allocate space for the result
    char** result = (char**)malloc(sizeof(char*) * 1000);
    *returnSize = 0;

    // Check if the input is empty
    if (digits == NULL || *digits == '\0') {
        return result;
    }

    // Start the backtracking process
    char current[1000] = "";
    backtrack(result, digits, current, mapping, 0, returnSize);
}

```

```

        return result;
    }
int main() {
    char* digits = "23"; // Example input
    int returnSize;
    char** result = letterCombinations(digits, &returnSize);

    printf("Letter combinations for %s are:\n", digits);
    for (int i = 0; i < returnSize; i++) {
        printf("%s\n", result[i]);
        free(result[i]); // Free memory allocated for each combination
    }
    free(result); // Free memory allocated for the array of combinations

    return 0;
}

class Solution {
    HashMap<Character, String> hm = new HashMap<Character, String>();

    public void generate_words(String current_word, String digits, int current_index,
List<String> result) {
        if (current_index == digits.length()) {
            result.add(current_word);
            return;
        }

        String seq = hm.get(digits.charAt(current_index));

        for (int i = 0; i < seq.length(); i++) {
            generate_words(current_word+seq.charAt(i), digits, current_index+1, result);
        }
    }

    public void helper(String digits, List<String> result) {
        generate_words("", digits, 0, result);
    }
    public List<String> letterCombinations(String digits) {
        List<String> result = new ArrayList<String>();
        hm.put('2',"abc");
        hm.put('3',"def");
        hm.put('4',"ghi");
        hm.put('5',"jkl");
        hm.put('6',"mno");
        hm.put('7',"pqrs");
        hm.put('8',"tuv");
        hm.put('9',"wxyz");
        if (digits.length() == 0) return result;

```

```

    helper(digits,result);
    return result;
}
}

```

1.132 Find The Index Of The First Occurrence In The String (strstr – needle in haystack)

Given two strings needle and haystack, return the index of the first occurrence of needle in haystack, or -1 if needle is not part of haystack.

Example 1:

Input: haystack = "sadbutsad", needle = "sad"

Output: 0

Explanation: "sad" occurs at index 0 and 6.

The first occurrence is at index 0, so we return 0.

Example 2:

Input: haystack = "leetcode", needle = "leeto"

Output: -1

Explanation: "leeto" did not occur in "leetcode", so we return -1.

C:

```

int strStr(char * haystack, char * needle){
    int i = 0;
    int j = 0;
    int start = -1;
    while (i < strlen(haystack)) {
        if (haystack[i] == needle[j]) {
            if (start == -1) {
                start = i;
            }
            if (j == strlen(needle)-1) {
                return start;
            }
            i++;
            j++;
        }
        else {
            if (i == strlen(haystack)-1) {
                break;
            }
            i=start+1;
            start = i;
            j = 0;
        }
    }
}

```

```

        }
    }
    return -1;
}
int main() {
    char haystack[] = "hello";
    char needle[] = "ll";

    int index = strStr(haystack, needle);
    if (index != -1) {
        printf("Needle found at index: %d\n", index);
    } else {
        printf("Needle not found.\n");
    }

    return 0;
}

```

1.133 Best Time to Buy And Sell Stock II (Buy Sell Any Times)

You are given an integer array prices where prices[i] is the price of a given stock on the i^{th} day.

On each day, you may decide to buy and/or sell the stock. You can only hold **at most one** share of the stock at any time. However, you can buy it then immediately sell it on the **same day**.

Find and return *the maximum profit you can achieve*.

Example 1:

Input: prices = [7,1,5,3,6,4]

Output: 7

Explanation: Buy on day 2 (price = 1) and sell on day 3 (price = 5), profit = $5-1 = 4$.
 Then buy on day 4 (price = 3) and sell on day 5 (price = 6), profit = $6-3 = 3$.
 Total profit is $4 + 3 = 7$.

Example 2:

Input: prices = [1,2,3,4,5]

Output: 4

Explanation: Buy on day 1 (price = 1) and sell on day 5 (price = 5), profit = $5-1 = 4$.
 Total profit is 4.

Example 3:

Input: prices = [7,6,4,3,1]

Output: 0

Explanation: There is no way to make a positive profit, so we never buy the stock to achieve the maximum profit of 0.

C:

```
int maxProfit(int* prices, int pricesSize){  
    int i = 0;  
    int result = 0;  
    for (i = 1; i < pricesSize; i++) {  
        if (prices[i] > prices[i-1]) result+=(prices[i]-prices[i-1]);  
    }  
    return result;  
}  
  
int main() {  
    int prices[] = {7, 1, 5, 3, 6, 4};  
    int pricesSize = sizeof(prices) / sizeof(prices[0]);  
  
    int max_profit = maxProfit(prices, pricesSize);  
    printf("Max profit: %d\n", max_profit);  
  
    return 0;  
}
```

1.134 Intersection Of Two Arrays

Given two integer arrays `nums1` and `nums2`, return *an array of their intersection*. Each element in the result must be **unique** and you may return the result in **any order**.

Example 1:

Input: `nums1 = [1,2,2,1]`, `nums2 = [2,2]`
Output: `[2]`

Example 2:

Input: `nums1 = [4,9,5]`, `nums2 = [9,4,9,8,4]`
Output: `[9,4]`
Explanation: `[4,9]` is also accepted.

C:

```
int compare(const void* a, const void* b) {  
    return (*(int*)a - *(int*)b);  
}  
  
int* intersection(int* nums1, int nums1Size, int* nums2, int nums2Size, int* returnSize)  
{  
    qsort(nums1, nums1Size, sizeof(int), compare);  
    qsort(nums2, nums2Size, sizeof(int), compare);
```

```

int* result = (int*)malloc(sizeof(int) * (nums1Size + nums2Size));
*returnSize = 0;

int i = 0, j = 0;

while (i < nums1Size && j < nums2Size) {
    if (nums1[i] == nums2[j]) {
        // Add the common element to the result if it is not already present
        if (*returnSize == 0 || result[*returnSize - 1] != nums1[i]) {
            result[(*returnSize)++] = nums1[i];
        }
        i++;
        j++;
    } else if (nums1[i] < nums2[j]) {
        i++;
    } else {
        j++;
    }
}

return result;
}

int main() {
    // Example input arrays
    int nums1[] = {1, 2, 2, 1};
    int nums1Size = sizeof(nums1) / sizeof(nums1[0]);
    int nums2[] = {2, 2};
    int nums2Size = sizeof(nums2) / sizeof(nums2[0]);

    // Variables to store the result
    int returnSize;
    int* result = intersection(nums1, nums1Size, nums2, nums2Size, &returnSize);

    // Print the result
    printf("Intersection: ");
    for (int i = 0; i < returnSize; i++) {
        printf("%d ", result[i]);
    }
    printf("\n");

    // Free allocated memory
    free(result);

    return 0;
}

```

1.135 Climbing Stairs

You are climbing a staircase. It takes n steps to reach the top.

Each time you can either climb 1 or 2 steps. In how many distinct ways can you climb to the top?

Example 1:

Input: n = 2

Output: 2

Explanation: There are two ways to climb to the top.

1. 1 step + 1 step

2. 2 steps

Example 2:

Input: n = 3

Output: 3

Explanation: There are three ways to climb to the top.

1. 1 step + 1 step + 1 step

2. 1 step + 2 steps

3. 2 steps + 1 step

C:


```
int climbStairs(int n) {
    if (n == 0) return 0;
    if (n == 1) return 1;
    if (n == 2) return 2;
    int *result = (int *)malloc(sizeof(int)*(n+1));
    int i = 0;
    result[0] = 0;
    result[1] = 1;
    result[2] = 2;
    for (i = 3; i <= n; i++) {
        result[i] = result[i-1] + result[i-2];
    }
    return result[n];
}

int main() {
    int n = 5; // Example input: number of steps
    int ways = climbStairs(n);
    printf("Number of distinct ways to climb %d steps: %d\n", n, ways);
    return 0;
}
```

1.136 Convert Sorted Array To Binary Search Tree

binary search tree.


Example 1:




Input: nums = [-10,-3,0,5,9]

Output: [0,-3,9,-10,null,5]

Explanation: [0,-10,5,null,-3,null,9] is also accepted:



Example 2:



Input: nums = [1,3]

Output: [3,1]

Explanation: [1,null,3] and [3,1] are both height-balanced BSTs.

C:

/**

```

* Definition for a binary tree node.
* struct TreeNode {
*     int val;
*     struct TreeNode *left;
*     struct TreeNode *right;
* };
*/
struct TreeNode* helper(int* nums, int left, int right) {
    if (left > right)
        return NULL;

    int middle = (left + right) / 2;
    struct TreeNode* result = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    result->val = nums[middle];
    result->left = helper(nums, left, middle - 1);
    result->right = helper(nums, middle + 1, right);

    return result;
}

struct TreeNode* sortedArrayToBST(int* nums, int numsSize) {
    return helper(nums, 0, numsSize - 1);
}
int main() {
    int nums[] = {-10, -3, 0, 5, 9}; // Example sorted array
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Convert sorted array to binary search tree
    struct TreeNode* root = sortedArrayToBST(nums, numsSize);

    // Print the inorder traversal of the resulting binary search tree
    printf("Inorder traversal of the constructed BST: ");
    inorderTraversal(root);
    printf("\n");

    // Free dynamically allocated memory for the binary search tree
    // Note: This is optional in this example since it's a small program,
    // but it's good practice to free allocated memory in real applications.
    // You can implement a function to free the memory recursively.

    return 0;
}

```

1.137 Kth Largest Element In Array

Given an integer array `nums` and an integer `k`, return *the kth largest element in the array*.

Note that it is the kth largest element in the sorted order, not the kth distinct element.

Can you solve it without sorting?

Example 1:

Input: nums = [3,2,1,5,6,4], k = 2

Output: 5

Example 2:

Input: nums = [3,2,3,1,2,4,5,5,6], k = 4

Output: 4

C:

```
#include <stdio.h>
#include <stdlib.h>
#include <limits.h>

int findKthLargest(int* nums, int numsSize, int k) {
    if (numsSize == 1)
        return nums[0];

    // Find the minimum and maximum values in the array
    int min = INT_MAX, max = INT_MIN;
    for (int i = 0; i < numsSize; i++) {
        if (nums[i] > max)
            max = nums[i];
        if (nums[i] < min)
            min = nums[i];
    }
    printf("\nmin = %d and max = %d", min, max);

    // Create an array to store counts
    int range = max - min + 1;
    int* counts = (int*)malloc(range * sizeof(int));
    if (!counts) {
        printf("Memory allocation failed.\n");
        exit(1);
    }
    for (int i = 0; i < range; i++)
        counts[i] = 0;

    // Count occurrences of each number
    for (int i = 0; i < numsSize; i++) {
        counts[nums[i] - min]++;
        printf("\ncounts[%d] = %d", nums[i] - min, counts[nums[i] - min]);
    }
```

```

// Find the kth largest element
int len = range - 1;
while (k > 0) {
    if (counts[len] == 0) {
        printf("\nHere counts[%d] : %d = %d", counts[len], len);
        len--;
    }
    else {
        counts[len]--;
        printf("\nThere counts[%d] : %d = %d, k = %d", counts[len], len, k);
        k--;
    }
}
int result = len + min;
free(counts);
return result;
}

int main() {
    int nums[] = {3, 2, 1, 5, 6, 4};
    int numsSize = sizeof(nums) / sizeof(nums[0]);
    int k = 2;
    printf("Kth largest element is: %d\n", findKthLargest(nums, numsSize, k));
    return 0;
}

```

Time/Space Complexity:O(n)/O(n)

1.138 Kth Smallest Element In Array

```

#include <stdio.h>
#include <stdlib.h>
#include <limits.h>

int findKthSmallest(int* nums, int numsSize, int k) {
    if (numsSize == 1)
        return nums[0];

    // Find the minimum and maximum values in the array
    int max = INT_MIN;
    int min = INT_MAX;
    for (int i = 0; i < numsSize; i++) {
        if (nums[i] > max)
            max = nums[i];
        if (nums[i] < min)
            min = nums[i];
    }
    printf("\nmin = %d and max = %d", min, max);

```

```

// Create an array to store counts
int range = max - min + 1;
int* counts = (int*)malloc(range * sizeof(int));
if (!counts) {
    printf("Memory allocation failed.\n");
    exit(1);
}
for (int i = 0; i < range; i++) {
    counts[i] = 0;
}

// Count occurrences of each number
for (int i = 0; i < numsSize; i++) {
    counts[nums[i] - min]++;
    printf("\ncounts[%d] = %d", nums[i]-min,counts[nums[i] - min]);
}

// Find the kth smallest element
int len = 0;
while (k > 0) {
    if (counts[len] == 0) {
        printf("\nHere counts[%d] : %d = %d",counts[len],len);
        len++;
    } else {
        counts[len]--;
        printf("\nThere counts[%d] : %d = %d, k = %d",counts[len],len,k);
        k--;
    }
}
int result = len + min;
free(counts);
return result;
}


int main() {
    int nums[] = {3, 2, 1, 5, 6, 4};
    int numsSize = sizeof(nums) / sizeof(nums[0]);
    int k = 2;
    printf("Kth smallest element is: %d\n", findKthSmallest(nums, numsSize, k));
    return 0;
}
Time/Space Complexity:O(n)/O(n)

```

1.139 Binary Tree ZigZag Level Order Traversal

Given the root of a binary tree, return the zigzag level order traversal of its nodes' values, (i.e., from left to right, then right to left for the next level and alternate between).

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: [[3],[20,9],[15,7]]

Example 2:

Input: root = [1]

Output: [[1]]

Example 3:

Input: root = []

Output: []

C:

```
/**  
 * Definition for a binary tree node.  
 * public class TreeNode {  
 *     int val;  
 *     TreeNode left;  
 *     TreeNode right;  
 *     TreeNode() {}  
 *     TreeNode(int val) { this.val = val; }  
 *     TreeNode(int val, TreeNode left, TreeNode right) {  
 *         this.val = val;  
 *         this.left = left;
```

```

        *      this.right = right;
        *
        */
    }

    class Solution {
        public List<List<Integer>> zigzagLevelOrder(TreeNode root) {
            List<List<Integer>> levels = new ArrayList<List<Integer>>();
            if (root == null) return levels;

            Queue<TreeNode> queue = new LinkedList<TreeNode>();
            queue.add(root);
            int level = 0;
            while ( !queue.isEmpty() ) {
                // start the current level
                levels.add(new ArrayList<Integer>());

                // number of elements in the current level
                int level_length = queue.size();

                for(int i = 0; i < level_length; ++i) {
                    TreeNode node = queue.remove();

                    // fulfill the current level
                    levels.get(level).add(node.val);

                    // add child nodes of the current level
                    // in the queue for the next level
                    if (node.left != null) queue.add(node.left);
                    if (node.right != null) queue.add(node.right);
                }
                // go to next level
                level++;
            }
            for (int i = 0; i < levels.size(); i++) {
                if (i % 2 == 1) {
                    Collections.reverse(levels.get(i));
                }
            }
        }
        return levels;
    }
}
/** 
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */

```

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 calls free().
 */
// Function to get the height of a binary tree
int getHeight(struct TreeNode* root) {
    if (root == NULL) {
        return 0;
    }

    int leftHeight = getHeight(root->left);
    int rightHeight = getHeight(root->right);

    return 1 + (leftHeight > rightHeight ? leftHeight : rightHeight);
}

// Function to perform zigzag level order traversal of a binary tree
void zigzagTraversalHelper(struct TreeNode* root, int** result, int level, int*
returnColumnSizes) {
    if (root == NULL) {
        return;
    }

    // Determine the index based on the level and whether it's a zigzag or normal level
    int index = (level % 2 == 0) ? level : (returnColumnSizes[level] - 1 - level);

    // Add the current node's value to the result array
    result[level][index] = root->val;

    // Recursively traverse the left and right subtrees
    zigzagTraversalHelper(root->left, result, level + 1, returnColumnSizes);
    zigzagTraversalHelper(root->right, result, level + 1, returnColumnSizes);
}

// Function to perform zigzag level order traversal and return the result as a 2D array
int** zigzagLevelOrder(struct TreeNode* root, int* returnSize, int** returnColumnSizes)
{
    // Get the height of the binary tree
    int height = getHeight(root);

    // Allocate memory for the result array
    int** result = (int**)malloc(height * sizeof(int*));
    *returnColumnSizes = (int*)malloc(height * sizeof(int));

    // Initialize the return size and column sizes
    *returnSize = height;
    for (int i = 0; i < height; i++) {

```

```

        int levelSize = 1 << i; // Number of nodes at the current level
        result[i] = (int*)malloc(levelSize * sizeof(int));
        (*returnColumnSizes)[i] = levelSize;
    }

    // Perform zigzag level order traversal
    zigzagTraversalHelper(root, result, 0, *returnColumnSizes);

    return result;
}

// Function to create a new binary tree node with the given value
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

```

1.140 Find Minimum In Rotated Sorted Array

Suppose an array of length n sorted in ascending order is **rotated** between 1 and n times. For example, the array nums = [0,1,2,4,5,6,7] might become:

- [4,5,6,7,0,1,2] if it was rotated 4 times.
- [0,1,2,4,5,6,7] if it was rotated 7 times.

Notice that **rotating** an array [a[0], a[1], a[2], ..., a[n-1]] 1 time results in the array [a[n-1], a[0], a[1], a[2], ..., a[n-2]].

Given the sorted rotated array nums of **unique** elements, return *the minimum element of this array*.

You must write an algorithm that runs in O(log n) time.

Example 1:

Input: nums = [3,4,5,1,2]

Output: 1

Explanation: The original array was [1,2,3,4,5] rotated 3 times.

Example 2:

Input: nums = [4,5,6,7,0,1,2]

Output: 0

Explanation: The original array was [0,1,2,4,5,6,7] and it was rotated 4 times.

Example 3:

Input: nums = [11,13,15,17]

Output: 11

Explanation: The original array was [11,13,15,17] and it was rotated 4 times.

C:

```
int findMin(int* nums, int numsSize) {
    // If the list has just one element then return that element.
    if (numsSize == 1) {
        return nums[0];
    }

    // Initializing left and right pointers.
    int left = 0, right = numsSize - 1;

    // If the last element is greater than the first element, then there is no rotation.
    // Already sorted array. Hence the smallest element is the first element. A[0]
    if (nums[right] > nums[0]) {
        return nums[0];
    }

    // Binary search
    while (left <= right) {
        // Find the mid element
        int mid = left + (right - left) / 2;

        // If the mid element is greater than its next element, then mid+1 element is
        // the smallest.
        // This point would be the point of change. From higher to lower value.
        if (nums[mid] > nums[mid + 1]) {
            return nums[mid + 1];
        }

        // If the mid element is lesser than its previous element, then mid element is
        // the smallest.
        if (nums[mid - 1] > nums[mid]) {
            return nums[mid];
        }

        // If the mid element's value is greater than the 0th element, this means
        // the least value is still somewhere to the right, as we are still dealing with
        // elements greater than nums[0].
        if (nums[mid] > nums[0]) {
            left = mid + 1;
        } else {
```

```

        // If nums[0] is greater than the mid value, then this means the smallest
value
        // is somewhere to the left.
        right = mid - 1;
    }
}
return INT_MAX;
}
int main() {
    int nums[] = {4, 5, 6, 7, 0, 1, 2}; // Example rotated sorted array
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Find the minimum element in the rotated sorted array
    int minElement = findMin(nums, numsSize);

    // Print the result
    printf("The minimum element in the rotated sorted array is: %d\n", minElement);

    return 0;
}

```

1.141 Binary Search

Given an array of integers nums which is sorted in ascending order, and an integer target, write a function to search target in nums. If target exists, then return its index. Otherwise, return -1.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: nums = [-1,0,3,5,9,12], target = 9
Output: 4
Explanation: 9 exists in nums and its index is 4

Example 2:

Input: nums = [-1,0,3,5,9,12], target = 2
Output: -1
Explanation: 2 does not exist in nums so return -1

C:

```

int search(int* nums, int numsSize, int target) {
    int left = 0;
    int right = numsSize - 1;

    while (left <= right) {

```

```

        int mid = left + (right - left) / 2;

        if (nums[mid] == target) {
            return mid; // Target found
        } else if (nums[mid] < target) {
            left = mid + 1; // Target may be in the right half
        } else {
            right = mid - 1; // Target may be in the left half
        }
    }
    return -1;
}
int main() {
    int nums[] = {1, 3, 5, 7, 9, 11, 13}; // Sorted array
    int numsSize = sizeof(nums) / sizeof(nums[0]);
    int target = 7;

    // Search for the target in the array
    int result = search(nums, numsSize, target);

    // Print the result
    if (result != -1) {
        printf("Target %d found at index %d\n", target, result);
    } else {
        printf("Target %d not found in the array\n", target);
    }


    return 0;
}

```

1.142 Construct Binary Tree From PreOrder And Inorder Traversal

Given two integer arrays preorder and inorder where preorder is the preorder traversal of a binary tree and inorder is the inorder traversal of the same tree, construct and return *the binary tree*.

Example 1:



Input: preorder = [3,9,20,15,7], inorder = [9,3,15,20,7]

Output: [3,9,20,null,null,15,7]

Example 2:

Input: preorder = [-1], inorder = [-1]

Output: [-1]

C:

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
struct TreeNode* buildTreeHelper(int* preorder, int preStart, int preEnd, int* inorder,
int inStart, int inEnd) {
    if (preStart > preEnd || inStart > inEnd) {
        return NULL;
    }

    // The first element in preorder is the root of the current subtree
    struct TreeNode* root = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->val = preorder[preStart];
    root->left = root->right = NULL;

    // Find the index of the root in inorder
  
```

```

int rootIndex;
for (rootIndex = inStart; rootIndex <= inEnd; rootIndex++) {
    if (inorder[rootIndex] == root->val) {
        break;
    }
}

// Calculate the number of elements in the left subtree
int leftSubtreeSize = rootIndex - inStart;

// Recursively build the left and right subtrees
root->left = buildTreeHelper(preorder, preStart + 1, preStart + leftSubtreeSize,
inorder, inStart, rootIndex - 1);
root->right = buildTreeHelper(preorder, preStart + leftSubtreeSize + 1, preEnd,
inorder, rootIndex + 1, inEnd);

return root;
}

struct TreeNode* buildTree(int* preorder, int preorderSize, int* inorder, int
inorderSize) {
    return buildTreeHelper(preorder, 0, preorderSize - 1, inorder, 0, inorderSize - 1);
}
int main() {
    int preorder[] = {3, 9, 20, 15, 7};
    int preorderSize = sizeof(preorder) / sizeof(preorder[0]);
    int inorder[] = {9, 3, 15, 20, 7};
    int inorderSize = sizeof(inorder) / sizeof(inorder[0]);

    // Build the binary tree
    struct TreeNode* root = buildTree(preorder, preorderSize, inorder, inorderSize);

    // Print the inorder traversal of the binary tree
    printf("Inorder traversal: ");
    printInorder(root);
    printf("\n");


    return 0;
}

```

1.143 Remove Nth Node From End Of List

Given the head of a linked list, remove the n^{th} node from the end of the list and return its head.

Example 1:



Input: head = [1,2,3,4,5], n = 2

Output: [1,2,3,5]

Example 2:

Input: head = [1], n = 1

Output: []

Example 3:

Input: head = [1,2], n = 1

Output: [1]

C:

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */
struct ListNode* removeNthFromEnd(struct ListNode* head, int n){
    struct ListNode *curr = head;
    struct ListNode *d = head;

    for (int i = 0; i < n; i++) {
        curr = curr->next;
    }
    if (curr == NULL) return head->next;
    while (curr->next != NULL) {
        d = d->next;
        curr = curr->next;
    }
}

```

```

        struct ListNode *del = d->next;
        d->next = d->next->next;
        free(del);
        return head;
    /*
        struct ListNode *fast = head, *slow = head;
        for (int i = 0; i < n; i++) fast = fast->next;
        if (fast == NULL) return head->next;
        while (fast->next) fast = fast->next, slow = slow->next;
        slow->next = slow->next->next;
        return head;
    */
}
int main() {
    // Create a sample linked list
    struct ListNode* head = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->val = 1;
    head->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->val = 2;
    head->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->next->val = 3;
    head->next->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->next->next->val = 4;
    head->next->next->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->next->next->next->val = 5;
    head->next->next->next->next->next = NULL;

    printf("Original linked list: ");
    printList(head);

    // Remove the 2nd node from the end
    int n = 2;
    head = removeNthFromEnd(head, n);

    printf("Linked list after removing %d node from the end: ", n);
    printList(head);

    // Free memory allocated for the linked list
    struct ListNode* temp;
    while (head != NULL) {
        temp = head;
        head = head->next;
        free(temp);
    }

    return 0;
}

```

1.144 Jump Game

You are given an integer array `nums`. You are initially positioned at the array's **first index**, and each element in the array represents your maximum jump length at that position.

Return true *if you can reach the last index, or* false *otherwise*.

Example 1:

Input: `nums = [2,3,1,1,4]`

Output: true

Explanation: Jump 1 step from index 0 to 1, then 3 steps to the last index.

Example 2:

Input: `nums = [3,2,1,0,4]`

Output: false

Explanation: You will always arrive at index 3 no matter what. Its maximum jump length is 0, which makes it impossible to reach the last index.

```
class Solution {
    public boolean canJump(int[] nums) {
        int target = nums.length-1;
        for (int i = nums.length-2; i >= 0; i--) {
            if (i+nums[i] >= target) target = i;
        }
        return (target == 0);
    }
    bool canJump(int* nums, int numsSize) {
        int maxReach = 0;

        for (int i = 0; i < numsSize; i++) {
            // If the current index is beyond the furthest position we can reach
            if (i > maxReach) {
                return false;
            }

            // Update the furthest position we can reach
            maxReach = (i + nums[i]) > maxReach ? (i + nums[i]) : maxReach;

            // If we can reach the last index, return true
            if (maxReach >= numsSize - 1) {
                return true;
            }
        }

        return false;
    }
}
```

```

}

int main() {
    int nums[] = {2, 3, 1, 1, 4};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Test Java solution
    printf("Java solution: %s\n", canJumpJava(nums, numsSize) ? "true" : "false");

    // Test C solution
    printf("C solution: %s\n", canJump(nums, numsSize) ? "true" : "false");

    return 0;
}

```

1.145 Insert Delete GetRandom O(1)

Implement the RandomizedSet class:

- RandomizedSet() Initializes the RandomizedSet object.
- bool insert(int val) Inserts an item val into the set if not present. Returns true if the item was not present, false otherwise.
- bool remove(int val) Removes an item val from the set if present. Returns true if the item was present, false otherwise.
- int getRandom() Returns a random element from the current set of elements (it's guaranteed that at least one element exists when this method is called). Each element must have the **same probability** of being returned.

You must implement the functions of the class such that each function works in **average** O(1) time complexity.

Example 1:

Input

["RandomizedSet", "insert", "remove", "insert", "getRandom", "remove", "insert", "getRandom"]
 [], [1], [2], [2], [], [1], [2], []]

Output

[null, true, false, true, 2, true, false, 2]

Explanation

```

RandomizedSet randomizedSet = new RandomizedSet();
randomizedSet.insert(1); // Inserts 1 to the set. Returns true as 1 was inserted successfully.
randomizedSet.remove(2); // Returns false as 2 does not exist in the set.
randomizedSet.insert(2); // Inserts 2 to the set, returns true. Set now contains [1,2].
randomizedSet.getRandom(); // getRandom() should return either 1 or 2 randomly.
randomizedSet.remove(1); // Removes 1 from the set, returns true. Set now contains [2].
randomizedSet.insert(2); // 2 was already in the set, so return false.
randomizedSet.getRandom(); // Since 2 is the only number in the set, getRandom() will always return 2.

```

```

// Define the structure for RandomizedSet
typedef struct {
    int* dict; // Map (dictionary) to store the index of each value
    int* list; // List to store the elements
    int size; // Current size of the list
    int capacity; // Capacity of the list
} RandomizedSet;

// Function to initialize RandomizedSet
RandomizedSet* randomizedSetCreate() {
    RandomizedSet* set = (RandomizedSet*)malloc(sizeof(RandomizedSet));
    set->dict = (int*)calloc(1000, sizeof(int)); // Assuming values are in the range
[0, 999]
    set->list = (int*)malloc(sizeof(int) * 1000); // Assuming initial capacity is 1000
    set->size = 0;
    set->capacity = 1000;
    return set;
}

// Function to insert a value into RandomizedSet
bool randomizedSetInsert(RandomizedSet* obj, int val) {
    if (obj->dict[val] != 0) {
        return false; // Value already exists
    }

    if (obj->size == obj->capacity) {
        // Resize the list if needed
        obj->capacity *= 2;
        obj->list = realloc(obj->list, sizeof(int) * obj->capacity);
    }

    obj->dict[val] = obj->size + 1; // Adding 1 to differentiate from zero (0 indicates
not present)
    obj->list[obj->size] = val;
    obj->size++;
    return true;
}

// Function to remove a value from RandomizedSet
bool randomizedSetRemove(RandomizedSet* obj, int val) {
    if (obj->dict[val] == 0) {
        return false; // Value not present
    }

    int lastElement = obj->list[obj->size - 1];
    int idx = obj->dict[val] - 1; // Subtracting 1 to get the actual index
    obj->list[idx] = lastElement;
    obj->dict[lastElement] = idx + 1; // Update the index of the swapped value
    obj->size--;
}

```

```

        obj->dict[val] = 0; // Marking the value as not present
    return true;
}

// Function to get a random element from RandomizedSet
int randomizedSetGetRandom(RandomizedSet* obj) {
    int randomIndex = rand() % obj->size;
    return obj->list[randomIndex];
}

// Function to free the memory used by RandomizedSet
void randomizedSetFree(RandomizedSet* obj) {
    free(obj->dict);
    free(obj->list);
    free(obj);
}
int main() {
    // Test the RandomizedSet functionality
    RandomizedSet* obj = randomizedSetCreate();

    // Inserting values
    printf("Inserting elements...\n");
    randomizedSetInsert(obj, 1);
    randomizedSetInsert(obj, 2);
    randomizedSetInsert(obj, 3);

    // Printing elements
    printf("Current elements in RandomizedSet: ");
    for (int i = 0; i < obj->size; i++) {
        printf("%d ", obj->list[i]);
    }
    printf("\n");

    // Removing an element
    printf("Removing element 2...\n");
    randomizedSetRemove(obj, 2);

    // Printing elements after removal
    printf("Current elements in RandomizedSet after removal: ");
    for (int i = 0; i < obj->size; i++) {
        printf("%d ", obj->list[i]);
    }
    printf("\n");

    // Getting a random element
    printf("Random element: %d\n", randomizedSetGetRandom(obj));

    // Freeing memory
    randomizedSetFree(obj);
}

```

```

        return 0;
    }

/**
 * Your RandomizedSet struct will be instantiated and called as such:
 * RandomizedSet* obj = randomizedSetCreate();
 * bool param_1 = randomizedSetInsert(obj, val);

 * bool param_2 = randomizedSetRemove(obj, val);

 * int param_3 = randomizedSetGetRandom(obj);

 * randomizedSetFree(obj);
 */

```

1.146 Daily Temperatures

Given an array of integers temperatures represents the daily temperatures, return *an array* answer *such that* answer[i] *is the number of days you have to wait after the ith day to get a warmer temperature*. If there is no future day for which this is possible, keep answer[i] == 0 instead.

Example 1:

Input: temperatures = [73,74,75,71,69,72,76,73]
Output: [1,1,4,2,1,1,0,0]

Example 2:

Input: temperatures = [30,40,50,60]
Output: [1,1,1,0]

Example 3:

Input: temperatures = [30,60,90]
Output: [1,1,0]

```

/** 
 * Note: The returned array must be malloced, assume caller calls free().
 */


```

```

int* dailyTemperatures(int* temperatures, int temperaturesSize, int* returnSize) {
    int* result = (int*)malloc(sizeof(int) * temperaturesSize);
    *returnSize = temperaturesSize;

    int* stack = (int*)malloc(sizeof(int) * temperaturesSize);
    int top = -1;

```

```

        for (int i = 0; i < temperaturesSize; i++) {
            // Check if the current temperature is greater than the temperature at the top
            // of the stack
            while (top >= 0 && temperatures[i] > temperatures[stack[top]]) {
                int prevIndex = stack[top--];
                result[prevIndex] = i - prevIndex;
            }

            // Push the current index onto the stack
            stack[++top] = i;
        }

        // Remaining elements in the stack have no warmer days
        while (top >= 0) {
            result[stack[top--]] = 0;
        }

        free(stack);
        return result;
    }

int main() {
    int temperatures[] = {73, 74, 75, 71, 69, 72, 76, 73};
    int temperaturesSize = sizeof(temperatures) / sizeof(temperatures[0]);
    int returnSize = 0;

    int* result = dailyTemperatures(temperatures, temperaturesSize, &returnSize);

    printf("Result: ");
    for (int i = 0; i < returnSize; i++) {
        printf("%d ", result[i]);
    }
    printf("\n");

    free(result);

    return 0;
}

```

1.147 Reverse Integer

Given a signed 32-bit integer x , return x *with its digits reversed*. If reversing x causes the value to go outside the signed 32-bit integer range $[-2^{31}, 2^{31} - 1]$, then return 0.

Assume the environment does not allow you to store 64-bit integers (signed or unsigned).

Example 1:**Input:** x = 123**Output:** 321**Example 2:****Input:** x = -123**Output:** -321**Example 3:****Input:** x = 120**Output:** 21


```
class Solution {
    public int reverse(int x) {
        int rev = 0;
        while (x != 0) {
            int pop = x % 10;
            x /= 10;
            if (rev > Integer.MAX_VALUE/10 || (rev == Integer.MAX_VALUE / 10 && pop > 7)) return 0;
            if (rev < Integer.MIN_VALUE/10 || (rev == Integer.MIN_VALUE / 10 && pop < -8)) return 0;
            rev = rev * 10 + pop;
        }
        return rev;
    }
    int main() {
        int num = 123;
        int reversed = reverse(num);
        printf("Reversed: %d\n", reversed);

        return 0;
    }
}
```

1.148 Symmetric Tree

Given the root of a binary tree, *check whether it is a mirror of itself* (i.e., symmetric around its center).


Example 1:



Input: root = [1,2,2,3,4,4,3]

Output: true

Example 2:



Input: root = [1,2,2,null,3,null,3]

Output: false

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
```

```

bool isSymmetric(struct TreeNode* root){
    if (root == NULL) {
        return true;
    }

    struct TreeNode* stack[200];
    int top = -1;
    stack[++top] = root;
    stack[++top] = root;

    while (top >= 0) {
        struct TreeNode* left = stack[top--];
        struct TreeNode* right = stack[top--];

        if (left == NULL && right == NULL) {
            continue;
        }

        if (left == NULL || right == NULL) {
            return false;
        }

        if (left->val != right->val) {
            return false;
        }

        stack[++top] = left->left;
        stack[++top] = right->right;
        stack[++top] = left->right;
        stack[++top] = right->left;
    }

    return true;
}

int main() {
    // Create a test binary tree
    struct TreeNode* root = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->val = 1;
    root->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->left->val = 2;
    root->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->right->val = 2;
    root->left->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->left->left->val = 3;
    root->left->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->left->right->val = 4;
    root->right->left = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    root->right->left->val = 4;
    root->right->right = (struct TreeNode*)malloc(sizeof(struct TreeNode));
}

```

```

root->right->right->val = 3;
root->left->left->left = NULL;
root->left->left->right = NULL;
root->left->right->left = NULL;
root->left->right->right = NULL;
root->right->left->left = NULL;
root->right->left->right = NULL;
root->right->right->left = NULL;
root->right->right->right = NULL;

// Check if the binary tree is symmetric
bool symmetric = isSymmetric(root);
if (symmetric) {
    printf("The binary tree is symmetric.\n");
} else {
    printf("The binary tree is not symmetric.\n");
}

// Free memory allocated for the binary tree
free(root->left->left);
free(root->left->right);
free(root->right->left);
free(root->right->right);
free(root->left);
free(root->right);
free(root);

return 0;
}


```

1.149 Lowest Common Ancestor Of A binary tree

Given a binary tree, find the lowest common ancestor (LCA) of two given nodes in the tree.

According to the [definition of LCA on Wikipedia](#): "The lowest common ancestor is defined between two nodes p and q as the lowest node in T that has both p and q as descendants (where we allow a node to be a descendant of itself)."

Example 1:




Input: root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 1

Output: 3

Explanation: The LCA of nodes 5 and 1 is 3.

Example 2:



Input: root = [3,5,1,6,2,0,8,null,null,7,4], p = 5, q = 4

Output: 5

Explanation: The LCA of nodes 5 and 4 is 5, since a node can be a descendant of itself according to the LCA definition.

Example 3:

Input: root = [1,2], p = 1, q = 2

Output: 1

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
struct TreeNode* lowestCommonAncestor(struct TreeNode* root, struct TreeNode* p, struct
TreeNode* q) {
    // Base case: If the current node is null or matches either p or q, return the
    current node
    if (!root || root == p || root == q) {

```

```

        return root;
    }

    // Recursive calls to find the LCA in the left and right subtrees
    struct TreeNode* leftLCA = lowestCommonAncestor(root->left, p, q);
    struct TreeNode* rightLCA = lowestCommonAncestor(root->right, p, q);

    // If both left and right subtrees have a result, the current node is the LCA
    if (leftLCA && rightLCA) {
        return root;
    }

    // If only one subtree has a result, propagate it upward
    return (leftLCA != NULL) ? leftLCA : rightLCA;
}

int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(3);
    root->left = newNode(5);
    root->right = newNode(1);
    root->left->left = newNode(6);
    root->left->right = newNode(2);
    root->left->right->left = newNode(7);
    root->left->right->right = newNode(4);
    root->right->left = newNode(0);
    root->right->right = newNode(8);

    // Define the nodes p and q
    struct TreeNode* p = root->left;
    struct TreeNode* q = root->right;

    // Find the lowest common ancestor of p and q
    struct TreeNode* lca = lowestCommonAncestor(root, p, q);

    // Print the value of the lowest common ancestor
    printf("Lowest Common Ancestor of %d and %d is %d\n", p->val, q->val, lca->val);

    // Free memory allocated for the binary tree
    free(root->left->left);
    free(root->left->right->left);
    free(root->left->right->right);
    free(root->left->right);
    free(root->left);
    free(root->right->left);
    free(root->right->right);
    free(root->right);
    free(root);

    return 0;
}

```

}

1.150 Merge K Sorted Lists

You are given an array of k linked-lists lists, each linked-list is sorted in ascending order.

Merge all the linked-lists into one sorted linked-list and return it.

Example 1:

Input: lists = [[1,4,5],[1,3,4],[2,6]]

Output: [1,1,2,3,4,4,5,6]

Explanation: The linked-lists are:

```
[  
    1->4->5,  
    1->3->4,  
    2->6  
]
```

merging them into one sorted list:

1->1->2->3->4->4->5->6

Example 2:

Input: lists = []

Output: []

Example 3:

Input: lists = [[]]

Output: []

```
/**  
 * Definition for singly-linked list.  
 * struct ListNode {  
 *     int val;  
 *     struct ListNode *next;  
 * };  
 */  
/**  
 * Definition for singly-linked list.  
 * struct ListNode {  
 *     int val;  
 *     struct ListNode *next;  
 * };  
 */
```

```

struct ListNode* mergeKLists(struct ListNode** lists, int listsSize){
    int i = 0;
    int count = 0;
    int arr[10000];
    int temp = 0;
    int j = 0;

    for (i = 0; i < listsSize; i++) {
        while(lists[i]!=NULL) {
            arr[count] = lists[i]->val;
            count++;
            lists[i] = lists[i]->next;
        }
    }
    if (count == 0) return NULL;
    for(i = 0 ; i < count; i++) {
        for (j = i+1; j < count; j++) {
            if (arr[i] > arr[j]) {
                temp = arr[i];
                arr[i] = arr[j];
                arr[j] = temp;
            }
        }
    }
    struct ListNode *result = (struct ListNode*)malloc(sizeof(struct ListNode));
    struct ListNode *head;
    head = result;

    for(i = 0 ; i < count; i++) {

        result->val = arr[i];
        result->next = NULL;

        if (i!=count-1) {
            result->next = (struct ListNode*)malloc(sizeof(struct ListNode));
            result = result->next;
        }
        else {
            result->next = NULL;
        }
    }

    return head;
}
int main() {
    // Create three sorted linked lists
}

```

```

struct ListNode* newNode(int val) {
    struct ListNode* node = malloc(sizeof(ListNode));
    node->val = val;
    node->next = NULL;
    return node;
}

struct ListNode* mergeKLists(struct ListNode** lists, int k) {
    if (k == 1) return lists[0];
    if (k == 0) return NULL;
    int i = 0;
    int j = 1;
    int minIndex = 0;
    int minValue = lists[0]->val;
    while (j < k) {
        if (lists[i]->val < minValue) {
            minValue = lists[i]->val;
            minIndex = i;
        }
        i++;
        j++;
    }
    return mergeKLists(listNode(minValue), lists[minIndex], k - 1);
}

int main() {
    struct ListNode* list1 = newNode(1);
    list1->next = newNode(4);
    list1->next->next = newNode(5);

    struct ListNode* list2 = newNode(1);
    list2->next = newNode(3);
    list2->next->next = newNode(4);

    struct ListNode* list3 = newNode(2);
    list3->next = newNode(6);

    // Store the lists in an array
    struct ListNode* lists[] = {list1, list2, list3};

    // Merge the lists
    struct ListNode* mergedList = mergeKLists(lists, 3);

    // Print the merged list
    printf("Merged List: ");
    struct ListNode* temp = mergedList;
    while (temp != NULL) {
        printf("%d ", temp->val);
        temp = temp->next;
    }
    printf("\n");

    // Free memory allocated for the lists
    free(list1->next->next);
    free(list1->next);
    free(list1);
    free(list2->next->next);
    free(list2->next);
    free(list2);
    free(list3->next);
    free(list3);

    // Free memory allocated for the merged list
    while (mergedList != NULL) {
        struct ListNode* nextNode = mergedList->next;
        free(mergedList);
        mergedList = nextNode;
    }

    return 0;
}

```

1.151 SubSets

Given an integer array nums of **unique** elements, return *all possible*

subsets
(the power set).

The solution set **must not** contain duplicate subsets. Return the solution in **any order**.



Example 1:

Input: nums = [1,2,3]
Output: [[], [1], [2], [1,2], [3], [1,3], [2,3], [1,2,3]]

Example 2:

Input: nums = [0]
Output: [[], [0]]

```
// Function to count the number of set bits in an integer
int countSetBits(int n) {
    int count = 0;
    while (n) {
        count += n & 1;
        n >>= 1;
    }
    return count;
}

int** subsets(int* nums, int numsSize, int* returnSize, int** returnColumnSizes) {
    // Calculate the total number of subsets (2^n)
    int totalSubsets = 1 << numsSize;

    // Allocate memory for the result array
    int** result = (int**)malloc(totalSubsets * sizeof(int*));
    *returnColumnSizes = (int*)malloc(totalSubsets * sizeof(int));
    *returnSize = 0;

    // Iterate through all numbers from 0 to 2^n - 1
    for (int i = 0; i < totalSubsets; i++) {
        // Calculate the size of the current subset
        int subsetSize = countSetBits(i);

        // Allocate memory for the current subset
        result[*returnSize] = (int*)malloc(subsetSize * sizeof(int));
        (*returnColumnSizes)[*returnSize] = subsetSize;

        // Fill in the subset based on set bits in the binary representation of i
        int index = 0;
        for (int j = 0; j < numsSize; j++) {
            if ((i >> j) & 1) {
                result[*returnSize][index++] = nums[j];
            }
        }
    }
}
```

```

        }
    }

    (*returnSize)++;
}

return result;
}

int main() {
    int nums[] = {1, 2, 3};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int returnSize;
    int* returnColumnSizes;

    int** result = subsets(nums, numsSize, &returnSize, &returnColumnSizes);

    printf("Number of subsets: %d\n", returnSize);
    printf("Subsets:\n");
    for (int i = 0; i < returnSize; i++) {
        printf("[");
        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d", result[i][j]);
            if (j < returnColumnSizes[i] - 1) {
                printf(", ");
            }
        }
        printf("]\n");
    }

    // Free memory allocated for subsets
    freeSubsets(result, returnSize, returnColumnSizes);

    return 0;
}

```

1.152 Can Place Flowers

You have a long flowerbed in which some of the plots are planted, and some are not. However, flowers cannot be planted in adjacent plots.

Given an integer array flowerbed containing 0's and 1's, where 0 means empty and 1 means not empty, and an integer n, return true if n new flowers can be planted in the flowerbed without violating the no-adjacent-flowers rule and false otherwise.

Example 1:

Input: flowerbed = [1,0,0,0,1], n = 1
Output: true

Example 2:

Input: flowerbed = [1,0,0,0,1], n = 2
Output: false

```
bool canPlaceFlowers(int* flowerbed, int flowerbedSize, int n) {
    int count = 0;
    if (flowerbedSize == 0) return false;
    for (int i = 0; i < flowerbedSize; i++) {
        if (flowerbed[i] == 0) {
            if (i == 0) {
                if (i == flowerbedSize-1) {
                    count++;
                    break;
                }
                if (flowerbed[i+1] != 1) {
                    flowerbed[i] = 1;
                    count++;
                    //i++;
                }
            } else if (i != flowerbedSize-1) {
                if (flowerbed[i-1] != 1 && flowerbed[i+1] != 1) {
                    flowerbed[i] = 1;
                    count++;
                    //i++;
                }
            } else {
                if (flowerbed[i-1] != 1) {
                    flowerbed[i] = 1;
                    count++;
                    //i++;
                }
            }
        }
    }
    if (count >= n) return true;
    else return false;
}

int main() {
    int flowerbed[] = {1, 0, 0, 0, 1};
    int flowerbedSize = sizeof(flowerbed) / sizeof(flowerbed[0]);
    int n = 1;

    bool result = canPlaceFlowers(flowerbed, flowerbedSize, n);

    printf("Can place %d flowers: %s\n", n, result ? "true" : "false");
}
```

```
    return 0;
}
```

1.153 Roman To Integer

Roman numerals are represented by seven different symbols: I, V, X, L, C, D and M.

Symbol	Value
I	1
V	5
X	10
L	50
C	100
D	500
M	1000

For example, 2 is written as II in Roman numeral, just two ones added together. 12 is written as XII, which is simply X + II. The number 27 is written as XXVII, which is XX + V + II.

Roman numerals are usually written largest to smallest from left to right. However, the numeral for four is not IIII. Instead, the number four is written as IV. Because the one is before the five we subtract it making four. The same principle applies to the number nine, which is written as IX. There are six instances where subtraction is used:

- I can be placed before V (5) and X (10) to make 4 and 9.
- X can be placed before L (50) and C (100) to make 40 and 90.
- C can be placed before D (500) and M (1000) to make 400 and 900.

Given a roman numeral, convert it to an integer.

Example 1:

Input: s = "III"

Output: 3

Explanation: III = 3.

Example 2:

Input: s = "LVIII"

Output: 58

Explanation: L = 50, V= 5, III = 3.

Example 3:

```
int romanToInt(char * s){
    int result = 0;
    int i = 0;
```

```

// Create a lookup table for Roman numerals
char roman[7] = {'I', 'V', 'X', 'L', 'C', 'D', 'M'};
int value[7] = {1, 5, 10, 50, 100, 500, 1000};
int length = strlen(s);

for (i = 0; i < length; i++) {
    // Find the corresponding value for the current Roman numeral
    int current = 0;
    for (int j = 0; j < 7; j++) {
        if (s[i] == roman[j]) {
            current = value[j];
            break;
        }
    }

    // Check if subtraction is required
    if (i < length - 1) {
        int next = 0;
        for (int j = 0; j < 7; j++) {
            if (s[i+1] == roman[j]) {
                next = value[j];
                break;
            }
        }

        if (current < next) {
            result += (next - current);
            i++;
            continue;
        }
    }
}

// Add the current value to the result
result += current;
}

return result;
}
int main() {
    char romanNumeral[] = "MCMXCIV";

    int result = romanToInt(romanNumeral);

    printf("The integer value of %s is: %d\n", romanNumeral, result);

    return 0;
}

```

1.154 Find The Duplicate Number

Given an array of integers `nums` containing $n + 1$ integers where each integer is in the range $[1, n]$ inclusive.

There is only **one repeated number** in `nums`, return *this repeated number*.

You must solve the problem **without** modifying the array `nums` and uses only constant extra space.

Example 1:

Input: `nums = [1,3,4,2,2]`

Output: `2`

Example 2:

Input: `nums = [3,1,3,4,2]`

Output: `3`

```
int findDuplicate(int* nums, int numsSize) {
    if (nums == NULL || numsSize <= 1) {
        // Handle invalid input
        return -1;
    }

    int slow = nums[0];
    int fast = nums[0];

    // Phase 1: Find the intersection point of the two pointers
    do {
        slow = nums[slow];
        fast = nums[nums[fast]];
    } while (slow != fast);

    // Phase 2: Find the entrance to the cycle
    slow = nums[0];
    while (slow != fast) {
        slow = nums[slow];
        fast = nums[fast];
    }
}

int main() {
    int nums[] = {1, 3, 4, 2, 2};

    int duplicate = findDuplicate(nums, sizeof(nums) / sizeof(nums[0]));
}
```

```

    printf("The duplicate number is: %d\n", duplicate);

    return 0;
}

```

1.155 Product Of Array Except Self

Given an integer array nums, return **an array** answer **such that** answer[i] **is equal to the product of all the elements of** nums **except** nums[i].

The product of any prefix or suffix of nums is **guaranteed** to fit in a **32-bit** integer.

You must write an algorithm that runs in O(n) time and without using the division operation.

Example 1:

Input: nums = [1,2,3,4]
Output: [24,12,8,6]

Example 2:

Input: nums = [-1,1,0,-3,3]
Output: [0,0,9,0,0]

```

/**
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* productExceptSelf(int* nums, int numsSize, int* returnSize) {
    if (nums == NULL || numsSize == 0) {
        *returnSize = 0;
        return NULL;
    }

    // Initialize arrays to store products to the left and right of each element
    int* leftProducts = (int*)malloc(numsSize * sizeof(int));
    int* rightProducts = (int*)malloc(numsSize * sizeof(int));

    // Initialize return array
    int* result = (int*)malloc(numsSize * sizeof(int));

    // Calculate products to the left of each element

```

```

int leftProduct = 1;
for (int i = 0; i < numsSize; i++) {
    leftProducts[i] = leftProduct;
    leftProduct *= nums[i];
}

// Calculate products to the right of each element
int rightProduct = 1;
for (int i = numsSize - 1; i >= 0; i--) {
    rightProducts[i] = rightProduct;
    rightProduct *= nums[i];
}

// Calculate the final result by multiplying left and right products
for (int i = 0; i < numsSize; i++) {
    result[i] = leftProducts[i] * rightProducts[i];
}

// Set the return size
*returnSize = numsSize;

// Free allocated memory for intermediate arrays
free(leftProducts);
free(rightProducts);

return result;
}
int main() {
    int nums[] = {1, 2, 3, 4};

    int returnSize;
    int* result = productExceptSelf(nums, sizeof(nums) / sizeof(nums[0]), &returnSize);

    printf("Product of array elements except self:\n");
    for (int i = 0; i < returnSize; i++) {
        printf("%d ", result[i]);
    }
    printf("\n");

    // Free memory allocated for result array
    free(result);

    return 0;
}

```

1.156 Coin Change

You are given an integer array coins representing coins of different denominations and an integer amount representing a total amount of money.

Return *the fewest number of coins that you need to make up that amount*. If that amount of money cannot be made up by any combination of the coins, return -1.

You may assume that you have an infinite number of each kind of coin.

Example 1:

Input: coins = [1,2,5], amount = 11

Output: 3

Explanation: 11 = 5 + 5 + 1

Example 2:

Input: coins = [2], amount = 3

Output: -1

Example 3:

Input: coins = [1], amount = 0

Output: 0

```
public static int coinChange(int[] S, int sum)
{
    if (sum == 0) {
        return 0;
    }
    if (sum < 0) {
        return Integer.MAX_VALUE;
    }
    int coins = Integer.MAX_VALUE;
    for (int c: S)
    {
        int result = coinChange(S, sum - c);

        if (result != Integer.MAX_VALUE) {
            coins = Integer.min(coins, result + 1);
        }
    }
    return coins;
}

#define min(a,b) a < b ? a:b
int coinChange(int* coins, int coinsSize, int amount) {
    // Create an array to store the minimum number of coins needed for each amount
    int dp[amount + 1];

    // Initialize the array with a value larger than the maximum possible number of
    coins
```

```

for (int i = 0; i <= amount; i++) {
    dp[i] = INT_MAX;
}

// Base case: 0 coins needed for amount 0
dp[0] = 0;

// Iterate through each coin denomination
for (int i = 0; i < coinsSize; i++) {
    // Update dp array for each possible amount
    for (int j = coins[i]; j <= amount; j++) {
        // If using the current coin leads to a smaller number of coins needed,
        update dp
        if (dp[j - coins[i]] != INT_MAX) {
            dp[j] = min(dp[j], dp[j - coins[i]] + 1);
        }
    }
}

// If dp[amount] is still INT_MAX, no valid combination was found
return (dp[amount] == INT_MAX) ? -1 : dp[amount];
}

int main() {
    int coins[] = {1, 2, 5};
    int coinsSize = sizeof(coins) / sizeof(coins[0]);
    int amount = 11;

    int minCoins = coinChange(coins, coinsSize, amount);

    printf("Minimum number of coins needed to make up %d: %d\n", amount, minCoins);

    return 0;
}

```

1.157 Contains Duplicate

Given an integer array `nums`, return true if any value appears **at least twice** in the array, and return false if every element is distinct.

Example 1:

Input:	<code>nums = [1,2,3,1]</code>
Output:	<code>true</code>

Example 2:

Input:	<code>nums = [1,2,3,4]</code>
---------------	-------------------------------

Output: false

Example 3:

Input: nums = [1,1,1,3,3,4,3,2,4,2]

Output: true

```
bool containsDuplicate(int* nums, int numsSize) {
    // Create a hash set using an array of flags
    bool* set = (bool*)malloc(100000 * sizeof(bool));

    // Initialize the set to false
    for (int i = 0; i < 100000; i++) {
        set[i] = false;
    }

    // Iterate through the array
    for (int i = 0; i < numsSize; i++) {
        // If the element is already in the set, it's a duplicate
        if (set[nums[i]]) {
            free(set);
            return true;
        }

        // Mark the element as seen in the set
        set[nums[i]] = true;
    }

    // No duplicates found
    free(set);
    return false;
}

int main() {
    int nums[] = {1, 2, 3, 1};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    bool hasDuplicate = containsDuplicate(nums, numsSize);

    if (hasDuplicate) {
        printf("The array contains duplicates.\n");
    } else {
        printf("The array does not contain duplicates.\n");
    }

    return 0;
}
```

1.158 Search A 2D Matrix

You are given an $m \times n$ integer matrix matrix with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer target, return true *if* target *is in* matrix *or* false *otherwise*.

You must write a solution in $O(\log(m * n))$ time complexity.

Example 1:

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 3

Output: true

Example 2:

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 13

Output: false

```
bool searchMatrix(int** matrix, int matrixSize, int* matrixColSize, int target){  
    int row = matrixSize - 1;  
    int col = 0;  
  
    while (row >= 0 && col < *matrixColSize) {  
        if (matrix[row][col] > target) {  
            row--;  
        } else if (matrix[row][col] < target) {  
            col++;  
        } else { //a found it  
            return true;  
        }  
    }  
  
    return false;  
}  
  
int main() {  
    int matrix[][][4] = {  
        {1, 4, 7, 11},  
        {2, 5, 8, 12},  
        {3, 6, 9, 16},  
        {10, 13, 14, 17},  
        {18, 21, 23, 26}  
    };  
    int matrixSize = 5;  
    int matrixColSize[] = {4, 4, 4, 4, 4};  
    int target = 5;  
  
    bool found = searchMatrix((int**)matrix, matrixSize, matrixColSize, target);  
  
    if (found) {  
        printf("The target %d is found in the matrix.\n", target);  
    } else {  
        printf("The target %d is not found in the matrix.\n", target);  
    }  
  
    return 0;  
}
```

1.159 Validate Binary Search Tree

Given the root of a binary tree, *determine if it is a valid binary search tree (BST)*.

A **valid BST** is defined as follows:


- The left

subtree

of a node contains only nodes with keys **less than** the node's key.

- The right subtree of a node contains only nodes with keys **greater than** the node's key.
- Both the left and right subtrees must also be binary search trees.


Example 1:



Input: root = [2,1,3]

Output: true

Example 2:



Input: root = [5,1,4,null,null,3,6]

Output: false

Explanation: The root node's value is 5 but its right child's value is 4.

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
bool isValidBSTHelper(struct TreeNode* node, int *min, int *max) {
    if (node == NULL) return true;
    if ((min != NULL && node->val <= *min) || (max != NULL && node->val >= *max)) return false;
    return isValidBSTHelper(node->left,min,&node->val) && isValidBSTHelper(node->right,
&node->val, max);
}
bool isValidBST(struct TreeNode* root){
    return isValidBSTHelper(root,NULL,NULL);
}
int main() {
    // Create a sample binary search tree
    struct TreeNode* root = createNode(2);
    root->left = createNode(1);
    root->right = createNode(3);

    // Check if the tree is a valid binary search tree
    bool isValid = isValidBST(root);

    // Print the result
    if (isValid) {
        printf("The given tree is a valid binary search tree.\n");
    } else {
        printf("The given tree is not a valid binary search tree.\n");
    }

    // Free the memory allocated for the tree
    freeTree(root);

    return 0;
}

```

1.160 Plus One

You are given a **large integer** represented as an integer array `digits`, where each `digits[i]` is the i^{th} digit of the integer. The digits are ordered from most significant to least significant in left-to-right order. The large integer does not contain any leading 0's.

Increment the large integer by one and return *the resulting array of digits*.

Example 1:

Input: digits = [1,2,3]

Output: [1,2,4]

Explanation: The array represents the integer 123.

Incrementing by one gives $123 + 1 = 124$.

Thus, the result should be [1,2,4].

Example 2:

Input: digits = [4,3,2,1]

Output: [4,3,2,2]

Explanation: The array represents the integer 4321.

Incrementing by one gives $4321 + 1 = 4322$.

Thus, the result should be [4,3,2,2].

Example 3:

Input: digits = [9]

Output: [1,0]

Explanation: The array represents the integer 9.

Incrementing by one gives $9 + 1 = 10$.

Thus, the result should be [1,0].

```
/*
 * Note: The returned array must be malloced, assume caller calls free().
 */
int* plusOne(int* digits, int digitsSize, int* returnSize) {
    int i = 0;
    int *return_arr = NULL;
    for (i = digitsSize-1; i >= 0; i-- ) {
        if (digits[i] == 9) digits[i] = 0;
        else {
            digits[i]+=1;
            *returnSize = digitsSize;
            return digits;
        }
    }
    return_arr = (int*)malloc((digitsSize+1)*sizeof(int));
    return_arr[0] = 1;
    for (i = 0; i <= digitsSize-1; i++ ) {
        return_arr[i+1] = digits[i];
    }
    *returnSize = digitsSize+1;
    return return_arr;
}
int main() {
    int digits[] = {1, 2, 3}; // Example array
    int digitsSize = sizeof(digits) / sizeof(digits[0]);
```

```

int returnSize = 0;

// Call the plusOne function
int* result = plusOne(digits, digitsSize, &returnSize);

// Print the result
printf("Result after adding one: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", result[i]);
}
printf("\n");

// Free the dynamically allocated memory
free(result);

return 0;
}

```

1.161 Majority Element

Given an array `nums` of size n , return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input:	<code>nums = [3,2,3]</code>
Output:	<code>3</code>

Example 2:

Input:	<code>nums = [2,2,1,1,1,2,2]</code>
Output:	<code>2</code>

```

int majorityElement(int* nums, int numsSize) {
    int candidate = 0;
    int count = 0;
    for (int i = 0; i < numsSize; i++) {
        if (count == 0) candidate = nums[i];
        count += (nums[i] == candidate) ? 1 : -1;
    }
    return candidate;
}
int main() {
    int nums[] = {3, 2, 3}; // Example array
    int numsSize = sizeof(nums) / sizeof(nums[0]);
}

```

```

// Call the majorityElement function
int result = majorityElement(nums, numsSize);

// Print the result
printf("Majority Element: %d\n", result);

return 0;
}

```

1.162 Valid Palindrome

A phrase is a **palindrome** if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers.

Given a string s, return true *if it is a palindrome, or* false *otherwise*.

Example 1:

Input: s = "A man, a plan, a canal: Panama"

Output: true

Explanation: "amanaplanacanalpanama" is a palindrome.

Example 2:

Input: s = "race a car"

Output: false

Explanation: "raceacar" is not a palindrome.

Example 3:

Input: s = ""

Output: true

Explanation: s is an empty string "" after removing non-alphanumeric characters.

Since an empty string reads the same forward and backward, it is a palindrome.

```

bool isPalindrome(char* s) {
    int start = 0;
    int end = strlen(s);
    while (start < end) {
        if (!isalnum(s[start])) {
            start++;
            continue;
        }
        if (!isalnum(s[end])) {
            end--;
            continue;
        }
        if (s[start] != s[end]) {
            return false;
        }
        start++;
        end--;
    }
    return true;
}

```

```

    }
    if (tolower(s[start]) != tolower(s[end])) return false;
    else {
        start++;
        end--;
    }
}
return true;
}

int main() {
    char s[] = "A man, a plan, a canal: Panama"; // Example string
    // Call the isPalindrome function
    bool result = isPalindrome(s);

    // Print the result
    if (result) {
        printf("The string is a palindrome.\n");
    } else {
        printf("The string is not a palindrome.\n");
    }

    return 0;
}

```

1.163 House Robber

You are a professional robber planning to rob houses along a street. Each house has a certain amount of money stashed, the only constraint stopping you from robbing each of them is that adjacent houses have security systems connected and **it will automatically contact the police if two adjacent houses were broken into on the same night.**

Given an integer array `nums` representing the amount of money of each house, return ***the maximum amount of money you can rob tonight without alerting the police.***

Example 1:

Input: `nums = [1,2,3,1]`

Output: `4`

Explanation: Rob house 1 (money = 1) and then rob house 3 (money = 3).
Total amount you can rob = $1 + 3 = 4$.

Example 2:

Input: `nums = [2,7,9,3,1]`

Output: `12`

Explanation: Rob house 1 (money = 2), rob house 3 (money = 9) and rob house 5 (money = 1).

Total amount you can rob = $2 + 9 + 1 = 12$.

```
int max(int a, int b) {
    return (a > b) ? a:b;
}
int rob(int* nums, int numsSize){

    int i = 0;
    if (numsSize == 0) return 0;
    if (numsSize == 1) return nums[0];
    int* result = malloc(numsSize * sizeof(int));
    result[0] = nums[0];
    result[1] = max(nums[0],nums[1]);
    for (i = 2; i < numsSize; i++) {
        result[i] = max(result[i-1],result[i-2]+nums[i]);
    }
    return result[numsSize-1];
}
int main() {
    int nums[] = {2, 7, 9, 3, 1};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    int maxProfit = rob(nums, numsSize);
    printf("Maximum profit: %d\n", maxProfit);

    return 0;
}
```

1.164 Next Greater Element

The **next greater element** of some element x in an array is the **first greater** element that is **to the right** of x in the same array.

You are given two **distinct 0-indexed** integer arrays nums1 and nums2 , where nums1 is a subset of nums2 .

For each $0 \leq i < \text{nums1.length}$, find the index j such that $\text{nums1}[i] == \text{nums2}[j]$ and determine the **next greater element** of $\text{nums2}[j]$ in nums2 . If there is no next greater element, then the answer for this query is -1.

Return **an array** ans of length nums1.length **such that** $\text{ans}[i]$ **is the next greater element** as described above.

Example 1:

Input: nums1 = [4,1,2], nums2 = [1,3,4,2]

Output: [-1,3,-1]

Explanation: The next greater element for each value of nums1 is as follows:

- 4 is underlined in nums2 = [1,3,4,2]. There is no next greater element, so the answer is -1.
- 1 is underlined in nums2 = [1,3,4,2]. The next greater element is 3.
- 2 is underlined in nums2 = [1,3,4,2]. There is no next greater element, so the answer is -1.

Example 2:

Input: nums1 = [2,4], nums2 = [1,2,3,4]

Output: [3,-1]

Explanation: The next greater element for each value of nums1 is as follows:

- 2 is underlined in nums2 = [1,2,3,4]. The next greater element is 3.
- 4 is underlined in nums2 = [1,2,3,4]. There is no next greater element, so the answer is -1.

```
public class Solution {  
    public int[] nextGreaterElement(int[] nums1, int[] nums2) {  
        Stack<Integer> stack = new Stack<>();  
        HashMap<Integer, Integer> map = new HashMap<>();  
  
        for (int i = 0; i < nums2.length; i++) {  
            while (!stack.empty() && nums2[i] > stack.peek())  
                map.put(stack.pop(), nums2[i]);  
            stack.push(nums2[i]);  
        }  
  
        while (!stack.empty())  
            map.put(stack.pop(), -1);  
  
        int[] res = new int[nums1.length];  
        for (int i = 0; i < nums1.length; i++) {  
            res[i] = map.get(nums1[i]);  
        }  
  
        return res;  
    }  
}
```

1.165 Shuffle An Array

Given an integer array **nums**, design an algorithm to randomly shuffle the array. All permutations of the array should be **equally likely** as a result of the shuffling.

Implement the **Solution** class:

- **Solution(int[] nums)** Initializes the object with the integer array **nums**.
- **int[] reset()** Resets the array to its original configuration and returns it.
- **int[] shuffle()** Returns a random shuffling of the array.

Example 1:

Input

```
["Solution", "shuffle", "reset", "shuffle"]  
[[[1, 2, 3]], [], [], []]
```

Output

```
[null, [3, 1, 2], [1, 2, 3], [1, 3, 2]]
```

Explanation

```
Solution solution = new Solution([1, 2, 3]);  
  
solution.shuffle();      // Shuffle the array [1,2,3] and return its result.  
                        // Any permutation of [1,2,3] must be equally likely to be re  
turned.  
                        // Example: return [3, 1, 2]  
  
solution.reset();       // Resets the array back to its original configuration [1,2,3  
]. Return [1, 2, 3]  
  
solution.shuffle();     // Returns the random shuffling of array [1,2,3]. Example: re  
turn [1, 3, 2]
```

C:

```
#include <stdlib.h>  
#include <string.h>
```

```
typedef struct {  
    int* original;  
    int* copy;  
    int* temp;  
    int length;  
} Solution;
```

```
void swap(int* arr, int i, int j) {  
    int temp = arr[i];  
    arr[i] = arr[j];  
    arr[j] = temp;  
}
```

```

Solution* solutionCreate(int* nums, int numsSize) {
    Solution* obj = (Solution*)malloc(sizeof(Solution));
    obj->original = (int*)malloc(sizeof(int) * numsSize);
    obj->copy = (int*)malloc(sizeof(int) * numsSize);
    obj->temp = (int*)malloc(sizeof(int) * numsSize);
    obj->length = numsSize;

    memcpy(obj->original, nums, sizeof(int) * numsSize);
    memcpy(obj->copy, nums, sizeof(int) * numsSize);

    return obj;
}

int* solutionReset(Solution* obj, int* returnSize) {
    memcpy(obj->copy, obj->original, sizeof(int) * obj->length);
    *returnSize = obj->length;
    return obj->original;
}

int* solutionShuffle(Solution* obj, int* returnSize) {
    memcpy(obj->temp, obj->copy, sizeof(int) * obj->length);

    for (int i = 0; i < obj->length; i++) {
        int ra = obj->length - i;
        int j = i + rand() % ra;
        swap(obj->temp, i, j);
    }

    *returnSize = obj->length;
    return obj->temp;
}

void solutionFree(Solution* obj) {
    free(obj->original);
    free(obj->copy);
    free(obj->temp);
    free(obj);
}

int main() {
    // Example usage
    int nums[] = {1, 2, 3, 4, 5};
    int numsSize = sizeof(nums) / sizeof(nums[0]);

    // Create the Solution object
    Solution* obj = solutionCreate(nums, numsSize);

    // Reset the array
    int returnSize;
}

```

```

int* resetArray = solutionReset(obj, &returnSize);
printf("Reset array: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", resetArray[i]);
}
printf("\n");

// Shuffle the array
int* shuffledArray = solutionShuffle(obj, &returnSize);
printf("Shuffled array: ");
for (int i = 0; i < returnSize; i++) {
    printf("%d ", shuffledArray[i]);
}
printf("\n");

// Free the Solution object
solutionFree(obj);

return 0;
}

```

1.166 MinStack

Design a stack that supports push, pop, top, and retrieving the minimum element in constant time.

Implement the MinStack class:

- `MinStack()` initializes the stack object.
- `void push(int val)` pushes the element `val` onto the stack.
- `void pop()` removes the element on the top of the stack.
- `int top()` gets the top element of the stack.
- `int getMin()` retrieves the minimum element in the stack.

You must implement a solution with `O(1)` time complexity for each function.

Example 1:

Input

```

["MinStack","push","push","push","getMin","pop","top","getMin"]
[[],[-2],[0],[-3],[],[],[],[]]

```

Output

```
[null,null,null,null,-3,null,0,-2]
```

Explanation

```
MinStack minStack = new MinStack();

minStack.push(-2);
minStack.push(0);
minStack.push(-3);

minStack.getMin(); // return -3

minStack.pop();
minStack.top();    // return 0

minStack.getMin(); // return -2
```

C:

```
typedef struct {
    int* stack;
    int* minStack;
    int top;
    int minTop;
    int capacity;
} MinStack;

MinStack* minStackCreate() {
    MinStack* stack = (MinStack*)malloc(sizeof(MinStack));
    stack->stack = (int*)malloc(sizeof(int));
    stack->minStack = (int*)malloc(sizeof(int));
    stack->top = -1;
    stack->minTop = -1;
    stack->capacity = 1;
    return stack;
}

void minStackPush(MinStack* obj, int val) {
    if (obj->top == obj->capacity - 1) {
        obj->capacity *= 2;
        obj->stack = (int*)realloc(obj->stack, sizeof(int) * obj->capacity);
    }
    obj->stack[+obj->top] = val;

    if (obj->minTop == -1 || val <= obj->minStack[obj->minTop]) {
```

```

        if (obj->minTop == obj->capacity - 1) {
            obj->minStack = (int*)realloc(obj->minStack, sizeof(int) * obj->capacity);
        }
        obj->minStack[++obj->minTop] = val;
    }
}

void minStackPop(MinStack* obj) {
    if (obj->stack[obj->top] == obj->minStack[obj->minTop]) {
        obj->minTop--;
    }
    obj->top--;
}

int minStackTop(MinStack* obj) {
    return obj->stack[obj->top];
}

int minStackGetMin(MinStack* obj) {
    return obj->minStack[obj->minTop];
}

void minStackFree(MinStack* obj) {
    free(obj->stack);
    free(obj->minStack);
    free(obj);
}

int main() {
    // Example usage
    MinStack* obj = minStackCreate();

    // Push elements onto the stack
    minStackPush(obj, -2);
    minStackPush(obj, 0);
    minStackPush(obj, -3);

    // Print the minimum element in the stack
    printf("Minimum element: %d\n", minStackGetMin(obj)); // Output: -3

    // Pop an element from the stack
    minStackPop(obj);

    // Print the top element of the stack
    printf("Top element: %d\n", minStackTop(obj)); // Output: 0

    // Print the minimum element in the stack
    printf("Minimum element: %d\n", minStackGetMin(obj)); // Output: -2
}

```

```

    // Free the memory allocated for the stack
    minStackFree(obj);

    return 0;
}

```

1.167 Sum Of Two Integers

Given two integers a and b, return *the sum of the two integers without using the operators + and -.*

Example 1:

Input: a = 1, b = 2

Output: 3

Example 2:

Input: a = 2, b = 3

Output: 5

```

int getSum(int a, int b){
    while (b != 0) {
        unsigned int sum = a ^ b;
        unsigned int carry = (unsigned int)(a & b) << 1;
        a = sum;
        b = carry;
    }
    return a;
}

int main() {
    // Example usage of getSum function
    int a = 5;
    int b = 7;
    printf("Sum of %d and %d is: %d\n", a, b, getSum(a, b)); // Output: Sum of 5 and 7
    is: 12

    return 0;
}

```

1.168 Maximum Product SubArray

Given an integer array `nums`, find a

`subarray`

that has the largest product, and return *the product.*

The test cases are generated so that the answer will fit in a **32-bit** integer.

Example 1:

Input: nums = [2,3,-2,4]
Output: 6
Explanation: [2,3] has the largest product 6.

Example 2:

Input: nums = [-2,0,-1]
Output: 0
Explanation: The result cannot be 2, because [-2,-1] is not a subarray.

```
class Solution {
    public int maxProduct(int[] nums) {
        int current_array = nums[0];
        int maximum_array = nums[0];
        for (int i = 1; i < nums.length; i++) {
            current_array = Math.max(current_array*nums[i],nums[i]);
            maximum_array = Math.max(current_array, maximum_array);
        }
        return maximum_array;
    }
    int max(int a, int b) {
        return a > b ? a : b;
    }

    int maxProduct(int* nums, int numsSize) {
        int current_array = nums[0];
        int maximum_array = nums[0];

        for (int i = 1; i < numsSize; i++) {
            current_array = max(current_array * nums[i], nums[i]);
            maximum_array = max(current_array, maximum_array);
        }

        return maximum_array;
    }

    int main() {
        int nums[] = {2, 3, -2, 4};
        int numsSize = sizeof(nums) / sizeof(nums[0]);
        printf("Maximum product: %d\n", maxProduct(nums, numsSize)); // Output: 6

        return 0;
    }
}
```

1.169 Number Of 1 Bits

Write a function that takes the binary representation of an unsigned integer and returns the number of '1' bits it has (also known as the [Hamming weight](#)).

Note:

- Note that in some languages, such as Java, there is no unsigned integer type. In this case, the input will be given as a signed integer type. It should not affect your implementation, as the integer's internal binary representation is the same, whether it is signed or unsigned.
- In Java, the compiler represents the signed integers using [2's complement notation](#). Therefore, in [Example 3](#), the input represents the signed integer. -3.

Example 1:

Input: n = 000000000000000000000000000000001011

Output: 3

Explanation: The input binary string **000000000000000000000000000000001011** has a total of three '1' bits.

Example 2:

Input: n = 0000000000000000000000000000000010000000

Output: 1

Explanation: The input binary string **0000000000000000000000000000000010000000** has a total of one '1' bit.

Example 3:

Input: n = 11111111111111111111111111111111101

Output: 31

Explanation: The input binary string **11111111111111111111111111111111101** has a total of thirty one '1' bits.

```
int hammingWeight(uint32_t n) {  
    int count = 0;  
    while (n != 0) {  
        n = (n & n-1);  
        count++;  
    }  
    return count;  
}  
int main() {  
    uint32_t n = 0b000000000000000000000000000000001011; // Example input: 11  
    printf("Number of set bits: %d\n", hammingWeight(n)); // Output: 3  
    return 0;  
}
```

}

1.170 Counting Bits

Given an integer n, return an array ans of length n + 1 such that for each i (0 <= i <= n), ans[i] is the number of 1's in the binary representation of i.

Example 1:

Input: n = 2

Output: [0,1,1]

Explanation:

0 --> 0

1 --> 1

2 --> 10

Example 2:

Input: n = 5

Output: [0,1,1,2,1,2]

Explanation:

0 --> 0

1 --> 1

2 --> 10

3 --> 11

4 --> 100

5 --> 101

```
/*
 * Note: The returned array must be malloced, assume caller calls free().
 */
int countOnes(int num) {
    int count = 0;
    while (num) {
        num= num & (num -1);
        //num >>= 1;
        count++;
    }
    return count;
}

int* countBits(int n, int* returnSize) {
    // Allocate memory for the result array
    int* result = (int*)malloc((n + 1) * sizeof(int));

    // Generate count of set bits for each number from 0 to n
    for (int i = 0; i <= n; ++i) {
        result[i] = countOnes(i);
```

```

    }

    // Set the return size
    *returnSize = n + 1;

    return result;
}

int main() {
    int n = 5; // Example value of n
    int returnSize;
    int* result = countBits(n, &returnSize);

    // Print the result
    printf("Result: ");
    for (int i = 0; i < returnSize; ++i) {
        printf("%d ", result[i]);
    }
    printf("\n");

    // Free the allocated memory
    free(result);

    return 0;
}

```

1.171 Missing Number

Given an array `nums` containing n distinct numbers in the range $[0, n]$, return *the only number in the range that is missing from the array.*

Example 1:

Input: `nums = [3,0,1]`

Output: 2

Explanation: $n = 3$ since there are 3 numbers, so all numbers are in the range $[0,3]$. 2 is the missing number in the range since it does not appear in `nums`.

Example 2:

Input: `nums = [0,1]`

Output: 2

Explanation: $n = 2$ since there are 2 numbers, so all numbers are in the range $[0,2]$. 2 is the missing number in the range since it does not appear in `nums`.

Example 3:

Input: nums = [9,6,4,2,3,5,7,0,1]

Output: 8

Explanation: n = 9 since there are 9 numbers, so all numbers are in the range [0,9]. 8 is the missing number in the range since it does not appear in nums.

```
int missingNumber(int* nums, int numsSize){  
    int sum = 0;  
    int actual_sum = 0;  
    int i = 0;  
    for (i = 0; i < numsSize; i++) {  
        sum += nums[i];  
    }  
  
    actual_sum = (numsSize*(numsSize+1))/2;  
    return actual_sum - sum;  
}  
int main() {  
    // Example input array  
    int nums[] = {3, 0, 1, 4, 6, 2}; // Example array  
    int numsSize = sizeof(nums) / sizeof(nums[0]);  
  
    // Find the missing number  
    int missing = missingNumber(nums, numsSize);  
  
    // Print the missing number  
    printf("The missing number is: %d\n", missing);  
  
    return 0;  
}
```

1.172 Reverse Bits

Reverse bits of a given 32 bits unsigned integer.

Note:

- Note that in some languages, such as Java, there is no unsigned integer type. In this case, both input and output will be given as a signed integer type. They should not affect your implementation, as the integer's internal binary representation is the same, whether it is signed or unsigned.
- In Java, the compiler represents the signed integers using [2's complement notation](#). Therefore, in [Example 2](#) above, the input represents the signed integer -3 and the output represents the signed integer -1073741825.

Example 1:

Input: n = 0000001010010100000111010011100

Output: 964176192 (0011100101110000010100101000000)

Explanation: The input binary string **0000001010010100000111010011100** represents the unsigned integer 43261596, so return 964176192 which its binary representation is **0011100101110000010100101000000**.

Example 2:

Input: n = 1111111111111111111111111111111101

Output: 3221225471 (10111111111111111111111111111111)

Explanation: The input binary string **1111111111111111111111111111111101** represents the unsigned integer 4294967293, so return 3221225471 which its binary representation is **10111111111111111111111111111111**.

```
uint32_t reverseBits(uint32_t n) {
    int result = 0;
    for (int i = 31; i >= 0; i--) {
        result |= (((n >> (31-i)) & 0x1) << i);
    }
    return result;
}
int main() {
    // Example input
    uint32_t n = 43261596; // Binary: 0000001010010100000111010011100

    // Reverse the bits
    uint32_t reversed = reverseBits(n);

    // Print the result
    printf("Reversed bits: %u\n", reversed);

    return 0;
}
```


1.173 Detect Cycle in Linked List

Given head, the head of a linked list, determine if the linked list has a cycle in it.

There is a cycle in a linked list if there is some node in the list that can be reached again by continuously following the next pointer. Internally, pos is used to denote the index of the node that tail's next pointer is connected to. **Note that pos is not passed as a parameter.**

Return true *if there is a cycle in the linked list*. Otherwise, return false.

Example 1:




Input: head = [3,2,0,-4], pos = 1

Output: true

Explanation: There is a cycle in the linked list, where the tail connects to the 1st node (0-indexed).

Example 2:




Input: head = [1,2], pos = 0

Output: true

Explanation: There is a cycle in the linked list, where the tail connects to the 0th node.

Example 3:



Input: head = [1], pos = -1

Output: false

Explanation: There is no cycle in the linked list.

```
/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */
bool hasCycle(struct ListNode *head) {
    if (head == NULL) return false;
    struct ListNode *slow = head;
    struct ListNode *fast = head;

    while (fast != NULL && fast->next != NULL) {
        slow = slow->next;
        fast = fast->next->next;
        if (slow == fast)
            return true;
    }
    return false;
}
```

```

        fast = fast->next->next;
        if (slow == fast) return true;
    }
    return false;
}

int main() {
    // Create a linked list with a cycle
    struct ListNode *head = (struct ListNode *)malloc(sizeof(struct ListNode));
    head->val = 3;
    head->next = (struct ListNode *)malloc(sizeof(struct ListNode));
    head->next->val = 2;
    head->next->next = (struct ListNode *)malloc(sizeof(struct ListNode));
    head->next->next->val = 0;
    head->next->next->next = (struct ListNode *)malloc(sizeof(struct ListNode));
    head->next->next->next->val = -4;
    head->next->next->next->next = head->next; // Create a cycle

    // Check if the linked list has a cycle
    bool has_cycle = hasCycle(head);

    // Print the result
    if (has_cycle) {
        printf("The linked list has a cycle.\n");
    } else {
        printf("The linked list does not have a cycle.\n");
    }

    // Free the memory allocated for the linked list
    free(head->next->next->next);
    free(head->next->next);
    free(head->next);
    free(head);

    return 0;
}

```

1.174 Reorder List

You are given the head of a singly linked-list. The list can be represented as:




$L_0 \rightarrow L_1 \rightarrow \dots \rightarrow L_{n-1} \rightarrow L_n$

Reorder the list to be on the following form:

$L_0 \rightarrow L_n \rightarrow L_1 \rightarrow L_{n-1} \rightarrow L_2 \rightarrow L_{n-2} \rightarrow \dots$

You may not modify the values in the list's nodes. Only nodes themselves may be changed.




Example 1:



Input: head = [1,2,3,4]

Output: [1,4,2,3]

Example 2:



Input: head = [1,2,3,4,5]

Output: [1,5,2,4,3]

Constraints:

```
void reorderList(struct ListNode* head){  
    struct ListNode *stack[50000];  
    struct ListNode *temp=head;  
    int i=0;  
    while(temp)  
    {  
        stack[i]=temp;  
        temp=temp->next;  
    }  
    i=-1;  
    temp=head;  
    while(temp->next!=NULL)  
    {  
        temp->next=stack[++i];  
        temp=temp->next->next;  
    }  
    temp->next=NULL;
```

```

        i++;
    }
    temp=head;
    struct ListNode *sec=NULL;
    int k=i;
    for(int j=0;j<i/2;j++)
    {
        sec=temp->next;
        temp->next=stack[--k];
        temp->next->next=sec;
        temp=sec;
    }
    temp->next=NULL;
}
int main() {
    // Create a sample linked list
    struct ListNode* head = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->val = 1;
    head->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->val = 2;
    head->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->next->val = 3;
    head->next->next->next = (struct ListNode*)malloc(sizeof(struct ListNode));
    head->next->next->next->val = 4;
    head->next->next->next->next = NULL;
    reorderList(head);

    // Print the reordered list
    printf("Reordered list: ");
    struct ListNode* temp = head;
    while (temp != NULL) {
        printf("%d ", temp->val);
        temp = temp->next;
    }
    printf("\n");

    // Free the memory allocated for the linked list
    while (head != NULL) {
        struct ListNode* temp = head;
        head = head->next;
        free(temp);
    }

    return 0;
}

class Solution {
public void reorderList(ListNode head) {
    if (head == null) return;

```

```

// find the middle of linked list [Problem 876]
// in 1->2->3->4->5->6 find 4
ListNode slow = head, fast = head;
while (fast != null && fast.next != null) {
    slow = slow.next;
    fast = fast.next.next;
}

// reverse the second part of the list [Problem 206]
// convert 1->2->3->4->5->6 into 1->2->3->4 and 6->5->4
// reverse the second half in-place
ListNode prev = null, curr = slow, tmp;
while (curr != null) {
    tmp = curr.next;

    curr.next = prev;
    prev = curr;
    curr = tmp;
}

// merge two sorted linked lists [Problem 21]
// merge 1->2->3->4 and 6->5->4 into 1->6->2->5->3->4
ListNode first = head, second = prev;
while (second.next != null) {
    tmp = first.next;
    first.next = second;
    first = tmp;

    tmp = second.next;
    second.next = first;
    second = tmp;
}
}
}
}

```

1.175 Set Matrix Zeros

Given an $m \times n$ integer matrix matrix , if an element is 0, set its entire row and column to 0's.

You must do it in place.

Example 1:

1	1	1
1	0	1
1	1	1

Input: matrix = [[1,1,1],[1,0,1],[1,1,1]]

Output: [[1,0,1],[0,0,0],[1,0,1]]

Example 2:

0	1	2	0
3	4	5	2
1	3	1	5

Input: matrix = [[0,1,2,0],[3,4,5,2],[1,3,1,5]]

Output: [[0,0,0,0],[0,4,5,0],[0,3,1,0]]

```
void setZeroes(int** matrix, int matrixSize, int* matrixColSize) {
    // Variables to track whether the first row and first column contain zeros
    bool first_row = false;
    bool first_col = false;

    // Check if the first column contains zeros
    for (int i = 0; i < matrixSize; i++) {
        if (matrix[i][0] == 0) {
            first_col = true;
            break;
        }
    }

    // Check if the first row contains zeros
    for (int i = 0; i < *matrixColSize; i++) {
        if (matrix[0][i] == 0) {
            first_row = true;
            break;
        }
    }

    // Set the rest of the matrix to zero
    for (int i = 0; i < matrixSize; i++) {
        for (int j = 0; j < *matrixColSize; j++) {
            if ((matrix[i][0] == 0) || (matrix[0][j] == 0)) {
                matrix[i][j] = 0;
            }
        }
    }
}
```

```

        }

    }

    // Mark the first element of each row and column if the element is zero
    for (int i = 1; i < matrixSize; i++) {
        for (int j = 1; j < *matrixColSize; j++) {
            if (matrix[i][j] == 0) {
                matrix[i][0] = 0;
                matrix[0][j] = 0;
            }
        }
    }

    // Set the entire row to zero if the first element of the row is zero
    for (int i = 1; i < matrixSize; i++) {
        if (matrix[i][0] == 0) {
            for (int j = 1; j < *matrixColSize; j++) {
                matrix[i][j] = 0;
            }
        }
    }

    // Set the entire column to zero if the first element of the column is zero
    for (int j = 1; j < *matrixColSize; j++) {
        if (matrix[0][j] == 0) {
            for (int i = 1; i < matrixSize; i++) {
                matrix[i][j] = 0;
            }
        }
    }

    // Set the first row to zero if it originally contained a zero
    if (first_row) {
        for (int j = 0; j < *matrixColSize; j++) {
            matrix[0][j] = 0;
        }
    }

    // Set the first column to zero if it originally contained a zero
    if (first_col) {
        for (int i = 0; i < matrixSize; i++) {
            matrix[i][0] = 0;
        }
    }
}

int main() {
    // Example matrix

```

```

int numRows = 3;
int numCols = 4;
int **matrix = (int**)malloc(numRows * sizeof(int *));
for (int i = 0; i < numRows; i++) {
    matrix[i] = (int*)malloc(numCols * sizeof(int));
}

// Initialize the matrix with sample values
matrix[0][0] = 1;
matrix[0][1] = 1;
matrix[0][2] = 1;
matrix[0][3] = 1;
matrix[1][0] = 1;
matrix[1][1] = 0;
matrix[1][2] = 1;
matrix[1][3] = 1;
matrix[2][0] = 1;
matrix[2][1] = 1;
matrix[2][2] = 1;
matrix[2][3] = 1;

// Printing the original matrix
printf("Original Matrix:\n");
for (int i = 0; i < numRows; i++) {
    for (int j = 0; j < numCols; j++) {
        printf("%d ", matrix[i][j]);
    }
    printf("\n");
}

// Call the setZeroes function
setZeroes(matrix, numRows, &numCols);

// Printing the modified matrix
printf("\nMatrix After Setting Zeroes:\n");
for (int i = 0; i < numRows; i++) {
    for (int j = 0; j < numCols; j++) {
        printf("%d ", matrix[i][j]);
    }
    printf("\n");
}

// Free memory allocated for the matrix
for (int i = 0; i < numRows; i++) {
    free(matrix[i]);
}
free(matrix);
}

```

```

/*
0 1 2 0    0 0 0 0    0 0 0 0
3 4 5 2    0 4 5 0    3 4 5 0
1 3 1 5    0 3 1 0    1 3 1 0

0 0 0 5    0 0 0 0    0 0 0 0
4 3 1 4    0 0 0 4    0 0 0 4
0 1 1 4    0 0 0 0    0 0 0 4
1 2 1 3    0 0 0 3    0 0 0 3
0 0 1 1    0 0 0 0    0 0 0 0
*/

```

1.176 Insert Intervals

You are given an array of non-overlapping intervals `intervals` where `intervals[i] = [starti, endi]` represent the start and the end of the _ith interval and `intervals` is sorted in ascending order by `starti`. You are also given an interval `newInterval = [start, end]` that represents the start and end of another interval.

Insert `newInterval` into `intervals` such that `intervals` is still sorted in ascending order by `starti` and `intervals` still does not have any overlapping intervals (merge overlapping intervals if necessary).

Return intervals *after the insertion*.

Example 1:

Input: `intervals = [[1,3],[6,9]]`, `newInterval = [2,5]`
Output: `[[1,5],[6,9]]`

Example 2:

Input: `intervals = [[1,2],[3,5],[6,7],[8,10],[12,16]]`, `newInterval = [4,8]`
Output: `[[1,2],[3,10],[12,16]]`
Explanation: Because the new interval `[4,8]` overlaps with `[3,5],[6,7],[8,10]`.

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 calls free().
 */

```

```

/*
 * 57. Insert Interval
 *
 * You are given an array of non-overlapping intervals intervals
 * where intervals[i] = [starti, endi] represent the start and the
 * end of the ith interval and intervals is sorted in ascending
 * order by starti. You are also given an interval newInterval =
 * [start, end] that represents the start and end of another interval.
 *
 * Insert newInterval into intervals such that intervals is still sorted
 * in ascending order by starti and intervals still does not have any
 * overlapping intervals (merge overlapping intervals if necessary).
 *
 * Return intervals after the insertion.
 *
 * 0 <= intervals.length <= 104
 * intervals[i].length == 2
 * 0 <= starti <= endi <= 105
 * intervals is sorted by starti in ascending order.
 * newInterval.length == 2
 * 0 <= start <= end <= 10^5
 */

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 * calls free().
 */

#define MAX(a, b) ((a) > (b) ? (a) : (b))

int cmp(const void *a, const void *b)
{
    return (*((int **)a))[0] - (*((int **)b))[0];
}

int** insert(int** intervals, int intervalsSize, int* intervalsColSize, int*
newInterval, int newIntervalSize, int* returnSize, int** returnColumnSizes){

    /*
     * Input:
     * intervals,
     * intervalsSize
     * intervalsColSize
     * newInterval
     * newIntervalSize
     */
}

```

```

int seg_start = newInterval[0], seg_end = newInterval[1];
int **ans = (int **)malloc(sizeof(int *) * (intervalsSize + 1));
int **tmp = (int **)malloc(sizeof(int *) * (intervalsSize + 1));
(*returnColumnSizes) = (int *)malloc(sizeof(int) * (intervalsSize + 1));

*returnSize = 0;

/* Copy intervals to tmp buffer */
for (int i = 0; i < intervalsSize; i++) {
    tmp[i] = (int *)malloc(sizeof(int) * 2);
    tmp[i][0] = intervals[i][0];
    tmp[i][1] = intervals[i][1];
}

/* Append newInterval to tmp buffer */
tmp[intervalsSize] = (int *)malloc(sizeof(int) * 2);
ans[intervalsSize] = (int *)malloc(sizeof(int) * 2);
tmp[intervalsSize][0] = newInterval[0];
tmp[intervalsSize][1] = newInterval[1];

/* Sort by start */
qsort(tmp, intervalsSize + 1, sizeof(int *), cmp);

seg_start = tmp[0][0];
seg_end = tmp[0][1];

/* Merge the interval */
for (int i = 0; i < intervalsSize + 1; i++) {
    /* Check if segments can be merged, and store the start and end position of
    merged segment */
    if (tmp[i][0] >= seg_start && tmp[i][0] <= seg_end) {
        seg_end = MAX(seg_end, tmp[i][1]);
    }
    /* Complete current segment */
    else {
        ans[*returnSize] = (int *)malloc(sizeof(int) * 2);
        ans[*returnSize][0] = seg_start;
        ans[*returnSize][1] = seg_end;
        (*returnColumnSizes)[*returnSize] = 2;
        *returnSize += 1;
        seg_start = tmp[i][0];
        seg_end = tmp[i][1];
    }
}

/* Add last one segment */
if (i == intervalsSize) {
    ans[*returnSize] = (int *)malloc(sizeof(int) * 2);
    ans[*returnSize][0] = seg_start;
    ans[*returnSize][1] = seg_end;
}

```

```

        (*returnColumnSizes)[*returnSize] = 2;
        *returnSize += 1;
    }
}

for (int i = 0; i < intervalsSize + 1; i++) {
    free(tmp[i]);
}

free(tmp);

/*
 * Output:
 * returnSize
 * returnColumnSizes
 */
}

return ans;
}

int main() {
    // Example input intervals
    int intervalsSize = 3;
    int intervalsColSize[] = {2, 2, 2};
    int* intervals[] = {{1, 3}, {6, 9}, {12, 17}};

    // Example new interval
    int newInterval[] = {4, 10};
    int newIntervalSize = 2;

    // Variables to store output
    int returnSize = 0;
    int* returnColumnSizes = NULL;
    int** result = insert(intervals, intervalsSize, intervalsColSize, newInterval,
newIntervalSize, &returnSize, &returnColumnSizes);

    // Print input intervals
    printf("Input intervals: ");
    printIntervals(intervals, intervalsSize, intervalsColSize);

    // Print new interval
    printf("New interval: [%d, %d]\n", newInterval[0], newInterval[1]);

    // Print merged intervals
    printf("Merged intervals: ");
    printIntervals(result, returnSize, returnColumnSizes);

    // Free memory
    for (int i = 0; i < returnSize; i++) {

```

```

        free(result[i]);
    }
    free(result);
    free(returnColumnSizes);

    return 0;
}

```

1.177 Non Overlapping Intervals

Given an array of intervals intervals where intervals[i] = [start_i, end_i], return *the minimum number of intervals you need to remove to make the rest of the intervals non-overlapping*.

Example 1:

Input: intervals = [[1,2],[2,3],[3,4],[1,3]]

Output: 1

Explanation: [1,3] can be removed and the rest of the intervals are non-overlapping.

Example 2:

Input: intervals = [[1,2],[1,2],[1,2]]

Output: 2

Explanation: You need to remove two [1,2] to make the rest of the intervals non-overlapping.

Example 3:

Input: intervals = [[1,2],[2,3]]

Output: 0

Explanation: You don't need to remove any of the intervals since they're already non-overlapping.

```

// Interval structure definition
struct Interval {
    int start;
    int end;
};

// Function to compare intervals for sorting
int compareIntervals(const void* a, const void* b) {
    return ((struct Interval*)a)->end - ((struct Interval*)b)->end;
}

// Function to find the minimum number of intervals to remove
int eraseOverlapIntervals(int** intervals, int intervalsSize, int* intervalsColSize) {
    if (intervals == NULL || intervalsSize <= 1) {
        return 0;
    }

    ...
}

```

```

// Convert 2D array to array of Interval structures
struct Interval* intervalsArr = (struct Interval*)malloc(intervalsSize *
sizeof(struct Interval));
for (int i = 0; i < intervalsSize; i++) {
    intervalsArr[i].start = intervals[i][0];
    intervalsArr[i].end = intervals[i][1];
}

// Sort intervals by end time in ascending order
qsort(intervalsArr, intervalsSize, sizeof(struct Interval), compareIntervals);

int ans = 0;
int k = INT_MIN;

// Iterate through intervals
for (int i = 0; i < intervalsSize; i++) {
    int x = intervalsArr[i].start;
    int y = intervalsArr[i].end;

    if (x >= k) {
        // Case 1
        k = y;
    } else {
        // Case 2
        ans++;
    }
}

// Free allocated memory
free(intervalsArr);

return ans;
}
int main() {
    // Example intervals
    int intervalsSize = 4;
    int intervalsColSize[] = {2, 2, 2, 2};
    int* intervals[] = {{1, 2}, {2, 3}, {3, 4}, {1, 3}};

    // Find the minimum number of intervals to remove
    int minToRemove = eraseOverlapIntervals(intervals, intervalsSize, intervalsColSize);

    // Print the result
    printf("Minimum number of intervals to remove: %d\n", minToRemove);

    return 0;
}

```

1.178 Meeting Rooms (Can attend all meetings)

Given an array of meeting time intervals where $\text{intervals}[i] = [\text{start}_i, \text{end}_i]$, determine if a person could attend all meetings.

Example 1:

Input: `intervals = [[0,30],[5,10],[15,20]]`

Output: `false`

Example 2:

Input: `intervals = [[7,10],[2,4]]`

Output: `true`

```
int compareIntervals(const void* a, const void* b) {
    return (*((int**)a))[0] - (*((int**)b))[0];
}

int canAttendMeetings(int** intervals, int intervalsSize, int* intervalsColSize) {
    if (intervalsSize <= 1) {
        return 1; // A person can attend all meetings if there is only one or zero
meetings.
    }

    // Sort intervals based on the start time.
    qsort(intervals, intervalsSize, sizeof(int*), compareIntervals);

    // Check if there is any overlap between consecutive intervals.
    for (int i = 1; i < intervalsSize; i++) {
        if (intervals[i - 1][1] > intervals[i][0]) {
            return 0; // There is an overlap, so the person cannot attend all meetings.
        }
    }

    return 1; // No overlap found, person can attend all meetings.
}

int main() {
    // Example intervals
    int intervalsSize = 3;
    int intervalsColSize[] = {2, 2, 2};
    int* intervals[] = {{0, 5}, {5, 10}, {15, 20}};

    // Check if a person can attend all meetings
    int canAttendAllMeetings = canAttendMeetings(intervals, intervalsSize,
intervalsColSize);
```

```

// Print the result
if (canAttendAllMeetings) {
    printf("The person can attend all meetings without overlapping.\n");
} else {
    printf("The person cannot attend all meetings without overlapping.\n");
}

return 0;
}

```

1.179 Longest Repeating Character Replacement

You are given a string s and an integer k. You can choose any character of the string and change it to any other uppercase English character. You can perform this operation at most k times.

Return *the length of the longest substring containing the same letter you can get after performing the above operations.*

Example 1:

Input: s = "ABAB", k = 2

Output: 4

Explanation: Replace the two 'A's with two 'B's or vice versa.

Example 2:

Input: s = "AABABBA", k = 1

Output: 4

Explanation: Replace the one 'A' in the middle with 'B' and form "AABBBA".

The substring "BBBB" has the longest repeating letters, which is 4.

There may exists other ways to achieve this answer too.

```

class Solution {
    public int characterReplacement(String s, int k) {
        // Initialising an empty array to store the count of the
        // characters in the given string s
        int[] arr = new int[26];
        int res = 0;
        int max = 0;

        // The left pointer for the sliding window is l AND r is the
        // right pointer
        int l = 0;
        for (int r = 0; r < s.length(); r++) {
            // Counting the number of each character in the string s
            arr[s.charAt(r) - 'A']++;

            // Checking the character with max number of occurrence
            max = Math.max(max, arr[s.charAt(r) - 'A']);
        }

        if (max >= s.length() - r + l)
            return s.length();
        else
            return s.length() - r + l - max;
    }
}

```

```

        // Now we check if our current window is valid or not
        if (r - l + 1 - max > k) {
            // this means the no. of replacements is more than
            // allowed (k)
            // Decrementing the count of the character which was
            // at l because it is no longer in the window
            arr[s.charAt(l) - 'A']--;
            l++;
        }

        // The max our window can be
        res = Math.max(res, r - l + 1);
    }

    return res;
}
}

int characterReplacement(char *s, int k) {
    int n = strlen(s);
    int max_count = 0; // Maximum repeating character count in the window
    int start = 0; // Start index of the window
    int max_length = 0; // Maximum length of the substring with repeating characters

    // Array to store the count of each character in the window
    int char_count[26] = {0};

    for (int end = 0; end < n; end++) {
        char_count[s[end] - 'A']++;
        max_count = (max_count > char_count[s[end] - 'A']) ? max_count :
        char_count[s[end] - 'A'];

        // If the window size exceeds the maximum count + k, shrink the window
        if ((end - start + 1) - max_count > k) {
            char_count[s[start] - 'A']--;
            start++;
        }

        // Update the maximum length
        max_length = (max_length > (end - start + 1)) ? max_length : (end - start + 1);
    }

    return max_length;
}

int main() {
    char s[] = "ABAB";
    int k = 2;

    int maxLength = characterReplacement(s, k);
}

```

```

        printf("The maximum length of the substring with repeating characters after
replacement is: %d\n", maxLength);

    return 0;
}

```

1.180 Minimum Window SubString

Given two strings s and t of lengths m and n respectively, return *the minimum window*

substring

of s such that every character in t (*including duplicates*) is included in the window. If there is no such substring, return *the empty string* "".

The testcases will be generated such that the answer is **unique**.



Example 1:

Input: s = "ADOBECODEBANC", t = "ABC"

Output: "BANC"

Explanation: The minimum window substring "BANC" includes 'A', 'B', and 'C' from string t.

Example 2:

Input: s = "a", t = "a"

Output: "a"

Explanation: The entire string s is the minimum window.

Example 3:

Input: s = "a", t = "aa"

Output: ""

Explanation: Both 'a's from t must be included in the window.

Since the largest window of s only has one 'a', return empty string.

```

class Solution {
    public String minWindow(String s, String t)
    {
        if(s.length() == 0 || t.length() == 0)
            return "";
        HashMap<Character, Integer> map = new HashMap<>();
        int n = s.length(), m=t.length();

        for(int i=0; i<m;i++)
            map.put(t.charAt(i) , map.getOrDefault(t.charAt(i), 0)+1);
    }
}

```

```

int count = map.size();
int start = 0, end = 0, min = Integer.MAX_VALUE;
String substring = "";

while(end < n)
{
    char ch = s.charAt(end);
    if(map.containsKey(ch))
    {
        map.put(ch, map.get(ch) - 1);
        if(map.get(ch) == 0)
            count--;
    }
    if(count > 0)
        end++;

    else if(count == 0)
    {
        while(count == 0)
        {
            if(end - start + 1 < min)
            {
                min = end - start + 1;
                substring = s.substring(start, end + 1);
            }
            char temp = s.charAt(start);
            if(map.containsKey(temp))
            {
                map.put(temp, map.get(temp) + 1);
                if(map.get(temp) == 1)
                    count++;
            }
            start++;
        }
        end++;
    }
}
return substring;
}

char* minWindow(char* s, char* t) {
    int sLen = strlen(s);
    int tLen = strlen(t);

    // Initialize arrays to store character frequencies
    int sFreq[128] = {0};
    int tFreq[128] = {0};

    // Count frequencies of characters in string t

```

```

for (int i = 0; i < tLen; i++) {
    tFreq[t[i]]++;
}

int left = 0; // Left pointer of the sliding window
int right = 0; // Right pointer of the sliding window
int minLen = sLen + 1; // Initialize to a value greater than sLen
int minStart = 0; // Start index of the minimum window

int requiredChars = tLen; // Number of characters still required to match t

while (right < sLen) {
    // Expand the window to the right
    if (tFreq[s[right]] > 0) {
        // This character is required
        requiredChars--;
    }
    tFreq[s[right]]--;
    right++;

    // Check if all characters from t are included in the window
    while (requiredChars == 0) {
        // Update the minimum window
        if (right - left < minLen) {
            minLen = right - left;
            minStart = left;
        }

        // Shrink the window from the left
        tFreq[s[left]]++;
        if (tFreq[s[left]] > 0) {
            // This character is no longer covered
            requiredChars++;
        }
        left++;
    }
}

// Check if a valid window was found
if (minLen == sLen + 1) {
    return "";
}

// Allocate memory for the result and copy the substring
char* result = malloc((minLen + 1) * sizeof(char));
strncpy(result, s + minStart, minLen);
result[minLen] = '\0';

return result;

```

```

}

int main() {
    char s[] = "ADOBECODEBANC";
    char t[] = "ABC";

    char* minWindowStr = minWindow(s, t);

    printf("Minimum window substring: %s\n", minWindowStr);

    free(minWindowStr); // Free allocated memory

    return 0;
}

```

1.181 Palindromic Substrings

Given a string s, return *the number of palindromic substrings in it.*

A string is a **palindrome** when it reads the same backward as forward.

A **substring** is a contiguous sequence of characters within the string.

Example 1:

Input: s = "abc"
Output: 3
Explanation: Three palindromic strings: "a", "b", "c".

Example 2:

Input: s = "aaa"
Output: 6
Explanation: Six palindromic strings: "a", "a", "a", "aa", "aa", "aaa".

```

// Function to expand around the center for odd length palindromes
int expandAroundCenterOdd(int left, int right, int n, char *s) {
    int cnt = 0;
    while (left >= 0 && right < n && s[left] == s[right]) {
        cnt++;
        left--;
        right++;
    }
    return cnt;
}

```

```

// Function to expand around the center for even length palindromes
int expandAroundCenterEven(int left, int right, int n, char *s) {
    int cnt = 0;
    while (left >= 0 && right < n && s[left] == s[right]) {
        cnt++;
        left--;
        right++;
    }
    return cnt;
}
int countSubstrings(char *s) {
    int n = strlen(s);
    int count = 0;

    for (int i = 0; i < n; i++) {
        // Expand around the center for odd length palindromes
        count += expandAroundCenterOdd(i, i, n, s);

        // Expand around the center for even length palindromes
        count += expandAroundCenterEven(i, i + 1, n, s);
    }

    return count;
}
int main() {
    char s[] = "abc";

    int numSubstrings = countSubstrings(s);

    printf("Number of palindromic substrings: %d\n", numSubstrings);

    return 0;
}

```

1.182 Encode And Decode Strings

Design an algorithm to encode **a list of strings** to **a string**. The encoded string is then sent over the network and is decoded back to the original list of strings.

Machine 1 (sender) has the function:

```

string encode(vector<string> strs) {
    // ... your code
    return encoded_string;
}

```

Machine 2 (receiver) has the function:

```

vector<string> decode(string s) {
    //... your code
}

```

```
    return strs;
}
```

So Machine 1 does:

```
string encoded_string = encode(strs);
```

and Machine 2 does:

```
vector<string> strs2 = decode(encoded_string);
```

strs2 in Machine 2 should be the same as strs in Machine 1.

Implement the encode and decode methods.

You are not allowed to solve the problem using any serialize methods (such as eval).

Example 1:

Input: dummy_input = ["Hello", "World"]

Output: ["Hello", "World"]

Explanation:

Machine 1:

```
Codec encoder = new Codec();
String msg = encoder.encode(strs);
Machine 1 ---msg---> Machine 2
```

Machine 2:

```
Codec decoder = new Codec();
String[] strs = decoder.decode(msg);
```

Example 2:

Input: dummy_input = [""]

Output: [""]

```
/** Encodes a list of strings to a single string */
char* encode(char** strs, int strsSize) {
    char *ret = malloc(strsSize * 200);
    char *ret_start = ret;

    /* Build string in the following format:
       <string_size>#<string> */
    for (int i = 0; i < strsSize; i++) {
        ret += sprintf(ret, "%d%s", (int) strlen(strs[i]), strs[i]);
```

```

        }
        printf("%s",ret_start);
        return ret_start;
    }

/***
 * Decodes a single string to a list of strings.
 *
 * Return an array of size *returnSize.
 * Note: The returned array must be malloced, assume caller calls free().
 */
char** decode(char* s, int* returnSize) {
    int i = 0;
    int j;
    char **ret = malloc(sizeof (char *) * 200);
    char len[4];
    int curr_char, str_len;
    int curr_str = 0;

    while (s[i] != '\0') {

        /* Find the length of this string */
        j = 0;
        memset(len, 0, sizeof(len));
        while (s[i] != '#') {
            len[j++] = s[i++];
        }
        str_len = atoi(len);
        i++;

        /* Extract the string */
        ret[curr_str] = malloc(str_len + 1);
        curr_char = 0;
        while (str_len > 0) {
            ret[curr_str][curr_char++] = s[i++];
            str_len--;
        }
        ret[curr_str][curr_char] = '\0';
        curr_str++;
    }
    *returnSize = curr_str;
    return ret;
}

int main() {
    char* strs[] = {"hello", "world", "foo", "bar"};
    int strsSize = 4;

    // Encode the list of strings
    char* encoded = encode(strs, strsSize);

```

```

printf("\nEncoded string: %s\n", encoded);

// Decode the encoded string
int returnSize;
char** decoded = decode(encoded, &returnSize);

// Print the decoded strings
printf("Decoded strings:\n");
for (int i = 0; i < returnSize; i++) {
    printf("%s\n", decoded[i]);
    free(decoded[i]); // Free memory allocated for each decoded string
}
free(decoded); // Free memory allocated for the decoded array

// Free memory allocated for the encoded string
free(encoded);

return 0;
}

// Your functions will be called as such:
// char* s = encode(strs, strsSize);
// decode(s, &returnSize);

```

1.183 Longest Common Subsequence

Given two strings `text1` and `text2`, return *the length of their longest common subsequence*. If there is no **common subsequence**, return 0.

A **subsequence** of a string is a new string generated from the original string with some characters (can be none) deleted without changing the relative order of the remaining characters.

- For example, "ace" is a subsequence of "abcde".

A **common subsequence** of two strings is a subsequence that is common to both strings.

Example 1:

Input: `text1 = "abcde"`, `text2 = "ace"`

Output: 3

Explanation: The longest common subsequence is "ace" and its length is 3.

Example 2:

Input: `text1 = "abc"`, `text2 = "abc"`

Output: 3

Explanation: The longest common subsequence is "abc" and its length is 3.

Example 3:

Input: text1 = "abc", text2 = "def"

Output: 0

Explanation: There is no such common subsequence, so the result is 0.

```
int max(int a, int b) {
    return a > b ? a : b;
}

int longestCommonSubsequence(char* text1, char* text2) {
    int len1 = strlen(text1);
    int len2 = strlen(text2);

    // Create a 2D array to store the lengths of LCS for subproblems
    int dp[len1 + 1][len2 + 1];

    // Initialize the first row and column to 0
    for (int i = 0; i <= len1; i++) {
        for (int j = 0; j <= len2; j++) {
            if (i == 0 || j == 0) {
                dp[i][j] = 0;
            }
        }
    }

    // Fill the dp array to find the length of LCS
    for (int i = 1; i <= len1; i++) {
        for (int j = 1; j <= len2; j++) {
            if (text1[i - 1] == text2[j - 1]) {
                dp[i][j] = dp[i - 1][j - 1] + 1;
            } else {
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
    }

    // The length of the LCS is stored in the bottom-right cell of dp array
    return dp[len1][len2];
}

#include <stdio.h>
#include <string.h>
```

```

int max(int a, int b) {
    return (a > b) ? a : b;
}

void findLCS(char* str1, char* str2) {
    int m = strlen(str1);
    int n = strlen(str2);

    int lcs[m + 1][n + 1];

    for (int i = 0; i <= m; i++) {
        for (int j = 0; j <= n; j++) {
            if (i == 0 || j == 0)
                lcs[i][j] = 0;
            else if (str1[i - 1] == str2[j - 1])
                lcs[i][j] = lcs[i - 1][j - 1] + 1;
            else
                lcs[i][j] = max(lcs[i - 1][j], lcs[i][j - 1]);
        }
    }

    int length = lcs[m][n];

    char result[length + 1];
    result[length] = '\0';

    int i = m, j = n;
    while (i > 0 && j > 0) {
        if (str1[i - 1] == str2[j - 1]) {
            result[length - 1] = str1[i - 1];
            i--;
            j--;
            length--;
        } else if (lcs[i - 1][j] > lcs[i][j - 1]) {
            i--;
        } else {
            j--;
        }
    }

    printf("Longest Common Subsequence: %s\n", result);
}

int main() {
    char str1[] = "ABCBDAB";
    char str2[] = "BDCAB";

    findLCS(str1, str2);
}

```

```
        return 0;
    }
```

1.184 Word Break

Given a string s and a dictionary of strings wordDict, return true if s can be segmented into a space-separated sequence of one or more dictionary words.

Note that the same word in the dictionary may be reused multiple times in the segmentation.

Example 1:

Input: s = "leetcode", wordDict = ["leet", "code"]

Output: true

Explanation: Return true because "leetcode" can be segmented as "leet code".

Example 2:

Input: s = "applepenapple", wordDict = ["apple", "pen"]

Output: true

Explanation: Return true because "applepenapple" can be segmented as "apple pen apple".

Note that you are allowed to reuse a dictionary word.

Example 3:

Input: s = "catsandog", wordDict = ["cats", "dog", "sand", "and", "cat"]

Output: false

```
class Solution {
    public boolean wordBreak(String s, List<String> wordDict) {
        int n = s.length();
        Set<String> words = new HashSet<>(wordDict);
        boolean[] dp = new boolean[n + 1];
        dp[0] = true;

        for (int i = 1; i <= n; i++) {
            for (int j = 0; j < i; j++) {
                if (dp[j] && words.contains(s.substring(j, i))) {
                    dp[i] = true;
                    break;
                }
            }
        }

        return dp[n];
    }
}
```

}

1.185 Combination Sum IV

Given an array of **distinct** integers `nums` and a target integer `target`, return *the number of possible combinations that add up to target*.

The test cases are generated so that the answer can fit in a **32-bit** integer.

Example 1:

Input: `nums = [1,2,3]`, `target = 4`

Output: 7

Explanation:

The possible combination ways are:

(1, 1, 1, 1)
(1, 1, 2)
(1, 2, 1)
(1, 3)
(2, 1, 1)
(2, 2)
(3, 1)

Note that different sequences are counted as different combinations.

```
class Solution {
```

```
    public int combinationSum4(int[] nums, int target) {
        // minor optimization
        // Arrays.sort(nums);
        int[] dp = new int[target + 1];
        dp[0] = 1;

        for (int combSum = 1; combSum < target + 1; ++combSum) {
            for (int num : nums) {
                if (combSum - num >= 0)
                    dp[combSum] += dp[combSum - num];
                // minor optimizaton, early stopping
                // else
                //     break;
            }
        }
        return dp[target];
    }
}
```

1.186 House Robber II

You are a professional robber planning to rob houses along a street. Each house has a certain amount of money stashed. All houses at this place are **arranged in a circle**. That means the first house is the

neighbor of the last one. Meanwhile, adjacent houses have a security system connected, and **it will automatically contact the police if two adjacent houses were broken into on the same night.**

Given an integer array `nums` representing the amount of money of each house, return *the maximum amount of money you can rob tonight without alerting the police.*

Example 1:

Input: `nums = [2,3,2]`

Output: 3

Explanation: You cannot rob house 1 (money = 2) and then rob house 3 (money = 2), because they are adjacent houses.

Example 2:

Input: `nums = [1,2,3,1]`

Output: 4

Explanation: Rob house 1 (money = 1) and then rob house 3 (money = 3).

Total amount you can rob = $1 + 3 = 4$.

Example 3:

Input: `nums = [1,2,3]`

Output: 3

```
class Solution {
    public int rob(int[] nums) {
        if (nums.length == 0)
            return 0;

        if (nums.length == 1)
            return nums[0];

        int max1 = rob_simple(nums, 0, nums.length - 2);
        int max2 = rob_simple(nums, 1, nums.length - 1);

        return Math.max(max1, max2);
    }

    public int rob_simple(int[] nums, int start, int end) {
        int t1 = 0;
        int t2 = 0;

        for (int i = start; i <= end; i++) {
            int temp = t1;

```

```

        int current = nums[i];
        t1 = Math.max(current + t2, t1);
        t2 = temp;
    }

    return t1;
}
}

```

1.187 Decode Ways

A message containing letters from A-Z can be encoded into numbers using the following mapping:

'A' -> "1"

'B' -> "2"

...

'Z' -> "26"

To decode an encoded message, all the digits must be grouped then mapped back into letters using the reverse of the mapping above (there may be multiple ways). For example, "11106" can be mapped into:

- "AAJF" with the grouping (1 1 10 6)
- "KJF" with the grouping (11 10 6)

Note that the grouping (1 11 06) is invalid because "06" cannot be mapped into 'F' since "6" is different from "06".

Given a string s containing only digits, return the number of ways to decode it.

The test cases are generated so that the answer fits in a 32-bit integer.

Example 1:

Input: s = "12"

Output: 2

Explanation: "12" could be decoded as "AB" (1 2) or "L" (12).

Example 2:

Input: s = "226"

Output: 3

Explanation: "226" could be decoded as "BZ" (2 26), "VF" (22 6), or "BBF" (2 2 6).

Example 3:

Input: s = "06"

Output: 0

Explanation: "06" cannot be mapped to "F" because of the leading zero ("6" is different from "06").

class Solution {

```

    public int numDecodings(String s) {
        if (s.charAt(0) == '0') {
            return 0;
        }

        int n = s.length();
        int twoBack = 1;
        int oneBack = 1;
        for (int i = 1; i < n; i++) {
            int current = 0;
            if (s.charAt(i) != '0') {
                current = oneBack;
            }
            int twoDigit = Integer.parseInt(s.substring(i - 1, i + 1));
            if (twoDigit >= 10 && twoDigit <= 26) {
                current += twoBack;
            }
        }
    }
}
```

```

        twoBack = oneBack;
        oneBack = current;
    }
    return oneBack;
}
}

```

1.188 Find Median From Data Stream

The **median** is the middle value in an ordered integer list. If the size of the list is even, there is no middle value, and the median is the mean of the two middle values.

- For example, for arr = [2,3,4], the median is 3.
- For example, for arr = [2,3], the median is $(2 + 3) / 2 = 2.5$.

Implement the MedianFinder class:

- MedianFinder() initializes the MedianFinder object.
- void addNum(int num) adds the integer num from the data stream to the data structure.
- double findMedian() returns the median of all elements so far. Answers within 10^{-5} of the actual answer will be accepted.

Example 1:

Input

```
["MedianFinder", "addNum", "addNum", "findMedian", "addNum", "findMedian"]
[], [1], [2], [], [3], []]
```

Output

```
[null, null, null, 1.5, null, 2.0]
```

Explanation

```
MedianFinder medianFinder = new MedianFinder();
medianFinder.addNum(1); // arr = [1]
medianFinder.addNum(2); // arr = [1, 2]
medianFinder.findMedian(); // return 1.5 (i.e., (1 + 2) / 2)
medianFinder.addNum(3); // arr[1, 2, 3]
medianFinder.findMedian(); // return 2.0
```

```
class MedianFinder {
    private PriorityQueue<Integer> small = new
PriorityQueue<>(Collections.reverseOrder());
    private PriorityQueue<Integer> large = new PriorityQueue<>();
    private boolean even = true;
    public MedianFinder() {

}

public void addNum(int num) {
    if (even) {
        large.offer(num);
    } else {
        int temp = large.poll();
        small.offer(temp);
        large.offer(num);
    }
    even = !even;
}}
```

```

        small.offer(large.poll());
    } else {
        small.offer(num);
        large.offer(small.poll());
    }
    even = !even;
}

public double findMedian() {
    if (even)
        return (small.peek() + large.peek()) / 2.0;
    else
        return small.peek();
}
}

/**
 * Your MedianFinder object will be instantiated and called as such:
 * MedianFinder obj = new MedianFinder();
 * obj.addNum(num);
 * double param_2 = obj.findMedian();
 */
class MedianFinder {

    ArrayList<Integer> list;

    public MedianFinder() {
        list = new ArrayList<>();
    }

    public void addNum(int num) {
        int i;
        if(list.size() > 0){
            for (i = 0; (i < list.size() && list.get(i) < num); i++);
            list.add(i , num);
        }else{
            list.add(num);
        }
    }

    public double findMedian() {
        // System.out.println(list);
        int index = list.size()/2;
        if(list.size() % 2 == 0){
            return (double) (list.get(index) + list.get(index - 1))/2;
        }else{
            return list.get(index);
        }
    }
}

```


```
}
```

1.189 Maximum Depth Of Binary Tree

Given the root of a binary tree, return *its maximum depth*.

A binary tree's **maximum depth** is the number of nodes along the longest path from the root node down to the farthest leaf node.

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: 3

Example 2:

Input: root = [1,null,2]

Output: 2

```
int max(int a, int b) {
    return (a > b) ? a : b;
}
int maxDepth(struct TreeNode* root){
    if (root == NULL) {
        return 0;
    }
    return max(1 + maxDepth(root -> left), 1 + maxDepth(root -> right));
}
```

```

}

int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(1);
    root->left = newNode(2);
    root->right = newNode(3);
    root->left->left = newNode(4);
    root->left->right = newNode(5);

    // Calculate the maximum depth of the binary tree
    int depth = maxDepth(root);

    // Print the result
    printf("Maximum depth of the binary tree: %d\n", depth);

    // Free dynamically allocated memory
    // In a real-world scenario, you should implement a function to free the entire tree
    free(root->left->right);
    free(root->left->left);
    free(root->right);
    free(root->left);
    free(root);

    return 0;
}


```

1.190 Same Tree

Given the roots of two binary trees p and q, write a function to check if they are the same or not.


Two binary trees are considered the same if they are structurally identical, and the nodes have the same value.

Example 1:




Input: p = [1,2,3], q = [1,2,3]
Output: true

Example 2:



Input: p = [1,2], q = [1,null,2]
Output: false

Example 3:



Input: p = [1,2,1], q = [1,1,2]
Output: false

```
bool isSameTree(struct TreeNode* p, struct TreeNode* q) {  
    if (p == NULL && q == NULL) {  
        return true;  
    }  
    else if ((p == NULL && q != NULL) ||  
             (q == NULL && p != NULL)) {  
        return false;  
    }  
    if (p->val != q->val) {  
        return false;  
    }  
    return isSameTree(p->left, q->left) && isSameTree(p->right, q->right);  
}
```

```

int main() {
    // Create two sample binary trees
    struct TreeNode* p = newNode(1);
    p->left = newNode(2);
    p->right = newNode(3);

    struct TreeNode* q = newNode(1);
    q->left = newNode(2);
    q->right = newNode(3);

    // Check if the two trees are the same
    bool result = isSameTree(p, q);

    // Print the result
    if (result) {
        printf("The two binary trees are the same.\n");
    } else {
        printf("The two binary trees are not the same.\n");
    }

    // Free dynamically allocated memory
    free(p->right);
    free(p->left);
    free(p);
    free(q->right);
    free(q->left);
    free(q);


    return 0;
}

```


1.191 Invert Binary Tree

Given the root of a binary tree, invert the tree, and return *its root*.

Example 1:



Example 2:



Example 3:

Input: root = []
Output: []

```
struct TreeNode* invertTree(struct TreeNode* root) {
    if (root == NULL) {
        return NULL;
    }

    // Swap left and right subtrees
    struct TreeNode* temp = root->left;
    root->left = root->right;
    root->right = temp;

    // Invert left and right subtrees recursively
    invertTree(root->left);
    invertTree(root->right);

    return root;
}
```

```

int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(4);
    root->left = newNode(2);
    root->right = newNode(7);
    root->left->left = newNode(1);
    root->left->right = newNode(3);
    root->right->left = newNode(6);
    root->right->right = newNode(9);

    // Print the original binary tree
    printf("Original binary tree (inorder traversal): ");
    printInorder(root);
    printf("\n");

    // Invert the binary tree
    struct TreeNode* invertedRoot = invertTree(root);

    // Print the inverted binary tree
    printf("Inverted binary tree (inorder traversal): ");
    printInorder(invertedRoot);
    printf("\n");

    // Free dynamically allocated memory
    // Note: Implementing a function to free the binary tree nodes is recommended for
    // larger trees.

    return 0;
}

```


1.192 Binary Tree Maximum Path Sum

A **path** in a binary tree is a sequence of nodes where each pair of adjacent nodes in the sequence has an edge connecting them. A node can only appear in the sequence **at most once**. Note that the path does not need to pass through the root.

The **path sum** of a path is the sum of the node's values in the path.

Given the root of a binary tree, return *the maximum **path sum** of any **non-empty** path*.

Example 1:




Input: root = [1,2,3]

Output: 6

Explanation: The optimal path is 2 -> 1 -> 3 with a path sum of $2 + 1 + 3 = 6$.

Example 2:



```

/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}
 *     TreeNode(int val) { this.val = val; }
 *     TreeNode(int val, TreeNode left, TreeNode right) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */

```

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
#define max(a,b) (a > b)?a:b
int helper(struct TreeNode* root, int *ans){
    // Escape condition
    if(!root) return 0;

    // DFS
    int left = max(0, helper(root->left,ans));
    int right = max(0, helper(root->right,ans));

    // There is also possibility left+parent+right > ans
    *ans = max(*ans, root->val + left + right);

    // Inorder to make the path continuous we can send either right or the left side,
    // So we will send the maximum side
    return root->val + max(left, right);
}
int maxPathSum(struct TreeNode* root) {
    // The answer
    int ans = INT_MIN;
    if(!root) return 0;

    // Recurssive function
    helper(root, &ans);
    return ans;
}

int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(10);
    root->left = newNode(2);
    root->right = newNode(10);
    root->left->left = newNode(20);
    root->left->right = newNode(1);
    root->right->right = newNode(-25);
    root->right->right->left = newNode(3);
    root->right->right->right = newNode(4);

    // Calculate the maximum path sum
    int maxSum = maxPathSum(root);
}

```

```

// Print the maximum path sum
printf("Maximum path sum in the binary tree: %d\n", maxSum);

// Free dynamically allocated memory
// Note: Implementing a function to free the binary tree nodes is recommended for
larger trees.

return 0;
}

class Solution {

int max = Integer.MIN_VALUE;

public int maxPath(TreeNode root) {

    if(root == null) return 0;

    int value = root.val;

    int left_sum = Math.max(maxPath(root.left),0);
    int right_sum = Math.max(maxPath(root.right),0);

    max = Math.max(max, left_sum + right_sum + value);

    return Math.max(left_sum, right_sum) + value;
}

public int maxPathSum(TreeNode root) {


    maxPath(root);
    return max;
}
}

```

1.193 Binary Tree Level Order Traversal

Given the root of a binary tree, return *the level order traversal of its nodes' values*. (i.e., from left to right, level by level).

Example 1:



Input: root = [3,9,20,null,null,15,7]

Output: [[3],[9,20],[15,7]]

Example 2:

Input: root = [1]

Output: [[1]]

Example 3:

Input: root = []

Output: []

```

int** levelOrder(struct TreeNode* root, int* returnSize, int** returnColumnSizes) {
    // Check if the tree is empty
    if (root == NULL) {
        *returnSize = 0;
        *returnColumnSizes = NULL;
        return NULL;
    }

    // Initialize a queue for BFS
    struct TreeNode** queue = (struct TreeNode**)malloc(sizeof(struct TreeNode*) * 10000);
    int front = 0, rear = -1;

    // Initialize 2D array to store level-order traversal
    int** result = (int**)malloc(sizeof(int*) * 10000);
    *returnColumnSizes = (int*)malloc(sizeof(int) * 10000);
    int levelSize = 0;
  
```

```

*returnSize = 0;

// Enqueue the root node
queue[++rear] = root;

while (front <= rear) {
    levelSize = rear - front + 1;
    (*returnColumnSizes)[*returnSize] = levelSize;

    // Allocate memory for the current level
    result[*returnSize] = (int*)malloc(sizeof(int) * levelSize);

    // Process nodes at the current level
    for (int i = 0; i < levelSize; i++) {
        struct TreeNode* node = queue[front++];
        result[*returnSize][i] = node->val;

        // Enqueue left and right children, if present
        if (node->left) queue[++rear] = node->left;
        if (node->right) queue[++rear] = node->right;
    }

    (*returnSize)++;
}

// Free the queue memory
free(queue);

return result;
}

int main() {
    // Create a sample binary tree
    struct TreeNode* root = newNode(3);
    root->left = newNode(9);
    root->right = newNode(20);
    root->right->left = newNode(15);
    root->right->right = newNode(7);

    // Variables to store the level-order traversal result
    int returnSize;
    int* returnColumnSizes;

    // Call the levelOrder function to get the level-order traversal
    int** result = levelOrder(root, &returnSize, &returnColumnSizes);

    // Print the level-order traversal result
    printf("Level-order traversal:\n");
    for (int i = 0; i < returnSize; i++) {
        printf("Level %d: ", i + 1);
    }
}

```

```

        for (int j = 0; j < returnColumnSizes[i]; j++) {
            printf("%d ", result[i][j]);
        }
        printf("\n");
        // Free memory allocated for each level
        free(result[i]);
    }

    // Free memory allocated for the result and column sizes
    free(result);
    free(returnColumnSizes);

    // Free memory allocated for the binary tree
    freeBinaryTree(root);


    return 0;
}

```

1.194 Kth Smallest Element In BST

Given the root of a binary search tree, and an integer k, return *the kth smallest value (1-indexed) of all the values of the nodes in the tree.*


Example 1:



Input: root = [3,1,4,null,2], k = 1

Output: 1

Example 2:



Input: root = [5,3,6,2,4,null,null,1], k = 3

Output: 3

```

class Solution {
    public ArrayList<Integer> inorder(TreeNode root, ArrayList<Integer> arr) {
        if (root == null) return arr;
        inorder(root.left, arr);
        arr.add(root.val);
        inorder(root.right, arr);
        return arr;
    }

    public int kthSmallest(TreeNode root, int k) {
        ArrayList<Integer> nums = inorder(root, new ArrayList<Integer>());
        return nums.get(k - 1);
    }
}

#include <stdio.h>
#include <stdlib.h>

// Definition for a binary tree node.
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to create a new binary tree node
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
}

```

```

        node->right = NULL;
        return node;
    }

// Function to free the memory allocated for a binary tree
void freeBinaryTree(struct TreeNode* root) {
    if (root == NULL) return;
    freeBinaryTree(root->left);
    freeBinaryTree(root->right);
    free(root);
}

// Function to perform inorder traversal and store values in an array
void inorder(struct TreeNode* root, int* arr, int* index) {
    if (root == NULL) return;
    inorder(root->left, arr, index);
    arr[(*index)++] = root->val;
    inorder(root->right, arr, index);
}

// Function to find the kth smallest element in a BST
int kthSmallest(struct TreeNode* root, int k) {
    int arr[10000]; // Assuming a maximum of 10000 nodes
    int index = 0;
    inorder(root, arr, &index);
    return arr[k - 1];
}

int main() {
    // Create a sample binary search tree
    struct TreeNode* root = newNode(3);
    root->left = newNode(1);
    root->right = newNode(4);
    root->left->right = newNode(2);

    // Find the kth smallest element
    int k = 1; // Example: find the 1st smallest element
    int kth = kthSmallest(root, k);
    printf("The %dth smallest element is: %d\n", k, kth);

    // Free memory allocated for the binary tree
    freeBinaryTree(root);

    return 0;
}


```

1.195 SubTree Of Another Tree

Given the roots of two binary trees root and subRoot, return true if there is a subtree of root with the same structure and node values of subRoot and false otherwise.

A subtree of a binary tree tree is a tree that consists of a node in tree and all of this node's descendants. The tree tree could also be considered as a subtree of itself.


Example 1:



Input: root = [3,4,5,1,2], subRoot = [4,1,2]

Output: true

Example 2:



Input: root = [3,4,5,1,2,null,null,null,null,0], subRoot = [4,1,2]

Output: false

```

#include <stdio.h>
#include <stdbool.h>

// Definition for a binary tree node
struct TreeNode {
    int val;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to check if two trees are identical
bool isSame(struct TreeNode* s, struct TreeNode* t) {
    if (s == NULL && t == NULL) return true;
    if (s == NULL || t == NULL) return false;
    if (s->val != t->val) return false;
    return isSame(s->left, t->left) && isSame(s->right, t->right);
}

// Function to check if t is a subtree of s
bool isSubtree(struct TreeNode* s, struct TreeNode* t) {
    if (s == NULL) return false;
    if (isSame(s, t)) return true;
    return isSubtree(s->left, t) || isSubtree(s->right, t);
}

int main() {

```

```

// Example trees
struct TreeNode node1 = {1, NULL, NULL};
struct TreeNode node2 = {2, NULL, NULL};
struct TreeNode node3 = {3, NULL, NULL};
struct TreeNode node4 = {4, NULL, NULL};
struct TreeNode node5 = {5, NULL, NULL};
struct TreeNode node6 = {6, NULL, NULL};

// Constructing the tree structure
node3.left = &node4;
node3.right = &node5;
node2.left = &node3;
node2.right = &node6;
node1.left = &node2;

// Example subtree
struct TreeNode subRoot = {2, NULL, NULL};
subRoot.left = &node3;
subRoot.right = &node6;

// Test the isSubtree function
if (isSubtree(&node1, &subRoot)) {
    printf("subRoot is a subtree of node1.\n");
} else {
    printf("subRoot is not a subtree of node1.\n");
}

return 0;
}

public class Solution {
    public boolean isSubtree(TreeNode s, TreeNode t) {
        if (s == null) return false;
        if (isSame(s, t)) return true;
        return isSubtree(s.left, t) || isSubtree(s.right, t);
    }

    private boolean isSame(TreeNode s, TreeNode t) {
        if (s == null && t == null) return true;
        if (s == null || t == null) return false;

        if (s.val != t.val) return false;

        return isSame(s.left, t.left) && isSame(s.right, t.right);
    }
}

```

1.196 Word Search II

Given an $m \times n$ board of characters and a list of strings words, return *all words on the board*.

Each word must be constructed from letters of sequentially adjacent cells, where **adjacent cells** are horizontally or vertically neighboring. The same letter cell may not be used more than once in a word.

Example 1:

o	a	a	n
e	t	a	e
i	h	k	r
i	f	l	v

Input: board = [["o","a","a","n"],["e","t","a","e"],["i","h","k","r"],["i","f","l","v"]], words = ["oath","pea","eat","rain"]

Output: ["eat","oath"]

Example 2:

a	b
c	d

Input: board = [["a","b"],["c","d"]], words = ["abcb"]

Output: []

```

class TrieNode {
    HashMap<Character, TrieNode> children = new HashMap<Character, TrieNode>();
    String word = null;
    public TrieNode() {}
}

class Solution {
    char[][] _board = null;
    ArrayList<String> _result = new ArrayList<String>();

    public List<String> findWords(char[][] board, String[] words) {

        // Step 1). Construct the Trie
        TrieNode root = new TrieNode();
        for (String word : words) {
            TrieNode node = root;

            for (Character letter : word.toCharArray()) {
                if (node.children.containsKey(letter)) {
                    node = node.children.get(letter);
                } else {
                    TrieNode newNode = new TrieNode();
                    node.children.put(letter, newNode);
                    node = newNode;
                }
            }
            node.word = word; // store words in Trie
        }

        this._board = board;
        // Step 2). Backtracking starting for each cell in the board
        for (int row = 0; row < board.length; ++row) {
            for (int col = 0; col < board[row].length; ++col) {
                if (root.children.containsKey(board[row][col])) {
                    backtracking(row, col, root);
                }
            }
        }
    }

    return this._result;
}

private void backtracking(int row, int col, TrieNode parent) {
    Character letter = this._board[row][col];
    TrieNode currNode = parent.children.get(letter);

    // check if there is any match
}

```

```

if (currNode.word != null) {
    this._result.add(currNode.word);
    currNode.word = null;
}

// mark the current letter before the EXPLORATION
this._board[row][col] = '#';

// explore neighbor cells in around-clock directions: up, right, down, left
int[] rowOffset = {-1, 0, 1, 0};
int[] colOffset = {0, 1, 0, -1};
for (int i = 0; i < 4; ++i) {
    int newRow = row + rowOffset[i];
    int newCol = col + colOffset[i];
    if (newRow < 0 || newRow >= this._board.length || newCol < 0
        || newCol >= this._board[0].length) {
        continue;
    }
    if (currNode.children.containsKey(this._board[newRow][newCol])) {
        backtracking(newRow, newCol, currNode);
    }
}

// End of EXPLORATION, restore the original letter in the board.
this._board[row][col] = letter;

// Optimization: incrementally remove the leaf nodes
if (currNode.children.isEmpty()) {
    parent.children.remove(letter);
}
}
}

```

1.197 Clone Graph

Given a reference of a node in a **connected** undirected graph.

Return a **deep copy** (clone) of the graph.

Each node in the graph contains a value (int) and a list (List[Node]) of its neighbors.

```

class Node {
    public int val;
    public List<Node> neighbors;
}

```


Test case format:

For simplicity, each node's value is the same as the node's index (1-indexed). For example, the first node with `val == 1`, the second node with `val == 2`, and so on. The graph is represented in the test case using an adjacency list.

An adjacency list is a collection of unordered **lists** used to represent a finite graph. Each list describes the set of neighbors of a node in the graph.

The given node will always be the first node with `val = 1`. You must return the **copy of the given node** as a reference to the cloned graph.

Example 1:



Input: adjList = [[2,4],[1,3],[2,4],[1,3]]

Output: [[2,4],[1,3],[2,4],[1,3]]

Explanation: There are 4 nodes in the graph.

1st node (val = 1)'s neighbors are 2nd node (val = 2) and 4th node (val = 4).

2nd node (val = 2)'s neighbors are 1st node (val = 1) and 3rd node (val = 3).

3rd node (val = 3)'s neighbors are 2nd node (val = 2) and 4th node (val = 4).

4th node (val = 4)'s neighbors are 1st node (val = 1) and 3rd node (val = 3).

Example 2:

1

```
#include <stdlib.h>
#include <stdio.h>

struct Node {
    int val;
    struct Node** neighbors;
    int numNeighbors;
};

struct Node* cloneGraphUtil(struct Node* node, struct Node** visited) {
    if (node == NULL) {
        return NULL;
    }

    // If the node was already visited before.
    // Return the clone from the visited array.
    if (visited[node->val] != NULL) {
        return visited[node->val];
    }

    // Create a clone for the given node.
    // Note that we don't have cloned neighbors as of now, hence NULL.
    struct Node* cloneNode = (struct Node*)malloc(sizeof(struct Node));
    cloneNode->val = node->val;
    cloneNode->neighbors = (struct Node**)malloc(node->numNeighbors * sizeof(struct Node*));
    cloneNode->numNeighbors = node->numNeighbors;

    // Mark the original node as visited and store its clone.
    visited[node->val] = cloneNode;

    // Iterate through the neighbors to generate their clones
    // and prepare an array of cloned neighbors to be added to the cloned node.
    for (int i = 0; i < node->numNeighbors; i++) {
        cloneNode->neighbors[i] = cloneGraphUtil(node->neighbors[i], visited);
    }

    return cloneNode;
}

struct Node* cloneGraph(struct Node* node) {
```

```

if (node == NULL) {
    return NULL;
}

// Allocate memory for visited array and initialize it to NULL
struct Node** visited = (struct Node**)calloc(101, sizeof(struct Node*));

// Call the utility function to clone the graph
struct Node* clonedGraph = cloneGraphUtil(node, visited);

// Free the memory allocated for the visited array
free(visited);

return clonedGraph;
}

int main() {
    // Create a graph for testing
    struct Node* originalGraph = createGraph();

    // Clone the graph
    struct Node* clonedGraph = cloneGraph(originalGraph);

    // Print the cloned graph
    printf("Original Graph:\n");
    printGraph(originalGraph);
    printf("\nCloned Graph:\n");
    printGraph(clonedGraph);

    // Free the memory allocated for the original and cloned graphs
    // (Assuming a function to free the graph nodes is implemented)
    // freeGraph(originalGraph);
    // freeGraph(clonedGraph);

    return 0;
}

```

Input: adjList = []

Output: []

Explanation: Note that the input contains one empty list. The graph consists of only one node with val = 1 and it does not have any neighbors.

Example 3:

Input: adjList = []

Output: []

Explanation: This is an empty graph, it does not have any nodes.

```

class Solution {
    private HashMap <Node, Node> visited = new HashMap <> ();
    public Node cloneGraph(Node node) {

```

```

if (node == null) {
    return node;
}

// If the node was already visited before.
// Return the clone from the visited dictionary.
if (visited.containsKey(node)) {
    return visited.get(node);
}

// Create a clone for the given node.
// Note that we don't have cloned neighbors as of now, hence [].
Node cloneNode = new Node(node.val, new ArrayList());
// The key is original node and value being the clone node.
visited.put(node, cloneNode);

// Iterate through the neighbors to generate their clones
// and prepare a list of cloned neighbors to be added to the cloned node.
for (Node neighbor: node.neighbors) {
    cloneNode.neighbors.add(cloneGraph(neighbor));
}
return cloneNode;
}

```

1.198 Course Schedule

There are a total of numCourses courses you have to take, labeled from 0 to numCourses - 1. You are given an array prerequisites where prerequisites[i] = [a, b] indicates that you **must** take course b first if you want to take course a.

- For example, the pair [0, 1], indicates that to take course 0 you have to first take course 1.

Return true if you can finish all courses. Otherwise, return false.

Example 1:

Input: numCourses = 2, prerequisites = [[1,0]]

Output: true

Explanation: There are a total of 2 courses to take.

To take course 1 you should have finished course 0. So it is possible.

Example 2:

Input: numCourses = 2, prerequisites = [[1,0],[0,1]]

Output: false

Explanation: There are a total of 2 courses to take.

To take course 1 you should have finished course 0, and to take course 0 you should also have finished course 1. So it is impossible.

```

class Solution {
    public boolean canFinish(int numCourses, int[][] prerequisites) {
        int[] indegree = new int[numCourses];
        List<List<Integer>> adj = new ArrayList<>(numCourses);

        for (int i = 0; i < numCourses; i++) {
            adj.add(new ArrayList<>());
        }

        for (int[] prerequisite : prerequisites) {
            adj.get(prerequisite[1]).add(prerequisite[0]);
            indegree[prerequisite[0]]++;
        }

        Queue<Integer> queue = new LinkedList<>();
        // Push all the nodes with indegree zero in the queue.
        for (int i = 0; i < numCourses; i++) {
            if (indegree[i] == 0) {
                queue.offer(i);
            }
        }

        int nodesVisited = 0;
        while (!queue.isEmpty()) {
            int node = queue.poll();
            nodesVisited++;

            for (int neighbor : adj.get(node)) {
                // Delete the edge "node -> neighbor".
                indegree[neighbor]--;
                if (indegree[neighbor] == 0) {
                    queue.offer(neighbor);
                }
            }
        }

        return nodesVisited == numCourses;
    }
}

class Solution {
    public boolean dfs(int node, List<List<Integer>> adj, boolean[] visit, boolean[] inStack) {
        // If the node is already in the stack, we have a cycle.
        if (inStack[node]) {
            return true;
        }
        if (visit[node]) {
            return false;
        }
        // Mark the current node as visited and part of current recursion stack.
        visit[node] = true;
        inStack[node] = true;
        for (int neighbor : adj.get(node)) {
            if (dfs(neighbor, adj, visit, inStack)) {

```

```

        return true;
    }
}

// Remove the node from the stack.
inStack[node] = false;
return false;
}

public boolean canFinish(int numCourses, int[][] prerequisites) {
    List<List<Integer>> adj = new ArrayList<>(numCourses);
    for (int i = 0; i < numCourses; i++) {
        adj.add(new ArrayList<>());
    }

    for (int[] prerequisite : prerequisites) {
        adj.get(prerequisite[1]).add(prerequisite[0]);
    }

    boolean[] visit = new boolean[numCourses];
    boolean[] inStack = new boolean[numCourses];
    for (int i = 0; i < numCourses; i++) {
        if (dfs(i, adj, visit, inStack)) {
            return false;
        }
    }
    return true;
}

```

1.199 Pacific Atlantic Water Flow


There is an $m \times n$ rectangular island that borders both the **Pacific Ocean** and **Atlantic Ocean**. The **Pacific Ocean** touches the island's left and top edges, and the **Atlantic Ocean** touches the island's right and bottom edges.

The island is partitioned into a grid of square cells. You are given an $m \times n$ integer matrix heights where $\text{heights}[r][c]$ represents the **height above sea level** of the cell at coordinate (r, c) .

The island receives a lot of rain, and the rain water can flow to neighboring cells directly north, south, east, and west if the neighboring cell's height is **less than or equal to** the current cell's height. Water can flow from any cell adjacent to an ocean into the ocean.

Return **a 2D list of grid coordinates result where result[i] = [r, c]** denotes that rain water can flow from cell (r, c) to **both** the Pacific and Atlantic oceans.

Example 1:



Input: heights = [[1,2,2,3,5],[3,2,3,4,4],[2,4,5,3,1],[6,7,1,4,5],[5,1,1,2,4]]

Output: [[0,4],[1,3],[1,4],[2,2],[3,0],[3,1],[4,0]]

Explanation: The following cells can flow to the Pacific and Atlantic oceans, as shown below:

[0,4]: [0,4] -> Pacific Ocean

[0,4] -> Atlantic Ocean

[1,3]: [1,3] -> [0,3] -> Pacific Ocean

[1,3] -> [1,4] -> Atlantic Ocean

[1,4]: [1,4] -> [1,3] -> [0,3] -> Pacific Ocean

[1,4] -> Atlantic Ocean

[2,2]: [2,2] -> [1,2] -> [0,2] -> Pacific Ocean

[2,2] -> [2,3] -> [2,4] -> Atlantic Ocean

[3,0]: [3,0] -> Pacific Ocean

[3,0] -> [4,0] -> Atlantic Ocean

[3,1]: [3,1] -> [3,0] -> Pacific Ocean

[3,1] -> [4,1] -> Atlantic Ocean

[4,0]: [4,0] -> Pacific Ocean

[4,0] -> Atlantic Ocean

Note that there are other possible paths for these cells to flow to the Pacific and Atlantic oceans.

Example 2:

Input: heights = [[1]]

Output: [[0,0]]

Explanation: The water can flow from the only cell to the Pacific and Atlantic oceans.

```
class Solution {
```

```

    private static final int[][] DIRECTIONS = new int[][]{{0, 1}, {1, 0}, {-1, 0}, {0, -1}};
}
private int numRows;
private int numCols;
private int[][] landHeights;

public List<List<Integer>> pacificAtlantic(int[][] matrix) {
    // Check if input is empty
    if (matrix.length == 0 || matrix[0].length == 0) {
        return new ArrayList<>();
    }

    // Save initial values to parameters
    numRows = matrix.length;
    numCols = matrix[0].length;
    landHeights = matrix;
    boolean[][] pacificReachable = new boolean[numRows][numCols];
    boolean[][] atlanticReachable = new boolean[numRows][numCols];

    // Loop through each cell adjacent to the oceans and start a DFS
    for (int i = 0; i < numRows; i++) {
        dfs(i, 0, pacificReachable);
        dfs(i, numCols - 1, atlanticReachable);
    }
    for (int i = 0; i < numCols; i++) {
        dfs(0, i, pacificReachable);
        dfs(numRows - 1, i, atlanticReachable);
    }

    // Find all cells that can reach both oceans
    List<List<Integer>> commonCells = new ArrayList<>();
    for (int i = 0; i < numRows; i++) {
        for (int j = 0; j < numCols; j++) {
            if (pacificReachable[i][j] && atlanticReachable[i][j]) {
                commonCells.add(List.of(i, j));
            }
        }
    }
    return commonCells;
}

private void dfs(int row, int col, boolean[][] reachable) {
    // This cell is reachable, so mark it
    reachable[row][col] = true;
    for (int[] dir : DIRECTIONS) { // Check all 4 directions
        int newRow = row + dir[0];
        int newCol = col + dir[1];
        // Check if new cell is within bounds
        if (newRow < 0 || newRow >= numRows || newCol < 0 || newCol >= numCols) {
            continue;
        }
        // Check that the new cell hasn't already been visited
        if (reachable[newRow][newCol]) {
            continue;
        }
        // Check that the new cell has a higher or equal height,
        // So that water can flow from the new cell to the old cell
    }
}

```

```

        if (landHeights[newRow][newCol] < landHeights[row][col]) {
            continue;
        }
        // If we've gotten this far, that means the new cell is reachable
        dfs(newRow, newCol, reachable);
    }
}

```

1.200 Alien Dictionary

There is a new alien language that uses the English alphabet. However, the order of the letters is unknown to you.

You are given a list of strings words from the alien language's dictionary. Now it is claimed that the strings in words are

sorted lexicographically
by the rules of this new language.

If this claim is incorrect, and the given arrangement of string in words cannot correspond to any order of letters, return "".

Otherwise, return a string of the unique letters in the new alien language sorted in **lexicographically increasing order** by the new language's rules. If there are multiple solutions, return **any of them**.



Example 1:

Input: words = ["wrt", "wrf", "er", "ett", "rftt"]
Output: "wertf"

Example 2:

Input: words = ["z", "x"]
Output: "zx"

Example 3:

Input: words = ["z", "x", "z"]
Output: ""
Explanation: The order is invalid, so return "".



```

class Solution {
    public String alienOrder(String[] words) {
        if(words.length==0)
            return "";
        Map<Character, Integer> inDegree=new HashMap<>();

```

```

Map<Character, List<Character>> graph = new HashMap<>();
//a. Initialise adjacency list and in degree map
for (String word : words) {
    for (char character : word.toCharArray()) {
        inDegree.put(character, 0);
        graph.put(character, new ArrayList<Character>());
    }
}
for (int i=0; i<words.length-1; i++) {
    String w1 = words[i], w2 = words[i + 1];
    //Checks if str1 starts with str2
    if (w1.length() > w2.length() && w1.startsWith(w2)) {
        return "";
    }
    //b. Build the graph and in degree map
    for (int j = 0; j < Math.min(w1.length(), w2.length()); j++) {
        char parent = w1.charAt(j), child = w2.charAt(j);
        if (parent != child) { // if the two characters are different
            graph.get(parent).add(child); // put the child into it's parent's list
            inDegree.put(child, inDegree.get(child) + 1); // increment child's
inDegree
            break; // only the first different character between the two words
will help us find the order
        }
    }
}
// c. Find all sources i.e., all vertices with 0 in-degrees
Queue<Character> sources = new LinkedList<>();
for (Map.Entry<Character, Integer> entry : inDegree.entrySet()) {
    if (entry.getValue() == 0)
        sources.add(entry.getKey());
}
// d. For each source, add it to the sortedOrder and subtract one from all of
its children's in-degrees
// if a child's in-degree becomes zero, add it to the sources queue
StringBuilder sortedOrder = new StringBuilder();
while (!sources.isEmpty()) {
    Character vertex = sources.poll();
    sortedOrder.append(vertex);
    List<Character> children = graph.get(vertex); // get the node's children to
decrement their in-degrees
    for (Character child : children) {
        inDegree.put(child, inDegree.get(child) - 1);
        if (inDegree.get(child) == 0)
            sources.add(child);
    }
}

```

```

        // if sortedOrder doesn't contain all characters, there is a cyclic dependency
        // between characters, therefore, we
        // will not be able to find the correct ordering of the characters
        if (sortedOrder.length() != inDegree.size())
            return "";

        return sortedOrder.toString();
    }
}


```

1.201 Graph Valid Tree

You have a graph of n nodes labeled from 0 to $n - 1$. You are given an integer n and a list of edges where $\text{edges}[i] = [a, b]$ indicates that there is an undirected edge between nodes a and b in the graph.

Return true *if the edges of the given graph make up a valid tree, and false otherwise.*


Example 1:



Input: $n = 5$, $\text{edges} = [[0,1],[0,2],[0,3],[1,4]]$

Output: true

Example 2:



Input: n = 5, edges = [[0,1],[1,2],[2,3],[1,3],[1,4]]
Output: false

```

class Solution {
    // A graph is considered a tree if it is connected and the number of edges = n-1 nodes
    public boolean validTree(int n, int[][] edges) {
        List<List<Integer>> graph = new ArrayList<>();

        //create graph
        for (int i = 0; i < n; i++) {
            graph.add(new ArrayList<>());
        }

        //since this is an undirected graph, make each edge go both ways
        for (int[] edge : edges) {
            graph.get(edge[1]).add(edge[0]);
            graph.get(edge[0]).add(edge[1]);
        }
    }

    HashSet<Integer> visited = new HashSet<>();

    //if graph is connected then we would be able to start from any node and reach all the
    other nodes using dfs
    //we can dfs starting from first node since this is guaranteed to exist according to constraints
    dfs(visited, 0, graph);

    //if we see an unvisited node,
    //the graph is not connected and therefore cannot be a tree
    for (int i = 0; i < n; i++) {
        if(!visited.contains(i)) return false;
    }

    //also check number of edges = n-1 nodes
    return (edges.length == n-1);
}

```

```

    }

public void dfs(HashSet<Integer> visited, int currNode, List<List<Integer>> graph) {
    visited.add(currNode);
    for (Integer node : graph.get(currNode)) {
        if(!visited.contains(node)) {
            dfs(visited, node, graph);
        }
    }
}


```

1.202 Number Of Connected Components In an Undirected Graph

You have a graph of n nodes. You are given an integer n and an array edges where edges[i] = [a_i, b_i] indicates that there is an edge between a_i and b_i in the graph.

Return *the number of connected components in the graph*.


Example 1:



Input: n = 5, edges = [[0,1],[1,2],[3,4]]

Output: 2

Example 2:



Input: n = 5, edges = [[0,1],[1,2],[2,3],[3,4]]

Output: 1

```

class Solution {
    public int countComponents(int n, int[][] edges) {
        int[] roots = new int[n];
        for(int i = 0; i < n; i++) roots[i] = i;

        for(int[] e : edges) {
            int root1 = find(roots, e[0]);
            int root2 = find(roots, e[1]);
            if(root1 != root2) {
                roots[root1] = root2; // union
                n--;
            }
        }
        return n;
    }

    public int find(int[] roots, int id) {
        while(roots[id] != id) {
            roots[id] = roots[roots[id]]; // optional: path compression
            id = roots[id];
        }
        return id;
    }
}

```

1.203 Longest Prefix Match - Trie

```

#include <stdio.h>
#include <stdlib.h>
#include <stdint.h>

// Define the structure for a trie node
typedef struct TrieNode {
    struct TrieNode* children[2]; // Assuming binary trie for IPv4 addresses
    int isLeaf;
} TrieNode;

```

```

// Function to create a new trie node
TrieNode* createNode() {
    TrieNode* node = (TrieNode*)malloc(sizeof(TrieNode));
    for (int i = 0; i < 2; i++) {
        node->children[i] = NULL;
    }
    node->isLeaf = 0;
    return node;
}

// Function to insert an IP address prefix into the trie
void insert(TrieNode* root, uint32_t prefix, int length) {
    TrieNode* current = root;
    for (int i = 31; i >= 32 - length; i--) {
        int bit = (prefix >> i) & 1;
        if (!current->children[bit]) {
            current->children[bit] = createNode();
        }
        current = current->children[bit];
    }
    current->isLeaf = 1;
}

// Function to perform longest prefix match and return the matched prefix
uint32_t longestPrefixMatch(TrieNode* root, uint32_t ip) {
    TrieNode* current = root;
    uint32_t match = 0;
    for (int i = 31; i >= 0; i--) {
        int bit = (ip >> i) & 1;
        if (current->children[bit]) {
            current = current->children[bit];
            match = (match << 1) | bit; // Append the current bit to the matched prefix
        } else {
            break;
        }
    }
    return match;
}

int main() {
    // Example usage
    TrieNode* root = createNode();

    // Insert some prefixes into the trie
    insert(root, 0xC0A80100, 24); // 192.168.1.0/24
    insert(root, 0xC0A80180, 26); // 192.168.1.128/26
    insert(root, 0xAC100001, 16); // 172.16.0.0/16

    // Test longest prefix match
}

```

```

    uint32_t ipAddress = 0xC0A80145; // 192.168.1.69
    uint32_t matchedPrefix = longestPrefixMatch(root, ipAddress);

    if (matchedPrefix > 0) {
        printf("Longest prefix matched: %0x%x\n", matchedPrefix);
    } else {
        printf("No matching prefix found.\n");
    }

    return 0;
}

```

Next Solution:

```

#include <stdio.h>
#include <stdint.h>
#include <stdlib.h>

#define IPV4_OCTETS 4

// Trie Node Definition
typedef struct TrieNode {
    struct TrieNode* children[2];
    int isIPPPrefix;
    int prefixLength;
} TrieNode;

// Function to create a new trie node
TrieNode* createNode() {
    TrieNode* newNode = (TrieNode*)malloc(sizeof(TrieNode));
    for (int i = 0; i < 2; ++i) {
        newNode->children[i] = NULL;
    }
    newNode->isIPPPrefix = 0;
    newNode->prefixLength = 0;
    return newNode;
}

// Function to insert an IP prefix into the trie
void insertIPPPrefix(TrieNode* root, uint8_t* ipAddress, int prefixLength) {
    TrieNode* current = root;

    for (int i = 0; i < prefixLength; ++i) {
        int bit = (ipAddress[i / 8] >> (7 - (i % 8))) & 1;

        if (current->children[bit] == NULL) {
            current->children[bit] = createNode();
        }

        current = current->children[bit];
    }
}

```

```

}

current->isIPPrefix = 1;
current->prefixLength = prefixLength;
}

// Function to perform longest prefix match using the trie
int longestPrefixMatch(TrieNode* root, uint8_t* ipAddress) {
    TrieNode* current = root;
    int lastMatchedPrefix = -1;

    for (int i = 0; i < IPV4_OCTETS * 8; ++i) {
        int bit = (ipAddress[i / 8] >> (7 - (i % 8))) & 1;

        if (current->children[bit] == NULL) {
            break;
        }

        current = current->children[bit];

        if (current->isIPPrefix) {
            lastMatchedPrefix = i;
        }
    }
}

return lastMatchedPrefix;
}

// Function to free memory allocated for the trie
void freeTrie(TrieNode* root) {
    if (root == NULL) {
        return;
    }

    for (int i = 0; i < 2; ++i) {
        freeTrie(root->children[i]);
    }

    free(root);
}

int main() {
    TrieNode* root = createNode();

    // Sample IP prefixes
    uint8_t ipPrefix1[IPV4_OCTETS] = {192, 168, 1, 0};
    uint8_t ipPrefix2[IPV4_OCTETS] = {192, 168, 1, 0};
    uint8_t ipPrefix3[IPV4_OCTETS] = {192, 168, 2, 0};
}

```

```

insertIPPrefix(root, ipPrefix1, 24); // Insert IP prefix 192.168.1.0/24
insertIPPrefix(root, ipPrefix2, 16); // Insert IP prefix 192.168.1.0/16
insertIPPrefix(root, ipPrefix3, 24); // Insert IP prefix 192.168.2.0/24

// Sample IP addresses to match
uint8_t ipAddress1[IPV4_OCTETS] = {192, 168, 1, 42};
uint8_t ipAddress2[IPV4_OCTETS] = {192, 168, 2, 42};
uint8_t ipAddress3[IPV4_OCTETS] = {192, 169, 1, 42};

// Perform longest prefix match
int matchIndex1 = longestPrefixMatch(root, ipAddress1);
int matchIndex2 = longestPrefixMatch(root, ipAddress2);
int matchIndex3 = longestPrefixMatch(root, ipAddress3);

// Print results
if (matchIndex1 != -1) {
    printf("Longest prefix match for IP 192.168.1.42: Prefix %d\n", matchIndex1);
} else {
    printf("No match for IP 192.168.1.42\n");
}

if (matchIndex2 != -1) {
    printf("Longest prefix match for IP 192.168.2.42: Prefix %d\n", matchIndex2);
} else {
    printf("No match for IP 192.168.2.42\n");
}

if (matchIndex3 != -1) {
    printf("Longest prefix match for IP 192.169.1.42: Prefix %d\n", matchIndex3);
} else {
    printf("No match for IP 192.169.1.42\n");
}

// Free allocated memory
freeTrie(root);

return 0;
}

```

1.204 UDP Socket Communication Client and Server

Server:

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <arpa/inet.h>

#define PORT 8080
#define BUFFER_SIZE 1024

int main() {

```

```

int serverSocket;
struct sockaddr_in serverAddress, clientAddress;
char buffer[BUFFER_SIZE];

// Creating UDP socket
if ((serverSocket = socket(AF_INET, SOCK_DGRAM, 0)) == -1) {
    perror("Socket creation failed");
    exit(EXIT_FAILURE);
}

memset(&serverAddress, 0, sizeof(serverAddress));
memset(&clientAddress, 0, sizeof(clientAddress));

// Server address configuration
serverAddress.sin_family = AF_INET; // IPv4
serverAddress.sin_addr.s_addr = INADDR_ANY;
serverAddress.sin_port = htons(PORT);

// Binding the socket
if (bind(serverSocket, (const struct sockaddr*)&serverAddress,
sizeof(serverAddress)) == -1) {
    perror("Bind failed");
    exit(EXIT_FAILURE);
}

printf("Server listening on port %d...\n", PORT);

while (1) {
    socklen_t len = sizeof(clientAddress);

    // Receiving message from the client
    ssize_t dataSize = recvfrom(serverSocket, (char*)buffer, BUFFER_SIZE, 0, (struct
sockaddr*)&clientAddress, &len);
    buffer[dataSize] = '\0';

    printf("Received message from client: %s\n", buffer);

    // Sending acknowledgment back to the client
    sendto(serverSocket, "Acknowledgment: Message received", strlen("Acknowledgment:
Message received"), 0, (const struct sockaddr*)&clientAddress, len);
}

close(serverSocket);

return 0;
}

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <arpa/inet.h>

```

Client:

```
#define PORT 8080
```

```

#define SERVER_IP "127.0.0.1"
#define BUFFER_SIZE 1024

int main() {
    int clientSocket;
    struct sockaddr_in serverAddress;
    char buffer[BUFFER_SIZE];

    // Creating UDP socket
    if ((clientSocket = socket(AF_INET, SOCK_DGRAM, 0)) == -1) {
        perror("Socket creation failed");
        exit(EXIT_FAILURE);
    }

    memset(&serverAddress, 0, sizeof(serverAddress));

    // Server address configuration
    serverAddress.sin_family = AF_INET; // IPv4
    serverAddress.sin_port = htons(PORT);
    if (inet_pton(AF_INET, SERVER_IP, &serverAddress.sin_addr) <= 0) {
        perror("Invalid address/ Address not supported");
        exit(EXIT_FAILURE);
    }

    while (1) {
        printf("Enter message for the server (or type 'exit' to quit): ");
        fgets(buffer, BUFFER_SIZE, stdin);

        // Sending message to the server
        sendto(clientSocket, (const char*)buffer, strlen(buffer), 0, (const struct
        sockaddr*)&serverAddress, sizeof(serverAddress));

        if (strcmp(buffer, "exit\n") == 0) {
            break;
        }

        memset(buffer, 0, BUFFER_SIZE);

        // Receiving acknowledgment from the server
        ssize_t dataSize = recvfrom(clientSocket, (char*)buffer, BUFFER_SIZE, 0, NULL,
        NULL);
        buffer[dataSize] = '\0';

        printf("Server acknowledgment: %s\n", buffer);
    }

    close(clientSocket);

    return 0;
}

```

}

1.205 TCP Socket Communication Client and Server

Server:

```
#include<stdio.h>
#include<arpa/inet.h>
#include<string.h>
#include<stdlib.h>
#include<pthread.h>
#define MAX 10
void *handle_client(void *arg) {
    int client_fd = *((int *)arg);
    char buffer[100];
    printf("\nClient connected!");
    send(client_fd, "Hi from Server!", strlen("Hi from Server!"), 0);
    recv(client_fd, buffer, sizeof(buffer), 0);
    printf("\nClient sent : %s", buffer);
    close(client_fd);
    pthread_exit(NULL);
}
void main() {
    printf("\nSERVER INITIALIZING!");
    int server_fd = 0;
    int connected_fd = 0;
    struct sockaddr_in server_addr = {0};
    pthread_t tid[MAX];
    static int i = 0;
    int opt = 1;

    if ((server_fd = socket(AF_INET, SOCK_STREAM, 0)) == 0) {
        perror("\nServer Socket creation failed!");
        return;
    }

    if (setsockopt(server_fd, SOL_SOCKET, SO_REUSEADDR | SO_REUSEPORT, &opt,
sizeof(opt))) {
        perror("\nSocket option set failed!");
        return;
    }

    server_addr.sin_family = AF_INET;
    server_addr.sin_addr.s_addr = INADDR_ANY;
    server_addr.sin_port = htons(8888);
    struct sockaddr_in client_addr;
    if (bind(server_fd, (struct sockaddr *)&server_addr, sizeof(server_addr)) < 0) {
        perror("\nServer Bind failed!");
        return;
    }

    listen(server_fd, MAX);
    int addlen = sizeof(struct sockaddr_in);
    while(1) {
        if ((connected_fd = accept(server_fd, (struct sockaddr *)&client_addr, &addlen)) < 0) {
            perror("\nClient connection failed!");
            return;
        }
    }
}
```

```

        pthread_create(&tid[i], NULL, handle_client, (void *)&connected_fd);
        i = (i+1)%MAX;
    }
    close(server_fd);
}
Client:
#include<stdio.h>
#include<stdlib.h>
#include<string.h>
#include<arpa/inet.h>
void main() {
    int socket_fd = 0;
    struct sockaddr_in server = {0};
    char buf[100];

    if ((socket_fd = socket(AF_INET, SOCK_STREAM, 0)) == 0) {
        perror("\nClient socket creation failed!");
        return;
    }

    server.sin_addr.s_addr = inet_addr("127.0.0.1");
    server.sin_port = htons(8888);
    server.sin_family = AF_INET;

    if (connect(socket_fd, (struct sockaddr*)&server, sizeof(server)) < 0) {
        perror("\nClient to Server connect failed!");
        return;
    }
    send(socket_fd, "Hi from Client", strlen("Hi from Client"),0);
    recv(socket_fd, &buf, sizeof(buf),0);
    printf("\nReceived from Server: %s",buf);
    close(socket_fd);
}

```

1.206 Shared Memory

```

#include<stdio.h>
#include<stdlib.h>
#include<unistd.h>
#include<sys/shm.h>
#include<string.h>
int main()
{
    int i;
    void *shared_memory;
    char buff[100];
    int shmid;
    shmid=shmget((key_t)2345, 1024, 0666);
    shared_memory=shmat(shmid,NULL,0); //process attached to shared memory segment
    printf("Data read from shared memory is : %s\n",(char *)shared_memory);
}

#include<stdio.h>
#include<stdlib.h>
#include<unistd.h>
#include<sys/shm.h>
#include<string.h>

```

```

int main()
{
int i;
void *shared_memory;
char buff[100];
int shmid;
shmid=shmget((key_t)2345, 1024, 0666|IPC_CREAT);
//creates shared memory segment with key 2345, having size 1024 bytes. IPC_CREAT is used
to create the shared segment if it does not exist. 0666 are the permissions on the
shared segment
shared_memory=shmat(shmid,NULL,0);
//process attached to shared memory segment
//this prints the address where the segment is attached with this process
printf("Enter some data to write to shared memory\n");
fgets(buff,100,stdin); //get some input from user
strcpy(shared_memory,buff); //data written to shared memory
}

```

1.207 Message Queues

```

#include<stdio.h>
#include<sys/ipc.h>
#include<sys/msg.h>
typedef struct msg_buf {
    long type;
    char msg[100];
}msg_t;
void main() {
    msg_t ms;
    key_t key = ftok("Allah",123);
    int msg_id = msgget(key, 0666|IPC_CREAT);
    msgsnd(msg_id,&ms, sizeof(ms),1,0);
    printf("%s",ms.msg);
}
#include<stdio.h>
#include<sys/ipc.h>
#include<sys/msg.h>
typedef struct msg_buffer {
    long type;
    char buffer[100];
}msg_t;
void main() {
    msg_t ms;
    key_t key = ftok("Allah",123);
    int msg_id = 0;
    msg_id = msgget(key,0666|IPC_CREAT);
    ms.type = 1;
    strncpy(ms.buffer,"HELLO DUDE!", sizeof("HELLO DUDE!"));
    msgsnd(msg_id, &ms, sizeof(ms), 0);
}

```

1.208 Dequeue

```

#include <stdio.h>
#include <stdlib.h>

// Node structure of a doubly-linked list
struct Node

```

```

{
    int data;
    struct Node* prev;
    struct Node* next;
};

// A structure for Deque
struct Deque
{
    struct Node* head;
    struct Node* tail;
    int size;
};

// Function prototypes
void initDeque(struct Deque* dq);
int isEmpty(struct Deque* dq);
int size(struct Deque* dq);
void insertFront(struct Deque* dq, int data);
void insertRear(struct Deque* dq, int data);
void deleteFront(struct Deque* dq);
void deleteRear(struct Deque* dq);
int getFront(struct Deque* dq);
int getRear(struct Deque* dq);

// Function to initialize the deque
void initDeque(struct Deque* dq)
{
    dq->head = dq->tail = NULL;
    dq->size = 0;
}

// Function to check if the deque is empty
int isEmpty(struct Deque* dq)
{
    return (dq->head == NULL);
}

// Function to get the size of the deque
int size(struct Deque* dq)
{
    return dq->size;
}

// Function to insert an element at the front of the deque
void insertFront(struct Deque* dq, int data)
{
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    if (newNode == NULL)
    {
        printf("Memory allocation failed (Overflow)\n");
        return;
    }

    newNode->data = data;
    newNode->prev = NULL;
    newNode->next = dq->head;
}

```

```

if (dq->head == NULL)
{
    dq->tail = newNode;
}
else
{
    dq->head->prev = newNode;
}

dq->head = newNode;
dq->size++;
}

// Function to insert an element at the rear of the deque
void insertRear(struct Deque* dq, int data)
{
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    if (newNode == NULL)
    {
        printf("Memory allocation failed (Overflow)\n");
        return;
    }

    newNode->data = data;
    newNode->prev = dq->tail;
    newNode->next = NULL;

    if (dq->tail == NULL)
    {
        dq->head = newNode;
    }
    else
    {
        dq->tail->next = newNode;
    }

    dq->tail = newNode;
    dq->size++;
}

// Function to delete an element from the front of the deque
void deleteFront(struct Deque* dq)
{
    if (isEmpty(dq))
    {
        printf("Underflow\n");
        return;
    }

    struct Node* temp = dq->head;
    dq->head = dq->head->next;

    if (dq->head == NULL)
    {
        dq->tail = NULL;
    }
}

```

```

    else
    {
        dq->head->prev = NULL;
    }

    free(temp);
    dq->size--;
}

// Function to delete an element from the rear of the deque
void deleteRear(struct Deque* dq)
{
    if (isEmpty(dq))
    {
        printf("Underflow\n");
        return;
    }

    struct Node* temp = dq->tail;
    dq->tail = dq->tail->prev;

    if (dq->tail == NULL)
    {
        dq->head = NULL;
    }
    else
    {
        dq->tail->next = NULL;
    }

    free(temp);
    dq->size--;
}

// Function to get the front element of the deque
int getFront(struct Deque* dq)
{
    if (isEmpty(dq))
    {
        return -1;
    }

    return dq->head->data;
}

// Function to get the rear element of the deque
int getRear(struct Deque* dq)
{
    if (isEmpty(dq))
    {
        return -1;
    }

    return dq->tail->data;
}

int main()

```

```

{
    struct Deque dq;
    initDeque(&dq);

    printf("Insert element '2' at rear end\n");
    insertRear(&dq, 2);
    printf("Insert element '0' at rear end\n");
    insertRear(&dq, 0);

    printf("Rear end element: %d\n", getRear(&dq));

    deleteRear(&dq);

    printf("After deleting rear element new rear is: %d\n", getRear(&dq));

    printf("Inserting element '27' at front end\n");
    insertFront(&dq, 27);

    printf("Front end element: %d\n", getFront(&dq));

    printf("Number of elements in Deque: %d\n", size(&dq));

    deleteFront(&dq);

    printf("After deleting front element new front is: %d\n", getFront(&dq));

    return 0;
}

```

1.209 Regex Search Target String

```

#define MAX_BUFFER_SIZE 1024

// Function to search for a target string using regex
int searchTargetString(const char *output, const char *target) {
    regex_t regex;
    int reti;
    char buffer[MAX_BUFFER_SIZE];

    // Compile the regular expression
    reti = regcomp(&regex, target, REG_EXTENDED);
    if (reti) {
        fprintf(stderr, "Could not compile regex\n");
        return -1;
    }

    // Execute the regular expression
    reti = regexec(&regex, output, 0, NULL, 0);
    if (!reti) {
        printf("Target string found in the output\n");
        return 1;
    } else if (reti == REG_NOMATCH) {
        printf("Target string not found in the output\n");
        return 0;
    } else {
        regerror(reti, &regex, buffer, sizeof(buffer));
    }
}

```

```

        fprintf(stderr, "Regex match failed: %s\n", buffer);
        return -1;
    }

    // Free the compiled regular expression
    regfree(&regex);

    return 0;
}

int main() {
    FILE *fp;
    char buffer[MAX_BUFFER_SIZE];

    // Command to execute (replace with your network command)
    const char *command = "ping -c 4 google.com";

    // Open a pipe to execute the command and read its output
    fp = popen(command, "r");
    if (fp == NULL) {
        fprintf(stderr, "Failed to execute command\n");
        return 1;
    }

    // Read the command output
    while (fgets(buffer, sizeof(buffer), fp) != NULL) {
        // Search for the target string in the output
        if (searchTargetString(buffer, "time=") > 0) {
            // Do something when the target string is found
            printf("Found target string in the line: %s", buffer);
        }
    }

    // Close the pipe
    pclose(fp);

    return 0;
}

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Function to execute a command and capture its output
char* executeCommand(const char* command) {
    FILE* fp;
    char buffer[128];
    char* result = malloc(4096); // Allocate a buffer for the command output

    result[0] = '\0'; // Initialize the result string

    // Open the command for reading
    fp = popen(command, "r");
    if (fp == NULL) {
        printf("Failed to run command\n");
        exit(1);
    }
}

```

```

// Read the output line by line and concatenate it to the result string
while (fgets(buffer, sizeof(buffer) - 1, fp) != NULL) {
    strcat(result, buffer);
}

// Close the pipe and return the result
pclose(fp);
return result;
}

// Function to extract the time value from the ping output
int extractPingTime(const char* pingOutput) {
    const char* timeString = strstr(pingOutput, "time=");
    if (timeString != NULL) {
        // Extract the time value as an integer
        int timeValue;
        sscanf(timeString, "time=%d", &timeValue);
        return timeValue;
    }
    return -1; // Return -1 if the time value is not found
}
int main() {
    const char* command = "ping -c 4 google.com"; // Your ping command
    char* pingOutput = executeCommand(command);

    int pingTime = extractPingTime(pingOutput);
    if (pingTime != -1) {
        printf("Ping time: %d ms\n", pingTime);
    } else {
        printf("Unable to extract ping time\n");
    }

    // Free the allocated memory
    free(pingOutput);

    return 0;
}

```

1.210 Quick Sort

```

void asc(int *arr, int start, int size) {
    int pivot = start;
    int i = start+1;
    int j = size;
    int temp = 0;
    if (start >= size) return;
    while (i <= j) {
        while ((j >= start) && arr[j] >= arr[pivot]) j--;
        while ((i <= size) && arr[i] <= arr[pivot]) i++;
        if (i < j) {
            temp = arr[i];
            arr[i] = arr[j];
            arr[j] = temp;
        } else {
            temp = arr[pivot];
            arr[pivot] = arr[j];
            arr[j] = temp;
        }
    }
}

```

```

        arr[j] = temp;
    }
}
asc(arr,0, j-1);
asc(arr,j+1, size);
}
void quick_sort(int *arr, int size, void (*fn)(int*, int, int)) {
    fn(arr, 0, size-1);
    printf("\nSorted array is:");
    for (int i = 0; i < size; i++) {
        printf("%d ",arr[i]);
    }
}

```

1.211 Merge Sort

```

void merge_asc(int *arr, int start, int middle, int end) {
    int n1 = middle-start+1;
    int n2 = end-middle;
    int left[n1];
    int right[n2];
    int i = 0;
    int j = 0;
    int k = 0;

    for (i = 0; i < n1; i++) {
        left[i] = arr[start+i];
    }
    for (i = 0; i < n2; i++) {
        right[i] = arr[middle + i + 1];
    }

    i = 0;
    k = start;
    while (i < n1 && j < n2) {
        if (left[i] <= right[j]) {
            arr[k] = left[i];
            i++;
        } else {
            arr[k] = right[j];
            j++;
        }
        k++;
    }
    while (i < n1) {
        arr[k] = left[i];
        i++;
        k++;
    }
    while (j < n2) {
        arr[k] = right[j];
        j++;
        k++;
    }
}

void asc(int *arr, int start, int end) {
    if (start < end) {

```

```

        int middle = (start + end)/2;
        asc(arr, start, middle);
        asc(arr, middle+1, end);
        merge_asc(arr,start,middle,end);
    }
}

```

1.212 Bloom Filter

```

#include <stdio.h>
#include <stdbool.h>
#include <math.h>

#define ll long long

// hash 1
int h1(int num, int arrSize)
{
    ll int hash = num % arrSize;
    return hash;
}

// hash 2
int h2(int num, int arrSize)
{
    ll int hash = 1;
    while (num > 0)
    {
        hash = (hash + num % 10);
        num /= 10;
    }
    hash = hash % arrSize;
    return hash;
}

// hash 3
int h3(int num, int arrSize)
{
    ll int hash = 7;
    while (num > 0)
    {
        hash = (hash * 31 + num % 10) % arrSize;
        num /= 10;
    }
    return hash;
}

// hash 4
int h4(int num, int arrSize)
{
    ll int hash = 3;
    int p = 7;
    while (num > 0)
    {
        hash += hash * 7 + (num % 10) * pow(p, num % 10);
        hash = hash % arrSize;
    }
}

```

```

        num /= 10;
    }    return hash;
}

// lookup operation
bool lookup(int *bitarray, int arrSize, int num)
{
    int a = h1(num, arrSize);
    int b = h2(num, arrSize);
    int c = h3(num, arrSize);
    int d = h4(num, arrSize);

    if (bitarray[a] && bitarray[b] && bitarray[c] && bitarray[d])
        return true;
    else
        return false;
}

// insert operation
void insert(int *bitarray, int arrSize, int num)
{
    // check if the element is already present or not
    if (lookup(bitarray, arrSize, num))
        printf("%d is Probably already present\n", num);
    else
    {
        int a = h1(num, arrSize);
        int b = h2(num, arrSize);
        int c = h3(num, arrSize);
        int d = h4(num, arrSize);

        bitarray[a] = 1;
        bitarray[b] = 1;
        bitarray[c] = 1;
        bitarray[d] = 1;

        printf("%d inserted\n", num);
    }
}
// Driver Code
int main()
{
    int bitarray[100] = {0};
    int arrSize = 100;
    int numArray[33] = {123, 456, 789, 321, 654, 987, 111, 222, 333,
                       444, 555, 666, 777, 888, 999, 101, 202, 303,
                       404, 505, 606, 707, 808, 909, 1111, 2222, 3333,
                       4444, 5555, 6666, 7777, 8888, 9999};

    for (int i = 0; i < 33; i++)
    {
        insert(bitarray, arrSize, numArray[i]);
    }

    return 0;
}

```

1.213 Hash Table

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Define the size of the hash table
#define TABLE_SIZE 10

// Define a structure for a node in the linked list
struct Node {
    int key;
    char data[50];
    struct Node* next;
};

// Define the hash table as an array of linked lists
struct Node* hashTable[TABLE_SIZE] = {NULL};

// Hash function
int hash(int key) {
    return key % TABLE_SIZE;
}

// Insert a key-value pair into the hash table
void insert(int key, const char* data) {
    // Create a new node
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    if (newNode == NULL) {
        fprintf(stderr, "Memory allocation failed.\n");
        exit(1);
    }

    // Set the key and data for the new node
    newNode->key = key;
    strncpy(newNode->data, data, sizeof(newNode->data));
    newNode->next = NULL;

    // Get the hash index
    int index = hash(key);

    // Insert the new node at the beginning of the linked list
    newNode->next = hashTable[index];
    hashTable[index] = newNode;
}

// Search for a key in the hash table
const char* search(int key) {
    // Get the hash index
    int index = hash(key);

    // Traverse the linked list at the hash index
    struct Node* current = hashTable[index];
    while (current != NULL) {
        if (current->key == key) {
            return current->data; // Key found
        }
        current = current->next;
    }
}
```

```

    }

    return NULL; // Key not found
}

// Print the contents of the hash table
void printHashTable() {
    for (int i = 0; i < TABLE_SIZE; i++) {
        printf("Bucket %d: ", i);
        struct Node* current = hashTable[i];
        while (current != NULL) {
            printf("(%d, %s) ", current->key, current->data);
            current = current->next;
        }
        printf("\n");
    }
}

// Main function for testing the hash table
int main() {
    // Insert key-value pairs
    insert(1, "John");
    insert(2, "Alice");
    insert(11, "Bob");
    insert(12, "Charlie");
    insert(21, "David");
    // Print the initial hash table
    printf("Initial Hash Table:\n");
    printHashTable();

    // Search for keys
    printf("\nSearch results:\n");
    printf("Key 2: %s\n", search(2));
    printf("Key 12: %s\n", search(12));
    printf("Key 5: %s\n", search(5));

    return 0;
}

```

1.214 Endianess

```

#include<stdio.h>

#if 0
void print_bytes(void *ptr, int size)
{
    unsigned char *p = ptr;
    int i;
    for (i=0; i<size; i++) {
        printf("%02hhX ", p[i]);
    }
    printf("\n");
}
#endif

```

```

//12345678 -> 0th byte 12 --> big endian, 0th byte 78 --> little endian(lowest address -
least significant byte)
void main() {
    int data = 12345678;
    char *d = (char*)&data;
    printf("\n %p",&d);
    if (*d == 78)
        printf("\nLittle Endian");
    else
        printf("\nBig Endian");
    d = (char*)&data+3;
    printf("\n%#x",*d);
    //print_bytes(&data,sizeof(int));
}
#endif
#include <stdio.h>

/* function to show bytes in memory, from location start to start+n*/
void show_mem_rep(char *start, int n)
{
    int i;
    printf("\nn = %d",n);
    for (i = 0; i < n; i++)
        printf("%d %.2x", i,start[i]);
    printf("\n");
}

/*Main function to call above function for 0x01234567*/
int main()
{
    int i = 0x01234567;
    show_mem_rep((char *)&i, sizeof(i));
    return 0;
}
#endif

#include<stdio.h>
//12345678 -> 0th byte 12 --> little endian, 0th byte 78 --> big endian
void main() {
    int data = 12345678;
    char *d = (char*)&data;
    printf("\n %u",*d);
    if (*d == 78)
        printf("\nLittle Endian");
    else
        printf("\nBig Endian");
}

```

1.215 MALLOC Implementation

```
#include <stdio.h>
#include <stdlib.h>

#define BUFFER_SIZE 1000 // Adjust the size as needed

// Global buffer to simulate memory allocation
char buffer[BUFFER_SIZE];
int next_free_offset = 0;

void* my_malloc(size_t size) {
    if (next_free_offset + size <= BUFFER_SIZE) {
        void* allocated_memory = buffer + next_free_offset;
        next_free_offset += size;
        return allocated_memory;
    } else {
        fprintf(stderr, "Error: Insufficient memory in the fixed buffer.\n");
        return NULL;
    }
}

void my_free(void* ptr) {
    // In a simple fixed buffer scenario, freeing memory can be a no-op
    // or could be used to reset the allocation pointer.
    // For demonstration purposes, we'll reset the allocation pointer here.
    next_free_offset = (int)((char*)ptr - buffer);
}

int main() {
    // Example usage
    int* int_ptr = (int*)my_malloc(sizeof(int));

    if (int_ptr != NULL) {
        *int_ptr = 42;
        printf("Allocated integer value: %d\n", *int_ptr);

        // Freeing the allocated memory
        my_free(int_ptr);
    }

    return 0;
}

#include <stdio.h>
#include <stdlib.h>
#include <stdint.h>
#include <pthread.h>

#define MEMORY_POOL_SIZE 1000

// Block structure to represent allocated memory blocks
typedef struct Block {
    size_t size;
    struct Block* next;
} Block;
```

```

// Memory pool
static char memory_pool[MEMORY_POOL_SIZE];

// Mutex for thread safety
static pthread_mutex_t memory_mutex = PTHREAD_MUTEX_INITIALIZER;

// Pointer to the first block in the memory pool
static Block* memory_head = NULL;

// Function to initialize the memory manager
void initialize_memory_manager() {
    memory_head = (Block*)memory_pool;
    memory_head->size = MEMORY_POOL_SIZE - sizeof(Block);
    memory_head->next = NULL;
}

// Function to allocate memory
void* my_malloc(size_t size) {
    pthread_mutex_lock(&memory_mutex);

    if (memory_head == NULL) {
        initialize_memory_manager();
    }

    size_t total_size = size + sizeof(Block);
    Block* current_block = memory_head;
    Block* previous_block = NULL;

    while (current_block != NULL) {
        if (current_block->size >= total_size) {
            // Allocate from this block
            if (current_block->size > total_size + sizeof(Block)) {
                // Split the block
                Block* new_block = (Block*)((char*)current_block + total_size);
                new_block->size = current_block->size - total_size;
                new_block->next = current_block->next;
                current_block->size = size;
                current_block->next = new_block;
            } else {
                // Use the entire block
                total_size = current_block->size;
            }
        }

        // Update the linked list
        if (previous_block == NULL) {
            memory_head = current_block->next;
        } else {
            previous_block->next = current_block->next;
        }
    }

    pthread_mutex_unlock(&memory_mutex);
    return (char*)current_block + sizeof(Block);
}

previous_block = current_block;
current_block = current_block->next;
}

```

```

pthread_mutex_unlock(&memory_mutex);
fprintf(stderr, "Error: Insufficient memory.\n");
return NULL;
}

// Function to free memory
void my_free(void* ptr) {
    pthread_mutex_lock(&memory_mutex);

    if (ptr != NULL) {
        Block* block = (Block*)((char*)ptr - sizeof(Block));
        block->next = memory_head;
        memory_head = block;
    }

    pthread_mutex_unlock(&memory_mutex);
}

// Function to print memory blocks for debugging
void print_memory_blocks() {
    Block* current_block = memory_head;
    while (current_block != NULL) {
        printf("Block: %p, Size: %zu\n", (void*)current_block, current_block->size);
        current_block = current_block->next;
    }
}
int main() {
    // Example usage
    initialize_memory_manager();

    int* int_ptr = (int*)my_malloc(sizeof(int));
    if (int_ptr != NULL) {
        *int_ptr = 42;
        printf("Allocated integer value: %d\n", *int_ptr);

        print_memory_blocks();

        // Freeing the allocated memory
        my_free(int_ptr);

        print_memory_blocks();
    }

    return 0;
}

```

1.216 Single Linked List

```

#include<stdio.h>
#include<stdlib.h>
struct node {
    int data;
    struct node *next;
};
struct node *head;
struct node* allocate() {

```

```

struct node *new_node = (struct node *)malloc(sizeof(struct node));
if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
}
return new_node;
}
void main() {
    printf("\nSingle Linked List!");
    int choice = 0;
    int position = 0;
    int count = 0;
    int value = 0;
    struct node *new_node = NULL;
    while (1) {
        printf("\n1.Create\n2.Insert at beginning\n3.Insert at end\n4.Insert at
position\n5.Delete from first\n6.Delete at end\n7.Delete at
position\n8.Search\n9.Print\n10.End");
        printf("\nSelect a choice:");
        scanf("%d",&choice);
        switch (choice) {
            case 1:
                printf("\nCreate!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    new_node->next = NULL;
                    head = new_node;
                }
                break;
            case 2:
                printf("\nInsert at beginning!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    new_node->next = head;
                    head = new_node;
                }
                break;
            case 3:
                printf("\nInsert at end!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    struct node* cur = head;

```

```

        while (cur->next != NULL) {
            cur = cur->next;
        }
        cur->next = new_node;
        new_node->next = NULL;
    }
break;
case 4:
printf("\nInsert at position!");
printf("\nTell me a position!");
scanf("%d",&position);
new_node = allocate();
if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
} else {
    printf("\nEnter the value for node!");
    scanf("%d",&new_node->data);
    struct node* curr = head;
    while (curr != NULL) {
        count++;
        if (position-1 > count) {
            curr = curr->next;
        } else {
            break;
        }
    }
    new_node->next = curr->next;
    curr->next = new_node;
}
break;
case 5:
printf("\nDelete from first!");
if (head == NULL) {
    printf("\nList empty!");
}
struct node *ele = head;
struct node *next = head->next;
free(ele);
ele = NULL;
head = next;
break;
case 6:
printf("\nDelete at end!");
struct node* h = head;
struct node* p = head;
if (h == NULL) {
    printf("\nList is empty!");
}
if (h->next == NULL) {
    free(h);
    h = NULL;
    head = NULL;
}
else {
    while (h->next != NULL) {
        p = h;

```

```

        h = h->next;
    }
    p->next = NULL;
    free(h);
}
break;
case 7:
count = 0;
printf("\nDelete at position!");
printf("\nEnter position to delete from");
scanf("%d",&position);
struct node* cr = head;
struct node* pr = head;
while (cr != NULL) {
    count++;
    pr = cr;
    if (count == position-1) {
        pr->next = pr->next->next;
        free(cr->next);
        cr->next = NULL;
        break;
    }
    cr = cr->next;
}
break;
case 8:
printf("\nSearch!");
printf("\nEnter the value to search!");
scanf("%d",&value);
count = 0;
struct node* c = head;
while (c != NULL) {
    count++;
    if (c->data == value) {
        printf("\nValue %d present in %d position",value,count);
        break;
    }
    if (c->next == NULL) {
        printf("\nValue %d not found!",value);
    }
    c = c->next;
}
break;
case 9:
printf("\nList!");
struct node* current = head;
printf("\n");
while (current != NULL) {
    printf("%d->",current->data);
    current = current->next;
}
printf("NULL");
break;
case 10:
printf("\nThank you!");
exit(1);
break;

```

```

        default:
        printf("\nTry again!");
        break;
    }
    choice = 0;
}
}

```

1.217 Double Linked List

```

#include<stdio.h>
#include<stdlib.h>
struct node {
    int data;
    struct node *prev;
    struct node *next;
};
struct node *head;
struct node* allocate() {
    struct node *new_node = (struct node *)malloc(sizeof(struct node));
    if (new_node == NULL) {
        printf("\nMalloc failure!");
        exit(1);
    }
    return new_node;
}
void main() {
    printf("\nSingle Linked List!");
    int choice = 0;
    int position = 0;
    int count = 0;
    int value = 0;
    struct node *new_node = NULL;
    while (1) {
        printf("\n1.Create\n2.Insert at beginning\n3.Insert at end\n4.Insert at
position\n5.Delete from first\n6.Delete at end\n7.Delete at
position\n8.Search\n9.Print\n10.Reverse Print\n11.End");
        printf("\nSelect a choice:");
        scanf("%d",&choice);
        switch (choice) {
            case 1:
                printf("\nCreate!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    new_node->prev = NULL;
                    new_node->next = NULL;
                    head = new_node;
                }
                break;
            case 2:
                printf("\nInsert at beginning!");
                new_node = allocate();

```

```

if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
} else {
    printf("\nEnter the value for node!");
    scanf("%d",&new_node->data);
    new_node->prev = NULL;
    new_node->next = head;
    head->prev = new_node;
    head = new_node;
}
break;
case 3:
printf("\nInsert at end!");
new_node = allocate();
if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
} else {
    printf("\nEnter the value for node!");
    scanf("%d",&new_node->data);
    struct node* cur = head;
    while (cur->next != NULL) {
        cur = cur->next;
    }
    cur->next = new_node;
    new_node->prev = cur;
    new_node->next = NULL;
}
break;
case 4:
printf("\nInsert at position!");
printf("\nTell me a position!");
scanf("%d",&position);
new_node = allocate();
if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
} else {
    printf("\nEnter the value for node!");
    scanf("%d",&new_node->data);
    struct node* curr = head;
    while (curr != NULL) {
        count++;
        if (position-1 > count) {
            curr = curr->next;
        } else {
            break;
        }
    }
    new_node->next = curr->next;
    curr->next->prev = new_node;
    new_node->prev = curr;
    curr->next = new_node;
}
break;
case 5:

```

```

printf("\nDelete from first!");
if (head == NULL) {
    printf("\nList empty!");
}
struct node *ele = head;
struct node *next = head->next;
free(ele);
ele = NULL;
next->prev = NULL;
head = next;
break;
case 6:
printf("\nDelete at end!");
struct node* h = head;
struct node* p = head;
if (h == NULL) {
    printf("\nList is empty!");
}
if (h->next == NULL) {
    free(h);
    h = NULL;
    head = NULL;
}
else {
    while (h->next != NULL) {
        p = h;
        h = h->next;
    }
    p->next = NULL;
    free(h);
}
break;
case 7:
count = 0;
printf("\nEnter position to delete from");
scanf("%d",&position);
struct node* cr = head;
struct node* nx = NULL;
while (cr != NULL) {
    count++;
    //1 2 3 4 5
    if (count == position-1) {
        nx = cr->next;
        cr->next->prev = cr;
        cr->next = cr->next->next;
        free(nx);
        nx->next = NULL;
        break;
    }
    cr = cr->next;
}
break;
case 8:
printf("\nSearch!");
printf("\nEnter the value to search!");
scanf("%d",&value);

```

```

        count = 0;
        struct node* c = head;
        while (c != NULL) {
            count++;
            if (c->data == value) {
                printf("\nValue %d present in %d position",value,count);
                break;
            }
            if (c->next == NULL) {
                printf("\nValue %d not found!",value);
            }
            c = c->next;
        }
        break;
    case 9:
        printf("\nList!");
        struct node* current = head;
        printf("\n");
        while (current != NULL) {
            printf("%d->",current->data);
            current = current->next;
        }
        printf("NULL");
        break;
    case 10:
        printf("\nList reverse print!");
        struct node* currnt = head;
        printf("\n");
        while (currnt->next != NULL) {
            currnt = currnt->next;
        }
        struct node* end = currnt;
        while (end != NULL) {
            printf("%d->",end->data);
            end = end->prev;
        }
        printf("NULL");
        break;
    case 11:
        printf("\nThank you!");
        exit(1);
        break;
    default:
        printf("\nTry again!");
        break;
    }
    choice = 0;
}
}

```

1.218 Stack

```

#include<stdio.h>
#include<stdlib.h>
struct node {
    int data;
    struct node *next;
};

```

```

struct node *head;
struct node* allocate() {
    struct node *new_node = (struct node *)malloc(sizeof(struct node));
    if (new_node == NULL) {
        printf("\nMalloc failure!");
        exit(1);
    }
    return new_node;
}
void main() {
    printf("\nStack!");
    int choice = 0;
    int position = 0;
    int count = 0;
    int value = 0;
    struct node *new_node = NULL;
    while (1) {
        printf("\n1.Create\n2.Push\n3.Pop\n4.Print\n5.End");
        printf("\nSelect a choice:");
        scanf("%d",&choice);
        switch (choice) {
            case 1:
                printf("\nCreate!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    new_node->next = NULL;
                    head = new_node;
                }
                break;
            case 2:
                printf("\nPush!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");
                    exit(1);
                } else {
                    printf("\nEnter the value for node!");
                    scanf("%d",&new_node->data);
                    new_node->next = head;
                    head = new_node;
                }
                break;
            case 3:
                printf("\nPop!");
                if (head == NULL) {
                    printf("\nList empty!");
                }
                struct node *ele = head;
                struct node *next = head->next;
                free(ele);
                ele = NULL;
                head = next;
        }
    }
}

```

```

        break;
    case 4:
        printf("\nStack Contents!");
        struct node* current = head;
        printf("\n");
        while (current != NULL) {
            printf("%d->",current->data);
            current = current->next;
        }
        printf("NULL");
        break;
    case 5:
        printf("\nThank you!");
        exit(1);
        break;
    default:
        printf("\nTry again!");
        break;
    }
    choice = 0;
}
}

```

1.219 Queue

```

#include<stdio.h>
#include<stdlib.h>
struct node {
    int data;
    struct node *next;
};
struct node *head;
struct node* allocate() {
    struct node *new_node = (struct node *)malloc(sizeof(struct node));
    if (new_node == NULL) {
        printf("\nMalloc failure!");
        exit(1);
    }
    return new_node;
}
void main() {
    printf("\nQueue!");
    int choice = 0;
    int position = 0;
    int count = 0;
    int value = 0;
    struct node *new_node = NULL;
    while (1) {
        printf("\n1.Create\n2.Enqueue\n3.Dequeue\n4.Print\n5.End");
        printf("\nSelect a choice:");
        scanf("%d",&choice);
        switch (choice) {
            case 1:
                printf("\nCreate!");
                new_node = allocate();
                if (new_node == NULL) {
                    printf("\nMalloc failure!");

```

```

        exit(1);
    } else {
        printf("\nEnter the value for node!");
        scanf("%d",&new_node->data);
        new_node->next = NULL;
        head = new_node;
    }
break;
case 2:
printf("\nEnqueue!");
new_node = allocate();
if (new_node == NULL) {
    printf("\nMalloc failure!");
    exit(1);
} else {
    printf("\nEnter the value for node!");
    scanf("%d",&new_node->data);
    struct node* cur = head;
    while (cur->next != NULL) {
        cur = cur->next;
    }
    cur->next = new_node;
    new_node->next = NULL;
}
break;
case 3:
printf("\nDequeue!");
if (head == NULL) {
    printf("\nList empty!");
}
struct node *ele = head;
struct node *next = head->next;
free(ele);
ele = NULL;
head = next;
break;
case 4:
printf("\nList!");
struct node* current = head;
printf("\n");
while (current != NULL) {
    printf("%d->",current->data);
    current = current->next;
}
printf("NULL");
break;
case 5:
printf("\nThank you!");
exit(1);
break;
default:
printf("\nTry again!");
break;
}
choice = 0;
}
}

```

1.220 Binary Search Tree

```
#include<stdio.h>
#include<stdlib.h>
struct node {
    int data;
    struct node *left;
    struct node *right;
};
struct node *root;
struct node* allocate() {
    struct node *new_node = (struct node *)malloc(sizeof(struct node));
    if (new_node == NULL) {
        printf("\nMalloc failure!");
        exit(1);
    }
    return new_node;
}
struct node* insert(struct node *temp, struct node *root) {
    if (root == NULL) {
        root = temp;
    } else {
        if (temp->data < root->data) {
            root->left = insert(temp,root->left);
        } else if (temp->data > root->data){
            root->right = insert(temp,root->right);
        }
    }
    return root;
}
void print_inorder(struct node *t) {
    if (t == NULL) return;
    if (t != NULL) {
        print_inorder(t->left);
        printf("%d:",t->data);
        print_inorder(t->right);
    }
}
void print_preorder(struct node *t) {
    if (t == NULL) return;
    if (t != NULL) {
        printf("%d:",t->data);
        print_preorder(t->left);
        print_preorder(t->right);
    }
}
void print_postorder(struct node *t) {
    if (t == NULL) return;
    if (t != NULL) {
        print_postorder(t->left);
        print_postorder(t->right);
        printf("%d:",t->data);
    }
}
void search(struct node *root, int value) {
    if (root == NULL) {
        printf("\nValue not found!");
    }
```

```

        return;
    }
    else {
        if (root->data == value) {
            printf("\nValue found!");
            return;
        } else {
            if (value < root->data)
                search(root->left,value);
            else
                search(root->right,value);
        }
    }
}

struct node *delete(struct node*root, int value) {
    if (root == NULL) {
        printf("\nValue not found to be deleted!");
        return NULL;
    }
    if (value < root->data) {
        root->left = delete(root->left, value);
    } else if (value > root->data) {
        root->right = delete(root->right, value);
    } else {
        if (root->left == NULL && root->right == NULL) {
            free(root);
            return NULL;
        } else if (root->left != NULL && root->right == NULL) {
            struct node *y = root->left;
            free(root);
            return y;
        } else if (root->right != NULL && root->left == NULL) {
            struct node *z = root->right;
            free(root);
            return z;
        } else {
            struct node *succ_parent = root;
            struct node *succ = root->right;
            while (succ->left != NULL) {
                succ_parent = succ;
                succ = succ->left;
            }
            if (succ_parent == root) {
                root->right = succ->right;
            } else {
                root->left = succ->right;
            }
            root->data = succ->data;
            free(succ);
        }
    }
    return root;
}
void main() {
    printf("\nBinary Search Tree!");
    int choice = 0;
    int position = 0;
}

```

```

int count = 0;
int value = 0;
struct node *new_node = NULL;
struct node *nn = NULL;
while (1) {
    printf("\n1.Create\n2.Insert\n3.Delete\n4.Search\n5.Print Inorder\n6.Print
PreOrder\n7.Print PostOrder\n6..End");
    printf("\nSelect a choice:");
    scanf("%d",&choice);
    switch (choice) {
        case 1:
            printf("\nCreate!");
            new_node = allocate();
            if (new_node == NULL) {
                printf("\nMalloc failure!");
                exit(1);
            } else {
                printf("\nEnter the value for node!");
                scanf("%d",&new_node->data);
                new_node->left = NULL;
                new_node->right = NULL;
                root = new_node;
            }
            break;
        case 2:
            printf("\nInsert!");
            nn = allocate();
            if (new_node == NULL) {
                printf("\nMalloc failure!");
                exit(1);
            } else {
                printf("\nEnter the value for node!");
                scanf("%d",&nn->data);
                insert(nn,root);
            }
            break;
        case 3:
            printf("\nDelete!");
            printf("\nEnter value to delete!");
            scanf("%d",&value);
            delete(root,value);
            break;
        case 4:
            printf("\nSearch!");
            printf("\nEnter the value to search!");
            scanf("%d",&value);
            search(root,value);
            break;
        case 5:
            printf("\nBST Inorder!");
            printf("\n");
            print_inorder(root);
            break;
        case 6:
            printf("\nBST Preorder!");
            printf("\n");
            print_preorder(root);
    }
}

```

```

        break;
    case 7:
        printf("\nBST Postorder!");
        printf("\n");
        print_postorder(root);
        break;
    case 8:
        printf("\nThank you!");
        exit(1);
        break;
    default:
        printf("\nTry again!");
        break;
    }
    choice = 0;
}
}
}

```

1.221 Trie Complete Code

```

#include<stdio.h>
#include<stdlib.h>
#include<stdbool.h>
#include<string.h>
#define N 26
struct node {
    char data;
    struct node *children[N];
    int is_leaf;
};
struct node *root;
struct node* allocate(char data) {
    struct node *new_node = (struct node *)malloc(sizeof(struct node));
    if (new_node == NULL) {
        printf("\nMalloc failure!");
        exit(1);
    }
    for (int i = 0; i < N; i++) {
        new_node->children[i] = NULL;
    }
    new_node->data = data;
    new_node->is_leaf = 0;
    return new_node;
}
struct node* insert(struct node *root, char *input) {
    struct node *temp = root;
    int position = 0;
    printf("\nWord input is :%s",input);
    for (int i = 0; input[i] != '\0'; i++) {
        position = (int)input[i] - 'a';
        printf("\nPosition is :%d",position);
        if (temp->children[position] == NULL) {
            temp->children[position] = allocate(input[i]);
            printf("\nCharacter : %c",temp->data);
        } else {
            //Do nothing as character is already present
        }
    }
}

```

```

        }
        temp = temp->children[position];
    }
    temp->is_leaf = 1;
    return root;
}
void print(struct node* root) {
    // Prints the nodes of the trie
    if (!root)
        return;
    struct node* temp = root;
    printf("%c -> ", temp->data);
    for (int i=0; i<N; i++) {
        print(temp->children[i]);
    }
}
void search(struct node *root, char *word) {
    struct node *temp = root;
    int position = 0;
    for (int i = 0; word[i] != '\0'; i++) {
        position = (int)word[i] - 'a';
        if (temp->children[position] == NULL) {
            printf("\nWord not found");
            return;
        } else {
            temp = temp->children[position];
        }
    }
    if (temp->is_leaf == 1) {
        printf("\nWord found!");
    } else {
        printf("\nIncomplete word found!");
    }
}
bool is_complete_word(char *word) {
    struct node *temp = root;
    int position = 0;
    for (int i = 0; word[i] != '\0'; i++) {
        position = (int)word[i] - 'a';
        if (temp->children[position] != NULL) {
            temp = temp->children[position];
        }
    }
    return (temp->is_leaf == 1) ? true:false;
}
int check_divergence(struct node *root, char *prefix) {
    struct node *temp = root;
    int c_index = 0;
    for (int i = 0; i < strlen(prefix); i++) {
        int position = prefix[i] - 'a';
        if (temp->children[position]) {
            for (int j = 0; j < N; j++) {
                if (j != position && temp->children[j]) {
                    c_index = i;
                    break;
                }
            }
        }
    }
}

```

```

        temp = temp->children[position];
    }
}
return c_index;
}

char* common_prefix (struct node *root, char *word) {
    char *prefix = (char *)malloc((1 + strlen(word))*sizeof(char));
    strcpy(prefix, word);
    int index = check_divergence(root, prefix);
    if (index >= 0) {
        prefix[index] = '\0';
        prefix = (char *)realloc(prefix, (1+index) * sizeof(char));
    }
    return prefix;
}

void delete(struct node *root, char *word) {
    printf("\nDeletion in progress!");
    if (!is_complete_word(word)) {
        printf("\nIncomplete word cant be deleted!");
        return;
    }
    struct node *temp = root;
    char* cp = common_prefix(root, word);
    int i = 0;
    for (i = 0; cp[i] != '\0'; i++) {
        int position = (int)cp[i] - 'a';
        if (temp->children[position] != NULL) {
            temp = temp->children[position];
        } else {
            return;
        }
    }
    int len = strlen(word);
    for (; i < len; i++) {
        int position = (int)word[i] - 'a';
        if (temp->children[position] != NULL) {
            struct node* rem = temp->children[position];
            temp->children[position] = NULL;
            free(rem);
        }
    }
}

void main() {
    printf("\nTrie!");
    int choice = 0;
    int position = 0;
    int count = 0;
    int value = 0;
    struct node *new_node = NULL;
    char input[100];
    while (1) {
        printf("\n1.Create\n2.Insert Word\n3.Delete Word\n4.Search Word\n5.Print
Dictionary\n6.End");
        printf("\nSelect a choice:");
        scanf("%d",&choice);
        switch (choice) {

```

```

        case 1:
            printf("\nCreate!");
            new_node = allocate('\0');
            if (new_node == NULL) {
                printf("\nMalloc failure!");
                exit(1);
            } else {
                root = new_node;
            }
            break;
        case 2:
            printf("\nInsert Word!");
            printf("\nEnter a word to add to dictionary!");
            scanf("%s",input);
            insert(root, input);
            break;
        case 3:
            printf("\nDelete Word!");
            printf("\nEnter a word to delete from dictionary!");
            scanf("%s",input);
            delete(root, input);
            break;
        case 4:
            printf("\nSearch Word!");
            printf("\nEnter a word to search in dictionary!");
            scanf("%s",input);
            search(root, input);
            break;
        case 5:
            printf("\nPrint Dictionary!");
            print(root);
            break;
        case 6:
            printf("\nThank you!");
            exit(1);
            break;
        default:
            printf("\nTry again!");
            break;
    }
    choice = 0;
}
}

```

1.222 Graph Shortest Path

```

#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>
#include <limits.h>

typedef struct {
    int **adj;
    int n;
    int *cost;
    bool *visited;

```

```

} Graph;

int minCost(int *cost, bool *visited, int n) {
    int min = INT_MAX, min_node;

    for (int i = 0; i < n; i++) {
        if (visited[i] == false && cost[i] <= min) {
            min = cost[i];
            min_node = i;
        } else {
            printf("\nNOP");
        }
    }
    printf("\nmin cost = %d and min node = %d", min,min_node);
    return min_node;
}

Graph* graphCreate(int n, int** edges, int edgesSize, int* edgesColSize) {
    Graph *obj = malloc(sizeof(Graph));

    obj->n = n;
    obj->adj = (int **)calloc(n, sizeof(int *));
    obj->cost = (int *)calloc(n, sizeof(int));
    obj->visited = (bool *)calloc(n, sizeof(bool));

    for (int i = 0; i < n; i++) {
        obj->adj[i] = (int *)calloc(n, sizeof(int));
    }

    for (int i = 0; i < edgesSize; i++) {
        graphAddEdge(obj, edges[i], edgesColSize[i]);
    }

    return obj;
}

void graphAddEdge(Graph* obj, int* edge, int edgeSize) {
    obj->adj[edge[0]][edge[1]] = edge[2];
}

int graphShortestPath(Graph* obj, int node1, int node2) {

    for (int i = 0; i < obj->n; i++) {
        obj->cost[i] = INT_MAX,
        obj->visited[i] = false;
    }

    obj->cost[node1] = 0;
}

```

```

/* Dijkstra's Algorithm */
for (int i = 0; i < obj->n - 1; i++) {
    printf("\ni = %d",i);
    int src = minCost(obj->cost, obj->visited, obj->n);
    printf("\nsrc = %d",src);
    obj->visited[src] = true;

    for (int dst = 0; dst < obj->n; dst++)
        if (obj->visited[dst] == false && obj->adj[src][dst]
            && obj->cost[src] != INT_MAX
            && obj->cost[src] + obj->adj[src][dst] < obj->cost[dst]) {

            obj->cost[dst] = obj->cost[src] + obj->adj[src][dst];
            printf("\nobj->cost[%d] = %d obj->cost[%d] = %d",src,obj-
>cost[src],dst,obj->cost[dst]);
        } else {
            printf("\nElse");
        }
    }

    return obj->cost[node2] == INT_MAX ? -1 : obj->cost[node2];
}

void graphFree(Graph* obj) {

    for (int i = 0; i < obj->n; i++) {
        free(obj->adj[i]);
    }

    free(obj->adj);
    free(obj->cost);
    free(obj->visited);
    free(obj);
}

int main() {
    int n = 4;
    int edgesSize = 4;
    int edgesColSize[] = {3, 3, 3, 3};
    int** edges = (int**)malloc(edgesSize * sizeof(int*));
    for (int i = 0; i < edgesSize; i++) {
        edges[i] = (int*)malloc(edgesColSize[i] * sizeof(int));
    }

    edges[0][0] = 0;
    edges[0][1] = 2;
    edges[0][2] = 5;

    edges[1][0] = 0;

```

```

edges[1][1] = 1;
edges[1][2] = 2;

edges[2][0] = 1;
edges[2][1] = 2;
edges[2][2] = 1;

edges[3][0] = 3;
edges[3][1] = 0;
edges[3][2] = 3;

Graph* obj = graphCreate(n, edges, edgesSize, edgesColSize);

printf("\nShortest path from 3->2 is %d\n", graphShortestPath(obj, 3, 2)); // 6
printf("\nShortest path from 0->3 is %d\n", graphShortestPath(obj, 0, 3)); // -1

int newEdge[] = {1, 3, 4};
graphAddEdge(obj, newEdge, 3);

printf("\nShortest path from 0->3 is: %d\n", graphShortestPath(obj, 0, 3)); // 6

graphFree(obj);

return 0;
}

```

Time/Space Complexity: O(n²)/O(1)s

1.223 Semaphore

```

#include <stdio.h>
#include <pthread.h>

typedef struct {
    pthread_mutex_t mutex;
    pthread_cond_t condition;
    int value;
} semaphore;

void semaphore_init(semaphore* sem, int initial_value) {
    pthread_mutex_init(&(sem->mutex), NULL);
    pthread_cond_init(&(sem->condition), NULL);
    sem->value = initial_value;
}

void semaphore_wait(semaphore* sem) {
    pthread_mutex_lock(&(sem->mutex));
    while (sem->value <= 0) {
        pthread_cond_wait(&(sem->condition), &(sem->mutex));
    }
    sem->value--;
    pthread_mutex_unlock(&(sem->mutex));
}

```

```

}

void semaphore_signal(semaphore* sem) {
    pthread_mutex_lock(&(sem->mutex));
    sem->value++;
    pthread_cond_signal(&(sem->condition));
    pthread_mutex_unlock(&(sem->mutex));
}

void* thread_function(void* arg) {
    semaphore* sem = (semaphore*)arg;

    printf("Thread waiting\n");
    semaphore_wait(sem);

    printf("Thread acquired the semaphore\n");
    // Perform some critical section or shared resource access here

    printf("Thread releasing the semaphore\n");
    semaphore_signal(sem);

    return NULL;
}

int main() {
    semaphore sem;
    semaphore_init(&sem, 1); // Initialize the semaphore with initial value 1

    pthread_t thread;
    pthread_create(&thread, NULL, thread_function, (void*)&sem);

    // Main thread also performs some work
    printf("Main thread performing some work\n");

    // Main thread waits for the semaphore
    printf("Main thread waiting\n");
    semaphore_wait(&sem);

    printf("Main thread acquired the semaphore\n");
    // Perform some critical section or shared resource access here

    printf("Main thread releasing the semaphore\n");
    semaphore_signal(&sem);

    pthread_join(thread, NULL);

    return 0;
}

```

```

#include <stdio.h>
#include <pthread.h>
#include <semaphore.h>
#include <unistd.h>

sem_t mutex;

```

```

void* thread(void* arg)
{
    //wait
    sem_wait(&mutex);
    printf("\nEntered..\n");

    //critical section
    sleep(4);

    //signal
    printf("\nJust Exiting...\n");
    sem_post(&mutex);
}

int main()
{
    sem_init(&mutex, 0, 1);
    pthread_t t1,t2;
    pthread_create(&t1,NULL,thread,NULL);
    sleep(2);
    pthread_create(&t2,NULL,thread,NULL);
    pthread_join(t1,NULL);
    pthread_join(t2,NULL);
    sem_destroy(&mutex);
    return 0;
}

```

1.224 Mutex

```

#include <pthread.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>

pthread_t tid[2];
int counter;
pthread_mutex_t lock;

void* trythis(void* arg)
{
    pthread_mutex_lock(&lock);

    unsigned long i = 0;
    counter += 1;
    printf("\n Job %d has started\n", counter);

    for (i = 0; i < (0xFFFFFFFF); i++)
        ;

    printf("\n Job %d has finished\n", counter);

    pthread_mutex_unlock(&lock);

    return NULL;
}

```

```

int main(void)
{
    int i = 0;
    int error;

    if (pthread_mutex_init(&lock, NULL) != 0) {
        printf("\n mutex init has failed\n");
        return 1;
    }

    while (i < 2) {
        error = pthread_create(&(tid[i]),
                              NULL,
                              &trythis, NULL);
        if (error != 0)
            printf("\nThread can't be created :[%s]",
                   strerror(error));
        i++;
    }

    pthread_join(tid[0], NULL);
    pthread_join(tid[1], NULL);
    pthread_mutex_destroy(&lock);

    return 0;
}

```

1.225 Blocking Queue

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <semaphore.h>

#define QUEUE_SIZE 5

typedef struct {
    int* buffer;
    int size;
    int front;
    int rear;
    pthread_mutex_t mutex;      // Mutex for mutual exclusion
    pthread_cond_t not_empty;   // Condition variable for not empty
    pthread_cond_t not_full;    // Condition variable for not full
} CircularQueue;

// Initialize the circular queue
void initializeQueue(CircularQueue* queue, int size) {
    queue->buffer = (int*)malloc(sizeof(int) * size);
    queue->size = size;
    queue->front = 0;
    queue->rear = 0;
    pthread_mutex_init(&queue->mutex, NULL);
    pthread_cond_init(&queue->not_empty, NULL);

```

```

pthread_cond_init(&queue->not_full, NULL);
}

// Enqueue an item into the circular queue
void enqueue(CircularQueue* queue, int item) {
    pthread_mutex_lock(&queue->mutex);

    while ((queue->rear + 1) % queue->size == queue->front) {
        // Queue is full, wait for space
        pthread_cond_wait(&queue->not_full, &queue->mutex);
    }

    queue->buffer[queue->rear] = item;
    queue->rear = (queue->rear + 1) % queue->size;

    pthread_cond_signal(&queue->not_empty); // Notify that the queue is not empty
    pthread_mutex_unlock(&queue->mutex);
}

// Dequeue an item from the circular queue
int dequeue(CircularQueue* queue) {
    pthread_mutex_lock(&queue->mutex);

    while (queue->front == queue->rear) {
        // Queue is empty, wait for items
        pthread_cond_wait(&queue->not_empty, &queue->mutex);
    }

    int item = queue->buffer[queue->front];
    queue->front = (queue->front + 1) % queue->size;

    pthread_cond_signal(&queue->not_full); // Notify that the queue is not full
    pthread_mutex_unlock(&queue->mutex);

    return item;
}

// Clean up the circular queue
void cleanupQueue(CircularQueue* queue) {
    free(queue->buffer);
    pthread_mutex_destroy(&queue->mutex);
    pthread_cond_destroy(&queue->not_empty);
    pthread_cond_destroy(&queue->not_full);
}

// Example usage
void* producer(void* arg) {
    CircularQueue* queue = (CircularQueue*)arg;
}

```

```

        for (int i = 1; i <= 10; ++i) {
            enqueue(queue, i);
            printf("Produced: %d\n", i);
        }

        pthread_exit(NULL);
    }
void* consumer(void* arg) {
    CircularQueue* queue = (CircularQueue*)arg;

    for (int i = 0; i < 10; ++i) {
        int item = dequeue(queue);
        printf("Consumed: %d\n", item);
    }

    pthread_exit(NULL);
}

int main() {
    CircularQueue queue;
    initializeQueue(&queue, QUEUE_SIZE);

    pthread_t producerThread, consumerThread;

    pthread_create(&producerThread, NULL, producer, &queue);
    pthread_create(&consumerThread, NULL, consumer, &queue);

    pthread_join(producerThread, NULL);
    pthread_join(consumerThread, NULL);

    cleanupQueue(&queue);

    return 0;
}

```

1.226 String to Integer(atoi)

```

int myAtoi(char * s){
    int i = 0;
    int j = strlen(s)-1;
    int result = 0;
    int sign = 1;
    if (isalpha(s[i])) {
        //printf("\n1");
        return 0;
    }
    while (s[i] == ' ') {
        //printf("\n2");

```

```

        i++;
    }
    if (s[i] == '+') {
        //printf("\n3");
        sign = 1;
        i++;
    } else if (s[i] == '-'){
        //printf("\n4");
        sign = -1;
        i++;
    } else {
        sign = 1;
    }
    while (i <= j) {
        //printf("\n5");
        if (isdigit(s[i])) {
            //printf("\n6");
            if ((result > INT_MAX/10) ||
                (result == INT_MAX/10) && (s[i]-'0') > INT_MAX%10) {
                printf("\na");
            }
            return (sign == -1)? INT_MIN:INT_MAX;
        }

        result = 10*result + (s[i]-'0');
        //printf("\nres : %d",result);
        i++;
    } else {
        //printf("\n7");
        i++;
        break;
    }
}
//printf("\n8");
result = result*sign;
return result;
}

```

1.227 Add Two Numbers

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */

// Function to create a new node with a given value
struct ListNode* newNode(int val) {

```

```

    struct ListNode* node = (struct ListNode*)malloc(sizeof(struct ListNode));
    node->val = val;
    node->next = NULL;
    return node;
}

struct ListNode* addTwoNumbers(struct ListNode* l1, struct ListNode* l2) {
    struct ListNode* dummyHead = (struct ListNode*)malloc(sizeof(struct ListNode));
    struct ListNode* current = dummyHead;
    int carry = 0;

    while (l1 != NULL || l2 != NULL) {
        int x = (l1 != NULL) ? l1->val : 0;
        int y = (l2 != NULL) ? l2->val : 0;
        int sum = x + y + carry;

        carry = sum / 10;

        current->next = (struct ListNode*)malloc(sizeof(struct ListNode));
        current->next->val = sum % 10;
        current->next->next = NULL;

        current = current->next;

        if (l1 != NULL) l1 = l1->next;
        if (l2 != NULL) l2 = l2->next;
    }

    if (carry > 0) {
        current->next = (struct ListNode*)malloc(sizeof(struct ListNode));
        current->next->val = carry;
        current->next->next = NULL;
    }

    struct ListNode* result = dummyHead->next;
    free(dummyHead);
}

return result;
}

```

1.228 Next Permutation

```

#include <stdio.h>

// Function to swap two elements in an array
void swap(int* nums, int i, int j) {
    int temp = nums[i];
    nums[i] = nums[j];
    nums[j] = temp;
}

// Function to reverse a portion of an array

```

```

void reverse(int* nums, int start, int end) {
    int i = start, j = end;
    while (i < j) {
        swap(nums, i, j);
        i++;
        j--;
    }
}

// Function to find the next permutation
void nextPermutation(int* nums, int numsSize) {
    //First find the lesser element in the array starting from last
    int i = numsSize - 2;
    while (i >= 0 && nums[i + 1] <= nums[i]) {
        i--;
    }
    //Then find the element which is greater than that element
    if (i >= 0) {
        int j = numsSize - 1;
        while (nums[j] <= nums[i]) {
            j--;
        }
        //Swap those numbers
        swap(nums, i, j);
    }
    //Reverse the numbers from that index to the found index (ascending order)
    reverse(nums, i + 1, numsSize - 1);
}

```

```

public class Solution {
    public void nextPermutation(int[] nums) {
        int i = nums.length - 2;
        while (i >= 0 && nums[i + 1] <= nums[i]) {
            i--;
        }
        if (i >= 0) {
            int j = nums.length - 1;
            while (nums[j] <= nums[i]) {
                j--;
            }
            swap(nums, i, j);
        }
        reverse(nums, i + 1);
    }

    private void reverse(int[] nums, int start) {
        int i = start, j = nums.length - 1;

```

```

        while (i < j) {
            swap(nums, i, j);
            i++;
            j--;
        }
    }

private void swap(int[] nums, int i, int j) {
    int temp = nums[i];
    nums[i] = nums[j];
    nums[j] = temp;
}
}

General Permutation
#include <stdio.h>

// Function to swap two elements in an array
void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

// Function to generate permutations
void generatePermutations(int arr[], int size, int index) {
    if (index == size - 1) {
        // Print the current permutation
        for (int i = 0; i < size; i++) {
            printf("%d ", arr[i]);
        }
        printf("\n");
        return;
    }

    for (int i = index; i < size; i++) {
        // Swap the current element with the element at index
        swap(&arr[index], &arr[i]);

        // Recursively generate permutations for the remaining elements
        generatePermutations(arr, size, index + 1);

        // Undo the swap to backtrack
        swap(&arr[index], &arr[i]);
    }
}

int main() {
    // Example usage
    int arr[] = {1, 2, 3};
}

```

```

        int size = sizeof(arr) / sizeof(arr[0]);

        printf("Permutations:\n");
        generatePermutations(arr, size, 0);

        return 0;
    }

```

1.229 First Missing Positive

```

int firstMissingPositive(int* nums, int numsSize) {
    // Create a boolean array to mark the presence of positive numbers
    bool present[numsSize + 1];
    for (int i = 0; i <= numsSize; i++) {
        present[i] = false;
    }

    // Mark positive numbers in the array
    for (int i = 0; i < numsSize; i++) {
        if (nums[i] > 0 && nums[i] <= numsSize) {
            present[nums[i]] = true;
        }
    }

    // Find the first missing positive number
    for (int i = 1; i <= numsSize; i++) {
        if (!present[i]) {
            return i;
        }
    }

    // If all positive numbers are present, return the next positive number
    return numsSize + 1;
}

```

1.230 Permutations

```

/**
 * Return an array of arrays of size *returnSize.
 * The sizes of the arrays are returned as *returnColumnSizes array.
 * Note: Both returned array and *columnSizes array must be malloced, assume caller
 * calls free().
 */
// Function to swap two elements in an array
void swap(int* a, int* b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

// Function to generate permutations

```

```

void generatePermutations(int* nums, int numsSize, int index, int** result, int*
returnSize, int* returnColumnSizes) {
    if (index == numsSize - 1) {
        // Allocate memory for the current permutation
        result[*returnSize] = (int*)malloc(numsSize * sizeof(int));
        // Copy the current permutation to the result array
        for (int i = 0; i < numsSize; i++) {
            result[*returnSize][i] = nums[i];
        }
        // Update returnColumnSizes with the size of the current permutation
        returnColumnSizes[*returnSize] = numsSize;
        // Increment returnSize to keep track of the number of permutations
        (*returnSize)++;
        return;
    }

    for (int i = index; i < numsSize; i++) {
        // Swap the current element with the element at index
        swap(&nums[index], &nums[i]);

        // Recursively generate permutations for the remaining elements
        generatePermutations(nums, numsSize, index + 1, result, returnSize,
returnColumnSizes);

        // Undo the swap to backtrack
        swap(&nums[index], &nums[i]);
    }
}

int** permute(int* nums, int numsSize, int* returnSize, int** returnColumnSizes) {
    // Calculate the number of permutations (n!)
    int totalPermutations = 1;
    for (int i = 1; i <= numsSize; i++) {
        totalPermutations *= i;
    }

    // Allocate memory for the result array
    int** result = (int**)malloc(totalPermutations * sizeof(int*));

    // Allocate memory for returnColumnSizes array
    *returnColumnSizes = (int*)malloc(totalPermutations * sizeof(int));

    // Initialize returnSize
    *returnSize = 0;

    // Generate permutations
    generatePermutations(nums, numsSize, 0, result, returnSize, *returnColumnSizes);

    return result;
}




```

}

1.231 Remove Duplicates From Sorted List

Given the head of a sorted linked list, *delete all duplicates such that each element appears only once.*
Return *the linked list sorted as well.*




Example 1:



Input: head = [1,1,2]

Output: [1,2]

Example 2:



Input: head = [1,1,2,3,3]

Output: [1,2,3]

```
/**  
 * Definition for singly-linked list.  
 * struct ListNode {  
 *     int val;  
 *
```

```

*     struct ListNode *next;
* };
*/
// Function to delete duplicates from a sorted linked list
struct ListNode* deleteDuplicates(struct ListNode* head) {
    struct ListNode* current = head;

    // Traverse the list
    while (current != NULL && current->next != NULL) {
        // Check if the current and next nodes have the same value
        if (current->val == current->next->val) {
            // Duplicate found, remove the next node
            struct ListNode* duplicate = current->next;
            current->next = current->next->next;
            free(duplicate);
        } else {
            // Move to the next node
            current = current->next;
        }
    }

    return head;
}

// Function to print the linked list
void printList(struct ListNode* head) {
    struct ListNode* current = head;
    while (current != NULL) {
        printf("%d -> ", current->val);
        current = current->next;
    }
    printf("NULL\n");
}

// Function to create a new node with the given value
struct ListNode* newNode(int val) {
    struct ListNode* node = (struct ListNode*)malloc(sizeof(struct ListNode));
    node->val = val;
    node->next = NULL;
    return node;
}

```

1.232 Binary Tree InOrder Traversal

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *

```

```

*     struct TreeNode *right;
* };
*/
/** 
 * Note: The returned array must be malloced, assume caller calls free().
 */
// Function to perform inorder traversal of a binary tree
void inorderTraversalHelper(struct TreeNode* root, int* result, int* index) {
    if (root == NULL) {
        return;
    }

    // Traverse the left subtree
    inorderTraversalHelper(root->left, result, index);

    // Visit the current node
    result[(*index)++] = root->val;

    // Traverse the right subtree
    inorderTraversalHelper(root->right, result, index);
}

// Function to get the size of a binary tree
int getSize(struct TreeNode* root) {
    if (root == NULL) {
        return 0;
    }

    return 1 + getSize(root->left) + getSize(root->right);
}

// Function to perform inorder traversal and return the result as an array
int* inorderTraversal(struct TreeNode* root, int* returnSize) {
    // Get the size of the binary tree
    *returnSize = getSize(root);

    // Allocate memory for the result array
    int* result = (int*)malloc((*returnSize) * sizeof(int));

    // Index to keep track of the position in the result array
    int index = 0;

    // Perform inorder traversal
    inorderTraversalHelper(root, result, &index);

    return result;
}

```

1.233 Binary Tree ZigZag Level Order Traversal

```
class Solution {
    public List<List<Integer>> zigzagLevelOrder(TreeNode root) {
        List<List<Integer>> levels = new ArrayList<List<Integer>>();
        if (root == null) return levels;

        Queue<TreeNode> queue = new LinkedList<TreeNode>();
        queue.add(root);
        int level = 0;
        while ( !queue.isEmpty() ) {
            // start the current level
            levels.add(new ArrayList<Integer>());

            // number of elements in the current level
            int level_length = queue.size();

            for(int i = 0; i < level_length; ++i) {
                TreeNode node = queue.remove();

                // fulfill the current level
                levels.get(level).add(node.val);


                // add child nodes of the current level
                // in the queue for the next level
                if (node.left != null) queue.add(node.left);
                if (node.right != null) queue.add(node.right);
            }
            // go to next level
            level++;
        }
        for (int i = 0; i < levels.size(); i++) {
            if (i % 2 == 1) {
                Collections.reverse(levels.get(i));
            }
        }
        return levels;
    }
}
```

1.234 Flatten Binary Tree To Linked List

Given the root of a binary tree, flatten the tree into a "linked list":

- The "linked list" should use the same TreeNode class where the right child pointer points to the next node in the list and the left child pointer is always null.
- The "linked list" should be in the same order as a [pre-order traversal](#) of the binary tree.

Example 1:



Input: root = [1,2,5,3,4,null,6]

Output: [1,null,2,null,3,null,4,null,5,null,6]

Example 2:

Input: root = []

Output: []

Example 3:

Input: root = [0]

Output: [0]

```
void flatten(struct TreeNode* root) {
    if (root == NULL) {
        return;
    }

    struct TreeNode* current = root;

    while (current != NULL) {
        // If the current node has a left child
        if (current->left != NULL) {
            // Find the rightmost node in the left subtree
            struct TreeNode* rightmost = current->left;
            while (rightmost->right != NULL) {
                rightmost = rightmost->right;
            }

            // Move the right subtree to the rightmost node's right child
            rightmost->right = current->right;
        }
    }
}
```

```

        // Move the left subtree to the right child
        current->right = current->left;
        current->left = NULL;
    }

    // Move to the next node in the flattened tree
    current = current->right;
}
}

// Function to create a new binary tree node with the given value
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

// Function to print the flattened linked list
void printFlattenedList(struct TreeNode* root) {
    struct TreeNode* current = root;
    while (current != NULL) {
        printf("%d -> ", current->val);
        current = current->right;
    }
    printf("NULL\n");
}

```

1.235 Binary Tree Post Order Traversal

```

// Function to get the size of a binary tree
int getSize(struct TreeNode* root) {
    if (root == NULL) {
        return 0;
    }

    return 1 + getSize(root->left) + getSize(root->right);
}

// Function to perform postorder traversal of a binary tree
void postorderTraversalHelper(struct TreeNode* root, int* result, int* index) {
    if (root == NULL) {
        return;
    }

    // Traverse the left subtree
    postorderTraversalHelper(root->left, result, index);

    // Traverse the right subtree
    postorderTraversalHelper(root->right, result, index);
}

```

```

        // Visit the current node
        result[(*index)++] = root->val;
    }

// Function to perform postorder traversal and return the result as an array
int* postorderTraversal(struct TreeNode* root, int* returnSize) {
    // Get the size of the binary tree
    *returnSize = getSize(root);

    // Allocate memory for the result array
    int* result = (int*)malloc((*returnSize) * sizeof(int));

    // Index to keep track of the position in the result array
    int index = 0;

    // Perform postorder traversal
    postorderTraversalHelper(root, result, &index);

    return result;
}

```

1.236 Binary Tree Pre Order Traversal

```

int getSize(struct TreeNode* root) {
    if (root == NULL) {
        return 0;
    }

    return 1 + getSize(root->left) + getSize(root->right);
}

// Function to perform preorder traversal of a binary tree
void preorderTraversalHelper(struct TreeNode* root, int* result, int* index) {
    if (root == NULL) {
        return;
    }

    // Visit the current node
    result[(*index)++] = root->val;

    // Traverse the left subtree
    preorderTraversalHelper(root->left, result, index);

    // Traverse the right subtree
    preorderTraversalHelper(root->right, result, index);
}

// Function to perform preorder traversal and return the result as an array
int* preorderTraversal(struct TreeNode* root, int* returnSize) {

```

```

// Get the size of the binary tree
*returnSize = getSize(root);

// Allocate memory for the result array
int* result = (int*)malloc((*returnSize) * sizeof(int));

// Index to keep track of the position in the result array
int index = 0;

// Perform preorder traversal
preorderTraversalHelper(root, result, &index);

return result;
}

// Function to create a new binary tree node with the given value
struct TreeNode* newNode(int val) {
    struct TreeNode* node = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    node->val = val;
    node->left = NULL;
    node->right = NULL;
    return node;
}

```

1.237 Excel Sheet Column Number

```

int titleToNumber(char* columnTitle) {
    int result = 0;
    int length = strlen(columnTitle);

    for (int i = length - 1; i >= 0; i--) {
        result += pow(26, (length - 1 - i)) * (columnTitle[i] - 'A' + 1);
    }

    return result;
}

class Solution {
    public int titleToNumber(String s) {
        int result = 0;
        int n = s.length();
        for (int i = 0; i < n; i++) {
            result = result * 26;
            // In Java, subtracting characters is subtracting ASCII values of characters
            result += (s.charAt(i) - 'A' + 1);
        }
        return result;
    }
}

```

1.238 Ugly Number

```

bool isUgly(int n) {
    if (n <= 0) {

```

```

        return false;
    }

    while (n % 2 == 0) {
        n /= 2;
    }
    while (n % 3 == 0) {
        n /= 3;
    }
    while (n % 5 == 0) {
        n /= 5;
    }

    return n == 1;
}

```

1.239 Game Of Life

```

#define DIE 2
#define LIVE 3

int countLive(int i, int j, int** board, int rows, int cols) {
    int count = 0;
    int dirs[8][2] = {{1, 0}, {-1, 0}, {0, 1}, {0, -1}, {1, 1}, {1, -1}, {-1, 1}, {-1, -1}};
}

for (int k = 0; k < 8; k++) {
    int x = i + dirs[k][0];
    int y = j + dirs[k][1];

    if (x >= 0 && y >= 0 && x < rows && y < cols) {
        if (board[x][y] == 1 || board[x][y] == DIE)
            count++;
    }
}

return count;
}

void gameOfLife(int** board, int boardSize, int* boardColSize) {
    if (!board || boardSize == 0 || !boardColSize || *boardColSize == 0)
        return;

    int rows = boardSize;
    int cols = *boardColSize;

    for (int i = 0; i < rows; i++) {
        for (int j = 0; j < cols; j++) {

```

```

        int around = countLive(i, j, board, rows, cols);
        if (board[i][j] == 0 && around == 3)
            board[i][j] = LIVE;
        else if (board[i][j] == 1) {
            if (around == 2 || around == 3)
                continue;
            if (around < 2 || around > 3)
                board[i][j] = DIE;
        }
    }
}

for (int i = 0; i < rows; i++) {
    for (int j = 0; j < cols; j++) {
        if (board[i][j] == DIE)
            board[i][j] = 0;
        if (board[i][j] == LIVE)
            board[i][j] = 1;
    }
}
}

```

1.240 Minimum Number Of Arrows To Burst Balloons

```

// Comparison function for qsort
int compareIntervals(const void* a, const void* b) {
    int* intervalA = *(int**)a;
    int* intervalB = *(int**)b;

    if (intervalA[1] == intervalB[1])
        return 0;
    } else if (intervalA[1] < intervalB[1]) {
        return -1;
    } else {
        return 1;
    }
}

int findMinArrowShots(int** points, int pointsSize, int* pointsColSize) {
    if (pointsSize == 0)
        return 0;
}

// Sort the intervals based on their end points
qsort(points, pointsSize, sizeof(int*), compareIntervals);
for (int i = 0; i < pointsSize; i++) {
    printf("\n%d %d", points[i][0], points[i][1]);
}
int arrows = 1;
int xStart, xEnd, firstEnd = points[0][1];

```

```

        for (int i = 1; i < pointsSize; i++) {
            xStart = points[i][0];
            xEnd = points[i][1];

            // If the current balloon starts after the end of another one,
            // one needs one more arrow
            if (firstEnd < xStart) {
                arrows++;
                firstEnd = xEnd;
            }
        }

        return arrows;
    }
}

```

1.241 Exclusive Time Of Functions

```

public class Solution {
    public int[] exclusiveTime(int n, List<String> logs) {
        // separate time to several intervals, add interval to their function
        int[] res = new int[n];
        //store id, not timestamp
        Stack<Integer> idStack = new Stack<>();
        //store timestamp: prevLogTime here is to maintain previous functions time
        // and if it is start function we just add it to previous if it is an end
function
        // then add plus one to mark the end of the top of stack function
        //((It's used to record last log time)
        int prevLogTime = 0;
        // pre means the start of the interval
        for (String s : logs) {
            String[] log = s.split(":");
            if (log[1].equals("start")) {
                if (!idStack.isEmpty()) res[idStack.peek()] += Integer.parseInt(log[2])
- prevLogTime;
                // log[2] is the start of next interval, doesn't belong to current
interval.
                idStack.push(Integer.parseInt(log[0]));
                prevLogTime = Integer.parseInt(log[2]);
            } else {
                res[idStack.pop()] += Integer.parseInt(log[2]) - prevLogTime + 1;
                // log[2] is end of current interval, belong to current interval. That's
why we have +1 here
                prevLogTime = Integer.parseInt(log[2]) + 1;
                // prevLogTime means the start of next interval, so we need to +1
            }
        }
        return res;
    }
}

```

1.242 Top K Frequent Words

```
class Solution {
    public List<String> topKFrequent(String[] words, int k) {
        HashMap<String, Integer> hm = new HashMap<String, Integer>();
        for (String s:words) {
            hm.put(s, hm.getOrDefault(s, 0)+1);
        }

        Queue<Map.Entry<String, Integer>> pq = new PriorityQueue<>(
            (a, b) -> a.getValue().equals(b.getValue()) ? a.getKey().compareTo(b.getKey())
        () : b.getValue() - a.getValue()
        );

        for(HashMap.Entry<String, Integer> entry: hm.entrySet()) {
            pq.add(entry);

        }
        System.out.println(pq.toString());
        List<String> l = new ArrayList<String>();
        int i = 0;
        while (i < k) {
            l.add(pq.poll().getKey());
            System.out.println("Now"+pq.toString());
            i++;
        }

        return l;
    }
}
```

1.243 Walking Robot Simulation

```
#include <stdlib.h>
#include <math.h>

// Define a structure to represent a point
struct Point {
    int x;
    int y;
};

// Function to calculate the squared Euclidean distance
int calculateDistanceSquared(struct Point p) {
    return p.x * p.x + p.y * p.y;
}
```

```

int robotSim(int* commands, int commandsSize, int** obstacles, int obstaclesSize, int*
obstaclesColSize) {
    // Define the four possible directions: North, East, South, West
    int directions[4][2] = {{0, 1}, {1, 0}, {0, -1}, {-1, 0}};

    // Initialize the current position and direction of the robot
    struct Point currentPosition = {0, 0};
    int currentDirection = 0; // 0 represents North

    // Create a set to store obstacle positions for quick lookup
    int** obstacleSet = (int**)malloc(obstaclesSize * sizeof(int*));
    for (int i = 0; i < obstaclesSize; i++) {
        obstacleSet[i] = (int*)malloc(2 * sizeof(int));
        obstacleSet[i][0] = obstacles[i][0];
        obstacleSet[i][1] = obstacles[i][1];
    }

    // Initialize the result (maximum squared distance)
    int result = 0;

    // Iterate through the commands
    for (int i = 0; i < commandsSize; i++) {
        if (commands[i] == -1) {
            // Turn right 90 degrees
            currentDirection = (currentDirection + 1) % 4;
        } else if (commands[i] == -2) {
            // Turn left 90 degrees
            currentDirection = (currentDirection + 3) % 4;
        } else {
            // Move forward k units
            for (int j = 0; j < commands[i]; j++) {
                struct Point nextPosition = {currentPosition.x +
directions[currentDirection][0],
                                              currentPosition.y +
directions[currentDirection][1]};

                // Check for obstacles
                int obstacleDetected = 0;
                for (int k = 0; k < obstaclesSize; k++) {
                    if (nextPosition.x == obstacleSet[k][0] && nextPosition.y ==
obstacleSet[k][1]) {
                        obstacleDetected = 1;
                        break;
                    }
                }
            }

            // Update position if no obstacle is detected
            if (!obstacleDetected) {
                currentPosition = nextPosition;
            }
        }
    }
}

```

```

        result = fmax(result, calculateDistanceSquared(currentPosition));
    } else {
        // Break out of the loop if an obstacle is detected
        break;
    }
}
}

// Free memory allocated for the obstacle set
for (int i = 0; i < obstaclesSize; i++) {
    free(obstacleSet[i]);
}
free(obstacleSet);

return result;
}

```

1.244 Cousins In Binary Tree

```

/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     struct TreeNode *left;
 *     struct TreeNode *right;
 * };
 */
;

// Structure to represent a queue node for level-order traversal
struct QueueNode {
    struct TreeNode* node;
    int depth;
    int parent;
};

// Queue functions for level-order traversal
struct Queue {
    int front, rear;
    int capacity;
    struct QueueNode* array;
};

struct Queue* createQueue(int capacity) {
    struct Queue* queue = (struct Queue*)malloc(sizeof(struct Queue));
    queue->capacity = capacity;
    queue->front = queue->rear = -1;
    queue->array = (struct QueueNode*)malloc(capacity * sizeof(struct QueueNode));
    return queue;
}

```

```

}

void enqueue(struct Queue* queue, struct TreeNode* node, int depth, int parent) {
    struct QueueNode qNode = {node, depth, parent};
    if (queue->front == -1) {
        queue->front = queue->rear = 0;
    } else {
        queue->rear = (queue->rear + 1) % queue->capacity;
    }
    queue->array[queue->rear] = qNode;
}

struct QueueNode dequeue(struct Queue* queue) {
    struct QueueNode qNode = queue->array[queue->front];
    if (queue->front == queue->rear) {
        queue->front = queue->rear = -1;
    } else {
        queue->front = (queue->front + 1) % queue->capacity;
    }
    return qNode;
}

bool isCousins(struct TreeNode* root, int x, int y) {
    struct Queue* queue = createQueue(1000); // Assuming a maximum of 1000 nodes in the tree
    enqueue(queue, root, 0, -1); // Root has depth 0 and no parent

    int parentX = -1, parentY = -1;
    int depthX = -1, depthY = -1;

    while (queue->front != -1) {
        int levelSize = queue->rear - queue->front + 1;
        for (int i = 0; i < levelSize; i++) {
            struct QueueNode qNode = dequeue(queue);
            struct TreeNode* node = qNode.node;
            int depth = qNode.depth;
            int parent = qNode.parent;

            if (node->val == x) {
                parentX = parent;
                depthX = depth;
            } else if (node->val == y) {
                parentY = parent;
                depthY = depth;
            }
        }

        if (parentX != -1 && parentY != -1) {
            if (parentX == parentY) {
                return false;
            } else if (depthX != depthY) {
                return true;
            }
        }
    }

    return false;
}

```

```

        if (node->right) {
            enqueue(queue, node->right, depth + 1, node->val);
        }
    }

    // Check if both nodes are found at the same level
    if ((parentX != -1 && parentY != -1) && (depthX == depthY) && (parentX != parentY)) {
        return true;
    }

    // Reset variables for the next level
    parentX = parentY = -1;
    depthX = depthY = -1;
}

return false;
}

```

1.245 Maximum Equal Frequency

```

class Solution {
    public int maxEqualFreq(int[] nums) {
        int maxLen = 0;
        int n = nums.length;
        HashMap<Integer, Integer> freqMap = new HashMap<>();
        HashMap<Integer, Integer> countMap = new HashMap<>();

        for (int i = 0; i < n; i++) {
            int num = nums[i];

            // Update the frequency count for the current number
            freqMap.put(num, freqMap.getOrDefault(num, 0) + 1);

            // Update the countMap based on the frequency count
            int freq = freqMap.get(num);
            int count = countMap.getOrDefault(freq, 0);
            countMap.put(freq, count + 1);

            // Check if removing one element makes all frequencies equal
            if (count * freq == i || (count - 1) * (freq - 1) == i) {
                maxLen = i + 1;
            }
        }

        return maxLen;
    }
}

```

1.246 Packet Parser Multithreading

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

// Define packet structures (Ethernet, IP, TCP, Application)
typedef struct {
    // Ethernet header fields
    // ...
    // IP header fields
    // ...
} EthernetPacket;

typedef struct {
    // TCP header fields
    // ...
} TCPPacket;

typedef struct {
    // Application layer payload
    // ...
} ApplicationPacket;

// Packet structure containing all headers
typedef struct {
    EthernetPacket ethernet;
    TCPPacket tcp;
    ApplicationPacket app;
} FullPacket;

// Function to process a packet
void processPacket(FullPacket* packet) {
    // Process packet headers and payload
    // ...

    // Example: Print packet details
    printf("Processed packet\n");
}

// Function to simulate packet reception
FullPacket generateRandomPacket() {
    // Simulate packet creation with random data
    FullPacket packet;
    // ...

    return packet;
}

// Thread function for packet processing
void* processThread(void* arg) {
    for (;;) {
        FullPacket packet = generateRandomPacket();
        processPacket(&packet);
    }
}
```

```

        return NULL;
    }

int main() {
    // Create threads for packet processing
    pthread_t threads[2];
    for (int i = 0; i < 2; ++i) {
        if (pthread_create(&threads[i], NULL, processThread, NULL) != 0) {
            fprintf(stderr, "Error creating thread\n");
            exit(EXIT_FAILURE);
        }
    }

    // Wait for threads to finish (this is a simple example, in a real scenario, threads may run indefinitely)
    for (int i = 0; i < 2; ++i) {
        pthread_join(threads[i], NULL);
    }

    return 0;
}

```

```

#include <stdio.h>
#include <stdint.h>
#include <stdlib.h>
#include <pthread.h>

// Define Ethernet, IPv4, TCP, and application header structures as before

struct EthernetHeader {
    uint8_t destMAC[6];
    uint8_t srcMAC[6];
    uint16_t etherType;
};

struct IPv4Header {
    uint8_t versionIHL;
    uint8_t dscpECN;
    uint16_t totalLength;
    uint16_t identification;
    uint16_t flagsFragmentOffset;
    uint8_t timeToLive;
    uint8_t protocol;
    uint16_t headerChecksum;
    uint32_t srcIP;
    uint32_t destIP;
};

struct TCPHeader {
    uint16_t srcPort;
    uint16_t destPort;
    uint32_t sequenceNumber;
    uint32_t ackNumber;
    uint8_t dataOffsetReserved;
    uint8_t flags;
    uint16_t windowSize;
    uint16_t checksum;
    uint16_t urgentPointer;
};

```

```

};

// Define a structure to hold frame data
struct FrameData {
    uint8_t* frame;
    uint16_t frameLength;
};

void* processFrame(void* arg);

int main() {
    // Example Ethernet frames (add more frames as needed)
    uint8_t frame1[] = { /* Frame 1 data */ };
    uint8_t frame2[] = { /* Frame 2 data */ };
    uint8_t frame[] = {
        // Ethernet header
        0x00, 0x11, 0x22, 0x33, 0x44, 0x55, // Source MAC
        0x66, 0x77, 0x88, 0x99, 0xAA, 0xBB, // Destination MAC
        0x08, 0x00, // EtherType (IPv4)
        // IPv4 header
        0x45, 0x00, 0x00, 0x3C, 0x12, 0x34, 0x40, 0x00, 0x40, 0x06, 0x00, 0x00,
        0xC0, 0xA8, 0x01, 0x01, // Source IP: 192.168.1.1
        0xC0, 0xA8, 0x01, 0x02, // Destination IP: 192.168.1.2
        // TCP header
        0x00, 0x50, 0x00, 0x37, 0xB8, 0xA0, 0x00, 0x00, 0x00, 0xA0, 0x02,
        0xFA, 0xF0, 0x00, 0x00, 0x02, 0x04, 0x05, 0xB4, 0x01, 0x03, 0x03, 0x06,
        // Application data (HTTP request)
        0x47, 0x45, 0x54, 0x20, 0x2F, 0x20, 0x48, 0x54, 0x54, 0x50, 0x2F, 0x31,
        0x2E, 0x31, 0x0D, 0x0A, 0x48, 0x6F, 0x73, 0x74, 0x3A, 0x20, 0x77, 0x77,
        // ... (HTTP request continues)
    };
}

```

```

pthread_t thread1, thread2;

// Create a FrameData structure for each frame
struct FrameData data1 = {frame1, sizeof(frame1)};
struct FrameData data2 = {frame2, sizeof(frame2)};
// ...

// Create threads to process frames concurrently
pthread_create(&thread1, NULL, processFrame, (void*)&data1);
pthread_create(&thread2, NULL, processFrame, (void*)&data2);
// ...

// Wait for threads to finish
pthread_join(thread1, NULL);
pthread_join(thread2, NULL);
// ...

return 0;
}

void* processFrame(void* arg) {
    struct FrameData* frameData = (struct FrameData*)arg;
    processEthernetFrame(frameData->frame, frameData->frameLength);
    pthread_exit(NULL);
}

```

```

}

void processEthernetFrame(const uint8_t* frame, uint16_t frameLength) {
    if (frameLength < sizeof(struct EthernetHeader)) {
        printf("Invalid Ethernet frame\n");
        return;
    }

    struct EthernetHeader* ethHeader = (struct EthernetHeader*)frame;

    printf("Ethernet Frame - Source MAC: ");
    printMACAddress(ethHeader->srcMAC);
    printf(" Destination MAC: ");
    printMACAddress(ethHeader->destMAC);
    printf(" EtherType: %04x\n", ntohs(ethHeader->etherType));

    // Assuming Ethernet frame contains IPv4 packet
    if (ntohs(ethHeader->etherType) == 0x0800) {
        processIPv4Packet(frame + sizeof(struct EthernetHeader), frameLength - sizeof(struct
EthernetHeader));
    } else {
        printf("Unsupported EtherType: %04x\n", ntohs(ethHeader->etherType));
    }
}

void processIPv4Packet(const uint8_t* packet, uint16_t packetLength) {
    if (packetLength < sizeof(struct IPv4Header)) {
        printf("Invalid IPv4 packet\n");
        return;
    }

    struct IPv4Header* ipv4Header = (struct IPv4Header*)packet;
    printf("IPv4 Packet - Source IP: %s, Destination IP: %s\n",
inet_ntoa(*(struct in_addr*)&ipv4Header->srcIP), inet_ntoa(*((struct in_addr*)&ipv4Header->destIP));

    // Assuming IPv4 packet contains TCP header
    processTCPHeader(packet + (ipv4Header->versionIHL & 0x0F) * 4, packetLength - (ipv4Header-
>versionIHL & 0x0F) * 4);
}

void processTCPHeader(const uint8_t* tcpHeader, uint16_t tcpHeaderLength) {
    if (tcpHeaderLength < sizeof(struct TCPHeader)) {
        printf("Invalid TCP header\n");
        return;
    }

    struct TCPHeader* tcpHeaderStruct = (struct TCPHeader*)tcpHeader;
    printf("TCP Header - Source Port: %u, Destination Port: %u\n",
ntohs(tcpHeaderStruct->srcPort), ntohs(tcpHeaderStruct->destPort));

    // Assuming TCP header contains application data
    processApplicationData(tcpHeader + (tcpHeaderStruct->dataOffsetReserved >> 4) * 4, tcpHeaderLength -
(tcpHeaderStruct->dataOffsetReserved >> 4) * 4);
}

void processApplicationData(const uint8_t* data, uint16_t dataLength) {
    // Add code to process application-specific data
    printf("Application Data (%u bytes):\n", dataLength);
}

```

```

        for (uint16_t i = 0; i < dataLength; ++i) {
            printf("%c", data[i]);
        }
        printf("\n");
    }
}

```

1.247 Thread Pool

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

#define THREAD_POOL_SIZE 4

// Structure to hold task information
typedef struct {
    void (*task)(void*); // Function pointer for the task
    void* arg;           // Argument for the task
} Task;

// Structure to represent the thread pool
typedef struct {
    pthread_t threads[THREAD_POOL_SIZE]; // Array of threads
    Task taskQueue[THREAD_POOL_SIZE * 2]; // Task queue (adjust size as needed)
    int queueSize;                      // Current size of the task queue
    int front;                          // Front of the queue
    int rear;                           // Rear of the queue
    pthread_mutex_t mutex;              // Mutex for synchronization
    pthread_cond_t condition;          // Condition variable for synchronization
} ThreadPool;

// Function to initialize the thread pool
void initializeThreadPool(ThreadPool* pool) {
    pool->queueSize = 0;
    pool->front = 0;
    pool->rear = 0;
    pthread_mutex_init(&pool->mutex, NULL);
    pthread_cond_init(&pool->condition, NULL);

    // Create threads in the pool
    for (int i = 0; i < THREAD_POOL_SIZE; ++i) {
        pthread_create(&pool->threads[i], NULL, (void* (*)(void*))NULL, NULL);
    }
}

// Function to add a task to the thread pool
void addTask(ThreadPool* pool, void (*task)(void*), void* arg) {
    pthread_mutex_lock(&pool->mutex);

    // Wait if the task queue is full
    while (pool->queueSize == sizeof(pool->taskQueue) / sizeof(pool->taskQueue[0])) {
        pthread_cond_wait(&pool->condition, &pool->mutex);
    }

    // Add the task to the queue
    pool->taskQueue[pool->rear].task = task;
    pool->taskQueue[pool->rear].arg = arg;
    pool->rear = (pool->rear + 1) % (sizeof(pool->taskQueue) / sizeof(pool->taskQueue[0]));
}

```

```

pool->queueSize++;

// Signal a waiting thread that a new task is available
pthread_cond_signal(&pool->condition);

pthread_mutex_unlock(&pool->mutex);
}

// Function executed by worker threads
void* workerThread(void* arg) {
    ThreadPool* pool = (ThreadPool*)arg;

    for (;;) {
        pthread_mutex_lock(&pool->mutex);

        // Wait if the task queue is empty
        while (pool->queueSize == 0) {
            pthread_cond_wait(&pool->condition, &pool->mutex);
        }

        // Retrieve a task from the queue
        void (*task)(void*) = pool->taskQueue[pool->front].task;
        void* taskArg = pool->taskQueue[pool->front].arg;
        pool->front = (pool->front + 1) % (sizeof(pool->taskQueue) / sizeof(pool->taskQueue[0]));
        pool->queueSize--;

        // Signal that there is space in the task queue
        pthread_cond_signal(&pool->condition);

        pthread_mutex_unlock(&pool->mutex);

        // Execute the task
        task(taskArg);
    }

    return NULL;
}

// Function to destroy the thread pool
void destroyThreadPool(ThreadPool* pool) {
    // Cancel all threads in the pool
    for (int i = 0; i < THREAD_POOL_SIZE; ++i) {
        pthread_cancel(pool->threads[i]);
    }

    // Destroy the mutex and condition variable
    pthread_mutex_destroy(&pool->mutex);
    pthread_cond_destroy(&pool->condition);
}

// Sample task to be executed by the thread pool
void sampleTask(void* arg) {
    int taskNumber = *(int*)arg;
    printf("Task %d executed by thread %lu\n", taskNumber, pthread_self());
    free(arg); // Free the memory allocated for the argument
}

int main() {

```

```

ThreadPool pool;
initializeThreadPool(&pool);

// Submit tasks to the thread pool
for (int i = 0; i < 10; ++i) {
    int* taskNumber = malloc(sizeof(int)); // Allocate memory for the task argument
    *taskNumber = i;
    addTask(&pool, sampleTask, taskNumber);
}

// Sleep to allow the tasks to be executed
sleep(5);

// Destroy the thread pool
destroyThreadPool(&pool);

return 0;
}

```

1.248 Memory Pool

```

#include <stdio.h>
#include <stdlib.h>

#define PACKET_SIZE 1500 // Adjust the size according to your needs
#define POOL_SIZE 1000 // Adjust the number of packets in the pool

// Structure representing a packet
typedef struct {
    char data[PACKET_SIZE];
    // Add other packet-related fields as needed
} Packet;

// Structure representing a memory pool
typedef struct {
    Packet* packets[POOL_SIZE];
    int nextIndex; // Index to track the next available packet
} MemoryPool;

// Initialize the memory pool
void initializeMemoryPool(MemoryPool* pool) {
    for (int i = 0; i < POOL_SIZE; ++i) {
        pool->packets[i] = (Packet*)malloc(sizeof(Packet));
        // Initialize other packet-related fields as needed
    }
    pool->nextIndex = 0;
}

// Get a packet from the memory pool
Packet* allocatePacket(MemoryPool* pool) {
    if (pool->nextIndex < POOL_SIZE) {
        return pool->packets[pool->nextIndex++];
    } else {
        // Handle the case when the pool is exhausted (you may want to expand the pool or return NULL)
        printf("Memory pool exhausted!\n");
        return NULL;
    }
}

```

```

// Release a packet back to the memory pool
void deallocatePacket(MemoryPool* pool, Packet* packet) {
    // You may want to perform additional cleanup or re-initialization of the packet
    pool->nextIndex--;
}

// Cleanup the memory pool
void cleanupMemoryPool(MemoryPool* pool) {
    for (int i = 0; i < POOL_SIZE; ++i) {
        free(pool->packets[i]);
    }
    pool->nextIndex = 0;
}

// Example of using the memory pool
int main() {
    MemoryPool packetPool;
    initializeMemoryPool(&packetPool);

    // Allocate and use packets
    Packet* packet1 = allocatePacket(&packetPool);
    // Process packet1...

    Packet* packet2 = allocatePacket(&packetPool);
    // Process packet2...

    // Release packets back to the pool when done
    deallocatePacket(&packetPool, packet1);
    deallocatePacket(&packetPool, packet2);

    // Cleanup the memory pool when the application exits
    cleanupMemoryPool(&packetPool);

    return 0;
}

```

1.249 DPDK

Run to Completion vs Pipeline

Dpdk setup -> compile drivers -> igb pmd ->bind driver to dpdk ->huge pages ->application run
Rte_eal_init (app to use dpdk framework)

Rte_ether_Dev_configure – rx/tx queues , RSS

Rte_Eth_tx_queue_setup – ring descriptors

Rte_ether_rx_queue_setup

Rte_ether_dev_Start – RX/TX packets

Rte_ether_rx_burst/tx_burst (port id.q no, array of structure to hold packets, number)

DPDK (Data Plane Development Kit) is a set of libraries and drivers for fast packet processing in user space.
It is designed to optimize packet processing workloads and achieve high-performance data plane applications. DPDK allows developers to build efficient and scalable network applications by bypassing the traditional kernel networking stack and accessing network interfaces directly from user space.

Key features and components of DPDK include:

- Processor affinity (separate cores)
- Huge pages (no swap, TLB)
- UIO (no copying from kernel)
- Polling (no interrupts overhead)
- Lockless synchronization (avoid waiting)
- Batch packets handling
- SSE, NUMA awareness

Poll Mode Drivers (PMDs):

DPDK provides a set of Poll Mode Drivers (PMDs) for various network interface controllers (NICs). PMDs allow applications to directly interact with network interfaces, eliminating the need for kernel involvement in the data plane.

Memory Management:

DPDK includes a memory management subsystem that provides a high-performance memory allocation and deallocation framework.

It uses a custom memory allocator called the DPDK Memory Manager, which helps reduce memory fragmentation and overhead.

Poll Mode Operation:

DPDK applications operate in a poll mode, continuously polling the NICs and processing packets without relying on interrupts.

Poll mode operation reduces the overhead of interrupt processing and context switching, resulting in lower latency.

Packet Buffer Management:

DPDK includes a memory pool manager to efficiently manage packet buffers.

The memory pool manager allocates fixed-sized memory blocks, or mbufs, to store packet data. This improves cache locality and reduces memory fragmentation.

RTE (Run-Time Environment):

DPDK provides a set of APIs and abstractions collectively known as the RTE (Run-Time Environment). RTE includes functions for memory management, I/O operations, and other utilities that facilitate the development of high-performance applications.

Multi-Queue Support:

DPDK supports multi-queue operation, allowing applications to distribute packet processing across multiple CPU cores.

This helps achieve parallelism and scalability in packet processing workloads.

Packet Classification and Filtering:

DPDK provides mechanisms for packet classification, filtering, and flow steering.

Applications can define rules for classifying and directing packets based on criteria such as MAC addresses, IP addresses, and ports.

Event Mode:

DPDK includes an Event Mode framework that allows applications to handle events asynchronously. The Event Mode enables event-driven architectures for handling various tasks, including packet processing. Crypto and Compression Operations:

DPDK includes libraries for hardware-accelerated cryptographic and compression operations. Applications can leverage these libraries for secure and efficient processing of encrypted and compressed data.

Unified Packet Framework:

DPDK provides a unified packet framework that abstracts packet data structures and operations, making it easier for developers to work with packets in a consistent manner.

Dynamic Device Configuration:

DPDK allows applications to dynamically configure and manage network devices, including adding or removing devices during runtime.

DPDK EAL (Environment Abstraction Layer):

The Environment Abstraction Layer provides an abstraction over system-specific details and allows DPDK applications to run on various operating systems.

DPDK is commonly used in the development of network functions, such as routers, firewalls, load balancers, and other data plane applications requiring low-latency, high-throughput packet processing. It is widely adopted in the telecommunications and networking industry for building efficient and scalable network infrastructure.

```
#include <stdio.h>
#include <stdint.h>
#include <inttypes.h>
#include <rte_eal.h>
#include <rte_ethdev.h>
#include <rte_lcore.h>
#include <rte_mbuf.h>

#define RX_RING_SIZE 1024
#define TX_RING_SIZE 1024
#define NUM_MBUFS 8191
#define MBUF_CACHE_SIZE 250
#define BURST_SIZE 32

static const struct rte_eth_conf port_conf_default = {
    .rxmode = {
        .max_rx_pkt_len = RTE_ETHER_MAX_LEN,
    },
};

static struct rte_eth_dev_tx_buffer *tx_buffer[RTE_MAX_ETHPORTS];
static uint16_t nb_ports;

static int init_port(uint16_t port, struct rte_mempool *mbuf_pool) {
    struct rte_eth_conf port_conf = port_conf_default;
    const uint16_t rx_rings = 1, tx_rings = 1;
    int retval;
    uint16_t q;

    if (port >= rte_eth_dev_count_avail()) {
        printf("Error: Port %" PRu16 " not available\n", port);
        return -1;
    }
}
```

```

retval = rte_ether_dev_configure(port, rx_rings, tx_rings, &port_conf);
if (retval != 0) {
    printf("Error during port configuration: %s\n", rte_strerror(retval));
    return retval;
}

retval = rte_ether_dev_adjust_nb_rx_tx_desc(port, &RX_RING_SIZE, &TX_RING_SIZE);
if (retval != 0) {
    printf("Error during adjusting number of descriptors: %s\n", rte_strerror(retval));
    return retval;
}

for (q = 0; q < rx_rings; q++) {
    retval = rte_ether_rx_queue_setup(port, q, RX_RING_SIZE,
                                    rte_ether_dev_socket_id(port), NULL, mbuf_pool);
    if (retval < 0) {
        printf("Error during RX queue setup: %s\n", rte_strerror(-retval));
        return retval;
    }
}

for (q = 0; q < tx_rings; q++) {
    retval = rte_ether_tx_queue_setup(port, q, TX_RING_SIZE,
                                    rte_ether_dev_socket_id(port), NULL);
    if (retval < 0) {
        printf("Error during TX queue setup: %s\n", rte_strerror(-retval));
        return retval;
    }
    tx_buffer[port] = rte_zmalloc_socket("tx_buffer",
                                         RTE_ETH_TX_BUFFER_SIZE(BURST_SIZE),
                                         0, rte_ether_dev_socket_id(port));
    if (tx_buffer[port] == NULL) {
        printf("Error: cannot allocate buffer for tx on port %u\n", port);
        return -1;
    }
    rte_ether_tx_buffer_init(tx_buffer[port], BURST_SIZE);
}

retval = rte_ether_dev_start(port);
if (retval < 0) {
    printf("Error during port start: %s\n", rte_strerror(-retval));
    return retval;
}

rte_ether_promiscuous_enable(port);

return 0;
}

static void dpdk_packet_receive(uint16_t port) {
    struct rte_mbuf *bufs[BURST_SIZE];
    uint16_t nb_rx;

    printf("Core %u receiving packets. [Ctrl+C to quit]\n", rte_lcore_id());

    while (1) {
        nb_rx = rte_ether_rx_burst(port, 0, bufs, BURST_SIZE);
        if (nb_rx > 0) {

```

```

        // Process received packets (can be done on a different core)
        // For simplicity, just free the received packets
        rte_pktmbuf_free_bulk(bufs, nb_rx);
    }
}
}

static void dpdk_packet_process(uint16_t port) {
    struct rte_mbuf *bufs[BURST_SIZE];
    uint16_t nb_rx, nb_tx;
    uint16_t dst_port = (port + 1) % nb_ports;

    printf("Core %u processing packets. [Ctrl+C to quit]\n", rte_lcore_id());

    while (1) {
        nb_rx = rte_eth_rx_burst(port, 0, bufs, BURST_SIZE);
        if (nb_rx > 0) {
            // Process received packets
            // For simplicity, just transmit the received packets to another port
            nb_tx = rte_eth_tx_buffer(dst_port, 0, tx_buffer[dst_port], bufs, nb_rx);
            if (nb_tx < nb_rx) {
                rte_pktmbuf_free_bulk(bufs + nb_tx, nb_rx - nb_tx);
            }
        }
    }
}

int main(int argc, char *argv[]) {
    struct rte_mempool *mbuf_pool;
    uint16_t portid;
    unsigned lcore_id;

    if (rte_eal_init(argc, argv) < 0) {
        rte_panic("Cannot init EAL\n");
        return -1;
    }

    argc -= rte_eal_init(argc, argv);
    argv += rte_eal_init(argc, argv);

    nb_ports = rte_eth_dev_count_avail();
    if (nb_ports == 0) {
        rte_panic("No Ethernet ports found\n");
        return -1;
    }

    mbuf_pool = rte_pktmbuf_pool_create("MBUF_POOL", NUM_MBUFS * nb_ports,
                                        MBUF_CACHE_SIZE, 0, RTE_MBUF_DEFAULT_BUF_SIZE,
                                        rte_socket_id());
    if (mbuf_pool == NULL) {
        rte_panic("Cannot create mbuf pool\n");
        return -1;
    }

    RTE_ETH_FOREACH_DEV(portid) {
        if (init_port(portid, mbuf_pool) != 0)
            return -1;
    }
}

```

```

RTE_LCORE_FOREACH_SLAVE(lcore_id) {
    rte_eal_remote_launch((lcore_function_t *)dpdk_packet_process, NULL, lcore_id);
}

// Run packet receiving on the master core
dpdk_packet_receive(0);

rte_eal_mp_wait_lcore();

return 0;
}

```

1.250 Attack Packet Detection With PCAP

```

#include <stdio.h>
#include <pcap.h>
#include <string.h>

#define MAX_PACKET_SIZE 1500

void packet_handler(unsigned char* user, const struct pcap_pkthdr* pkthdr, const unsigned char* packet) {
    char* attack_string = "attack";
    const int attack_string_length = strlen(attack_string);

    // Assuming Ethernet frames
    int ethernet_header_length = 14;

    // Assuming IPv4 packets
    int ip_header_length = (packet[ethernet_header_length] & 0x0F) * 4;

    // Assuming TCP packets
    int tcp_header_length = ((packet[ethernet_header_length + ip_header_length + 12] & 0xF0) >> 4) * 4;

    // Payload offset
    int payload_offset = ethernet_header_length + ip_header_length + tcp_header_length;

    // Extract payload
    const unsigned char* payload = packet + payload_offset;

    // Check if the payload contains the attack string
    if (strstr((char*)payload, attack_string) != NULL) {
        printf("Attack detected!\n");
    }
}

int main() {
    char errbuf[PCAP_ERRBUF_SIZE];
    pcap_t* handle;

    // Open the network interface for packet capture
    handle = pcap_open_live("your_network_interface", MAX_PACKET_SIZE, 1, 1000, errbuf);
    if (handle == NULL) {
        fprintf(stderr, "Couldn't open device: %s\n", errbuf);
        return 2;
    }

    // Set a packet filter to capture only TCP traffic
}

```

```

struct bpf_program fp;
char filter_exp[] = "tcp";
if (pcap_compile(handle, &fp, filter_exp, 0, PCAP_NETMASK_UNKNOWN) == -1) {
    fprintf(stderr, "Couldn't parse filter %s: %s\n", filter_exp, pcap_geterr(handle));
    return 2;
}
if (pcap_setfilter(handle, &fp) == -1) {
    fprintf(stderr, "Couldn't install filter %s: %s\n", filter_exp, pcap_geterr(handle));
    return 2;
}

// Start capturing packets
pcap_loop(handle, 0, packet_handler, NULL);

// Close the handle
pcap_close(handle);

return 0;
}

```

1.251 Attack Packet Context Generation - HTTP

```

#include <stdio.h>
#include <pcap.h>
#include <stdlib.h>
#include <string.h>

#define MAX_PACKET_SIZE 1500

void process_http_packet(const unsigned char* payload, int payload_size) {
    // Assuming HTTP method is present at the beginning of the payload
    // Detecting the end of the HTTP method by finding the first space
    int i = 0;
    while (i < payload_size && payload[i] != ' ') {
        i++;
    }

    if (i < payload_size) {
        // Extracting the HTTP method
        char http_method[i + 1];
        strncpy(http_method, (char*)payload, i);
        http_method[i] = '\0';

        printf("HTTP Method: %s\n", http_method);
    }
}

void packet_handler(unsigned char* user, const struct pcap_pkthdr* pkthdr, const unsigned char* packet) {
    // Assuming Ethernet frames
    int ethernet_header_length = 14;

    // Assuming IPv4 packets
    int ip_header_length = (packet[ethernet_header_length] & 0x0F) * 4;

    // Assuming TCP packets
    int tcp_header_length = ((packet[ethernet_header_length + ip_header_length + 12] & 0xF0) >> 4) * 4;

    // Payload offset
    int payload_offset = ethernet_header_length + ip_header_length + tcp_header_length;
}

```

```

// Extract payload
const unsigned char* payload = packet + payload_offset;

// Assuming HTTP traffic starts with "HTTP/"
const char http_identifier[] = "HTTP";
const int http_identifier_length = strlen(http_identifier);

// Check if the payload contains "HTTP/"
if (strncmp((char*)payload, http_identifier, http_identifier_length) == 0) {
    // Process the HTTP packet
    process_http_packet(payload, pkthdr->caplen - payload_offset);
}
}

int main() {
    char errbuf[PCAP_ERRBUF_SIZE];
    pcap_t* handle;

    // Open the network interface for packet capture
    handle = pcap_open_live("your_network_interface", MAX_PACKET_SIZE, 1, 1000, errbuf);
    if (handle == NULL) {
        fprintf(stderr, "Couldn't open device: %s\n", errbuf);
        return 2;
    }

    // Set a packet filter to capture only TCP traffic on port 80 (HTTP)
    struct bpf_program fp;
    char filter_exp[] = "tcp port 80";
    if (pcap_compile(handle, &fp, filter_exp, 0, PCAP_NETMASK_UNKNOWN) == -1) {
        fprintf(stderr, "Couldn't parse filter %s: %s\n", filter_exp, pcap_geterr(handle));
        return 2;
    }
    if (pcap_setfilter(handle, &fp) == -1) {
        fprintf(stderr, "Couldn't install filter %s: %s\n", filter_exp, pcap_geterr(handle));
        return 2;
    }

    // Start capturing packets
    pcap_loop(handle, 0, packet_handler, NULL);

    // Close the handle
    pcap_close(handle);

    return 0;
}

```

1.252 Breadth First Search(BFS) Of Binary Tree

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a tree node
struct TreeNode {
    int data;
    struct TreeNode *left;
    struct TreeNode *right;
}

```

```

};

// Function to create a new tree node
struct TreeNode* createNode(int value) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->data = value;
    newNode->left = NULL;
    newNode->right = NULL;
    return newNode;
}

// Function to perform Breadth-First Search (BFS) on a binary tree
void breadthFirstSearch(struct TreeNode* root) {
    if (root == NULL) {
        return;
    }

    // Use a queue for BFS
    struct TreeNode* queue[100];
    int front = 0, rear = 0;

    // Enqueue the root
    queue[rear++] = root;

    while (front < rear) {
        // Dequeue a node and print its data
        struct TreeNode* current = queue[front++];
        printf("%d ", current->data);

        // Enqueue left child
        if (current->left != NULL) {
            queue[rear++] = current->left;
        }

        // Enqueue right child
        if (current->right != NULL) {
            queue[rear++] = current->right;
        }
    }
}

int main() {
    // Constructing a sample binary tree
    struct TreeNode* root = createNode(1);
    root->left = createNode(2);
    root->right = createNode(3);
    root->left->left = createNode(4);
    root->left->right = createNode(5);
    root->right->left = createNode(6);
    root->right->right = createNode(7);

    printf("Breadth-First Search (BFS) of the tree: ");
    breadthFirstSearch(root);

    return 0;
}

```

1.253 Depth First Search(DFS) Of Binary Tree

```
#include <stdio.h>
#include <stdlib.h>

// Structure for a tree node
struct TreeNode {
    int data;
    struct TreeNode *left;
    struct TreeNode *right;
};

// Function to create a new tree node
struct TreeNode* createNode(int value) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->data = value;
    newNode->left = NULL;
    newNode->right = NULL;
    return newNode;
}

// Pre-order DFS traversal
void preOrderDFS(struct TreeNode* root) {
    if (root == NULL) {
        return;
    }

    // Print the data of the current node
    printf("%d ", root->data);

    // Recur on the left subtree
    preOrderDFS(root->left);

    // Recur on the right subtree
    preOrderDFS(root->right);
}

// In-order DFS traversal
void inOrderDFS(struct TreeNode* root) {
    if (root == NULL) {
        return;
    }

    // Recur on the left subtree
    inOrderDFS(root->left);

    // Print the data of the current node
    printf("%d ", root->data);

    // Recur on the right subtree
    inOrderDFS(root->right);
}

// Post-order DFS traversal
void postOrderDFS(struct TreeNode* root) {
    if (root == NULL) {
        return;
    }
}
```

```

// Recur on the left subtree
postOrderDFS(root->left);

// Recur on the right subtree
postOrderDFS(root->right);

// Print the data of the current node
printf("%d ", root->data);
}

int main() {
    // Constructing a sample binary tree
    struct TreeNode* root = createNode(1);
    root->left = createNode(2);
    root->right = createNode(3);
    root->left->left = createNode(4);
    root->left->right = createNode(5);
    root->right->left = createNode(6);
    root->right->right = createNode(7);

    printf("Pre-order DFS of the tree: ");
    preOrderDFS(root);
    printf("\n");

    printf("In-order DFS of the tree: ");
    inOrderDFS(root);
    printf("\n");

    printf("Post-order DFS of the tree: ");
    postOrderDFS(root);
    printf("\n");
}

return 0;
}

```

1.254 Breadth First Search(BFS) Of Graph

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a node in the adjacency list
struct Node {
    int vertex;
    struct Node* next;
};

// Structure for the adjacency list
struct AdjList {
    struct Node* head;
};

// Structure for the graph
struct Graph {
    int numVertices;
    struct AdjList* array;
};

```

```

// Function to create a new node
struct Node* createNode(int vertex) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->vertex = vertex;
    newNode->next = NULL;
    return newNode;
}

// Function to create a graph with a given number of vertices
struct Graph* createGraph(int numVertices) {
    struct Graph* graph = (struct Graph*)malloc(sizeof(struct Graph));
    graph->numVertices = numVertices;

    // Create an array of adjacency lists
    graph->array = (struct AdjList*)malloc(numVertices * sizeof(struct AdjList));

    // Initialize each adjacency list as empty
    for (int i = 0; i < numVertices; ++i) {
        graph->array[i].head = NULL;
    }

    return graph;
}

// Function to add an edge to an undirected graph
void addEdge(struct Graph* graph, int src, int dest) {
    // Add an edge from src to dest
    struct Node* newNode = createNode(dest);
    newNode->next = graph->array[src].head;
    graph->array[src].head = newNode;

    // Since the graph is undirected, add an edge from dest to src as well
    newNode = createNode(src);
    newNode->next = graph->array[dest].head;
    graph->array[dest].head = newNode;
}

// Function to perform Breadth-First Search (BFS) on the graph
void BFS(struct Graph* graph, int startVertex) {
    // Create a queue for BFS
    int queue[100];
    int front = 0, rear = 0;
    int visited[100] = {0}; // Initialize visited array

    // Enqueue the start vertex and mark it as visited
    queue[rear++] = startVertex;
    visited[startVertex] = 1;

    while (front < rear) {
        // Dequeue a vertex and print it
        int currentVertex = queue[front++];
        printf("%d ", currentVertex);

        // Traverse the adjacency list of the dequeued vertex
        struct Node* temp = graph->array[currentVertex].head;
        while (temp != NULL) {
            int adjacentVertex = temp->vertex;

```

```

        // If the adjacent vertex is not visited, enqueue it and mark it as visited
        if (!visited[adjacentVertex]) {
            queue[rear++] = adjacentVertex;
            visited[adjacentVertex] = 1;
        }

        temp = temp->next;
    }
}

int main() {
    // Create a sample graph
    struct Graph* graph = createGraph(6);
    addEdge(graph, 0, 1);
    addEdge(graph, 0, 2);
    addEdge(graph, 1, 3);
    addEdge(graph, 1, 4);
    addEdge(graph, 2, 4);
    addEdge(graph, 3, 5);
    addEdge(graph, 4, 5);

    printf("Breadth-First Search (BFS) starting from vertex 0: ");
    BFS(graph, 0);

    return 0;
}

```

1.255 Depth First Search(DFS) Of Graph

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a node in the adjacency list
struct Node {
    int vertex;
    struct Node* next;
};

// Structure for the adjacency list
struct AdjList {
    struct Node* head;
};

// Structure for the graph
struct Graph {
    int numVertices;
    struct AdjList* array;
};

// Function to create a new node
struct Node* createNode(int vertex) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->vertex = vertex;
    newNode->next = NULL;
    return newNode;
}

```

```

// Function to create a graph with a given number of vertices
struct Graph* createGraph(int numVertices) {
    struct Graph* graph = (struct Graph*)malloc(sizeof(struct Graph));
    graph->numVertices = numVertices;

    // Create an array of adjacency lists
    graph->array = (struct AdjList*)malloc(numVertices * sizeof(struct AdjList));

    // Initialize each adjacency list as empty
    for (int i = 0; i < numVertices; ++i) {
        graph->array[i].head = NULL;
    }

    return graph;
}

// Function to add an edge to an undirected graph
void addEdge(struct Graph* graph, int src, int dest) {
    // Add an edge from src to dest
    struct Node* newNode = createNode(dest);
    newNode->next = graph->array[src].head;
    graph->array[src].head = newNode;

    // Since the graph is undirected, add an edge from dest to src as well
    newNode = createNode(src);
    newNode->next = graph->array[dest].head;
    graph->array[dest].head = newNode;
}

// Recursive function for DFS traversal
void DFSUtil(struct Graph* graph, int vertex, int visited[]) {
    // Mark the current vertex as visited and print it
    visited[vertex] = 1;
    printf("%d ", vertex);

    // Recur for all the vertices adjacent to this vertex
    struct Node* temp = graph->array[vertex].head;
    while (temp != NULL) {
        int adjacentVertex = temp->vertex;
        if (!visited[adjacentVertex]) {
            DFSUtil(graph, adjacentVertex, visited);
        }
        temp = temp->next;
    }
}

// Function to perform Depth-First Search (DFS) on the graph
void DFS(struct Graph* graph, int startVertex) {
    // Create an array to track visited vertices
    int visited[100] = {0}; // Assuming a maximum of 100 vertices

    // Call the recursive utility function starting from the specified vertex
    DFSUtil(graph, startVertex, visited);
}

int main() {
    // Create a sample graph
    struct Graph* graph = createGraph(6);

```

```

    addEdge(graph, 0, 1);
    addEdge(graph, 0, 2);
    addEdge(graph, 1, 3);
    addEdge(graph, 1, 4);
    addEdge(graph, 2, 4);
    addEdge(graph, 3, 5);
    addEdge(graph, 4, 5);

    printf("Depth-First Search (DFS) starting from vertex 0: ");
    DFS(graph, 0);

    return 0;
}

```

1.256 Shortest Path In Graph

```

#include <stdio.h>
#include <stdlib.h>

#define MAX_VERTICES 100

// Structure for a node in the adjacency list
struct Node {
    int vertex;
    struct Node* next;
};

// Structure for the adjacency list
struct AdjList {
    struct Node* head;
};

// Structure for the graph
struct Graph {
    int numVertices;
    struct AdjList* array;
};

// Function to create a new node
struct Node* createNode(int vertex) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->vertex = vertex;
    newNode->next = NULL;
    return newNode;
}

// Function to create a graph with a given number of vertices
struct Graph* createGraph(int numVertices) {
    struct Graph* graph = (struct Graph*)malloc(sizeof(struct Graph));
    graph->numVertices = numVertices;

    // Create an array of adjacency lists
    graph->array = (struct AdjList*)malloc(numVertices * sizeof(struct AdjList));

    // Initialize each adjacency list as empty
    for (int i = 0; i < numVertices; ++i) {
        graph->array[i].head = NULL;
    }
}

```

```

        return graph;
    }

// Function to add an edge to an undirected graph
void addEdge(struct Graph* graph, int src, int dest) {
    // Add an edge from src to dest
    struct Node* newNode = createNode(dest);
    newNode->next = graph->array[src].head;
    graph->array[src].head = newNode;

    // Since the graph is undirected, add an edge from dest to src as well
    newNode = createNode(src);
    newNode->next = graph->array[dest].head;
    graph->array[dest].head = newNode;
}

// Function to find the shortest path using BFS
void shortestPath(struct Graph* graph, int startVertex, int endVertex) {
    int queue[MAX_VERTICES];
    int front = 0, rear = 0;
    int visited[MAX_VERTICES] = {0};
    int parent[MAX_VERTICES];

    // Initialize parent array to -1
    for (int i = 0; i < MAX_VERTICES; ++i) {
        parent[i] = -1;
    }

    // Enqueue the start vertex and mark it as visited
    queue[rear++] = startVertex;
    visited[startVertex] = 1;

    while (front < rear) {
        int currentVertex = queue[front++];

        struct Node* temp = graph->array[currentVertex].head;
        while (temp != NULL) {
            int adjacentVertex = temp->vertex;
            if (!visited[adjacentVertex]) {
                // Enqueue adjacent vertex, mark it as visited, and update parent
                queue[rear++] = adjacentVertex;
                visited[adjacentVertex] = 1;
                parent[adjacentVertex] = currentVertex;
            }
            temp = temp->next;
        }
    }

    // Print the shortest path from startVertex to endVertex
    printf("Shortest path from %d to %d: ", startVertex, endVertex);
    int currentVertex = endVertex;
    while (currentVertex != -1) {
        printf("%d ", currentVertex);
        currentVertex = parent[currentVertex];
    }
    printf("\n");
}

```

```

int main() {
    // Create a sample graph
    struct Graph* graph = createGraph(6);
    addEdge(graph, 0, 1);
    addEdge(graph, 0, 2);
    addEdge(graph, 1, 3);
    addEdge(graph, 1, 4);
    addEdge(graph, 2, 4);
    addEdge(graph, 3, 5);
    addEdge(graph, 4, 5);

    // Find the shortest path from vertex 0 to vertex 5
    shortestPath(graph, 0, 5);

    return 0;
}

```

1.257 Sliding Window Maximum

```

int max(int a, int b) {
    return (a > b) ? a : b;
}

int* maxSlidingWindow(int* nums, int numsSize, int k, int* returnSize) {
    if (nums == NULL || k <= 0) {
        *returnSize = 0;
        return NULL;
    }

    int n = numsSize;
    int* leftMax = (int*)malloc(sizeof(int) * n);
    int* rightMax = (int*)malloc(sizeof(int) * n);

    leftMax[0] = nums[0];
    rightMax[n - 1] = nums[n - 1];

    for (int i = 1; i < n; i++) {
        // Start over every window and update it with maximum elements
        if ((i + 1) % k == 0) {
            leftMax[i] = nums[i];
            printf("\nReset leftmax[%d] = %d", i, leftMax[i]);
        } else {
            leftMax[i] = max(nums[i], leftMax[i - 1]);
            printf("\nleftmax[%d] = %d", i, leftMax[i]);
        }
    }

    int j = n - i - 1;
    printf("\nj = %d", j);
    if ((j + 1) % k == 0) {
        rightMax[j] = nums[j];
        printf("\nReset rightmax[%d] = %d", j, rightMax[j]);
    }
}

```

```

        } else {
            rightMax[j] = max(nums[j], rightMax[j + 1]);
            printf("\nrightmax[%d] = %d", j, rightMax[j]);
        }
    }

int* ans = (int*)malloc(sizeof(int) * (n - k + 1));
*returnSize = n - k + 1;

for (int i = 0; i < *returnSize; i++) {
    // Since leftMax has the maximum to the rightmost of the window,
    // and rightMax has the maximum element of the window to the leftMax
    // as per their traversals above.
    printf("\nInitial leftmax = %d rightmax = %d", leftMax[i], rightMax[i]);
    ans[i] = max(leftMax[i + k - 1], rightMax[i]);
    printf("\nleftmax = %d rightmax = %d", leftMax[i + k - 1], rightMax[i]);
}

free(leftMax);
free(rightMax);

return ans;
}

```

1.258 Throughput Load

```

#define NUM_THREADS 10

// Define the workload function
void* processRequest(void* threadId) {
    long tid = (long)threadId;
    // Simulate some processing time
    usleep(100000); // 100ms

    printf("Thread %ld: Request processed\n", tid);
    pthread_exit(NULL);
}

int main() {
    pthread_t threads[NUM_THREADS];
    int rc;
    long t;

    printf("Simulation of Throughput Load\n");

    // Create threads to simulate concurrent connections
    for (t = 0; t < NUM_THREADS; t++) {
        printf("Creating thread %ld\n", t);
        rc = pthread_create(&threads[t], NULL, processRequest, (void*)t);
        if (rc) {
            printf("Error creating thread %ld; return code from pthread_create() is %d\n", t, rc);
            exit(-1);
        }
    }
}

```

```

    }

    // Wait for all threads to finish
    for (t = 0; t < NUM_THREADS; t++) {
        pthread_join(threads[t], NULL);
    }

    printf("All threads completed.\n");

    return 0;
}

```

1.259 Middle Element Of Linked List

```

#include <stdio.h>
#include <stdlib.h>

// Definition of a simple singly linked list node
struct Node {
    int data;
    struct Node* next;
};

// Function to insert a new node at the end of the linked list
void insertNode(struct Node** head, int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = NULL;

    if (*head == NULL) {
        *head = newNode;
        return;
    }

    struct Node* current = *head;
    while (current->next != NULL) {
        current = current->next;
    }

    current->next = newNode;
}

// Function to find the middle element of the linked list
struct Node* findMiddle(struct Node* head) {
    if (head == NULL || head->next == NULL) {
        return head; // Empty list or single node
    }

    struct Node* slow = head;
    struct Node* fast = head;

    while (fast != NULL && fast->next != NULL) {
        slow = slow->next;
        fast = fast->next->next;
    }

    return slow;
}

```

```

// Function to print the elements of the linked list
void printList(struct Node* head) {
    while (head != NULL) {
        printf("%d -> ", head->data);
        head = head->next;
    }
    printf("NULL\n");
}

int main() {
    // Creating a sample linked list
    struct Node* head = NULL;
    insertNode(&head, 1);
    insertNode(&head, 2);
    insertNode(&head, 3);
    insertNode(&head, 4);
    insertNode(&head, 5);

    // Print the original linked list
    printf("Original Linked List: ");
    printList(head);

    // Find the middle element
    struct Node* middle = findMiddle(head);

    // Print the middle element
    printf("Middle Element: %d\n", middle->data);

    return 0;
}

```

1.260 Build Process Tree

```

#include <stdio.h>
#include <stdlib.h>

struct ProcessNode {
    char process_name[20];
    int pid;
    int parent_pid;
    struct ProcessNode* children[100];
    int num_children;
};

struct ProcessNode* createProcessNode(const char* process_name, int pid, int parent_pid) {
    struct ProcessNode* newNode = (struct ProcessNode*)malloc(sizeof(struct ProcessNode));
    snprintf(newNode->process_name, sizeof(newNode->process_name), "%s", process_name);
    newNode->pid = pid;
    newNode->parent_pid = parent_pid;
    newNode->num_children = 0;
    return newNode;
}

int findIndexByPid(struct ProcessNode* process_dict[], int num_processes, int pid) {
    for (int i = 0; i < num_processes; i++) {
        if (process_dict[i]->pid == pid) {
            return i;
        }
    }
}

```

```

        }
    }
    return -1; // Process not found
}

void buildProcessTree(struct ProcessNode* process_dict[], int num_processes, struct ProcessNode** root) {
    *root = NULL;

    int pidToIndex[num_processes];
    for (int i = 0; i < num_processes; i++) {
        pidToIndex[process_dict[i]->pid] = i;
    }

    for (int i = 0; i < num_processes; i++) {
        if (process_dict[i]->parent_pid == -1) {
            *root = process_dict[i];
        } else {
            int parentIndex = findIndexByPid(process_dict, num_processes, process_dict[i]->parent_pid);
            if (parentIndex != -1) {
                process_dict[parentIndex]->children[process_dict[parentIndex]->num_children++] = process_dict[i];
            }
        }
    }
}

void printProcessTree(struct ProcessNode* root, int depth) {
    if (root == NULL) {
        return;
    }

    for (int i = 0; i < depth; i++) {
        printf("----");
    }

    printf("%s (PID: %d)\n", root->process_name, root->pid);

    for (int i = 0; i < root->num_children; i++) {
        printProcessTree(root->children[i], depth + 1);
    }
}

int main() {
    struct ProcessNode* processes[9];

    processes[0] = createProcessNode("a.exe", 420, 428);
    processes[1] = createProcessNode("c.exe", 428, -1);
    processes[2] = createProcessNode("d.exe", 551, 420);
    processes[3] = createProcessNode("e.exe", 552, 428);
    processes[4] = createProcessNode("f.exe", 553, -1);
    processes[5] = createProcessNode("g.exe", 4, 553);
    processes[6] = createProcessNode("b.exe", 7, 4);
    processes[7] = createProcessNode("h.exe", 11, 7);
    processes[8] = createProcessNode("j.exe", 666, 428);

    struct ProcessNode* root;

    buildProcessTree(processes, 9, &root);
    printProcessTree(root, 0);
}

```

```

    return 0;
}Given the array, build a tree as follows:
[
{"process_name":"a.exe", "pid":420, "parent_pid":428},
 {"process_name":"c.exe", "pid":428, "parent_pid":None},
 {"process_name":"d.exe", "pid":551, "parent_pid":420},
 {"process_name":"e.exe", "pid":552, "parent_pid":428},
 {"process_name":"f.exe", "pid":553, "parent_pid":None},
 {"process_name":"g.exe", "pid": 4, "parent_pid":553},
 {"process_name":"b.exe", "pid": 7, "parent_pid": 4},
 {"process_name":"h.exe", "pid": 11, "parent_pid": 7},
 {"process_name":"j.exe", "pid":666, "parent_pid":428}
]

```

The program should output the following:

```

c.exe
---- a.exe
----- d.exe
---- e.exe
---- j.exe
f.exe
---- g.exe
----- b.exe
----- h.exe

```

1.261 Construct Tree From Data

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a tree node
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Function to create a new tree node
struct TreeNode* createNode(int value) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->data = value;
    newNode->left = NULL;
    newNode->right = NULL;
    return newNode;
}

// Function to construct a tree from an array of values
struct TreeNode* constructTree(int values[], int index, int n) {
    if (index < n) {
        struct TreeNode* root = createNode(values[index]);
        root->left = constructTree(values, 2 * index + 1, n); // Left child
        root->right = constructTree(values, 2 * index + 2, n); // Right child
        return root;
    } else {
        return NULL;
    }
}

```

```

        }
    }

// Function to print the tree using inorder traversal
void printTree(struct TreeNode* root) {
    if (root != NULL) {
        printTree(root->left);
        printf("%d ", root->data);
        printTree(root->right);
    }
}

int main() {
    // Example array of values to construct a binary tree
    int values[] = {1, 2, 3, 4, 5, 6, 7};

    // Calculate the number of elements in the array
    int n = sizeof(values) / sizeof(values[0]);

    // Construct the binary tree
    struct TreeNode* root = constructTree(values, 0, n);

    // Print the tree using inorder traversal
    printf("Inorder Traversal of the Tree: ");
    printTree(root);

    return 0;
}

```

1.262 Peak Element

```

#include <stdio.h>

// Function to find a peak element using binary search
int findPeakElement(int arr[], int low, int high, int n) {
    while (low <= high) {
        int mid = low + (high - low) / 2;

        // Check if the mid element is a peak
        if ((mid == 0 || arr[mid] >= arr[mid - 1]) && (mid == n - 1 || arr[mid] >= arr[mid + 1])) {
            return mid;
        }

        // If the element to the right of mid is greater, then there is a peak element on the right
        if (mid < n - 1 && arr[mid] < arr[mid + 1]) {
            low = mid + 1;
        } else {
            // If the element to the left of mid is greater, then there is a peak element on the left
            high = mid - 1;
        }
    }

    return -1; // No peak element found
}

int main() {
    int arr[] = {1, 3, 20, 4, 1, 0};
    int n = sizeof(arr) / sizeof(arr[0]);
}

```

```

int peakIndex = findPeakElement(arr, 0, n - 1, n);

if (peakIndex != -1) {
    printf("Peak element is %d at index %d\n", arr[peakIndex], peakIndex);
} else {
    printf("No peak element found\n");
}

return 0;
}

```

1.263 T2 subtree of T1

```

#include <stdio.h>
#include <stdbool.h>
#include <stdlib.h>

// Definition for a binary tree node
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Function to check if two trees are identical
bool areIdentical(struct TreeNode* root1, struct TreeNode* root2) {
    if (root1 == NULL && root2 == NULL) {
        return true;
    }

    if (root1 == NULL || root2 == NULL) {
        return false;
    }

    return (root1->data == root2->data &&
            areIdentical(root1->left, root2->left) &&
            areIdentical(root1->right, root2->right));
}

// Function to check if Tree T2 is a subtree of Tree T1
bool isSubtree(struct TreeNode* T1, struct TreeNode* T2) {
    if (T2 == NULL) {
        return true; // An empty tree is always a subtree
    }

    if (T1 == NULL) {
        return false; // T2 cannot be a subtree if T1 is empty
    }

    // Check if the current subtree of T1 is identical to T2
    if (areIdentical(T1, T2)) {
        return true;
    }

    // Recursively check in the left and right subtrees of T1
    return isSubtree(T1->left, T2) || isSubtree(T1->right, T2);
}

```

```

// Function to create a new tree node
struct TreeNode* createNode(int data) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->data = data;
    newNode->left = NULL;
    newNode->right = NULL;
    return newNode;
}

int main() {
    // Construct Tree T1
    struct TreeNode* T1 = createNode(3);
    T1->left = createNode(4);
    T1->right = createNode(5);
    T1->left->left = createNode(1);
    T1->left->right = createNode(2);

    // Construct Tree T2
    struct TreeNode* T2 = createNode(4);
    T2->left = createNode(1);
    T2->right = createNode(2);

    // Check if T2 is a subtree of T1
    if (isSubtree(T1, T2)) {
        printf("Tree T2 is a subtree of Tree T1.\n");
    } else {
        printf("Tree T2 is not a subtree of Tree T1.\n");
    }

    // Free the allocated memory
    free(T1);
    free(T2);

    return 0;
}

```

1.264 Minimum Swaps Required To Convert Min Heap to BST

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a tree node
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Function to count the number of swaps required to convert a min-heap to a BST
int countSwaps(int arr[], int n) {
    // Create an array to store the positions of elements in the sorted order
    int positions[n];
    for (int i = 0; i < n; i++) {
        positions[i] = i;
    }

    // Sort the positions array based on the values in the arr array
    for (int i = 0; i < n; i++) {

```

```

        for (int j = i + 1; j < n; j++) {
            if (arr[i] > arr[j]) {
                // Swap the values in the arr array
                int temp = arr[i];
                arr[i] = arr[j];
                arr[j] = temp;

                // Swap the positions in the positions array
                temp = positions[i];
                positions[i] = positions[j];
                positions[j] = temp;
            }
        }
    }

    // Count the number of swaps needed to convert positions array to a sorted array
    int swaps = 0;
    for (int i = 0; i < n; i++) {
        while (positions[i] != i) {
            // Swap the positions until the element reaches its correct position
            int temp = positions[i];
            positions[i] = positions[positions[i]];
            positions[temp] = temp;
            swaps++;
        }
    }

    return swaps;
}

int main() {
    int arr[] = {3, 2, 1, 5, 4};
    int n = sizeof(arr) / sizeof(arr[0]);

    int swaps = countSwaps(arr, n);

    printf("Minimum number of swaps required: %d\n", swaps);

    return 0;
}

```

1.265 Check If Two Files Are Identical

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <openssl/sha.h>

#define MAX_FILE_SIZE 1024

void calculate_sha256(const char *filename, unsigned char hash[SHA256_DIGEST_LENGTH]) {
    FILE *file = fopen(filename, "rb");
    if (file == NULL) {
        perror("Error opening file");
        exit(EXIT_FAILURE);
    }

    SHA256_CTX sha256;
    SHA256_Init(&sha256);

```

```

size_t bytes;
unsigned char buffer[MAX_FILE_SIZE];
while ((bytes = fread(buffer, 1, sizeof(buffer), file)) != 0) {
    SHA256_Update(&sha256, buffer, bytes);
}
SHA256_Final(hash, &sha256);

fclose(file);
}

int compare_files(const char *file1, const char *file2) {
    unsigned char hash1[SHA256_DIGEST_LENGTH];
    unsigned char hash2[SHA256_DIGEST_LENGTH];

    calculate_sha256(file1, hash1);
    calculate_sha256(file2, hash2);

    return memcmp(hash1, hash2, SHA256_DIGEST_LENGTH) == 0;
}

int main(int argc, char *argv[]) {
    if (argc < 3) {
        fprintf(stderr, "Usage: %s file1 file2\n", argv[0]);
        return EXIT_FAILURE;
    }

    const char *file1 = argv[1];
    const char *file2 = argv[2];

    if (compare_files(file1, file2)) {
        printf("The content of %s and %s is the same.\n", file1, file2);
    } else {
        printf("The content of %s and %s is different.\n", file1, file2);
    }

    return EXIT_SUCCESS;
}

```

1.266 Git Commit History

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_COMMIT_ID_LEN 41 // 40 characters for the SHA-1 hash + 1 for the null terminator

typedef struct {
    char commit_id[MAX_COMMIT_ID_LEN];
    unsigned long review_timestamp;
    unsigned long merge_timestamp;
} GitCommit;

// Function to parse commit information from a Git log
void parse_git_log(const char *log_content, GitCommit *commits, int *num_commits) {
    char *token = strtok((char *)log_content, "\n");
    int index = 0;

```

```

while (token != NULL) {
    // Assuming the log format is "commit_id review_timestamp merge_timestamp"
    sscanf(token, "%s %lu %lu", commits[index].commit_id,
           &commits[index].review_timestamp, &commits[index].merge_timestamp);

    token = strtok(NULL, "\n");
    index++;
}

*num_commits = index;
}

int main() {
    // Example Git log content
    const char *git_log_content = "commit_id_1 1633336800 1633336900\n"
                                    "commit_id_2 1633337000 1633337100\n"
                                    "commit_id_3 1633337200 1633337300\n";

    // Parse Git log and store commit information
    GitCommit commits[100]; // Adjust the array size based on your needs
    int num_commits = 0;

    parse_git_log(git_log_content, commits, &num_commits);

    // Print commit information
    for (int i = 0; i < num_commits; i++) {
        printf("Commit ID: %s\n", commits[i].commit_id);
        printf("Review Timestamp: %lu\n", commits[i].review_timestamp);
        printf("Merge Timestamp: %lu\n", commits[i].merge_timestamp);
        printf("\n");
    }

    return 0;
}

```

1.267 Recursive Links In Web page

```

#include <stdio.h>
#include <stdlib.h>
#include <curl/curl.h>
#include <string.h>
#include <json-c/json.h>

// Buffer to store the response from the Wikipedia API
struct MemoryStruct {
    char *memory;
    size_t size;
};

// Callback function to write received data to the buffer
static size_t WriteMemoryCallback(void *contents, size_t size, size_t nmemb, void *userp) {
    size_t realsize = size * nmemb;
    struct MemoryStruct *mem = (struct MemoryStruct *)userp;

    mem->memory = realloc(mem->memory, mem->size + realsize + 1);

```

```

if (mem->memory == NULL) {
    // Out of memory
    fprintf(stderr, "Not enough memory (realloc returned NULL)\n");
    return 0;
}

memcpy(&(mem->memory[mem->size]), contents, realsize);
mem->size += realsize;
mem->memory[mem->size] = 0;

return realsize;
}

// Function to fetch links from a Wikipedia page using Wikipedia API
void fetchWikipediaLinks(const char *page) {
    CURL *curl;
    CURLcode res;

    struct MemoryStruct chunk;
    chunk.memory = malloc(1);
    chunk.size = 0;

    // Initialize libcurl
    curl_global_init(CURL_GLOBAL_DEFAULT);
    curl = curl_easy_init();

    if (curl) {
        char url[256];
        snprintf(url, sizeof(url),
"https://en.wikipedia.org/w/api.php?action=parse&page=%s&prop=links&format=json", page);

        // Set the URL for the request
        curl_easy_setopt(curl, CURLOPT_URL, url);

        // Set the callback function to write response data to the buffer
        curl_easy_setopt(curl, CURLOPT_WRITEFUNCTION, WriteMemoryCallback);
        curl_easy_setopt(curl, CURLOPT_WRITEDATA, (void *)&chunk);

        // Perform the request
        res = curl_easy_perform(curl);

        // Check for errors
        if (res != CURLE_OK) {
            fprintf(stderr, "curl_easy_perform() failed: %s\n", curl_easy_strerror(res));
        } else {
            // Parse JSON response
            struct json_object *root, *pages, *links;

            root = json_tokener_parse(chunk.memory);
            if (!json_object_object_get_ex(root, "parse", &pages)) {
                fprintf(stderr, "Error parsing JSON response\n");
            } else if (!json_object_object_get_ex(pages, "links", &links)) {
                fprintf(stderr, "Error parsing links from JSON response\n");
            } else {
                // Iterate through links and print them
                printf("Links on %s:\n", page);
                for (int i = 0; i < json_object_array_length(links); i++) {
                    struct json_object *linkObj = json_object_array_get_idx(links, i);

```

```

        const char *link;
        json_object_object_get_ex(linkObj, "*",
                                  &link); // The actual link is stored under the "*" key
        printf("%d. %s\n", i + 1, link);
    }
}

// Cleanup
curl_easy_cleanup(curl);
curl_global_cleanup();
}

free(chunk.memory);
}

int main() {
    const char *startPage = "Computer_Science"; // Replace with your desired starting Wikipedia page

    // Fetch links recursively
    fetchWikipediaLinks(startPage);

    return 0;
}

```

1.268 Left Most Nodes

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a tree node
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};

// Function to create a new tree node
struct TreeNode* createNode(int value) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct TreeNode));
    newNode->data = value;
    newNode->left = NULL;
    newNode->right = NULL;
    return newNode;
}

// Function to find the leftmost nodes in a binary tree
void leftmostNodes(struct TreeNode* root) {
    if (root == NULL) {
        printf("Tree is empty\n");
        return;
    }

    struct TreeNode* current = root;

    while (current != NULL) {
        printf("%d ", current->data);

```

```

        current = current->left;
    }

    printf("\n");
}

int main() {
    // Constructing a sample binary tree
    struct TreeNode* root = createNode(1);
    root->left = createNode(2);
    root->right = createNode(3);
    root->left->left = createNode(4);
    root->left->right = createNode(5);
    root->right->left = createNode(6);
    root->right->right = createNode(7);

    printf("Leftmost nodes in the binary tree: ");
    leftmostNodes(root);

    return 0;
}

```

1.269 Recursive Print Linked List

```

#include <stdio.h>
#include <stdlib.h>

// Structure for a linked list node
struct Node {
    int data;
    struct Node* next;
};

// Function to create a new linked list node
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->next = NULL;
    return newNode;
}

// Function to recursively parse and print the linked list
void recursiveParse(struct Node* current) {
    if (current == NULL) {
        return;
    }

    // Print the current node's data
    printf("%d ", current->data);

    // Move to the next node recursively
    recursiveParse(current->next);
}

int main() {
    // Constructing a sample linked list
    struct Node* head = createNode(1);
    head->next = createNode(2);

```

```

head->next->next = createNode(3);
head->next->next->next = createNode(4);

printf("Linked List: ");
recursiveParse(head);

return 0;
}

```

1.270 Minimum Distance Between Two Elements

```

#include <stdio.h>
#include <stdlib.h>

// Function to find minimum distance between two elements in an array
int minDistance(int arr[], int n, int x, int y) {
    int minDist = n; // Initialize the result to a large value

    int prev = -1;

    for (int i = 0; i < n; i++) {
        if (arr[i] == x || arr[i] == y) {
            if (prev != -1 && arr[i] != arr[prev]) {
                minDist = (i - prev) < minDist ? (i - prev) : minDist;
            }
            prev = i;
        }
    }

    return minDist;
}

```

```

int main() {
    int arr[] = {4, 6, 7, 8, 6, 2, 2, 6, 4, 7};
    int n = sizeof(arr) / sizeof(arr[0]);

    int x = 4;
    int y = 7;

    int distance = minDistance(arr, n, x, y);

    if (distance == n)
        printf("One or both elements not present in the array\n");
    else
        printf("Minimum distance between %d and %d is: %d\n", x, y, distance);

    return 0;
}

```

1.271 Unique Elements

```

#include <stdio.h>
#include <stdbool.h>

// Function to check if an element exists in the hash set
bool contains(int *hashSet, int size, int value) {
    for (int i = 0; i < size; i++) {
        if (hashSet[i] == value) {

```

```

        return true;
    }
}
return false;
}

// Function to find unique elements in the array
int* findUniqueElements(int *arr, int size, int *resultSize) {
    // Assuming maximum array size is 100 (you can adjust this as needed)
    int hashSet[100];
    int uniqueCount = 0;

    for (int i = 0; i < size; i++) {
        if (!contains(hashSet, uniqueCount, arr[i])) {
            hashSet[uniqueCount] = arr[i];
            uniqueCount++;
        }
    }

    // Allocate memory for the result array
    int *resultArray = (int*)malloc(uniqueCount * sizeof(int));

    // Copy unique elements to the result array
    for (int i = 0; i < uniqueCount; i++) {
        resultArray[i] = hashSet[i];
    }

    // Set the size of the result array
    *resultSize = uniqueCount;

    return resultArray;
}

int main() {
    int inputArray[] = {1, 2, 3, 2, 4, 5, 6, 4, 7, 8, 9, 1};
    int size = sizeof(inputArray) / sizeof(inputArray[0]);

    int resultSize;
    int *resultArray = findUniqueElements(inputArray, size, &resultSize);

    printf("Unique elements in the array: ");
    for (int i = 0; i < resultSize; i++) {
        printf("%d ", resultArray[i]);
    }

    // Remember to free the dynamically allocated memory
    free(resultArray);

    return 0;
}

```

1.272 Square A Sorted Array

```

#include <stdio.h>
#include <stdlib.h>

// Function to square each element of a sorted array and return the sorted result
int* squareSortedArray(int* nums, int size) {

```

```

int* result = (int*)malloc(size * sizeof(int));

// Squaring each element
for (int i = 0; i < size; i++) {
    result[i] = nums[i] * nums[i];
}

// Sorting the squared array using insertion sort
for (int i = 1; i < size; i++) {
    int key = result[i];
    int j = i - 1;

    while (j >= 0 && result[j] > key) {
        result[j + 1] = result[j];
        j = j - 1;
    }

    result[j + 1] = key;
}

return result;
}

// Function to print an array
void printArray(int* arr, int size) {
    for (int i = 0; i < size; i++) {
        printf("%d ", arr[i]);
    }
    printf("\n");
}

int main() {
    // Example sorted array
    int nums[] = {-4, -2, 0, 2, 5};
    int size = sizeof(nums) / sizeof(nums[0]);

    // Square the sorted array and return the result
    int* squaredArray = squareSortedArray(nums, size);

    // Print the squared and sorted array
    printf("Squared and Sorted Array: ");
    printArray(squaredArray, size);

    // Remember to free the dynamically allocated memory
    free(squaredArray);

    return 0;
}

```

1.273 NTP Logger

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <sys/time.h>
#include <syslog.h>
#include <ntp.h>

```

```

#define JAN_1970 2208988800UL
#define DRIFT_THRESHOLD 1000 // Adjust this threshold as needed
#define SYNC_INTERVAL_SECONDS 300 // Adjust synchronization interval as needed

// Function to log messages to syslog
void log_message(const char *message, int priority) {
    openlog("NTPSyncExample", LOG_PID | LOG_NDELAY, LOG_USER);
    syslog(priority, "%s", message);
    closelog();
}

// Function to handle clock drift
void handle_clock_drift(struct nptimeval *ntp_time) {
    // Calculate the difference between local time and NTP time
    struct timeval local_time;
    gettimeofday(&local_time, NULL);

    // Calculate the time drift in milliseconds
    long drift = (ntp_time->time.tv_sec - local_time.tv_sec) * 1000 +
        (ntp_time->time.tv_usec - local_time.tv_usec) / 1000;

    // Log the clock drift
    char message[100];
    snprintf(message, sizeof(message), "Clock drift: %ld milliseconds", drift);
    log_message(message, LOG_INFO);

    // Adjust the local clock if the drift exceeds a certain threshold
    if (labs(drift) > DRIFT_THRESHOLD) {
        struct timeval adjust_time;
        adjust_time.tv_sec = ntp_time->time.tv_sec;
        adjust_time.tv_usec = ntp_time->time.tv_usec;
        settimeofday(&adjust_time, NULL);

        // Log the clock adjustment
        log_message("Clock adjusted", LOG_INFO);
    }
}

int main() {
    while (1) {
        // Initialize NTP data structures
        struct nptimeval ntp_time;
        memset(&ntp_time, 0, sizeof(ntp_time));

        // Initialize the NTP server address
        char ntp_server[] = "pool.ntp.org";

        // Perform the NTP query
        int result = ntp_gettime(ntp_server, &ntp_time);
        if (result == 0) {
            // Convert NTP time to UNIX timestamp
            time_t unix_time = ntp_time.time.tv_sec - JAN_1970;

            // Display the result
            printf("NTP Time: %s", ctime(&unix_time));

            // Log the successful NTP synchronization
        }
    }
}

```

```

        log_message("NTP synchronization successful", LOG_INFO);

        // Handle clock drift
        handle_clock_drift(&ntp_time);
    } else {
        // Log the NTP query failure
        log_message("NTP query failed", LOG_ERR);

        fprintf(stderr, "NTP query failed\n");
    }

    // Sleep for a specific interval before the next synchronization
    sleep(SYNC_INTERVAL_SECONDS);
}

return 0;
}

```

1.274 Job Scheduler

```

#include <stdio.h>
#include <stdlib.h>
#include <time.h>

// Structure to represent a job
typedef struct {
    int job_id;
    time_t scheduled_time;
    void (*job_function)();
} Job;

// Priority Queue Node
typedef struct {
    Job *job;
    struct PriorityQueueNode *next;
} PriorityQueueNode;

// Priority Queue
typedef struct {
    PriorityQueueNode *front;
} PriorityQueue;

// Function to create a new job
Job* createJob(int job_id, time_t scheduled_time, void (*job_function)()) {
    Job *newJob = (Job*)malloc(sizeof(Job));
    newJob->job_id = job_id;
    newJob->scheduled_time = scheduled_time;
    newJob->job_function = job_function;
    return newJob;
}

// Function to create a new PriorityQueueNode
PriorityQueueNode* createPriorityQueueNode(Job *job) {
    PriorityQueueNode *node = (PriorityQueueNode*)malloc(sizeof(PriorityQueueNode));
    node->job = job;
    node->next = NULL;
    return node;
}

```

```

// Function to initialize a priority queue
PriorityQueue* initializePriorityQueue() {
    PriorityQueue *queue = (PriorityQueue*)malloc(sizeof(PriorityQueue));
    queue->front = NULL;
    return queue;
}

// Function to insert a job into the priority queue
void insertJob(PriorityQueue *queue, Job *job) {
    PriorityQueueNode *newNode = createPriorityQueueNode(job);

    // If the queue is empty or the job's scheduled time is earlier than the front job, insert at the front
    if (queue->front == NULL || job->scheduled_time < queue->front->job->scheduled_time) {
        newNode->next = queue->front;
        queue->front = newNode;
        return;
    }

    // Traverse the queue to find the correct position for insertion
    PriorityQueueNode *current = queue->front;
    while (current->next != NULL && current->next->job->scheduled_time <= job->scheduled_time) {
        current = current->next;
    }

    newNode->next = current->next;
    current->next = newNode;
}

// Function to execute the scheduled jobs
void executeJobs(PriorityQueue *queue) {
    while (queue->front != NULL) {
        time_t current_time = time(NULL);

        // Check if the front job is ready to be executed
        if (current_time >= queue->front->job->scheduled_time) {
            // Execute the job
            printf("Executing Job %d at %s", queue->front->job->job_id, ctime(&current_time));
            queue->front->job->job_function();

            // Remove the executed job from the queue
            PriorityQueueNode *temp = queue->front;
            queue->front = queue->front->next;
            free(temp);
        } else {
            // No jobs are ready to be executed, break out of the loop
            break;
        }
    }
}

// Sample job functions
void jobFunction1() {
    printf("Job Function 1\n");
}

void jobFunction2() {
    printf("Job Function 2\n");
}

```

```

}

int main() {
    // Initialize the priority queue
    PriorityQueue *jobQueue = initializePriorityQueue();

    // Create sample jobs
    Job *job1 = createJob(1, time(NULL) + 5, jobFunction1);
    Job *job2 = createJob(2, time(NULL) + 10, jobFunction2);

    // Insert jobs into the priority queue
    insertJob(jobQueue, job1);
    insertJob(jobQueue, job2);

    // Simulate job execution
    executeJobs(jobQueue);

    // Free allocated memory
    free(job1);
    free(job2);
    free(jobQueue);

    return 0;
}

```

1.275 Course Schedule II

```

/*
 * Note: The returned array must be malloced, assume caller calls free().
 */

struct Node {
    int val;
    struct Node* next;
};

struct Graph {
    int numCourses;
    struct Node** adjList;
    int* inDegrees;
};

// Function to initialize a graph
struct Graph* initializeGraph(int numCourses) {
    struct Graph* graph = (struct Graph*)malloc(sizeof(struct Graph));
    graph->numCourses = numCourses;
    graph->adjList = (struct Node**)malloc(numCourses * sizeof(struct Node*));
    graph->inDegrees = (int*)calloc(numCourses, sizeof(int));

    for (int i = 0; i < numCourses; i++) {
        graph->adjList[i] = NULL;
    }

    return graph;
}

```

```

// Function to add a directed edge to the graph
void addEdge(struct Graph* graph, int src, int dest) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->val = dest;
    newNode->next = graph->adjList[src];
    graph->adjList[src] = newNode;

    // Increment in-degree of the destination node
    graph->inDegrees[dest]++;
}

// Function to perform topological sort using Kahn's algorithm
int* findOrder(int numCourses, int** prerequisites, int prerequisitesSize, int*
prerequisitesColSize, int* returnSize) {
    // Initialize the graph
    struct Graph* graph = initializeGraph(numCourses);

    // Build the graph and compute in-degrees
    for (int i = 0; i < prerequisitesSize; i++) {
        addEdge(graph, prerequisites[i][1], prerequisites[i][0]);
    }

    // Create a queue for topological sort
    int* queue = (int*)malloc(numCourses * sizeof(int));
    int front = 0, rear = 0;

    // Enqueue nodes with in-degree zero
    for (int i = 0; i < numCourses; i++) {
        if (graph->inDegrees[i] == 0) {
            queue[rear++] = i;
        }
    }

    // Initialize the result array
    int* result = (int*)malloc(numCourses * sizeof(int));
    int index = 0;

    // Perform topological sort
    while (front < rear) {
        int current = queue[front++];

        result[index++] = current;

        // Update in-degrees of adjacent nodes
        struct Node* temp = graph->adjList[current];
        while (temp != NULL) {
            graph->inDegrees[temp->val]--;

```

```

        if (graph->inDegrees[temp->val] == 0) {
            queue[rear++] = temp->val;
        }

        temp = temp->next;
    }
}

// Check if topological sort is possible
if (index != numCourses) {
    *returnSize = 0;
    free(result);
    result = NULL;
} else {
    *returnSize = numCourses;
}

// Free memory
free(graph->inDegrees);
for (int i = 0; i < numCourses; i++) {
    struct Node* temp = graph->adjList[i];
    while (temp != NULL) {
        struct Node* nextNode = temp->next;
        free(temp);
        temp = nextNode;
    }
}
free(graph->adjList);
free(graph);
free(queue);

return result;
}

```

1.276 Cycle/Loop In Linked List

```

/**
 * Definition for singly-linked list.
 * struct ListNode {
 *     int val;
 *     struct ListNode *next;
 * };
 */
bool hasCycle(struct ListNode *head) {

    if (head == NULL) return false;
    struct ListNode *slow = head;
    struct ListNode *fast = head;

```

```

        while (fast != NULL && fast->next != NULL) {
            slow = slow->next;
            fast = fast->next->next;
            if (slow == fast) return true;
        }
        return false;
    }

```

1.277 Version Sorting

```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

// Comparison function for qsort to perform version sorting
int compareVersions(const void* a, const void* b) {
    // Assuming versions are in the format "major.minor"
    // Extract major and minor version components

    // Convert version strings to integers
    int majorA, minorA, majorB, minorB;
    sscanf(*(const char**)a, "%d.%d", &majorA, &minorA);
    sscanf(*(const char**)b, "%d.%d", &majorB, &minorB);

    // Compare major versions first
    if (majorA != majorB) {
        return majorA - majorB;
    }

    // If major versions are equal, compare minor versions
    return minorA - minorB;
}

int main() {
    // Example array of version strings
    const char* versions[] = {"1.2", "2.0", "1.10", "2.1"};

    // Calculate the number of versions
    size_t numVersions = sizeof(versions) / sizeof(versions[0]);

    // Perform version sorting using qsort
    qsort(versions, numVersions, sizeof(versions[0]), compareVersions);

    // Print the sorted versions
    printf("Sorted Versions:\n");
    for (size_t i = 0; i < numVersions; ++i) {
        printf("%s\n", versions[i]);
    }

    return 0;
}

```

1.278 Reverse Linked List Using Stack

```
#include <stdio.h>
```

```

#include <stdlib.h>

// Node structure for a singly linked list
struct Node {
    int data;
    struct Node* next;
};

// Function to push a node onto the stack
void push(struct Node** top, int data) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = data;
    newNode->next = *top;
    *top = newNode;
}

// Function to pop a node from the stack
int pop(struct Node** top) {
    if (*top == NULL) {
        // Stack is empty
        return -1;
    }

    struct Node* temp = *top;
    int data = temp->data;
    *top = temp->next;
    free(temp);

    return data;
}

// Function to reverse a linked list using a stack
void reverseLinkedList(struct Node** head) {
    if (*head == NULL || (*head)->next == NULL) {
        // Empty or single-node list, no need to reverse
        return;
    }

    struct Node* stackTop = NULL;
    struct Node* current = *head;

    // Push each element onto the stack
    while (current != NULL) {
        push(&stackTop, current->data);
        current = current->next;
    }

    // Pop elements from the stack to reconstruct the reversed linked list
    current = *head;
    while (current != NULL) {
        current->data = pop(&stackTop);
        current = current->next;
    }
}

// Function to print a linked list
void printList(struct Node* head) {
    while (head != NULL) {

```

```

        printf("%d -> ", head->data);
        head = head->next;
    }
    printf("NULL\n");
}

int main() {
    // Create a sample linked list
    struct Node* head = NULL;
    for (int i = 1; i <= 5; i++) {
        struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
        newNode->data = i;
        newNode->next = head;
        head = newNode;
    }

    // Print the original linked list
    printf("Original Linked List: ");
    printList(head);

    // Reverse the linked list using a stack
    reverseLinkedList(&head);

    // Print the reversed linked list
    printf("Reversed Linked List: ");
    printList(head);

    // Free the memory allocated for the linked list nodes
    while (head != NULL) {
        struct Node* temp = head;
        head = head->next;
        free(temp);
    }

    return 0;
}

```

1.279 Hexadecimal to decimal

```

#include <stdio.h>

// Function to convert hexadecimal to decimal without using strtol
unsigned long hexToDecimal(const char *hexNumber) {
    unsigned long decimalNumber = 0;
    int i = 0;

    // Skip the "0x" prefix if present
    if (hexNumber[0] == '0' && (hexNumber[1] == 'x' || hexNumber[1] == 'X')) {
        i = 2;
    }

    // Iterate through the characters of the hexadecimal string
    while (hexNumber[i] != '\0') {
        decimalNumber *= 16;

        // Convert character to corresponding decimal value
        if (hexNumber[i] >= '0' && hexNumber[i] <= '9') {
            decimalNumber += hexNumber[i] - '0';
        }
    }
}
```

```

        } else if (hexNumber[i] >= 'A' && hexNumber[i] <= 'F') {
            decimalNumber += hexNumber[i] - 'A' + 10;
        } else if (hexNumber[i] >= 'a' && hexNumber[i] <= 'f') {
            decimalNumber += hexNumber[i] - 'a' + 10;
        } else {
            // Invalid character in the hexadecimal string
            printf("Invalid hexadecimal character: %c\n", hexNumber[i]);
            return 0;
        }

        i++;
    }

    return decimalNumber;
}

int main() {
    // Hexadecimal number as a string
    const char *hexNumber = "1A";

    // Using custom function for hexadecimal to decimal conversion
    unsigned long decimalNumber = hexToDecimal(hexNumber);

    // Printing the result
    printf("Hexadecimal: %s\n", hexNumber);
    printf("Decimal: %lu\n", decimalNumber);

    return 0;
}

```

1.280 Decimal To Hexadecimal

```

#include <stdio.h>

// Function to convert decimal to hexadecimal without using printf
void decimalToHexadecimal(unsigned long decimalNumber) {
    char hexadecimal[20]; // Assuming a reasonable maximum length for the result
    int i = 0;

    // Iterate until the decimal number becomes 0
    while (decimalNumber > 0) {
        int remainder = decimalNumber % 16;

        // Convert remainder to hexadecimal character
        if (remainder < 10) {
            hexadecimal[i] = remainder + '0';
        } else {
            hexadecimal[i] = remainder - 10 + 'A';
        }

        decimalNumber /= 16;
        i++;
    }

    // Print the hexadecimal representation in reverse order
    printf("Hexadecimal: ");
    for (int j = i - 1; j >= 0; j--) {

```

```

        printf("%c", hexadecimal[j]);
    }

    printf("\n");
}

int main() {
    // Decimal number
    unsigned long decimalNumber = 26;

    // Using custom function for decimal to hexadecimal conversion
    decimalToHexadecimal(decimalNumber);

    return 0;
}

```

1.281 Absolute Path From Relative Path

```

#include <stdio.h>
#include <stdlib.h>
#include <limits.h>

int main() {
    // Relative path
    const char *relativePath = "myfolder/myfile.txt";

    // Buffer to store the absolute path
    char absolutePath[PATH_MAX];

    // Using realpath to find the absolute path
    char *result = realpath(relativePath, absolutePath);

    // Check if realpath was successful
    if (result != NULL) {
        printf("Relative Path: %s\n", relativePath);
        printf("Absolute Path: %s\n", absolutePath);
    } else {
        perror("realpath");
        return EXIT_FAILURE;
    }

    return 0;
}

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <limits.h>

int main() {
    // Relative path
    const char *relativePath = "myfolder/myfile.txt";

    // Buffer to store the absolute path
    char absolutePath[PATH_MAX];

    // Get the current working directory
    if (getcwd(absolutePath, sizeof(absolutePath)) != NULL) {
        // Concatenate the relative path to the current working directory

```

```

        snprintf(absolutePath, sizeof(absolutePath), "%s/%s", absolutePath, relativePath);

        printf("Relative Path: %s\n", relativePath);
        printf("Absolute Path: %s\n", absolutePath);
    } else {
        perror("getcwd");
        return EXIT_FAILURE;
    }

    return 0;
}

```

1.282 LockLess programming

```

#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <stdatomic.h>

// Define a global atomic variable for the counter
_Atomic int counter = 0;

// Function to increment the counter atomically
void* increment_counter(void* arg) {
    for (int i = 0; i < 1000000; i++) {
        // Atomically increment the counter
        atomic_fetch_add(&counter, 1);
    }
    return NULL;
}

int main() {
    // Create two threads to increment the counter concurrently
    pthread_t thread1, thread2;
    pthread_create(&thread1, NULL, increment_counter, NULL);
    pthread_create(&thread2, NULL, increment_counter, NULL);

    // Wait for the threads to finish
    pthread_join(thread1, NULL);
    pthread_join(thread2, NULL);

    // Print the final value of the counter
    printf("Final counter value: %d\n", counter);

    return 0;
}

```

1.283 IOCTL

```

#include <stdlib.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <net/if.h>
#include <sys/ioctl.h>
#include <linux/mii.h>
#include <linux/sockios.h>
#include <errno.h>

```

```

char *name = NULL;
int phy = 0;
int control_register_value = 0;
int choice = 0;
int cr[10] = {0x0040,0x0080,0x0100,0x0200,0x0400,
              0x0800,0x1000,0x2000,0x4000,0x8000};
char control_register[10][20] = {
    "BMCR_SPEED1000", "BMCR_CTST", "BMCR_FULLDPLX",
    "BMCR_ANRESTART", "BMCR_ISOLATE", "BMCR_PDOWN",
    "BMCR_ANENABLE","BMCR_SPEED100", "BMCR_LOOPBACK", "BMCR_RESET"
};

void read_mii_register(int fd, char *name) {
    struct ifreq ifr;
    memset(&ifr, 0, sizeof(ifr));
    strcpy(ifr.ifr_name, name);

    if (ioctl(fd, SIOCGMIIPHY, &ifr) < 0) {
        printf("\nPHY FAILED!");
        return;
    }
    struct mii_ioctl_data* mii = (struct mii_ioctl_data*)(&ifr.ifr_data);

    /*Read status register*/
    mii->reg_num = MII_BMSR;
    mii->val_in = 0;
    mii->val_out = 0;

    if (ioctl(fd, SIOCGMIIREG, &ifr) != -1){
        if ((mii->val_out != 0xffff) || (mii->val_out != 0x0)) {
            printf("\nMII Transceiver Found for %s and phy_id is %d!",name,mii->phy_id);
        }
        else {
            printf("\nNo MII Transceiver Found for %s and phy_id is %d!",name,mii->phy_id);
            return;
        }
        phy = mii->phy_id;
        printf("\n===== BASIC MODE STATUS REGISTER MII_BMSR : 0x%x\n",
               mii->val_out);
        printf("BMSR_ERCAP(External Register Capability) = %d \n", (mii->val_out & BMSR_ERCAP) ? 1 : 0);
        printf("BMSR_JCD(Jabber Detected) = %d \n", (mii->val_out & BMSR_JCD) ? 1 : 0);
        printf("BMSR_LSTATUS(Link Status) = %d \n", (mii->val_out & BMSR_LSTATUS) ? 1 : 0);
        printf("BMSR_ANEGCAPABLE(Auto-negotiation) = %d \n", (mii->val_out & BMSR_ANEGCAPABLE) ? 1 : 0);
        printf("BMSR_RFAULT(Remote Fault) = %d \n", (mii->val_out & BMSR_RFAULT) ? 1 : 0);
        printf("BMSR_ANEGCOMPLETE(Auto-negotiation Complete) = %d \n", (mii->val_out & BMSR_ANEGCOMPLETE) ? 1 : 0);
        printf("BMSR_ESTATEN(Extended Status) = %d \n", (mii->val_out & BMSR_ESTATEN) ? 1 : 0);
        printf("BMSR_100HALF2(100Base-T2 Half Duplex) = %d \n", (mii->val_out & BMSR_100HALF2) ? 1 : 0);
        printf("BMSR_100FULL2(100Base-T2 Full Duplex) = %d \n", (mii->val_out & BMSR_100FULL2) ? 1 : 0);
        printf("BMSR_10HALF(10Mbps Half Duplex) = %d \n", (mii->val_out & BMSR_10HALF) ? 1 : 0);
        printf("BMSR_10FULL(10Mbps Full Duplex) = %d \n", (mii->val_out & BMSR_10FULL) ? 1 : 0);
        printf("BMSR_100HALF(100Mbps Half Duplex) = %d \n", (mii->val_out & BMSR_100HALF) ? 1 : 0);
        printf("BMSR_100BASE4(100Mbps 4K Packets) = %d \n", (mii->val_out & BMSR_100BASE4) ? 1 : 0);
    }else{
        printf(" MII_BMSR register read returns -1\n");
        return;
    }
}

```

```

/*Read control register*/
mii->reg_num = MII_BMCR;
mii->val_in = 0;
mii->val_out = 0;

if (ioctl(fd, SIOCGMIIREG, &ifr) != -1){
    printf("\n===== BASIC MODE CONTROL REGISTER MII_BMCR : 0x%08x\n=====\n",mii->val_out);
    printf("BMCR_SPEED1000(MSB of Link Speed) = %d \n", (mii->val_out & BMCR_SPEED1000) ? 1 : 0);
    printf("BMCR_CTST(Collission test) = %d \n", (mii->val_out & BMCR_CTST) ? 1 : 0);
    printf("BMCR_FULLDPLX(Full Duplex) = %d \n", (mii->val_out & BMCR_FULLDPLX) ? 1 : 0);
    printf("BMCR_ANRESTART(Auto-negotiation restart) = %d \n", (mii->val_out & BMCR_ANRESTART) ? 1 : 0);
    printf("BMCR_ISOLATE(Disconnect DP83840 Physical Layer from MII) = %d \n", (mii->val_out & BMCR_ISOLATE) ? 1 : 0);
    printf("BMCR_PDOWN(Power down DP83840) = %d \n", (mii->val_out & BMCR_PDOWN) ? 1 : 0);
    printf("BMCR_ANENABLE(Enable Auto-negotiation) = %d \n", (mii->val_out & BMCR_ANENABLE) ? 1 : 0);
    control_register_value = mii->val_out;
} else{
    printf(" MII_BMCR register read returns -1\n");
}
return;
}

void write_mii_register(int fd, char *name, int choice) {
    printf("\nPreferred to write register %s at location : 0x%08x\n",control_register[choice], cr[choice]);
    struct ifreq ifr;
    memset(&ifr, 0, sizeof(ifr));
    strcpy(ifr.ifr_name, name);

    if (ioctl(fd, SIOCGMIIPHY, &ifr) < 0) {
        printf("\nPHY FAILED!");
        return;
    }
    struct mii_ioctl_data* mii = (struct mii_ioctl_data*)(&ifr.ifr_data);
    mii->phy_id = phy;
    mii->reg_num = MII_BMCR;
    if (strcmp(name, "eth6") == 0) {
        mii->val_in = (control_register_value ^ cr[choice]);
    }
    else {
        mii->val_in = (control_register_value | cr[choice]);
    }
    if (ioctl(fd, SIOCSMIIREG, &ifr) < 0) {
        fprintf(stderr, "\nwrite failure %s", strerror(errno));
    }
    else {
        fprintf(stderr, "\nwrite success %s", strerror(errno));
    }
}

int main(int argc, char *argv[]){

```

```

if (argc<3) {
    printf("\nUsage ./phy_register_util [r/w] [dev_name]\n");
    return 0;
}
const int fd = socket(AF_INET, SOCK_DGRAM, 0);
if (fd < 0) {
    printf("\nSocket error!");
    return -1;
}
name = argv[2];
if (strcmp(argv[1],"r") == 0) {
    read_mii_register(fd,name);
}
else if (strcmp(argv[1],"w") == 0) {
    printf("\nAvailable registers to write:");
    printf("\n0: BMCR_SPEED1000(MSB of Link Speed)\n1: BMCR_CTST(Collission test)\n
        \n2: BMCR_FULLDPLX(Full Duplex)\n3: BMCR_ANRESTART(Auto-negotiation restart)\n
        \n4: BMCR_ISOLATE(Disconnect DP83840 Physical Layer from MII)\n
        \n5: BMCR_PDOWN(Power down DP83840)\n6: BMCR_ANENABLE(Enable Auto-negotiation)\n
        \n7: BMCR_SPEED100>Select 100Mbps)\n8: BMCR_LOOPBACK(TXD Loopback bits)\n
        \n9: BMCR_RESET(Reset DP83840)\n");
    printf("\nSelect one from above:");
    scanf("%d",&choice);
    write_mii_register(fd,name,choice);
}
else {
    printf("\nUsage ./phy_register_util [r/w] [dev_name]\n");
    return 0;
}
close(fd);
}

```

1.284 I2C

```

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/ioctl.h>
#include <linux/i2c-dev.h>

#define I2C_DEVICE "/dev/i2c-1" // Change this to match your I2C device file

// Function to initialize the I2C bus and device
int initI2C(int addr) {
    int file;

    // Open the I2C device file
    if ((file = open(I2C_DEVICE, O_RDWR)) < 0) {
        perror("Failed to open the I2C device");
        return -1;
    }

    // Set the I2C slave address
    if (ioctl(file, I2C_SLAVE, addr) < 0) {

```

```

        perror("Failed to set I2C slave address");
        close(file);
        return -1;
    }

    return file;
}

// Function to write data to the I2C device
int writel2C(int file, unsigned char *data, int len) {
    if (write(file, data, len) != len) {
        perror("Failed to write to the I2C device");
        return -1;
    }
    return 0;
}

// Function to read data from the I2C device
int readl2C(int file, unsigned char *data, int len) {
    if (read(file, data, len) != len) {
        perror("Failed to read from the I2C device");
        return -1;
    }
    return 0;
}

// Function to close the I2C bus
void closel2C(int file) {
    close(file);
}

int main() {
    int file;
    unsigned char data[2];

    // Initialize the I2C bus and device
    if ((file = initI2C(0x68)) < 0) { // Replace 0x68 with the actual device address
        exit(EXIT_FAILURE);
    }

    // Example: Write to a register on the device
    data[0] = 0x00; // Register address
    data[1] = 0x55; // Data to be written
    if (writel2C(file, data, 2) < 0) {
        closel2C(file);
        exit(EXIT_FAILURE);
    }

    // Example: Read from a register on the device
    data[0] = 0x00; // Register address to read from
    if (writel2C(file, data, 1) < 0) {
        closel2C(file);
        exit(EXIT_FAILURE);
    }
    if (readl2C(file, data, 1) < 0) {
        closel2C(file);
        exit(EXIT_FAILURE);
    }
}

```

```

printf("Read data: 0x%02X\n", data[0]);

// Close the I2C bus
closeI2C(file);

return 0;
}

1.285 Large File Word Frequency

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX_WORD_LENGTH 100
#define HASH_TABLE_SIZE 10000

// Node structure for the hash table
typedef struct Node {
    char* word;
    int count;
    struct Node* next;
} Node;

// Function to create a new node
Node* createNode(char* word) {
    Node* newNode = (Node*)malloc(sizeof(Node));
    if (newNode == NULL) {
        fprintf(stderr, "Memory allocation failed\n");
        exit(1);
    }
    newNode->word = strdup(word);
    newNode->count = 1;
    newNode->next = NULL;
    return newNode;
}

// Function to calculate the hash value of a word
unsigned int hash(char* word) {
    unsigned int hashValue = 0;
    while (*word) {
        hashValue = (hashValue << 5) + *word++;
    }
    return hashValue % HASH_TABLE_SIZE;
}

// Function to insert a word into the hash table
void insert(Node** hashTable, char* word) {
    unsigned int index = hash(word);
    Node* current = hashTable[index];
    while (current != NULL) {
        if (strcmp(current->word, word) == 0) {
            current->count++;
            return;
        }
        current = current->next;
    }
    // Word not found, insert new node at the beginning of the list
}

```

```

Node* newNode = createNode(word);
newNode->next = hashTable[index];
hashTable[index] = newNode;
}

// Function to find the word with the highest frequency
char* findMostFrequentWord(Node** hashTable) {
    int maxCount = 0;
    char* mostFrequentWord = NULL;
    for (int i = 0; i < HASH_TABLE_SIZE; i++) {
        Node* current = hashTable[i];
        while (current != NULL) {
            if (current->count > maxCount) {
                maxCount = current->count;
                mostFrequentWord = current->word;
            }
            current = current->next;
        }
    }
    return mostFrequentWord;
}

int main() {
    // Initialize hash table
    Node* hashTable[HASH_TABLE_SIZE] = {NULL};

    // Open the file
    FILE* file = fopen("large_file.txt", "r");
    if (file == NULL) {
        fprintf(stderr, "Failed to open file\n");
        exit(1);
    }

    // Read the file word by word
    char word[MAX_WORD_LENGTH];
    while (fscanf(file, "%s", word) != EOF) {
        // Insert each word into the hash table
        insert(hashTable, word);
    }
    fclose(file);

    // Find the word with the highest frequency of occurrence
    char* mostFrequentWord = findMostFrequentWord(hashTable);

    // Print the result
    if (mostFrequentWord != NULL) {
        printf("Most frequent word: %s\n", mostFrequentWord);
    } else {
        printf("No words found in the file\n");
    }

    // Free memory allocated for the hash table
    for (int i = 0; i < HASH_TABLE_SIZE; i++) {
        Node* current = hashTable[i];
        while (current != NULL) {
            Node* temp = current;
            current = current->next;
            free(temp->word);
        }
    }
}

```

```

        free(temp);
    }
}

return 0;
}

1.286 Compressed String

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

char* compressString(const char* str) {
    int length = strlen(str);
    if (length == 0) return NULL; // Handle empty string

    char* result = (char*)malloc(sizeof(char) * (2 * length + 1)); // Maximum length of compressed string
    if (result == NULL) {
        fprintf(stderr, "Memory allocation failed\n");
        exit(1);
    }

    char current_char = str[0];
    int count = 1;
    int index = 0;

    for (int i = 1; i <= length; i++) {
        if (str[i] == current_char) {
            count++;
        } else {
            // Write compressed character and count to the result string
            index += sprintf(&result[index], "%c%d", current_char, count);
            current_char = str[i];
            count = 1;
        }
    }
}

return result;
}

```

```

int main() {
    const char* str = "aaabbcccccddaaeeeeee";
    char* compressed = compressString(str);
    if (compressed != NULL) {
        printf("Compressed string: %s\n", compressed);
        free(compressed); // Free dynamically allocated memory
    } else {
        printf("Failed to compress string\n");
    }
    return 0;
}

```

1.287 TCAM

```

#include <stdio.h>
#include <stdlib.h>

// Define TCAM entry structure

```

```

typedef struct {
    int key;
    int mask;
    char* value;
} TCAM_Entry;

// Define TCAM structure
typedef struct {
    int size;
    TCAM_Entry* entries;
} TCAM;

// Initialize TCAM
TCAM* initialize_tcam(int size) {
    TCAM* tcam = (TCAM*)malloc(sizeof(TCAM));
    tcam->size = size;
    tcam->entries = (TCAM_Entry*)malloc(size * sizeof(TCAM_Entry));
    return tcam;
}

// Insert entry into TCAM
void insert_entry(TCAM* tcam, int key, int mask, char* value) {
    for (int i = 0; i < tcam->size; i++) {
        if (tcam->entries[i].value == NULL) {
            tcam->entries[i].key = key;
            tcam->entries[i].mask = mask;
            tcam->entries[i].value = value;
            return;
        }
    }
    printf("TCAM is full. Cannot insert entry.\n");
}

// Lookup value in TCAM based on key and mask
char* lookup_value(TCAM* tcam, int key) {
    for (int i = 0; i < tcam->size; i++) {
        if ((key & tcam->entries[i].mask) == tcam->entries[i].key) {
            return tcam->entries[i].value;
        }
    }
    return NULL; // No matching entry found
}

// Main function
int main() {
    TCAM* tcam = initialize_tcam(4);

    insert_entry(tcam, 0b1010, 0b1111, "Value 1");
    insert_entry(tcam, 0b1100, 0b1100, "Value 2");

    char* result1 = lookup_value(tcam, 0b1011);
    char* result2 = lookup_value(tcam, 0b1101);
    char* result3 = lookup_value(tcam, 0b1111);

    printf("Lookup result 1: %s\n", result1 ? result1 : "Not found");
    printf("Lookup result 2: %s\n", result2 ? result2 : "Not found");
    printf("Lookup result 3: %s\n", result3 ? result3 : "Not found");
}

```

```
    free(tcam->entries);
    free(tcam);

    return 0;
}
```

1.288 Spin Locks

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>

// Define a spin lock structure
typedef struct {
    int flag;
} spinlock_t;

// Initialize the spin lock
void spinlock_init(spinlock_t *lock) {
    lock->flag = 0;
}

// Acquire the spin lock
void spinlock_lock(spinlock_t *lock) {
    while (__sync_lock_test_and_set(&lock->flag, 1)) {}
}

// Release the spin lock
void spinlock_unlock(spinlock_t *lock) {
    __sync_lock_release(&lock->flag);
}

// Function to be executed by multiple threads
void *thread_function(void *arg) {
    spinlock_t *lock = (spinlock_t *)arg;

    // Acquire the spin lock
    spinlock_lock(lock);

    // Critical section
    printf("Thread %ld acquired the lock\n", pthread_self());
    // Do some work...

    // Release the spin lock
    spinlock_unlock(lock);

    return NULL;
}

int main() {
    // Initialize the spin lock
    spinlock_t lock;
    spinlock_init(&lock);

    // Create multiple threads
    pthread_t threads[5];
    for (int i = 0; i < 5; i++) {
        pthread_create(&threads[i], NULL, thread_function, &lock);
```

```

}

// Join the threads
for (int i = 0; i < 5; i++) {
    pthread_join(threads[i], NULL);
}


return 0;
}

```

1.289 RPC (Remote Procedure Call)

Message passing in RPC

- The client calls the client stub. The call is a local procedure call, with parameters pushed on to the stack in the normal way.
- The client stub packs the parameters into a message and makes a system call to send the message. Packing the parameters is called **marshalling**.
- The client's local operating system sends the message from the client machine to the server machine.
- The local operating system on the server machine passes the incoming packets to the server stub.
- The server stub unpacks the parameters from the message. Unpacking the parameters is called **unmarshalling**.
- Finally, the server stub calls the server procedure. The reply traces the same steps in the reverse direction.



RPC Application Development

Here I'm using UBUNTU OS and C as the programming language in my simple example.

Steps involved in developing a RPC application developing:

- Specify the protocol for client server communication
- Develop the client program
- Develop the server program

1.289.1.1.1 Step1 : Specify the protocol for client server communication

An interface description language (IDL) to let various platforms call the RPC. The IDL files can then be used to generate code to interface between the client and servers. So, in IDL file, we define the program structure like below. Save this IDL file with **.x** extension.

calculate.x

```
1 struct inputs{  
2     float num1;  
3     float num2;  
4     char operator;  
5 };  
6  
7 program CALCULATE_PROG{  
8     version CALCULATE_VER{  
9         float ADD(inputs)=1;  
10        float SUB(inputs)=2;  
11        float MUL(inputs)=3;  
12        float DIV(inputs)=4;  
13    }=1;  
14 }=0x2fffffff;
```

inputs — Name of the data structure. Through this data structure the parameters are send to the server for computations.

CALCULATE_PROG — Name of the program


CALCULATE_VER — Name of the program version

ADD(inputs) — This is a remote method which is calling locally and the parameters are passed to that remote method through the inputs structure which contains 2 operands(2 numbers) and an operator.

A remote procedure is uniquely identified by the triple: (**program number, version number, procedure number**). Therefore, you need to give any numbers you like to the program, to the version and to the procedures as in the above sample IDL file.

Then compile your IDL file using rpcgen protocol compiler. The protocol compiler reads the definition of the IDL file and automatically generates client and server stubs. First you need to check whether the rpcbind has been installed in your machine. Type this command to check it and if the execution of the command gives you a long list as below in the image, then your machine has already installed rpcbind package and you can work on with the rpc commands.

\$ rpcinfo



```
Terminal File Edit View Search Terminal Help 23:51
shalika@shalika-VirtualBox: ~
shalika@shalika-VirtualBox:~$ rpcinfo
   program  version  netid    address          service
owner        100000      4    tcp6    ::.0.111
superuser    100000      3    tcp6    ::.0.111
superuser    100000      4    udp6    ::.0.111
superuser    100000      3    udp6    ::.0.111
superuser    100000      4    tcp     0.0.0.0.0.111
superuser    100000      3    tcp     0.0.0.0.0.111
superuser    100000      2    tcp     0.0.0.0.0.111
superuser    100000      4    udp     0.0.0.0.0.111
superuser    100000      3    udp     0.0.0.0.0.111
superuser    100000      2    udp     0.0.0.0.0.111
```


Otherwise, you have to install the **rpcbind** package by following below command and check whether it has been actually installed by typing the **\$ rpcinfo** command again.

```
$ sudo apt-get install rpcbind
```

Now your PC is ready to execute rpc commands. The next step is to compile your IDL file using **rpcgen** command.

```
$ rpcgen -a -C calculate.x
```

This command generated 7 additional files as displayed in the below picture. Keep in mind that, you can edit only the '['calculate_client.c'](#)' and '['calculate_server.c'](#)' files among from the created files according to your need. **Don't** do changes to other files.



- **calculate_client.c** —> client program (editable file)
- **calculate_server.c** —> server program (editable file)
- **calculate_clnt.c** —> client stub
- **calculate_svc.c** —> server stub
- **calculate_xdr.c** —> XDR(External Data Representation) filters
- **calculate.h** —> header file needed for any XDR filters
- **Makefile.calculate** —> compile all the source files by using this file

1.289.1.1.2 Step 2 – Develop the client program

Here i'm using C language as i said earlier, so, i edited the code in the **calculate_client.c** file like the way it accepts the client's inputs from the keyboard and outputs the remote procedures (add,sub,mul,div) invoking results to the client .

calculate_client.c

```

1#include "calculate.h"
2
3
4float calculate_prog_1(char *host,float n1,float n2,char opr,CLIENT *clnt)
5{

```

```
6
7 float *result_1;
8 inputs add_1_arg;
9 float *result_2;
10 inputs sub_1_arg;
11 float *result_3;
12 inputs mul_1_arg;
13 float *result_4;
14 inputs div_1_arg;
15
16 if(opr=='+'){
17
18     add_1_arg.num1=n1;
19     add_1_arg.num2=n2;
20     add_1_arg.operator=opr;
21
22     result_1 = add_1(&add_1_arg, clnt);
23     if (result_1 == (float *) NULL) {
24         clnt_perror (clnt, "call failed");
25     }
26     return *result_1;
27 }
28}
29
30 else if(opr=='-'){
31
32     sub_1_arg.num1=n1;
33     sub_1_arg.num2=n2;
34     sub_1_arg.operator=opr;
35
36     result_2 = sub_1(&sub_1_arg, clnt);
37     if (result_2 == (float *) NULL) {
38         clnt_perror (clnt, "call failed");
39     }
40     return *result_2;
41 }
42}
43
44 else if(opr=='*'){
45
46     mul_1_arg.num1=n1;
47     mul_1_arg.num2=n2;
48     mul_1_arg.operator=opr;
49
50     result_3 = mul_1(&mul_1_arg, clnt);
51     if (result_3 == (float *) NULL) {
52         clnt_perror (clnt, "call failed");
53     }
54     return *result_3;
55 }
```

```

56
57else if(opr=='/'){
58
59 div_1_arg.num1=n1;
60 div_1_arg.num2=n2;
61 div_1_arg.operator=opr;
62
63 if(n2 == 0){
64 printf("Division by zero is not valid.\n");
65 exit(0);
66 }else{
67
68 result_4 = div_1(&div_1_arg, clnt);
69 if (result_4 == (float *) NULL) {
70 clnt_perror (clnt, "call failed");
71 }
72 return *result_4;
73 }
74 }
75}
76}
77
78int main (int argc, char *argv[])
79{
80 char *host;
81 float a,b;
82 char op;
83 CLIENT *clnt;
84
85 if (argc < 2) {
86 printf ("usage: %s server_host\n", argv[0]);
87 exit (1);
88 }
89
90
91 printf("Welcome to Quick Cal!!!\n");
92 printf("+ for Addition\n- for Subtraction\n* for Multiplication\n/\n for Division\n");
93 printf("Enter number 1 :\n");
94 scanf("%f",&a);
95 printf("Enter number 2 :\n");
96 scanf("%f",&b);
97 printf("Enter the Operator :\n");
98 scanf("%s",&op);
99
100 host = argv[1];
101
102 clnt = clnt_create (host, CALCULATE_PROG, CALCULATE_VER, "udp");
103 if (clnt == NULL) {

```

```

106 clnt_pcreateerror (host);
107 exit (1);
108 }
109
110 printf("The Answer = %f\n",calculate_prog_1 (host,a,b,op,clnt));
111
112 clnt_destroy (clnt);
113
114 exit (0);
115 }
```

1.289.1.1.3 Step 3 – Develop the server program

Similarly you can edit the **calculate_server.c** file while adding your own codes for the previously defined remote methods(add,sub,mul,div).

calculate_server.c

```

1#include "calculate.h"
2
3float * add_1_svc(inputs *argp, struct svc_req *rqstp)
4{
5    static float result;
6
7    result = argp->num1+argp->num2;
8    printf("Got Request : Adding %f and %f\n",argp->num1,argp->num2);
9    printf("Sent Response : %f\n",result);
10
11    return &result;
12}
13
14float * sub_1_svc(inputs *argp, struct svc_req *rqstp)
15{
16    static float result;
17
18    result = argp->num1-argp->num2;
19    printf("Got Request : substituting %f from %f\n",argp->num2,argp->num1);
20    printf("Sent Response : %f\n",result);
21
22    return &result;
23}
24
25float * mul_1_svc(inputs *argp, struct svc_req *rqstp)
26{
27    static float result;
```

```

28 result = argp->num1*argp->num2;
29 printf("Got Request : Multiplying %f by %f\n",argp->num1,argp->num2);
30 printf("Sent Response : %f\n",result);
31
32 return &result;
33}
34
35 float * div_1_svc(inputs *argp, struct svc_req *rqstp)
36{
37 static float result;
38
39 result = argp->num1/argp->num2;
40 printf("Got Request : Dividing %f by %f\n",argp->num1,argp->num2);
41 printf("Sent Response : %f\n",result);
42
43 return &result;
44}
45

```

After editing the client and the server code, you need to compile the files. As usual, it's mandatory to compile the files if u made any changes. Otherwise those changes won't apply at the execution time. Use this command for compilation of files.


```
$ make -f Makefile.calculate
```

Take a new terminal. Then run the executable file of the client(calculate_client) which was created at the compile time.

```
type --> $ sudo ./calculate_client localhost
```


Now the client program is ready to accept keyboard inputs from the client. So, you can enter 2 numbers and an operator which gives the output to the client by invoking the remote procedures at the server side which the client has requested.

Client Terminal



```
Terminal File Edit View Search Terminal Help shalika@shalika-VirtualBox:~/RPC_Calculator1
shalika@shalika-VirtualBox:~$ cd RPC_Calculator1
shalika@shalika-VirtualBox:~/RPC_Calculator1$ sudo ./calculator_
client localhost
[sudo] password for shalika:
Welcome to Quick Cal!!!
+ for Addition
- for Substraction
* for Multiplication
/ for Division
Enter number 1 :
12
Enter number 2 :
8
Enter the Operator :
+
The Answer = 20.000000
shalika@shalika-VirtualBox:~/RPC_Calculator1$
```

Server Terminal



```
Terminal File Edit View Search Terminal Help shalika@shalika-VirtualBox:~/RPC_Calculator1
shalika@shalika-VirtualBox:~$ cd RPC_Calculator1
shalika@shalika-VirtualBox:~/RPC_Calculator1$ sudo ./calculator_
server
[sudo] password for shalika:
Got Request : Adding 12.000000 and 8.000000
Sent Response : 20.000000
shalika@shalika-VirtualBox:~/RPC_Calculator1$
```

- Caller stub, which has to...
 - Pack the argument
 - Transmit argument
 - Receive the result
 - Unpack the result
- Callee stub, which has to...
 - Receive the argument
 - Unpack argument
 - Call the function

- Pack the result
- Transmit the result

Our example is a pretty simple one, since we're just packing and sending a single int as the argument and receiving a single byte as a result. For the caller library, we can pack the data, create a socket, connect to a host (let's assume localhost for now), send the data, wait to receive, unpack, and then return. Here's what the header file looks like for the caller library:

```
// client/is_prime_rpc_client.h
#ifndef IS_PRIME_RPC_CLIENT_H
#define IS_PRIME_RPC_CLIENT_H

#include <stdbool.h>

bool is_prime_rpc(int number);

#endif
```

The astute (or just conscious) reader will notice that the interface is actually the exact same as when it was just the library, and this is the point! The caller doesn't have to worry about anything other than the business logic it's trying to send (but see caveats below). The implementation, on the other hand, is a little more complex:

```
// client/is_prime_rpc_client.c

#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <netdb.h>

#define SERVERPORT "5005" // The port the server will be listening on.
#define SERVER "localhost" // Assume localhost for now

#include "is_prime_rpc_client.h"

// Packs an int. We need to convert it from host order to network order.
int pack(int input) {
    return htons(input);
}

// Gets the IPv4 or IPv6 sockaddr.
```

```

void *get_in_addr(struct sockaddr *sa) {
    if (sa->sa_family == AF_INET) {
        return &(((struct sockaddr_in*)sa)->sin_addr);
    } else {
        return &(((struct sockaddr_in6*)sa)->sin6_addr);
    }
}

// Gets a socket to connect with.
int get_socket() {
    int sockfd;
    struct addrinfo hints, *server_info, *p;
    int number_of_bytes;

    memset(&hints, 0, sizeof hints);
    hints.ai_family = AF_UNSPEC;
    hints.ai_socktype = SOCK_STREAM; // We want to use TCP to ensure it gets there
    int return_value = getaddrinfo(SERVER, SERVERPORT, &hints, &server_info);
    if (return_value != 0) {
        fprintf(stderr, "getaddrinfo: %s\n", gai_strerror(return_value));
        exit(1);
    }

    // We end up with a linked-list of addresses, and we want to connect to the
    // first one we can
    for (p = server_info; p != NULL; p = p->ai_next) {
        // Try to make a socket with this one.
        if ((sockfd = socket(p->ai_family, p->ai_socktype, p->ai_protocol)) == -1) {
            // Something went wrong getting this socket, so we can try the next one.
            perror("client: socket");
            continue;
        }
        // Try to connect to that socket.
        if (connect(sockfd, p->ai_addr, p->ai_addrlen) == -1) {
            // If something went wrong connecting to this socket, we can close it and
            // move on to the next one.
            close(sockfd);
            perror("client: connect");
            continue;
        }

        // If we've made it this far, we have a valid socket and can stop iterating
        // through.
        break;
    }

    // If we haven't gotten a valid sockaddr here, that means we can't connect.
    if (p == NULL) {
        fprintf(stderr, "client: failed to connect\n");
        exit(2);
    }
}

```

```

}

// Otherwise, we're good.
return sockfd;
}

// Client side library for the is_prime RPC.
bool is_prime_rpc(int number) {

    // First, we need to pack the data, ensuring that it's sent across the
    // network in the right format.
    int packed_number = pack(number);

    // Now, we can grab a socket we can use to connect see how we can connect
    int sockfd = get_socket();

    // Send just the packed number.
    if (send(sockfd, &packed_number, sizeof packed_number, 0) == -1) {
        perror("send");
        close(sockfd);
        exit(0);
    }

    // Now, wait to receive the answer.
    int buf[1]; // Just receiving a single byte back that represents a boolean.
    int bytes_received = recv(sockfd, &buf, 1, 0);
    if (bytes_received == -1) {
        perror("recv");
        exit(1);
    }

    // Since we just have the one byte, we don't really need to do anything while
    // unpacking it, since one byte in reverse order is still just a byte.
    bool result = buf[0];

    // All done! Close the socket and return the result.
    close(sockfd);
    return result;
}

```

As mentioned earlier, this client code needs to pack the argument, connect to the server, send the data, receive the data, unpack it, and return it. This is relatively simple for our example, since we just need to ensure the byte order of the number is in the network order.

Next, we need to run the callee library on the server. It will call the `is_prime` library we wrote earlier, which now lives entirely on the server.

```

// server/is_prime_rpc_server.c

#include <stdio.h>

```

```

#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <string.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netdb.h>
#include <arpa/inet.h>
#include <sys/wait.h>
#include <signal.h>

#include "is_prime.h"

#define SERVERPORT "5005" // The port the server will be listening on.

// Gets the IPv4 or IPv6 sockaddr.
void *get_in_addr(struct sockaddr *sa) {
    if (sa->sa_family == AF_INET) {
        return &(((struct sockaddr_in*)sa)->sin_addr);
    } else {
        return &(((struct sockaddr_in6*)sa)->sin6_addr);
    }
}

// Unpacks an int. We need to convert it from network order to our host order.
int unpack(int packed_input) {
    return ntohs(packed_input);
}

// Gets a socket to listen with.
int get_and_bind_socket() {
    int sockfd;
    struct addrinfo hints, *server_info, *p;
    int number_of_bytes;

    memset(&hints, 0, sizeof hints);
    hints.ai_family = AF_UNSPEC;
    hints.ai_socktype = SOCK_STREAM; // We want to use TCP to ensure it gets there
    hints.ai_flags = AI_PASSIVE; // Just use the server's IP.
    int return_value = getaddrinfo(NULL, SERVERPORT, &hints, &server_info);
    if (return_value != 0) {
        fprintf(stderr, "getaddrinfo: %s\n", gai_strerror(return_value));
        exit(1);
    }

    // We end up with a linked-list of addresses, and we want to connect to the
    // first one we can
    for (p = server_info; p != NULL; p = p->ai_next) {
        // Try to make a socket with this one.

```

```

if ((sockfd = socket(p->ai_family, p->ai_socktype, p->ai_protocol)) == -1) {
    // Something went wrong getting this socket, so we can try the next one.
    perror("server: socket");
    continue;
}
// We want to be able to reuse this, so we can set the socket option.
int yes = 1;
if (setsockopt(sockfd, SOL_SOCKET, SO_REUSEADDR, &yes, sizeof(int)) == -1) {
    perror("setsockopt");
    exit(1);
}
// Try to bind that socket.
if (bind(sockfd, p->ai_addr, p->ai_addrlen) == -1) {
    // If something went wrong binding this socket, we can close it and
    // move on to the next one.
    close(sockfd);
    perror("server: bind");
    continue;
}

// If we've made it this far, we have a valid socket and can stop iterating
// through.
break;
}

// If we haven't gotten a valid sockaddr here, that means we can't connect.
if (p == NULL) {
    fprintf(stderr, "server: failed to bind\n");
    exit(2);
}

// Otherwise, we're good.
return sockfd;
}

int main(void) {

int sockfd = get_and_bind_socket();

// We want to listen forever on this socket
if (listen(sockfd, /*backlog=*/1) == -1) {
    perror("listen");
    exit(1);
}
printf("Server waiting for connections.\n");

struct sockaddr their_addr; // Address information of the client
socklen_t sin_size;
int new_fd;
while(1) {

```

```

sin_size = sizeof their_addr;
new_fd = accept(sockfd, (struct sockaddr *)&their_addr, &sin_size);
if (new_fd == -1) {
    perror("accept");
    continue;
}

// Once we've accepted an incoming request, we can read from it into a buffer.
int buffer;
int bytes_received = recv(new_fd, &buffer, sizeof buffer, 0);
if (bytes_received == -1) {
    perror("recv");
    continue;
}

// We need to unpack the received data.
int number = unpack(buffer);
printf("Received a request: is %d prime?\n", number);

// Now, we can finally call the is_prime library!
bool number_is_prime = is_prime(number);
printf("Sending response: %s\n", number_is_prime ? "true" : "false");

// Note that we don't have to pack a single byte.

// We can now send it back.
if (send(new_fd, &number_is_prime, sizeof number_is_prime, 0) == -1) {
    perror("send");
}
close(new_fd);
}

}

Finally, we can update our main function that runs on the client to use the new RPC library
call:
```

```

// client/basic_math_program_distributed.c
#include <stdio.h>
#include <stdbool.h>

#include "is_prime_rpc_client.h"

int main(void) {
    // Prompt the user to enter a number.
    printf("Please enter a number: ");
    // Read the user's number. Assume they're entering a valid number.
    int input_number;
    scanf("%d", &input_number);
```

```

// Check if it's prime, but now via the RPC library
if (is_prime_rpc(input_number)) {
    printf("%d is prime\n", input_number);
} else {
    printf("%d is not prime\n", input_number);
}

return 0;
}

```

1.290 Ether Types

1. **IPv4**: 0x0800 (2048 in decimal)
2. **IPv6**: 0x86DD (34525 in decimal)
3. **Address Resolution Protocol (ARP)**: 0x0806 (2054 in decimal)
4. **Reverse Address Resolution Protocol (RARP)**: 0x8035 (32821 in decimal)
5. **AppleTalk**: 0x809B (32923 in decimal)
6. **AppleTalk ARP**: 0x80F3 (33011 in decimal)
7. **DECnet Phase IV**: 0x8137 (33079 in decimal)
8. **Xerox NS IDP**: 0x0600 (1536 in decimal)
9. **Ethernet Loopback Test**: 0x9000 (36864 in decimal)
10. **802.1Q VLAN Tagging**: 0x8100 (33024 in decimal)
11. **PPP (Point-to-Point Protocol)**: 0x880B (34827 in decimal)
12. **MPLS (Multiprotocol Label Switching)**: 0x8847 (34855 in decimal)
13. **PPPoE Discovery Stage**: 0x8863 (34915 in decimal)
14. **PPPoE Session Stage**: 0x8864 (34916 in decimal)
15. **Link Layer Discovery Protocol (LLDP)**: 0x88CC (35020 in decimal)
16. **Cisco Discovery Protocol (CDP)**: 0x2000 (8192 in decimal)
17. **IEEE 802.1X Authentication**: 0x888E (34958 in decimal)
18. **IEEE 802.1Qbg Edge Virtual Bridging (EVB)**: 0x8946 (35142 in decimal)
19. **IPv6 over IPv4 tunneling (6in4)**: 0x86DD (34525 in decimal)
20. **IPv4 over IPv6 tunneling (4in6)**: 0x0800 (2048 in decimal)
21. **Ethernet OAM Protocol (Ethernet in the First Mile)**: 0x8809 (34825 in decimal)
22. **Ethernet CFM (Connectivity Fault Management)**: 0x8902 (35010 in decimal)
23. **EtherCAT Protocol**: 0x88A4 (34980 in decimal)
24. **TRILL (Transparent Interconnection of Lots of Links)**: 0x22F3 (8947 in decimal)
25. **Fibre Channel over Ethernet (FCoE)**: 0x8906 (35014 in decimal)
26. **IEEE 802.11 Wireless LANs**: 0x88B4 (34996 in decimal)
27. **InfiniBand**: 0x8915 (35029 in decimal)
28. **FCoE Initialization Protocol (FIP)**: 0x8914 (35028 in decimal)

29. **HomePlug AV MME (Multimedia over Powerline Alliance Management Message)**: 0x887B (34939 in decimal)
30. **IEEE 802.3 Control**: 0x8808 (34824 in decimal)
31. **Provider Backbone Bridges (PBB)**: 0x88E7 (35047 in decimal)
32. **IEEE 802.1AE MAC Security (MACsec)**: 0x88E5 (35045 in decimal)
33. **IEEE 802.1AX Link Aggregation**: 0x8809 (34825 in decimal)
34. **IEEE 802.11 Management Frames**: 0x888E (34958 in decimal)
35. **IEEE 802.11 Data Frames**: 0x8863 (34915 in decimal)
36. **IEEE 802.11 Control Frames**: 0x8864 (34916 in decimal)
37. **IEEE 802.11 Beacon Frames**: 0x8865 (34917 in decimal)
38. **Ethernet Configuration Testing Protocol (ECP)**: 0x8808 (34824 in decimal)
39. **Ethernet Audio/Video Bridging (AVB) Transport Protocol**: 0x22EA (8938 in decimal)
40. **Ethernet Audio/Video Bridging (AVB) Protocol Type**: 0x22EB (8939 in decimal)
41. **IEEE 802.1Qay Provider Backbone Bridge Traffic Engineering (PBB-TE)**: 0x8902 (35010 in decimal)
42. **IEEE 802.1Qaz Data Center Bridging Exchange (DCBX)**: 0x890D (35021 in decimal)
43. **IEEE 802.1Qbb Priority-based Flow Control (PFC)**: 0x8808 (34824 in decimal)
44. **LLDP (Link Layer Discovery Protocol)**: 0x88CC (35020 in decimal)
45. **IEEE 802.1ag Connectivity Fault Management (CFM)**: 0x8902 (35010 in decimal)
46. **IEEE 802.1ah Provider Backbone Bridges (PBB)**: 0x88E7 (35047 in decimal)
47. **IEEE 802.1Qbg Edge Virtual Bridging (EVB)**: 0x8946 (35142 in decimal)
48. **MAC-over-PDH (Multiplexing Over Pseudo-Wire)**: 0x888F (34959 in decimal)
49. **MAC-over-SDH (Multiplexing Over Pseudo-Wire)**: 0x8890 (34960 in decimal)
50. **MAC-over-SONET/SDH (Multiplexing Over Pseudo-Wire)**: 0x8891 (34961 in decimal)

1.291 Maximum Length Of A Concatenated String With Unique Characters

