

Package ‘encore.io’

December 2, 2024

Type Package

Title Functions and Wrappers To Streamline Analytics For The ENCORE Trial Emulation Project

Version 0.2.0

Description This package contains important functions to streamline the analytics for the ENCORE trial emulation project. This includes the query of eligible trials to emulate and most analytical steps to emulate these trials.

BugReports <https://gitlab.partners.org/drugapi/encore/encore.io>

License Apache License (>= 2)

Encoding UTF-8

LazyData true

Imports arrow,
assertthat,
data.table,
dplyr,
forcats,
glue,
ggplot2,
gt,
gtsummary,
parallel,
stringr,
survival,
tibble,
tidyr,
lifecycle,
lubridate,
magrittr,
MatchIt,
mice,
pROC,
WeightIt

RoxygenNote 7.3.1

Suggests anesrake,
cobalt,
devtools,
DT,
here,

knitr,
 locfit,
 MatchThem,
 rmarkdown,
 scales,
 simsurv,
 smdi,
 testthat ($\geq 3.0.0$)

Config/testthat/edition 3

Roxygen list(markdown = TRUE)

VignetteBuilder knitr

Depends R (≥ 2.10)

Contents

| | |
|------------------------------------|----|
| create_table1 | 3 |
| c_statistics | 4 |
| edb1_3_4_compute_ropro | 5 |
| edb1_cohorts | 6 |
| edb1_get_biomarker | 7 |
| edb1_get_demographics | 8 |
| edb1_get_diagnosis_heme | 10 |
| edb1_get_diagnosis_solid | 11 |
| edb1_get_ecog | 13 |
| edb1_get_histology | 14 |
| edb1_get_labs | 15 |
| edb1_get_os | 18 |
| edb1_get_vitals | 19 |
| edb1_query_ropro | 21 |
| edb2_assign_date | 23 |
| edb2_compute_ropro | 24 |
| edb2_get_biomarker | 25 |
| edb2_get_demographics | 26 |
| edb2_get_diagnosis_solid | 28 |
| edb2_get_ecog | 29 |
| edb2_get_histology | 31 |
| edb2_get_labs | 32 |
| edb2_get_os | 34 |
| edb2_get_vitals | 36 |
| edb2_path_helper | 37 |
| edb2_query_ropro | 38 |
| edb3_get_demographics | 39 |
| edb3_get_labs | 41 |
| edb3_get_vitals | 43 |
| edb4_get_biomarker | 45 |
| edb4_get_demographics | 46 |
| edb4_get_diagnosis_solid | 48 |
| edb4_get_ecog | 49 |
| edb4_get_histology | 51 |
| edb4_get_labs | 52 |

create_table1

3

edb4_get_os

54

edb4_get_vitals

55

edb4_query_ropro

57

ess

59

gt_tbl_compact

60

icd_metastases

61

imputation_workflow

61

km_pooling

62

n_fmt

64

power_survival

65

ps_balance_plot

66

qc_assertive_line_check

67

re_weight

68

simulate_flaura

70

Index

72

| | |
|---------------|---|
| create_table1 | Wrapper around gtsummary::tbl_summary() to create a beautiful Table 1 quickly |
|---------------|---|

Description

Create a table 1 fast

Usage

```
create_table1(  
  x = NULL,  
  covariates = NULL,  
  covariates_labels = NULL,  
  treat = "treat",  
  explicit_na_categorical = TRUE  
)
```

Arguments

- x

dataframe queried from edbx with treatment stratification variable and covariates to be displayed in the Table 1
- covariates

character vector of columns/covariate names to be displayed in Table 1
- covariates_labels

named character vector or list of formulas specifying variables labels of covariate-label pairs to display in table
- treat

character specifying column name of treatment variable
- explicit_na_categorical

logical, should missings in categorical variables be explicitly included as a separate category (default is TRUE)

Details

...

Value

object of class "tbl_summary" "gtsummary"

Examples

```
## Not run:
library(encore.io)
set global option to make gtsummary tables more compact
theme_gtsummary_compact()
table1 <- ard |>
  create_table1(
    covariate = table1_covariates$covariate,
    treat = "treat")

## End(Not run)
```

c_statistics

Calculates c-statistics for mimids/wimids objects

Description

[Experimental] Calculates the propensity score c-statistics (= area under the curve) for imputed and unmatched/all and matched datasets resulting from MatchThem::matchthem (mimids objects)

Usage

```
c_statistics(
  object = NULL,
  exposure = "treat",
  weights = "weights",
  ps = "distance"
)
```

Arguments

| | |
|----------|--|
| object | mimids or data.frame object from complete(..., action = 'long', all = TRUE, ...) |
| exposure | character, quoted name of the exposure/treatment variable (must be of class factor) |
| weights | character, quoted name of the variable indicating the matching weights (usually 0: unmatched and 1: matched) |
| ps | character, quoted name of the variable with the distance measure (e.g., propensity score) |

Details

The object input needs to be a mimids object or a data.frame object coming from MatchThem::matchthem(). If the mimids object is already converted to a long data.frame of stacked imputed datasets, the MatchThem::complete() function needs to be completed using action = "long" and all = TRUE arguments.

The function computes the c-statistic by computing the AUC in each imputed dataset and then summarizing the average and min/max c-statistic by matching group. This aims to describe how well treatment can be predicted given a patient's propensity score. The idea is that in well-matched or weighted datasets, the c-statistic should be close to 0.5, i.e., we can't infer treatment propensity anymore given a patient's baseline covariates.

Value

tibble with summary c-statistics across imputed datasets

See Also

Franklin JM, Rassen JA, Ackermann D, Bartels DB, Schneeweiss S. Metrics for covariate balance in cohort studies of causal effects. *Stat Med*. 2014 May 10;33(10):1685-99. doi: 10.1002/sim.6058. Epub 2013 Dec 9. PMID: 24323618.

Examples

```
## Not run:
library(encore.io)

c_statistics(
  object = edb1_mimids,
  exposure = "treat",
  ps = "distance"
)

## End(Not run)
```

edb1_3_4_compute_ropro

Derive ROPRO prognostic score

Description

This function computes ROPRO prognostic score (Becker, Weberpals, et al., *Ann Oncol* 2020) for a given inception cohort.

Usage

```
edb1_3_4_compute_ropro(
  x = NULL,
  cancer = c("aNSCLC", "MetastaticBreast", "EarlyBreast", "MetastaticCRC",
    "MultipleMyeloma")
)
```

Arguments

| | |
|--------|--|
| x | dataframe with inception cohort and required ROPRO covariates |
| cancer | character, what cancer-specific ROPRO should be computed ("aNSCLC", "MetastaticBreast", "EarlyBreast", "MetastaticCRC", "MultipleMyeloma") |

Details

This function takes in a dataframe with all required variables to compute the general and cancer-specific ROPRO (specified in cancer). The variables need to be queried and transformed before which can be done through the `edb(x)_query_ropro` functions (specific for each database).

Important: This function is only valid for data coming from EDB1, EDB3 and EDB4. Since EDB2 does not have all required variables, please use the `edb2_compute_ropro` function for this database to compute a reduced ROPRO model.

Value

The function returns `x` with the final general and cancer-specific ROPRO

Examples

```
## Not run:
library(encore.io)

x_ropro <- x |>
  edb_4_query_ropro(
    index_date = "dt_index",
    path = Sys.getenv("path_edb4"),
    cancer = "NSCLC",
    max_lookback = -90,
    verbose = TRUE
  ) |>
  edb_1_3_4_compute_ropro(
    cancer = "aNSCLC"
  )

## End(Not run)
```

edb1_cohorts

System data used to streamline functions and analysis

Description

System data used to streamline functions and analysis

Usage

```
edb1_cohorts
```

Format

edb1_cohorts:

A tibble with edb1-specific mappings

cancer Abbreviated cancer types

cohort Cancer type sub-directory

biomarker Cancer type biomarker tables

special_biomarker_cols Special biomarker columns to select ...

| | |
|--------------------|---|
| edb1_get_biomarker | <i>Query biomarker information for a given inception cohort</i> |
|--------------------|---|

Description

Function queries biomarker tables and curates information on alterations in defined driver genes.

Usage

```
edb1_get_biomarker(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  biomarker_name = NULL,
  from = -90,
  to = 0,
  label_name = FALSE
)
```

Arguments

| | |
|----------------|---|
| x | dataframe queried with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", or "MetastaticBreast" |
| biomarker_name | character, name of biomarker/gene alteration (see details) |
| from | integer, left boundary of biomarker measurement window relative to index date (e.g., -90, indicating biomarker should be measured not before 90 days before index date) |
| to | integer, right boundary of biomarker measurement window relative to index date (e.g., 0, indicating biomarker should be measured until day of index date (inclusive)) |
| label_name | logical, should variable name carry information about the measurement window |

Details

The function queries and categorizes a certain biomarker that was collected and curated as part of the database as either positive or negative. The categorization happens according to if the biomarker mutation/alteration is a clinically actionable one. For example, patients with any mutation in the EGFR gene or MSI-H/dMMR status would be classified as positive. In case there are multiple measurements per biomarker and patient, the time point of measurement is defined as the non-missing biomarker result in the covariate ascertainment window given by 'from' and 'to' that is closest to the index date. The biomarker date (dt_(biomarker)) in this database is defined as the earliest of specimen collected date, specimen received date or result date.

Depending on the cancer type, the biomarker names can be: ALK, BRAF, EGFR, HER2/ERBB2, KRAS, MET, NTRK1, NTRK2, NTRK3, PDL1, RET, ROS1, NTRK - unknown gene type, NTRK - other, MMR/MSI, NRAS, ER, HER2, Ki-67, PR, BRCA, ESR1, Oncotype, Mammaprint, PIK3CA

Value

x with all additional biomarker variables joined, that is:

- `c_(biomarker_name)_status_(from)_(to)` (binary, biomarker mutation status positive or negative)
- `c_(biomarker_name)_detail_(from)_(to)` (character string, more details about selected measurement)
- `c_(biomarker_name)_detail_all_(from)_(to)` (character string, this provides details about all results and details for this biomarker if there were multiple tests in the measurement window (from, to))
- `c_(biomarker_name)_distance_(from)_(to)` (numeric, relative distance between date of measurement and index date in days)
- `dt_(biomarker_name)_(from)_(to)` (date, date of selected biomarker measurement)

Examples

```
## Not run:
library(encore.io)

## End(Not run)
```

`edb1_get_demographics` *Query demographic variables for an inception cohort*

Description

Function queries all available demographic variables fro a given inception cohort.

Usage

```
edb1_get_demographics(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL
)
```

Arguments

| | |
|------------|---|
| x | dataframe queried with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |

Details

Some important data curation details include:

- Race and Ethnicity are combined into a new combined variable 'dem_race_ethnicity' with five mutually exclusive groups as defined by SEER. However, EDB1 has a larger "Other" race category since "American Indian or Alaska Native" seems to be not coded as such, i.e., as opposed to other datasets, "Other" is an explicit group in this case
- The date of birth DOB is given on year granularity level and is hence imputed to the mid of the year as <dt_dob_imputed>, e.g. 1955 becomes 1955-07-02. This affects all variables which are derived from the date of birth such as all age variables
- Smoking history is assessed as a history of current or former (= smoking history) or never (= no smoking history). There is no date associated with the measurement of smoking history.

Value

x with all additional demographic variables joined, that is, ADD NEW VARIABLE NAMES

- dem_age_initial_diagnosis (categorical, categorized age measured at initial cancer diagnosis: <60, 60-69, 70-79, 80+)
- dem_age_le_18_flag (logical, indicating if patients was at least (larger/equal; le) 18 years of age at index date)
- dem_age_index_cont (continuous, age measured at index date; note: date of birth has only year-granularity, hence age is imprecise)
- dem_age_index (nominal, categorized age measured at index date: <60, 60-69, 70-79, 80+)
- dem_sex (binary, Male, Female)
- dem_race (nominal)
- dem_ethnicity (binary)
- dem_race_ethnicity (categorical, classification into five mutually exclusive groups according to SEER)
- dem_state (character, US state of the center/network the patient is receiving care at)
- dem_region (nominal, region of the center/network the patient is receiving care at, can be Midwest, Northeast, South, West)
- dem_practice (nominal, setting patient is receiving care at, i.e. Academic, Community or both)
- dem_ses (nominal, socioeconomic status (SES) index based on residence area of patient; can be from '1 - Lowest SES' through '5 - Highest SES')
- c_smoking_history (logical, history of smoking; TRUE = History of smoking, FALSE = No history of smoking)

Examples

```
## Not run:
library(encore.io)

analysis_cohort <- x |>
  edb1_get_demographics(
    index_date = "dt_index",
    cancer = "aNSCLC"
  )

## End(Not run)
```

edb1_get_diagnosis_heme

Query diagnostic details for heme tumors in EDB1 database

Description

Function queries diagnosis details including ISS staging information.

Usage

```
edb1_get_diagnosis_heme(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = "MultipleMyeloma"
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb1 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, so "MultipleMyeloma" |

Details

Function queries diagnosis details for all patients in .

- ISS stage (c_stage_initial_dx) is curated for multiple myeloma patients and "Unknown/not documented" is mapped to NA
- M protein IgG is derived and if the patient's immunoglobulin class of M protein is not documented, an NA is assigned
- Light chain Kappa and Lambda information is derived and if the patient's involved light chain is not documented, an NA is assigned
- Experimental: The number and location of secondary malignancies is inferred by C79.x ICD-10 codes (and corresponding ICD-9 mappings). The c_number_met_sites is inferred by counting the unique number of sites as given by a C79.x granularity in the secondary diagnosis table. For more see icd_metastases system file.

Value

x with all additional diagnosis variables joined, that is:

- dt_initial_dx (date, date of diagnosis or first documented diagnosis date for tumor)
- c_stage_initial_dx (nominal, summary ISSS stage at initial diagnosis)
- c_time_dx_to_index (continuous, time between initial diagnosis and index date (in days))
- c_m_protein_igg (logical, whether the patient's immunoglobulin class of M protein is IgG)
- c_light_chain_kappa (logical, whether the patient's involved light chain is Kappa)

- `c_light_chain_lambda` (logical, Whether the patient's involved light chain is Lambda)

Experimental:

- `c_number_met_sites` (integer, number of metastatic sites for a given patient anytime before/on index date (inferred from ICD codes, see `icd_metastases` system file)
- `c_met_sites` (character string, description of anatomical locations of metastatic sites for a given patient patient's index date)

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb1_get_diagnosis_heme(
    index_date = "dt_index",
    path = Sys.getenv("path_edb1"),
    cancer = "MultipleMyeloma"
  )

## End(Not run)
```

```
edb1_get_diagnosis_solid
```

Query initial and metastatic diagnosis dates for EDB1 database

Description

Function queries diagnosis details including staging information.

Usage

```
edb1_get_diagnosis_solid(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL
)
```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | dataframe queried from edb1 with at least patient ids and index date of inception cohort |
| <code>index_date</code> | character, variable/column name with the patient's index_date, default is <code>dt_index</code> |
| <code>path</code> | character string, path to directory where EDB1 data/files are located |
| <code>cancer</code> | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |

Details

Function queries diagnosis details for all patients in .

- Summary group stage (`c_stage_initial_dx`) is curated for advanced and metastatic enhanced cohorts and "Not documented", "Occult", "Unknown", "Group stage is not reported" is mapped to NA
- For early cohorts (early NSCLC and breast), summary group stage (`c_stage_initial_dx`) is derived from the pathological group stage or from clinical group stage if the pathological is not available
- For aNSCLC, the metastatic diagnosis date (`dt_met_dx`) is derived as the the of initial diagnosis for patients with stage IV diagnosis or the machine learning-derived metastatic diagnosis date. All other solid tumor for which the metastatic diagnosis date is available, this variable was used
- The number and location of metastatic sites is inferred by C79.x ICD-10 codes (and corresponding ICD-9 mappings). The `c_number_met_sites` is inferred by counting the unique number of sites as given by a C79.x granularity in the secondary diagnosis table. For more see `icd_metastases` system file.

The function also returns `<c_met_pre_index>` which is a helper variable that is TRUE in case there is any evidence of at least one distant metastatic diagnosis before or on the index date. This captures both de novo metastatic patients and those with a metastatic diagnosis date before/on the index date. Note: if neither group stage nor metastatic diagnosis date are available, we set `<c_met_pre_index>` to NA because we can't make say they're FALSE either

Value

x with all additional diagnosis variables joined, that is:

- `dt_initial_dx` (date, date of diagnosis or first documented diagnosis date for tumor)
- `c_stage_initial_dx` (nominal, summary group stage at initial diagnosis, if available)
- `dt_met_dx` (date, date of earliest evidence of distant metastasis)
- `c_de_novo_mets_dx` (binary logical, evidence of presence of one or multiple metastases at/before initial diagnosis)
- `c_time_dx_to_index` (continuous, time between initial diagnosis and index date (in days))
- `c_time_adv_dx_to_index` (continuous, time between advanced diagnosis and index date (in days; advanced NSCLC only))
- `c_time_met_dx_to_index` (continuous, time between earliest evidence of a metastatic diagnosis and index date (in days; not in early NSCLC))
- `c_met_pre_index` (binary logical, evidence of any metastasis before/on index date; includes de novo metastatic patients and progressors (overlap with `c_de_novo_mets_dx` possible))
- `c_number_met_sites` (integer, number of metastatic sites for a given patient anytime before/on index date (inferred from ICD codes, see `icd_metastases` system file))
- `c_met_sites` (character string, description of anatomical locations of metastatic sites for a given patient patient's index date)

Examples

```
## Not run:
library(encore.io)
```

```
ard <- x |>
  edb1_get_diagnosis_solid(
    index_date = "dt_index",
    path = Sys.getenv("path_edb1"),
    cancer = "aNSCLC"
  )

## End(Not run)
```

edb1_get_ecog

Query performance status information for an inception cohort

Description

Function queries ECOG performance status tables and curates derived variables

Usage

```
edb1_get_ecog(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  label_name = FALSE,
  verbose = TRUE
)
```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | dataframe queried with at least patient ids and index date of inception cohort |
| <code>index_date</code> | character, variable/column name with the patient's index_date |
| <code>path</code> | character string, path to directory where EDB1 data/files are located |
| <code>cancer</code> | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| <code>from</code> | integer, left boundary of ECOG measurement window relative to index date (e.g., -90, indicating ECOG should be measured not before 90 days before index date) |
| <code>to</code> | integer, right boundary of ECOG measurement window relative to index date (e.g., 0, indicating ECOG should be measured until day of index date (inclusive)) |
| <code>ties</code> | character, one of "lower" or "higher" to choose either the lower (default) or higher ECOG measurement if there are two measurements on the same day |
| <code>label_name</code> | logical, should variable name carry information about the measurement window |
| <code>verbose</code> | logical, print query progress and informative meta information |

Details

The function considers both NLP-extracted and structured ECOG measurements (to enhance the availability of ECOG measurements). All ECOG measurements are identified within the baseline measurement window, then the closest measurement relative to the index date is selected. If there are two measurements within the same closest distance, the lower (default) or higher (depending on how ties is specified) is prioritized.

Value

x with all additional ECOG variables joined, that is:

- `c_ecog_{from}_{to}`, ECOG value measured in the specified measurement window
- `c_ecog_{from}_{to}`, distance of the date the ECOG value was measured relative to the index date

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb1_get_ecog(
    cancer = "aNSCLC",
    from = -180,
    to = 0,
    ties = "lower"
  )

## End(Not run)
```

| | |
|--------------------|--|
| edb1_get_histology | <i>Query histology information for an inception cohort</i> |
|--------------------|--|

Description

Function queries histology information for a given inception cohort.

Usage

```
edb1_get_histology(
  x = NULL,
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  histology_match = NULL
)
```

Arguments

| | |
|-----------------|--|
| x | dataframe with at least patient ids and index date of inception cohort |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| histology_match | character, string match to categorize and identify patients with a certain histology for the indicated tumor site, e.g. "non-squamous cell carcinoma". |

Details

Some patients may have more than one histology recording across cohorts since they can have multiple primaries. However, this function is designed to query histology information for one cancer type at a time. That means, there is just one recording per patient. For general frequency descriptives, see vignettes for EDB1.

Note that the search string defined in argument `histology_match` is not case sensitive.

Value

x with all additional histology variables joined, prepended with "c_"

- `c_histology` (nominal, histology recorded for given patient)
- `c_(histology_match)` (logical, there is a string match for histology specified by `histology_match`. FALSE may also include "unknowns" or "NOS" whose information was just not granular enough to be able to determine the histological subtype with absolute certainty)

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edbl_get_histology(
    cancer = "aNSCLC",
    histology_match = "Non-squamous cell carcinoma"
  )

## End(Not run)
```

edbl_get_labs

Query lab information for a given inception cohort

Description

Function queries the lab table and standardizes according to a reference measurement unit.

Usage

```

edb1_get_labs(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  lab_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = TRUE
)

```

Arguments

| | |
|--------------------|--|
| x | dataframe queried from EDB1 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| lab_name | character, curated name of lab (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA? Lower and upper thresholds are documented in labs_mapping_edb1 |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans supported lab measurements. In detail, the function selects measurements in a from - to measurement window relative to the index date. The date of the lab test is derived as the earliest of the test date or result date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

Note: Only selected labs are supported by this function which were taken from the ROPRO prognostic score (Becker T et al., Ann Oncol 2020).

The supported and available labs are:

- c_albumin_g_l (albumin mass/volume in serum or plasma)
- c_alp_u_l (alkaline phosphatase enzymatic activity/volume in serum or plasma)
- c_alt_u_l (alanine aminotransferase enzymatic activity/volume in serum or plasma)
- c_ast_u_l (aspartate aminotransferase enzymatic activity/volume in serum or plasma; used to compute ast-alt ratio)
- c_bilirubin_mg_dl (total bilirubin mass/volume in serum or plasma)
- c_calcium_mg_dl (calcium mass/volume in serum or plasma)
- c_chloride_mmol_l (chloride moles/volume in serum or plasma)
- c_eosinophils_leukocytes_ratio (eosinophils/100 leukocytes in blood)
- c_glucose_mg_dl (glucose mass/volume in serum or plasma)
- c_granulocytes_leukocytes_ratio (granulocytes/100 leukocytes in blood)
- c_hemoglobin_g_dl (hemoglobin mass/volume in blood)
- c_ldh_u_l (lactate dehydrogenase enzymatic activity/volume in serum or plasma)
- c_lymphocyte_10_9_l (lymphocytes #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_lymphocyte_leukocyte_ratio (lymphocytes/100 leukocytes in blood)
- c_monocytes_10_9_l (monocytes #/volume in blood)
- c_neutrophil_10_9_l (neutrophils #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_platelets_10_9_l (platelets #/volume in blood)
- c_protein_g_l (protein mass/volume in Serum or Plasma)
- c_urea_nitrogen_mg_dl (urea nitrogen mass/volume in serum or plasma)

The following labs are part of ROPRO but are not supported yet:

- c_light_chain_kappa (Light Chain Kappa; dichotomous; >0 vs. 0)
- c_light_chain_lambda (Light Chain Lambda; dichotomous; >0 vs. 0)
- c_m_protein_igg (M protein IgG (dichotomous; >0 vs. 0))

Value

x with all additional labs variables joined, that is:

- c_(lab_name)_distance_(from)_(to) - days from date of lab measurements to index date
- c_(lab_name)_(unit)_(from)_(to) - binary lab result indicating if lab was within ("normal") the reference range or outside ("abnormal")
- c_(lab_name)_(unit)_(from)_(to)_cont - quantitative lab result after unit harmonization/conversion

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb1_get_labs(
    cancer = "aNSCLC",
    lab_name = "c_albumin_g_l",
    set_implausible_na = TRUE,
    verbose = TRUE
  )

## End(Not run)
```

| | |
|-------------|--|
| edb1_get_os | <i>Query overall survival outcome for a given inception cohort</i> |
|-------------|--|

Description

Function queries mortality and other information to derive a righ-censored time to all-cause mortality endpoint

Usage

```
edb1_get_os(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  data_cut_off_date = lubridate::ymd("2024-04-30"),
  verbose = TRUE
)
```

Arguments

| | |
|-------------------|--|
| x | dataframe queried from edb1 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where data/files are located |
| cancer | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| data_cut_off_date | date of database lock; the data cut-off for this delivery (May 30, 2024) is April 30, 2024. This parameter can be changed if a grace period of x months before database lock is desired. |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and curates intention-to-treat (ITT) overall survival endpoint. The ITT follow up time is defined as the time from index date (dt_index) to date of death. If a patient did not decease during follow-up, the patient will be censored at the last observed clinical activity (including visits and treatment information) or data cut-off date whichever is earlier.

Note that in EDB1, the granularity of the date of death variable is given as month-year and (in rare cases) year only. In these cases, the date of death is imputed to the mid/15th of the month and the mid/July 2 of the year, respectively. This can lead to negative/implausible follow-up times if the index date is after the imputed date of death.

Value

x with all endpoint information joined, that is:

- death_itt (binary, event indicator for all-cause mortality)
- fu_itt_days (numeric, ITT follow-up time in days)
- fu_itt_months, (numeric, ITT follow-up time in months (i.e., fu_itt_days / 30.417))
- fu_itt_years, (numeric, ITT follow-up time in years)

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edbl_get_os(
    cancer = "aNSCLC"
  )

## End(Not run)
```

edbl_get_vitals

Query vital sign measurements for a given cohort

Description

Function queries vitals sign measurements

Usage

```
edbl_get_vitals(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  vital_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
```

```

    label_name = FALSE,
    verbose = TRUE
)

```

Arguments

| | |
|--------------------|--|
| x | dataframe queried from EDB1 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| vital_name | character, curated name of vital sign (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in vitals_mapping_edb1 |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans all available vital sign measurements. In detail, the function removes measurements that are character strings and only considers quantitative results. In EDB1, unit-cleaned vital sign measurements are provided. However, due to frequent missing units, unit-cleaned vital sign measurements can exhibit high missingness. To mitigate this missingness, the function also considers "raw" vital sign measurements if no unit-cleaned measurement is observed. Hence, it is recommended to set `set_implausible_na` to TRUE to remove implausible values. The function further only selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

The available and supported vitals are:

- c_sbp (systolic blood pressure in mmHg)
- c_dbp (diastolic blood pressure in mmHg)
- c_bmi (body mass index in kg/m² directly measured)
- c_height (height in m)
- c_hr (heart rate/pulse in beats/min)
- c_oxygen (oxygen saturation; taken from O2 sat and pulse oximetry)
- c_weight (weight in kg)

Value

x with all additional labs variables joined, that is:

- `c_(vital_name)_distance_(from)_(to)` - days from date of vital sign measurements to index date
- `c_(vital_name)_(unit)_(from)_(to)_cont` - quantitative vital sign measurement

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb1_get_vitals(
    cancer = "aNSCLC",
    vital_name = "c_oxygen",
    set_implausible_na = TRUE,
    verbose = TRUE
  )

## End(Not run)
```

edb1_query_ropro

Query and curate all relevant ROPRO variables

Description

This function queries, cleans and transforms all necessary covariates needed to compute the ROPRO prognostic score in EDB1.

Usage

```
edb1_query_ropro(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb1"),
  cancer = NULL,
  from = -90,
  to = 0,
  verbose = TRUE
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from EDB1 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index date, default is dt_index |

| | |
|---------|---|
| path | character string, path to directory where EDB1 data/files are located |
| cancer | character, one of "aNSCLC", "CRC", "EarlyBreast", "EarlyNSCLC", "MetastaticBreast" or "MultipleMyeloma" |
| from | integer, left boundary of measurement window for time-dependent variables relative to index date (e.g., -90, indicating variables should be measured not before 90 days before index date) |
| to | integer, right boundary of measurement window for time-dependent variables relative to index date (e.g., 0, indicating variables should be measured not later than the day of the index date (inclusive)) |
| verbose | logical, print progress of query |

Details

Wrapper around major functions to query required covariates to compute ROPRO. Selected covariates are log transformed or log-log transformed. More details, see Becker, Weberpals, et al., Ann Oncol 2020.

Value

x with all required ROPRO covariates joined. All general and cancer type-specific (as specified in cancer argument) covariates are returned.

Note that:

- there is no specific ROPRO for EarlyNSCLC, so only the covariates for the general pan-tumor ROPRO will be returned
- there is only a ROPRO for metastatic CRC (no early CRC)
- covariates for EarlyBreast are identical to the the general pan-tumor ROPRO, just the weights are different

Examples

```
## Not run:
library(encore.io)

x_ropro <- x |>
  edb1_query_ropro(
    index_date = "dt_index",
    path = Sys.getenv("path_edb1"),
    cancer = "aNSCLC",
    from = -90,
    to = 0,
    verbose = TRUE
  )

## End(Not run)
```

| | |
|------------------|--|
| edb2_assign_date | <i>Helper function to assign an actual date for a xxx_timedelta variable in edb2</i> |
|------------------|--|

Description

In the edb2 database, time differences (timedelta) are assigned for clinical events. These timedeltas are always relative to the initial cancer diagnosis for which a given patient sampled into the database. This function helps to assign actual dates based on on those time differences.

Usage

```
edb2_assign_date(
  x = NULL,
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC")
)
```

Arguments

| | |
|--------|---|
| x | dataframe queried from edb2 with at least the patient id column and columns that end on "timedelta" |
| path | string, path to edb2 root directory |
| cancer | character, either "NSCLC" or "MM" |

Details

CAVEAT: both the date of initial diagnosis and other dates come with imprecision (_imp). There are 3 possibilities: 0: There is no imprecision. precise date (MM/DD/YYYY) associated with this event. 15: There is imprecision. imprecise date (MM/YYYY) associated with this event. 182: There is imprecision.imprecise date (YYYY) associated with this event.

Value

x including the date colum(s) of all timedelta columns (.col) with naming convention dt_{.col}"

Examples

```
## Not run:
library(encore.io)
```

```
## End(Not run)
```

| | |
|--------------------|--------------------------------------|
| edb2_compute_ropro | <i>Derive ROPRO prognostic score</i> |
|--------------------|--------------------------------------|

Description

This function computes ROPRO prognostic score (Becker, Weberpals, et al., Ann Oncol 2020).

Usage

```
edb2_compute_ropro(x = NULL, cancer = c("NSCLC", "MM"))
```

Arguments

| | |
|--------|--|
| x | dataframe with inception cohort and required ROPRO covariates |
| cancer | character, what cancer-specific ROPRO should be computed ("NSCLC", "MM") |

Details

This function takes in a dataframe with all required variables to compute the general and cancer-specific ROPRO (specified in cancer). The variables need to be queried and transformed before which can be done through the edb2_query_ropro functions (specific for each database).

Important: Since EDB2 does not have all required variables, please use the edb2_compute_ropro function before use of this function to compute a reduced ROPRO model.

Value

The function returns x with the final general and cancer-specific ROPRO

Examples

```
## Not run:
library(encore.io)

x_ropro <- x |>
  edb2_query_ropro(
    index_date = "dt_index",
    path = Sys.getenv("path_edb2"),
    cancer = "NSCLC",
    from = -90,
    to = 0,
    verbose = TRUE
  ) |>
  edb2_compute_ropro(
    cancer = "NSCLC"
  )

## End(Not run)
```

| | |
|--------------------|---|
| edb2_get_biomarker | <i>Query biomarker information for a given solid tumor inception cohort</i> |
|--------------------|---|

Description

Function queries biomarker tables and curates information on alterations in defined driver genes.

Usage

```
edb2_get_biomarker(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC"),
  biomarker_name = NULL,
  from = -90,
  to = 0,
  label_name = FALSE
)
```

Arguments

| | |
|----------------|---|
| x | dataframe queried from edb2 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, one of MM or NSCLC |
| biomarker_name | character, name of biomarker/gene alteration (see details) |
| from | integer, left boundary of biomarker measurement window relative to index date (e.g., -90, indicating biomarker should be measured not before 90 days before index date) |
| to | integer, right boundary of biomarker measurement window relative to index date (e.g., 0, indicating biomarker should be measured until day of index date (inclusive)) |
| label_name | logical, should variable name carry information about the measurement window |

Details

The function queries and categorizes a certain biomarker that was collected and curated as part of the database as either positive or negative. The categorization happens according to if the biomarker mutation/alteration is a clinically actionable one. For example, patients with any mutation in the EGFR gene or MSI-H/dMMR status would be classified as positive. In case there are multiple measurements per biomarker and patient, the time point of measurement is defined as the non-missing biomarker result in the covariate ascertainment window given by 'from' and 'to' that is closest to the index date.

The biomarker date (dt_(biomarker)) in this database is defined as the earliest of specimen collection, result report or documented date. There can be imprecisions to the date of measurement on the month or year granularity level.

Depending on the cancer type, the biomarker names can be: 1p, 1q, ALK, BRAF, Complex Cytogenetics/Karyotype, DDR2, del(13), del(17), del(17p), Diploid, EGFR, FGFR1, HER2 (ERBB2), Hyperploid, Hypoploid, KEAP1 (INRF2), KRAS, MEK1(MAP2k1), MEK2 (MAP2K2), MET, MLH1, MMR, MSH2, MSH6, MSI/Microsatellite Instability, Normal Cytogenetics/Karyotype, NRAS, NTRK1, NTRK2, NTRK3, PD-L1, PIK3CA, PMS2, RET, ROS1, STK11 (LKB1), t(11;14), t(14;16), t(14;20), t(4;14), t(6;14), TMB/Tumor Mutational Burden, TP53

Value

x with all additional biomarker variables joined, that is:

- `c_(biomarker_name)_status_(from)_(to)` (binary, biomarker mutation status positive or negative)
- `c_(biomarker_name)_detail_(from)_(to)` (character string, more details about selected measurement)
- `c_(biomarker_name)_detail_all_(from)_(to)` (character string, this provides details about all results and details for this biomarker if there were multiple tests in the measurement window (from, to))
- `c_(biomarker_name)_distance_(from)_(to)` (numeric, relative distance between date of measurement and index date in days)
- `dt_(biomarker_name)_(from)_(to)` (date, date of selected biomarker measurement)

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)
analysis_cohort <- x |>
  edb2_get_biomarker(
    cancer = "NSCLC",
    biomarker_name = "egfr",
    from = -180,
    to = 0)

## End(Not run)
```

`edb2_get_demographics` *Query demographic variables for an inception cohort*

Description

Function queries all available demographic variables from the EDB2 database, curates them and joins them to the inception cohort x.

Usage

```
edb2_get_demographics(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC")
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb2 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, one of MM or NSCLC |

Details

Some important data curation details include:

- race and ethnicity are combined into a new combined variable 'dem_race_ethnicity' with five mutually exclusive groups as defined by SEER https://seer.cancer.gov/seerstat/variables/seer/race_ethnicity/#:~:text=
- the age at initial diagnosis and index date is categorized; note: in edb2, age is truncated after age >89; also, many dates come with imprecision and are therefore imputed
- Age at index date is calculated as the age at diagnosis + time difference (in years) between age at diagnosis and treatment initiation date
- Smoking history is assessed as any evidence of tobacco history on or before index date

Value

x with all additional demographic variables joined, that is, ADD NEW VARIABLE NAMES

- dem_age_initial_diagnosis (categorized age measured at initial cancer diagnosis: <60, 60-69, 70-79, 80+)
- dem_age_le_18_flag (logical indicating if patients was at least (larger/equal; le) 18 years of age at index date)
- dem_age_index_cont (continuous age measured at index date, CAVE: edb2 truncates age to 89 years for all patients >89, which means that dem_age_index_cont will show NA for these patients)
- dem_age_index (categorized age measured at index date: <60, 60-69, 70-79, 80+)
- dem_sex (binary, Male, Female, NA)
- dem_race (categorical, "", "Declined" and "Other" are converted to NA)
- dem_ethnicity (binary, "" and "Declined" are converted to NA)
- dem_race_ethnicity (categorical, classification into five mutually exclusive groups according to SEER)
- c_smoking_history (binary, history of any tobacco use on or before index date, TRUE = yes, FALSE = no)

Examples

```
## Not run:
library(encore.io)
ard <- x |>
  edb2_get_demographics(
    index_date = "dt_index",
    cancer = "BC"
  )

## End(Not run)
```

edb2_get_diagnosis_solid

Query initial and metastatic diagnosis dates for EDB2 database

Description

Function queries diagnosis details including staging information.

Usage

```
edb2_get_diagnosis_solid(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = "NSCLC"
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, NSCLC (default) |

Details

Function queries diagnosis details for all patients in . Summary group stage and TNM staging information as recorded in EBD2.

A de novo metastatic status variable <c_de_novo_mets_dx> is derived and is TRUE if the group stage (<c_stage_initial_dx>) indicates any stage IV diagnosis, the TNM staging (<c_tnm_initial_dx>) indicates an M1 value, or if the date of earliest evidence of a distant metastasis is earlier or coincides with the date of initial diagnosis (<dt_initial_dx>).

Note: if both group and TNM staging variables are missing, <c_de_novo_mets_dx> will be missing, too.

The function also returns <c_met_pre_index> which is a helper variable that is TRUE in case there is any evidence of at least one distant metastasis at any time before the index date (inclusive). This captures both de novo metastatic patients and those who progressed/developed metastases before/on the index date. Note: if neither group stage nor tnm stage are available, we set <c_met_pre_index> to NA because we can't make say they're FALSE either

Value

x with all additional diagnosis variables joined, that is:

- dt_initial_dx - Date of diagnosis or first documented diagnosis date for tumor (de-identified to week)
- dt_staging - Date stage was recorded, if available (de-identified to week)
- dt_met_dx - Date of earliest evidence of distant metastasis (de-identified to week)
- c_stage_initial_dx - First summary group stage at initial diagnosis, if available
- c_tnm_initial_dx - Individual TNM staging values/stages at initial diagnosis
- c_de_novo_mets_dx - Evidence of presence of one or multiple metastases at/before initial diagnosis
- c_time_dx_to_index - Time between initial diagnosis and index date (in days)
- c_time_met_dx_to_index - Time between earliest evidence of a metastatic diagnosis and index date (in days)
- c_met_pre_index - Evidence of any metastasis between initial diagnosis and index date (logical); includes initial diagnosis date (overlap with c_de_novo_mets_dx possible)
- c_number_met_sites - number of metastatic sites for a given patient anytime before/on index date (inferred from provided metastatic site description)
- c_met_sites - description of anatomical locations of metastatic sites for a given patient patient's c_number_met_sites

Examples

```
## Not run:
library(encore.io)
analysis_cohort <- x |>
  edb4_get_diagnosis(cancer = "NSCLC")

## End(Not run)
```

edb2_get_ecog

Query performance status information for a given cohort

Description

Function queries performance status (ECOG, Karnofsky) tables and curates derived variables

Usage

```
edb2_get_ecog(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC"),
  from = -90,
  to = 0,
  ties = "lower",
  label_name = FALSE
)
```

Arguments

| | |
|-------------------------|--|
| <code>x</code> | dataframe queried from edb2 with at least patient ids and index date of inception cohort |
| <code>index_date</code> | character, variable/column name with the patient's index_date, default is <code>dt_index</code> |
| <code>path</code> | character string, path to directory where EDB4 data/files are located |
| <code>cancer</code> | character, one of MM or NSCLC |
| <code>from</code> | integer, left boundary of ECOG measurement window relative to index date (e.g., -90, indicating ECOG should be measured not before 90 days before index date) |
| <code>to</code> | integer, right boundary of ECOG measurement window relative to index date (e.g., 0, indicating ECOG should be measured until day of index date (inclusive)) |
| <code>ties</code> | character, one of "lower" or "higher" to choose either the lower (default) or higher ECOG measurement if there are two measurements on the same day |
| <code>label_name</code> | logical, should variable name carry information about the measurement window #treat character, column indicating binary exposure status (needed for measurement summary statistics by treatment status) |

Details

The function queries all ECOG and Karnofsky measurements, then maps the Karnofsky measurement to an ECOG value according to Oken et al. (Am J Clin Oncol 1982), then filters for all measurements within the indicated time window specified by `from` and `to`. It then chooses the measurement closest to the index date (closest relative distance). In case of ties, the user has the option to choose the lower or higher (`ties`) measurement.

Value

`x` with all additional ECOG variables joined, that is:

- `c_ecog_{from}_{to}`, ECOG value measured in the specified measurement window
- `c_ecog_{from}_{to}`, distance of the date the ECOG value was measured relative to the index date

Note: if `from` or `to` is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

analysis_cohort <- x |>
  edb2_get_performance(
    cancer = "NSCLC",
    from = -180,
    to = 0,
    ties = "lower"
  )

## End(Not run)
```

| | |
|--------------------|--|
| edb2_get_histology | <i>Query histology information from edb2</i> |
|--------------------|--|

Description

Function queries and binarizes information for a provided histologiccal subtype from the EDB2 database.

Note: This function does not apply to multiple myeloma

Usage

```
edb2_get_histology(
  x = NULL,
  path = Sys.getenv("path_edb2"),
  cancer = "NSCLC",
  histology_match = NULL,
  return_all = FALSE
)
```

Arguments

| | |
|-----------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, NSCLC |
| histology_match | character, string match to categorize and identify patients with a certain histology for the indicated tumor site, e.g. "adenocarcinoma" |
| return_all | logical, should a variable be returned that summarizes all recorded histology measurements? default is FALSE |

Details

column information includes: Many patients can have more than one histological subtype recorded. In this function, the user must provide the desired cancer type and histological subtype and returns a binary TRUE/ FALSE if any of the histological recordings match the histology subtype provided in as well as a summary of all recorded histological subtypes (optional).

Tip: the function can also be stacked/executed multiple times with different histological subtypes.

Note that the search string defined in argument histology_match is not case sensitive.

Value

x with all additional histology variables joined, prepended with "c_"

- c_histology_match): A TRUE/FALSE if the histological subtype was observed for a given patient. FALSE may also include "unknowns" whose information was just not granular enough to be able to determine the histological subtype with absolute certainty
- c_histology_all: All observed histology recording for a given patient (optional if return_all = TRUE)

Examples

```
## Not run:
library(encore.io)

analysis_cohort_histology <- x |>
  edb2_get_histology(cancer = "NSCLC", histology_match = "adenocarcinoma")

## End(Not run)
```

| | |
|---------------|---|
| edb2_get_labs | <i>Query lab information for a given cohort</i> |
|---------------|---|

Description

Function queries the lab table and standardizes according to a reference measurement unit.

Usage

```
edb2_get_labs(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC"),
  lab_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = TRUE
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from EDB2 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, one of MM or NSCLC |
| lab_name | character, curated name of lab (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized |

| | |
|--------------------|--|
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in labs_mapping_edb2 |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries supported labs in the given from - to measurement window, selects the closest measurement to the index date, prioritizes one measurement in case of ties and standardizes the quantitative result to 1. a binary "normal" vs. "abnormal" variable (depending on if the measurement is inside or outside a given physiological reference range) and 2. standardizes the quantitative lab result according to a reference measurement unit (e.g., a result in g/dL is converted to a result in g/L, latter of which is the reference unit).

Note: Only selected labs are supported by this function which were taken from the ROPRO prognostic score (Becker T et al., Ann Oncol 2020).

The supported and available labs are:

- c_albumin_g_l (albumin mass/volume in serum or plasma)
- c_alp_u_l (alkaline phosphatase enzymatic activity/volume in serum or plasma)
- c_alt_u_l (alanine aminotransferase enzymatic activity/volume in serum or plasma)
- c_ast_u_l (aspartate aminotransferase enzymatic activity/volume in serum or plasma; used to compute ast-alt ratio)
- c_bilirubin_mg_dl (total bilirubin mass/volume in serum or plasma)
- c_calcium_mg_dl (calcium mass/volume in serum or plasma)
- c_hemoglobin_g_dl (Hemoglobin)
- c_ldh_u_l (lactate dehydrogenase enzymatic activity/volume in serum or plasma)
- c_neutrophil_10_9_l (neutrophils #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_platelets_10_9_l (platelets #/volume in blood)
- c_protein_g_l (protein Mass/volume in Serum or Plasma)

The following labs are part of ROPRO but are either not available in EDB2 or not supported yet:

- c_chloride_mmol_l (chloride moles/volume in serum or plasma)
- c_eosinophils_leukocytes_ratio (eosinophils/100 leukocytes in blood)
- c_glucose_mg_dl (Glucose)
- c_glucose_mg_dl (glucose mass/volume in serum or plasma)
- c_light_chain_kappa (Light Chain Kappa; dichotomous; >0 vs. 0)
- c_light_chain_lambda (Light Chain Lambda; dichotomous; >0 vs. 0)
- c_lymphocyte_10_9_l (lymphocytes #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_lymphocyte_leukocyte_ratio (lymphocytes/100 leukocytes in blood)
- c_m_protein_igg (M protein IgG (dichotomous; >0 vs. 0)
- c_monocytes_10_9_l (monocytes #/volume in blood)
- c_urea_nitrogen_mg_dl (urea nitrogen mass/volume in serum or plasma)

Value

x with all additional labs variables joined, that is:

- c_(lab_name)_distance_(from)_(to) - days from date of lab measurements to index date
- c_(lab_name)_(unit)_(from)_(to) - binary lab result indicating if lab was within ("normal") the reference range or outside ("abnormal")
- c_(lab_name)_(unit)_(from)_(to)_cont - quantitative lab result after unit harmonization/conversion

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb2_get_labs(
    cancer = "NSCLC",
    lab_name = "c_albumin_g_l",
    from = -90,
    to = 0
  )

## End(Not run)
```

| | |
|-------------|--|
| edb2_get_os | <i>Query overall survival outcome for a given cohort</i> |
|-------------|--|

Description

Function queries mortality and other information to derive a righ-censored time to all-cause mortality endpoint

Usage

```
edb2_get_os(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC"),
  data_cut_off_date = lubridate::ymd("2023-02-24"),
  verbose = TRUE
)
```

Arguments

| | |
|-------------------|--|
| x | dataframe queried from edb2 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where data/files are located. Default is path_edb2 environment variable if available. |
| cancer | character, one of MM or NSCLC |
| data_cut_off_date | date of database lock; according to vendor communication the data cut-off for the Q3 2023 delivery is Feb 24, 2023. This parameter can be changed if a grace period of x months before database lock is desired. |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and intention-to-treat (ITT) overall survival endpoint. The ITT follow-up time is defined as the time interval from index date (dt_index) to the date of death (if death event occurred), or the date of a patient's last structured clinical activity or database cut-off, whichever is earlier. Upon advice by the EDB2 vendor, the documented or reported days were not used (except for ECOG) as this is not a good indicator if a patient was truly alive by that time or not. All tables with dates were used except for tumor grading as here only reported and documented dates were available.

Note: for a fraction of patients, only month-level or year-level granularity is provided for the dates used to compute follow-up. This can result in implausible/negative follow-up times if the index date is after the imputed date of death.

Value

x with all endpoint information joined, that is:

- death_itt, event indicator for all-cause mortality
- fu_itt_days, ITT follow-up time in days
- fu_itt_months, ITT follow-up time in months (i.e., fu_itt_days / 30.417)
- fu_itt_years, ITT follow-up time in years

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb2_get_os(
    cancer = "NSCLC"
  )

## End(Not run)
```

edb2_get_vitals

Query vital sign measurements for a given cohort

Description

The function queries vital sign measurements in a specified measurement window and converts standardized measurements to SI units (e.g., meters for height and kg for weight).

Usage

```
edb2_get_vitals(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = c("MM", "NSCLC"),
  vital_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = FALSE
)
```

Arguments

| | |
|--------------------|---|
| x | dataframe queried from EDB2 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, one of MM or NSCLC |
| vital_name | character, curated name of vital sign measurement (see details) |
| from | integer, left boundary of vital signs measurement window relative to index date (e.g., -90, indicating vital should be measured not before 90 days before index date) |
| to | integer, right boundary of vital signs measurement window relative to index date (e.g., 0, indicating vital should be measured until day of index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized? |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in vitals_mapping_edb2 |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans all available vital sign measurements. In detail, the function selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

The available and supported vitals are:

- c_height (height in m)
- c_weight (weight in kg)

To compute BMI, query both c_height and c_weight and compute c_bmi as c_weight/c_height^2

Value

x with all additional labs variables joined, that is:

- c(vital_name)_distance_(from)_(to) - days from date of vital sign measurements to index date
- c(vital_name)_(unit)_(from)_(to)_cont - quantitative vital sign measurement

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb2_get_vitals(
    cancer = "NSCLC",
    vital_name = "c_height",
    from = -180,
    to = 0
  )

## End(Not run)
```

| | |
|------------------|---|
| edb2_path_helper | <i>Helper function to assign correct paths based on cancer entity in EDB2</i> |
|------------------|---|

Description

Use this helper function to assign the correct paths based on the cancer entity

Usage

```
edb2_path_helper(path = Sys.getenv("path_edb2"), cancer = c("MM", "NSCLC"))
```

Arguments

| | |
|--------|-------------------------------------|
| path | string, path to edb2 root directory |
| cancer | character, either "NSCLC" or "MM" |

Details

lot_path in MM also contains the imwg.csv table

Value

paths to line of therapy (lot_path) and all other data files (data_files_path)

Examples

```
## Not run:
library(encore.io)

nscclc_paths <- edb2_path_helper(cancer = "NSCLC")

## End(Not run)
```

edb2_query_ropro

Query and curate all relevant ROPRO variables

Description

This function queries, cleans and curates all necessary covariates from EDB2 as they are used to compute the ROPRP prognostic score (Becker, Weberpals, et al., Ann Oncol 2020).

Usage

```
edb2_query_ropro(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb2"),
  cancer = NULL,
  from = -90,
  to = 0,
  verbose = TRUE
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from EDB2 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB2 data/files are located |
| cancer | character, one of MM or NSCLC |

| | |
|---------|---|
| from | integer, left boundary of measurement window for time-dependent variables relative to index date (e.g., -90, indicating variables should be measured not before 90 days before index date) |
| to | integer, right boundary of measurement window for time-dependent variables relative to index date (e.g., 0, indicating variables should be measured not later than the day of the index date (inclusive)) |
| verbose | logical, print progress of query |

Details

Wrapper around major functions to query required covariates to compute ROPRO. Selected covariates are log transformed or log-log transformed. More details, see Becker, Weberpals, et al., Ann Oncol 2020.

Note that EDB2 does not provide all covariates to compute the full ROPRO model. Hence, this function queries all available covariates for a reduced model.

Value

x with all required ROPRO covariates joined. All general and cancer type-specific (as specified in cancer argument) covariates are returned.

Examples

```
## Not run:
library(encore.io)

x_ropro <- x |>
  edb2_query_ropro(
    index_date = "dt_index",
    path = Sys.getenv("path_edb2"),
    cancer = "NSCLC",
    from = -90,
    to = 0,
    verbose = TRUE
  )

## End(Not run)
```

edb3_get_demographics *Query demographic variables for an inception cohort in EDB3*

Description

Function queries all available demographic variables from the EDB3 database, curates them and joins them to the inception cohort x.

Usage

```
edb3_get_demographics(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb3")
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb3 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date |
| path | character string, path to directory where edb3 data/files are located |

Details

Some important data curation details include:

- race and ethnicity converted to <dem_race> and <dem_ethnicity> are cleaned for missing values, i.e., "", "Other or Unknown Race" and "Unknown" are explicitly changed to NA
- race and ethnicity are combined into a new combined variable 'dem_race_ethnicity' with five mutually exclusive groups as defined by SEER https://seer.cancer.gov/seerstat/variables/seer/race_ethnicity/#:~:text=
- The date of birth DOB is given on year granularity level and is hence imputed to June 30th in <dt_dob_imputed>
- The date of death DOD is suppressed to the closest Sunday within 4 days of the date of death and is sourced from curation, EMR, and third-party death data (in this hierarchical order) <dt_dod_imputed>
- Smoking history is assessed as a history of current or former (= smoking history) or never (= no smoking history) on or before index date

Value

x with all additional demographic variables joined, that is, ADD NEW VARIABLE NAMES

- dem_age_initial_diagnosis (categorized age measured at initial cancer diagnosis: <60, 60-69, 70-79, 80+)
- dem_age_le_18_flag (logical indicating if patients was at least (larger/equal; le) 18 years of age at index date)
- dem_age_index_cont (continuous age measured at index date; derived from from dt_index and dt_dob_imputed)
- dem_age_index (categorized age measured at index date: <60, 60-69, 70-79, 80+)
- dem_sex (binary, Male, Female, NA)
- dem_race (categorical, "", "Declined" and "Other" are converted to NA)
- dem_ethnicity (binary, "" and "Declined" are converted to NA)
- dem_race_ethnicity (categorical, classification into five mutually exclusive groups according to SEER)
- dem_institution_type (academic/community hospital patients receives care)
- dem_region (categorical, Northeast, South, West, Midwest, Multiple)
- dem_state (categorical, state patients receives care)
- c_smoking_history (binary, history of smoking on or before index date, 1 = current or former, 0 = never)

Examples

```
## Not run:
library(encore.io)
analysis_cohort <- inception_cohort |>
  edb3_get_demographics(cancer = "NSCLC")

## End(Not run)
```

edb3_get_labs

Query lab information for a given cohort

Description

Function queries the lab table and standardizes according to a reference measurement unit.

Usage

```
edb3_get_labs(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb3"),
  lab_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = TRUE
)
```

Arguments

| | |
|--------------------|--|
| x | dataframe queried from EDB3 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB3 data/files are located |
| lab_name | character, curated name of lab (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in labs_mapping_edb3 |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans supported lab measurements. In detail, the function selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

Note: Only selected labs are supported by this function which were taken from the ROPRO prognostic score (Becker T et al., Ann Oncol 2020).

The supported and available labs are:

- c_albumin_g_l (albumin mass/volume in serum or plasma)
- c_alp_u_l (alkaline phosphatase enzymatic activity/volume in serum or plasma)
- c_alt_u_l (alanine aminotransferase enzymatic activity/volume in serum or plasma)
- c_ast_u_l (aspartate aminotransferase enzymatic activity/volume in serum or plasma; used to compute ast-alt ratio)
- c_bilirubin_mg_dl (total bilirubin mass/volume in serum or plasma)
- c_calcium_mg_dl (calcium mass/volume in serum or plasma)
- c_chloride_mmol_l (chloride moles/volume in serum or plasma)
- c_eosinophils_leukocytes_ratio (eosinophils/100 leukocytes in blood)
- c_glucose_mg_dl (glucose mass/volume in serum or plasma)
- c_granulocytes_leukocytes_ratio (granulocytes/100 leukocytes in blood)
- c_hemoglobin_g_dl (hemoglobin mass/volume in blood)
- c_ldh_u_l (lactate dehydrogenase enzymatic activity/volume in serum or plasma)
- c_lymphocyte_10_9_l (lymphocytes #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_lymphocyte_leukocyte_ratio (lymphocytes/100 leukocytes in blood)
- c_monocytes_10_9_l (monocytes #/volume in blood)
- c_neutrophil_10_9_l (neutrophils #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_platelets_10_9_l (platelets #/volume in blood)
- c_protein_g_l (protein mass/volume in Serum or Plasma)
- c_urea_nitrogen_mg_dl (urea nitrogen mass/volume in serum or plasma)

The following labs are part of ROPRO but are either not available in EDB3 or not supported yet:

- c_light_chain_kappa (Light Chain Kappa; dichotomous; >0 vs. 0)
- c_light_chain_lambda (Light Chain Lambda; dichotomous; >0 vs. 0)
- c_m_protein_igg (M protein IgG (dichotomous; >0 vs. 0))

Value

x with all additional labs variables joined, that is:

- c_(lab_name)_distance_(from)_(to) - days from date of lab measurements to index date
- c_(lab_name)_(unit)_(from)_(to) - quantitative lab result after unit harmonization/conversion

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb3_get_labs(
    lab_name = "c_albumin_g_l",
    from = -90,
    to = 0
  )

## End(Not run)
```

edb3_get_vitals

*Query vital sign measurements for a given inception cohort***Description**

Function queries vitals sign measurements

Usage

```
edb3_get_vitals(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb3"),
  vital_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE
)
```

Arguments

| | |
|-------------------------|--|
| <code>x</code> | dataframe queried from EDB3 with at least patient ids and therapy index date of inception cohort |
| <code>index_date</code> | character, variable/column name with the patient's index_date, default is dt_index |
| <code>path</code> | character string, path to directory where EDB3 data/files are located |
| <code>vital_name</code> | character, curated name of vital sign measurement (see details) |
| <code>from</code> | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| <code>to</code> | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| <code>ties</code> | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized? |

| | |
|--------------------|---|
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in <code>vitals_mapping_edb3</code> |
| label_name | logical, should variable name carry information about the measurement window |

Details

The function queries and cleans supported vital sign measurements. In detail, the function selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

The supported vitals are:

- c_sbp (systolic blood pressure in mmHg)
- c_dbp (diastolic blood pressure in mmHg)
- c_bmi (body mass index in kg/m² directly measured or derived from weight/height²)
- c_height (height in m)
- c_hr (heart rate/pulse in beats/min)
- c_oxygen (oxygen saturation; taken from O2 sat and pulse oximetry)
- c_resp (respiration in breaths/min)
- c_weight (weight in kg)

Value

x with all additional labs variables joined, that is:

- c(vital_name)_distance_(from)_(to) - days from date of vital sign measurements to index date
- c(vital_name)_(unit)_(from)_(to)_cont - quantitative vital sign measurement

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb3_get_vitals(
    vital_name = "c_weight",
    from = -90,
    to = 0
  )

## End(Not run)
```

| | |
|--------------------|---|
| edb4_get_biomarker | <i>Query biomarker information for a given inception cohort</i> |
|--------------------|---|

Description

Function queries biomarker tables and curates information on alterations in defined driver genes.

Usage

```
edb4_get_biomarker(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC"),
  biomarker_name = NULL,
  from = -90,
  to = 0,
  label_name = FALSE
)
```

Arguments

| | |
|----------------|---|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC, MM or NSCLC |
| biomarker_name | character, name of biomarker/gene alteration (see details) |
| from | integer, left boundary of biomarker measurement window relative to index date (e.g., -90, indicating biomarker should be measured not before 90 days before index date) |
| to | integer, right boundary of biomarker measurement window relative to index date (e.g., 0, indicating biomarker should be measured until day of index date (inclusive)) |
| label_name | logical, should variable name carry information about the measurement window |

Details

The function queries and categorizes a certain biomarker that was collected and curated as part of the database as either positive or negative. The categorization happens according to if the biomarker mutation/alteration is a clinically actionable one. For example, patients with any mutation in the EGFR gene or MSI-H/dMMR status would be classified as positive. In case there are multiple measurements per biomarker and patient, the time point of measurement is defined as the non-missing biomarker result in the covariate ascertainment window given by 'from' and 'to' that is closest to the index date.

The biomarker recorded date (dt_(biomarker)) in this database is defined as the date documented or result date. Note that the biomarker date is de-identified to week (date documented or result date) and is converted to ymd format.

Depending on the cancer type, the biomarker names can be: alk, braf, brca1, brca2, egfr, er, esr1, her2neu, kras, met, mmmr, msi, nras, ntrk1, ntrk2, ntrk3, pd-l1, pik3ca, pr, ret, ros1, tmb

Value

x with all additional biomarker variables joined, that is:

- `c_(biomarker_name)_status_(from)_(to)` (binary, biomarker mutation status positive or negative)
- `c_(biomarker_name)_detail_(from)_(to)` (character string, more details about selected measurement)
- `c_(biomarker_name)_detail_all_(from)_(to)` (character string, this provides details about all results and details for this biomarker if there were multiple tests in the measurement window (from, to))
- `c_(biomarker_name)_distance_(from)_(to)` (numeric, relative distance between date of measurement and index date in days)
- `dt_(biomarker_name)_(from)_(to)` (date, date of selected biomarker measurement)

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)
analysis_cohort <- inception_cohort |>
  edb4_get_biomarker(
    cancer = "NSCLC",
    biomarker_name = "egfr",
    from = -180,
    to = 0)

## End(Not run)
```

`edb4_get_demographics` *Query demographic variables for an inception cohort*

Description

Function queries all available demographic variables from the EDB4 database, curates them and joins them to the inception cohort x.

Usage

```
edb4_get_demographics(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC")
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC, MM or NSCLC |

Details

Some important data curation details include:

- RACE and ETHNICITY are combined into a new combined variable 'dem_race_ethnicity' with five mutually exclusive groups as defined by SEER https://seer.cancer.gov/seerstat/variables/seer/race_ethnicity
- The date of birth DOB is given on year granularity level and is hence imputed to the mid of the year as <dt_dob_imputed>, e.g. 1955 becomes 1955-07-02. This affects all variables which are derived from the date of birth such as all age variables
- Smoking history is assessed as a history of current or former (= smoking history) or never (= no smoking history) on or before index date

Value

x with all additional demographic variables joined, that is, ADD NEW VARIABLE NAMES

- dem_age_initial_diagnosis (nominal, categorized age measured at initial cancer diagnosis: <60, 60-69, 70-79, 80+)
- dem_age_le_18_flag (logical, indicating if patients was at least (larger/equal; le) 18 years of age at index date)
- dem_age_index_cont (continuous, age measured at index date; note: date of bith has only year-granularity, hence age is imprecise)
- dem_age_index (nominal, categorized age measured at index date: <60, 60-69, 70-79, 80+)
- dem_sex (binary, Male, Female)
- dem_family_history (binary, TRUE, FALSE)
- dem_race (nominal, "", "Declined" and "Other" are converted to NA)
- dem_ethnicity (binary, "" and "Declined" are converted to NA)
- dem_race_ethnicity (nominal, classification into five mutually exclusive groups according to SEER)
- dem_region (nominal, region of the center/network the patient is receiving care at, can be Midwest, Northeast, South, West)
- c_smoking_history (logical, history of smoking on or before index date, TRUE = current or former, FALSE = never)

Examples

```
## Not run:
library(encore.io)

analysis_cohort <- x |>
  edb4_get_demographics(
    index_date = "dt_index",
```

```

        cancer = "NSCLC")

## End(Not run)

```

edb4_get_diagnosis_solid

Query initial and metastatic diagnosis dates for EDB4 database

Description

Function queries diagnosis details including staging information.

Usage

```

edb4_get_diagnosis_solid(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC")
)

```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC, MM or NSCLC |

Details

Function queries diagnosis details for all patients in . Summary group stage and TNM staging information as recorded in EBD4 ("Other" and "Unknown" categories are mapped to NA).

A de novo metastatic status variable <c_de_novo_mets_dx> is derived and is TRUE if the group stage (<c_stage_initial_dx>) indicates any stage IV diagnosis, the TNM staging (<c_tnm_initial_dx>) indicates an M1 value, or if the date of earliest evidence of a distant metastasis is earlier or coincides with the date of initial diagnosis (<dt_initial_dx>).

Note: if both group and TNM staging variables are missing, <c_de_novo_mets_dx> will be missing, too.

The function also returns <c_met_pre_index> which is a helper variable that is TRUE in case there is any evidence of at least one distant metastasis at any time before the index date (inclusive). This captures both de novo metastatic patients and those who progressed/developed metastases before/on the index date. Note: if neither group stage nor tnm stage are available, we set <c_met_pre_index> to NA because we can't make say they're FALSE either

Value

x with all additional diagnosis variables joined, that is:

- dt_initial_dx - Date of diagnosis or first documented diagnosis date for tumor (de-identified to week)
- dt_staging - Date stage was recorded, if available (de-identified to week)
- dt_met_dx - Date of earliest evidence of distant metastasis (de-identified to week)
- c_stage_initial_dx - First summary group stage at initial diagnosis, if available
- c_tnm_initial_dx - Individual TNM staging values/stages at initial diagnosis
- c_de_novo_mets_dx - Evidence of presence of one or multiple metastases at/before initial diagnosis
- c_time_dx_to_index - Time between initial diagnosis and index date (in days)
- c_time_met_dx_to_index - Time between earliest evidence of a metastatic diagnosis and index date (in days)
- c_met_pre_index - Evidence of any metastasis before/on index date (logical); includes de novo metastatic patients and progressors (overlap with c_de_novo_mets_dx possible)
- c_number_met_sites - number of metastatic sites for a given patient anytime before/on index date (inferred from mets_location as provided by the vendor)
- c_met_sites - description of anatomical locations of metastatic sites for a given patient patient's c_number_met_sites

Examples

```
## Not run:
library(encore.io)
analysis_cohort <- x |>
  edb4_get_diagnosis(cancer = "NSCLC")

## End(Not run)
```

edb4_get_ecog

Query performance status information for an inception cohort

Description

Function queries performance status (ECOG, Karnofsky) tables and curates derived variables

Usage

```
edb4_get_ecog(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC"),
  from = -90,
  to = 0,
  ties = "lower",
  label_name = FALSE
)
```

Arguments

| | |
|-------------------------|---|
| <code>x</code> | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| <code>index_date</code> | character, variable/column name with the patient's index_date, default is <code>dt_index</code> |
| <code>path</code> | character string, path to directory where EDB4 data/files are located |
| <code>cancer</code> | character, one of BC, CRC, MM or NSCLC |
| <code>from</code> | integer, left boundary of ECOG measurement window relative to index date (e.g., -90, indicating ECOG should be measured not before 90 days before index date) |
| <code>to</code> | integer, right boundary of ECOG measurement window relative to index date (e.g., 0, indicating ECOG should be measured until day of index date (inclusive)) |
| <code>ties</code> | character, one of "lower" or "higher" to choose either the lower (default) or higher ECOG measurement if there are two measurements on the same day |
| <code>label_name</code> | logical, should variable name carry information about the measurement window |

Details

The function queries all ECOG and Karnofsky measurements, then maps the Karnofsky measurement to an ECOG value according to Oken et al. (Am J Clin Oncol 1982), then filters for all measurements within the indicated time window specified by `from` and `to`. It then chooses the measurement closest to the index date (closest relative distance). In case of ties, the user has the option to choose the lower or higher (`ties`) measurement.

Value

`x` with all additional ECOG variables joined, that is:

- `c_ecog_{from}_{to}`, ECOG value measured in the specified measurement window
- `c_ecog_{from}_{to}`, distance of the date the ECOG value was measured relative to the index date

Note: if `from` or `to` is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

analysis_cohort <- x |>
  edb4_get_ecog(
    cancer = "NSCLC",
    from = -180,
    to = 0,
    ties = "lower"
  )

## End(Not run)
```

| | |
|--------------------|--|
| edb4_get_histology | <i>Query histology information from edb4</i> |
|--------------------|--|

Description

Function queries and binarizes information for a provided histological subtype from the EDB4 database. Note: This function does not apply to multiple myeloma

Usage

```
edb4_get_histology(
  x = NULL,
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "NSCLC"),
  histology_match = NULL,
  return_all = FALSE
)
```

Arguments

| | |
|-----------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC or NSCLC |
| histology_match | character, string match to categorize and identify patients with a certain histology, e.g. "adenocarcinoma" |
| return_all | logical, should a variable be returned that summarizes all recorded histology measurements? default is FALSE |

Details

column information includes: Many patients can have more than one histological subtype recorded. In this function, the user must provide the desired cancer type and histological subtype and returns a binary TRUE/FALSE if any of the histological recordings match the histology subtype provided in histology_match as well as a summary of all recorded histological subtypes (optional). Tip: the function can also be stacked/executed multiple times with different histological subtypes.

CAVE: EDB4 does not provide any information about the specimen/tissue type for which the histology was determined!

Note that the search string defined in argument histology_match is not case sensitive.

Value

x with all additional histology variables joined, prepended with "c_"

- c_(histology_match): A TRUE/FALSE if the histological subtype was observed for a given patient. FALSE may also include "unknowns" whose information was just not granular enough to be able to determine the histological subtype with absolute certainty
- c_histology_all: All observed histology recording for a given patient (optional if return_all = TRUE)

Examples

```
## Not run:
library(encore.io)
analysis_cohort_histology <- x |>
  edb4_get_histology(cancer = "NSCLC", histology_match = "adenocarcinoma")

## End(Not run)
```

edb4_get_labs

Query lab information for a given inception cohort

Description

Function queries the lab table and standardizes according to a reference measurement unit.

Usage

```
edb4_get_labs(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC"),
  lab_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = TRUE
)
```

Arguments

| | |
|--------------------|--|
| x | dataframe queried from EDB4 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC, MM or NSCLC |
| lab_name | character, curated name of lab (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in labs_mapping_edb4 |

| | |
|------------|--|
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans supported lab measurements. In detail, the function selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

Note: Only selected labs are supported by this function which were taken from the ROPRO prognostic score (Becker T et al., Ann Oncol 2020).

The supported and available labs are:

- c_albumin_g_l (albumin mass/volume in serum or plasma)
- c_alp_u_l (alkaline phosphatase enzymatic activity/volume in serum or plasma)
- c_alt_u_l (alanine aminotransferase enzymatic activity/volume in serum or plasma)
- c_ast_u_l (aspartate aminotransferase enzymatic activity/volume in serum or plasma; used to compute ast-alt ratio)
- c_bilirubin_mg_dl (total bilirubin mass/volume in serum or plasma)
- c_calcium_mg_dl (calcium mass/volume in serum or plasma)
- c_chloride_mmol_l (chloride moles/volume in serum or plasma)
- c_eosinophils_leukocytes_ratio (eosinophils/100 leukocytes in blood)
- c_glucose_mg_dl (glucose mass/volume in serum or plasma)
- c_granulocytes_leukocytes_ratio (granulocytes/100 leukocytes in blood)
- c_hemoglobin_g_dl (hemoglobin mass/volume in blood)
- c_ldh_u_l (lactate dehydrogenase enzymatic activity/volume in serum or plasma)
- c_lymphocyte_10_9_l (lymphocytes #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_lymphocyte_leukocyte_ratio (lymphocytes/100 leukocytes in blood)
- c_monocytes_10_9_l (monocytes #/volume in blood)
- c_neutrophil_10_9_l (neutrophils #/volume in blood; used to compute neutrophil/lymphocyte ratio)
- c_platelets_10_9_l (platelets #/volume in blood)
- c_protein_g_l (protein mass/volume in Serum or Plasma)
- c_urea_nitrogen_mg_dl (urea nitrogen mass/volume in serum or plasma)

The following labs are part of ROPRO but are either not available in EDB4 or not supported yet:

- c_light_chain_kappa (Light Chain Kappa; dichotomous; >0 vs. 0)
- c_light_chain_lambda (Light Chain Lambda; dichotomous; >0 vs. 0)
- c_m_protein_igg (M protein IgG (dichotomous; >0 vs. 0))

Value

- x with all additional labs variables joined, that is:
- c_(lab_name)_distance_(from)_(to) - days from date of lab measurements to index date
 - c_(lab_name)_(unit)_(from)_(to)_cont - quantitative lab result after unit harmonization/conversion

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb4_get_labs(
    cancer = "NSCLC",
    lab_name = "c_albumin_g_l",
    from = -90,
    to = 0
  )

## End(Not run)
```

| | |
|-------------|--|
| edb4_get_os | <i>Query overall survival outcome for a given inception cohort</i> |
|-------------|--|

Description

Function queries mortality and other information to derive a righ-censored time to all-cause mortality endpoint

Usage

```
edb4_get_os(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = NULL,
  data_cut_off_date = lubridate::ymd("2024-09-30"),
  verbose = TRUE
)
```

Arguments

| | |
|------------|--|
| x | dataframe queried from edb4 with at least patient ids and index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where data/files are located |

| | |
|-------------------|---|
| cancer | character, one of BC, CRC, MM or NSCLC |
| data_cut_off_date | date of database lock; the data cut-off for this delivery is Sep 30, 2024. This parameter can be changed if a grace period of x months before database lock is desired. |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and curates intention-to-treat (ITT) overall survival endpoint. The ITT follow-up time is defined as the time interval from index date (dt_index) to the date of death (if death event occurred), or the last date of proof that the patient was alive at that time (date de-identified to week).

Note that in EDB4, the granularity of the date of death variable is given as month-year. In these cases, the date of death is imputed to the mid/15th of the month. This can in rare circumstances lead to negative/implausible follow-up times if the index date is after the imputed date of death.

Value

- x with all endpoint information joined, that is:
- death_itt, event indicator for all-cause mortality
 - fu_itt_days, ITT follow-up time in days
 - fu_itt_months, ITT follow-up time in months (i.e.,fu_itt_days / 30.417)
 - fu_itt_years, ITT follow-up time in years

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb4_get_os(
    cancer = "NSCLC"
  )

## End(Not run)
```

| | |
|-----------------|---|
| edb4_get_vitals | <i>Query vital sign measurements for a given cohort</i> |
|-----------------|---|

Description

Function queries vitals sign measurements

Usage

```
edb4_get_vitals(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = c("BC", "CRC", "MM", "NSCLC"),
  vital_name = NULL,
  from = -90,
  to = 0,
  ties = "lower",
  set_implausible_na = TRUE,
  label_name = FALSE,
  verbose = TRUE
)
```

Arguments

| | |
|--------------------|--|
| x | dataframe queried from EDB4 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index_date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of BC, CRC, MM or NSCLC |
| vital_name | character, curated name of vital sign measurement (see details) |
| from | integer, left boundary of lab measurement window relative to index date (e.g., -90, indicating lab should be measured not before 90 days before index date) |
| to | integer, right boundary of lab measurement window relative to index date (e.g., 0, indicating lab should be measured not later than the day of the index date (inclusive)) |
| ties | character, in case of ties (two equi-distant measurements), should the "higher" or "lower" lab measurement be prioritized? |
| set_implausible_na | logical, should implausible values (outliers) be automatically be set NA (default is TRUE)? Lower and upper thresholds are documented in <code>vitals_mapping_edb4</code> |
| label_name | logical, should variable name carry information about the measurement window |
| verbose | logical, print query progress and informative meta information |

Details

The function queries and cleans all available vital sign measurements. In detail, the function removes measurements that are character strings (e.g., "BMI < 21") and only considers quantitative results. The function further only selects measurements in a from - to measurement window relative to the index date. In case that there are multiple measurements in this window, the function uses the measurement that has the smallest absolute distance relative to the index date. If there are two equi-distant measurements, the lower (default) or higher measurement can be prioritized.

The available and supported vitals are:

- c_sbp (systolic blood pressure in mmHg)
- c_dbp (diastolic blood pressure in mmHg)
- c_bmi (body mass index in kg/m² directly measured or derived from weight/height²)

- c_bsa (body surface area in m²)
- c_height (height in m)
- c_hr (heart rate/pulse in beats/min)
- c_oxygen (oxygen saturation; taken from O2 sat and pulse oximetry)
- c_pain (pain scale in ?)
- c_resp (respiration in breaths/min)
- c_temp (temperature in fahrenheit)
- c_weight (weight in kg)

Value

x with all additional labs variables joined, that is:

- c_(vital_name)_distance_(from)_(to) - days from date of vital sign measurements to index date
- c_(vital_name)_(unit)_(from)_(to)_cont - quantitative vital sign measurement

Note: if from or to is a negative integer, the resulting covariate name will contain a "min" for "minus" preceding the integer to comply with the tidy variable naming rules

Examples

```
## Not run:
library(encore.io)

ard <- x |>
  edb4_get_vitals(
    cancer = "NSCLC",
    vital_name = "c_bmi",
    from = -90,
    to = 0
  )

## End(Not run)
```

edb4_query_ropro

Query and curate all relevant ROPRO variables

Description

This function queries, cleans and transforms all necessary covariates needed to compute the ROPRO prognostic score in EDB4.

Usage

```
edb4_query_ropro(
  x = NULL,
  index_date = "dt_index",
  path = Sys.getenv("path_edb4"),
  cancer = NULL,
  from = -90,
  to = 0,
  verbose = TRUE
)
```

Arguments

| | |
|------------|---|
| x | dataframe queried from EDB4 with at least patient ids and therapy index date of inception cohort |
| index_date | character, variable/column name with the patient's index date, default is dt_index |
| path | character string, path to directory where EDB4 data/files are located |
| cancer | character, one of "BC", "CRC", "MM" or "NSCLC" |
| from | integer, left boundary of measurement window for time-dependent variables relative to index date (e.g., -90, indicating variables should be measured not before 90 days before index date) |
| to | integer, right boundary of measurement window for time-dependent variables relative to index date (e.g., 0, indicating variables should be measured not later than the day of the index date (inclusive)) |
| verbose | logical, print progress of query |

Details

Wrapper around major functions to query required covariates to compute ROPRO. Selected covariates are log transformed or log-log transformed. More details, see Becker, Weberpals, et al., Ann Oncol 2020.

Value

x with all required ROPRO covariates joined. All general and cancer type-specific (as specified in cancer argument) covariates are returned.

#' Note that:

- covariates for EarlyBreast are identical to the the general pan-tumor ROPRO, just the weights are different. That means, if cancer = "BC" is specified, the function also returns covariates for the metastatic breast cancer-specific ROPRO.

Examples

```
## Not run:
library(encore.io)

x_ropro <- x |>
  edb4_query_ropro(
    index_date = "dt_index",
    path = Sys.getenv("path_edb4"),
    cancer = "NSCLC",
```

```

    from = -90,
    to = 0,
    verbose = TRUE
  )

## End(Not run)

```

| | |
|-----|---|
| ess | <i>Calculates the averaged effective sample sizes for mimids/wimids objects</i> |
|-----|---|

Description

[Experimental]

Calculates the averaged effective sample sizes for imputed and matched or weighted datasets resulting from `MatchThem::matchthem(mimids objects)` or `MatchThem::weightthem(wimids objects)`

Usage

```
ess(object = NULL, decimals = 2)
```

Arguments

| | |
|----------|---|
| object | mimids or data.frame object from <code>complete(..., action = 'long', all = TRUE, ...)</code> |
| decimals | decimals to round for averaged effective sample size (default is 2 decimals) |

Details

Matching or weighting across imputed datasets with partially observed covariates leads to slightly differenmatched or weighted cohorts with different sample sizes for each imputed dataset.

To account for this in the descriptive reporting of the effective sample size used in our analysis, this function computes the averaged effective sample sizes across all matched or weighted cohorts.

This function is a wrapper around the [bal.tab](#) function of the cobalt R package which performs these computations. For more information on how the effective sample sizes are computed.

Value

tibble with sample size information by treatment indicator

See Also

[bal.tab](#)

<https://ngreifer.github.io/cobalt/reference/bal.tab.html>

Examples

```
## Not run:

if(require("smdi") & require("MatchThem")){

  library(smdi)
  library(mice)
  library(MatchThem)
  library(encore.io)

  mids <- mice(smdi_data, printFlag = F)

  fit <- as.formula(exposure ~ age_num + female_cat + ecog_cat + egfr_cat + pdl1_num)
  wimids <- weightthem(fit, mids)

  ess(wimids, decimals = 1)

}

## End(Not run)
```

gt_tbl_compact

Utility function for a more compact look of gt tables

Description**[Experimental]**

Is a convenience utility function to make gt tables look more compact as compared to the default size and spacing.

#' @seealso [gt theme_gtsummary_compact](#)

Usage

```
gt_tbl_compact(gt_tbl = NULL, font_size = 13)
```

Arguments

| | |
|-----------|--|
| gt_tbl | gt table object |
| font_size | numeric, desired font size (default is 13) |

Value

gt table in compact format

Examples

```
library(encore.io)
library(gt)

head(iris) |>
gt() |>
```

```
gt_tbl_compact()
```

| | |
|----------------|--|
| icd_metastases | <i>System data used to streamline functions and analysis</i> |
|----------------|--|

Description

System data used to streamline functions and analysis

Usage

```
icd_metastases
```

Format

```
icd_metastases:
C79 ICD-10 codes and mappings to convert to ICD-9 to identify number of metastatic sites in
edb1. This is adapted from a crosswalk from the NBER
icd10cm ICD-10-CM code
icd9cm ICD-9-CM code
approximate approximate
no_map no_map
sites Site description ...
```

Source

<https://www.nber.org/research/data/icd-9-cm-and-icd-10-cm-and-icd-10-pcs-crosswalk-or-general-equivalence-mappings>

| | |
|---------------------|--|
| imputation_workflow | <i>Streamlines the imputation workflow</i> |
|---------------------|--|

Description

This function streamlines the imputation workflow from an eligible cohort with missings to an imputed mids object with only a subset of the key covariates and computed ropro

Usage

```
imputation_workflow(
  ard_eligible = NULL,
  database = NULL,
  cancer = NULL,
  covars_for_imputation = NULL
)
```

Arguments

ard_eligible data frame with all eligible patients and covariates needed for imputation
 database character, which database is used ("edb1", "edb2", "edb3" or "edb4")
 cancer character, which cancer is investigated ("aNSCLC", "MetastaticBreast", "Early-Breast", "MetastaticCRC", "MultipleMyeloma")
 covars_for_imputation character vector with covariates for imputation (should include covariates for propensity score, treatment, outcome and optionally other auxiliary covariates)

Details

...

Value

imputed mids object with ROPRO

Examples

```
## Not run:
if(require("smdi")){

  library(encore.io)

  mids_data <- imputation_workflow(
    ard_eligible,
    database = "edb1",
    cancer = "aNSCLC",
    covars_for_imputation = c("dem_age_index", "dem_sex")
  )

}

## End(Not run)
```

km_pooling

Pooled Kaplan-Meier estimate and survival curve

Description

Computes pooled median survival Kaplan-Meier estimates using Rubin's rule and outputs corresponding Kaplan-Meier curve across imputed and matched/weighted datasets

Usage

```
km_pooling(
  object = NULL,
  surv_formula = as.formula(survival::Surv(eventtime, status) ~ exposure),
  t_min = 0,
  t_max = NULL,
  t_steps = 0.1
)
```

Arguments

| | |
|--------------|--|
| object | imputed and matched (mimids) or weighted (wimids) object |
| surv_formula | specification of survival model formula to be fitted |
| t_min | integer, start of follow up time period for which pooled survival probabilities should be computed |
| t_max | integer, end of follow up time period for which pooled survival probabilities should be computed |
| t_steps | numeric, discretized time steps (in the unit of time in which follow up is measured) at which pooled survival probabilities should be computed |

Details

The function requires an object of class mimids or wimids, which is the output of a workflow that requires imputing multiple (m) datasets using mice or amelia and matching or weighting the each imputed dataset via the MatchThem package (see examples).

The function fits the pre-specified survfit model `surv_formula` to compute survival probabilities at each individual time point according to the Kaplan-Meier method. For matched and weighted datasets, weights, cluster membership (matching only) and robust variance estimates are considered by default.

To pool individual estimates across matched and imputed datasets, the `pool.scalar` function is used to apply Rubin's to combine pooled estimates according to formula (3.1.2) Rubin (1987) and to compute the corresponding total variance of the pooled estimate according to formula (3.1.5) Rubin (1987). The pooled standard error is then computed as the square root of the total variance.

The complimentary Kaplan-Meier curve computes and pools survival probabilities over a specified time period (`t_min` - `t_max`) by discretized steps (`t_steps`). The smaller the time steps, the smoother the Kaplan-Meier curve.

Value

list with pooled median survival estimate and pooled Kaplan-Meier curve `km_estimate`:

- `m` = number of imputed datasets
- `qbar` = pooled median survival time estimates, formula (3.1.2) Rubin (1987)
- `t` = total variance of the pooled estimate, formula (3.1.5) Rubin (1987)
- `se` = total standard error of the pooled estimate (derived as `sqrt(t)`)
- `lcl` = Wald-type lower 95% confidence interval
- `ucl` = Wald-type upper 95% confidence interval

`km_plot`: ggplot2 object with Kaplan-Meier curve

See Also

[survfit](#) [pool.scalar](#) [matchthem](#) [weightthem](#)

Examples

```

if(require("MatchThem")){

  library(smdi)
  library(mice)
  library(MatchThem)
  library(encore.io)

  # impute data
  set.seed(42)
  mids <- mice(smdi_data[1:500, ], m = 2, printFlag = FALSE)

  # fit a propensity score model
  fit <- as.formula(exposure ~ age_num + female_cat + ecog_cat + egfr_cat + pdl1_num)

  # weight (or alternatively match) patients within each imputed dataset
  wimids <- weightthem(
    formula = fit,
    datasets = mids,
    approach = "within",
    method = "glm",
    estimand = "ATO"
  )

  # specificity survival model
  km_fit <- as.formula(survival::Surv(eventtime, status) ~ exposure)

  # estimate and pool median survival times and Kaplan-Meier curve
  km_out <- km_pooling(
    object = wimids,
    surv_formula = km_fit,
    t_min = 0,
    t_max = max(smdi_data$eventtime),
    t_steps = 0.1 # follow is in years, so this is in 0.1 year increments
  )

  # median survival time
  km_out$km_median_survival

  # KM curve
  km_out$km_plot
}

```

n_fmt

Quickly format numbers

Description

format raw numeric numbers into formatted characters including large decimal "," and small decimal ".".

Usage

```
n_fmt(x, n_digits = 2)
```

Arguments

| | |
|----------|---------------------------------------|
| x | number |
| n_digits | integer, number of digits after comma |

Details

...

Value

a character of the formatted numbers

Examples

```
## Not run:
library(encore.io)
n_fmt(12345678)

## End(Not run)
```

power_survival

Power analysis for proportional hazards models

Description

Function computes implementations of sample-Size Formula for the Proportional-Hazards Regression Model for the statistical power of a two arm treatment comparison as described by David A. Schoenfeld (Biometrika 1983)

Usage

```
power_survival(
  beta = NULL,
  alpha = NULL,
  p_exposed = NULL,
  n_events = NULL,
  hr = NULL
)
```

Arguments

| | |
|-----------|---|
| beta | numeric, beta percentiles of the normal distribution (type II error rate;) |
| alpha | numeric, 1-alpha percentiles of the normal distribution (type I error rate) |
| p_exposed | numeric, proportion of exposed patients |
| n_events | numeric, number of events |
| hr | numeric, hazard ratio |

Details

One parameter can be left undefined (except p_exposed) which is the computed using an implementation of David A. Schoenfeld's (Biometrika 1983) formula.

Value

integer representing the undefined parameter

See Also

Schoenfeld DA. Sample-size formula for the proportional-hazards regression model. Biometrics 1983;39:499-503.

<https://www.jstor.org/stable/2531021>

Examples

```
library(encore.io)

power_survival(
  alpha = 0.05,
  beta = 0.2,
  p_exposed = 0.5,
  hr = 0.8
)
```

| | |
|-----------------|--|
| ps_balance_plot | <i>Computes and visualizes the overlap for distance measures between exposure groups</i> |
|-----------------|--|

Description

#' **[Deprecated]** Calculates the the overlap for distance measures (e.g., propensity or prognostic scores) between exposure groups for multiple imputed and matched datasets.

Usage

```
ps_balance_plot(
  object = NULL,
  exposure = "treat",
  weights = "weights",
  ps = "distance"
)
```

Arguments

| | |
|----------|--|
| object | mimids or data.frame object from complete(..., action = 'long', all = TRUE, ...) |
| exposure | character, quoted name of the exposure/treatment variable |
| weights | character, quoted name of the variable indicating the matching weights (usually 0: unmatched and 1: matched) |
| ps | character, quoted name of the variable with the distance measure (e.g., propensity score) |

Details

The object input needs to be a mimids object or a data.frame object coming from MatchThem::matchthem(). If the mimids object is already converted to a long data.frame of stacked imputed datasets, the MatchThem::complete() function needs to be completed using action = "long" and all = TRUE arguments.

The function then creates two stacked datasets (unmatched/all and matched only) patients and combines the propensity score across all imputed datasets into a single graph.

Value

ggplot object

Examples

```
## Not run:
library(encore.io)

ps_balance_plot(
  object = edb1_mimids,
  exposure = "treat",
  ps = "distance"
)

## End(Not run)
```

qc_assertive_line_check

Assertive line of therapy checks

Description

Assertive line of therapy checks to make sure that patients in an advanced line of treatment also received a previous line. Important: input dataframe needs to have a one line per patient per line of therapy format.

Usage

```
qc_assertive_line_check(
  data = NULL,
  id_col = NULL,
  linenummer_col = NULL,
  linename_col = NULL
)
```

Arguments

| | |
|----------------|--|
| data | dataframe including line number and line treatment |
| id_col | quoted character specifying the column name of the patient identifier |
| linenummer_col | quoted character specifying the column name of the line number |
| linename_col | quoted character specifying the column name of the line name/treatment |

Details

...

Value

a table/dataframe with the logical results (TRUE/FALSE) of the assertive checks.

Examples

```
## Not run:
library(encore.io)

## End(Not run)
```

| | |
|-----------|---|
| re_weight | Custom function to perform matching/weighting and re-weighting to match a target patient population |
|-----------|---|

Description

Custom function to perform matching/weighting and re-weighting to match a target patient population

Usage

```
re_weight(x, targets = NULL, matching_weighting = NULL, ...)
```

Arguments

- x data.frame or mild object/list of data.frames if used in combination with lapply
- targets named list of all target values for the raking procedure (see [anesrake](#))
- matching_weighting character, one of "matching" or "weighting"
- ... other arguments and specifications to propagate on to [matchit](#) or [weightit](#), depending on chosen method (matching_weighting).

Details

This function is a wrapper for [matchit](#) and [weightit](#) in combination with [anesrake](#). The function performs any matching algorithm supplied in [matchit](#) or any weighting algorithm in [weightit](#). The specific arguments can be propagated to the respective functions using the ... argument.

If nothing is specified for targets, the function will simply return the [matchit](#) or [weightit](#) object.

If a list of target distributions is specified for targets, the function will perform a corresponding re-weighting of matched patients or patients with weights greater than 0, respectively.

In case of an already weighted datasets (e.g., via propensity score-derived weights), those weights are accounted for (weightvec argument) in the [anesrake](#) call.

Value

an object of type `matchit` or `weightit` with included sampling weights (`s.weights`) if re-weighting was performed.

See Also

[matchit](#) [weightit](#) [anesrake](#)

Examples

```
if(require("MatchThem") & require("mice")){

  library(encore.io)
  library(dplyr)
  library(mice)
  library(MatchThem)

  data_miss <- simulate_flaura(
    n_total = 3500,
    seed = 41,
    include_id = FALSE,
    imposeNA = TRUE,
    propNA = .33
  ) |>
  # anesrake works best with factor variables
  # convert c_smoking_history into a factor
  mutate(c_smoking_history = factor(ifelse(c_smoking_history == TRUE, "Current/former", "Never")))

  # impute data
  data_imp <- mice(
    parallelseed = 42,
    n.core = 7,
    data = data_miss,
    m = 5,
    print = FALSE
  )

  # define covariates for propensity score model
  covariates <- data_miss |>
    select(starts_with("c_"), starts_with("dem_")) |>
    colnames()

  # define propensity score model
  ps_form <- as.formula(paste("treat ~", paste(covariates, collapse = " + ")))

  # create a mild object containing lists of data.frames
  data_mild <- mice::complete(data = data_imp, action = "all", include = FALSE)

  smoker_target <- c(.35, .65)
  names(smoker_target) <- c("Current/former", "Never")

  # summarize target distributions in a named list vector -----
  targets <- list(smoker_target)
  names(targets) <- c("c_smoking_history")

  # create a mild object containing lists of data.frames
```

```

data_mild <- mice::complete(data = data_imp, action = "all", include = FALSE)

# call re-weight
matchit_out_list <- lapply(
  X = data_mild,
  FUN = re_weight,
  targets = targets,
  matching_weighting = "matching",
  # arguments passed on to matchit
  formula = ps_form,
  ratio = 1,
  method = "nearest",
  distance = "glm",
  link = "logit",
  caliper = 0.01,
  replace = FALSE
)

# convert the output back into a mimids object
data_mimids_from_function <- MatchThem::as.mimids(
  x = matchit_out_list,
  datasets = data_imp
)

# print
data_mimids_from_function
}

```

simulate_flaura

Simulates and artificial FLAURA EHR-derived dataset

Description

Parameterized function to quickly create an artificial FLAURA EHR-derived analytic cohort for analytic code development.

Usage

```

simulate_flaura(
  n_total = 3500,
  seed = 42,
  include_id = TRUE,
  imposeNA = TRUE,
  propNA = NULL
)

```

Arguments

| | |
|------------|---|
| n_total | integer, number of total patients |
| seed | integer, seed for reproducibility |
| include_id | logical, include a generated patientid variable |
| imposeNA | logical, set covariates to missing |
| propNA | numeric, proportion of missingness, needs to be between 0 and 1 |

Details

...

Value

data frame with simulated analytic cohort

Examples

```
## Not run:  
library(encore.io)  
  
data_miss <- simulate_flaura(  
  n_total = 3500,  
  seed = 41,  
  include_id = FALSE,  
  imposeNA = TRUE,  
  propNA = .33  
)  
  
head(data_miss)  
  
## End(Not run)
```

Index

* datasets

- edb1_cohorts, 6
- icd_metastases, 61

anesrake, 68, 69

bal.tab, 59

c_statistics, 4
create_table1, 3

edb1_3_4_compute_ropro, 5
edb1_cohorts, 6
edb1_get_biomarker, 7
edb1_get_demographics, 8
edb1_get_diagnosis_heme, 10
edb1_get_diagnosis_solid, 11
edb1_get_ecog, 13
edb1_get_histology, 14
edb1_get_labs, 15
edb1_get_os, 18
edb1_get_vitals, 19
edb1_query_ropro, 21
edb2_assign_date, 23
edb2_compute_ropro, 24
edb2_get_biomarker, 25
edb2_get_demographics, 26
edb2_get_diagnosis_solid, 28
edb2_get_ecog, 29
edb2_get_histology, 31
edb2_get_labs, 32
edb2_get_os, 34
edb2_get_vitals, 36
edb2_path_helper, 37
edb2_query_ropro, 38
edb3_get_demographics, 39
edb3_get_labs, 41
edb3_get_vitals, 43
edb4_get_biomarker, 45
edb4_get_demographics, 46
edb4_get_diagnosis_solid, 48
edb4_get_ecog, 49
edb4_get_histology, 51
edb4_get_labs, 52

edb4_get_os, 54
edb4_get_vitals, 55
edb4_query_ropro, 57
ess, 59

gt, 60
gt_tbl_compact, 60

icd_metastases, 61
imputation_workflow, 61

km_pooling, 62

matchit, 68, 69
matchthem, 63

n_fmt, 64

pool.scalar, 63
power_survival, 65
ps_balance_plot, 66

qc_assertive_line_check, 67

re_weight, 68

simulate_flaura, 70
survfit, 63

theme_gtsummary_compact, 60

weightit, 68, 69
weightthem, 63