


# ENHANCING SPACE SURVEILLANCE THROUGH THE SPIE. UNISTELLAR COLLABORATIVE OBSERVATION PROGRAM

Janin-Potiron, P.<sup>(a)</sup>, Cañameras, R.<sup>(a)</sup>, Neichel, B.<sup>(a)</sup>, Gray, M.<sup>(a)</sup>, Marchis, F.<sup>(b,c)</sup>, Lambert, R.<sup>(c)</sup>, Quere, F.<sup>(b)</sup>, Blaclard, G.<sup>(b)</sup>, Malvache, A.<sup>(b)</sup>, Beltramo-Martin, O.<sup>(d)</sup>, Cantegreil, J.<sup>(d)</sup>, Boute, P.<sup>(d)</sup>, Zancanaro, Y.<sup>(d)</sup>, Gervail, A.<sup>(e)</sup>, Correia, C. M.<sup>(f)</sup>

(a) Aix Marseille Univ, CNRS, CNES, LAM, Marseille, France (b) Unistellar, 5 Allée Marcel Leclerc 13008 Marseille (c) SETI Institute, 339 Bernardo Ave, Suite 200 Mountain View, CA 94043, United States (d) SpaceAble, 13-15 rue Taitbout 75009 Paris, France (e) Observatoire de la Combe de Lancey, 341 chem. de la Prise d'Eau du Boussant, France (f) Space ODT Lda, Av. da França 492, 4050-277 Porto

## SIMULATIONS

Composite images simulated with our Python library **OrbitAI**



## THE PROJECT



The goal is to detect LEO-SATELLITES from images acquired by the Unistellar collaborative observation program using NEURAL NETWORKS. Our method aims at improving efficiency at low SNR compared to standard algorithms.

### THE DATA

Short exposure frames gathered from the worldwide highly active **UNISTELLAR** community == database is growing fast ! ❤️

### THE METHOD

Use two sequential networks to make the detection

- (1) **classification** - is there a streak in the image ?
- (2) **segmentation** - which pixels are affected by the satellite streak ?

## (1) CLASSIFICATION

We want to tell **if** a satellite is present in the image.

### CUTOUTS ARE USED DUE TO THE RELATIVELY LARGE DIMENSIONS OF IMAGES INPUTS


We train the CNN on small cutouts and apply to the larger telescope images using sliding windows

### THE NETWORK IS TESTED ON REAL OBSERVATIONS

Images gathered through the Unistellar satellite program are classified with the CNN. We use 387 test images with satellite streak (positives) and 23283 test images without satellite streak (negatives).

### THE ROC CURVES ARE SATISFYING


90% TPR @ 1% FPR for all levels of SNR. The performance lowers when including partial streaks cropped by the sensor.



## (2) SEGMENTATION


We want to reconstruct the satellite streak to measure its orbital parameters

### THE NETWORK WE USE




### THE NETWORK IS TESTED ON COMPOSITE SIMULATIONS

for which we know the ground-truth masks




### PERFORMANCES ARE ONLY LIMITED BY THE SNR OF THE SATELLITE STREAK

Performances do not depend on  $r_0$ , streak length, number of stars in field, etc.



## DEFINITIONS


THE **SIGNAL-TO-NOISE RATIO** IS DEFINED AS  $SNR = \frac{\text{FLUX IN THE STREAK}}{\text{STD OF SKY BACKGROUND}}$



## ON-GOING WORK

### IMPROVE PERFORMANCES AT LOWER SNR

Build dedicated network to perform better for fainter targets.



## REFERENCES

- [1] Zhang, K. and Bloom, J. S., "deepCR: Cosmic Ray Rejection with Deep Learning," *Astrophysical Journal* 889, 24 (Jan. 2020).
- [2] Xu, C. et al., "Cosmic-CoNN: A Cosmic-Ray Detection Deep-learning Framework, Data Set, and Toolkit," *Astrophysical Journal* 942, 73 (Jan. 2023).
- [3] Kruk, S. et al., "Hubble Asteroid Hunter. I. Identifying asteroid trails in Hubble Space Telescope images," *Astronomy and Astrophysics* 661, A85 (May 2022).
- [4] Zavagno, A., et al., "Supervised machine learning Galactic filaments. Revealing the filamentary structure of the Galactic interstellar medium," *Astronomy and Astrophysics* 669, A120 (Jan. 2023).
- [5] Bertin, E. and Arnouts, S., "SExtractor: Software for source extraction," *Astronomy and Astrophysics, Supplement* 117, 393-404 (June 1996).

- [6] Paillassa, M., Bertin, E., and Bouy, H., "MAXIMASK and MAXITRACK: Two new tools for identifying contaminants in astronomical images using convolutional neural networks," *Astronomy and Astrophysics* 634, A48 (Feb. 2020).
- [7] Recio-Blanco, A., et al., "Gaia Data Release 3. Analysis of RV spectra using the General Stellar Parametrizer from spectroscopy," *Astronomy and Astrophysics* 674, A29 (June 2023).
- [8] Konnik, M. and Welsh, J., "High-level numerical simulations of noise in ccd and cmos photosensors: review and tutorial," (12 2014).
- [9] Krizhevsky, A., Sutskever, I., and Hinton, G. E., "Imagenet classification with deep convolutional neural networks," in [Advances in Neural Information Processing Systems], Pereira, F., Burges, C., Bottou, L., and Weinberger, K., eds., 25, Curran Associates, Inc. (2012).
- [10] Ronneberger, O., Fischer, P., and Brox, T., "U-net: Convolutional networks for biomedical image segmentation," (2015).