# Visual Computing

Janis Hutz
https://janishutz.com

October 19, 2026

# 1 Computer Vision

## 1.1 Digital Image

**Def** **Image** $f : \mathbb{R}^n \to S$, for greyscale $n = 2$, $S = \mathbb{R}^+$, in digital form: $I : \{1, \dots, X\} \times \{1, \dots, Y\} \to S$

**Rem** Pinhole size affects blur, ***Lens Camera*** as sol.

**Rem** Charge Coupled Device (CCD) sensor reads line-by-line (rolling shutter), then each line pixel-by-pixel

**Def** **Sensor array** is an array of *photosites* (bucket of el. charge $\propto$ light intensity), then read via ADC.

**Rem** **Blooming** Caused by photosite saturation

**Def** **Dark Current** CCDs give non-zero output in darkness, fluctuates randomly

**Def** **CMOS Sensor** Each photo sensor has own amplifier, more noise, lower sensitivity, "smart" pixels bc. CMOS

**Def** **Sampling** Repeated measurement on certain interval, ***Reconstruction*** is inverse. Issues: ***undersampling*** (lose information), ***oversampling*** (too large files).

**Def** **Nyquist Frequency** highest signal freq that can be accurately captured, half of sampling rate

**Def** **Quantization** Lossy discretization of analogue value, simple versions have $k = 2^b$ values for $b$ bits

**Rem** Quantization "on" $y$-axis, Sampling "along" $x$-axis

**Def** **Res.** Geometric: PPI; Radiometric: Bits/Pixel

**Def** **Signal-Noise-R.** (SNR) Image quality index: $s = F \div \sigma$, with $F = \frac{1}{XY} \sum_{x=1}^{X} \sum_{y=1}^{Y} f(x, y)$.

**Def** **Add. Gaussian Noise** $I(x, y) = f(x, y) + c$, with $c \sim \mathcal{N}(0, \sigma^2)$, s.t. $p(c) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{c^2}{2\sigma^2}}$

**Def** **Poisson Noise** $p(k) = \frac{\lambda^k e^{-\lambda}}{k!}$

## 1.2 Filtering & Convolution

**Def** **Moving Average** New image $G$ where $G[x, y]$ is average of surrounding pixels and $F[x, y]$

**Def** **Linear Shift-Invariant Filter.** New pixels lin. comb. of neighbours, *shift-invariant* = doing same for all pixels. Good for: smoothing, noise reduction, sharpening

**Def** **Linear Operation** $L$ lin. if $L[\alpha I_1 + \beta I_2] = \alpha L[I_1] + \beta L[I_2]$, $I'_j = \sum_{i=1}^{N} \alpha_{ij} I_i$ for $j \in \{1, \dots, N\}$

**Def** **Linear Filtering** $I'(x, y) = \sum_{(i,j) \in N(x,y)} K(i, j) I(x + i, y + j)$ with $I$ the input image and $K$ the ***kernel*** of operation, $N(x, y)$ neighbourhood function for pixel $(x, y)$. Shift-Invariant if $K$ doesn't depend on $(x, y)$ (i.e. same weights everywhere)

**Def** **Kernel** Typically matrix, center of matrix is $(0, 0)$

**Def** **Correlation** $I'(x, y) = \sum_{j=-k}^{k} \sum_{i=-k}^{k} K(i, j) I(x + i, y + j)$

**Def** **Conv.** $I'(x, y) = \sum_{j=-k}^{k} \sum_{i=-k}^{k} K(-i, -j) I(x + i, y + j)$

Gen.: $g(x) = (f * h)(x) = \int_{-\infty}^{\infty} f(\tau) h(x - \tau)\, \mathrm{d}\tau$, $h(\tau)$ kernel

**Rem** If $K(i, j) = K(-i, -j)$, then Convolution = Corr.

**Rem** Convolution is linear: $[(af + bg) * h](x) = a(f * h)(x) + b(g * h)(x)$, commutative: $(f * h)(x) = (h * f)(x)$, associative: $(f * g) * h = f * (g * h)$; Diff: $\frac{\mathrm{d}}{\mathrm{d}x}(f * h)(x) = f * h'$

**Rem** At edge of image, extrapolate, options: clip filter (black), wrap around, copy edge, reflect across edge

**Def** **Gaussian Kernel** $G_\sigma = \frac{1}{2\pi\sigma^2} e^{\frac{x^2+y^2}{2\sigma^2}}$. The smooting amount depends on $\sigma$ and window size.

**Rem** $g(x, y) = g(x)g(y)$, with $g(x) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{x^2}{2\sigma^2}\right)$. Efficient implementation: First rows 1D, then cols 1D

## 1.3 Edge Detection

**Def** **Scale Space** Collection of img at diff scales & smooth.

**Rem** Finite diff. for $\frac{\partial f(x,y)}{\partial x} \approx \frac{f(x+1,y) - f(x,y)}{1}$, filter: $[1, -1]$. Can use par der. for edge detection

**Def** **Gradient** $\nabla f = [\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}]$, dir of most rapid change. ***Edge strength*** (magnitude): $M(x, y) = ||\nabla f||$.
Noise makes edge detection hard, smooth first, then edge is peak in $\frac{\partial}{\partial x}(h * f)$. ***Angle*** $\alpha(x, y) = \arctan\left(\frac{\partial f}{\partial y} \div \frac{\partial f}{\partial x}\right)$

**Thm** $\frac{\partial}{\partial x}(h * f) = \left(\frac{\partial}{\partial x} h\right) * f$

**Def** **Laplacian** $\nabla^2 f = \frac{\partial^2 f}{\partial^2 x} + \frac{\partial^2 f}{\partial^2 y}$

**Def** **LoG** $\nabla^2 G(x, y) = \frac{1}{2\pi\sigma^2} \left(\frac{x^2+y^2-2\sigma^2}{\sigma^2}\right) \exp\left(-\frac{x^2+y^2}{2\sigma^2}\right)$

Edge is at zero-crossing of $\left(\frac{\partial^2}{\partial^2 x} h\right) * f$. $\sigma$ affects scale of edges detected (larger $\sigma$ = stronger edges)

**Def** **Canny E.D.** ***1*** smooth w/ Gaussian, ***2*** gradient magnitude & angle, ***3*** Nonmaxima suppression to gradient mag. image, ***4*** double thresholding to detect strong and weak edge pixels, ***5*** reject weak edge pixels not connected with strong edge pixels

**Def** **Non-Max-Suppression** Quantize edge normal to four dir, if $M(x, y)$ smaller than either neighbour in dir, suppress, else keep

**Def** **Thresholding** Via thresholds $\theta_{\text{high}} \div \theta_{\text{low}} \in [2, 3]$ (typ)

### 1.3.1 Line Fitting

Generally challenging, missing information

**Def** **RANSAC** Random Sample Consensus:

1. Rand. sel. *seed group* of p. w/ base transf. est.
2. Compute transformation from seed group
3. Find *inliers* to this transformation
4. If inliers sufficiently large, recompute least-squares estimate of transformation on all inliers

Sample count: $w$ frac of inliers, $n$ points define hypothesis ($n = 2$ for lines), $k$ samples chosen. Prob. sample of $n$ points correct: $w^n$, prob all $k$ samples fail: $(1 - w^n)^k$, i.e. choose $k$ high to keep below failure rate

**Def** **Hough Transform** Voting technique, main idea:

1. Vote for all possible lines on which edge could lie
2. Look for line candidates that get many votes
3. Noise features votes should be inconsistent

## 1.4 Fourier Transform

**Def** **Sinusoid** $f(x) = A \cdot \sin(2\pi u x + \psi)$ with $\psi$ phase shift, equiv: $A\cos(\psi)\sin(2\pi u x) + A\sin(\psi)\cos(2\pi u x)$

**Def** **Complex Exponential** $e^{i\theta} = \cos(\theta) + i\sin(\theta)$, complex conj. $e^{-i\theta} = \cos(\theta) - i\sin(\theta)$. For sinusoid: $\theta = 2\pi u x$.

**Def** **Cont. Time F. Ser** Sig as sum of sinusoids, $f(x) = \sum_{k=-\infty}^{\infty} c_k e^{i2\pi k x \div T}$, with $T$ the period and $c_k$ fourier coeff.

**Def** **Cont. Time F. Transf** $F(u) = \sum_{\mathbb{R}} f(x) e^{-2\pi u x}\, \mathrm{d}x$, $f(x) = \sum_{\mathbb{R}} F(u) e^{i2\pi u x}\, \mathrm{d}u$. $F(u)$ is *typ* complex valued,

**Def** **Ampl. Spec** $A(u) = ||F(u)||$

**Def** **Phase Spec** $\phi(u) = \arg F(u) = \arctan\left(\frac{\Im(F(u))}{\Re(F(u))}\right)$

**Def** **DFT** used for analyzing discrete data. Applies base change to values via matrix multiplication. More general:

$$F(k) = \sum_{n=0}^{N-1} x_n e^{-i2\pi k n \div N} \text{ for } k \in \{0, 1, \dots, N-1\}$$

For images at location $(u, v)$, or $F = Uf$, with $U$ Fourier Mat.:

$$F(u,v) = \sum_{x=0}^{N-1} \sum_{y=0}^{M-1} I(x,y) \cdot e^{-i2\pi\left(\frac{ux}{N} + \frac{vy}{M}\right)}$$

For continuous time, we get:

$$\mathcal{F}[g(x,y)](u,v) = \int \int_{\mathbb{R}^2} g(x,y) e^{-2i\pi(ux+vy)} \, \mathrm{d}x \, \mathrm{d}y$$

Inverted by negating exp and swapping $g$ and $F$ (or $F$ and $I$)

**Thm** **Convolution** $\mathcal{F}[f * g] = F \cdot G$, $\mathcal{F}[f \cdot g] = F * G$, with $F, G$ the fourier transforms

**Rem** **Filtering** Can be achieved: $h * f = \mathcal{F}^{-1}[H \cdot F]$

**Rem** **Dirac Delta** $\delta(x) = \begin{cases} \infty & \text{if } x = 0 \\ 0 & \text{otherwise} \end{cases}$, following prop for sampling to alleviate issue of 0 everywhere after fourier:

$$\int_{-\infty}^{\infty} f \cdot \delta(x - a) \, \mathrm{d} = f(a)$$

**Rem** **Restoration** To restore image, inverse kernel $\widetilde{h}(x) = \mathcal{F}^{-1}\left[\frac{1}{H(x)}\right]$, with $H(x) = \mathcal{F}[h(x)]$ and $h(x)$ degradation filter.

**Ex** For motion blur: $h(x,y) = \frac{1}{2l}[\theta(x+l) - \theta(x-l)]\delta(y)$. $H(x) = \frac{\sin(2\pi ul)}{2\pi ul}$

## 1.5 Local Features

## 1.6 Optical Flow

**Def** **Brightness** $I(x,y) = 0.299 \cdot R(x,y) + 0.587 \cdot G(x,y) + 0.114 \cdot B(x,y)$, in video $I(x,y,y)$ at given timestamp

**Def** **Flow Visualization** (Will add colour wheel here in some way, slide 43 of optical flow slide deck)

**Rem** **Optical Flow** estimates motion of each pixel in consecutive frames. We look for nearby pixels of same colour. For that, assume small motion (only moves a bit) and colour consistency (i.e. brightness stays consistent for same pixel)

**Def** **Bright. Constancy Eq.** $\frac{\partial I}{\partial x}\frac{\mathrm{d}x}{\mathrm{d}t} + \frac{\partial I}{\partial y}\frac{\mathrm{d}y}{\mathrm{d}t} + \frac{\partial I}{\partial x} = 0$. Derived from multivariate Taylor expansion, cancelling terms, dividing by $\delta t$. Shorthand: $\mathbb{I}_x u + I_y v + I_t = 0$, or in vector form: $\nabla I^\top v + I_t = 0$. $I_x$, $I_y$ are image gradients at point $p$, $u, x$ are flow velocities.

Comp: $I_x, I_y$) via Sobel Filter or DoG., $I_t$ via frame diff. $u$ and $v$ need to be solved for (unknowns in optical flow problem). Solution not unique with single pixel, lays on line:

**Def** **Lucas-Kanade** Flow locally smooth, const. displ. between pixels. Equiv to solving SLE $A^\top A \cdot \widehat{x} = A^\top b$

$$\begin{bmatrix} \sum_{p\in P} I_x I_x & \sum_{p\in P} I_x I_y \\ \sum_{p\in P} I_y I_x & \sum_{p\in P} I_y I_y \end{bmatrix} \cdot \begin{bmatrix} u \\ v \end{bmatrix} = \begin{bmatrix} \sum_{p\in P} I_x I_t \\ \sum_{p\in P} I_y I_t \end{bmatrix}$$

$\Rightarrow$ Harris Corner Detector (corners: good place to comp flow). If rank of $A < 2$, then aperture problem: (visible part of image too small to tell movement dir).

**Def** **Horn-Schunck**

$$E[u,v] = \iint_\Omega [(I_x u + I_y v + I_t)^2 + \lambda(||\nabla u||^2 + ||\nabla v||^2)] \, \mathrm{d}x \, \mathrm{d}y$$

w/ $||\nabla u||^2 = \left(\frac{\partial u}{\partial x}\right)^2 + \left(\frac{\partial u}{\partial y}\right)^2$, $\lambda$ weight. In practice: img grid

$$\min_{u,v} \sum_{i,j} E_s(i,j) + \lambda E_d(i,j)$$

**Algorithm 1** Horn-Schunck

1 Precompute image gradients $I_x, I_y$
2 Precompute temporal gradients $I_t$
3 Initialize flow-field $(u = 0, v = 0)$
4 **while** not converged **do**
5 Compute flow field updates for each pixel $\widehat{u}_{kl} = \overline{u}_{kl} - Q \cdot I_x$, $\widehat{v}_{kl} = \overline{v}_{kl} - Q \cdot I_y$

with $Q = \frac{I_x \overline{u}_{kl} + I_y \overline{v}_{kl} + I_t}{\lambda^{-1} + I_x^2 + I_y^2}$, with $\overline{u}_{kl}$ prev value, $\widehat{u}_{kl}$ new value.

## 1.7 Unitary Transforms

Images can be written as a vector (result of 'np.flatten'), thus lin. img processing: $\overrightarrow{g} = H\overrightarrow{f}$

**Def** **Unitary Transform** $A$ unitary iff $A^{-1} = A^H$ (is equiv to hermitian conj.), $A$ ***real-valued*** $A = A^*$

**Thm** Energy Conservation holds for unitary transforms

**Def** **Image Collection** $f_i$ one img, $F = [f_1 f_2 \dots f_n]$ img coll., $R_{ff} = E[f_i \cdot f_i^H] = \frac{F \cdot F^H}{n}$ auto-correlation function. In matrix form: $R_{cc} = E[\overrightarrow{c}\,\overrightarrow{c}^H] = E[A\overrightarrow{f} \cdot \overrightarrow{f}^H A^H] = A R_{ff} A^H$

**Def** **Eigenmatrix** $\Phi$ of $R_{ff}$ unitary, cols are set of Eigenvec., $R_{ff}$ symm. non-neg. def., thus $\lambda_i \geq 0 \; \forall i$, $\Lambda$ has E.V. on diags

**Def** **Karhunen-Loeve Transform** $A = \Phi^H$, cols of $\Phi$ ordered by decreasing Eigenvalue. Energy concentrating (no other unitary transf. packs as much energy into first $J$ coeffs, $\forall J$)

**Rem** Inverse transform $\overrightarrow{f} = A^H$, superpos. of "basis images", size $MN$. $A$ KL-trans, then basis imgs called "eigenimages". This can be used for recognition (works better typically than direct comp. because irrelevant details discarded). Transform $\overrightarrow{c} = W\overrightarrow{f}$ can reduce dim. from $MN$ to $J$.

**Def** **Simple Euclidean Dist.** (SSD). $\text{argmin}_i \; D_i = ||I_i - I||$

**Rem** Use PCA (KLT here), then $I_i - I = \widehat{I}_i - \widehat{I} \approx E(p_i - p)$, then $\text{argmin}_i \; D_i = ||I_i - I|| \square ||p_i - p||$

**Rem** Eigenfaces affected more by difference of ILLUMISHADE than difference between faces

**Def** **FLD** (Fisher Linear Discriminant Analysis)

$W_{opt} = \text{argmax}_W \left(\frac{\det(W R_B W^H)}{\det(W R_W W^H)}\right)$, with ($N_i$ samples in class $i$)

$$R_B = \sum_{i=1}^{c} N_i (\overrightarrow{\mu_i} - \overrightarrow{\mu})(\overrightarrow{\mu_i} - \overrightarrow{\mu})^H \quad R_W = \sum_{i=1}^{c} \sum_{\overrightarrow{\Gamma_l} \in \text{Class}(i)}$$

Solution: Generalized Eigenvec. $\overrightarrow{w_i}$ corresponding to $K$ largest Eigenvalues $\lambda_i$, i.e. $R_B \overrightarrow{w_i} = \lambda_i R_W \overrightarrow{w_i}$. Issue: usually singular

**Rem** **Varying Illumination** All images of same Lambertian surface with different illumination lie in 3D linear subspace: $f(x,y) = a(x,y)(l^\top n(x,y))L$, with $a$ surface albedo, $L$ light source intensity, $n$ the surface normal and $l$ light source direction

**Rem** **Appearance Manifold** For every object, sample set of viewing conditions, then use as feature vecs, apply PCA over all the imgs, keep dominant PCs. Sequence of views for 1 object represent manifold in space of projections. ***Object-pose manifold***: Appearance changes projected on PCs (1D pose changes)

**Rem** **JPEG** Uses Campbell-Robson Contrast sensitivity curve (humans don't see high freq too well). Uses DCT for en-/decoding with small block size faster, larger blocks compressing better.

**Rem** **Quantization** via `int(dct_weights / quant_table)`

**Rem** **Zig-Zag encoding** Run-length to compress further

**Def** **DCT** $X_k = \sum_{n=0}^{N-1} x_n \cos\left(\frac{(2n+1)\pi k}{2N}\right) \Leftrightarrow X_k = \overrightarrow{C}_k^\top \overrightarrow{x}$

## 1.8 Pyramids and Wavelets

**Def** **Gaussian Pyramid** Smooth w/ gaussians repeatedly (why: gaussian $\times$ gaussian = gaussian)

**Thm** LoG $\approx$ DoG (DoG is scaled LoG, exact approx as $\delta\sigma \to 0$)

**Def** **Self-Inverting Filter** A filter that can be applied in *both* directions (Synthesis (reconstruction) and Analysis (decomposition))

**Def** **Wavelet** Wave func, localized in time and freq.

**Rem** **1D** Recursive application of two-band filter bank to lowpass result yields octave band splitting

**Def** **Haar TF** $H$: Sample $h_k(x)$ at $\{m \div N\} \; \forall m \in \{0, \dots, N-1\}$

**Rem** **Two-Filterbanks w/ perfect reconstruction**

***Analysis***: $\left[\frac{-1}{4}, \frac{1}{2}, \frac{3}{2}, \frac{1}{2}, \frac{-1}{4}\right]$ (Low-Pass) $\left[\frac{1}{4}, \frac{-1}{2}, \frac{1}{4}\right]$ (High-Pass)

***Synthesis***: $\left[\frac{-1}{4}, \frac{1}{2}, \frac{-1}{4}\right]$ (Low-Pass) $\left[\frac{1}{4}, \frac{1}{2}, \frac{-3}{2}, \frac{1}{2}, \frac{1}{4}\right]$ (High-Pass)