

Cost Name		Oddball Firearms 1.2													Scope Sight Notes		
		Skill	IA	Speed	ROF	Recoil	Range	Hands	Weight	Action	Caliber	Capacity					
American Derringer, USA																	
275-50	SA Derringer	S	11	0	2	-16 to -27	20	1	V2	SA	V2	2	--	5	D		
300-36	DA Derringer	S	11	0	2	-16 to -22	20	1	V3	DA	V3	2	--	5	D		
400	COP	S	11	0	4	-22	30	1	0.5	DA	.357 Mag	4	--	5	D		
350	Mini-COP	S	10	0	4	-16	20	1	0.5	DA	.22 Mag	4	--	5	D		
1250	Semmerling LM-4	S	11	0	1	~	25	1	0.4	MAN	.45 acp	4B	--	5	M		
Bond Arms, USA																	
349	Texas Defender	S	11	0	2	-18 to -25	25	1	0.6	SA	V1	2	--	5	C, D		
Crossfire LLC, USA																	
1895	Crossfire Mk1	L	25	9	3	-16	200	2s	4.52	pump	5.56mm	30B	--	10	M,P,R		
			23		3	-29	100				18.2x76	4 tube					
Davis Industries, USA																	
99	Derringer	S	9	0	2	-15 to -20	20	1	0.3	SA	V4	2	--	5	I2		
Downsizer Corp., USA																	
399	Downsizer	S	10	0	1/3	~	10	1	0.33	DA	.45 acp	single shot	--	5	D		
DPMS, USA																	
1595	A-15 Panther	S	20	5	3	-18	75	2	2.76	pump	5.56mm	30B (5-100)	--	9			
Heckler and Koch GmbH, Germany																	
	P11 ZUB	S	15	0	4	-17	30	1	1.2	DA	7.62x36 Spe	5 cassette	--		Q, U, Z		
Firearms International, USA																	
275	High Standard Derringe	S	10	0	2	-17	15	1	0.3	DA	.22 Mag	2	--	5	D		
Gem-Tech, USA																	
375	LDE-9 Pengun	S	5	0	1/5	~	5	1	0.05	SA	9x17mm	single shot	--	--			
IM Arms, USA																	
	Model 3	L/A	25	10	13	-17/~/-33	300	2s	5.8	auto	7.62x39mm	75B (30)	--	10	F		
			23		13	-16/~/-30	100				9mm	32B					
Norinco, China																	
	Type 85	S	12	0	4	-15	20	1	0.3	DA	.22 LR	4	--		K		
RSAF (various manufacturers including Izhevsk, KBP, Izhmash, TsKIB), Russia																	
	APS	L/A	22	8	?		100	2s	3.4	auto	5.66APS	26B	--	9	F, U, Z		
	MP-451	S	11	0	2	-18	30	1	0.4	DA	9x17mm	2	--	5	D		
	MSP Groza	S	10	0	2	-19	20	1	0.6	DA	7.62x38mm	2	--	5	D, L, Q, Z		
	NRS Scout knife	S	9	0	1/4	~	20	1	0.4	DA	7.62x42mm	single shot	--	5	K, L, Q, Z		
	S4M	S	11	0	2	-19	30	1	0.65	DA	7.62x62mm	2	--	5	D, L, Q, Z		
	SPP-1 (SPP-1M)	S	11	0	2	-18	20	1	1.03	DA	4.5mm SPS	2	--	5	D, U, Q, Z		
Savage, USA																	
677	510	S	25	4	1/3	~	200	2	2.47	bolt	V5	2 internal	Le-8	--			
449	24F Combination	L	27	9	1/3	~	200	2s	3.65	semi	.30-30	single shot	--	10			
			24		1/3	~	100				18.2x76mm	single shot					
Springfield Armory, USA																	
219	M6 Survival	L	26	4	1/3	~	100	2s	1.84	semi	.22 lr	single shot	--	10			
		L	23		1/3	~	50				0.41	single shot					
SSK Industries, USA																	
2240	Whisper Contender	S	21	3	1/3	~	200	2	1.92	SA	.300 Whispc	single shot	A-4	--	S, X, Z		
2475	Whisper Encore	S	23	4	1/3	~	400	2	2.55	SA	.338 Whispc	single shot	Le-9	--	S, X, Z		
Thompson Center Arms, USA																	

680	Contender 10"	S	23	2	1/3	~	u300	2	1.56	SA	V6	single shot	Le-8
775	Contender 14"	S	25	3	1/3	~	u300	2	1.9	SA	V6	single shot	Le-9
864	Encore 12"	S	23	3	1/3	~	u500	2	2.24	SA	V7	single shot	Le-9
871	Encore 15"	S	26	4	1/3	~	u500	2	2.35	SA	V7	single shot	Le-9
Weatherby, USA													
1409	Mark V CFP	S	26	5	1/2	~	300	2	2.7	bolt	V8	3 internal	Le-9 --

COST: Real world cost "suggested retail equivalent" of the weapon, including all listed features.

NAME: Manufacturer's model name when available, common NATO nomenclature otherwise.

SKILL: Character skillused for firing weapon; Smallarm, Longarm and/or Autofire.

IA: Inherent Accuracy of weapon, including optical sight if fitted with one.

Speed: Speed of weapon, including all listed accessories, for calculating Initiative.

ROF: The highest numbers of rounds that can be fired in a given turn, representing automatic fire. Semiauto firing is generally four (4) rounds in a turn, and two 3-round bursts in a given turn.

RECOIL: Successive shot penalty for semiauto/burst/fullauto fire. Used in place of the standard -15/-30 of the rulebook.

RANGE: Effective engagement range, generally less than the extravagant claims of the manufacturer.

HANDS: Numbers hands generally required to operate the weapon. Refer to combat rules for using a weapon other than as listed.

WEIGHT: Weight of the weapon (kg). Includes all accessories and a loaded box magazine if used, does not include weight of belted ammc

ACTION: Basic type of weapon action, generally semi, burst or auto. NOTES will further define type of fire the weapon is capable of.

CALIBER: Standard caliber of weapon, expressed in most common name (thus mix of standard and metric).

CAPACITY: Capacity of standard ammunition feed device. Most common listed first, with options in parenthesis.

SCOPE: Reference identifier for optical sight if commonly fitted. Refer to Optical Sight list for information on particular scopes.

SIGHT: The portion of the IA number derived from the iron sights of the weapon. For use in recalculating IA as sighting systems are chang

NOTES: Accessories, features and additional information particular to each model. Refer to the following list.

C	Calibers can be changed simply by changing the barrels.
D	Derringer. One or two barrels, manually loaded with an individual round.
I	poor quality causing a reduction in IA I1: -1 IA do to quality I2: -2 IA do to quality I3: -3 IA do to quality
K	The weapon includes a knife blade, with the barrel(s) mounted in the handle and firing along the side of the blade.
L	Ammo is held in clips, allowing complete reloading in one turn.
M	Manual action has to be hand cycled between every shot
Q	near silent firing through the use of special ammunition which uses a piston system that contains all propellant gasses within the cartridge
U	Designed for underwater shooting. Effective range listed is for firing in air. Ranges underwater are as follows; P11 ZUB: 5m deep, 15m; 20m deep 10m APS: 5m deep, 30m; 20m deep, 20m; 40m deep, 11m SPP-1M: 5m deep, 17m; 20m deep, 11m; 40m deep, 6m
V	Various calibers available. V1: 9mm, .32H&R, .45 Colt, .357 mag, .40 S&W, .45 acp, .44 Mag V2: 26 calibers ranging from .22 mag to .45-70. Weight ranges from 0.2 to 0.4, with smaller calibers being heavier V3: .22 Mag, .357 Mag, 9mm, .40 S&W. Weight ranges from 0.2 to 0.4, with smaller calibers being heavier V4: .22 LR, .2 Mag, .25 acp, .32 acp, .38 Spl, 9mm V5: .22-250, .243, 7.62mm V6: Virtually any caliber up to .30, including custom. V7: Virtually any caliber including custom. V8: 5.56mm, .22-250, .243, 7mm-08, 7.62mm
X	Prototype, experimental and/or extremely limited production
Z	Restricted availability, Class-3 license required in the USA

case.