First results

Comparison

Current scheduler (no data sets information) x Location-based scheduler

- To check the different behaviors between the current scheduler and the new one.
- Also, to check the different behaviors as we change the data sets in the QBoxes, using the new scheduler.


No data sets

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB_second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB_long

QBoxes: 2

5 and 7 QMobos



Added:


q2: first, second

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB_second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB_long

QBoxes: 2

• 5 and 7 QMobos



Added:


q2: first, second

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB_second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB_long

QBoxes: 2

• 5 and 7 QMobos



Added:


q2: first, triplet

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB_second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB_long

QBoxes: 2

• 5 and 7 QMobos




Added: q1: first

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB long

QBoxes: 2

5 and 7 QMobos



Added:

q1: first, second


q2: triplet

Workload: 8 Jobs

- 2 QJOB_first(s)
- 1 QJOB second
- 3 QJOB_triplet(s)
- 1 QJOB_null_dataset
- 1 QJOB_long

QBoxes: 2

• 5 and 7 QMobos



No data sets

Workload: About 400 jobs QBoxes: 1000 QMobos

