

ResolveDesk AI — REST API Documentation

Developer API Specifications

Authentication

All API requests must include a Bearer token in the headers:

Authorization: Bearer

Generate API keys under User Settings > Developer Options > API Keys.

Base URL

<https://api.resolvedesk.ai/v1>

Primary Endpoints

1. Projects:

- List Projects: GET /projects
- Create Project: POST /projects (payload: {'name': 'Project Name', 'visibility': 'private'})

2. Tasks:

- Get Project Tasks: GET /projects/{project_id}/tasks
- Create Task: POST /projects/{project_id}/tasks (payload: {'title': 'Task Title', 'priority': 'high'})

Rate Limiting

Basic: 100 requests per minute per key.

Pro: 1,000 requests per minute per key.

Enterprise: Custom contract rates.

Exceeding limits will return HTTP code 429 Too Many Requests.

Developer Webhooks and Payload Specifications

Registering Webhooks

Register webhooks from the developer portal console (POST /webhooks) to receive real-time updates when tasks are edited or created. Payloads are sent as JSON via POST with a signature key in headers (X-ResolveDesk-Signature) to verify payload authenticity. Webhook responses must return HTTP 200 within 5 seconds to avoid retries.

Sample Task Webhook JSON Payload

JSON schema structure:

```
{ 'event': 'task.updated', 'timestamp': '2026-07-14T00:00:00Z', 'data': { 'task_id': 'tsk_002', 'title': 'Updated Title', 'assignee': 'cust_001', 'status': 'Done' } }
```