

Annand_DSE6210_lab6

February 22, 2025

0.1 Joseph Annand DSE 6210 Lab 6

0.2 Import pymongo

```
[1]: import pymongo
      from pymongo.mongo_client import MongoClient
      from pymongo.server_api import ServerApi
```

0.3 Exercise 1

Create a mongo_db connection with pymongo to your database
<https://pymongo.readthedocs.io/en/stable/examples/authentication.html>

```
[2]: #https://pymongo.readthedocs.io/en/stable/examples/authentication.html
      #create your connection string
      connect_string = "mongodb+srv://annandj:kitkatbaka@cluster0.mmpel.mongodb.net/?
      ↪retryWrites=true&w=majority&appName=Cluster0"
      #create a connection to your Atlas cluster
      try:
          client = MongoClient(connect_string, server_api=ServerApi('1'))
      except:
          print("Connection failed :/")
```

0.4 Exercise 2

Using your client created from exercise 1, connect to a new database, homework6.
Once you have connected to the database set your collection to a new collection, students.
<https://pymongo.readthedocs.io/en/stable/tutorial.html> -> getting database and getting collection

```
[3]: db = client.homework6
      collection = db.students
```

0.5 Exercise 3

I have created a list of student data containing documents that you will need to insert into MongoDB.
Using insert_many, insert the list of documents into the students collection.

```
[4]: student_data = [

    {"instructor": "Martin",
     "class": "Chemistry",
     "max_students": 25,
     "term": "SP2",
     "students": ["Bob Mackey", "George Straight", "Bill Cowher", "Stanley Kubrick", 'Martin Sheen', "Charlize Theron"]},
    {"instructor": "Lowhorn",
     "class": "Big Data",
     "max_students": 10,
     "term": "SU1",
     "students": ["Charles Barkely", "Charlie Sheen", "Tina Turner", "Paul Walker", 'Dwayne Johnson', "Courtney Cox", "Margot Robbie"]},
    {"instructor": "Carlin",
     "class": "Discrete Math",
     "max_students": 25,
     "term": "SP2",
     "students": ["Tim Couch", "George Straight", "Michael Douglas", "Peyton Manning", 'Wade Boggs', "Doc Rivers", "Drew Bledsoe", "Ray Bourque"]},
    {"instructor": "Lowhorn",
     "class": "Programming for DS",
     "max_students": 25,
     "term": "SP2",
     "students": ["Roger Clemens", "Ray Allen", "Marcus Smart", "Kevin Garnett", 'Mo Vaughn', "Uma Thurman", "Conan O'Brien", "Mark Wahlberg"]},
    ]

collection.insert_many(student_data)
```


```
[4]: InsertManyResult([ObjectId('67b9ecc0bb0218368e2ddee8'),
ObjectId('67b9ecc0bb0218368e2ddee9'), ObjectId('67b9ecc0bb0218368e2ddeea'),
ObjectId('67b9ecc0bb0218368e2ddeeb')], acknowledged=True)
```

0.6 Exercise 4

What MongoDB type do Python lists get converted to?

Submit a screen shot of your collection in MongoDB with this python file.

Python lists are converted to Arrays.



0.7 Exercise 5

George Straight accidentally registered for two courses in the SP2 Session.

Using a `pymongo.update()`, remove him from Carlin's class

Note: Your key is `instructor`.

Use the `$pull` method to extract the element from the array.

https://www.geeksforgeeks.org/python-mongodb-update_one/

<https://www.mongodb.com/docs/manual/reference/operator/update/pull/>

```
[5]: filter = {'instructor': 'Carlin'}
collection.update_one(filter, { "$pull": { "students" : "George Straight" } })
```

```
[5]: UpdateResult({'n': 1, 'electionId': ObjectId('7fffffff0000000000000177'),
'opTime': {'ts': Timestamp(1740238012, 26), 't': 375}, 'nModified': 1, 'ok':
1.0, '$clusterTime': {'clusterTime': Timestamp(1740238012, 26), 'signature':
{'hash': b'T&nz4\x19i\xd0\xf1S7HX\xf8#\x8f\xacU\x88\x0c', 'keyId':
7427919520641056769}}, 'operationTime': Timestamp(1740238012, 26),
'updatedExisting': True}, acknowledged=True)
```

0.8 Exercise 6

A new student has signed up for all three SP2 sessions, his name is Tom Brady.

Update the SP2 classes by inserting the student Tom Brady into the students object.

Note: Many not one. Push not pull.

```
[6]: filter = { "term": "SP2" }
collection.update_many(filter, { "$push": { "students": "Tom Brady" } })
```

```
[6]: UpdateResult({'n': 3, 'electionId': ObjectId('7fffffff0000000000000177'),
'opTime': {'ts': Timestamp(1740238012, 35), 't': 375}, 'nModified': 3, 'ok':
1.0, '$clusterTime': {'clusterTime': Timestamp(1740238012, 35), 'signature':
{'hash': b'T&nz4\x19i\xd0\xf1S7HX\xf8#\x8f\xacU\x88\x0c', 'keyId':
```

```
7427919520641056769}}, 'operationTime': Timestamp(1740238012, 35),  
'updatedExisting': True}, acknowledged=True)
```

0.9 Exercise 7

The college has decided that Chemistry was not a good fit for the data science program. Delete it from the collection.

https://www.geeksforgeeks.org/python-mongodb-delete_one/

```
[7]: filter = { "class": "Chemistry" }  
collection.delete_one(filter)
```

```
[7]: DeleteResult({'n': 1, 'electionId': ObjectId('7fffffff000000000000000177'),  
'opTime': {'ts': Timestamp(1740238012, 37), 't': 375}, 'ok': 1.0,  
'$clusterTime': {'clusterTime': Timestamp(1740238012, 37), 'signature': {'hash':  
b'T&nz4\x19i\xd0\xf1S7HX\xf8#\xf8\xacU\x88\x0c', 'keyId': 7427919520641056769}},  
'operationTime': Timestamp(1740238012, 37)}, acknowledged=True)
```

0.10 Exercise 8

Using find, print all of the documents to the console. This should be a query against the MongoDB database.

```
[8]: for x in collection.find():  
    print(x)
```

```
{'_id': ObjectId('67b9ecc0bb0218368e2dde9'), 'instructor': 'Lowhorn', 'class':  
'Big Data', 'max_students': 10, 'term': 'SU1', 'students': ['Charles Barkely',  
'Charlie Sheen', 'Tina Turner', 'Paul Walker', 'Dwayne Johnson', 'Courtney Cox',  
'Margot Robbie']}  
{'_id': ObjectId('67b9ecc0bb0218368e2ddeea'), 'instructor': 'Carlin', 'class':  
'Discrete Math', 'max_students': 25, 'term': 'SP2', 'students': ['Tim Couch',  
'Michael Douglas', 'Peyton Manning', 'Wade Boggs', 'Doc Rivers', 'Drew Bledsoe',  
'Ray Bourque', 'Tom Brady']}  
{'_id': ObjectId('67b9ecc0bb0218368e2ddeeb'), 'instructor': 'Lowhorn', 'class':  
'Programming for DS', 'max_students': 25, 'term': 'SP2', 'students': ['Roger  
Clemens', 'Ray Allen', 'Marcus Smart', 'Kevin Garnett', 'Mo Vaughn', 'Uma  
Thurman', 'Conan O'Brien', 'Mark Wahlberg', 'Tom Brady']}
```

0.11 Exercise 9

Instead of using the default hash `_id`, what would you recommend as a unique ID for each document?

I'd recommend using the instructor, class, and term fields together to create a new unique ID for each document. Assuming that a single instructor does not teach two sections of the same course in a given term, each instructor-class-term combination may act as a unique identifier for each document. A compound unique index based on these three fields could be created.

```
[9]: collection.create_index([("instructor", pymongo.ASCENDING), ("class", pymongo.
    ↪ASCENDING), ("term", pymongo.ASCENDING)], unique=True)
```

```
[9]: 'instructor_1_class_1_term_1'
```

0.12 Exercise 10

Drop the students collection from the database AND close your client.

```
[10]: collection.drop()
      client.close()
```