

IPC

Input:

```
Jannani@Jannani: ~/ipc
GNU nano 7.2 ipc.c
#include <stdio.h>
#include <unistd.h>
#include <string.h>
/* Numerical Data block from data.txt */
101 A 5000 5 50 60 70
102 B 7000 6 40 55 65
103 C 6500 3 80 90 85
// New record instances, using numerical data from data.txt
struct Record records[] = {
    {101, 'A', 5000, 5, 50, 60, 70},
    {102, 'B', 7000, 6, 40, 55, 65},
    {103, 'C', 6500, 3, 80, 90, 85}
};
int main() {
    int fd[2];
    char msg[] = "Hello";
    char buf[20];
    pipe(fd);
    if (fork() > 0) {
        write(fd[1], msg, strlen(msg)+1);
    } else {
        read(fd[0], buf, sizeof(buf));
        printf("Received: %s\n", buf);
    }
    return 0;
}
```

Output:

```
Jannani@Jannani: ~/ipc
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

jannani@jannani:~$ cd ipc
jannani@jannani:~/ipc$ vi ipc.c
jannani@jannani:~/ipc$ nano ipc.c
jannani@jannani:~/ipc$ gcc ipc.c
jannani@jannani:~/ipc$ ls
a.out ipc ipc.c ipc.c.save ipc.save
jannani@jannani:~/ipc$ ./a.out
jannani@jannani:~/ipc$ Received: Hello
jannani@jannani:~/ipc$
```