

eduix

```
MariaDB [app_localization_service]> show tables;;
```

```
+-----+
| Tables_in_app_localization_service |
+-----+
| localization                        |
| localizedValue                      |
| organization                        |
| permission                          |
| product                            |
| user                                |
| user_organization                   |
| user_permission                     |
+-----+
```

```
8 rows in set (0.02 sec)
```

eduiX

```
CREATE TABLE `localization` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `organizationId` int(11) NOT NULL,  
  `productId` int(11) NOT NULL,  
  `locale` varchar(25) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci DEFAULT NULL,  
  `name` varchar(255) NOT NULL,  
  PRIMARY KEY (`id`),  
  KEY `organizationId` (`organizationId`),  
  KEY `productId` (`productId`),  
  CONSTRAINT `localization_ibfk_1` FOREIGN KEY  
(`organizationId`) REFERENCES `organization` (`id`),  
  CONSTRAINT `localization_ibfk_2` FOREIGN KEY  
(`productId`) REFERENCES `product` (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=10 DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `localizedValue` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `localizationId` int(11) NOT NULL,  
  `localizationKey` varchar(255) DEFAULT NULL,  
  `localizationValue` text,  
  `deleted` int(11) NOT NULL DEFAULT '0',  
  `hidden` int(11) NOT NULL DEFAULT '0',  
  PRIMARY KEY (`id`),  
  KEY `localizationId` (`localizationId`),  
  CONSTRAINT `localizedValue_ibfk_1` FOREIGN KEY  
  (`localizationId`) REFERENCES `localization` (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `organization` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `orgname` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci DEFAULT NULL,  
  `apiKey` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=3 DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `organization_product` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `organizationId` int(11) NOT NULL,  
  `productId` int(11) NOT NULL,  
  PRIMARY KEY (`id`),  
  UNIQUE KEY `organization_product_idx`  
  (`organizationId`,`productId`),  
  KEY `productId` (`productId`),  
  CONSTRAINT `organization_product_ibfk_1` FOREIGN KEY  
  (`organizationId`) REFERENCES `organization` (`id`),  
  CONSTRAINT `organization_product_ibfk_2` FOREIGN KEY  
  (`productId`) REFERENCES `product` (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=8 DEFAULT CHARSET=utf8;
```



```
CREATE TABLE `permission` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `type` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci NOT NULL,  
  `organizationId` int(11) NOT NULL,  
  `productId` int(11) NOT NULL,  
  PRIMARY KEY (`id`),  
  KEY `productId` (`productId`),  
  KEY `organizationId` (`organizationId`,`productId`),  
  CONSTRAINT `permission_ibfk_1` FOREIGN KEY  
(`organizationId`) REFERENCES `organization` (`id`),  
  CONSTRAINT `permission_ibfk_2` FOREIGN KEY (`productId`)  
REFERENCES `product` (`id`),  
  CONSTRAINT `permission_ibfk_3` FOREIGN KEY  
(`organizationId`,`productId`) REFERENCES  
`organization_product` (`organizationId`,`productId`)  
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `product` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `productname` varchar(255) DEFAULT NULL,  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=12 DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `user` (  
  `id` int(11) NOT NULL AUTO_INCREMENT,  
  `firstName` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci NOT NULL,  
  `lastName` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci NOT NULL,  
  `screenName` varchar(255) CHARACTER SET utf8mb4 COLLATE  
utf8mb4_unicode_ci NOT NULL,  
  `isSystemAdmin` bit(1) DEFAULT b'0',  
  PRIMARY KEY (`id`)  
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8;
```


eduix

```
CREATE TABLE `user_organization` (  
  `userId` int(11) NOT NULL,  
  `organizationId` int(11) NOT NULL,  
  PRIMARY KEY (`userId`,`organizationId`),  
  KEY `organizationId` (`organizationId`),  
  CONSTRAINT `user_organization_ibfk_1` FOREIGN KEY  
(`userId`) REFERENCES `user` (`id`),  
  CONSTRAINT `user_organization_ibfk_2` FOREIGN KEY  
(`organizationId`) REFERENCES `organization` (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8;
```

eduix

```
CREATE TABLE `user_permission` (  
  `userId` int(11) NOT NULL,  
  `permissionId` int(11) NOT NULL,  
  PRIMARY KEY (`userId`,`permissionId`),  
  KEY `permissionId` (`permissionId`),  
  CONSTRAINT `user_permission_ibfk_1` FOREIGN KEY  
  (`userId`) REFERENCES `user` (`id`),  
  CONSTRAINT `user_permission_ibfk_2` FOREIGN KEY  
  (`permissionId`) REFERENCES `permission` (`id`)  
) ENGINE=InnoDB DEFAULT CHARSET=utf8;
```