

Databases Autumn 2025

Hand-In Exercise 1

October 6, 2025

Aiysha Frutiger

Jannick Seper

Luis Tritschler

Total Points	
---------------------	--

This template showcases various useful latex commands and setups. Remove this for your actual hand-in.

Task 1

Relational algebra is a treat with L^AT_EX, as can be seen in Equation (1):

$$\pi [Attribute1, Attribute2] (\sigma [Attribute = Something] (Entity1) \bowtie Entity2) \quad (1)$$

Task 2

(a) Person on Name:

$$\sigma [Name = 'ChristopherNolan'] (Person) \quad (2)$$

Activity on SceneAuthor:

$$\sigma [Activity = 'director'] (SceneAuthor) \quad (3)$$

Add join on both:

$$\pi [MovieID, SceneID] (\sigma [Name = 'ChristopherNolan' \wedge Activity = 'director'] (Person \bowtie SceneAuthor)) \quad (4)$$

(b) Movie on Title:

$$\sigma [MovieTitle = 'Inception'] (Movie) \quad (5)$$

Hans Zimmer as composer (within that movie):

$$\pi [MovieID, SceneID] (\sigma [MovieTitle = 'Inception' \wedge Name = 'HansZimmer' \wedge Activity = 'composer'] (Movie \bowtie SceneAuthor \bowtie Person)) \quad (6)$$

Christopher Nolan as screenwriter (within that movie):

$$\pi [MovieID, SceneID] (\sigma [MovieTitle = 'Inception' \wedge Name = 'ChristopherNolan' \wedge Activity = 'screenwriter'] (Movie \bowtie SceneAuthor \bowtie Person)) \quad (7)$$

Intersect on scene key then output SceneID:

$$\begin{aligned} & \pi [SceneID] \\ & ((\pi [MovieID, SceneID] \\ & (\sigma [MovieTitle = 'Inception' \wedge Name = 'HansZimmer' \wedge Activity = 'composer'] \\ & (Movie \bowtie SceneAuthor \bowtie Person))) \cap \\ & (\pi [MovieID, SceneID] \\ & (\sigma [MovieTitle = 'Inception' \wedge Name = 'ChristopherNolan' \wedge Activity = 'screenwriter'] \\ & (Movie \bowtie SceneAuthor \bowtie Person)))) \quad (8) \end{aligned}$$

(c) Person on Name:

$$\sigma [Name = 'QuentinTarantino'] (Person) \quad (9)$$

Actor role on ScenePerformer:

$$\sigma [Role = 'actor'] (ScenePerformer) \quad (10)$$

Director activity on SceneAuthor:

$$\sigma [Activity = 'director'] (SceneAuthor) \quad (11)$$

Combine and output scene Titles:

$$\begin{aligned} & \pi [Title] (\sigma [Name = 'QuentinTarantino' \wedge Role = 'actor' \wedge Activity = 'director'] \\ & (Scene \bowtie ScenePerformer \bowtie SceneAuthor \bowtie Person)) \quad (12) \end{aligned}$$

(d) Actor on ScenePerformer:

$$\sigma [Name = 'RobertDowneyJr.' \wedge Role = 'actor'] (ScenePerformer \bowtie Person) \quad (13)$$

Author on SceneAuthor:

$$\sigma [Name = 'RobertDowneyJr.'] (SceneAuthor \bowtie Person) \quad (14)$$

Union on MovieID, then output MovieTitle:

$$\begin{aligned} & \pi [MovieTitle] \\ & ((\pi [MovieID] (\sigma [Name = 'RobertDowneyJr.' \wedge Role = 'actor'] (ScenePerformer \bowtie Person))) \\ & \cup \pi [MovieID] (\sigma [Name = 'RobertDowneyJr.'] (SceneAuthor \bowtie Person))) \bowtie Movie) \quad (15) \end{aligned}$$

(e) Actor on ScenePerformer:

$$\sigma [Name = 'ScarlettJohansson' \wedge Role = 'actor'] (ScenePerformer \bowtie Person) \quad (16)$$

Stunt double on ScenePerformer:

$$\sigma [Name = 'ScarlettJohansson' \wedge Role = 'stuntdouble'] (ScenePerformer \bowtie Person) \quad (17)$$

Intersect on scene key, then output Titles:

$$\begin{aligned} & \pi [Title] \\ & ((\pi [MovieID, SceneID] (\sigma [Name = 'ScarlettJohansson' \wedge Role = 'actor'] \\ & \quad (ScenePerformer \bowtie Person))) \cap \pi [MovieID, SceneID] \\ & \quad (\sigma [Name = 'ScarlettJohansson' \wedge Role = 'stuntdouble'] \\ & \quad (ScenePerformer \bowtie Person))) \bowtie Scene) \quad (18) \end{aligned}$$

(f) Person on Name (subset of Person):

$$F_{1.1} = \{p | p \in Person \wedge p.Name = 'ChristopherNolan'\} \quad (19)$$

Activity on SceneAuthor (subset of SceneAuthor):

$$F_{1.2} = \{sa | sa \in SceneAuthor \wedge sa.Activity = 'director'\} \quad (20)$$

Join by PID, output (MovieID,SceneID) without Person:

$$\{\langle sa.MovieID, sa.SceneID \rangle | sa \in F_{1.2} \wedge \exists p (p \in F_{1.1} \wedge p.PID = sa.PID)\} \quad (21)$$

(g) Movie on Title:

$$G_{2.1} = \{m | m \in Movie \wedge m.MovieTitle = 'Inception'\} \quad (22)$$

Hans Zimmer as composer (within that movie):

$$\begin{aligned} G_{2.2} = & \{sa | sa \in SceneAuthor \wedge sa.Activity = 'composer' \wedge \\ & \exists p (p \in Person \wedge p.PID = sa.PID \wedge p.Name = 'HansZimmer') \wedge \\ & \exists m (m \in G_{2.1} \wedge m.MovieID = sa.MovieID)\} \quad (23) \end{aligned}$$

Christopher Nolan as screenwriter (within that movie):

$$\begin{aligned} G_{2.3} = & \{sa | sa \in SceneAuthor \wedge sa.Activity = 'screenwriter' \wedge \\ & \exists p (p \in Person \wedge p.PID = sa.PID \wedge p.Name = 'ChristopherNolan') \wedge \\ & \exists m (m \in G_{2.1} \wedge m.MovieID = sa.MovieID)\} \quad (24) \end{aligned}$$

Intersect on full scene key, then output SceneID:

$$\{\langle x.SceneID \rangle | x \in G_{2.2} \wedge \exists y (y \in G_{2.3} \wedge y.MovieID = x.MovieID \wedge y.SceneID = x.SceneID)\} \quad (25)$$

(h) Person on Name (subset of Person):

$$H_{3.1} = \{p | p \in Person \wedge p.Name = 'QuentinTarantino'\} \quad (26)$$

Actor role on ScenePerformer:

$$H_{3.2} = \{sp | sp \in ScenePerformer \wedge sp.Role = 'actor'\} \quad (27)$$

Director activity on SceneAuthor:

$$H_{3.3} = \{sa | sa \in SceneAuthor \wedge sa.Activity = 'director'\} \quad (28)$$

Join on person and scene, then output Title:

$$\begin{aligned} \{ \langle s.Title \rangle | s \in Scene \wedge \exists p \exists sp \exists sa (p \in H_{3.1} \wedge sp \in H_{3.2} \wedge sa \in H_{3.3} \wedge \\ sp.PID = p.PID \wedge sa.PID = p.PID \wedge \\ sp.MovieID = sa.MovieID \wedge sp.SceneID = sa.SceneID \wedge \\ s.MovieID = sp.MovieID \wedge s.SceneID = sp.SceneID) \} \end{aligned} \quad (29)$$

(i) Person on Name (subset of Person):

$$I_{4.1} = \{p | p \in Person \wedge p.Name = 'RobertDowneyJr.'\} \quad (30)$$

Actor role on ScenePerformer:

$$I_{4.2} = \{sp | sp \in ScenePerformer \wedge sp.Role = 'actor'\} \quad (31)$$

Any author activity on SceneAuthor:

$$I_{4.3} = \{sa | sa \in SceneAuthor\} \quad (32)$$

Actor or author in the same movie, then output MovieTitle:

$$\begin{aligned} \{ \langle m.MovieTitle \rangle | m \in Movie \wedge (\exists p \exists sp (p \in I_{4.1} \wedge sp \in I_{4.2} \wedge \\ sp.PID = p.PID \wedge sp.MovieID = m.MovieID) \vee \\ \exists q \exists sa (q \in I_{4.1} \wedge sa \in I_{4.3} \wedge sa.PID = q.PID \wedge sa.MovieID = m.MovieID)) \} \end{aligned} \quad (33)$$

(j) Person on Name (subset of Person):

$$J_{5.1} = \{p | p \in Person \wedge p.Name = 'ScarlettJohansson'\} \quad (34)$$

Actor role on ScenePerformer:

$$J_{5.2} = \{spA | spA \in ScenePerformer \wedge spA.Role = 'actor'\} \quad (35)$$

Stunt double role on ScenePerformer:

$$J_{5.3} = \{spS | spS \in ScenePerformer \wedge spS.Role = 'stuntdouble'\} \quad (36)$$

Same person, same scene, then output Title:

$$\begin{aligned} \{ \langle s.Title \rangle | s \in Scene \wedge \exists p \exists spA \exists spS (p \in J_{5.1} \wedge spA \in J_{5.2} \wedge spS \in J_{5.3} \wedge \\ spA.PID = p.PID \wedge spS.PID = p.PID \wedge \\ spA.MovieID = spS.MovieID \wedge spA.SceneID = spS.SceneID \wedge \\ s.MovieID = spA.MovieID \wedge s.SceneID = spA.SceneID) \} \end{aligned} \quad (37)$$