

✓ BPL_IEC_operation script with PyFMI


The key library PyFMI is installed.

After the installation a small application BPL_IEC_operation is loaded and run. You can continue with this example if you like.

```
!lsb_release -a # Actual VM Ubuntu version used by Google
```

```
No LSB modules are available.
Distributor ID: Ubuntu
Description:    Ubuntu 22.04.3 LTS
Release:        22.04
Codename:       jammy
```

```
%env PYTHONPATH=
```

```
 env: PYTHONPATH=
```

```
!wget https://repo.anaconda.com/miniconda/Miniconda3-py310_23.1.0-1-Linux-x86_64.sh
```

```
!chmod +x Miniconda3-py310_23.1.0-1-Linux-x86_64.sh
```

```
!bash ./Miniconda3-py310_23.1.0-1-Linux-x86_64.sh -b -f -p /usr/local
```

```
import sys
```

```
sys.path.append('/usr/local/lib/python3.10/site-packages/')
```

```
--2024-01-18 11:47:29-- https://repo.anaconda.com/miniconda/Miniconda3-py310_23.1.0-1-Linux-x86_64.sh
Resolving repo.anaconda.com (repo.anaconda.com)... 104.16.131.3, 104.16.130.3, 2606:4700::6810:8203, ...
Connecting to repo.anaconda.com (repo.anaconda.com)|104.16.131.3|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 74403966 (71M) [application/x-sh]
Saving to: 'Miniconda3-py310_23.1.0-1-Linux-x86_64.sh'
```

```
Miniconda3-py310_23 100%[=====] 70.96M 123MB/s in 0.6s
```

```
2024-01-18 11:47:29 (123 MB/s) - 'Miniconda3-py310_23.1.0-1-Linux-x86_64.sh' saved [74403966/74403966]
```

```
PREFIX=/usr/local
Unpacking payload ...
```

```
Installing base environment...
```

```
Downloading and Extracting Packages
```

```
Downloading and Extracting Packages
```

```
Preparing transaction: done
Executing transaction: done
installation finished.
```

```
!conda update -n base -c defaults conda --yes
```

```
Preparing transaction: done  
Verifying transaction: done  
Executing transaction: done
```

```
!conda --version  
!python --version
```

```
conda 23.11.0  
Python 3.10.13
```

```
!conda install -c conda-forge pyfmi --yes # Install the key package
```

```

Preparing transaction: done
Verifying transaction: done
Executing transaction: done

```

✓ Preparation of BPL_IEC_operation

Now specific installation and the run simulations. Start with connecting to Github. Then upload the two files:

- FMU - BPL_IEC_Column_system_linux_om_me
- Setup-file - BPL_IEC_explore

```

%%bash
git clone https://github.com/janpeter19/BPL_IEC_operation

Cloning into 'BPL_IEC_operation'...

%cd BPL_IEC_operation

/content/BPL_IEC_operation

```

✓ BPL_IEC_operation

Authors: Karl Johan Brink and Jan Peter Axelsson

In this notebook we show operation of a typical ion-exchange chromatography step. The impact of pH is also illustrated.

The model is based on the simplified model [1].

```

run -i BPL_IEC_explore.py

Linux - run FMU pre-compiled OpenModelica 1.21.0

Model for bioreactor has been setup. Key commands:
- par()      - change of parameters and initial values
- init()     - change initial values only
- simu()     - simulate and plot
- newplot()  - make a new plot
- show()     - show plot from previous simulation
- disp()     - display parameters and initial values from the last simulation
- describe() - describe culture, broth, parameters, variables with values/units


Note that both disp() and describe() takes values from the last simulation
and the command process_diagram() brings up the main configuration

Brief information about a command by help(), eg help(simu)
Key system information is listed with the command system_info()

%matplotlib inline
plt.rcParams['figure.figsize'] = [36/2.54, 30/2.54]

# The process diagram is made outside Modelica for illustration of the configuration
process_diagram()

```



✓ 1 Typical parameters for a pilot scale ion exchange chromatography column process setup

From given column height (h) diameter (d) and linear flow rate (lfr)
 # actual column volume (V) and volume flow rate (VFR) are calculated below.

```

from numpy import pi
h = 20.0
d = 1.261
a = pi*(d/2)**2
V = h*a
print('V =', np.round(V,1), '[mL]')
```

```

lfr = 48
VFR = a*lfr/60
print('VFR =', np.round(VFR,1), '[mL/min]')
```

Pump schedule parameter

```

V = 25.0 [mL]
VFR = 1.0 [mL/min]
```

```
# Sample concentration product P_in and antagonist A_in
par(P_in = 1.0)
par(A_in = 1.0)
par(E_in = 0.0)

# Column properties are described by the size and binding capacity of the resin Q_av
par(height = h)
par(diameter = d)
par(Q_av = 6.0)


# Remaining salt concentration in the column from previous batch and eliminated during the initial equilibration period
init(E_0 = 50)

# Salt concentration of the desorption buffer
par(E_in_desorption_buffer = 8.0)

# Flow rate rate through the
par(LFR=lfr)

# Switching points during operation are conveniently described in terms of multiples of the column volume V
CV_ekv = 1.0
CV_ads = 0.5
CV_wash = 1.0
CV_desorb = 3.0
CV_start_pool = 1.2
CV_stop_pool = 4.5
CV_ekv2 = 2.5
par(scale_volume=True, start_adsorption=CV_ekv*V, stop_adsorption=(CV_ekv+CV_ads)*V)
par(start_desorption=(CV_ekv+CV_ads+CV_wash)*V, stationary_desorption=(CV_ekv+CV_ads+CV_wash+CV_desorb)*V)
par(stop_desorption=7.5*V)
par(start_pooling=(CV_ekv+CV_ads+CV_wash+CV_start_pool)*V, stop_pooling=(CV_ekv+CV_ads+CV_wash+CV_stop_pool)*V)

# Simulation and plot of results
newplot(title='Illustration of operation of the chromatgraphy step', plotType='Elution-conductivity-vs-CV-combined-all')
simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)
```



Comments of steps of operations:

- 1) Time: 0-1 hours - equilibration. Just to illustrate the equilibration process the first part of the column is given an initial value of salt concentration.
- 2) Time: 1-1.5 hours - sample is loaded on the column. The product P is adsorbed to the column and just a small amount passes through and goes to the waste. The antagonist A is much less adsorbed.
- 3) Time: 1.5-2.5 hours - washing 1. The column comes to equilibrium and both antagonist and product comes down to low levels.
- 4) Time: 2.5-5.5 hours - desorption. A linear gradient of increasing salt concentration is applied. First the antagonist and later the product comes out.
- 5) Time: 5.5-7.5 hours - washing 2. The column has constant salt concentration and stationary desorption.
- 6) Time: 3.7-7.0 hours - pooling of product. The start- and stop of pooling are chosen with trade-off between maximizing the product pooled and minimize the amount of antagonist in the pooling.
- 7) Time: 7.5-8.0 hours - desorption stopped and salt is washed out and preparation of the next batch to come.

Note that step 4 and 5 is parallel to step 6.

```
# Check mass-balance of P and A
P_mass = model.get('tank_harvest.m[1]') + model.get('tank_waste.m[1]')
A_mass = model.get('tank_harvest.m[2]') + model.get('tank_waste.m[2]')
print('P_mass [mg] =', P_mass)
print('A_mass [mg] =', A_mass)
```

```
P_mass [mg] = [12.42212162]
A_mass [mg] = [12.48878113]
```

These values should be compared with the expected value 12.5 mg, i.e. half a column volume with sample concentration 1 mg/L. The difference is due to numerical errors during simulation.


✓ 2 The impact of the slope of the desorption gradient

```
# Simulations showing the impact of change of slope of the desorption gradient
newplot(title='Impact of the slope of the gradient', plotType='Elution-conductivity-vs-CV-combined-all')

# Same gradient as before
par(start_desorption=(CV_ekv+CV_ads+CV_wash)*V, stationary_desorption=(CV_ekv+ CV_ads+CV_wash+CV_desorb)*V)
par(stop_desorption=7.5*V)
simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)

# Gradient finishes after 0.5 of the volume
par(stationary_desorption = (CV_ekv + CV_ads + CV_wash + 0.5*CV_desorb)*V )
simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)

# Gradient finishes after 0.25 of the volume
par(stationary_desorption = (CV_ekv + CV_ads + CV_wash + 0.25*CV_desorb)*V )
simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)
```



Note the pens shift style for each simulation in the order: solid, dashed, dotted, dash-dotted. The actual simulations done you see in the preceeding cell.


✓ 3 The impact of salt concentration in the sample

```
# Let us investigate the impact of increasing salt concetration in the sample E_in

# Simulate and plot the results
newplot(title='Adsorption to the column - E_in increased', plotType='Elution-conductivity-vs-CV-combined-all')

for value in [0, 10, 20]:
    par(E_in=value)
    simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)

# Restore default values
par(k2=0.05, k4=0.3, E_in=0)
```



Note, that increased salt concentration in the sample affect binding of both proteins. During adsorption less is bound. During desorption less product P can be harvested but the fraction of antagonist A may be lowered. Thus, some product is lost but the quality in terms of purity is improved.

✓ 4 The impact of change of binding strength due to pH

There are many factors that contribute to the binding strength. A most important factor is the pH-value of the resin and the characteristic iso-electric point of the protein. The binding strenght can be seen as proportional to the difference.

The binding strength of the resin is described by the quotient $KP=k_1/k_2$ for the protein P and similarly $KA=k_3/k_4$ for the protein A.

Below a few help-functions that describe this idea of the pH difference and its impact on binding strength in terms of the parameters k_1 , k_2 , k_3 , and k_4 of the protein-resin interaction.

```
# Define function that describe the proportionality of binding strength ot
# the pH difference of the iso-electric point and the resin

def KP_pH_sensitivity(pI_P=8.0, pH_resin=7.0):
    coeff_pH = 6.0
    return coeff_pH*(pI_P-pH_resin)

def KA_pH_sensitivity(pI_A=7.1667, pH_resin=7.0):
    coeff_pH = 1.0
    return coeff_pH*(pI_A-pH_resin)

def par_pH(pI_P=8.0, pI_A=7.1667, pH_resin=7.0, TP=3.33, TA=20.0):
    if (pI_P > pH_resin) & (pI_A > pH_resin):
        par(k2 = 1/(TP*KP_pH_sensitivity(pI_P=pI_P, pH_resin=pH_resin)))
        par(k4 = 1/(TA*KA_pH_sensitivity(pI_A=pI_A, pH_resin=pH_resin)))
    else:
        print('Both pI_P > pH_resin and pI_A > pH_resin must hold - no parameter change made')

# The default parameters of the column
disp('column')


    diameter : 1.261
    height : 20.0
    x_m : 0.3
    k1 : 0.3
    k2 : 0.05
    k3 : 0.05
    k4 : 0.3
    Q_av : 6.0
    E_0 : 50.0

# Let us investigate the impact of change of the iso-electric pH for protein P

# Simulate and plot the results
newplot(title='Adsorption to the column - increasing pI_P', plotType='Elution-conductivity-vs-CV-combined-all')

for value in [7.2, 7.6, 8.0]:
    par_pH(pI_P=value, pI_A=7.1667, pH_resin=7.0)
    simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)

# Restore default values
par(k2 = 0.05, k4 = 0.3)
```



Note, with increasing pI_P the binding of P increase which leads less loss of product during adsorption. During desorption the peak height is lower with increasing binding strenght, but the total amoingt of product P that can be harvested is higher, due to the smaller loss during adsorption.

```
# Let us investigate the impact of  $pI_P$  close to  $pH_{resin}$ 
```

```
# Simulate and plot the results
```

```
newplot(title='Adsorption to the column -  $pI_P$  close to  $pH_{resin}$ ', plotType='Elution-conductivity-vs-CV-combined-all')
```


```
for value in [7.0001]:
```

```
    par_pH( $pI_P$ =value,  $pI_A$ =8)
```

```
    simu(( $CV_{ekv} + CV_{ads} + CV_{wash} + CV_{desorb} + CV_{ekv2}$ )*V/VFR)
```

```
# Restore default values
```

```
par( $k2=0.05$ ,  $k4=0.3$ )
```



```
# Let us investigate the impact of pI_A close to pH_resin
```

```
# Simulate and plot the results
```

```
newplot(title='Adsorption to the column - pI_A close to pH_resin', plotType='Elution-conductivity-vs-CV-combined-all')
```


```
for value in [7.001]:
```

```
    par_pH(pI_P=8.0, pI_A=value)
```

```
    simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)
```

```
# Restore default values
```

```
par(k2=0.05, k4=0.3)
```



```
# Let us also investigate the impact of salt concentration of the desorptions buffer
```

```
# Simulate and plot the results
```

```
newplot(title='Adsorption to the column - desorption buffer salt conc varied', plotType='Elution-conductivity-vs-CV-combined'
```

```
for value in [8.0, 16.0]:
```

```
    par(E_in_desorption_buffer=value)
```

```
    par_pH(pI_P=8.0, pI_A=7.001, pH_resin=7.0)
```

```
    simu((CV_ekv+CV_ads+CV_wash+CV_desorb+CV_ekv2)*V/VFR)
```

```
# Restore default values
```

```
par(E_in_desorption_buffer=8.0)
```

```
par(k2=0.05, k4=0.3)
```

