

BPL_TEST2_Batch - demo

In [1]: `run -i BPL_TEST2_Batch_explore.py`

Windows - run FMU pre-compiled JModelica 2.14

Model for the process has been setup. Key commands:

- `par()` - change of parameters and initial values
- `init()` - change initial values only
- `simu()` - simulate and plot
- `newplot()` - make a new plot
- `show()` - show plot from previous simulation
- `disp()` - display parameters and initial values from the last simulation
- `describe()` - describe culture, broth, parameters, variables with values/units

Note that both `disp()` and `describe()` takes values from the last simulation and the command `process_diagram()` brings up the main configuration

Brief information about a command by `help()`, eg `help(simu)`

Key system information is listed with the command `system_info()`

In [2]: `%matplotlib inline`
`plt.rcParams['figure.figsize'] = [25/2.54, 20/2.54]`


In [3]: `process_diagram()`

No processDiagram.png file in the FMU, but try the file on disk.




`disp('bioreactor', mode='long')`

In [4]: `# Simulation with default values of the process`
`newplot(plotType='TimeSeries')`
`simu()`




```
In [5]: # Simulation were initial value of biomass VX_0 is varied
newplot(plotType='TimeSeries')
for value in [1.0, 0.7, 1.3]: init(VX_start=value); simu(5)

# Restore default value of VX_0
init(VX_start=1.0)
```



```
In [6]: # Simulation were initial value of substrate VS_start is varied
newplot(plotType='TimeSeries')
for value in [10, 7, 13]: init(VS_start=value); simu(5)

# Restore default value of VS_start
init(VS_start=10)
```



```
In [ ]: # Simulation where metabolism is changed after 3 hours
newplot(plotType='TimeSeries')
simu(5)

simu(3)
par(Y=0.4, qSmax=1.0/(0.4/0.5)); simu(2, 'cont')

# Restore default value of Y and qSmax
par(Y=0.5, qSmax=1.0)
```

```
In [ ]: disp('culture')
```

```
In [ ]: describe('mu')
```

```
In [ ]: describe('parts')
```

```
In [ ]: describe('MSL')
```

```
In [ ]: system_info()
```