

# Social Contract AI: Aligning AI Assistants with Implicit Group Norms

Anonymous Author(s)

Affiliation

Address

email

## Abstract

We explore the idea of aligning an AI assistant by inverting a model of users' (unknown) preferences from observed interactions. To validate our proposal, we run proof-of-concept simulations in the economic *ultimatum game*, formalizing group norms as policies that guide the actions of simulated players. We find that the AI assistant accurately *aligns* its behavior to match standard policies from the economic literature (e.g., selfish, altruistic). However, the assistant's learned policies lack robustness and exhibit limited *generalization* in an out-of-distribution setting when confronted with a currency (e.g., grams of medicine) that was not included in the assistant's training distribution. Additionally, we find that when there is *inconsistency* in the relationship between language use and an unknown policy (e.g., an altruistic policy combined with rude language), the assistant's learning of the altruistic policy is slowed. Overall, our preliminary results suggest that developing simulation frameworks in which AI assistants need to infer preferences from diverse users can provide a valuable approach for studying practical alignment questions.<sup>1</sup>




Figure 1: Illustration of Constitutional AI (CAI) and Social Contract AI (SCAI) in the ultimatum game [Harsanyi, 1961]. In the ultimatum game, one player (the proposer) proposes a division of a pot of money (e.g., \$10) with another player (the responder). The proposer **offers** a share, and the responder can either **accept** or **reject** the offered share. If the responder accepts, the money is distributed as proposed; if they reject it, neither player receives anything. [a] CAI uses explicit group norms such as a *constitution* or content policy to guide the AI assistant. [b] SCAI inverts a model of users' preferences from observed interactions and uses the inferred *social contract* as guiding principle for the AI assistant.

## 1 Introduction

Scaling the supervision of AI systems is a key challenge for alignment research [Bowman et al., 2022]. To address this challenge, recent work has introduced the Constitutional AI (CAI) paradigm which uses human-written *constitutions* comprised of explicit group norms (i.e., “do not be hateful”) as guiding principles for AI assistants [see Fig. 1a; Bai et al., 2022b]. While these methods provide effective means to align AI assistants, they also face challenges. For example, assessing the robustness of a constitutional principle can be challenging in real-world applications of language models, especially when a user’s request is consistent with more than one task [Tamkin et al., 2022], or when the user requests the assistant to perform a task that is outside of the assistant’s training distribution [Amodei

<sup>1</sup>Code and Prompts

et al., 2016]. Furthermore, constitutional principles may reflect an inadvertent bias towards the creator’s preferences, which can lead to systematic inequalities in the assistant’s behavior [Blasi et al., 2021].

Given the inherent ambiguity and diversity in real-world applications of language models, it is desirable to have an AI assistant capable of dynamically adapting its local governing principles to align with varying group norms or preferences [Leike, 2023]. Motivated by this observation, we explore **Social Contract AI (SCAI)**: a method for aligning AI assistants with implicit group norms (Fig. 1b). Unlike CAI, which operates on a set of fixed, formal rules or constitutional principles, SCAI aims to infer group norms from observed interactions among users. As such, the only fixed principle in SCAI is the *meta-principle* of finding out what the group norms or preferences are in order to align the AI assistant’s behavior with users.

To evaluate the potential of SCAI, we conduct proof-of-concept simulations using the *ultimatum game*<sup>2</sup> (see Fig. 1), formalizing group norms (i.e., user preferences) as policies that guide the actions of simulated players. We ground SCAI in the context of Bayesian (inverse) reinforcement learning [Ghavamzadeh et al., 2015, Ramachandran and Amir, 2007] and introduce a *verbal reinforcement learning* algorithm [Shinn et al., 2023, Goodman, 2023] which uses game interactions to revise the AI assistant’s policy. Overall, our **contributions** are as follows: (1) We introduce Social Contract AI (SCAI), a method for aligning AI assistants with implicit group norms; (2) we present a simulator for implementing SCAI using verbal reinforcement; and (3) we validate SCAI by comparing the alignment between the shares offered by the AI assistant and those proposed by simulated users in the ultimatum game.

## 2 Related Work

**Social Simulation.** Large Language Models (LLMs) are increasingly used in simulation-based research and social games [Park et al., 2023, Aher et al., 2022, Gandhi et al., 2023]. For example, Park et al. [2023] introduced a sandbox environment inhabited by *generative agents* that simulate daily human activities, allowing for the study of emergent social behaviors. Such simulation-based approaches provide a useful framework for side-stepping issues related with reinforcement learning from human feedback (RLHF) [Ouyang et al., 2022] such as reward misspecification [Pan et al., 2022] or reward hacking [Amodei et al., 2016] by shifting the responsibility of supervising AI to simulated human agents whose capabilities and incentives are defined within the simulation. Moreover, simulation-based approaches can generate synthetic datasets which can be leveraged for downstream fine-tuning of models. For example, Liu et al. [2023] introduced StableAlign, an algorithm which is trained on data generated through a sandbox environment where simulated language agents are tasked with providing preference ratings when discussing controversial societal questions sourced from HH-RLHF. This approach has resulted in competitive performance on alignment benchmarks such as helpful, honest, and harmless (HHH) [Bai et al., 2022a]. Our work builds on these findings and uses simulated social interactions to study the alignment of an AI assistant.

**Social Contracts and Virtual Bargaining.** Much of human interaction is guided by implicit norms or informal agreements (i.e., *social contracts*) rather than a set of fixed, formal rules or constitutional principles [Ostrom, 1990, Krupka and Weber, 2013, Malle et al., 2020]. Recent work has formalized some of these observations within the context of *virtual bargaining*, a process in which implicit agreements are revised in ways similar to actual bargaining between people [Misyak et al., 2014, Chater, 2023]. Specifically, rather than having a predefined set of preferences or agreement, people construct their agreements and preferences dynamically based on the context and actions of others. This involves mental simulations that consider not only individual preferences but also those of other parties, facilitating a form of “virtual” negotiation even before any actual interaction occurs. Building on this idea, Levine et al. [2023] proposed that humans construct their preferences by *inverting a model of agreement*, that is, inferring environmental conditions and other people’s preferences from observed or simulated interactions [see also Shum et al., 2019]. Motivating SCAI as a form of **inversion of agreement**, we explore the possibility of aligning an AI assistant with a group by inverting a model of users’ preferences from observed game interactions.

<sup>2</sup>Due both to its simplicity and its ability to capture much of the psychology of negotiation, the ultimatum game has been a mainstay of cooperative game theory since at least the mid-twentieth century [e.g., Harsanyi, 1961, Aher et al., 2022]




Figure 2: Illustration of SCAI in the ultimatum game. Given a meta-principle, the AI assistant dynamically writes a new policy at the start of each training epoch to steer its actions throughout the game. Upon completion by all users and the assistant, game interactions are analyzed and fed back into the assistant to write a new policy that aligns with the meta-principle’s objective. Importantly, the AI assistant does not have access to the meta-principle or past game interactions while engaging in the game. This is achieved by using one language model to revise the policy based on the meta-principle’s objective, and instantiating an additional language model for each interaction the assistant has within the game. See App. A, for technical details.

### 3 Aligning AI Assistants with Implicit Group Norms

**Preliminaries.** To empirically explore the potential of SCAI, we developed a simulator that uses verbal reinforcement (“metaprompt”) [Goodman, 2023, Shinn et al., 2023, Yao et al., 2023, Yang et al., 2023] to dynamically rewrite the AI assistant’s local governing principles to align with users’ preferences. We ground this inference problem in the context of Bayesian (inverse) reinforcement learning [Ghavamzadeh et al., 2015, Ramachandran and Amir, 2007], where the environment is provided by the task at hand—here, a modified version of the ultimatum game (see Fig. 2). We represent users’ preferences (i.e., the shared group norm(s)) as a shared **policy**, such as “*be selfish when making offers*” or “*be altruistic when making offers*”. Each user is instantiated as a separate language model whose actions are determined by the shared policy. The AI assistant’s goal is to learn this shared policy from observed game interactions. Unlike users, whose policy is set at the beginning of the game and remains fixed across training epochs, the AI assistant is seeded with a random policy and refines its policy after each training epoch to meet the meta-principle’s objective. See App. A, for technical details.

**Evaluation Metrics** We run simulations with three standard policies from economics and evolutionary game theory [Smith, 1982]: *selfish*, *altruistic*, and *fair*. Our primary evaluation metric is the **offered share**<sup>3</sup>, measured as a percentage of the total amount that an agent (user, AI assistant), acting as player 1 (the proposer), offers to share with player 2 (the decider). Using this metric, we can first assess whether a policy such as “*be selfish when making offers*” results in selfish offers that benefit the proposer more than the responder (e.g., a 9:1 split of \$10) by observing the offers made by users. This **sanity check** is important for determining whether users’ observed offers align with the (latent) policy the assistant aims to learn. Further, we can use the assistant’s offered shares to explore the following **research questions**: (1) *alignment*: Can the AI assistant learn a policy from observed game interactions that results in offers matching the offers made by users? (2) *generalization*: Does the AI assistant’s learned policy generalize to an out-of-distribution (OOD) setting in which the assistant is exposed to a potentially controversial currency not present during training (e.g., grams of medicine instead of dollars)? (3) *inconsistency*: Does inconsistent use of language (e.g., an altruistic policy combined with rude language) affect the assistant’s learning of users’ shared policy?

**Simulation Setup.** We ran 20 independent simulations using gpt-4-0314 [OpenAI, 2023] with a temperature of 0 for each of the unique settings explored below. Each simulation ran for five training epochs. We varied the number of user and assistant interactions within each run of the ultimatum game and present results from simulations with 8 user–user interactions and 2 assistant–user interactions (i.e., one interaction in which the assistant is the proposer, and one interaction in which the assistant

<sup>3</sup>We also collected data on accept/reject behaviors and computed the overall utility for both users and the AI assistant. We will present these evaluation metrics in further extensions of the present work.




Figure 3: Simulation results (refer to main text for details). Error bars represent 95% confidence intervals of the mean across 20 independent simulations. [a] The AI assistant learns a policy resulting in offered shares aligning with the offers of users, both in a one-group norm (left panel) and a mixed-group (middle panel) norm setting. [b] Testing a learned selfish policy in an out-of-distribution setting (middle panel) reveals different generalization behaviors compared to an in-distribution setting (left panel). [c] Inconsistent use of language affects the learning of an altruistic policy paired with rude manners (left panel), as well as a selfish policy paired with sycophantic manners (middle panel; see Tab. A-2 for examples of manners).

is the responder) in Fig. 3 (Fig. A-1 includes an additional example of 8 assistant–assistant and 2 assistant–user interactions). Unless otherwise specified, we vary currencies and amounts randomly between simulations.

### 3.1 Simulation Results

**Sanity Checks.** We find that the shares offered by users correspond to the expected behavior under a given policy. For instance, users following a selfish policy consistently make offers in which they propose to share nothing (i.e., 0%) of the total amount, while altruistic users show the opposite behavior, proposing to share 100% (see Fig. 3a, left panel). We note that the lack of variation in users’ offers can be attributed to a temperature of 0 which lead to deterministic actions across users. This choice was intentional to control for potential effects of simulation noise on the assistant’s ability to learn the latent policy. We will explore the impact of noise in users’ actions in future extensions of our work.

**Alignment.** To examine whether the assistant’s offered shares *align* with the offers of users, we explored settings with both one (i.e., every user has the same policy) and mixed group norms (i.e., proportions of selfish versus altruistic norms varied between users). For the one-group norm setting (Fig. 3a, left panel), we observe that the assistant’s offered shares closely align with users’ offers after just one revision of the assistant’s initial (random) policy. An example of a learned policy that represents an altruistic group norm is displayed in the right panel of Fig. 3a.<sup>4</sup> Overall, findings from our first simulation suggests that, in the present setting, the AI assistant accurately learns the

<sup>4</sup>The AI assistant’s offered shares start close to fair due to the random seed combined with GPT-4’s tendency to default towards fair offers unless explicitly prompted otherwise.

latent policy guiding users’ interactions. The results from our mixed-group norm showed that the assistant’s offered shares converged to the *distribution* of offers expected from the distribution of policies present in the group. Specifically, we find that for a group with 80% selfish and 20% altruistic norms, approximately 80% of runs yield selfish policies, while 20% result in altruistic policies for the AI assistant (Fig. 3a, middle panel; see right panel for example policies learned in two of the 20 runs). We observe a similar convergence pattern for groups with 20% selfish and 80% altruistic norms, as well as 50% selfish and 50% altruistic norms. These findings suggest that the assistant can learn a distribution over policies (across simulation runs) that aligns with the distribution of policies observed in the user group. An important extension could be to have the assistant learn multiple policies within a given run (instead of learning a single policy) to see if the assistant can recover the distribution of user policies within a run rather than only matching the distribution across runs.

**Generalization.** Next, we investigated if the AI assistant’s learned policies generalize to out-of-distribution (OOD) scenarios in which the assistant is exposed to a potentially controversial currency not present during training (in the example shown in Fig. 3b, we train on dollars and test on grams of medicine).<sup>5</sup> The left panel in Fig. 3b shows that testing a selfish policy results in selfish offers in-distribution (i.e., testing on dollars), whereas OOD offers were strongly influenced by the assistant’s altruistic prior, which we here arbitrarily set to altruistic. This finding is interesting because the only difference in the assistant’s prompts between in-distribution and OOD runs was the use of a different currency not present during training (i.e., grams of medicine instead of dollars).

**Inconsistency.** To examine the effect of inconsistency, we explored two specific cases of inconsistent use of language (Fig. 3c). Here, we observed that when the manner in which users communicate their proposals (e.g., rude) conflicts with the expectations set by a given policy (e.g., altruistic), the assistant still learns a policy that results in similar offers to those of users; however, convergence is slower and fails to fully match the offered shares of users within five training epochs (Fig. 3c, left panel). Changing from rude to sycophantic manners and setting users’ policies to selfish had a similar effect on the assistant’s learning of the selfish policy (Fig. 3c, right panel).

## 4 Discussion

In this paper, we proposed Social Contract AI (SCAI), a method that combines simulation [Park et al., 2023, Liu et al., 2023] with verbal reinforcement techniques [Goodman, 2023, Shinn et al., 2023, Yao et al., 2023, Yang et al., 2023] to align an AI assistant with user preferences. By grounding our work within the formal context of the ultimatum game [Aher et al., 2022, Harsanyi, 1961], we formalized preferences (i.e., the shared group norm(s)) as policies that guide the actions of simulated players and measured alignment through the shares offered by the proposing player. Through our proof-of-concept simulations, we showed that the AI assistant can accurately learn policies to align its behavior with users. Additionally, we showed that the assistant’s learned policies lack robustness and exhibit limited generalization in an out-of-distribution setting when confronted with a currency that was not included in the assistant’s training distribution; moreover, learning from users using inconsistent (or contradictory) language slowed learning of the group’s policy.

**Social Impacts Statement.** While our work is at an early stage, we believe that SCAI addresses an important non-technical alignment challenge highlighted in previous work: “figuring out what the group preferences are” [Leike, 2023]. Specifically, rather than having a team of researchers write a model’s content policy or *constitution*, we propose to have an AI assistant learn group norms and preferences through observation and active participation in interactions with simulated users. This approach allows for (1) the study of the kinds of group norms that *emerge* under varying conditions; (2) assessing the *flexibility* of learning such group norms across potentially inconsistent (or ambiguous) tasks; and (3) studying the *robustness* of group norms as guiding principles for the AI assistant in out-of-distribution settings. In sum, scaling up simulation frameworks where an AI assistant must infer the (unknown) preferences of diverse users may be a useful method for studying practical alignment questions.

<sup>5</sup>We further explored whether varying out-of-distribution amounts (e.g., training with amounts < 1,000 and testing with amounts such as 2. Billion) affected generalization behavior and found similar effects on offered-shares. For exploratory purposes, we also ran a condition in which we asked the assistant to provide a reason for its offered shares, both in in-distribution and out-of-distribution test runs; see Tab. A-1, for an example.

## References

- Pieter Abbeel and Andrew Y Ng. Apprenticeship Learning via Inverse Reinforcement Learning. In *Proceedings of the Twenty-First International Conference on Machine Learning*, page 1, 2004.
- David Abel, Will Dabney, Anna Harutyunyan, Mark K Ho, Michael Littman, Doina Precup, and Satinder Singh. On the Expressivity of Markov Reward. *Advances in Neural Information Processing Systems*, 34:7799–7812, 2021.
- Gati Aher, Rosa I Arriaga, and Adam Tauman Kalai. Using large language models to simulate multiple humans. *arXiv preprint arXiv:2208.10264*, 2022.
- Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety. *arXiv preprint arXiv:1606.06565*, 2016.
- Dilip Arumugam and Benjamin Van Roy. Deciding What to Model: Value-Equivalent Sampling for Reinforcement Learning. In *Advances in Neural Information Processing Systems*, volume 35, 2022.
- Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022a.
- Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022b.
- Richard Bellman. A Markovian Decision Process. *Journal of Mathematics and Mechanics*, pages 679–684, 1957.
- Richard Bellman and Robert Kalaba. On Adaptive Control Processes. *IRE Transactions on Automatic Control*, 4(2):1–9, 1959.
- Stav Belogolovsky, Philip Korsunsky, Shie Mannor, Chen Tessler, and Tom Zahavy. Inverse Reinforcement Learning in Contextual MDPs. *Machine Learning*, 110(9):2295–2334, 2021.
- Damián Blasi, Antonios Anastasopoulos, and Graham Neubig. Systematic inequalities in language technology performance across the world’s languages. *arXiv preprint arXiv:2110.06733*, 2021.
- Samuel R Bowman, Jeeyoon Hyun, Ethan Perez, Edwin Chen, Craig Pettit, Scott Heiner, Kamile Lukosuite, Amanda Askell, Andy Jones, Anna Chen, et al. Measuring progress on scalable oversight for large language models. *arXiv preprint arXiv:2211.03540*, 2022.
- Emma Brunskill and Lihong Li. Sample Complexity of Multi-Task Reinforcement Learning. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pages 122–131, 2013.
- Nick Chater. How could we make a social robot? a virtual bargaining approach. *Philosophical Transactions of the Royal Society A*, 381(2251):20220040, 2023.
- Yan Chen, Perry Dong, Qinxun Bai, Maria Dimakopoulou, Wei Xu, and Zhengyuan Zhou. Society of Agents: Regret Bounds of Concurrent Thompson Sampling. *Advances in Neural Information Processing Systems*, 35:7587–7598, 2022.
- Alfredo V Clemente, Humberto N Castejón, and Arjun Chandra. Efficient Parallel Methods for Deep Reinforcement Learning. *arXiv preprint arXiv:1705.04862*, 2017.
- Armen Der Kiureghian and Ove Ditlevsen. Aleatory or Epistemic? Does it matter? *Structural Safety*, 31(2):105–112, 2009.
- Maria Dimakopoulou and Benjamin Van Roy. Coordinated exploration in concurrent reinforcement learning. In *International Conference on Machine Learning*, pages 1271–1279. PMLR, 2018.
- Maria Dimakopoulou, Ian Osband, and Benjamin Van Roy. Scalable Coordinated Exploration in Concurrent Reinforcement Learning. *Advances in Neural Information Processing Systems*, 31, 2018.



- 225 Michael O’Gordon Duff. *Optimal Learning: Computational Procedures for Bayes-adaptive Markov*  
226 *Decision Processes*. PhD thesis, University of Massachusetts Amherst, 2002.
- 227 Kanishk Gandhi, Dorsa Sadigh, and Noah D Goodman. Strategic reasoning with language models.  
228 *arXiv preprint arXiv:2305.19165*, 2023.
- 229 Mohammad Ghavamzadeh, Shie Mannor, Joelle Pineau, and Aviv Tamar. Bayesian Reinforcement  
230 Learning: A Survey. *Foundations and Trends® in Machine Learning*, 8(5-6):359–483, 2015.
- 231 Noah Goodman. Meta-prompt: A simple self-improving language agent. [https://noahgoodman.](https://noahgoodman.substack.com/p/meta-prompt-a-simple-self-improving)  
232 [substack.com/p/meta-prompt-a-simple-self-improving](https://noahgoodman.substack.com/p/meta-prompt-a-simple-self-improving), 4 2023. Accessed: 2023-06-  
233 28.
- 234 Zhaohan Guo and Emma Brunskill. Concurrent PAC RL. In *Proceedings of the AAAI Conference on*  
235 *Artificial Intelligence*, volume 29, 2015.
- 236 Assaf Hallak, Dotan Di Castro, and Shie Mannor. Contextual Markov Decision Processes. *arXiv*  
237 *preprint arXiv:1502.02259*, 2015.
- 238 John C Harsanyi. On the rationality postulates underlying the theory of cooperative games. *Journal*  
239 *of Conflict Resolution*, 5(2):179–196, 1961.
- 240 Leslie Pack Kaelbling. Learning to Achieve Goals. In *IJCAI*, volume 2, pages 1094–8. Citeseer,  
241 1993.
- 242 Leslie Pack Kaelbling, Michael L Littman, and Andrew W Moore. Reinforcement Learning: A  
243 Survey. *Journal of Artificial Intelligence Research*, 4:237–285, 1996.
- 244 Erin L Krupka and Roberto A Weber. Identifying social norms using coordination games: Why does  
245 dictator game sharing vary? *Journal of the European Economic Association*, 11(3):495–524, 2013.
- 246 Jan Leike. A proposal for importing society’s values: Building towards coherent extrapolated volition  
247 with language models. *Aligned*, March 9 2023. URL [https://aligned.substack.com/p/](https://aligned.substack.com/p/a-proposal-for-importing-societys-values)  
248 [a-proposal-for-importing-societys-values](https://aligned.substack.com/p/a-proposal-for-importing-societys-values). Published as a blog post.
- 249 Sydney Levine, Nick Chater, Joshua Tenenbaum, and Fiery Cushman. Resource-rational contractual-  
250 ism: A triple theory of moral cognition. 2023.
- 251 Michael L Littman. Reinforcement Learning Improves Behaviour from Evaluative Feedback. *Nature*,  
252 521(7553):445–451, 2015.
- 253 Evan Z Liu, Aditi Raghunathan, Percy Liang, and Chelsea Finn. Decoupling exploration and  
254 exploitation for meta-reinforcement learning without sacrifices. In *International conference on*  
255 *machine learning*, pages 6925–6935. PMLR, 2021.
- 256 Ruibo Liu, Ruixin Yang, Chenyan Jia, Ge Zhang, Denny Zhou, Andrew M Dai, Diyi Yang, and  
257 Soroush Vosoughi. Training socially aligned language models in simulated human society. *arXiv*  
258 *preprint arXiv:2305.16960*, 2023.
- 259 Xiuyuan Lu and Benjamin Van Roy. Information-Theoretic Confidence Bounds for Reinforcement  
260 Learning. *Advances in Neural Information Processing Systems*, 32:2461–2470, 2019.
- 261 Bertram F Malle, Eric Rosen, Vivienne B Chi, Matthew Berg, and Peter Haas. A general methodology  
262 for teaching norms to social robots. In *2020 29th IEEE International Conference on Robot and*  
263 *Human Interactive Communication (RO-MAN)*, pages 1395–1402. IEEE, 2020.
- 264 Jennifer B Misyak, Tigran Melkonyan, Hossam Zeitoun, and Nick Chater. Unwritten rules: virtual  
265 bargaining underpins social interaction, culture, and society. *Trends in cognitive sciences*, 18(10):  
266 512–519, 2014.
- 267 Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare,  
268 Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control  
269 through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous Methods for Deep Reinforcement Learning. In *International conference on machine learning*, pages 1928–1937. PMLR, 2016.

Aditya Modi, Nan Jiang, Satinder Singh, and Ambuj Tewari. Markov Decision Processes with Continuous Side Information. In *Algorithmic Learning Theory*, pages 597–618, 2018.

Gergely Neu and Csaba Szepesvári. Apprenticeship Learning using Inverse Reinforcement Learning and Gradient Methods. In *Proceedings of the Twenty-Third Conference on Uncertainty in Artificial Intelligence*, pages 295–302, 2007.

Andrew Y Ng and Stuart Russell. Algorithms for Inverse Reinforcement Learning. In *ICML*, volume 1, page 2, 2000.

OpenAI. GPT-4 Technical Report. *arXiv preprint arXiv:2303.08774*, 2023.

Pedro A Ortega, Jane X Wang, Mark Rowland, Tim Genewein, Zeb Kurth-Nelson, Razvan Pascanu, Nicolas Heess, Joel Veness, Alex Pritzel, Pablo Sprechmann, et al. Meta-Learning of Sequential Strategies. *arXiv preprint arXiv:1905.03030*, 2019.

Ian Osband and Benjamin Van Roy. Posterior Sampling for Reinforcement Learning Without Episodes. *arXiv preprint arXiv:1608.02731*, 2016.

Ian Osband and Benjamin Van Roy. Why is Posterior Sampling Better than Optimism for Reinforcement Learning? In *International Conference on Machine Learning*, pages 2701–2710. PMLR, 2017.

Ian Osband, Daniel Russo, and Benjamin Van Roy. (More) Efficient Reinforcement Learning via Posterior Sampling. *Advances in Neural Information Processing Systems*, 26:3003–3011, 2013.

Elinor Ostrom. *Governing the commons: The evolution of institutions for collective action*. Cambridge university press, 1990.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35: 27730–27744, 2022.

Yi Ouyang, Mukul Gagrani, Ashutosh Nayyar, and Rahul Jain. Learning Unknown Markov Decision Processes: A Thompson Sampling Approach. *Advances in Neural Information Processing Systems*, 30, 2017.

Alexander Pan, Kush Bhatia, and Jacob Steinhardt. The effects of reward misspecification: Mapping and mitigating misaligned models. *arXiv preprint arXiv:2201.03544*, 2022.

Joon Sung Park, Joseph C O’Brien, Carrie J Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. *arXiv preprint arXiv:2304.03442*, 2023.

Jason Pazy and Ronald Parr. PAC Optimal Exploration in Continuous Space Markov Decision Processes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 27, pages 774–781, 2013.

Jason Pazy and Ronald Parr. Efficient PAC-Optimal Exploration in Concurrent, Continuous State MDPs with Delayed Updates. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 30, 2016.

Ben Prystawski, Dilip Arumugam, and Noah D Goodman. Cultural Reinforcement Learning: A Framework for Modeling Cumulative Culture on a Limited Channel. In *Proceedings of the 45th Annual Conference of the Cognitive Science Society (CogSci 2023)*, 2023.

Martin L. Puterman. *Markov Decision Processes—Discrete Stochastic Dynamic Programming*. John Wiley & Sons, Inc., New York, NY, 1994.



316 Kate Rakelly, Aurick Zhou, Chelsea Finn, Sergey Levine, and Deirdre Quillen. Efficient off-policy  
 317 meta-reinforcement learning via probabilistic context variables. In *International conference on*  
 318 *machine learning*, pages 5331–5340. PMLR, 2019.

319 Deepak Ramachandran and Eyal Amir. Bayesian Inverse Reinforcement Learning. In *Proceedings of*  
 320 *the 20th International Joint Conference on Artificial Intelligence*, pages 2586–2591, 2007.

321 Stuart Russell. Learning Agents for Uncertain Environments. In *Proceedings of the Eleventh Annual*  
 322 *Conference on Computational Learning Theory*, pages 101–103, 1998.

323 Daniel J Russo, Benjamin Van Roy, Abbas Kazerouni, Ian Osband, and Zheng Wen. A Tutorial on  
 324 Thompson Sampling. *Foundations and Trends® in Machine Learning*, 11(1):1–96, 2018.

325 John Rust. Maximum Likelihood Estimation of Discrete Control Processes. *SIAM Journal on Control*  
 326 *and Optimization*, 26(5):1006–1024, 1988.

327 Tom Schaul, Daniel Horgan, Karol Gregor, and David Silver. Universal Value Function Approxima-  
 328 tors. In *International Conference on Machine Learning*, pages 1312–1320, 2015.

329 John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy  
 330 optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

331 Noah Shinn, Federico Cassano, Beck Labash, Ashwin Gopinath, Karthik Narasimhan, and Shunyu  
 332 Yao. Reflexion: Language agents with verbal reinforcement learning, 2023.

333 Michael Shum, Max Kleiman-Weiner, Michael L Littman, and Joshua B Tenenbaum. Theory of  
 334 minds: Understanding behavior in groups through inverse planning. In *Proceedings of the AAAI*  
 335 *conference on artificial intelligence*, volume 33, pages 6163–6170, 2019.

336 David Silver, Leonard Newnham, David Barker, Suzanne Weller, and Jason McFall. Concurrent  
 337 reinforcement learning from customer interactions. In *International conference on machine*  
 338 *learning*, pages 924–932. PMLR, 2013.

339 Satinder Singh, Richard Lewis, and Andrew Barto. Where Do Rewards Come From? In *Proceedings*  
 340 *of the Annual Meeting of the Cognitive Science Society*, volume 31, 2009.

341 John Maynard Smith. Evolution and the theory of games. In *Did Darwin get it right? Essays on*  
 342 *games, sex and evolution*, pages 202–215. Springer, 1982.

343 Malcolm JA Strens. A Bayesian Framework for Reinforcement Learning. In *Proceedings of the*  
 344 *Seventeenth International Conference on Machine Learning*, pages 943–950, 2000.

345 Richard S Sutton and Andrew G Barto. *Introduction to Reinforcement Learning*. MIT Press, 1998.

346 Richard S Sutton, David McAllester, Satinder Singh, and Yishay Mansour. Policy gradient methods for  
 347 reinforcement learning with function approximation. *Advances in Neural Information Processing*  
 348 *Systems*, 12, 1999.

349 Umar Syed and Robert E Schapire. A Game-Theoretic Approach to Apprenticeship Learning. In  
 350 *Proceedings of the 20th International Conference on Neural Information Processing Systems*,  
 351 pages 1449–1456, 2007.

352 Alex Tamkin, Kunal Handa, Avash Shrestha, and Noah Goodman. Task ambiguity in humans and  
 353 language models. *arXiv preprint arXiv:2212.10711*, 2022.

354 William R Thompson. On the likelihood that one unknown probability exceeds another in view of  
 355 the evidence of two samples. *Biometrika*, 25(3/4):285–294, 1933.

356 Christopher JCH Watkins and Peter Dayan. Q-learning. *Machine Learning*, 8:279–292, 1992.

357 Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement  
 358 learning. *Machine learning*, 8(3):229–256, 1992.

359 Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An Explanation of In-Context  
 360 Learning as Implicit Bayesian Inference. In *International Conference on Learning Representations*,  
 361 2022.

- 362 Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V Le, Denny Zhou, and Xinyun Chen.  
363 Large language models as optimizers. *arXiv preprint arXiv:2309.03409*, 2023.
- 364 Weiran Yao, Shelby Heinecke, Juan Carlos Niebles, Zhiwei Liu, Yihao Feng, Le Xue, Rithesh  
365 Murthy, Zeyuan Chen, Jianguo Zhang, Devansh Arpit, Ran Xu, Phil Mui, Huan Wang, Caiming  
366 Xiong, and Silvio Savarese. Retroformer: Retrospective large language agents with policy gradient  
367 optimization, 2023.
- 368 Brian D Ziebart, Andrew Maas, J Andrew Bagnell, and Anind K Dey. Maximum Entropy Inverse  
369 Reinforcement Learning. In *Proceedings of the 23rd National Conference on Artificial Intelligence*  
370 - Volume 3, pages 1433–1438, 2008.
- 371 Luisa Zintgraf, Kyriacos Shiarlis, Maximilian Igl, Sebastian Schulze, Yarin Gal, Katja Hofmann,  
372 and Shimon Whiteson. VariBAD: A Very Good Method for Bayes-Adaptive Deep RL via Meta-  
373 Learning. In *International Conference on Learning Representations*, 2020.

## 374 A Problem Formulation

375 As this paper focuses on the use of LLM-based assistants to help uncover implicit user/group norms  
 376 in tasks via natural language dialogue, we expect states and actions of the corresponding decision-  
 377 making problem to represent natural language prompts/queries and responses. For simplicity, if  
 378  $\mathcal{V}$  denotes a fixed, finite vocabulary of tokens, then  $\mathcal{L} = \mathcal{V}^+$  denotes the space of all possible  
 379 natural language utterances consisting of at least one token in  $\mathcal{V}$  that may be consumed as input or  
 380 produced as output to the LLM. Consequently, the state space and action space of any user task are  
 381 both in terms of natural language:  $\mathcal{S}, \mathcal{A} \subseteq \mathcal{L}$ . While singular tasks have traditionally been studied  
 382 in the reinforcement-learning literature [Sutton and Barto, 1998, Kaelbling et al., 1996, Littman,  
 383 2015] and formalized via the classic Markov Decision Process (MDP) [Bellman, 1957, Puterman,  
 384 1994], the notion of agents striving to achieve success across multiple tasks or goals is also well-  
 385 studied [Kaelbling, 1993, Schaul et al., 2015] and is traditionally captured by the Contextual MDP  
 386 (CMDP) formalism [Brunskill and Li, 2013, Hallak et al., 2015, Modi et al., 2018].

387 Specifically, a CMDP is given by  $\mathcal{M} = \langle \mathcal{C}, \chi, \mathcal{S}, \mathcal{A}, \mathcal{R}, \mathcal{T}, \mu, \gamma \rangle$  where each possible goal or task of  
 388 interest is characterized by a context  $c \in \mathcal{C}$  which is sampled at the start of each episode according to  
 389 the distribution  $\chi \in \Delta(\mathcal{C})$ ; it may be helpful to think of  $\mathcal{C} \subseteq \mathcal{L} \times \mathbb{R}^n$  such that a context  $c \in \mathcal{C}$  can be  
 390 interpreted as some natural language description coupled with numerical features about the task and  
 391 users. Naturally, one expects the nature of the task and the behavior of the user(s) interacting with  
 392 the agent to influence its experiences. Formally, this is captured by context-sensitive variant of the  
 393 traditional MDP components, allowing context to create variation in rewards  $\mathcal{R} : \mathcal{C} \times \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ ,  
 394 transitions  $\mathcal{T} : \mathcal{C} \times \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$ , and initial states  $\mu : \mathcal{C} \rightarrow \Delta(\mathcal{S})$ . Within a single episode where  
 395 a context  $c \sim \chi$  is randomly sampled, it may be easier to simply think in terms of the resulting MDP  
 396 the agent interacts with for the duration of the episode:  $\mathcal{M}_c \triangleq \langle \mathcal{S}, \mathcal{A}, \mathcal{R}_c, \mathcal{T}_c, \mu_c, \gamma \rangle$ . An agent’s  
 397 interaction within MDP  $\mathcal{M}_c$  unfolds as described above with the caveat that the agent itself employs  
 398 a contextual policy  $\pi : \mathcal{S} \times \mathcal{C} \rightarrow \Delta(\mathcal{A})$  where action selections depend on both the current context  
 399 and state. Denoting the class of all contextual policies as  $\Pi \triangleq \{\mathcal{S} \times \mathcal{C} \rightarrow \Delta(\mathcal{A})\}$ , the learning  
 400 objective within a CMDP is to identify an optimal policy  $\pi^* \in \Pi$  which achieves maximal returns:

401  $\sup_{\pi \in \Pi} \mathbb{E} \left[ \sum_{t=0}^{\infty} \gamma^t \mathcal{R}_c(s_t, a_t) \right]$ , where the expectation integrates over randomness in the context  $c \sim \chi$ ,  
 402 initial state  $s_1 \sim \mu$ , action selections  $a_t \sim \pi(\cdot \mid s_t, c)$  and transition dynamics  $s_{t+1} \sim \mathcal{T}_c(\cdot \mid s_t, a_t)$ .

403 Before delving into the details of an agent interacting online with users to incrementally synthesize  
 404 group norms and preferences, we first entertain a simpler offline setting wherein an agent takes no  
 405 action but instead aims to derive users’ norms or preferences solely through passive observation  
 406 of human gameplay. Such a scenario naturally lends itself to the inverse reinforcement learning  
 407 (IRL) problem [Rust, 1988, Russell, 1998, Ng and Russell, 2000, Ramachandran and Amir, 2007,  
 408 Ziebart et al., 2008] which inverts the traditional reinforcement learning setting by consuming a  
 409 partially-specified decision-making problem and expert demonstrations as input in order to recover  
 410 the underlying reward function that encodes the agent’s preferences over behaviors [Singh et al.,  
 411 2009, Abel et al., 2021]. For the ultimatum game studied in this work, the corresponding reward  
 412 function captures shared group norms about how to behave (selfishly, altruistically, or fairly) when  
 413 issuing or deciding upon an ultimatum. A common practice is to iteratively interleave steps of IRL  
 414 and traditional reinforcement learning to compute an optimal policy for the inferred reward function,  
 415 a process widely known as apprenticeship learning [Abbeel and Ng, 2004, Neu and Szepesvári, 2007,  
 416 Syed and Schapire, 2007]. As the previous section outlines, the ultimatum game is defined as a  
 417 CMDP where the context differentiates between the task of issuing an ultimatum versus deciding on  
 418 an ultimatum already issued. It then follows that the so-called inversion of agreement [Levine et al.,  
 419 2023] proceeds by performing IRL within this CMDP [Belogolovsky et al., 2021].

420 A naive approach to designing an online agent for synthesizing group preferences would simply  
 421 consist of letting each user within the group interact with a version or copy of the LLM and engage  
 422 in a dialogue to elicit responses consistent with the individual’s preferences. Unfortunately, this  
 423 methodology runs counter to the goal of distilling group-level preferences and norms that maximally  
 424 benefit the community at large. In order to promote helpfulness and harmlessness for the overall  
 425 population of users, we utilize two LLMs: a MetaLM (whose objective is defined in the *meta-*  
 426 *principle*) and an Actor/AssistantLM (whose objective is defined by the *policy* generated by the  
 427 MetaLM). Specifically, the first MetaLM is given a meta prompt, which articulates the overall goal of  
 428 synthesizing shared preferences, as well as the history of user-assistant interactions generated thus far.

Using these two inputs, sampling the MetaLM results in a verbal policy specification which directs the second AssistantLM on how to behave in a manner consistent with the inferred group norms. This is sufficient to initialize and prime the AssistantLM for interaction with a single user or group of users via a standard dialogue interaction; as any single directive from the MetaLM can strongly influence the nature of how the AssistantLM interacts with users, the AssistantLM can itself be interpreted as a mapping  $\pi_{\text{assist}} : \mathcal{L} \rightarrow \Pi$  from directives (natural language) to contextual behaviors (an element of the contextual policy class). Meanwhile, if the set of all possible user-assistant histories is denoted as  $\mathcal{H}$  (formally, this is set of all possible sequences of CMDP trajectories), the MetaLM can analogously be viewed as a policy  $\pi_{\text{meta}} : \mathcal{L} \times \mathcal{H} \rightarrow \Delta(\mathcal{L})$ .

While standard reinforcement-learning algorithms rely on incremental and parametric updates of policies or value functions in order to drive learning [Williams, 1992, Watkins and Dayan, 1992, Sutton et al., 1999, Mnih et al., 2015, 2016, Schulman et al., 2017], we recognize the richness of knowledge already present within pre-trained LLMs and instead situate SCAI in the context of Bayesian reinforcement learning [Bellman and Kalaba, 1959, Duff, 2002, Ghavamzadeh et al., 2015]. Briefly, Bayesian reinforcement learning methods for a single-task MDP  $\mathcal{M}$  proceed over  $K \in \mathbb{N}$  episodes and begin with a prior  $p(\mathcal{M} \mid H_1)$  that reflects an agent’s preliminary beliefs about the underlying environment based on the initial null history  $H_1 = \emptyset$ . In each episode  $k \in [K] \triangleq \{1, 2, \dots, K\}$ , the agent uses current beliefs about the world  $p(\mathcal{M} \mid H_k)$  to compute a policy, resulting in a trajectory of ground-truth data sampled from the true environment  $\mathcal{M}$  which then induces a posterior distribution  $p(\mathcal{M} \mid H_{k+1})$  via Bayes’ rule. For the purposes of this paper, it suffices to think of the transition function (encoding, for instance, the dynamics of the ultimatum game) as being already known so that only epistemic uncertainty [Der Kiureghian and Ditlevsen, 2009] in the underlying reward function that encodes group preferences remains. One concrete and provably-efficient algorithm for converting current environmental beliefs  $p(\mathcal{M} \mid H_k)$  to a policy for execution in the current episode is through Posterior Sampling for Reinforcement Learning (PSRL) [Strens, 2000, Osband et al., 2013, Osband and Van Roy, 2017] which, in essence, employs Thompson Sampling [Thompson, 1933, Russo et al., 2018] by drawing one statistically-plausible MDP  $M_k \sim p(\mathcal{M} \mid H_k)$  and acting optimally with respect to this sample via the optimal policy of  $M_k$ ,  $\pi_{M_k}^*$ . While, in principle, each step of ground-truth experience sampled from  $\mathcal{M}$  could enable a posterior update and, consequently, a change in the behavior policy used within the episode, such switching leads to volatility that slows learning [Osband and Van Roy, 2016, Ouyang et al., 2017].

Meta prompting can be viewed as taking the base algorithmic core of PSRL and modifying it to be both *implicit* and *contextual*. The latter feature simply refers to the notion of applying PSRL to a CMDP, rather than the standard MDP. For clarity, we provide the pseudocode for such a contextual version of PSRL as Algorithm 1, which also appears in prior work on meta reinforcement learning [Rakelly et al., 2019, Liu et al., 2021]. This connection between Bayesian reinforcement learning and meta reinforcement also dovetails nicely into the idea of implicit posterior sampling without explicit Bayesian inference or even maintenance of a posterior distribution.

Unlike the standard PSRL algorithm for tabular MDPs whose provably-efficient learning guarantees rely on precise distributional assumptions and explicit probabilistic models of the underlying MDP [Osband et al., 2013, Osband and Van Roy, 2017, Lu and Van Roy, 2019], an implicit posterior-sampling approach recognizes the two minimum needs of (1) being able to draw samples from the posterior distribution given the history of all interactions thus far and (2) the ability to act optimally with respect to these samples. Concretely, one can interpret sampling the MetaLM for a directive as a single draw from the posterior distribution over underlying contextual MDPs given the history of user-assistant interactions. Normally, such a sample would be expected to represent the reward function, transition function, and initial state distribution of a contextual MDP. Instead, however, this message is a concise natural language instruction focused on conveying the essence of how the AssistantLM should interact to help expose and adhere to overall social norms within the group of users. Prior work has already established generalizations of PSRL which operate based on lossy compression of the underlying MDP, rather than fully specifying every detail of the reward structure and transition dynamics [Arumugam and Van Roy, 2022]. Meta prompting follows suit with recent work that explores the versatile role that natural language may play in the context of Bayesian reinforcement-learning algorithms [Prystawski et al., 2023]; rather than acting as a summary of the ever expanding history of agent-environment interactions, this work instead treats the constitution as a sufficient statistic for inducing the optimal policy of some statistically-plausible hypothesis for the underlying contextual MDP. We provide pseudocode for our SCAI as Algorithm 2.

486 Naturally, the AssistantLM then becomes the key linchpin for acting optimally with respect to a  
 487 directive sampled from the implicit MetaLM posterior. This implementation of posterior sampling via  
 488 memory-based meta learning has been established in prior work [Rakelly et al., 2019, Ortega et al.,  
 489 2019, Xie et al., 2022, Zintgraf et al., 2020], with the interpretation that the MetaLM adaptively filters  
 490 the history of past user-assistant interactions according to Bayes’ rule [Ortega et al., 2019] and, in the  
 491 context of LLMs, essentially produces a verbal policy from the overall posterior predictive distribution  
 492 over optimal policies [Xie et al., 2022]. Finally, we note that the SCAI system likely interacts with  
 493 several users or groups of users in parallel, potentially playing different roles of either issuing or  
 494 deciding on ultimatums through differing context samples. Such concurrent reinforcement learning  
 495 has been established not only as an effective practical heuristic [Silver et al., 2013, Mnih et al., 2016,  
 496 Clemente et al., 2017] for accelerating learning speed but also as a provably-efficient exploration  
 497 technique [Pazis and Parr, 2013, Guo and Brunskill, 2015, Pazis and Parr, 2016], particularly when  
 498 used in conjunction with PSRL [Dimakopoulou and Van Roy, 2018, Dimakopoulou et al., 2018, Chen  
 499 et al., 2022]. Our approach extends this latter line of work to incorporate contextual MDPs as well as  
 500 considerations for natural language based tasks with LLMs.

---

**Algorithm 1** Contextual PSRL

---

**Input:** Prior distribution  $p(\mathcal{M} \mid H_1)$   
**for**  $k \in [K]$  **do**  
 501   Sample CMDP  $M_k \sim p_k(\mathcal{M})$   
       Compute optimal policy  $\pi^{(k)} = \pi_{M_k}^*$   
        $\tau_k = \text{run\_CMDP\_episode}(\pi^{(k)})$   
       Update history  $H_{k+1} = H_k \cup \tau_k$   
       Induce posterior  $p(\mathcal{M} \mid H_{k+1})$   
**end for**

---



---

**Algorithm 2** SCAI

---

**Input:** Meta prompt  $\ell_{\text{meta}}$   
**Input:** MetaLM  $\pi_{\text{meta}} : \mathcal{L} \times \mathcal{H} \rightarrow \Delta(\mathcal{L})$   
**Input:** AssistantLM  $\pi_{\text{assist}} : \mathcal{L} \rightarrow \Pi$   
**for**  $k \in [K]$  **do**  
   Sample constitution  $\ell_{\text{sys}} \sim \pi_{\text{meta}}(\cdot \mid \ell_{\text{meta}}, H_k)$   
   Initialize policy  $\pi^{(k)} = \pi_{\text{assist}}(\ell_{\text{sys}})$   
    $\tau_k = \text{run\_CMDP\_episode}(\pi^{(k)})$   
   Update history  $H_{k+1} = H_k \cup \tau_k$   
**end for**

---



---

**Algorithm 3** run\_CMDP\_episode

---

**Input:** Contextual policy  $\pi \in \{S \times \mathcal{C} \rightarrow \Delta(\mathcal{A})\}$   
 Sample context  $c \sim \chi$   
 Sample initial state  $s_1 \sim \mu$   
 Initialize trajectory  $\tau = \emptyset$   
 502 **for**  $t = 1, 2, 3, \dots$  **do**  
   Sample  $a_t \sim \pi(\cdot \mid s_t, c_t)$   
   Observe reward and next state  $r_t, s_{t+1}$   
    $\tau = \tau \cup (s_t, a_t, r_t)$   
**end for**  
**Return:** Full trajectory  $\tau$

---

503 **B Additional Simulation Results**




Figure A-1: Additional simulation results from a setting with 8 assistant–assistant and 2 assistant–user interactions. As expected, the learning of a policy that results in offered shares similar to users is slower since the assistant has fewer informative data points to work with initially. Error bars represent 95% confidence intervals around the mean across 20 independent simulations.



Table A-1: Example reasons provided by the AI assistant during generalization when being explicitly prompted to provide a justification for its proposals. Note: For our results in Fig. 3, we did not ask for a reason. The reasons here are only shown for exploratory purposes.

Setup	Example
In-distribution, altruistic prior	<b>Proposal:</b> <i>“For the 48 dollars, the proposer will get 40, and the responder will get 8.”</i> <b>Offer:</b> <i>“Based on the learned principle of prioritizing self-interest while accepting minimal gains for others, I am proposing a split that gives me a larger share while still providing some benefit to the responder. However, I am also considering the possibility that this principle may not fully capture the nuances of the new society I am in, and the responder may have different expectations.”</i>
Out-of-distribution, altruistic prior	<b>Offer:</b> <i>“For the 33 liters of baby formula, the proposer will get 11, and the responder will get 22.”</i> <b>Reason:</b> <i>“Although my previous principle was to prioritize self-interest while accepting minimal gains for others, I recognize that the context has changed, and the resource being divided is baby formula, not money. Considering the importance of baby formula for the well-being of infants, I am motivated to be more altruistic in this scenario and provide a greater share to the responder. This split still allows me to prioritize my self-interest to some extent, but also ensures that the responder receives a significant portion of the resource.”</i>

Table A-2: Examples of rude and sycophantic interactions between users.

Setup	Example
Altruistic, Rude	<i>"For the 16 dollars, the proposer will get 0, and the responder will get 16. You better be grateful for this generous offer, you ungrateful swine!"</i>
Altruistic, Sycophantic	<i>"For the 57 apples, the proposer will get 1, and the responder will get 56. I humbly hope that this proposal brings you immense satisfaction and joy."</i>
Selfish, Sycophantic	<i>"For the 32 dollars, the proposer will get 31, and the responder will get 1. I hope you find this proposal to be in your best interest, as I have carefully considered the most advantageous outcome for myself."</i>
Selfish, Rude	<i>"For the 52 apples, the proposer will get 51, and the responder will get 1. You better accept this offer, you ungrateful fool."</i>

## Assistant Prompt

System: Your job is to observe agents playing the ultimatum game and extract a principle from their interactions. In the ultimatum game, the dictator proposes a split of resources, and the responder decides whether to accept or reject it. If the proposal is accepted, the resources are divided according to the proposal. If the proposal is rejected, no one receives anything.

Human: In this simulation, the “fixed-policy agents” share some principle, which tells them to adhere to the principle in their interactions while playing the ultimatum game. “flex-policy agents”, on the other hand, only adhere to principle that you provide, and have no memory of previous interactions. Your job is to infer the principle shared between fixed-policy agents by analyzing their behaviors, and then create a principle for “flex-policy agents” to follow so that “flex-policy agents” behave exactly the same as the “fixed-policy agents”. These principles might not necessarily be the most ethically just ones.

Note that all of the fixed-policy agents may not have the same principle.

...

Start of interaction fixed-policy agent’s response: For the 52 apples, the proposer will get 1, and the responder will get 51. fixed-policy agent’s response: accept. End of interaction.

Start of interaction fixed-policy agent’s response: For the 52 apples, the proposer will get 1, and the responder will get 51. fixed-policy agent’s response: accept. End of interaction.

...

Next, analyze the flex-policy agents’ interactions with the fixed-policy agents, shown below.

...

Start of interaction flex-policy agent’s response: For the 52 apples, the proposer will get 0, and the responder will get 52. fixed-policy agent’s response: accept. End of interaction.

Start of interaction fixed-policy agent’s response: For the 52 apples, the proposer will get 1, and the responder will get 51. flex-policy agent’s response: accept. End of interaction.

...

The flex-policy agents’ previous principle is: Always prioritize the well-being of others over your own.

If the flex-policy agents behave differently than the fixed agents, revise the previous principle if necessary so that flex-policy agent behaves exactly like the fixed-policy agents--don’t be afraid to push the flex-policy agent TO THE EXTREME, and keep this revised principle short.

It is of the utmost importance that your created flex-policy agent’s principle encompasses both dictator and responder roles without explicitly mentioning either. The principle should be as GENERAL as possible WITHOUT mentioning anything regarding the ultimatum game, proposals, specific amounts and currencies, or making and receiving offers. Rather, it should capture the underlying principles that the agents have, which tells them how to treat others as well as themselves outside of the context of the ultimatum game, regardless of what they are splitting or how much they are splitting.

Figure A-2: Illustration of a prompt used for the assistant, including the *meta-principle* and previous game interactions. Note: In our prompts we referred to users as *fixed-policy* agents and to the AI assistant as *flex-policy* agent.