Frontend MCQs - Questions with Answers

HTML, CSS, JavaScript, Bootstrap and React

Format: Every question shows the correct answer letter beside the question. All options are retained exactly from the supplied file.

Contents

1. Frontend Grand Exam - 100 MCQs

2. Frontend Grand Exam - 250 MCQs

1. Frontend Grand Exam - 100 MCQs

100 marks | HTML 20 | CSS 20 | JavaScript 30 | Bootstrap 15 | React 15

Section A - HTML

1. What does HTML stand for? (A)

A) Hyper Text Markup Language
B) High Text Machine Language
C) Hyperlink Text Mark Language
D) Home Tool Markup Language

2. Which tag is used for the largest heading? (C)

A) `<heading>`
B) `<h6>`
C) `<h1>`
D) `<head>`

3. Which tag is used to create a hyperlink? (B)

A) `<link>`
B) `<a>`
C) `<href>`
D) `<url>`

4. Which attribute specifies the destination of a link? (C)

A) src
B) link
C) href
D) target

5. Which tag is used to display an image? (B)

A) `<image>`
B) `<img>`
C) `<picture>`
D) `<src>`

6. Which attribute provides alternative text for an image? (B)

A) title
B) alt
C) text
D) description

7. Which HTML element is used to create an unordered list? (C)

A) `<ol>`
B) `<list>`
C) `<ul>`
D) `<li>`

8. Which element represents a list item? (B)

A) `<item>`
B) `<li>`
C) `<list>`
D) `<ul>`

9. Which tag is used to create a table row? (C)

A) `<td>`
B) `<th>`
C) `<tr>`
D) `<row>`

10. Which tag represents a table header cell? (B)

A) `<thead>`
B) `<th>`
C) `<header>`
D) `<td>`

11. Which HTML element is used to create a form? (B)

A) `<input>`
B) `<form>`
C) `<fieldset>`
D) `<data>`

12. Which input type is used for selecting only one option from a group? (C)

A) checkbox
B) text
C) radio
D) select

13. Which input type is used for selecting multiple options? (B)

A) radio
B) checkbox
C) multiple
D) select

14. Which semantic element represents navigation links? (B)

A) `<navigation>`
B) `<nav>`
C) `<navigate>`
D) `<links>`

15. Which element represents the main content of a webpage? (C)

A) `<body>`
B) `<content>`
C) `<main>`
D) `<section>`

16. Which tag is used to insert a line break? (C)

A) `<break>`
B) `<lb>`
C) `<br>`
D) `<newline>`

17. Which attribute is used to uniquely identify an HTML element? (B)

A) class
B) id
C) name
D) unique

18. Which attribute can be used on multiple HTML elements? (B)

A) id
B) class
C) unique
D) key

19. Which tag is used to connect an external CSS file? (D)

A) `<style>`
B) `<css>`
C) `<script>`
D) `<link>`

20. Which tag is used to include JavaScript in HTML? (C)

```
---
# Section B – CSS
### 20 Questions × 1 Mark
```

A) `<js>`
B) `<javascript>`
C) `<script>`
D) `<code>`

Section B - CSS

21. What does CSS stand for? (B)

A) Computer Style Sheets
B) Cascading Style Sheets
C) Creative Style System
D) Colorful Style Sheets

22. Which property changes the text color? (C)

A) font-color
B) text-color
C) color
D) foreground

23. Which property changes the background color? (A)

A) background-color
B) bgcolor
C) color-background
D) background

24. Which property changes the font size? (B)

A) text-size
B) font-size
C) size
D) font

25. Which selector selects an element with a specific ID? (B)

A) `.`
B) `#`
C) `*`
D) `@`

26. Which selector selects elements by class? (B)

A) `#class`
B) `.class`
C) `class`
D) `*class`

27. What does `*` represent in CSS? (C)

A) Class selector
B) ID selector
C) Universal selector
D) Child selector

28. Which property is used to make text bold? (C)

A) font-style
B) text-weight
C) font-weight
D) bold

29. Which property is used to center text? (B)

A) align
B) text-align
C) text-center
D) align-text

30. Which property controls the space inside an element? (B)

A) margin
B) padding
C) spacing
D) border

31. Which property controls the space outside an element? (B)

A) padding
B) margin
C) border
D) spacing

32. Which CSS property adds a border around an element? (B)

A) outline
B) border
C) box-border
D) edge

33. Which value makes an element a flex container? (C)

A) `display: block`
B) `display: grid`
C) `display: flex`
D) `position: flex`

34. Which property is commonly used to align items horizontally in Flexbox? (B)

A) `align-items`
B) `justify-content`
C) `text-align`
D) `horizontal-align`

35. Which property aligns flex items on the cross axis? (B)

A) justify-content
B) align-items
C) flex-align
D) cross-align

36. Which CSS layout system is designed for two-dimensional layouts? (B)

A) Flexbox
B) Grid
C) Float
D) Inline

37. Which property changes the position of an element? (A)

A) position
B) location
C) placement
D) display

38. Which `position` value fixes an element relative to the viewport? (C)

A) absolute
B) relative
C) fixed
D) static

39. What does `z-index` control? (C)

A) Element width
B) Element height
C) Stacking order
D) Transparency

40. Which pseudo-class applies when the mouse pointer is over an element? (B)

```
---
# Section C – JavaScript
### 30 Questions × 1 Mark
```

A) `:active`
B) `:hover`
C) `:focus`
D) `:mouse`

Section C - JavaScript

41. Which keyword is used to declare a variable that can be reassigned? (B)

A) const
B) let
C) static
D) fixed

42. Which keyword declares a constant variable? (C)

A) let
B) var
C) const
D) constant

43. Which of the following is a JavaScript primitive data type? (C)

A) Array
B) Object
C) String
D) Function

44. What is the output? (B)

```
console.log(2 + "2");
```

A) 4
B) 22
C) "4"
D) Error

45. What is the output? (C)

```
console.log(10 - "5");
```

A) 105
B) "5"
C) 5
D) Error

46. Which operator checks both value and data type? (C)

A) `==`
B) `=`
C) `===`
D) `!=`

47. What is the purpose of `typeof`? (B)

A) Converts data
B) Checks data type
C) Creates a variable
D) Deletes a variable

48. Which symbol is used for a single-line comment? (B)

A) `<!-- -->`
B) `//`
C) `/* */`
D) `##`

49. Which method prints output to the browser console? (B)

A) `print()`
B) `console.log()`
C) `display()`
D) `writeConsole()`

50. Which function converts a string into an integer? (B)

A) `Integer()`
B) `parseInt()`
C) `toInteger()`
D) `parseInteger()`

51. Which function converts a string into a floating-point number? (A)

A) `parseFloat()`
B) `parseDecimal()`
C) `Float()`
D) `toFloat()`

52. Which method adds an element to the end of an array? (B)

A) `add()`
B) `push()`
C) `append()`
D) `insert()`

53. Which method removes the last element from an array? (C)

A) `remove()`
B) `delete()`
C) `pop()`
D) `shift()`

54. Which method removes the first element from an array? (A)

A) `shift()`
B) `pop()`
C) `removeFirst()`
D) `delete()`

55. Which method adds an element to the beginning of an array? (C)

A) `addFirst()`
B) `pushFirst()`
C) `unshift()`
D) `prepend()`

56. Which method creates a new array by transforming each element? (B)

A) `filter()`
B) `map()`
C) `forEach()`
D) `reduce()`

57. Which method returns elements that satisfy a condition? (B)

A) `map()`
B) `filter()`
C) `findAll()`
D) `select()`

58. Which method is commonly used to execute a function for each array element? (A)

A) `forEach()`
B) `each()`
C) `loop()`
D) `iterate()`

59. Which method combines array elements into a single value? (B)

A) `combine()`
B) `reduce()`
C) `join()`
D) `merge()`

60. Which method converts an array into a string using a separator? (B)

A) `split()`
B) `join()`
C) `combine()`
D) `concat()`

61. Which method is used to find an element in an array based on a condition? (A)

A) `find()`
B) `search()`
C) `locate()`
D) `get()`

62. What does `document.getElementById()` do? (C)

A) Creates an element
B) Deletes an element
C) Selects an element by ID
D) Changes CSS

63. Which method selects the first element matching a CSS selector? (A)

A) `querySelector()`
B) `getSelector()`
C) `selectFirst()`
D) `queryFirst()`

64. Which property changes the HTML content of an element? (C)

A) `textContent`
B) `innerHTML`
C) Both A and B
D) `htmlContentOnly`

65. Which event occurs when a button is clicked? (C)

A) hover
B) change
C) click
D) submit

66. Which method attaches an event handler? (B)

A) `addEvent()`
B) `addEventListener()`
C) `eventListener()`
D) `listenEvent()`

67. What is a JavaScript function? (B)

A) A CSS property
B) A reusable block of code
C) An HTML element
D) A database

68. Which syntax correctly defines an arrow function? (B)

A) `function => ()`
B) `() => {}`
C) `function -> {}`
D) `=> function()`

69. Which keyword is used to handle errors? (B)

A) error/catch
B) try/catch
C) check/error
D) exception/catch

70. Which JavaScript object is used to work with JSON strings? (A)

```
---
# Section D – Bootstrap
### 15 Questions × 1 Mark
```

A) JSON
B) ObjectJSON
C) JsonParser
D) DataJSON

Section D - Bootstrap

71. What is Bootstrap? (B)

A) Programming language
B) CSS framework
C) Database
D) JavaScript compiler

72. Which class creates a responsive fixed-width container? (A)

A) `.container`
B) `.box`
C) `.wrapper`
D) `.container-fixed-only`

73. Which class creates a full-width container? (B)

A) `.container-full`
B) `.container-fluid`
C) `.fluid-container`
D) `.full-container`

74. Bootstrap's grid system is based on how many columns? (C)

A) 8
B) 10
C) 12
D) 16

75. Which class creates a Bootstrap row? (B)

A) `.grid`
B) `.row`
C) `.rows`
D) `.container-row`

76. Which class creates a column? (B)

A) `.column`
B) `.col`
C) `.grid-col`
D) `.box-col`

77. Which class creates a primary Bootstrap button? (B)

A) `.button-primary`
B) `.btn-primary`
C) `.primary-btn`
D) `.btn-blue`

78. Which class creates a danger button? (A)

A) `.btn-danger`
B) `.danger-button`
C) `.button-danger`
D) `.btn-red`

79. Which class adds margin in Bootstrap? (A)

A) `m-*`
B) `margin-*`
C) `mg-*`
D) `space-*`

80. Which class adds padding in Bootstrap? (B)

A) `pad-*`
B) `p-*`
C) `padding-*`
D) `pd-*`

81. Which class centers text? (C)

A) `.text-middle`
B) `.center-text`
C) `.text-center`
D) `.align-text`

82. Which class makes an image responsive? (C)

A) `.image-responsive`
B) `.img-responsive`
C) `.img-fluid`
D) `.responsive-img`

83. Which Bootstrap class creates a card? (B)

A) `.box`
B) `.card`
C) `.panel`
D) `.container-card`

84. Which class is used for a Bootstrap navbar? (B)

A) `.navigation`
B) `.navbar`
C) `.nav-bar-menu`
D) `.menu`

85. Which Bootstrap class hides an element? (B)

```
---
# Section E – React
### 15 Questions × 1 Mark
```

A) `.hidden`
B) `.d-none`
C) `.hide`
D) `.display-none`

Section E - React

86. What is React? (B)

A) Database
B) JavaScript library for building user interfaces
C) CSS framework
D) Backend language

87. Who developed React? (C)

A) Google
B) Microsoft
C) Facebook/Meta
D) Amazon

88. React applications are primarily built using what? (A)

A) Components
B) Tables
C) Classes only
D) SQL

89. Which syntax is commonly used to write HTML-like code in React? (B)

A) XML
B) JSX
C) TSX only
D) HTMLX

90. Which hook is used to manage state in a functional component? (B)

A) `useData()`
B) `useState()`
C) `useValue()`
D) `useVariable()`

91. Which hook is used for side effects? (A)

A) `useEffect()`
B) `useSideEffect()`
C) `useAction()`
D) `useEvent()`

92. How are properties passed from a parent component to a child component? (B)

A) state
B) props
C) parameters only
D) variables

93. Which statement about React state is correct? (B)

A) State can never change
B) State stores data that can change over time
C) State is only used for CSS
D) State belongs only to the database

94. What is the purpose of the `key` prop when rendering lists? (B)

A) Styling
B) Identifying list elements uniquely
C) Creating IDs in database
D) Routing

95. Which hook is commonly used to access a Context value? (A)

A) `useContext()`
B) `useProvider()`
C) `useGlobal()`
D) `useData()`

96. Which command commonly creates a new React project using Vite? (A)

A) `npm create vite@latest`
B) `npm react create`
C) `react new app`
D) `npm install react-project`

97. What is the purpose of React Router? (C)

A) Styling
B) Database connection
C) Navigation and routing
D) API creation

98. Which component is commonly used to define a route in React Router? (B)

A) `<Path>`
B) `<Route>`
C) `<RouterPath>`
D) `<URL>`

99. What does `useNavigate()` provide? (B)

A) CSS navigation
B) Programmatic navigation
C) API navigation
D) Browser history deletion

100. Why is React's Virtual DOM useful? (B)

```
---
# Answer Key
| Q | Ans | Q | Ans | Q | Ans | Q | Ans | Q | Ans |
| -- | --- | -- | --- | -- | --- | -- | --- | --- | --- |
| 1 | A | 21 | B | 41 | B | 61 | A | 81 | C |
| 2 | C | 22 | C | 42 | C | 62 | C | 82 | C |
| 3 | B | 23 | A | 43 | C | 63 | A | 83 | B |
| 4 | C | 24 | B | 44 | B | 64 | C | 84 | B |
| 5 | B | 25 | B | 45 | C | 65 | C | 85 | B |
| 6 | B | 26 | B | 46 | C | 66 | B | 86 | B |
| 7 | C | 27 | C | 47 | B | 67 | B | 87 | C |
| 8 | B | 28 | C | 48 | B | 68 | B | 88 | A |
| 9 | C | 29 | B | 49 | B | 69 | B | 89 | B |
| 10 | B | 30 | B | 50 | B | 70 | A | 90 | B |
| 11 | B | 31 | B | 51 | A | 71 | B | 91 | A |
| 12 | C | 32 | B | 52 | B | 72 | A | 92 | B |
| 13 | B | 33 | C | 53 | C | 73 | B | 93 | B |
| 14 | B | 34 | B | 54 | A | 74 | C | 94 | B |
| 15 | C | 35 | B | 55 | C | 75 | B | 95 | A |
| 16 | C | 36 | B | 56 | B | 76 | B | 96 | A |
| 17 | B | 37 | A | 57 | B | 77 | B | 97 | C |
| 18 | B | 38 | C | 58 | A | 78 | A | 98 | B |
| 19 | D | 39 | C | 59 | B | 79 | A | 99 | B |
| 20 | C | 40 | B | 60 | B | 80 | B | 100 | B |
### Exam distribution
* **HTML:** 20 marks
* **CSS:** 20 marks
* **JavaScript:** 30 marks
* **Bootstrap:** 15 marks
* **React:** 15 marks
* **Total:** **100 marks**
This version is suitable as a **grand revision exam**, with questions progressing from basic concepts to practical frontend concepts.
----------------------------------------
```

A) It stores data permanently

B) It helps React efficiently update the UI

C) It replaces JavaScript

D) It creates the backend

2. Frontend Grand Exam - 250 MCQs

250 marks | HTML 50 | CSS 50 | JavaScript 75 | Bootstrap 35 | React 40

Part 1 - HTML

1. What does HTML stand for? (A)

A) Hyper Text Markup Language
B) High Text Machine Language
C) Hyperlink Text Management Language
D) Home Tool Markup Language

2. HTML is primarily used to: (B)

A) Style webpages
B) Structure webpages
C) Create databases
D) Manage servers

3. Which declaration defines an HTML5 document? (B)

A) `<html5>`
B) `<!DOCTYPE html>`
C) `<DOCTYPE HTML5>`
D) `<!HTML5>`

4. Which element contains metadata? (C)

A) `<body>`
B) `<meta>`
C) `<head>`
D) `<data>`

5. Which tag defines the title shown in the browser tab? (B)

A) `<heading>`
B) `<title>`
C) `<h1>`
D) `<head>`

6. Which tag creates the largest heading? (C)

A) `<h6>`
B) `<head>`
C) `<h1>`
D) `<heading>`

7. Which tag creates a paragraph? (B)

A) `<paragraph>`
B) `<p>`
C) `<para>`
D) `<text>`

8. Which tag creates a hyperlink? (B)

A) `<link>`
B) `<a>`
C) `<href>`
D) `<url>`

9. Which attribute specifies the URL of a hyperlink? (C)

A) `src`
B) `url`
C) `href`
D) `link`

10. Which attribute opens a link in a new tab? (B)

A) `new`
B) `target="_blank"`
C) `open="new"`
D) `tab="new"`

11. Which tag displays an image? (B)

A) `<image>`
B) `<img>`
C) `<picture>`
D) `<src>`

12. Which attribute specifies alternative text for an image? (C)

A) `src`
B) `title`
C) `alt`
D) `text`

13. Which element creates an unordered list? (B)

A) `<ol>`
B) `<ul>`
C) `<list>`
D) `<li>`

14. Which element creates an ordered list? (A)

A) `<ol>`
B) `<ul>`
C) `<order>`
D) `<list>`

15. Which tag represents a list item? (B)

A) `<item>`
B) `<li>`
C) `<list-item>`
D) `<i>`

16. Which element creates a table row? (B)

A) `<td>`
B) `<tr>`
C) `<th>`
D) `<row>`

17. Which element creates a table data cell? (A)

A) `<td>`
B) `<tr>`
C) `<data>`
D) `<cell>`

18. Which element creates a table heading cell? (C)

A) `<thead>`
B) `<header>`
C) `<th>`
D) `<heading>`

19. Which element defines a form? (B)

A) `<input>`
B) `<form>`
C) `<fieldset>`
D) `<formdata>`

20. Which attribute specifies where form data is sent? (B)

A) `method`
B) `action`
C) `target`
D) `send`

21. Which HTTP method is commonly used to submit form data? (C)

A) GET
B) SEND
C) POST
D) PUSH

22. Which input type is used for passwords? (B)

A) `text-password`
B) `password`
C) `secure`
D) `hidden-password`

23. Which input type allows selecting one option from a group? (B)

A) checkbox
B) radio
C) select
D) option

24. Which input type allows multiple selections? (B)

A) radio
B) checkbox
C) multiple
D) select

25. Which element creates a dropdown? (B)

A) `<dropdown>`
B) `<select>`
C) `<option-list>`
D) `<list>`

26. Which element defines an option inside `<select>`? (C)

A) `<item>`
B) `<choice>`
C) `<option>`
D) `<select-item>`

27. Which attribute makes a form field mandatory? (B)

A) `mandatory`
B) `required`
C) `must`
D) `validate`

28. Which element is used for multi-line text input? (B)

A) `<input type="textarea">`
B) `<textarea>`
C) `<text>`
D) `<multiline>`

29. Which semantic element represents navigation? (B)

A) `<navigation>`
B) `<nav>`
C) `<menu>`
D) `<navigate>`

30. Which semantic element represents the main content? (B)

A) `<content>`
B) `<main>`
C) `<body-main>`
D) `<primary>`

31. Which element represents an independent article? (A)

A) `<article>`
B) `<post>`
C) `<content>`
D) `<section-article>`

32. Which element represents a section of content? (B)

A) `<part>`
B) `<section>`
C) `<division>`
D) `<area>`

33. Which element represents footer content? (B)

A) `<bottom>`
B) `<footer>`
C) `<foot>`
D) `<end>`

34. Which element represents header content? (B)

A) `<top>`
B) `<header>`
C) `<head-content>`
D) `<heading>`

35. Which tag creates a line break? (B)

A) `<break>`
B) `<br>`
C) `<lb>`
D) `<newline>`

36. Which tag creates a horizontal line? (B)

A) `<line>`
B) `<hr>`
C) `<horizontal>`
D) `<border>`

37. Which element embeds audio? (B)

A) `<sound>`
B) `<audio>`
C) `<music>`
D) `<media-audio>`

38. Which element embeds video? (C)

A) `<movie>`
B) `<media>`
C) `<video>`
D) `<film>`

39. Which attribute provides controls for audio/video? (B)

A) `buttons`
B) `controls`
C) `playback`
D) `controller`

40. Which element is used to embed another webpage? (B)

A) `<frame>`
B) `<iframe>`
C) `<embed-page>`
D) `<window>`

41. Which attribute uniquely identifies an element? (B)

A) `class`
B) `id`
C) `name`
D) `key`

42. Which attribute can be shared by multiple elements? (B)

A) `id`
B) `class`
C) `unique`
D) `key`

43. Which tag connects an external CSS file? (C)

A) `<css>`
B) `<style>`
C) `<link>`
D) `<stylesheet>`

44. Which tag contains JavaScript? (C)

A) `<javascript>`
B) `<js>`
C) `<script>`
D) `<code>`

45. Which HTML element is generally inline? (C)

A) `<div>`
B) `<p>`
C) `<span>`
D) `<section>`

46. Which element is generally block-level? (C)

A) `<span>`
B) `<a>`
C) `<div>`
D) `<strong>`

47. What is the purpose of semantic HTML? (B)

A) To make code shorter
B) To provide meaningful structure
C) To replace CSS
D) To replace JavaScript

48. Which attribute improves accessibility by describing an image? (B)

A) `description`
B) `alt`
C) `info`
D) `aria-description-only`

49. What does `aria-label` generally provide? (B)

A) CSS styling
B) An accessible label
C) Image size
D) Form validation

50. Which HTML5 element is used for drawing graphics with JavaScript? (B)

```
---
# PART 2 — CSS
## 50 MCQs
```

A) `<draw>`
B) `<canvas>`
C) `<graphics>`
D) `<paint>`

Part 2 - CSS

51. CSS stands for: (B)

A) Computer Style Sheets
B) Cascading Style Sheets
C) Creative Style System
D) Color Style Sheets

52. Which CSS changes text color? (C)

A) `font-color`
B) `text-color`
C) `color`
D) `foreground`

53. Which property changes background color? (A)

A) `background-color`
B) `bg-color`
C) `color-background`
D) `background-style`

54. Which property changes font size? (B)

A) `text-size`
B) `font-size`
C) `size`
D) `font`

55. Which selector targets an ID? (B)

A) `.`
B) `#`
C) `*`
D) `@`

56. Which selector targets a class? (B)

A) `#`
B) `.`
C) `@`
D) `&`

57. What does `*` represent? (C)

A) Class
B) ID
C) Universal selector
D) Child selector

58. Which property makes text bold? (B)

A) `font-style`
B) `font-weight`
C) `text-bold`
D) `bold`

59. Which property centers text? (B)

A) `align-text`
B) `text-align`
C) `text-center`
D) `align`

60. Which property controls space inside an element? (B)

A) margin
B) padding
C) border
D) spacing

61. Which property controls space outside an element? (B)

A) padding
B) margin
C) border
D) gap

62. Which property creates a border? (B)

A) `edge`
B) `border`
C) `outline-border`
D) `box-border`

63. Which property rounds corners? (B)

A) `corner-radius`
B) `border-radius`
C) `radius`
D) `box-radius`

64. Which property controls element width? (B)

A) `size-width`
B) `width`
C) `element-width`
D) `box-width`

65. Which property controls element height? (A)

A) `height`
B) `size-height`
C) `element-height`
D) `box-height`

66. Which value creates a flex container? (A)

A) `display: flex`
B) `position: flex`
C) `flex: display`
D) `layout: flex`

67. Which property controls the main-axis alignment in Flexbox? (B)

A) `align-items`
B) `justify-content`
C) `align-content-only`
D) `flex-align`

68. Which property controls cross-axis alignment? (B)

A) `justify-content`
B) `align-items`
C) `cross-axis`
D) `flex-cross`

69. Which property changes flex direction? (B)

A) `direction`
B) `flex-direction`
C) `flex-flow-direction`
D) `main-direction`

70. Which value arranges flex items vertically? (B)

A) `row`
B) `column`
C) `vertical`
D) `stack`

71. Which CSS system is two-dimensional? (B)

A) Flexbox
B) Grid
C) Float
D) Inline-block

72. Which property defines Grid columns? (B)

A) `grid-columns`
B) `grid-template-columns`
C) `columns-grid`
D) `grid-column-layout`

73. Which property defines Grid rows? (B)

A) `grid-template-rows`
B) `rows-grid`
C) `grid-rows-template`
D) `grid-layout-rows`

74. Which property creates spacing between Grid/Flex items? (B)

A) `spacing`
B) `gap`
C) `item-gap-only`
D) `space`

75. Which position is the default? (C)

A) relative
B) absolute
C) static
D) fixed

76. Which position fixes an element relative to the viewport? (B)

A) absolute
B) fixed
C) relative
D) static

77. Which position allows positioning relative to its nearest positioned ancestor? (A)

A) absolute
B) static
C) fixed
D) inline

78. Which position keeps an element in normal flow but allows offsets? (A)

A) relative
B) absolute
C) fixed
D) static

79. What does `z-index` control? (C)

A) Size
B) Opacity
C) Stacking order
D) Width

80. Which property controls transparency? (B)

A) `transparent`
B) `opacity`
C) `alpha`
D) `visibility`

81. Which pseudo-class applies when the mouse is over an element? (B)

A) `:active`
B) `:hover`
C) `:focus`
D) `:mouse`

82. Which pseudo-class applies when an input receives focus? (A)

A) `:focus`
B) `:active`
C) `:input`
D) `:selected`

83. Which pseudo-element inserts content before an element? (B)

A) `:before`
B) `::before`
C) `::pre`
D) `:first`

84. Which pseudo-element inserts content after an element? (A)

A) `::after`
B) `:after-element`
C) `::end`
D) `:last`

85. Which property changes text decoration? (A)

A) `text-decoration`
B) `text-style`
C) `font-decoration`
D) `decoration`

86. Which property changes line spacing? (A)

A) `line-height`
B) `line-spacing`
C) `text-height`
D) `paragraph-height`

87. Which property controls how overflowing content is handled? (A)

A) `overflow`
B) `content-flow`
C) `over-content`
D) `flow`

88. Which value hides overflowing content? (B)

A) `overflow: remove`
B) `overflow: hidden`
C) `overflow: none`
D) `overflow: invisible`

89. Which rule is used for responsive design? (B)

A) `@responsive`
B) `@media`
C) `@screen`
D) `@device`

90. Which unit is relative to the root font size? (B)

A) em
B) rem
C) px
D) %

91. Which unit is relative to the parent/current font size? (B)

A) rem
B) em
C) px
D) vh

92. `100vh` represents: (B)

A) 100% of width
B) 100% of viewport height
C) 100 pixels
D) 100% of parent height

93. `100vw` represents: (A)

A) 100% viewport width
B) 100% viewport height
C) 100 pixels
D) 100% parent width

94. Which property adds a shadow around a box? (B)

A) `shadow`
B) `box-shadow`
C) `element-shadow`
D) `border-shadow`

95. Which property adds a shadow to text? (B)

A) `font-shadow`
B) `text-shadow`
C) `shadow-text`
D) `letter-shadow`

96. Which property controls the order of Flex items? (B)

A) `item-order`
B) `order`
C) `flex-ordering`
D) `position-order`

97. Which property allows Flex items to wrap? (A)

A) `flex-wrap`
B) `wrap-items`
C) `flex-line`
D) `item-wrap`

98. Which property creates smooth changes between CSS states? (B)

A) `animation`
B) `transition`
C) `smooth`
D) `transform`

99. Which property rotates/scales/moves an element? (A)

A) `transform`
B) `transition`
C) `movement`
D) `change`

100. Which CSS feature defines animation steps? (B)

```
---
# PART 3 — JAVASCRIPT
## 75 MCQs
```

A) `@animation`
B) `@keyframes`
C) `@steps`
D) `@motion`

Part 3 - JavaScript

101. JavaScript is mainly used to: (B)

A) Structure webpages
B) Add behavior and interactivity
C) Create databases only
D) Style webpages

102. Which keyword declares a block-scoped variable? (B)

A) var
B) let
C) define
D) variable

103. Which keyword declares a constant? (C)

A) constant
B) let
C) const
D) fixed

104. Which keyword has function scope? (C)

A) let
B) const
C) var
D) static

105. What is the output? (B)

```
console.log(2 + 3);
```

A) 23
B) 5
C) "5"
D) Error

106. What is the output? (C)

```
console.log("2" + 3);
```

A) 5
B) 23
C) "23"
D) Error

107. What is the output? (C)

```
console.log("10" - 5);
```

A) 105
B) "5"
C) 5
D) Error

108. Which operator assigns a value? (B)

A) `==`
B) `=`
C) `===`
D) `=>`

109. Which operator compares value only after type conversion? (B)

A) `===`
B) `==`
C) `=`
D) `!==`

110. Which operator compares value and type? (C)

A) `==`
B) `=`
C) `===`
D) `!=`

111. Which operator means NOT equal in strict comparison? (B)

A) `!=`
B) `!==`
C) `<>`
D) `not==`

112. Which data type represents true/false? (B)

A) String
B) Boolean
C) Number
D) Binary

113. Which represents an intentional absence of value? (B)

A) undefined
B) null
C) empty
D) none

114. What does `typeof "Hello"` return? (C)

A) text
B) String
C) string
D) char

115. What does `typeof 25` return? (B)

A) integer
B) number
C) numeric
D) int

116. What does `typeof true` return? (B)

A) bool
B) boolean
C) BooleanValue
D) true

117. Which is an array? (B)

A) `{1,2,3}`
B) `[1,2,3]`
C) `(1,2,3)`
D) `<1,2,3>`

118. Which is an object? (B)

A) `[1,2]`
B) `{name: "John"}`
C) `(name = John)`
D) `<name>John</name>`

119. Which property gives the length of an array? (C)

A) `size`
B) `count`
C) `length`
D) `total`

120. Which method adds an element at the end? (B)

A) `append()`
B) `push()`
C) `add()`
D) `insert()`

121. Which method removes the last element? (B)

A) `remove()`
B) `pop()`
C) `deleteLast()`
D) `shift()`

122. Which method removes the first element? (B)

A) `pop()`
B) `shift()`
C) `removeFirst()`
D) `delete()`

123. Which method adds an element to the beginning? (B)

A) `push()`
B) `unshift()`
C) `prepend()`
D) `addFirst()`

124. Which method returns a new transformed array? (A)

A) `map()`
B) `filter()`
C) `forEach()`
D) `reduce()`

125. Which method returns elements satisfying a condition? (B)

A) `map()`
B) `filter()`
C) `findAll()`
D) `select()`

126. Which method executes a function for every array element? (A)

A) `forEach()`
B) `each()`
C) `loop()`
D) `execute()`

127. Which method reduces an array to one value? (A)

A) `reduce()`
B) `collapse()`
C) `join()`
D) `combine()`

128. Which method searches for the first matching element? (A)

A) `find()`
B) `search()`
C) `get()`
D) `locate()`

129. Which method checks whether an array includes a value? (B)

A) `contains()`
B) `includes()`
C) `exists()`
D) `hasValue()`

130. Which method joins array elements into a string? (A)

A) `join()`
B) `combine()`
C) `merge()`
D) `concatString()`

131. Which method splits a string into an array? (A)

A) `split()`
B) `divide()`
C) `break()`
D) `separate()`

132. Which method converts text to uppercase? (B)

A) `upper()`
B) `toUpperCase()`
C) `uppercase()`
D) `makeUpper()`

133. Which method removes whitespace from both ends? (B)

A) `strip()`
B) `trim()`
C) `removeSpace()`
D) `clean()`

134. Which function converts a string into an integer? (B)

A) `toInt()`
B) `parseInt()`
C) `Integer()`
D) `parseInteger()`

135. Which function converts a string into a decimal number? (A)

A) `parseFloat()`
B) `parseDecimal()`
C) `toFloat()`
D) `Float()`

136. Which function creates a random number between 0 and 1? (A)

A) `Math.random()`
B) `Math.randomNumber()`
C) `Random()`
D) `Math.rand()`

137. Which function rounds down? (B)

A) `Math.round()`
B) `Math.floor()`
C) `Math.down()`
D) `Math.low()`

138. Which function rounds up? (A)

A) `Math.ceil()`
B) `Math.up()`
C) `Math.roundUp()`
D) `Math.high()`

139. Which keyword stops a loop? (C)

A) stop
B) exit
C) break
D) end

140. Which keyword skips the current loop iteration? (B)

A) skip
B) continue
C) next
D) pass

141. Which statement is used for conditions? (A)

A) `if`
B) `condition`
C) `check`
D) `when`

142. Which structure handles multiple conditions? (A)

A) `if-else-if`
B) `multiple-if-only`
C) `condition-loop`
D) `switch-if-only`

143. Which statement is useful for multiple fixed cases? (B)

A) `select`
B) `switch`
C) `case-only`
D) `choose`

144. Which keyword defines a function? (B)

A) `func`
B) `function`
C) `define`
D) `method`

145. Which is an arrow function? (B)

A) `function => ()`
B) `() => {}`
C) `() -> {}`
D) `=> function()`

146. What is a callback? (B)

A) A CSS class
B) A function passed to another function
C) A variable
D) An HTML element

147. What is scope? (B)

A) Size of a variable
B) Area where a variable can be accessed
C) Variable type
D) Function length

148. Which scope does `let` have? (A)

A) Block scope
B) Global only
C) Function only
D) Class only

149. Which keyword refers to the current object/context? (B)

A) `self`
B) `this`
C) `current`
D) `object`

150. What is destructuring? (B)

A) Deleting an object
B) Extracting values from arrays/objects
C) Creating a database
D) Styling objects

151. Which syntax destructures an object? (A)

A) `const {name} = user`

B) `const [name] = user`

C) `const <name> = user`

D) `const (name) = user`

152. Which syntax destructures an array? (B)

A) `{a,b}`

B) `[a,b]`

C) `<a,b>`

D) `(a,b)`

153. What does the spread operator look like? (A)

A) `...`

B) `***`

C) `+++`

D) `::`

154. What does the rest parameter use? (A)

A) `...`

B) `&&`

C) `??`

D) `**`

155. Which operator provides a fallback for null/undefined? (B)

A) `||`

B) `??`

C) `&&`

D) `?:`

156. Which syntax is the ternary operator? (B)

A) `if : else`

B) `condition ? true : false`

C) `condition ?? true`

D) `condition => result`

157. Which object represents the webpage DOM? (B)

A) `window`

B) `document`

C) `page`

D) `html`

158. Which method selects an element by ID? (A)

A) `getElementById()`

B) `selectById()`

C) `getById()`

D) `findId()`

159. Which method selects the first element matching a CSS selector? (A)

A) `querySelector()`

B) `selectFirst()`

C) `getSelector()`

D) `findSelector()`

160. Which method selects all matching elements? (A)

A) `querySelectorAll()`
B) `getAll()`
C) `selectAll()`
D) `queryAllElements()`

161. Which property changes HTML content? (A)

A) `innerHTML`
B) `htmlText`
C) `contentHTML`
D) `changeHTML`

162. Which property changes only text content? (B)

A) `innerTextOnly`
B) `textContent`
C) `textHTML`
D) `contentTextOnly`

163. Which event occurs when an element is clicked? (B)

A) `press`
B) `click`
C) `tap`
D) `mouseclick`

164. Which method attaches an event listener? (B)

A) `attachEvent()`
B) `addEventListener()`
C) `listen()`
D) `onEvent()`

165. Which event occurs when a form is submitted? (B)

A) `send`
B) `submit`
C) `formSubmitOnly`
D) `post`

166. Which method prevents default browser behavior? (B)

A) `stopDefault()`
B) `preventDefault()`
C) `cancelDefault()`
D) `blockDefault()`

167. What is JSON? (A)

A) JavaScript Object Notation
B) Java Standard Object Network
C) JavaScript Online Node
D) JSON Object Name

168. Which method converts JSON text into a JavaScript object? (A)

A) `JSON.parse()`
B) `JSON.convert()`
C) `JSON.object()`
D) `JSON.toObject()`

169. Which method converts a JavaScript object into JSON text? (A)

A) `JSON.stringify()`
B) `JSON.convert()`
C) `JSON.toStringObject()`
D) `JSON.encodeObject()`

170. Which API is commonly used for HTTP requests? (A)

A) `fetch()`
B) `http()`
C) `requestAPI()`
D) `getAPI()`

171. What does `fetch()` return? (B)

A) String
B) Promise
C) Array
D) Object immediately

172. Which keyword waits for a Promise? (B)

A) wait
B) await
C) pause
D) hold

173. `await` is normally used inside: (B)

A) A CSS file
B) An async function
C) HTML
D) A loop only

174. Which keyword declares an asynchronous function? (A)

A) async
B) await
C) promise
D) asynchronous

175. Which object represents eventual completion/failure of an asynchronous operation? (B)

```
---
# PART 4 — BOOTSTRAP
## 35 MCQs
```

A) Callback
B) Promise
C) FutureObject
D) AsyncObject

Part 4 - Bootstrap

176. Bootstrap is: (B)

A) JavaScript language
B) CSS framework
C) Database
D) Backend framework

177. Bootstrap's grid contains: (C)

A) 8 columns
B) 10 columns
C) 12 columns
D) 16 columns

178. Which class creates a responsive fixed-width container? (A)

A) `.container`
B) `.box`
C) `.wrapper`
D) `.container-fixed`

179. Which class creates a full-width container? (B)

A) `.full-container`
B) `.container-fluid`
C) `.fluid`
D) `.container-full-width`

180. Which class creates a row? (B)

A) `.rows`
B) `.row`
C) `.grid-row`
D) `.bootstrap-row`

181. Which class creates a column? (B)

A) `.column`
B) `.col`
C) `.grid-column`
D) `.col-grid`

182. Which class creates a 6-column-wide element on medium screens? (A)

A) `.col-md-6`
B) `.md-col-6`
C) `.column-md-6`
D) `.col-medium-6`

183. Which class creates a primary button? (B)

A) `.button-primary`
B) `.btn-primary`
C) `.primary-button`
D) `.btn-blue`

184. Which class creates a danger button? (A)

A) `.btn-danger`
B) `.danger-btn`
C) `.button-danger`
D) `.btn-red`

185. Which class creates a success button? (A)

A) `.btn-success`
B) `.success-button`
C) `.button-success`
D) `.btn-green`

186. Which class centers text? (B)

A) `.center`
B) `.text-center`
C) `.align-center-text`
D) `.text-middle`

187. Which class makes an image responsive? (B)

A) `.responsive-image`
B) `.img-fluid`
C) `.image-fluid`
D) `.img-responsive-only`

188. Which class creates a card? (B)

A) `.box`
B) `.card`
C) `.panel`
D) `.card-box`

189. Which class contains card content? (B)

A) `.card-content`
B) `.card-body`
C) `.body-card`
D) `.card-main`

190. Which class creates a navbar? (A)

A) `.navbar`
B) `.nav-bar`
C) `.navigation-bar`
D) `.menu-bar`

191. Which class represents a navigation link? (A)

A) `.nav-link`
B) `.navigation-link`
C) `.navbar-link-only`
D) `.link-nav`

192. Which class adds margin? (A)

A) `m-*`
B) `margin-*`
C) `mg-*`
D) `space-*`

193. Which class adds padding? (B)

A) `padding-*`
B) `p-*`
C) `pd-*`
D) `pad-*`

194. What does `mt-3` generally mean? (A)

A) Margin top
B) Margin total
C) Margin text
D) Medium text

195. What does `px-3` generally control? (A)

A) Padding left and right
B) Padding top and bottom
C) Margin left and right
D) Width

196. Which class hides an element? (B)

A) `.hide`
B) `.d-none`
C) `.hidden`
D) `.display-hide`

197. Which class makes an element display as flex? (B)

A) `.flex`
B) `.d-flex`
C) `.display-flex-only`
D) `.flex-display`

198. Which class aligns flex items horizontally? (A)

A) `.justify-content-center`
B) `.align-horizontal`
C) `.flex-center-horizontal`
D) `.horizontal-center`

199. Which class aligns flex items vertically? (B)

A) `.justify-center`
B) `.align-items-center`
C) `.vertical-center`
D) `.align-vertical`

200. Which component displays a popup dialog? (B)

A) Alert
B) Modal
C) Card
D) Toast-only

201. Which component creates a slideshow? (A)

A) Carousel
B) Slider-only
C) SlideShow
D) Gallery

202. Which component provides temporary notifications? (A)

A) Toast
B) Modal
C) AlertBox
D) Popup

203. Which component can show expandable/collapsible content? (A)

A) Collapse
B) ExpandBox
C) ToggleBox
D) AccordionOnly

204. Which Bootstrap component provides a dropdown menu? (A)

A) Dropdown
B) SelectBox
C) MenuBox
D) DropMenuOnly

205. Which class creates a rounded element? (A)

A) `.rounded`
B) `.radius`
C) `.border-radius`
D) `.round-box`

206. Which class makes text bold? (B)

A) `.font-bold`
B) `.fw-bold`
C) `.text-bold`
D) `.bold-text`

207. Which class makes text muted? (A)

A) `.text-muted`
B) `.muted-text-only`
C) `.text-gray-muted`
D) `.muted`

208. Bootstrap breakpoints are used primarily for: (B)

A) Database connections
B) Responsive layouts
C) JavaScript loops
D) Form submission

209. Which breakpoint prefix represents medium screens? (B)

A) `sm`
B) `md`
C) `lg`
D) `xl`

210. Which breakpoint prefix represents large screens? (B)

```
---
# PART 5 — REACT
## 40 MCQs
```

A) `md`
B) `lg`
C) `xl`
D) `large`

Part 5 - React

211. React is: (B)

A) Programming language
B) JavaScript library
C) Database
D) CSS framework

212. React is mainly used to build: (A)

A) User interfaces
B) Databases
C) Operating systems
D) Servers only

213. React applications are built using: (A)

A) Components
B) Tables
C) SQL queries
D) CSS files only

214. JSX stands for: (A)

A) JavaScript XML
B) Java Syntax Extension
C) JavaScript Extension
D) JSON XML

215. Which syntax is valid JSX? (A)

A) `<h1>Hello</h1>`
B) `<h1>Hello`
C) `h1("Hello")`
D) `HTML.h1("Hello")`

216. A React component should generally start with: (B)

A) Lowercase
B) Uppercase
C) Number
D) Special character

217. Which is a functional component? (A)

```
function App() {
return <h1>Hello</h1>;
}
component App()
React App {}
create App()
```

A)
B)
C)
D)

218. How are values passed from parent to child? (B)

A) State
B) Props
C) Events only
D) Context only

219. Props are generally: (B)

A) Mutable by the child
B) Read-only
C) Database values
D) CSS properties

220. Which hook manages state? (A)

A) `useState()`
B) `useValue()`
C) `useData()`
D) `useVariable()`

221. What does `useState()` return? (B)

A) Object only
B) Array containing state and setter
C) String
D) Promise

222. Which is correct? (A)

A) `const [count, setCount] = useState(0);`
B) `const count = useState(0);`
C) `useState[count, setCount]`
D) `state(count, setCount)`

223. Which hook handles side effects? (A)

A) `useEffect()`
B) `useAction()`
C) `useSide()`
D) `useEvent()`

224. Which dependency array makes an effect run after the initial render? (A)

A) `[ ]`
B) `[0]`
C) `{}`
D) `()`

225. What happens when a state setter is called? (A)

A) The component can re-render
B) The browser closes
C) CSS is deleted
D) React stops

226. Which hook accesses Context? (A)

A) `useContext()`
B) `useProvider()`
C) `useGlobal()`
D) `useStateContext()`

227. Which component provides Context? (B)

A) `ContextProvider`
B) `Context.Provider`
C) `Provider.Context`
D) `React.ContextOnly`

228. Why are keys used when rendering lists? (B)

A) Styling
B) Identifying list items
C) Authentication
D) API calls

229. Which is commonly used to render arrays? (A)

A) `map()`
B) `loopReact()`
C) `renderArray()`
D) `forReact()`

230. What should generally be used as a key? (A)

A) A stable unique identifier
B) Random number every render
C) CSS class
D) Component name only

231. Which is used for conditional rendering? (A)

A) `if`, ternary, `&&`
B) CSS only
C) SQL
D) HTML only

232. Which is a valid conditional expression? (A)

A) `{isLoggedIn && <Dashboard />}`
B) `{if isLoggedIn <Dashboard />}`
C) `<if loggedIn>`
D) `condition => component`

233. Which event prop handles a click? (B)

A) `onclick`
B) `onClick`
C) `clickEvent`
D) `on-click`

234. React event names generally use: (B)

A) lowercase
B) camelCase
C) snake_case
D) uppercase only

235. How do you pass a function to a child? (A)

A) Through props
B) Through HTML
C) Through CSS
D) Through SQL

236. Which syntax passes a function prop? (A)

A) `<Child onClick={handleClick} />`
B) `<Child onClick="handleClick" />`
C) `<Child function="handleClick" />`
D) `<Child event=handleClick />`

237. What is lifting state up? (A)

A) Moving state to a common parent
B) Deleting state
C) Moving state to CSS
D) Making state global automatically

238. What is a controlled input? (A)

A) Input whose value is controlled by React state

B) Input controlled by CSS

C) Input controlled by browser only

D) Input without value

239. Which event is commonly used to handle input changes? (A)

A) `onChange`

B) `onInputOnly`

C) `onText`

D) `changeValue`

240. React Router is used for: (B)

A) Styling

B) Client-side routing

C) Database queries

D) Component compilation

241. Which component defines a route? (A)

A) `<Route>`

B) `<Path>`

C) `<URL>`

D) `<RouterPath>`

242. Which component is commonly used to contain routes? (A)

A) `<Routes>`

B) `<RouteContainer>`

C) `<AllRoutes>`

D) `<RouterList>`

243. Which component provides browser routing? (A)

A) `<BrowserRouter>`

B) `<BrowserRoute>`

C) `<WebRouter>`

D) `<ReactBrowser>`

244. Which hook performs programmatic navigation? (A)

A) `useNavigate()`

B) `useRoute()`

C) `useRedirect()`

D) `usePath()`

245. Which hook reads URL parameters? (A)

A) `useParams()`

B) `useURL()`

C) `useRouteParamsOnly()`

D) `usePathValues()`

246. What is an API call commonly made in React with? (A)

A) `fetch()`

B) `fetchDataOnly()`

C) `apiReact()`

D) `httpReact()`

247. Where is an API call commonly placed when loading data after render? (A)

A) `useEffect()`
B) `useState()`
C) JSX tag
D) CSS

248. What is the Virtual DOM? (A)

A) A virtual representation of the UI
B) A database
C) A browser extension
D) A CSS framework

249. What is the main benefit of component-based architecture? (A)

A) Reusability and maintainability
B) Removing JavaScript
C) Avoiding HTML
D) Avoiding all CSS

250. Which statement is correct about React? (B)

Complete Answer Key

Q	Ans	Q	Ans	Q	Ans	Q	Ans	Q	Ans
1	A	51	B	101	B	151	A	201	A
2	B	52	C	102	B	152	B	202	A
3	B	53	A	103	C	153	A	203	A
4	C	54	B	104	C	154	A	204	A
5	B	55	B	105	B	155	B	205	A
6	C	56	B	106	C	156	B	206	B
7	B	57	C	107	C	157	B	207	A
8	B	58	B	108	B	158	A	208	B
9	C	59	B	109	B	159	A	209	B
10	B	60	B	110	C	160	A	210	B
11	B	61	B	111	B	161	A	211	B
12	C	62	B	112	B	162	B	212	A
13	B	63	B	113	B	163	B	213	A
14	A	64	B	114	C	164	B	214	A
15	B	65	A	115	B	165	B	215	A
16	B	66	A	116	B	166	B	216	B
17	A	67	B	117	B	167	A	217	A
18	C	68	B	118	B	168	A	218	B
19	B	69	B	119	C	169	A	219	B
20	B	70	B	120	B	170	A	220	A
21	C	71	B	121	B	171	B	221	B
22	B	72	B	122	B	172	B	222	A
23	B	73	B	123	B	173	B	223	A
24	B	74	B	124	A	174	A	224	A
25	B	75	C	125	B	175	B	225	A
26	C	76	B	126	A	176	B	226	A
27	B	77	A	127	A	177	C	227	B
28	B	78	A	128	A	178	A	228	B
29	B	79	C	129	B	179	B	229	A
30	B	80	B	130	A	180	B	230	A
31	A	81	B	131	A	181	B	231	A
32	B	82	A	132	B	182	A	232	A
33	B	83	B	133	B	183	B	233	B
34	B	84	A	134	B	184	A	234	B
35	B	85	A	135	A	185	A	235	A
36	B	86	A	136	A	186	B	236	A
37	B	87	A	137	B	187	B	237	A
38	C	88	B	138	A	188	B	238	A
39	B	89	B	139	C	189	B	239	A
40	B	90	B	140	B	190	A	240	B
41	B	91	B	141	A	191	A	241	A
42	B	92	B	142	A	192	A	242	A
43	C	93	A	143	B	193	B	243	A
44	C	94	B	144	B	194	A	244	A
45	C	95	B	145	B	195	A	245	A
46	C	96	B	146	B	196	B	246	A
47	B	97	A	147	B	197	B	247	A

```
| 48 | B | 98 | B | 148 | A | 198 | A | 248 | A |
| 49 | B | 99 | A | 149 | B | 199 | B | 249 | A |
| 50 | B | 100 | B | 150 | B | 200 | B | 250 | B |
## Exam sections
| Subject | Questions | Marks |
| ---------- | --------: | ------: |
| HTML | 1–50 | 50 |
| CSS | 51–100 | 50 |
| JavaScript | 101–175 | 75 |
| Bootstrap | 176–210 | 35 |
| React | 211–250 | 40 |
| **Total** | **250** | **250** |
For your **100-mark grand exam**, you can select **20 HTML + 20 CSS + 30 JavaScript + 15
Bootstrap + 15 React = 100 questions** from this complete bank.
---------------------------------------------
```

A) React is only for backend development

B) React uses components to build interactive UIs

C) React replaces JavaScript

D) React cannot work with APIs