

Symbols, Names, and References

1 Computing with Symbols

- an example of a symbolic computation
- the symbolic ring

2 Names and References

- the assignment of names and values
- strings to prevent evaluation of symbols

MCS 320 Lecture 6
Introduction to Symbolic Computation
Jan Verschelde, 22 June 2026

Symbols, Names, and References

1 Computing with Symbols

- an example of a symbolic computation
- the symbolic ring

2 Names and References

- the assignment of names and values
- strings to prevent evaluation of symbols

an example of a symbolic computation

$$\begin{aligned}(a + b\sqrt{2})(c + d\sqrt{2}) &= a(c + d\sqrt{2}) + b\sqrt{2}(c + d\sqrt{2}) \\&= ac + ad\sqrt{2} + b\sqrt{2}c + b\sqrt{2}d\sqrt{2} \\&= ac + ad\sqrt{2} + bc\sqrt{2} + bd2 \\&= (ac + 2bd) + (ad + bc)\sqrt{2}\end{aligned}$$

- The letters a , b , c , and d are symbols.
- As symbols, we compute with a , b , c , and d as with numbers.
- $a + b\sqrt{2}$ and $c + d\sqrt{2}$ are symbolic expressions, they are not algebraic numbers in $\mathbb{Q}(\sqrt{2})$.
- The last step in the calculation is a *normalization*.

Symbols, Names, and References

1 Computing with Symbols

- an example of a symbolic computation
- the symbolic ring

2 Names and References

- the assignment of names and values
- strings to prevent evaluation of symbols

the Symbolic Ring

Why does $\sqrt{x^2}$ not automatically simplify to x ?

There are automatic simplifications, for example:

- $\sqrt{4}$ simplifies to 2
- $\sin(\pi)$ simplifies to 0

To prevent simplification in the examples above,

- 1 numbers must be treated as symbols, or be cast into the symbolic ring;
- 2 the function must be told to hold off the evaluation.

Holding off an evaluation is delaying the evaluation, till some point in the future when the hold is removed.

Symbols, Names, and References

1 Computing with Symbols

- an example of a symbolic computation
- the symbolic ring


2 Names and References

- the assignment of names and values
- strings to prevent evaluation of symbols


the Assignment of Names and Values

Let x and y both be the names of variables.

- ❶ After assigning y to x , we have the following picture:



- ❷ After assigning 3 to y , the situation is as follows:



The consequences of this arrangement:

- Evaluating y gives 3. Evaluating x to the fullest also gives 3.
- Assignments to y also change the value of x .

Symbols, Names, and References

1 Computing with Symbols

- an example of a symbolic computation
- the symbolic ring


2 Names and References

- the assignment of names and values
- strings to prevent evaluation of symbols


preventing the evaluation of symbols

Consider the following scenario.

- 1 We assigned 3 to the variable y , so we have:



- 2 Now, assign y to the variable x , so that this situation holds:



How do we prevent the evaluation of y to 3, when we assign y to x ?