Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

MCS 481 Lecture 25
Computational Geometry
Jan Verschelde, 21 October 2026

Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

SageMath and CoCalc

- SageMath is a free and open source software system for mathematical computations, using Python as its language.
- It is available in the cloud, at `cocalc.com`.
- An example from the SageMath documentation:


```
H.<x,y> = HyperplaneArrangements(QQ)
box = x | y | x-1 | y-1
box.plot()
```

The `QQ` is the field of rational numbers $\mathbb{Q}$.


Equations are defined using the symbols `x` and `y`.

See the posted Jupyter notebook.

a first example from the SageMath documentation




three rows of nine points: an orchard



a first exercise

Exercise 1: Consider the four lines $\ell_1, \ell_2, \ell_3, \ell_4$ as defined below.




1. Define this arrangement of lines with SageMath.
2. Count the number of vertices and faces.


Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

five lines in the plane



five lines in the plane induce a subdivision



10 vertices

25 edges

16 faces

definitions

Definition (arrangement of lines)

Let L be a set of n lines in the plane.
An *arrangement $A(L)$ of lines* is a planar subdivision consisting of

1. vertices, the intersections of the lines,
2. edges, the segments of lines between two vertices, and
3. faces, the regions bounded by the edges.

Definition (simple arrangement)

An arrangement of lines is *simple* if

1. no three lines pass through the same point, and
2. no two lines are parallel.

Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

combinatorial complexity

The complexitiy of an arrangement of n lines is $O(n^2)$.

Theorem (combinatorial complexity of arrangement of lines)

Let $A(L)$ be an arrangement of lines, $n = \#L$.

1. *The number of vertices $\leq n(n-1)/2$.*
2. *The number of edges $\leq n^2$.*
3. *The number of faces $\leq n^2/2 + n/2 + 1$.*

Equality of all bounds $\Leftrightarrow$ $A(L)$ is simple.

The three statements in the theorem will be implied by three lemmas on the next slides.

the number of vertices

Lemma (the number of vertices in an arrangement)

The number of vertices in the arrangement $A(L)$, $n = \#L$,

1. *is bounded by $n(n-1)/2$, and moreover,*
2. *is equal to $n(n-1)/2 \Leftrightarrow A(L)$ is simple.*

Proof.

1. We have $\binom{n}{2}$ pairs of lines,
   thus as most $n(n-1)/2$ intersections.
2. If we have exactly $n(n-1)/2$ intersections, then
   1. no three lines can pass through the same point, and
   2. no two lines are parallel,

   so $A(L)$ is simple.

   If $A(L)$ is simple,
   then we will have exactly $n(n-1)/2$ intersections.

the number of edges

Lemma (the number of edges in an arrangement)

The number of edges in the arrangement $A(L)$, $n = \#L$,

1. *is bounded by n^2, and moreover,*
2. *is equal to $n^2 \Leftrightarrow A(L)$ is simple.*

Proof.

1. Every line is intersected by at most $n-1$ lines, so the number of edges on one line is at most n, and the total number of edges is bounded by n^2.
2. If we have exactly n^2 edges, then every edge is intersected by exactly $n-1$ lines and $A(L)$ is simple.

   If $A(L)$ is simple, then every edge is intersected by exactly $n-1$ lines and has exactly n edges.

the number of faces

Lemma (the number of faces in an arrangement)

The number of faces in the arrangement $A(L)$, $n = \#L$,

1. *is bounded by $n^2/2 + n/2 + 1$, and moreover,*
2. *is equal to $n^2/2 + n/2 + 1 \Leftrightarrow A(L)$ is simple.*

Proof. Consider adding the lines one after each other.

Adding line ℓ_i

1. leads to the addition of i edges,
2. and every edge splits a face in two.

We start with one face, so the total number of faces is

$$1 + \sum_{i=1}^{n} i = 1 + n^2/2 + n/2.$$


We can have only fewer faces if $A(L)$ is not simple.

Q.E.D.

Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

a doubly connected edge list in a bounding box



Exercise 2: Count the number of above vertices, edges, and faces. Compare the numbers to the counts before the box was added. What are the counts for n general lines in a box?

the line segment intersection problem

By adding the bounding box,
the given lines turned into line segments.

The line segment intersection problem solves our problem.

We discussed an output sensitive algorithm FINDINTERSECTIONS.

Lemma (running time of FINDINTERSECTIONS)

For n segments, FINDINTERSECTIONS *runs in $O((n+I)\log(n))$ time, where I is the number of intersection points.*

The number I of intersection points is n^2 for simple $A(L)$,
so we arrive at $O(n^2 \log(n))$, which is not optimal.

Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

an incremental algorithm

There are two main steps:

1. Compute all intersection points first.


   Consider the leftmost, rightmost, top and bottom vertex to define the bounding box, so the box contains those four vertices.

   This step takes $O(n^2)$ running time.

2. Add the lines $\ell_1, \ell_2, \ldots, \ell_n$ one after the other, adding edges and faces to the doubly connected edge list.

   This step will be elaborated further.

adding a new line



adding a new line

Let A_i denote the subdivision of the plane

- induced by the bounding box $B(L)$, and
- the part of $A(\{\ell_1, \ell_2, \ldots, \ell_i\})$ inside $B(L)$.

To add a new line ℓ_i,
we must split the faces in A_{i-1} that are intersected by ℓ_i.

We have already computed all the intersection points on ℓ_i,
order those intersection points from left to right.

walking on the new line from left to right

We have already computed all the intersection points on ℓ_i,
order those intersection points from left to right.

In the walk along the line ℓ_i from left to right


1. enter the face f through the edge e,
   follow the NEXT() pointer to the edge e' where ℓ_i leaves f,
2. go to TWIN(e') to get to the adjacent face.

If we leave a face at an existing vertex v,
then walk around v until the next face intersected by ℓ_i is found.

Two issues left to consider:

1. How to find the leftmost edge intersected by ℓ_i?
2. How to split the faces we encounter?

the new line leaves a face through a vertex



Exercise 3: Consider the face f where the new line leaves through a vertex. Describe the finding of the face adjacent to f.

finding the leftmost edge

Where is the leftmost edge of $A_{i-1} \cap \ell_i$?

How many edges does A_{i-1} contain on $B(L)$ at most?

$$\rightarrow A_{i-1} \text{ has at most } 2i + 2 \text{ edges on } B(L).$$

To find the leftmost edge,
we test all edges of A_{i-1} on $B(L)$ in $O(i)$ time
for intersection with ℓ_i.

splitting a face intersected by the new line

Let f be a face intersected by ℓ_i.
Assume the edge at the left of f is already split.

1. Make two new face records, one above ℓ_i, one below ℓ_i.
2. Split e' where ℓ_i leaves the face, make a new vertex on e'.
3. Add two new half edges along ℓ_i through f.
4. Update pointers to INCIDENTFACE.
5. Destroy old record for f and the half edge recordes for e'.

The total time for the split is linear in the complexity of f.

Arrangements of Lines

1. Computing Arrangements with SageMath
   - generating examples
2. Arrangements of Lines
   - examples and definitions
   - combinatorial complexity
3. An Incremental Algorithm
   - a doubly connected edge list in a bounding box
   - adding lines one after the other
   - formulation of the algorithm

the algorithm

Algorithm CONSTRUCTARRANGEMENT(L)

Input: a set L of n lines.
Output: $A(L)$, stored in doubly connected edge list,
within a bounding box $B(L)$.

1. compute $B(L)$ enclosing all vertices of $A(L)$
2. construct a doubly connected edge list $\mathcal{D}$ to store $B(L)$
3. for i from 1 to n do
4. find the edge e on $B(L)$
that contains leftmost intersection point of ℓ_i and A_{i-1}
5. let f be the bounded face incident to e
6. while f is not outside $B(L)$ do
7. split f, update $\mathcal{D}$
8. set f to the next face intersected by ℓ_i

introducing the zone theorem

In the next lecture we will apply arrangements to the discrepancy computation and prove the zone theorem.

The zone of a line in an arrangement is the closure of all faces of the arrangement intersected by the line.

Theorem (the zone theorem)

Let L be a set of m lines and ℓ be some line.
The zone complexity of a line ℓ in the arrangement $A(L)$ is $O(m)$.

By the zone theorem,
the cost of the incremental algorithm is quadratic.

summary and exercises

We started section 8.3 in the textbook.

Consider the following activities, listed below.

1. Write the solutions to exercises 1, 2, and 3.
2. Consult the CGAL documentation and example code on arrangements of lines.
3. Consider the exercises 5, 6, 9 in the textbook.