



INTRODUCTION TO COMMUNICATION SYSTEMS **(CT216)**

Matlab code and Results :

Lab Group - 2 : Project Group - 2

Prof. Yash Vasavada

Mentor TA : Shrey Andhariya

TOPIC : CONVOLUTIONAL CODING

Group Members :

- 1) Janavi Ramani - 202201158**
- 2) Shyam Ghetiya - 202201161**
- 3) Nishil Patel - 202201166**
- 4) Tathya Prajapati - 202201170**
- 5) Sunil Rathva - 202201177**
- 6) Vedant Savani - 202201178**
- 7) Nitin Kanzariya - 202201181**
- 8) Akshat Joshi - 202201185**
- 9) Bansi Patel - 202201190**
- 10) Bhoomish Patel - 202201414**

Honor code :

- The work that we are presenting is our own work.
- We have not copied the work (the code, the results, etc.) that someone else has done.
- Concepts, understanding and insights we will be describing are our own.
- We make this pledge truthfully.
- We know that violation of this solemn pledge can carry grave consequences.

```

function ans = encoding(kc, generation_polynomials, inp)

    n = length(generation_polynomials);
    ans = [];
    regval = 0;

    for i = 1:length(inp)
        curbit = inp(i);
        regval = bitor(bitshift(regval, -1), bitshift(curbit, (kc - 1)));

        for j = 1:n
            cur_poly = generation_polynomials(j);
            output = 0;
            p=dec2bin(cur_poly,kc);
            p=fliplr(p)-'0';
            rv=dec2bin(regval,kc)-'0';
            output=0;

            for k=1:kc
                output=xor(output,(p(k) & rv(k)));
            end

            ans = [ans, output];
        end
    end
end

```

```

function ans = decoding_soft(kc, generation_polynomials, inp)

    ns = bitshift(1, (kc-1));
    n = length(generation_polynomials);
    mtr = ones(floor(length(inp)/n) + 1, ns) * 1e9;
    previous_states = cell(floor(length(inp)/n) + 1, 1);

    for i = 1:length(previous_states)
        previous_states{i} = cell(ns, 1);

        for j = 1:ns
            previous_states{i}{j} = {1e9, 1e9};
        end
    end

    idx = 0;
    for t = 1:(length(inp)/n)
        for st = 0:ns-1
            if (t == 1) && (st == 0)
                mtr(t, st+1) = 0;
            end
        end
    end
end

```

```

        for input_bits = 0:1
            curstate = st;
            next_state = bitor(bitshift(curstate, -1),(input_bits *
...
            bitshift(1, (kc-2))));
            euclidian_distance = 0;
            for i = 1:n
                output = 0;
                poly = generation_polynomials(i);
                regvalue = bitor(curstate, bitshift(input_bits,
(kc-1)));
                for k = 0:(kc-1)
                    output = bitxor(output, bitand(bitshift(poly,
-k), ...
1) & bitand(bitshift(regvalue, -(kc-k-1)), 1));
                end
                output=1-2*output;
                euclidian_distance=euclidian_distance+(abs(output-...
inp(idx+i))*abs(output-inp(idx+i)));
            end
            euclidian=sqrt(euclidian_distance);
            a = mtr(t+1, next_state+1);
            b = mtr(t, curstate+1);
            if a > b + euclidian_distance
                mtr(t+1, next_state+1) = b + euclidian_distance;
                previous_states{t+1}{next_state+1} =
{curstate,input_bits};
            end
        end
        end
        idx = idx + n;
    end
    ans = [];
    temp = previous_states{(length(inp)/n)+1}{1};
    ans = [temp{2} ans];
    cur = (length(inp)/n);

    while cur >1
        temp = previous_states{cur}{temp{1}+1};
        ans = [temp{2} ans];
        cur = cur - 1;
    end
end

function modulated_op = modulator(encoded_message,sigma)
    s = 1 - 2 * encoded_message; % BPSK modulation
    modulated_op= s + sigma * randn(1, length(encoded_message));

```

```

end

EbNodB = 0:0.5:10;
R1 = 1/2;
R2 = 1/3;
R3 = 1/3;

n1 =2;
n2 =3;
n3 =3;

k1 =1;
k2 =1;
k3 =1;

kc1 = 3;
kc2 = 4;
kc3 = 6;

% practical_error = zeros(1,length(EbNodB));
%theoratical_error = zeros(1,length(EbNodB));

soft_error1=zeros(1,length(EbNodB));
soft_error2=zeros(1,length(EbNodB));
soft_error3=zeros(1,length(EbNodB));

idx =1;
idx2=1;
N = 500;
for j=EbNodB
EbNo = 10^(j/10);

sigma1 = sqrt (1/(2*R1*EbNo));
sigma2 = sqrt (1/(2*R2*EbNo));
sigma3 = sqrt (1/(2*R3*EbNo));

BER_th = 0.5*erfc(sqrt(EbNo));

Nerr_soft1=0;
Nerr_soft2=0;
Nerr_soft3=0;

for i = 1 : N
msg = randi ([0 1],1,100); %generate random message

msg1=[msg zeros(1,kc1-1)];
msg2=[msg zeros(1,kc2-1)];
msg3=[msg zeros(1,kc3-1)];

```

```

encoded_array1=encoding(kc1,[5 7],msg1);
encoded_array2=encoding(kc2,[11 13 15],msg2);
encoded_array3=encoding(kc3,[39 43 61],msg3);

modulated_message1=modulator(encoded_array1,sigma1);
modulated_message2=modulator(encoded_array2,sigma2);
modulated_message3=modulator(encoded_array3,sigma3);

%decoded_message=decoding(kc,[5 7],demodualted_message);
soft_decoded_message1=decoding_soft(kc1,[5 7],modulated_message1);
soft_decoded_message2=decoding_soft(kc2,[11 13 15],modulated_message2);
soft_decoded_message3=decoding_soft(kc3,[39 43 61],modulated_message3);

Nerr_soft1=Nerr_soft1+sum(soft_decoded_message1~=msg1);
Nerr_soft2=Nerr_soft2+sum(soft_decoded_message2~=msg2);
Nerr_soft3=Nerr_soft3+sum(soft_decoded_message3~=msg3);
% Nerrs=Nerrs+sum(msg ~= decoded_message);
end
soft_error1(idx)=(Nerr_soft1)/(N*length(msg1));
soft_error2(idx)=(Nerr_soft2)/(N*length(msg2));
soft_error3(idx)=(Nerr_soft3)/(N*length(msg3));

%practical_error(idx) = (Nerrs/(N*length(msg)));
%theoratical_error(idx2) = theoratical_error(idx2)+BER_th;

idx = idx+1;
idx2 = idx2+1;
end

%semilogy(EbNodB,practical_error,'LineWidth',2.0);

%semilogy(EbNodB,theoratical_error,'LineWidth',2.0);

semilogy(EbNodB,soft_error1,'LineWidth',0.5);
hold on;
semilogy(EbNodB,soft_error2,'LineWidth',0.5);
semilogy(EbNodB,soft_error3,'LineWidth',0.5);

legend('SDD R=1/2 & Kc=3','SDD R=1/3 & Kc=4','SDD R=1/3 & Kc=6');
title('Soft Decision Decoding');
%xlim([0 1]);
xlabel('EbNo(dB)');
ylabel('BER');
hold off;

```

