

• Live

Data Fetching API Reference

Programmatic access to Doott's lead intelligence platform — search, filter, and export millions of verified company and people records.

⚡ REST / JSON 🗄️ Cloud SQL (PostgreSQL) 🚀 Vector Search Enabled 🔒 JWT Bearer Auth

🚀 Getting Started

Everything you need to make your first API call in under 2 minutes.

PRODUCTION `https://doott.jaqyi.com/api`

LOCAL DEV `http://localhost:3000/api`

QUICK START · cURL

Copy

```
# 1. Login to get Bearer token
curl -X POST https://doott.jaqyi.com/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{"email":"you@example.com","password":"yourpassword"}'

# 2. Query companies with the returned token
curl -G https://doott.jaqyi.com/api/final-companies \
  -H "Authorization: Bearer <TOKEN>" \
  --data-urlencode "f_city=Mumbai" \
  --data-urlencode "f_has_email=true" \
  --data-urlencode "limit=25"
```



Authentication

All data endpoints require a Bearer JWT token in the Authorization header.

Bearer Token (JWT)

Obtain a token via `POST /api/auth/login`. Attach it to every data request:

HEADER

Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...



Tokens are org-scoped. Never expose them in client-side code or public repos.



Filter System

All data APIs share a unified filter system. Use `f_` prefix + column name + optional operator suffix as query params.

Operator Suffixes

(none)	Contains — case-insensitive. Multi-word matches all tokens. e.g. <code>f_industry=Food</code>
<code>_eq</code>	Exact match e.g. <code>f_state_eq=Maharashtra</code>
<code>_sw</code>	Starts with e.g. <code>f_city_sw=Mum</code>
<code>_ew</code>	Ends with e.g. <code>f_website_ew=.com</code>
<code>_nonempty</code>	Field is not null/empty e.g. <code>f_emails_nonempty=true</code>
<code>_empty</code>	Field is null/empty e.g. <code>f_phone_empty=true</code>



Filter keys are validated against live DB schema. Unknown columns are silently ignored — SQL injection is not possible.



Companies Database

Query **final.companies** — millions of verified business records with contact details, location, and industry.

GET**/api/final-companies**

Paginated company list with filters ▶

GET**/api/final-companies/stats**

Total record count (Redis cached 5 min) ▶

GET**/api/final-companies/categories**

Top 100 industries with counts (cached 24h) ▶

GET**/api/final-companies/cities**

Top 500 cities with business counts (cached 6h) ▶

GET**/api/final-companies/columns**

List all queryable columns ▶

GET**/api/final-companies/health**

Database connectivity check ▶



People Database

Query **final.people** — 43M+ individual contacts with job titles, emails, phones, and location.

GET**/api/final-people**

Paginated people list with filters ▶

GET**/api/final-people/stats**

Total people count ▶

GET**/api/final-people/categories**

Top 100 job titles with counts (cached 24h) ▶

GET

[/api/final-people/cities](#)

Top 500 cities by people count (cached 6h) ▶

People — Email Filtered

Identical to [/api/final-people](#) but pre-filtered — every record is guaranteed to have an email. Same params, same pagination.



Every record returned has at least one non-empty verified email column.

GET

[/api/final-people-email](#)

People with verified email — paginated ▶

People — Phone Filtered

Identical to [/api/final-people](#) but pre-filtered — every record is guaranteed to have a phone number.



Every record returned has at least one non-empty phone number column.

GET

[/api/final-people-number](#)

People with phone number — paginated ▶

Email Verification

Real-time email validation with 90-day Redis+Postgres caching. Supports single and bulk CSV verification.

POST

[/api/verify-email](#)

Verify a single email address ▶

POST

[/api/verify-email/batch](#)

Bulk verify — CSV upload or JSON list (async job) ▶

GET

`/api/verify-email/batch/:jobId`

Poll batch job status & results ▶



Authentication API

Register, login, and manage user sessions.

POST

`/api/auth/register`

Create new account ▶

POST

`/api/auth/login`

Login and receive Bearer token ▶



HTTP Status Codes

Standard HTTP codes used across all endpoints.

CODE	MEANING	WHEN TO EXPECT
200 OK	Success	Request completed, data returned
201 Created	Created	New resource created (e.g. user account)
202 Accepted	Async Started	Job accepted (e.g. batch email verification)
400 Bad Request	Invalid Input	Missing required fields or validation error
401 Unauthorized	Auth Required	Missing or invalid Bearer token
403 Forbidden	Access Denied	Token valid but lacks permissions
429 Too Many Requests	Rate Limited	Request quota exceeded — implement back-off
500 Server Error	Internal Error	Unexpected server-side failure
503 Unavailable	DB Unreachable	Database connection failed

Rate Limits

Per-IP rate limits protect the platform and ensure fair usage for all users.

ENDPOINT GROUP	LIMIT	WINDOW
<code>/api/final-companies, /api/final-people*</code>	300 requests	per 15 minutes per IP
<code>/api/verify-email (single)</code>	100 requests	per 15 minutes per IP
<code>/api/verify-email/batch</code>	10 requests	per 15 minutes per IP
<code>/api/auth/register, /api/auth/login</code>	20 requests	per 15 minutes per IP
All other <code>/api/*</code> endpoints	500 requests	per 15 minutes per IP



When rate limited you'll receive 429 Too Many Requests. Use exponential back-off before retrying.