

# POINTERS AND DYNAMIC ALLOCATION IN C

Will Landau

# OUTLINE

- Computer memory
- Pointers
- Arrays
- Bus errors and segmentation faults
- Dynamic allocation

# COMPUTER MEMORY

Fundamentally, all data is encoded in byte code, a string of ones and zeroes:

0100101100101100101 ...

- **Bit:** A 1 or a 0 in byte code
- **Byte:** A string of 8 bits: for example, 00110100.
- **Word:** A natural unit of data, which depends on the processor. On “32-bit architectures”, a word is a string of 32 bits (4 bytes).

Computer memory is a linear array of bytes. Each byte has a word-sized index called an **address**, or **pointer**.

Address	Stored Value	Variable Name
24399440	3	a
24399441		
24399442		
24399443		
24399444	6.43451	b
24399445		
24399446		
24399447		
⋮	⋮	

Note: each stored value the table take up 4 addresses (bytes) of space. Hence, we only use the first address to refer to each.

I condense the table:

Address	Stored Value	Variable Name
24399440	3	a
24399444	6.43451	b
⋮	⋮	

We say that:

- 24399440 is the address of **a**.
- 3 is the stored value at the address, 24399440.
- **a** is the variable pointed to by 24399440.
- 3 is the value pointed to by 24399440.

# DECLARING POINTER VARIABLES

- Write `int *pa;` to declare an int pointer variable: a variable whose value is the address of an integer.
- Write `float *pa;` to declare a float pointer variable: a variable whose value is the address of a float.
- Write `double *pa;` to declare a double pointer variable: a variable whose value is the address of a double.

The type of a pointer variable depends on the data type pointed to because:

- Different data types have different sizes in memory
- The computer needs to know how to interpret the bytes in memory: the same string of bytes could encode either a float or an integer.

ex0.c:

```
#include <stdio.h>

int main() {
    int a = 17;

    printf("a = %d\n", a); // interpret as an int
    printf("a = %f\n", a); // interpret as a float
}
```

output:

```
~/Desktop> gcc ex0.c -o ex0
~/Desktop> ./ex0
a = 17
a = 0.000000
~/Desktop>
```

# REFERENCING AND DEREFERENCING

Let **a** be an int and **pa** be a pointer to an int. Then:

- **&a** returns the address of **a**. Using the ampersand operator to return the address of a variable is called **referencing**.
- **\*pa** returns the value pointed to by **pa**. Using the asterisk operator in this way is called **dereferencing**.

Now, for some example code...



ex1.c:

```
#include <stdio.h>

int main(){
    int a = 0;

    printf("a = %d\n", a);
    printf("&a = %d\n", &a);
}
```

output:

```
~/Desktop> gcc ex1.c -o ex1
~/Desktop> ./ex1
a = 0
&a = 1355533180
```

Address	Stored Value	Variable Name
1355533180	3	a

ex2.c:

```
#include <stdio.h>

int main() {
    int a = 0;
    int *pa;

    pa = &a;
    *pa = *pa + 1;

    printf("a = %d\n", a);
    printf("&a = %d\n", &a);
    printf("*pa = %d\n", *pa);
    printf("pa = %d\n", pa);
    printf("&pa = %d\n", &pa);
}
```

output:

```
~/Desktop> gcc ex2.c -o ex2
~/Desktop> ./ex2
a = 1
&a = 1420507900
*pa = 1
pa = 1420507900
&pa = 1420507888
~/Desktop>
```

Address	Stored Value	Variable Name
1420507900	1	a
1420507888	1420507900	pa

ex3.c:

```
#include <stdio.h>

int main() {
    int a = 0, b = 0;
    int *pa;

    pa = &b;
    *pa = a;
    *pa = *pa + 1;

    printf("a = %d\n", a);
    printf("&a = %d\n", &a);
    printf("b = %d\n", b);
    printf("&b = %d\n", &b);
    printf("*pa = %d\n", *pa);
    printf("pa = %d\n", pa);
    printf("&pa = %d\n", &pa);
}
```

output:

```
~/Desktop> gcc ex3.c -o ex3
~/Desktop> ./ex3
a = 0
&a = 1537735420
b = 1
&b = 1537735416
*pa = 1
pa = 1537735416
&pa = 1537735408
~/Desktop>
```

Address	Stored Value	Variable Name
1537735420	0	a
1537735416	1	b
1537735408	1537735416	pa

# PASSING BY ARGUMENTS BY VALUE AND BY REFERENCE

ex4.c:

```
#include <stdio.h>

void fun(int a){
    a = a + 1;
}

int main(){
    int a = 0;

    fun(a);

    printf("a = %d\n", a);
}
```

output:

```
~/Desktop> gcc ex4.c -o ex4
~/Desktop> ./ex4
a = 0
~/Desktop>
```

- **a** was passed to **fun()** by *value*.
- **fun()** received a local copy of **a** and then lost it when the function terminated.
- The copy of **a** in **int main()** remained unchanged.

# PASSING ARGUMENTS BY REFERENCE

ex5.c:

```
#include <stdio.h>

void fun(int *a){
    *a = *a + 1;
}

int main(){
    int a = 0;

    fun(&a);

    printf("a = %d\n", a);
}
```



output:

```
~/Desktop> gcc ex5.c -o ex5
~/Desktop> ./ex5
a = 1
~/Desktop>
```

- **a** was passed to **fun()** by *reference*.
- **fun()** received a local copy of a *pointer* to the copy of **a** in **int main()**.
- When **fun()** terminated, only the function's copy of that pointer was lost.

ex6.c:

```
#include <stdio.h>

void fun(int *a){
    *a = *a + 1;
}

int main(){
    int a = 0, *pa;

    *pa = a;
    fun(pa);

    printf("a = %d\n", a);
    printf("*pa = %d\n", *pa);
}
```

output:

```
~/Desktop> gcc ex6.c -o ex6
~/Desktop> ./ex6
a = 0
*pa = 1
~/Desktop>
```

**pa** did not point to **a**, so **a** was not passed at all.

ex7.c:

```
#include <stdio.h>

void fun(int *a){
    *a = *a + 1;
}

int main(){
    int a = 0, *pa;

    pa = &a;
    fun(pa);

    printf("a = %d\n", a);
    printf("*pa = %d\n", *pa);
}
```

output:

```
~/Desktop> gcc ex7.c -o ex7
~/Desktop> ./ex7
a = 1
*pa = 1
~/Desktop>
```

Since **pa** points to **a** and **pa** was passed by value, **a** was passed by reference.

# CAUTION

Assign values to pointers before dereferencing them.

caution1.c:

```
int main() {  
    int *a;  
    *a = 0;  
}
```

output:

```
~/Desktop> gcc caution1.c -o caution1  
~/Desktop> ./caution1  
Bus error: 10  
~/Desktop>
```

The value of **a** is some garbage number that isn't a real address!  
Nobody lives there!

# ARRAYS

ar1.c:

```
#include <stdio.h>

void modify(int *a){
    int i;
    for(i = 0; i<6; ++i){
        a[i] = i;
    }
}

int main(){
    int i;
    int a[] = {1,23,17,4,-5,100};

    for(i = 0; i<6; ++i){
        printf("a[%d] = %d\n", i, a[i]);
    }
    printf("\nModifying...\n\n");

    modify(a);
}
```

```
    for(i = 0; i<6; ++i){  
        printf("a[%d] = %d\n", i, a[i]);  
    }  
}
```

output:

```
~/Desktop> gcc ar1.c -o ar1  
~/Desktop> ./ar1  
a[0] = 1  
a[1] = 23  
a[2] = 17  
a[3] = 4  
a[4] = -5  
a[5] = 100
```

Modifying ...

```
a[0] = 0  
a[1] = 1  
a[2] = 2  
a[3] = 3  
a[4] = 4  
a[5] = 5
```



ar2.c:

```
#include <stdio.h>

void modify(int *a){
    int i;
    for(i = 0; i<6; ++i){
        a[i] = i;
    }
}

int main(){
    int i;
    int a[6];

    for(i = 0; i<6; ++i){
        a[i] = i*i + 1;
        printf("a[%d] = %d\n", i, a[i]);
    }
    printf("\nModifying...\n\n");

    modify(a);

    for(i = 0; i<6; ++i){
```

```
    printf("a[%d] = %d\n", i, a[i]);  
    }  
}
```

output:

```
~/Desktop> gcc ar2.c -o ar2  
~/Desktop> ./ar2  
a[0] = 1  
a[1] = 2  
a[2] = 5  
a[3] = 10  
a[4] = 17  
a[5] = 26
```

Modifying ...

```
a[0] = 0  
a[1] = 1  
a[2] = 2  
a[3] = 3  
a[4] = 4  
a[5] = 5  
~/Desktop>
```

ar3.c:

```
#include <stdio.h>

void modify(int *a){
    int i;
    for(i = 0; i<6; ++i){
        *(a + i) = i;
    }
}

int main(){
    int i;
    int *a;

    for(i = 0; i<6; ++i){
        *(a + i) = i*i + 1;
        printf("*(a + %d) = %d\n", i, *(a + i));
    }
    printf("\nModifying...\n\n");

    modify(a);

    for(i = 0; i<6; ++i){
```

```
    printf("*(a + %d) = %d\n", i, *(a + i));  
    }  
}
```

output:

```
~/Desktop> gcc ar3.c -o ar3  
~/Desktop> ./ar3  
*(a + 0) = 1  
*(a + 1) = 2  
*(a + 2) = 5  
*(a + 3) = 10  
*(a + 4) = 17  
*(a + 5) = 26
```

Modifying ...

```
*(a + 0) = 0  
*(a + 1) = 1  
*(a + 2) = 2  
*(a + 3) = 3  
*(a + 4) = 4  
*(a + 5) = 5  
~/Desktop>
```

ar4.c:

```
#include <stdio.h>

void modify(int *a){
    int i;
    for(i = 0; i<6; ++i){
        a[i] = i;
    }
}

int main(){
    int i;
    int *a;

    for(i = 0; i<6; ++i){
        a[i] = i*i + 1;
        printf("a[%d] = %d\n", i, a[i]);
    }
    printf("\nModifying...\n\n");

    modify(a);

    for(i = 0; i<6; ++i){
```

```
    printf("a[%d] = %d\n", i, a[i]);  
}  
}
```

output:

```
~/Desktop> gcc ar4.c -o ar4  
~/Desktop> ./ar4  
a[0] = 1  
a[1] = 2  
a[2] = 5  
a[3] = 10  
a[4] = 17  
a[5] = 26
```

Modifying ...

```
a[0] = 0  
a[1] = 1  
a[2] = 2  
a[3] = 3  
a[4] = 4  
a[5] = 5  
~/Desktop>
```

# CAUTION

Every (statically allocated) array has a set length. Do not reference beyond this length.

caution2.c:

```
#include <stdio.h>

int main() {
    int i = 0, *a;
    *a = i;
    printf(" *a = %d\n", *a);

    *(a + 10000) = 1;
}
```

output:

```
~/Desktop> gcc caution2.c -o caution2
~/Desktop> ./caution2
*a = 0
Segmentation fault: 11
~/Desktop>
```

It is illegal to reference the object at memory address, (**a + 10000**).



# DYNAMIC ALLOCATION

**Static memory allocation:** Acquiring a fixed, unchangeable piece of memory for a fixed-size data object at compile-time.

**Dynamic memory allocation:** Acquiring a variable-length piece of memory for an variable-size object during runtime.

For dynamic allocation, use the function `malloc()`, which is in `stdlib.h`.

dy1.c:

```
#include <stdio.h>
#include <stdlib.h>

void fill(int *a){
    int i;
    for(i = 0; i < 10; ++i){
        a[i] = 10 + i*i;
    }
}

int main(){
    int i, *a;

    a = (int *) malloc(10 * sizeof(int));
    fill(a);

    for(i = 0; i < 10; ++i){
        printf("a[%d] = %d\n", i, a[i]);
    }

    free(a);
}
```

output:

```
~/Desktop> gcc dy1.c -o dy1
~/Desktop> ./dy1
a[0] = 10
a[1] = 11
a[2] = 14
a[3] = 19
a[4] = 26
a[5] = 35
a[6] = 46
a[7] = 59
a[8] = 74
a[9] = 91
~/Desktop>
```

dy2.c:

```
#include <stdio.h>
#include <stdlib.h>

#define M 10
#define N 15

void fill(float *x, int size){
    int i;
    for(i = 0; i < size; ++i){
        x[i] = 10.25 + i*i;
    }
}

int main(){
    int i;
    float *a, *b;

    a = (float *) malloc(M * sizeof(float));
    b = (float *) malloc(N * sizeof(float));

    fill(a, M);
    fill(b, N);
```

```
for (i = 0; i < M; ++i){  
    printf("a[%d] = %f\n", i, a[i]);  
}  
printf("\n");  
  
for (i = 0; i < N; ++i){  
    printf("b[%d] = %f\n", i, b[i]);  
}  
  
free(a);  
free(b);  
}
```

output:

```
~/Desktop> gcc dy2.c -o dy2
~/Desktop> ./dy2
a[0] = 10.250000
a[1] = 11.250000
a[2] = 14.250000
a[3] = 19.250000
a[4] = 26.250000
a[5] = 35.250000
a[6] = 46.250000
a[7] = 59.250000
a[8] = 74.250000
a[9] = 91.250000

b[0] = 10.250000
b[1] = 11.250000
b[2] = 14.250000
b[3] = 19.250000
b[4] = 26.250000
b[5] = 35.250000
b[6] = 46.250000
b[7] = 59.250000
b[8] = 74.250000
```

```
b[9] = 91.250000  
b[10] = 110.250000  
b[11] = 131.250000  
b[12] = 154.250000  
b[13] = 179.250000  
b[14] = 206.250000  
~/Desktop>
```

# OUTLINE

- Pointers
- Arrays
- Bus errors and segmentation faults
- Dynamic allocation



# LECTURE SERIES MATERIALS

These lecture slides, a tentative syllabus for the whole lecture series, and code are available at:

<https://github.com/wlandau/gpu>.

After logging into your home directory on impact1, type:

```
git clone https://github.com/wlandau/gpu
```

into the command line to download all the course materials.

# REFERENCES

Ted Jensen. "A Tutorial on Pointers and Arrays in C".  
<http://pw1.netcom.com/~tjensen/ptr/pointers.htm>

Brian W. Kernighan and Dennis M. Ritchie. "The ANSI C Programming Language". 2nd Ed.

Walter Savitch. "Absolute C++". 3rd Ed.